1 **An Interactive Tool to Forecast US Hospital Needs in the Coronavirus 2019 Pandemic**
2

3 Kenneth J. Locey[1*], Thomas A. Webb[1**], Jawad Khan[2***], Anuja K. Antony[3†], Bala Hota[1,3,4††]

Affiliations

[1] Center for Quality, Safety and Value Analytics, Rush University Medical Center, Chicago,
Illinois, 60612, USA.

[2] Knowledge Management Services, Rush University Medical Center, Chicago, Illinois, 60612,
USA.

[3] Department of Surgery, Division of Plastic and Reconstructive Surgery, Rush University
Medical Center, Chicago, Illinois, 60612, USA.

[4] Department of Internal Medicine, Division of Infectious Diseases, Rush Medical College,
Chicago, Illinois, 60612, USA.

[*] Corresponding author. email: Kenneth_J_Locey@rush.edu

Coauthor Contact emails
[**] Thomas_A_Webb@rush.edu
[***] Jawad_Khan@rush.edu
[†] Anuja_K_Antony@rush.edu
[††] Bala_Hota@rush.edu

ABSTRACT

Hospital enterprises have been continually faced with anticipating the spread of COVID-

19 and the effects it is having on visits, admissions, bed needs, and crucial supplies. While many

studies have focused on understanding the basic epidemiology of the disease, few open source

tools have been made available to aid hospitals in their planning. We developed a web-based

application (available at: http://covid19forecast.rush.edu/) for US states and territories that

allows users to choose from a suite of models already employed in characterizing the spread of

COVID-19. Users can obtain forecasts for hospital visits and admissions as well as anticipated

needs for ICU and non-ICU beds, ventilators, and personal protective equipment supplies. Users

can also customize a large set of inputs, view the variability in forecasts over time, and download

forecast data. We describe our web application and its models in detail and provide

recommendations and caveats for its use. Our application is primarily designed for hospital

leaders, healthcare workers, and government official who may lack specialized knowledge in

epidemiology and modeling. However, specialists can also use our open source code as a

platform for modification and deeper study. As the dynamics of COVID-19 change, our

application will also change to meet emerging needs of the healthcare community.

INTRODUCTION

Coronavirus disease 2019 (COVID-19) was declared a global pandemic by the World Health Organization on March 11th 2020. By then, confirmed COVID-19 cases were reported among 109 countries and exceeded 128,000 worldwide (data source: Johns Hopkins University Center for Systems Science and Engineering). That number increased more than 10-fold in less than one month. As COVID-19 spreads within and among nations, healthcare enterprises grapple with the challenges of preparing for the growing number of COVID-19 patients and with appropriating the resources needed to treat patients while protecting healthcare professionals. In the United States (US), policy makers and hospital leaders prognosticate on how to best allocate resources in the face of an anticipated surge in demand that may last for several months to come (Bukhari and Jameel, 2020). However, even as COVID-19 threatens to overwhelm healthcare systems, the predictive analytics tools that would otherwise allow hospitals to make informed decisions are lagging behind the increasing number of studies aimed at characterizing the basic epidemiology of COVID-19.

To meet the pressing needs of hospital enterprises we developed an interactive, open-source web-based application to provide state- and hospital-specific forecasts of COVID-19 patients and related supplies. Our application is available on the http://covid19forecast.rush.edu/ website and allows users to employ a suite of models already used in the prediction of COVID-19 cases. It then couples these models to granular customizable inputs to produce hospital-level forecasts for COVID-19 visits and admits, ICU and non-ICU beds, ventilators, and various personal protective equipment (PPE) supply needs. Our efforts are aimed at addressing immediate and anticipated healthcare demands, and to allow informed decision-making by government officials and healthcare professionals who may lack specialized expertise in epidemiology, modeling, and data science. By making our aggregated data and source code freely available, and by offering additional source code outside the application itself, epidemiologists, modelers, and data scientists may also find our application useful as is, or as a modifiable resource for deeper analysis.

In this paper, we describe our application in detail, focusing on the data and models it uses, the inputs it allows users to enter, and the graphs, tables, and downloadable data it provides. We also provide guidance on the use of this application, the interpretation of its

outputs, and the caveats of our approach. Finally, we discuss the value of our application to
meeting the needs of the healthcare community, its potential as a tool for generating novel
insights, and modifications to come. In addition to our aim of empowering administrators,
physicians, and governmental agencies to make informed decisions, we sought to enable other
predictive healthcare analytics teams and researchers. Specifically, the modification and
deployment of our application's source code requires a minimal set of widely popular open
source software (e.g., python language, Jupyter notebook) and little-to-no experience in web
development.
99
100
101 **FUNCTIONALITY AND USE**
102
Overview – Our open-source application allows users 1) to aggregate data from a popular open-
source repository of COVID-19 data, 2) to track and forecast the progression of COVID-19 cases
across US states using a suite of well-known models, 3) customize a large set of input parameters
to provide state- and hospital-specific forecasts for numbers of hospital visits, admitted patients,
ICU needs, and personal protective equipment (PPE) supply needs. The application also allows
users to adjust the length of forecasts, to adjust expected time lags in patient visits, to adjust the
average length of stay (LOS) for ICU and non-ICU patients, to examine forecasts from previous
days, and to download forecast data for deeper analysis.
111
Data – Our application accesses COVID-19 data from the Johns Hopkins University Center for
Systems Science and Engineering (JHU CSSE) (2). Specifically, our application downloads,
aggregates, and stores daily reports from the JHU CSSE public GitHub repository
(https://github.com/CSSEGISandData/COVID-19). These daily reports contain cumulative
numbers of confirmed cases, and cumulative numbers of reported deaths and recoveries for
counties, states, provinces, and nations reported since January 22nd, 2020. For select models, our
application uses population sizes for US states and territories based on data from the US Census
Bureau (2010 – 2019). Our application also uses dates of COVID-19 arrival in US states and
territories based on data available from state and territory governmental agencies (e.g.,
Departments of Health).

Modeling COVID-19 cases – Our application begins by modeling the cumulative COVID-19

cases for a selected state, and allows users to choose from four simplistic models of growth that

have been used in characterizing the spread of COVID-19 as well as one popular

epidemiological model that has been frequently used in the study of COVID-19 (Fig 1).

Altogether, the following suite of models allows users the ability to compare and contrast

forecasts resulting from different forms of growth and varying complexity of disease dynamics

and social response (e.g., testing lags, social distancing).

Exponential growth – Initial stages of growth often appear limited only by the inherent growth

rate (r) of the population or disease. In this way, exponential growth proceeds multiplicatively

according to a simple functional form, $N_t = N_0 e^{rt}$, where N_0 is the initial infected population size,

t is the amount of passed, and N_t is the infected population size at t. The exponential model has

been widely used to characterize the spread of COVID-19 the during initial weeks of infection

(e.g., Graselli, Presenti, and Cecconi 2020, Lui *et al*. 2020, Remuzzi and Remuzzi, 2020; Fig 2).

Because it assumes that r is constant, the exponential model has a simple log-linear

transformation, $\log(N_t) = \log(N_0) + t \cdot r$, that allows log-transformed numbers of cases to be

regressed on t (Sit, Poulin-Costello, and Bergerud 1994). Our application uses this exponential

regression to obtain predictions for the expected cumulative number of confirmed COVID-19

cases (N). This model has explained upwards of 99% of variation in the initial days or weeks of

COVID-19 spread within states; however, it quickly begins to fail because it only allows for

continued rapid growth (Fig 2).

Quadratic growth – Initial stages of growth may be more rapid than that expected from the

exponential model while the latter monotonic increase in N can proceed less rapidly than

predicted by the exponential. In these cases, growth may be quadratic, i.e., characterized by a

constant change in growth rate. Early COVID-19 studies have implicated quadratic growth in

spread of COVID-19 (e.g., Brandenburg 2020; Fang, Ne, and Penny 2020) and the quadratic

model, to date, has continued to perform well (Fig 2). The quadratic function, $f(x) = x^2 + x + c$, is

a 2nd order polynomial that can be applied to population growth as $N_t = \beta_1 t^2 + \beta_2 t + N_0$. Our

application uses numerical optimization of the fitted parameters, β_1 and β_2, to find the best fit

quadratic function for a given time series and hence, to predict values for (*N*). This model has,

thus far, improved as COVID-19 spreads and has explained upwards of 99% of variation in

COVID-19 cases among states (Fig 2). However, like the exponential model, the quadratic

model only allows for continued growth, i.e., no saturation. Consequently, the quadratic model

must eventually fail as COVID-19 cases saturate.

Logistic growth – Exponential growth within a population cannot continue *ad infinitum*. Instead,

growth must slow as an upper limit is approached or as natural limitations to disease spread (e.g.,

immunity, contact among hosts) are encountered. The logistic model captures this slowing and

eventual saturation, resulting in a sigmoidal or s-shaped growth curve (Maynard-Smith 1978,

Bacaër 2011, Fig 1). In addition to exponential and quadratic growth, early COVID-19 studies

have implicated logistic growth in the spread of the disease (Roosa *et al*. 2020, Wu *et al*. 2020).

Like the quadratic model, the logistic model has also continued to perform well as states have

progressed in COVID-19 infection (Fig 2). The logistic model takes a relatively simple

functional form, $N_t = \frac{\alpha}{1+e^{-rt}}$, where α is the upper limit of N and r is the intrinsic rate of

increase. Our application uses numerical optimization of α and r to find the best fit logistic

function and hence, predicted values for *N*. This model has, to date, improved as COVID-19

spreads and has explained upwards of 99% of variation in COVID-19 cases among states (Fig 2).

Gaussian growth – The Gaussian (i.e., normal) distribution can provide a relatively simple and

close approximation to complex epidemiological models (Buckingham-Jeffery *et al*. 2018):

$$f(x) = \frac{1}{\sigma\sqrt{2\pi}}e^{-\frac{1}{2}\left(\frac{x-\mu}{\sigma}\right)^2}$$

This symmetrical curve has two parameters, mean = μ, standard deviation = σ, and belongs to the

family of exponential distributions (Fig 1). When used to model spread of disease, Gaussian

curves are symmetrical around a climax day with the change in the rate of growth determining

the standard deviation about the curve. Gaussian models have previously been successful in

approximating the spread of COVID-19 in Germany (Schlickeiser and Schlickeiser 2020). Our

application uses numerical optimization of μ and σ and the cumulative distribution function of

the Gaussian model to find the best fit cumulative Gaussian function and hence, predicted values

for N. This model has, thus far, explained >99% of variation in COVID-19 cases among states

and continues to improve as COVID-19 spreads (Fig 2).

SEIR-SD – To date, COVID-19 studies have used a variety of epidemiological models to

characterize the spread of the disease within populations. The modeling in several of these

studies has been based on refinements to the classic SEIR model of Hethcote and Tudor (1980)

(see Boldog *et al*. 2020, Peng *et al*. 2020, Lui *et al*. 2020, Wang *et al*. 2020). In this model, a

contagious disease drives changes in the fraction of susceptible persons (S), the fraction of

persons exposed but not yet exhibiting infection (E), the fraction of infectious persons (I), and

the fraction of persons recovered (R), where $S + E + I + R = 1$. These SEIR subpopulations are

modeled as compartments in the following set of ordinary differential equations:

$$\frac{dS}{dt} = \beta SI \, , \qquad \frac{dE}{dt} = \beta SI - \alpha E$$

$$\frac{dI}{dt} = \alpha E - \gamma I \, , \qquad \frac{dR}{dt} = \gamma I$$

In these equations, α is the inverse of the incubation period, and γ is the inverse of the average

infectious period, and β is the average number of contacts of infected persons with susceptible

persons per unit time. Our application imputes the initial value of β from a well-known

simplifying relationship between γ and the basic reproductive number (R_0), i.e., $\beta = \gamma R_0$

(Ridenhour *et al*. 2018, Rocklöv *et al*. 2020, Rãdulescu and Cavanagh 2020, Lin et al. 2020).

We allowed β to decrease in proportion to I. We assumed that people will, on average,

reduce their contact with others when the populace is aware that an increasing percent of their

population is infected. This approach allows an inherent degree of social distancing to emerge as

a frequency-dependent phenomenon. We also simulated an explicit effect of social distancing (λ)

to capture the overall strength of response to public health policies. These effects were included

as time-iterative modifications to β:

$$\beta_{t+1} = \frac{\beta_t}{\lambda I + 1}$$

213   This function allows β to remain unchanged when either I or λ equal 0. When λ equals 1, the

214   daily change in β is governed by the implicit frequency-dependent effect of I. Importantly,

215   simple algebraic rearrangement shows that the product of social distancing (λ) and the fraction

216   infected (I) determines the percent daily change in contact rate (β):

218
$$\lambda I + 1 = \frac{\beta_t}{\beta_{t+1}}$$

220
$$\lambda \cdot 100 \cdot I = 100 \cdot \frac{\beta_t - \beta_{t+1}}{\beta_{t+1}}$$

222   As a result, λ determines the daily proportional change in the contact rate per infected fraction of

223   the total population:

224
$$\lambda = \frac{\beta_t - \beta_{t+1}}{I\beta_{t+1}}$$

We also modified the classic SEIR model to account for initial time lags in COVID-19

testing. Specifically, and particularly in the US, widespread testing for COVID-19 may have

artificially dampened the apparent number of positive cases within the first month of the first

reported infection. We accounted for this effect by modifying the apparent size of I while

allowing the actual size of I to grow according to the SEIR-SD dynamic. This time-iterative

modification took the following logistic functional form:

233
$$I_t \frac{1}{1+e^{-\tau t + \varepsilon}},$$

where τ and ε are fitted parameters. This equation models testing as low-to-nonexistent during

the initial weeks of outbreak, and then accelerates afterwards.

To date, the SEIR-SD model has generally performed as well as or better than the

exponential, quadratic, logistic, and gaussian models (Fig 2). Our application performs a pseudo-

optimization on the SEIR-SD model parameters and a likely date of initial infection, as opposed

to using the first reported occurrence. Our implementation of the SEIR-SD model is based on an

unbiased search of multivariate parameter space within ranges of parameter values derived from

population sizes for US states and territories and the increasing corpus of COVID-19 literature

(Table 1). Our application performs 50,000 iterations and chooses the set of parameters that

maximize the explained variation in observed data. This implementation avoids the

computational challenges of applying numerical optimizers to complex simulation models and

avoids the problems that these optimizers can have in becoming trapped in local minima.

Forecasting COVID-19 cases – Our application allows users to select one of the above-

mentioned models and a location from a list of US states and territories (Fig 3). It then plots the

reported number of cumulative COVID-19 cases along with model predictions (up to present

day) and forecasts (up to 60 days ahead) (Fig 3). Users can also view how the predictions and

forecasts have changed over the last 10 days (Fig 3).

Forecasting hospital visits and admits via time lags – Our application allows users to enter the

expected percent of state-wide COVID-19 cases that visit their hospital as well as the expected

percent of those admitted. Going further, we accounted for the tendency of infected persons to

not seek immediate medical attention. We modeled these time lags as Poisson distributed random

variables, whereby portions of newly infected patients may wait 1, 2, 3, …, days to visit the

hospital. The Poisson distribution has ideal properties for modeling this scenario. Specifically, it

is a discrete probability distribution (*x*-values correspond to days) with a simplistic formulation

(e.g., the mean equals the variance), where the only parameter needed to obtain the probability

mass function (i.e., mean), directly corresponds to the expected average time lag. Users can view

the change in the forecasted patient census by adjusting the expected time lag (Fig 4).

Forecasting hospital bed and ICU needs via daily carry-over – Our application allows users to

forecast the number of hospital beds, ICU beds, and ventilators needed. The user begins by

entering expected values for the percent of COVID-19 patients admitted to critical care, the

expected average length of stay (LOS) for ICU and non-ICU patients, as well as the expected

percent of ICU patients on ventilators. The application then uses these inputs to calculate the

fraction of newly admitted ICU, non-ICU, and ICU-ventilator patients expected each day.

Because bed needs must also reflect the numbers of beds needed for new admissions, those

opened from discharges, and those currently occupied, our application models the daily carry-

over of the patient census using expected LOS and the cumulative distribution function (cdf) of

the binomial distribution.

The binomial distribution is a discrete probability distribution that models binary

outcomes (e.g., patients either leave the hospital or stay for an additional day) and requires only

two parameters (p, n). We set the value of p to 0.5 and set the value of n to be twice the average

LOS. Doing so produces a symmetrical probability mass function (pmf), with a mean equal to

the average LOS. This pmf is then converted to a cdf, which produces a first approximation for

the fraction of 1-day, 2-day, …, etc., patients that are expected to be discharged on the present

day. The fraction of patients not expected to be discharged are then carried over to the following

day, e.g., a 1st-day patient becomes a 2nd-day patient and thereby has a different probability of

leaving the hospital on the current day. This process is then iterated from the date of the first

COVID-19 admit to the latest day in the user-requested forecast window (Fig 5).

Forecasting supply needs – Our application allows users to forecast personal protective

equipment (PPE) needs in accordance with the forecasted census of COVID-19 ICU, non-ICU,

and ICU on ventilator patients. Users can enter expected per patient per day values for surgical

gloves, nitrile exam gloves, vinyl exam gloves, anti-fog procedural face masks, fluid resistant

procedural face masks, extra-large yellow isolation gowns, anti-fog (with film) surgical face

masks, anti-fog full face shields, and particulate filter respirators. These values entered are then

multiplied by the respective patient type across the forecasted patient census to produce

graphical and tabulated results (Fig 6).

Provisioning of forecasted data – Our application allows users to download forecast data in .csv

format from each displayed table. This includes a table of forecasted cases, visits, and admits, a

table of ICU and non-ICU bed needs, and a table of PPE supply needs. These downloadable files

correspond to the model chosen by the user. Importantly, for layout purposes, the application

does not display rows of data beyond a 14-day forecast. Instead, the user can view data from

longer forecasts via the downloadable .csv files.

Provisioning of source code – Source code for our application was built using the Python

language (v3.7.4), Jupyter notebook, and the python-based Voila software which converts

Jupyter notebooks to dashboard-like applications. All code and associated data are available

from the public GitHub SupplyDemand repository, found on the Rush Quality Safety and Value

analytics GitHub organization (https://github.com/Rush-Quality-Analytics/SupplyDemand). The

repository provides an informative README.md file and the source code includes extensive

commenting to assist users in their use and potential modification.

DISCUSSION

Meeting immediate needs – Hospitals and healthcare enterprises are endeavoring to make

appropriate preparations and acquire adequate supplies to meet the challenges of the COVID-19

pandemic. While many studies have aimed to characterize the basic epidemiology of the disease,

and many online tools have been developed to visualize its spread, few tools have been

developed that empower hospitals to make informed decisions about expected visits and admits,

ICU beds, ventilator, and PPE needs. To this end, our application is already in use by our home

institution and several hospitals across the country and is available on the

http://covid19forecast.rush.edu/ website. Consequently, the present work is intended to 1) make

our application broadly known to the healthcare and scientific communities 2) give healthcare

providers an in-depth understanding of our application, and 3) to point specialists, non-

specialists, and in-house predictive analytics teams to a freely available tool that can also serve

as modifiable platform of analytical source code and aggregated data. While some regions in the

United States have started to experience peaks in cases with plateaus and declines, we anticipate

that until a vaccine is available, episodes of repeated increased cases will be seen, for which

forecast models will inform operational responses.

Novel insights for applied and basic research – While our intention was not to provide *de novo*

models or to provide refined epidemiological parameter estimates, our tool does allow for novel

insights. First, our SEIR-SD model incorporates two phenomena of global, national, and local

concern, i.e., social distancing and lags in COVID-19 testing. To our knowledge few extensions

of the SEIR model have accounted for social distancing in being driven by an emergent social

response to increased percent infected and as driven by external forces (e.g., public policy).

Likewise, few if any SEIR models have accounted for the influence of lags in testing on the

apparent size of the infected population. Second, we envision that applied and basic research

studies can be conducted using the downloadable data of our application and the freely available

source code. Specifically, users can investigate any number of simple-to-complex relationships

using the downloadable forecast data that results from our suite of models and which is offered

alongside adjustable forecast windows, time-lags, lengths of stay, as well as other customizable

parameters and aggregated data (population size, date of first reported infection, numbers of

confirmed COVID-19 cases).

Pending and potential modifications – We are continually improving the functionality and

performance of our application to meet the predictive analytic needs of our home institution and

broader healthcare community. In the near future, we will include models to predict the eventual

decline of the pandemic and potential resurgence as social distancing guidelines and other

mitigating policies are relaxed. We also look to provide the functionality to 1) examine regions

outside the US, 2) examine county-level regions within the US, 3) include a greater array of

supply needs and forecasts for numbers of providers and staff needed, and 4) allow providers to

begin planning how and when to increase the number of elective surgeries and ambulatory visits.

In building our open-source application from a small set of freely available and highly popular

software tools, we expect that other researchers and healthcare analytics teams could readily

pursue these and other improvements.

Caveats and limitations – Our web application is versatile and easy to use. However, users

should consider the following caveats and limitations of modeling. First, our application draws

from a widely used COVID-19 dataset that may not reflect the true prevalence of COVID-19

within each US state and territory. While our application allows users to enter several parameters

(e.g., % of infected visiting one's hospital), these may change over time. Additionally, length of

stay for ICU and non-ICU patients likely fluctuates and may not necessarily be binomially

distributed. Similarly, time lags in hospital visits may not necessarily be Poisson distributed and

may also fluctuate across time. PPE usage rates may also fluctuate based on changing hospital

policies and supply shortages. Finally, our application does not account for differences in

susceptibility to COVID-19 with respect to age nor the influence of comorbid conditions and

sociodemographic factors.

367   **ACKNOWLEDGMENTS**

368   We thank the Johns Hopkins University Center for Systems Science and Engineering (JH CSSE)

369   for continuing to provide daily updated data on the COVID-19 pandemic.

REFERENCES

1. Anderson, R.M., Heesterbeek, H., Klinkenberg, D. and Hollingsworth, T.D. 2020. How will country-based mitigation measures influence the course of the COVID-19 epidemic? *The Lancet*. 395:931-934.

2. Brandenburg, A. 2020. Quadratic growth during the 2019 novel coronavirus epidemic. *arXiv preprint arXiv:2002.03638*.

3. Bacaër, N. 2011. *A short history of mathematical population dynamics*. Springer Science & Business Media.

4. Boldog, P., Tekeli, T., Vizi, Z., Dénes, A., Bartha, F.A. and Röst, G. 2020. Risk assessment of novel coronavirus COVID-19 outbreaks outside China. *Journal of clinical medicine*. 9:571.

5. Buckingham-Jeffery, E., Isham, V. and House, T. 2018. Gaussian process approximations for fast inference from infectious disease data. *Mathematical biosciences*. 301:111-120.

6. Bukhari, Q. and Jameel, Y. 2020. Will coronavirus pandemic diminish by summer? Available at: *http://dx.doi.org/10.2139/ssrn.3556998.*

7. Cao, Z., Zhang, Q., Lu, X., Pfeiffer, D., Jia, Z., Song, H. and Zeng, D.D. 2020. Estimating the effective reproduction number of the 2019-nCoV in China. medRxiv: 2020.01.27.20018952; doi: https://doi.org/10.1101/2020.01.27.20018952.

8. Fang, Y., Nie, Y. and Penny, M. 2020. Transmission dynamics of the COVID-19 outbreak and effectiveness of government interventions: A data-driven analysis. *Journal of medical virology*. 92:645-659.

9. Hethcote, H.W. and Van den Driessche, P. 1991. Some epidemiological models with nonlinear incidence. *Journal of Mathematical Biology*. 29:271-287.

10. Grasselli, G., Pesenti, A. and Cecconi, M. 2020. Critical care utilization for the COVID-19 outbreak in Lombardy, Italy: early experience and forecast during an emergency response. *Jama*. doi:10.1001/jama.2020.4031.

11. Johns Hopkins University Center for Systems Science and Engineering, 2019 Novel Coronavirus COVID-19 (2019-nCoV) Data Repository. https://github.com/CSSEGISandData/COVID-19.

412 12. Kucharski, A.J., Russell, T.W., Diamond, C., Liu, Y., Edmunds, J., Funk, S., Eggo, R.M.,
413   Sun, F., Jit, M., Munday, J.D. and Davies, N. 2020. Early dynamics of transmission and
414   control of COVID-19: a mathematical modelling study. *The Lancet Infectious Diseases*.
415   https://doi.org/10.1016/S1473-3099(20)30144-4.
416
417 13. Lin, Q., Zhao, S., Gao, D., Lou, Y., Yang, S., Musa, S.S., Wang, M.H., Cai, Y., Wang, W.,
418   Yang, L. and He, D. 2020. A conceptual model for the coronavirus disease 2019
419   (COVID-19) outbreak in Wuhan, China with individual reaction and governmental
420   action. *International journal of infectious diseases*. 93:211-216.
421
422 14. Liu, Y., Gayle, A.A., Wilder-Smith, A. and Rocklöv, J. 2020. The reproductive number of
423   COVID-19 is higher compared to SARS coronavirus. *Journal of travel medicine*. 22:1-4.
424   https://doi.org/10.1093/jtm/taaa021
425
426 15. Locey, K.J. and White, E.P. 2013. How species richness and total abundance constrain the
427   distribution of abundance. *Ecology letters*. 16:1177-1185.
428
429 16. Pedersen, M.G. and Meneghini, M. 2020. Quantifying undetected COVID-19 cases and
430   effects of containment measures in Italy. *ResearchGate Preprint* (online 21 March 2020)
431   DOI. 2020;10.
432
433 17. Maier, B.F. and Brockmann, D. 2020. Effective containment explains sub-exponential
434   growth in confirmed cases of recent COVID-19 outbreak in Mainland China. *arXiv*
435   preprint arXiv:2002.07572.
436
437 18. Maynard-Smith, J. 1978. *Models in ecology*. Cambridge University Press. Cambridge.
438
439 19. Peng, L., Yang, W., Zhang, D., Zhuge, C. and Hong, L. 2020. Epidemic analysis of COVID-
440   19 in China by dynamical modeling. *arXiv preprint arXiv:2002.06563*.
441
442 20. Read, J.M., Bridgen, J.R., Cummings, D.A., Ho, A. and Jewell, C.P. 2020. Novel
443   coronavirus 2019-nCoV: early estimation of epidemiological parameters and epidemic
444   predictions. *MedRxiv*. doi: https://doi.org/10.1101/2020.01.23.20018549
445
446 21. Remuzzi, A. and Remuzzi, G. 2020. COVID-19 and Italy: what next? *The Lancet*. doi:
447   https://doi.org/10.1016/S0140-6736(20)30627-9
448
449 22. Ridenhour, B., Kowalik, J.M. and Shay, D.K. 2018. Unraveling R 0: Considerations for
450   Public Health Applications. *American journal of public health*. 108:S445-S454.
451

23. Rocklöv, J., Sjödin, H., Wilder-Smith, A. 2020. COVID-19 outbreak on the Diamond
Princess cruise ship: estimating the epidemic potential and effectiveness of public health
countermeasures. *Journal of travel medicine*. doi: https://doi.org/10.1093/jtm/taaa030

24. Roosa, K., Lee, Y., Luo, R., Kirpich, A., Rothenberg, R., Hyman, J.M., Yan, P. and Chowell,
G. 2020. Real-time forecasts of the COVID-19 epidemic in China from February 5th to
February 24th, 2020. *Infectious Disease Modelling*. 5: 256-263.

25. Sit, V., Poulin-Costello, M. and Bergerud, W. 1994. *Catalogue of curves for curve fitting*.
Forest Science Research Branch, Ministry of Forests.

26. Wang, H., Wang, Z., Dong, Y., Chang, R., Xu, C., Yu, X., Zhang, S., Tsamlag, L., Shang,
M., Huang, J. and Wang, Y. 2020. Phase-adjusted estimation of the number of
coronavirus disease 2019 cases in Wuhan, China. *Cell Discovery*. 6:1-8.

27. WHO Director-General's opening remarks at the media briefing on COVID19 -March 2020.
https://www.who.int/dg/speeches/detail/who-director-general-s-opening-remarks-at-the-
media-briefing-on-covid-19---11-march-2020.

28. Wu, K., Darcet, D., Wang, Q. and Sornette, D. 2020. Generalized logistic growth modeling
of the COVID-19 outbreak in 29 provinces in China and in the rest of the world. arXiv
preprint arXiv:2003.05681.

29. You, C., Deng, Y., Hu, W., Sun, J., Lin, Q., Zhou, F., Pang, C.H., Zhang, Y., Chen, Z. and
Zhou, X.H. 2020. Estimation of the time-varying reproduction number of COVID-19
outbreak in China. *Available at SSRN 3539694*.

Table 1. Biological parameters for the SEIR-SD model. Our application attempts to optimize the

following SEIR-SD parameters within ranges of reported values for the average incubation

period, the average infectious period, and the basic reproductive number.

Parameter	Description	Reported Range	References
Avg. Incubation period (latent period)	Days during which an infected individual cannot infect others.	5 – 6 days	Anderson *et al*. 2020 Pederson and Meneghini 2020 Wang *et al*. 2020 Kucharski *et al*. 2020 Cao *et al*. 2020
Avg. Infectious period	Days over which an infected person remains infective.	1.6 – 13 days	You *et al*. 2020 Maier and Brockmann 2020 Wang *et al*. 2020 Read *et al*. 2020
Basic Reproductive Number (R_0)	Average number of secondary infections generated by a primary infection at the onset of outbreak	2.1 – 6.5	You *et al*. 2020 Pederson and Meneghini 2020 Maier and Brockmann 2020 Wang *et al*. 2020 Lui *et al*. 2020

482
483
484

485 **Figure 1.** Our application allows users to choose from five models that have previously been

486 employed in the study of COVID-19, the general cumulative forms of which are depicted below.

487 While the exponential and quadratic (2^{nd} degree polynomial) models only allow for continued

488 increase in cumulative cases, the logistic, Gaussian, and SEIR-SD models allow cumulative

489 cases to saturate.

491
492
493
494

Figure 2. Confidence interval (CI) hulls for the performance of models across US states and
territories from March 16th to April 15th. The Johns Hopkins University Center for Systems
Science and Engineering (JH CSSE) data shows most states beginning to report COVID-19 cases
by Marth 10th and we allowed the models a week of data before fitting them. The *x*-axis is in
days since the first reported case, occurring on or after March 10th. Lightly colored hulls are
90% CI, hulls of intermediate darkness are 50%, and the darkest hulls are 10% CI. Performance
is measured via a modified r^2 of observed versus predicted values where the *y*-intercept is forced
through 0 (*sensu* Locey and White 2013). The *y*-axes are scaled to show the greatest resolution
for each model and are not scaled similarly across all models. Lower right: Mean r^2 values
among states for all models except the exponential. This figure reveals the accuracy of models
fitted to observed data, but do not pertain to the accuracy of future forecasts.

Figure 3. The top pane of the application features the ability to choose a location and one of four

models for fitting data (black dots) and for making forecasts. The user then clicks a teal button to

update the application's plots of fitted predictions (gray-scale lines) and forecasts (colored lines).

The application allows the user to extend the forecast window to 60 days and view

logarithmically transformed data. The current image is the result of fitting the quadratic model to

Illinois COVID-19 data and includes a forecast window of 10 days. Forecasts up to 10 days old

are displayed to aid users in examining forecast variability. Values for coefficients of

determination (r^2) pertain to observed versus predicted values, where the *y*-intercept is forced

through 0 (*sensu* Locey and White 2013).

516
517

518
519
520
521

Figure 4. The second pane of our application allows users to set values for the percent of
COVID-19 patients in a given state visiting their hospital, the percent admitted, and the percent
admitted to critical care. Users can also enter the expected length of stay (LOS) for critical
patients (ICU), non-critical care patient, the percent of ICU patients expected to be on
ventilators, values for various PPE supply needs, and an expected time lag between when
patients first experience symptom and when they visit the hospital. The application then plots the
forecasted numbers of new visits and new admits, and then tabulates the forecasted total cases,
new cases, new visits, and new admits. See figures 4 and 5 for plots and tables of patient census
and PPE needs. The application informs the user that forecasted data beyond 14 days are
available via csv downloads.

532
533

534
535
536
537

538   **Figure 5.** The third pane our application plots and tabulates the forecasted patient census. Left:

539   A graph of forecasted numbers of critical care and non-critical care patients. Right: A table of

540   forecasted bed needs for all COVID-19 patients, non-ICU patients, ICU patients, and ICU

541   patients on ventilators. The application informs the user that forecasted data beyond 14 days are

542   available via csv downloads.

Figure 6. The bottom pane of our application plots and tabulates forecasted PPE needs. Left:
Forecasted PPE needs are plotted to reveal overall expected trends. PPE supplies with similar
input values become plotted on top of each other. Right: Forecasted PPE are tabulated with color
coding that corresponds to the figure on the left, to allow easier visual interpretation. The
application informs the user that forecasted data beyond 14 days are available via csv downloads.
Users can click the teal button at the bottom to display or refresh downloadable csv files.

558