Humeral elevation workspace during daily life of adults with spinal cord injury who use a manual wheelchair compared to age and sex matched able-bodied controls

Brianna M. Goodwin[1,2], Stephen M. Cain[3], Meegan G. Van Straaten[4], Emma Fortune[1,2], and Melissa M. B. Morrow[1,2]

(1) Division of Health Care Policy and Research, Department of Health Sciences Research, Mayo Clinic, Mayo Clinic, Rochester, MN, USA
(2) Robert D. and Patricia E. Kern Center for the Science of Health Care Delivery, Mayo Clinic, Rochester, MN, USA
(3) Department of Mechanical Engineering, University of Michigan, Ann Arbor, MI, USA
(4) Department of Physical Medicine and Rehabilitation, Mayo Clinic, Rochester, MN, USA

Corresponding Author:

Melissa (Missy) M. B. Morrow
200 First Street SW
Rochester, MN 55905
507-266-3400
morrow.melissa@mayo.edu

Abstract:

Shoulder pain and pathology are extremely common for individuals with spinal cord injuries (SCI) who

use manual wheelchairs (MWC). Although risky humeral kinematics have been measured during

wheelchair-based activities performed in the lab, little is known about arm kinematics in the free-living

environment. The purpose of this study was to measure the humeral elevation workspace throughout a

typical day for individuals with SCI who use a MWC and matched able-bodied controls. Thirty-four

individuals with SCI who use a MWC (42.7 ± 12.7 years of age, 28 males/6 females, C6-L1) and 34 age-

and sex-matched controls were enrolled. Participants wore three inertial measurement units (IMU) on

their upper arms and torso for one to two days. Humeral elevation angles were estimated and the

percentage of time individuals spent in five elevation bins ($0\text{-}30°$, $30\text{-}60°$, $60\text{-}90°$, $90\text{-}120°$, and $120\text{-}180°$)

were calculated. For both arms, the SCI cohort spent a significantly lower percentage of the day in $0\text{-}30°$

of humeral elevation (Dominant: SCI= $15.7 \pm 12.6\%$, Control= $32.1 \pm 15.6\%$, $p<0.0001$; Non-Dominant:

SCI= $21.9 \pm 17.8\%$, Control= $34.3 \pm 15.5\%$, $p=0.001$) and a significantly higher percentage of time in

elevations associated with tendon compression ($30\text{-}60°$ of humeral elevation, Dominant: SCI=

$62.8 \pm 14.4\%$, Control= $49.9.1 \pm 13.0\%$, $p<0.0001$; Non-Dominant: SCI= $58.8 \pm 14.9\%$, Control=

$48.3 \pm 13.6\%$, $p=0.003$) than controls. The increased percentage of time individuals with SCI spent in

elevations associated with tendon compression may contribute to increased shoulder pathology.

Characterizing the humeral elevation workspace utilized throughout a typical day may help in

understanding the increased prevalence of shoulder pain and pathology in individuals with SCI who use

MWCs.

Introduction

Shoulder pain is the most common site of musculoskeletal pain in adults with spinal cord injuries (SCI) who use manual wheelchairs (MWC) and its existence can significantly limit a person's functional abilities (1). Shoulder pain is reported in 37-70% of individuals with SCI who use a MWC (2-7). This differs vastly from the 2.9% of the general able-bodied population who experience shoulder pain (8). Although shoulder pain can develop any time after SCI, it is most commonly developed within the first five years (9) and often lasts longer than one year (3). Of the MWC users who experience pain, up to 93% have pathological signs on MRI (10), most commonly in the supraspinatus tendon (11).

In general, non-traumatic supraspinatus tendon tears in the shoulder have been thought to be caused by a combination of intrinsic and extrinsic factors (12). However, these effects can be exacerbated by overuse (13). One extrinsic factor is the narrowing of the subacromial space which causes compression of the supraspinatus tendons under the coracoacomial arch, and is hypothesized to lead to increased tendon pathology and pain (14, 15). Individualized musculoskeletal models utilizing MRI have estimated the risk of supraspinatus tendon compression through various humeral planes and elevations (16). The magnitude of glenohumeral elevation was the greatest kinematic predictor of tendon compression risk, followed by the specific plane of elevation. Results showed the supraspinatus tendon had the greatest risk of compression at humerothoracic elevations angles between 30-60° (15). Biplane fluoroscopic imaging of the shoulder joint during dynamic motion has shown similar results and demonstrated that at higher humeral elevations, as the humeral head rotates posteriorly, the supraspinatus tendon may no longer be under the coracoacromial arch, therefore, not at risk of compression (17). Understanding where tendon compression risk occurs can provide insights when interpreting the humeral elevation workspace of activities of daily living.

MWC propulsion, transfers, and other wheelchair-based activities of daily living have been investigated in laboratory environments to characterize the upper extremity kinematics that pose a risk for

shoulder tendon compression (18-20). Although in-laboratory data provide accurate quantifications of

how MWC users utilize their arms to complete specific activities, it is unable to quantify the exposure to

potentially risky postures in daily-living. To understand the daily exposure to risky shoulder motion,

inertial measurement units (IMUs) can be used to measure the angular velocity and acceleration of body

segments throughout an entire day in environments of daily living. IMU-based methods for quantifying

shoulder movement show good agreement with position-based motion capture and have been used to

quantify shoulder elevation angles; however a limited number of studies have applied these methods to

free-living full-day collections (21-26). To the best of our knowledge no study has utilized these methods

to understand the humeral elevation workspace of MWC users throughout an entire day.

The purpose of this study was to use IMUs to measure the humeral elevation workspace

throughout a typical day for individuals with SCI who use a MWC and compare it to matched able-bodied

controls. Comparison to controls allows for understanding of how humeral elevation exposure during

daily life differs when the option to use the lower extremities for weight bearing and mobility is removed.

This study also aimed to understand the effects of years of MWC use, pain, sex, and level of SCI on the

humeral elevation workspace. Due to the increased prevalence of shoulder pain and pathology in MWC

users compared to able-bodied controls (11) and the potential role that humeral elevation has on shoulder

tendon compression (15), we hypothesized that MWC users would utilize a different humeral elevation

workspace than able-bodied adults. Specifically, we hypothesized individuals with SCI would spend a

higher percentage of time at elevation angles associated with tendon compression risk. Understanding the

humeral elevation workspace of individuals with SCI may contribute to understanding why increased

levels of shoulder pain and pathology occur for this population.

Methods

Participant Enrollment

This study was approved by the Mayo Clinic Institutional Review Board. Individuals with an SCI

who used a MWC as their main mode of mobility were recruited through querying medical records and

care providers of local clinics. Sex- and age- (±2.5 years) matched able-bodied controls were recruited

through email distribution lists and classified ads. Participants for both cohorts were considered for

inclusion in the study if they were between 18-70 years of age and had functional range of motion at both

shoulders. Functional range of motion was defined as active humeral thoracic flexion, abduction of at

least 150° and the ability of the participant to touch the opposite shoulder, the back of his/her neck and

his/her low back. Prior to accrual to the study a licensed physical therapist (MVS) performed a screening

physical exam to confirm inclusion and exclusion criteria. Participants with SCI were excluded if they

self-reported previous diagnoses of complete supraspinatus tendon tears bilaterally. Controls were

excluded with a known unilateral or bilateral complete supraspinatus tendon tear(s). Additionally,

participants in both cohorts were excluded if there were conditions/factors which might have hindered

protocol adherence and controls were also excluded if they had any musculoskeletal or neurological

disorder which might have impacted shoulder health or changed the individual's ability to walk

independently.

Questionnaires and IMU Instrumentation

Upon enrollment, participants attended an in-lab visit. A licensed physical therapist screened

participants for eligibility and informed consent was obtained. Participants self-reported their hand

dominance and were asked if they had pain on either or both shoulders. All participants completed the

Disabilities of the Arm, Shoulder, and Hand (DASH) questionnaire (27) for both right and left arms. The

DASH encompasses 30 questions which ask individuals to rate their difficulty, pain, and satisfaction

when accomplishing specific tasks on a 5 point scale. Scores range from 0-100, with 0 indicating no

difficulty and 100 indicating the most difficulty, pain, and dissatisfaction. The DASH has been shown to

be reliable and to have high validity (28). Additionally, the SCI cohort filled out the Wheelchair User

Shoulder Pain Index (WUSPI) for both the right and left shoulders. To complete the WUSPI, participants

were asked to rate their shoulder pain when completing 15 tasks on a visual analog scale between "no

pain" and "worst pain ever experienced" (29). Possible scores ranged from 0 (no pain) and 150 (worst

pain ever experienced in all categories). The WUSPI is valid and reliable for this population (30).

Although we acknowledge that the DASH and WUSPI were designed to be filled out once, as part of a

larger study, both surveys were filled out for both arms to evaluate pain and function as it related to each

arm

Participants were given three wireless IMUs (Emerald or Opal, APDM, Inc., Portland, OR). Each

IMU contained a 3-axis accelerometer (±200 g), 3-axis gyroscope ($\pm2000°$/s), and 3-axis magnetometer

(±8 Guass). The three IMUs remained synchronized via a proprietary wireless protocol, recorded data at

128 Hz and saved the data to internal storage. In order to maximize the consistency of IMU placement

and functional calibration movements across participants, written handouts, video guides and in-person

instruction were provided. Participants were instructed to wear one IMU on each lateral upper arm and

one on the anterior of the torso; IMUs were secured on the body with elastic and Velcro straps. Each IMU

was labeled with the wear location (left arm, right arm, or torso) and an arrow indicating the proper

mounting orientation. Participants were instructed to wear the sensors during the entire length of two

typical days, excluding bathing and swimming, and take them off before going to bed. Both cohorts were

asked to perform their regular daily routines; participants in the control cohort did not use MWCs. Upon

donning the sensors for a day, participants performed a set of functional calibration postures (Fig 1,

Appendix A). Due to the collection of multiple days of data, participants were responsible for charging

the IMUs overnight using a provided charging station. After the data collection, participants returned the

sensors with a pre-paid mailer or in person to the study staff.

Fig 1: Functional calibration used to align IMU's with the body. Postures included static upright
neutral posture with upper arms resting against the thorax (posture 1), static and dynamic arm t-
pose/movement (shoulder abduction = 90º, posture 2), static and dynamic flexion pose/movement
(shoulder flexion = 90°, posture 3), dynamic flexion and extension of the torso (movement 4), and
simulated wheelchair use or walking (movement 5). Postures 2 and 3 were completed for both the right
and left arms separately. (Note: The individual pictured is a co-author).

Data Processing

Data were downloaded through Motion Studio (APDM, Inc., Portland, OR) and outputs included

estimates of the orientations of each IMU relative to an inertial frame (Fig 2). The orientation estimates

were derived from the combined acceleration and angular velocity data, rather than only the acceleration

data. While researchers have used IMU-measured acceleration only to estimate arm orientation (31, 32),

there are known limitations to this approach (33) , namely, the challenge of separating the measured

acceleration into gravitational and body caused components. Algorithms that use both measured

acceleration and angular velocity to estimate IMU orientation or attitude (orientation relative to gravity)

are well understood and are critical in strapdown inertial navigation (34). These algorithms integrate the

angular velocity signal to estimate orientation during periods with high dynamics (significant body

acceleration) and use the acceleration signal to update or correct the orientation during periods with low

dynamics (measured acceleration close to the acceleration of gravity). Further, these algorithms take

different forms and have been proven to be highly accurate for estimating attitude (35-38). Additionally,

the orientation estimates were calculated without magnetometer data due to the unknown and likely non-

uniform magnetic fields present throughout field data collections. While the orientation algorithm used by

APDM is proprietary, sensor fusion methods (e.g. Kalman filters) used to estimate IMU orientation from

raw sensor data are well understood and well documented in the literature (21, 34, 35). Custom MATLAB

(Mathworks, Natick, MA) code was written to calculate orientations of anatomical axes relative to IMU-

fixed reference frames using data collecting during each participant's functional calibration postures and

movements (Fig 1; Appendix A). Orientation of a given body segment (upper arm or thorax) in an inertial

(world) reference frame was then estimated using the orientation of the IMU and the orientation of the

anatomical axes relative to the IMU-fixed reference frame (Appendix B). Humeral elevation and thorax

deviation angles were defined as the angle between the long axis of the body segment (defined from the

function calibration) and vertical; these angles are only dependent on the estimated direction of gravity

relative to the body segment and, therefore, are drift-free metrics for quantifying body segment motions.

The calculated humeral elevation angles range between 0-180°, with 0° indicating the arm was down and

perfectly aligned with gravity and 180° indicating the arm was raised overhead and aligned with gravity.

These methods have previously been validated in unpublished data where five individuals with SCI

performed 10 reaching tasks. The absolute error and percent of error when compared to the gold standard

(electromagnetic system) were -0.06±1.12° and -1.44±1.28%, respectively, for the range of motion. The

absolute error and percent of error for the maximum elevation achieved during each reach were

2.59±2.47° and 2.04±2.47%, respectively.

Fig 2: Data processing workflow. This included data collected, IMU orientation, IMU alignment to arm through calibration postures, representative data, and humeral elevation bins. The percentage of time spent in each bin was calculated and used for analysis. (Note: The individual pictured is a co-author).

It is important to note that humerothoracic elevation angles and elevation planes relative to the

thorax were not calculated as these calculations require accounting for relative drift between the

orientation estimates of arm and torso IMUs. While the attitude estimates are accurate and do not drift,

the yaw or heading estimates do drift, making accurate calculation of humerothoraic angles over long

periods of time difficult (24). This difficulty is best illustrated by the fact that studies that use IMUs to

quantify shoulder motion during long periods in the real world either do not calculate shoulder angles(31,

39-41) or acknowledge the limitations of the methodology (24). Other work (25, 42) claims to accurately

calculate shoulder angle of elevation but not plane of elevation; however, shoulder angle of elevation

cannot be calculated accurately without the plane of elevation (43). Correcting the drift between sensors

about vertical is an active research area and requires a joint specific approach (44, 45). Therefore, in our

analysis, data in which the thorax deviation angle was more than 30° were eliminated in order to allow

humeral elevation angles to be interpreted similarly to humerothoracic elevation angles; 30° was selected

based on a sensitivity analysis performed during a prior study.

The percentage of daily wear time each participant spent in five humeral elevation bins were

calculated (0-30°, 30-60°, 60-90°, 90-120°, and 120-180°). The bin sizes were chosen as a means to

combine three theories: 1) a painful arc of motion occurs between 60-120° of arm abduction (46), 2)

Rapid Upper Limb Assessment (RULA) which bins risky arm postures between 0-20°, 20-45°, 45-90°,

and >90° (47), and 3) the subacromial risk area of 30-60° (15).

Periods of non-wear were determined using methods from Lugade and colleagues (2014) and

were excluded from data analysis. Data were also excluded from analysis if the functional calibration

postures were not completed properly or if at least eight hours of data were not collected after the

elimination of non-wear time. Data were included if one or two complete days were collected; if two days

were included all data were combined before the calculation of the percent of time in humeral elevation

bins.

Statistical Analysis

Multivariate analyses of variance (MANOVA) were used to test for the main effects of cohort,

sex, age, pain (measured by the WUSPI and DASH), level of injury, and years of MWC use on both

dominant and non-dominant side humeral elevation bins ($\alpha=0.05$). To test for level of injury the SCI

cohort was divided into three groups based on their injury level; cervical (C6-C8), high/mid thoracic (T1-

T8), and low thoracic/lumbar (T9-L1). Within groups, analysis of variance (ANOVA) was used to test for

the main effect of humeral elevation bin for both arms. When significant main effects were observed, post

hoc paired t-tests were performed. A Bonferroni correction factor was used to adjust the alpha level from

0.05 to 0.01 due to the calculation of time in five bins.

Results

Thirty-four participants with SCI who used a MWC, and 34 age (±2.5 years) and sex matched,

able-bodied adults were enrolled (Table 1). There were no statistical differences between the cohort's

self-reported weight, height, and dominant hand.

Table 1: Participant Demographics

	SCI	Control	P-value
Age	42.7 +/- 12.7 (22.6 - 63.3)	42.6 +/- 12.5 (24.3 - 61.0)	0.776
Sex	28 males/6 females	28 males/6 females	-
Self-reported weight (kg)	80.7 +/- 17.2 (54.0 - 145.1)	81.6 +/- 17.5 (56.7 - 149.7)	0.6822
Self-reported height (cm)	177.4 +/- 7.6 (160.0 - 195.6)	178.4 +/- 9.5 (160.0 - 205.7)	0.417
Injury Level			
Cervical (C6-C8)	7	-	-
High/mid thoracic (T1-T8)	16		
Low thoracic/lumbar (T9-L1)	11		
Years of manual wheelchair use (years)	11.5 +/- 10.7 (0.5 - 36.0)	-	-
Dominant arm	27 right/7 left	32 right/2 left	0.058
DASH (dominant arm)	15.2 +/- 17.5 (0 - 71.7)	1.3 +/- 2.9 (0- 15)	<0.0001
DASH (non-dominant arm)	13.6 +/- 14.2 (0 - 51.7)	1.1 +/- 3.3 (0 - 15)	<0.0001
WUSPI (dominant arm)	12.7 +/- 20.4 (0 - 71.2)	-	-
WUSPI (non-dominant arm)	10.8 +/- 16.2 (0 - 71.6)	-	-
Presence of pain	26	9	<0.0001
Number of participants	34	34	-

Excluded Data

One control was excluded from the study due to complete supraspinatus tear; however no SCI participants were excluded due to the previous diagnosis of a complete supraspinatus tear. Seven pairs of data were excluded from the analysis due to exclusion criteria (Fig 3). Data were collected for an average (SD) of 11.4(2.1) and 11.9(1.3) hours for the SCI and control cohorts, respectively. Additionally, on average 18.3(14.0) and 28.0(10.3) percent of the day was excluded because the trunk was at or over 30° for the SCI and control cohorts, respectively.

	Number of SCI files	Number of Control files
1 Day of data included in analysis	9	3
2 Days of data included in analysis	25	31

Fig 3: Data exclusion processes.
Data was excluded if either SCI or control did not collect data, a minimum of 8 hours of data were not collected, or one sensor malfunctioned. Data was included in analysis if one or two days of data was collected.

Humeral Elevation Workspace

There was a main effect of cohort across humeral elevation bins on both dominant and non-dominant sides ($p<0.0001$). Additionally, there was a main effect of humeral elevation bin for both cohorts and arms (dominant: $p<0.0001$, non-dominant: $p=0.005$, Fig 4). Individuals with SCI spent significantly more time in 30-60° of humeral elevation than all other elevations bins on both their dominant and non-dominant sides ($p<0.001$, Table 2). The SCI cohort spent 63% and 59% of their daily wear time (approximately 7 hours per day) at these elevations on their dominant and non-dominant sides, respectively. The controls also spent the greatest amount of daily wear time in this elevation bin at 50% and 48% on their dominant and non-dominant arm respectively, which was significantly lower than the SCI cohort for both arms (dominant: $p<.0001$, non-dominant: $p=0.003$, Table 2).

Fig 4: The percentage of time in each humeral elevation.
A) The average percentage of time throughout a typical day individuals in the SCI and control cohorts spent in 0-30°, 30-60°, 60-90°, 90-120°, and 120-180° of humeral elevation for their dominant and non-dominant sides. B) Percentage of time throughout a typical day individuals in the SCI and control cohorts spent in 0-30°, 30-60°, 60-90°, 90-120°, and 120-180° of humeral elevation for their dominant arm (top) and their non-dominant arm (bottom). For each boxplot the central line (red) represents the median, the edges of the box are the 25th and 75th percentiles, and the error bars extend the most extreme data points not considered outliers and, the outliers are denoted by red +. ** indicates $p < 0.0001$ and * indicates $p < 0.005$.

228 **Table 2: The average (SD) percentage of the day individuals with SCI and matched able-bodied**
229 **controls spent in five humeral elevation bins throughout one or two days**

Bin	SCI Dominant Hand Percentage (%)	Control Dominant Hand Percentage (%)	P-Value	SCI Non-Dominant Arm Percentage (%)	Control Non-Dominant Arm Percentage (%)	P-Value
0-30°	15.7 (12.6)	32.1 (15.6)	<0.0001	21.9 (17.8)	34.3 (15.5)	0.001
30-60°	62.8 (14.4)	49.9 (13.0)	<0.0001	58.8 (14.9)	48.3 (13.6)	0.003
60-90°	18.4 (11.0)	16.2 (9.6)	0.410	17.7 (14.8)	15.6 (6.2)	0.430
90-120°	2.8 (5.3)	1.4 (1.0)	0.145	1.4 (1.4)	1.6 (1.2)	0.589
120° - 180°	0.2 (0.4)	0.4 (0.8)	0.320	0.2 (0.5)	0.3 (0.3)	0.430

231   For the SCI cohort, the second largest percentage of time was spent in 60-90° of humeral

232 elevation (approximately 20% of their day for both arms). Controls spent their second largest percentage

233 of time in 0-30° of elevation for both arms, which was significantly higher than the amount of time the

234 SCI cohort spent in this elevation bin (p<0.001). Individuals with SCI spent comparable amounts of time

235 in 0-30° and 60-90° of elevation, while controls spent significantly more time in 0-30° than 60-90° of

236 humeral elevation on the dominant (p<0.001) and non-dominant (p<0.0001) sides.

237   On average, participants in both cohorts spent less than 3% of their day (<25 minutes) in

238 elevations over 90° for both arms. There were no significant differences between cohorts for the 60-90°

239 90-120°and >120° humeral elevation bins or between dominant and non-dominant arms for each cohort

240 and each elevation bin.

241 *Pain*

242   Pain, measured by the DASH and WUSPI, did not have a significant effect on the percentage of

time an individual spent in any humeral elevation bins for both dominant and non-dominant arms

(p>0.01).

Sex, Age, Injury level, and Years of MWC Use

There were no main effects of sex (Table 3), age (Table 4), injury level (Table 3), or years of

MWC Use (Table 4) on either arm ($p > 0.01$).

Table 3: The percentage of time individuals spent in humeral elevation bins based on their injury
level and sex

Injury Level			
	Cervical	High/mid thoracic	Low thoracic/ lumbar	P-Value
Dominant Arm			
0-30°	20.3 ± 12.5	15.5 ± 14.0	13.1 ± 11.4	0.521
30-60°	57.4 ± 11.0	63.0 ± 15.9	66.0 ± 15.1	0.493
60-90°	18.0 ± 9.7	18.4 ± 12.4	18.8 ± 11.2	0.988
90-120°	3.7 ± 5.2	3.0 ± 6.9	1.8 ± 2.9	0.769
120-180°	0.6 ± 0.8	0.1 ± 0.2	0.2 ± 0.2	0.050
Non-Dominant Arm			
0-30°	24.7 ± 16.9	20.6 ± 21.1	22.1 ± 15.0	0.888
30-60°	56.9 ± 11.3	59.4 ± 18.6	59.0 ± 12.6	0.937
60-90°	16.5 ± 9.1	18.9 ± 19.	16.6 ± 11.4	0.910
90-120°	1.6 ± 1.2	1.0 ± 1.0	1.9 ± 1.9	0.275
120-180°	0.3 ± 0.4	0.06 ± 0.09	0.4 ± 0.8	0.266
Sex			
	Male	Female	P - Value
Dominant Arm			
0-30°	14.4 ± 12.	21.9 ± 15.3	0.199
30-60°	62.8 ± 14.4	63.2 ± 17.4	0.950
60-90°	19.4 ± 11.7	13.8 ± 8.0	0.267
90-120°	3.2 ± 5.9	1.0 ± 0.8	0.381
120-180°	0.2 ± 0.5	0.2 ± 0.3	0.814
Non-Dominant Arm			
0-30°	20.4 ± 18.3	29.0 ± 16.2	0.294
30-60°	59.1 ± 15.6	57.4 ± 14.2	0.814
60-90°	18.8 ± 16.1	12.2 ± 7.6	0.337
90-120°	1.5 ± 1.5	1.2 ± 0.8	0.691
120-180°	0.2 ± 0.5	0.1 ± 0.1	0.565

Table 4: The linear regression values for the percentage of time individuals spent in humeral elevation bins based on age and years of MWC use

	Age		Years of MWC use	
	R^2	P-Value	R^2	P-Value
Dominant Arm				
0-30°	0.104	0.06	0.009	0.60
30-60°	0.037	0.28	0.000	0.97
60-90°	0.013	0.41	0.008	0.62
90-120°	0.000	0.94	0.002	0.82
120-180°	0.002	0.79	0.047	0.22
Non-Dominant Arm				
0-30°	0.027	0.35	0.001	0.84
30-60°	0.002	0.81	0.009	0.58
60-90°	0.025	0.37	0.007	0.65
90-120°	0.000	0.88	0.054	0.19
120-180°	0.049	0.21	0.023	0.39

Discussion

This study aimed to understand the humeral elevation workspace utilized throughout a typical day by individuals with SCI who use a MWC. These results were compared to controls to better understand factors which may contributed to a higher rate of both pain and tendon pathology associated with years of MWC use (11). Both individuals with SCI and controls spent the majority of their day (~80%) in elevation angles between 0 and 60°. However, individuals with SCI spent significantly more time in humeral elevations associated with supraspinatus tendon compression (30-60°) than controls. There was no evidence of the effect of injury level, years of MWC use, age, or sex on the humeral elevation workspace individuals with SCI spend time in.

With the growing capabilities of wearable technology, many SCI-specific algorithms have been created and validated to accompany and enhance data captured in a lab setting (49). Many of the studies using wearable technology to understand movement of MWC users have focused specifically on wheelchair propulsion and use (50, 51), with less focus on understanding humeral elevation angles or overuse of the arms of MWC users. The data presented in the current study supplements data collected in

a laboratory setting and other free-living MWC use metrics by providing lengths of exposure to risky

postures in the free living environment.

Recently it has been suggested that compression of the supraspinatus tendon occurs at low

elevation angles. Giphart, van der Meijden (17) suggested that subacromial impingement syndrome

occurs below 70° of humeral elevation and the minimum distance between the footprint of the

supraspinatus tendon and greater tuberosity occurred between 36° and 65° of humeral elevation.

Additionally, using individualized bone models (from MRI) and group averaged kinematics, Lawrence,

Schlangen (15) used musculoskeletal simulation models to suggest the minimum distance between the

coracoacomial arch and humerus occurred at 42° of humerothoracic elevation. Our results show that

individuals with SCI who use a MWC spent significantly more time than controls in a similar range of

humeral elevations (30-60°). This difference could be in part due to differences in the arm elevation

workspace during mobility. During MWC propulsion the humeral elevation required is between 25 and

55° at a self-selected speed (52, 53); however during walking the humeral elevation angles required are

much lower (54). The difference in humeral elevation during mobility likely is not the only contributor to

this increase, as MWC users move about 3 km less than able-bodied individuals and only spend a small

amount of their day actually propelling themselves; estimates range from 16 to 54 minutes per day (50,

55). Another contributing factor to this discrepancy may be wheelchair setup; for example MWC users

may not place their arms in a neutral resting position (0-30°) due to the location of their arm rest. In

addition to the humeral elevation workspace differing during propulsion for MWC users and walking for

able-bodied individuals, the loading of the shoulder is also different during these two tasks and likely

contributes to the increase in pathology in MWC users. Further, additional data collections and analyses

are needed to fully understand the clinical implications of the differences in humeral elevation between

the wheelchair users and able-bodied control group. Future work will determine more details about these

differences such as the activity levels and/or participant activities while in 30-60° of humeral elevation.

These future analyses can guide whether a reduction of time spent in these elevation angles should be

considered as a possible intervention to prevent or treat shoulder dysfunction.

Capturing a holistic view of an individual's exposure to potentially risky humeral elevation is

dependent on many factors including occupation and activities performed throughout a day. A study

looking at 10 able-bodied elderly adults using only accelerometery data found that less than 4% of an

individual's day was spent in elevations above 90°, with the average elevation angle occurring at 40°

(42). These results are very similar to the data presented in the current study for both cohorts; about 3% of

the day was spent in elevations over 90°. Previous reports have suggested that extended periods of time in

overhead motion may be the cause of increased shoulder pain. Our results paired with the most recent

modeling and imaging data may suggest that injury to the supraspinatus tendon due to tendon

compression of the SCI cohort occurs due to increased time between 30-60° of humeral elevations.

Further, pain in higher elevation angles may be caused by other mechanisms (15). Continuing to map this

workspace for individuals with SCI who use a MWC while they perform specific tasks (i.e., propulsion or

transfers) may help us to further understand daily risk exposures and the contribution of specific tasks.

Although out of the scope of this study, activity detection is an active area of research for our group (55).

Multiple challenges exist when using unsupervised real-world IMU data. First, accounting for and

correcting the drift of IMU-based body segment orientation estimates is a common challenge in

understanding the relative orientation of body segments (i.e. joint angles), especially for extended data

collections (see excellent discussion in (24)). The current algorithms utilized in this study do not take the

plane of motion into account; 30° of humeral elevation in front of the body, to the side, or behind would

all be interpreted as 30° of humeral elevation and are indistinguishable. While we could have used the

orientation estimates to calculate humerothoracic angle of elevation and plane of elevation, we know that

those calculations would contain errors from the heading/yaw drift. Heading drift directly affects the

plane of elevation and accurately calculating the plane of elevation is critical to accurately calculating

humerothoracic angle of elevation. Therefore, the data presented here only used the angle of the humerus

relative to vertical (humeral elevation angle) and not the trunk (humerothoracic angle). This was

compensated for by eliminating humeral elevation time points where the trunk angle was at or over 30° of

tilt; participants may have been leaning over or lying down. On average about 10% more data was

eliminated from the control data sets than the SCI data sites, indicating the controls had more variability

and movement of their trunk than the SCI cohort. Even with these limitations, the methods used in this

study to estimate sensor orientation and humeral elevation are more accurate than other methods using

only acceleration data, especially during movements with high dynamics (35-38).

There are limitations with the data presented in this study to consider. Previous studies have

found that up to four days of data collection are needed to represent propulsion trends consistent

throughout a MWC user's daily life (56). Only one or two days of data were collected for participants in

this study due to participant availability and adherence to the protocol. We attempted to compensate for

this by asking participants to wear the sensors on 'typical days.' The calibration protocol used in this

study enabled us to determine humeral elevations without an in-lab calibration. As participants performed

the calibration protocol unsupervised, it's possible that there could be errors induced by incorrect neutral

and 90° calibration postures. The data presented here were binned into 30° ranges below 120° of humeral

elevation; however, creating bins with different boundaries may affect the results. Appendix C shows the

average percent of time in 10° bins. Additionally, there are other factors beyond humeral elevation that

contribute to shoulder injury in the SCI population including increased load on the shoulder due to MWC

propulsion, body transfers, and repetitive motion. Loading of the shoulder although not measured in this

study, has an important role in the increased pathology and pain for MWC users.

Conclusions

This study aimed to understand the humeral elevation workspace throughout a typical day of

individuals with SCI who use a MWC and compare it to the workspace of age- and sex-matched controls.

Our data suggest that individuals with SCI who use a MWC may spend more time in a potentially risky

humeral elevation range (30-60°) than the controls. The findings from this study do not support an effect

of age, sex, pain, injury level, or years since injury on the humeral elevation workspace for adults with

SCI who use a MWC. Future work should expand the understanding of loading of the upper extremity

during daily life and characterize more in-depth information about shoulder workspace and activities of

daily living across injury levels and groups with and without pain and pathology.

Conflicts of Interest:

There are no conflicts of interest to disclose.

Acknowledgements:

This publication was made possible by funding from the National Institutes of Health (grant no. R01

HD84423-01), Mayo Clinic Robert D. and Patricia E. Kern Center for the Science of Health Care

Delivery, and the National Center for Advancing Translational Sciences (UL1 TR002377).

Appendix

Appendix A: Defining sensor-to-segment alignment matrices

When using inertial sensors to quantify the movement of body segments, determining the sensor-to-segment alignment is critical to enable accurate quantification of the orientation of the body segment rather than the orientation of the sensor. In other words, the orientation of a body segment's anatomical reference frame with respect to the sensor reference frame must be determined so that estimates of the sensor orientation can be used to understand body segment orientation. In our study, we utilize functional alignment movements, in which participants complete some known movements or poses for which at least one anatomical axis can be estimated in an inertial measurement unit's (IMU's) body-fixed frame of reference.

Our functional alignment poses and movements are as follows:

   FA1. Sitting/standing upright with arms at sides
   FA2. Right arm t-pose (Figure 1 Posture 2)
   FA3. Dynamic ab/adduction of the right shoulder, keeping right arm movement in frontal plane
   FA4. Right arm flexion pose (Figure 1 Posture 3)
   FA5. Dynamic flexion/extension of the right shoulder, keeping right arm movement in sagittal plane
   FA6. Left arm t-pose (similar to Figure 1 Posture 2)
   FA7. Dynamic ab/adduction of the left shoulder, keeping left arm movement in frontal plane
   FA8. Left arm flexion pose (similar Figure 1 Posture 3)
   FA9. Dynamic flexion/extension of the left shoulder, keeping left arm movement in sagittal plane
   FA10. Dynamic trunk flexion/extension, keeping movement of thorax in sagittal plane
   FA11. Sitting/standing upright with arms at sides
   FA12. Simulated wheelchair propulsion or arm swing

Using data (IMU measured accelerations and angular velocities) from the above poses and movements, we construct sensor-to-segment alignment matrices for the thorax, right arm, and left arm as described below.

For the thorax, we first use the average acceleration due to gravity measured by the torso-mounted IMU during FA1 and FA11 to define a body segment fixed z- axis (superior-inferior axis,$\hat{Z}_{thorax}$) for the thorax:

$$\hat{Z}_{thorax} = \frac{\vec{a}_{FA1\,\&\,FA11}}{\sqrt{\vec{a}_{FA1\,\&\,FA11} \cdot \vec{a}_{FA1\,\&\,FA11}}} \qquad (1)$$

This establishes the thorax posture for which the thorax deviation angle is equal to zero. The average axis of rotation for the thorax (torso-mounted IMU) measured during FA10 is used to define the thorax x-axis (medial-lateral axis) for the thorax. To determine the average axis of rotation of the thorax segment ($\hat{X}_{thorax}$), a principal components analysis is performed on the measured segment angular velocity measured during FA10. The first principal component is the unit vector defining the average axis of rotation.

388 We define an anterior-posterior axis ($\hat{Y}_{thorax}$) for the thorax as the unit vector orthogonal to the superior-
389 inferior axis and medial-lateral axis:

$$\hat{Y}_{thorax} = \frac{\hat{Z}_{thorax} \times \hat{X}_{thorax}}{\text{norm}(\hat{Z}_{thorax} \times \hat{X}_{thorax})} \quad (2)$$

390 Finally, we ensure that the medial-lateral axis is orthogonal to the anterior-posterior and superior-inferior
391 axes:

$$\hat{X}_{thorax} = \hat{Y}_{thorax} \times \hat{Z}_{thorax} \quad (3)$$

392 The resulting unit vectors ($\hat{X}_{thorax}, \hat{Y}_{thorax}, \hat{Z}_{thorax}$) define a body-segment fixed frame aligned with
393 estimated anatomical axes. The direction cosine matrix that defines the transformation of measurements
394 made in the sensor-fixed frame to those in a thorax-fixed frame is defined by Equation (4), where each
395 row of the matrix contains the components of the segment-fixed axes.

$$\text{R}_{thorax|sensor} = \begin{bmatrix} \hat{X}_{thorax} \\ \hat{Y}_{thorax} \\ \hat{Z}_{thorax} \end{bmatrix} \quad (4)$$

397 For the left and right arm, we aim to establish an axis that represents the long-axis of the humerus
398 (defined here as the z-axis). Starting with the right arm, we first get one estimate of the z-axis of the upper
399 arm by using acceleration measured during FA2 and angular velocity measured during FA3.

$$\hat{X}_{RArm1} = \frac{\vec{a}_{FA2}}{\sqrt{\vec{a}_{FA2} \cdot \vec{a}_{FA2}}} \quad (5)$$

400 A principal components analysis is performed on the measured segment angular velocity measured during
401 FA3; the first principal component is the unit vector defining the average axis of rotation during FA3
402 ($\hat{Y}_{RArm1}$). The first estimate of the z-axis of the upper arm is calculated:

$$\hat{Z}_{RArm1} = \hat{X}_{RArm1} \times \hat{Y}_{RArm1} \quad (6)$$

403 We choose $\hat{Z}_{RArm1} = \hat{Z}_{RArm1}$ or $\hat{Z}_{RArm1} = -\hat{Z}_{RArm1}$ such that $\hat{Z}_{RArm1}$ points superiorly (determined by
404 examining $\vec{a}_{FA1}$ for the right arm). We get a second estimate of the z-axis of the upper arm by using
405 acceleration measured during FA4 and angular velocity measured during FA5.

$$\hat{X}_{RArm2} = \frac{\vec{a}_{FA4}}{\sqrt{\vec{a}_{FA4} \cdot \vec{a}_{FA4}}} \quad (7)$$

406 A principal components analysis is performed on the measured segment angular velocity measured during
407 FA5; the first principal component is the unit vector defining the average axis of rotation during FA5
408 ($\hat{Y}_{RArm2}$). The second estimate of the z-axis of the upper arm is calculated:

$$\hat{Z}_{RArm2} = \hat{X}_{RArm2} \times \hat{Y}_{RArm2} \quad (8)$$

409   We choose $\hat{Z}_{RArm2} = \hat{Z}_{RArm2}$ or $\hat{Z}_{RArm2} = -\hat{Z}_{RArm2}$ such that $\hat{Z}_{RArm2}$ points superiorly (determined by
410   examining $\vec{a}_{FA1}$ for the right arm).

411   We define the right arm z-axis using the two estimates:

$$\hat{Z}_{RArm} = \frac{mean([\hat{Z}_{RArm1}; \hat{Z}_{RArm2}])}{norm(mean([\hat{Z}_{RArm1}; \hat{Z}_{RArm2}]))} \tag{9}$$

412   We construct a right arm x-axis:

$$\hat{X}_{RArm} = \frac{\hat{Y}_{RArm1} \times \hat{Z}_{RArm}}{norm(\hat{Y}_{RArm1} \times \hat{Z}_{RArm})} \tag{10}$$

413   We choose $\hat{X}_{RArm} = \hat{X}_{RArm}$ or $\hat{X}_{RArm} = -\hat{X}_{RArm}$ such that $\hat{X}_{RArm}$ points up during FA2 (determined by
414   examining $\vec{a}_{FA2}$ for the right arm).

415   Finally, we construct a right arm y-axis:

$$\hat{Y}_{RArm} = \hat{Z}_{RArm} \times \hat{X}_{RArm} \tag{11}$$

416   The resulting unit vectors $(\hat{X}_{RArm}, \hat{Y}_{RArm}, \hat{Z}_{RArm})$ define a body-segment fixed frame aligned with
417   estimated anatomical axes for the right arm. The direction cosine matrix that defines the transformation of
418   measurements made in the sensor-fixed frame to those in a right arm-fixed frame is defined by Equation
419   (12), where each row of the matrix contains the components of the segment-fixed axes.

$$R_{RArm|sensor} = \begin{bmatrix} \hat{X}_{RArm} \\ \hat{Y}_{RArm} \\ \hat{Z}_{RArm} \end{bmatrix} \tag{12}$$

421   For the left arm we first get one estimate of the z-axis of the upper arm by using acceleration measured
422   during FA6 and angular velocity measured during FA7.

$$\hat{X}_{LArm1} = \frac{\vec{a}_{FA6}}{\sqrt{\vec{a}_{FA6} \cdot \vec{a}_{FA6}}} \tag{13}$$

423   A principal components analysis is performed on the measured segment angular velocity measured during
424   FA7; the first principal component is the unit vector defining the average axis of rotation during FA7
425     $(\hat{Y}_{LArm1})$. The first estimate of the z-axis of the upper arm is calculated:

$$\hat{Z}_{LArm1} = \hat{X}_{LArm1} \times \hat{Y}_{LArm1} \tag{14}$$

426   We choose $\hat{Z}_{LArm1} = \hat{Z}_{LArm1}$ or $\hat{Z}_{LArm1} = -\hat{Z}_{LArm1}$ such that $\hat{Z}_{LArm1}$ points superiorly (determined by
427   examining $\vec{a}_{FA1}$ for the left arm). We get a second estimate of the z-axis of the upper arm by using
428   acceleration measured during FA8 and angular velocity measured during FA9.

$$\hat{X}_{LArm2} = \frac{\vec{a}_{FA8}}{\sqrt{\vec{a}_{FA8} \cdot \vec{a}_{FA8}}} \tag{15}$$

429   A principal components analysis is performed on the measured segment angular velocity measured during
430   FA9; the first principal component is the unit vector defining the average axis of rotation during FA9
431   ($\hat{Y}_{LArm2}$). The second estimate of the z-axis of the upper arm is calculated:

$$\hat{Z}_{LArm2} = \hat{X}_{LArm2} \times \hat{Y}_{LArm2} \tag{16}$$

432   We choose $\hat{Z}_{LArm2} = \hat{Z}_{LArm2}$ or $\hat{Z}_{LArm2} = -\hat{Z}_{LArm2}$ such that $\hat{Z}_{LArm2}$ points superiorly (determined by
433   examining $\vec{a}_{FA1}$ for the left arm).

434   We define the left arm z-axis using the two estimates:

$$\hat{Z}_{LArm} = \frac{mean([\hat{Z}_{LArm1}; \hat{Z}_{LArm2}])}{norm(mean([\hat{Z}_{LArm1}; \hat{Z}_{LArm2}]))} \tag{17}$$

435   We construct a left arm x-axis:

$$\hat{X}_{LArm} = \frac{\hat{Y}_{LArm1} \times \hat{Z}_{LArm}}{\text{norm}(\hat{Y}_{LArm1} \times \hat{Z}_{LArm})} \tag{18}$$

436   We choose $\hat{X}_{LArm} = \hat{X}_{LArm}$ or $\hat{X}_{LArm} = -\hat{X}_{LArm}$ such that $\hat{X}_{LArm}$ points down during FA6 (determined
437   by examining $\vec{a}_{FA6}$ for the left arm).

438   Finally, we construct a left arm y-axis:

$$\hat{Y}_{LArm} = \hat{Z}_{LArm} \times \hat{X}_{LArm} \tag{19}$$

439   The resulting unit vectors ($\hat{X}_{LArm}, \hat{Y}_{LArm}, \hat{Z}_{LArm}$) define a body-segment fixed frame aligned with
440   estimated anatomical axes for the left arm. The direction cosine matrix that defines the transformation of
441   measurements made in the sensor-fixed frame to those in a left arm-fixed frame is defined by Equation
442   (19), where each row of the matrix contains the components of the segment-fixed axes.

$$R_{LArm|sensor} = \begin{bmatrix} \hat{X}_{LArm} \\ \hat{Y}_{LArm} \\ \hat{Z}_{LArm} \end{bmatrix} \tag{20}$$

444 **Appendix B:** Calculating humeral elevation thorax deviation angles

445 The humeral elevation angle and thorax deviation angle are defined as the angle between the segment z-
446 axis and vertical and are calculated by first calculating the direction cosine matrix describing the
447 orientation of the body segment in the inertial/world reference frame:

$$R_{world|segment} = R_{world|sensor}\left(R_{segment|sensor}\right)^T \tag{21}$$

448 Where $R_{world|sensor}$ is the direction cosine matrix describing the rotation from the sensor reference frame
449 to the inertial/world reference frame and $R_{sensor|segment}$ is the sensor-to-segment alignment from
450 Equation (4), (12), or (20). Humeral elevation angles and thorax deviation angles are then calculated from
451 Equation (22).

$$\theta = acos\left(R_{world|segment}(3,:) \cdot [0 \quad 0 \quad 1]\right) \tag{22}$$

452 Where $R_{world|segment}(3,:)$ refers to the last row of $R_{world|segment}$.

453   **Appendix C:** The distribution of the percentage of time the SCI and control cohort spent in 10° bins for
454   both the dominant and non-dominant arms.

References:

1.   Cooper RA, Boninger ML, Robertson RN. Repetitive Strain Injury Among Manual Wheelchair Users. Team Rehab Report. 1998;9(2):35-8.

2.   Curtis KA, Drysdale GA, Lanza RD, Kolber M, Vitolo RS, West R. Shoulder pain in wheelchair users with tetraplegia and paraplegia. Archives of physical medicine and rehabilitation. 1999;80(4):453-7.

3.   Alm M, Saraste H, Norrbrink C. Shoulder pain in persons with thoracic spinal cord injury: prevalence and characteristics. Journal of rehabilitation medicine. 2008;40(4):277-83.

4.   Samuelsson K, Tropp H, Gerdle B. Shoulder pain and its consequences in paraplegic spinal cord-injured, wheelchair users. Spinal cord. 2004;42(1):41.

5.   Dalyan M, Cardenas D, Gerard B. Upper extremity pain after spinal cord injury. Spinal cord. 1999;37(3):191-5.

6.   Divanoglou A, Augutis M, Sveinsson T, Hultling C, Levi R. Self-reported health problems and prioritized goals in community-dwelling individuals with spinal cord injury in Sweden. Journal of rehabilitation medicine. 2018;50(10):872-8.

7.   Dyson-Hudson TA, Kirshblum SC. Shoulder pain in chronic spinal cord injury, part 1: epidemiology, etiology, and pathomechanics. Taylor & Francis; 2004.

8.   Greving K, Dorrestijn O, Winters J, Groenhof F, Van der Meer K, Stevens M, et al. Incidence, prevalence, and consultation rates of shoulder complaints in general practice. Scandinavian journal of rheumatology. 2012;41(2):150-5.

9.   Sie IH, Waters RL, Adkins RH, Gellman H. Upper extremity pain in the postrehabilitation spinal cord injured patient. Archives of physical medicine and rehabilitation. 1992;73(1):44-8.

10.   Giner-Pascual M, Alcanyis-Alberola M, González LM, Aguilar-Rodriguez M, Querol F. Shoulder pain in cases of spinal injury: influence of the position of the wheelchair seat. International Journal of Rehabilitation Research. 2011;34(4):282-9.

11.   Akbar M, Balean G, Brunner M, Seyler TM, Bruckner T, Munzinger J, et al. Prevalence of rotator cuff tear in paraplegic patients compared with controls. JBJS. 2010;92(1):23-30.

12.   Seitz AL, McClure PW, Finucane S, Boardman III ND, Michener LA. Mechanisms of rotator cuff tendinopathy: intrinsic, extrinsic, or both? Clinical biomechanics. 2011;26(1):1-12.

13.   Carpenter JE, Flanagan CL, Thomopoulos S, Yian EH, Soslowsky LJ. The effects of overuse combined with intrinsic or extrinsic alterations in an animal model of rotator cuff tendinosis. The American journal of sports medicine. 1998;26(6):801-7.

14.   Braman JP, Zhao KD, Lawrence RL, Harrison AK, Ludewig PM. Shoulder impingement revisited: evolution of diagnostic understanding in orthopedic surgery and physical therapy. Medical & biological engineering & computing. 2014;52(3):211-9.

15.   Lawrence RL, Schlangen DM, Schneider KA, Schoenecker J, Senger AL, Starr WC, et al. Effect of glenohumeral elevation on subacromial supraspinatus compression risk during simulated reaching. Journal of Orthopaedic Research. 2017;35(10):2329-37.

16.   Lawrence RL, Sessions WC, Jensen MC, Staker JL, Eid A, Breighner R, et al. The effect of
glenohumeral plane of elevation on supraspinatus subacromial proximity. Journal of Biomechanics.
2018;79:147-54.

17.   Giphart JE, van der Meijden OA, Millett PJ. The effects of arm elevation on the 3-dimensional
acromiohumeral distance: a biplane fluoroscopy study with normative data. Journal of shoulder and elbow
surgery. 2012;21(11):1593-600.

18.   Koontz AM, Cooper RA, Boninger ML, Souza AL, Fay BT. Shoulder kinematics and kinetics
during two speeds of wheelchair propulsion. Journal of rehabilitation research and development.
2002;39(6):635-50.

19.   Morrow MM, Kaufman KR, An KN. Scapula kinematics and associated impingement risk in
manual wheelchair users during propulsion and a weight relief lift. Clinical biomechanics.
2011;26(4):352-7.

20.   Requejo P, Mulroy S, Haubert LL, Newsam C, Gronley J, Perry J. Evidence-based strategies to
preserve shoulder function in manual wheelchair users with spinal cord injury. Topics in Spinal Cord
Injury Rehabilitation. 2008;13(4):86-119.

21.   El-Gohary M, McNames J. Shoulder and elbow joint angle tracking with inertial sensors. IEEE
Transactions on Biomedical Engineering. 2012;59(9):2635-41.

22.   Bouvier B, Duprey S, Claudon L, Dumas R, Savescu A. Upper Limb Kinematics Using Inertial
and Magnetic Sensors: Comparison of Sensor-to-Segment Calibrations. Sensors (Basel).
2015;15(8):18813-33.

23.   Cutti AG, Giovanardi A, Rocchi L, Davalli A, Sacchetti R. Ambulatory measurement of shoulder
and elbow kinematics through inertial and magnetic sensors. Med Biol Eng Comput. 2008;46(2):169-78.

24.   Kirking B, El-Gohary M, Kwon Y. The feasibility of shoulder motion tracking during activities
of daily living using inertial measurement units. Gait & posture. 2016;49:47-53.

25.   Chapman RM, Torchia MT, Bell J-E, Van Citters DW. Continuously monitoring shoulder motion
after total shoulder arthroplasty: maximum elevation and time spent above 90° of elevation are critical
metrics to monitor. Journal of shoulder and elbow surgery. 2019.

26.   Langohr GDG, Haverstock JP, Johnson JA, Athwal GS. Comparing daily shoulder motion and
frequency after anatomic and reverse shoulder arthroplasty. Journal of shoulder and elbow surgery.
2018;27(2):325-32.

27.   Hudak PL, Amadio PC, Bombardier C, Beaton D, Cole D, Davis A, et al. Development of an
upper extremity outcome measure: the DASH (disabilities of the arm, shoulder, and head). American
journal of industrial medicine. 1996;29(6):602-8.

28.   Beaton DE, Katz JN, Fossel AH, Wright JG, Tarasuk V, Bombardier C. Measuring the wole or
the parts?: Validity, reliability, and responsiveness of the disabilities of the arm, shoulder and hand
outcome measure in different regions of the upper extremity. Journal of Hand Therapy. 2001;14(2):128-
42.

29.   Curtis K, Roach K, Applegate EB, Amar T, Benbow C, Genecco T, et al. Development of the
wheelchair user's shoulder pain index (WUSPI). Spinal Cord. 1995;33(5):290.

30.   Curtis K, Roach K, Applegate E, Amar T, Benbow C, Genecco T, et al. Reliability and validity of
the wheelchair user's shoulder pain index (WUSPI). Spinal Cord. 1995;33(10):595.

31.   Coley B, Jolles BM, Farron A, Aminian K. Arm position during daily activity. Gait & Posture.
2008;28(4):581-7.

32.   Amasay T, Zodrow K, Kincl L, Hess J, Karduna A. Validation of tri-axial accelerometer for the
calculation of elevation angles. International Journal of Industrial Ergonomics. 2009;39(5):783-9.

33.   Amasay T, Latteri M, Karduna AR. In vivo measurement of humeral elevation angles and
exposure using a triaxial accelerometer. Human factors. 2010;52(6):616-26.

34.   Savage PG. Strapdown inertial navigation integration algorithm design part 1: Attitude
algorithms. Journal of guidance, control, and dynamics. 1998;21(1):19-28.

35.   Sabatini AM. Quaternion-based extended Kalman filter for determining orientation by inertial
and magnetic sensing. IEEE transactions on Biomedical Engineering. 2006;53(7):1346-56.

36.   Madgwick S. An efficient orientation filter for inertial and inertial/magnetic sensor arrays. Report
x-io and University of Bristol (UK). 2010;25:113-8.

37.   McGinnis RS, Cain SM, Tao S, Whiteside D, Goulet GC, Gardner EC, et al. Accuracy of femur
angles estimated by IMUs during clinical procedures used to diagnose femoroacetabular impingement.
IEEE Transactions on Biomedical Engineering. 2015;62(6):1503-13.

38.   McGinnis RS, Cain SM, Davidson SP, Vitali RV, McLean SG, Perkins N, editors. Validation of
complementary filter based IMU data fusion for tracking torso angle and rifle orientation. ASME
International Mechanical Engineering Congress and Exposition; 2014: American Society of Mechanical
Engineers.

39.   Coley B, Jolles BM, Farron A, Aminian K. Detection of the movement of the humerus during
daily activity. Medical & biological engineering & computing. 2009;47(5):467-74.

40.   Granzow RF, Schall Jr MC, Smidt MF, Chen H, Fethke NB, Huangfu R. Characterizing exposure
to physical risk factors among reforestation hand planters in the Southeastern United States. Applied
Ergonomics. 2018;66:1-8.

41.   Schall Jr MC, Fethke NB, Chen H. Working postures and physical activity among registered
nurses. Applied ergonomics. 2016;54:243-50.

42.   Chapman RM, Torchia MT, Bell J-E, Van Citters DW. Assessing shoulder biomechanics of
healthy elderly individuals during activities of daily living using inertial measurement units: high
maximum elevation is achievable but rarely used. Journal of biomechanical engineering.
2019;141(4):041001.

43.   An KN, Browne A, Korinek S, Tanaka S, Morrey B. Three-dimensional kinematics of
glenohumeral elevation. Journal of Orthopaedic Research. 1991;9(1):143-9.

44.   Seel T, Schauer T, Raisch J, editors. Joint axis and position estimation from inertial measurement
data by exploiting kinematic constraints. 2012 IEEE International Conference on Control Applications;
2012: IEEE.

45.   Vitali R, Cain S, McGinnis R, Zaferiou A, Ojeda L, Davidson S, et al. Method for estimating
three-dimensional knee rotations using two inertial measurement units: Validation with a coordinate
measurement machine. Sensors (Basel). 2017;17(9):1970.

46.   Kessel L, Watson M. The painful arc syndrome. Clinical classification as a guide to management.
The Journal of bone and joint surgery British volume. 1977;59(2):166-72.

47.   McAtamney L, Corlett EN. RULA: a survey method for the investigation of work-related upper
limb disorders. Applied ergonomics. 1993;24(2):91-9.

48.   Lugade V, Fortune E, Morrow M, Kaufman K. Validity of using tri-axial accelerometers to
measure human movement - Part I: Posture and movement detection. Med Eng Phys. 2014;36(2):169-76.

49.   Goodwin BM, Fortune E, Van Straaten MG, Morrow MM. Outcome Measures of Free-Living
Activity in Spinal Cord Injury Rehabilitation. Current Physical Medicine and Rehabilitation Reports.
2019:1-6.

50.   Sonenblum SE, Sprigle S, Lopez RA. Manual wheelchair use: bouts of mobility in everyday life.
Rehabilitation research and practice. 2012;2012.

51.   Tolerico ML, Ding D, Cooper RA, Spaeth DM. Assessing mobility characteristics and activity
levels of manual wheelchair users. Journal of rehabilitation research and development. 2007;44(4):561.

52.   Collinger JL, Boninger ML, Koontz AM, Price R, Sisto SA, Tolerico ML, et al. Shoulder
biomechanics during the push phase of wheelchair propulsion: a multisite study of persons with
paraplegia. Archives of physical medicine and rehabilitation. 2008;89(4):667-76.

53.   Rao SS, Bontrager EL, Gronley JK, Newsam CJ, Perry J. Three-dimensional kinematics of
wheelchair propulsion. IEEE Transactions on Rehabilitation Engineering. 1996;4(3):152-60.

54.   Collins SH, Adamczyk PG, Kuo AD. Dynamic arm swinging in human walking. Proceedings of
the Royal Society B: Biological Sciences. 2009;276(1673):3679-88.

55.   Fortune E, Cloud-Biebl BA, Madansingh SI, Ngufor CG, Van Straaten MG, Goodwin BM, et al.
Estimation of manual wheelchair-based activities in the free-living environment using a neural network
model with inertial body-worn sensors. Journal of electromyography and kinesiology. 2019.

56.   Schneider S, Popp WL, Brogioli M, Albisser U, Demkó L, Debecker I, et al. Reliability of
wearable-sensor-derived measures of physical activity in wheelchair-dependent spinal cord injured
patients. Frontiers in neurology. 2018;9:1039.