High throughput wastewater SARS-CoV-2 detection enables forecasting of community

infection dynamics in San Diego county

Smruthi Karthikeyan[1], Nancy Ronquillo[2], Pedro Belda-Ferre[1], Destiny Alvarado[2], Tara

Javidi[2], Christopher A. Longhurst[1,3], Rob Knight[1,4,5,6]

[1] Department of Pediatrics, University of California, San Diego, La Jolla, California, USA

[2] Department. of Electrical and Computer Engineering, University of California, San Diego,

La Jolla, CA 92093, USA

[3] Department of Biomedical Informatics, University of California, San Diego, La Jolla, CA,

USA

[4] Department of Bioengineering, University of California, San Diego, La Jolla, CA, USA

[5] Department of Computer Science & Engineering, University of California, San Diego, La

Jolla, CA, USA

[6] Center for Microbiome Innovation, University of California, San Diego, La Jolla, CA, USA

Address correspondence to:

Rob Knight

Department of Pediatrics

University of California San Diego

9500 Gilman Drive, MC 0763

La Jolla, CA 92093, USA

robknight@ucsd.edu

+1 858-246-1184

Abstract
28
Large-scale wastewater surveillance has the ability to greatly augment the tracking of

infection dynamics especially in communities where the prevalence rates far exceed the

testing capacity. However, current methods for viral detection in wastewater are severely

lacking in terms of scaling up for high throughput. In the present study, we employed an

automated magnetic-bead based concentration approach for viral detection in sewage that can

effectively be scaled up for processing 24 samples in a single 40-minute run. The method

compared favorably to conventionally used methods for viral wastewater concentrations with

higher recovery efficiencies from input sample volumes as low as 10ml and can enable the

processing of over 100 wastewater samples in a day. The sensitivity of the high-throughput

protocol was shown to detect cases as low as 2 in a hospital building with a known COVID-

19 caseload. Using the high throughput pipeline, samples from the influent stream of the

primary wastewater treatment plant of San Diego county (serving 2.3 million residents) were

processed for a period of 13 weeks. Wastewater estimates of SARS-CoV-2 viral genome

copies in raw untreated wastewater correlated strongly with clinically reported cases by the

county, and when used alongside past reported case numbers and temporal information in an

autoregressive integrated moving average (ARIMA) model enabled prediction of new

reported cases up to 3 weeks in advance. Taken together, the results show that the high-

throughput surveillance could greatly ameliorate comprehensive community prevalence

assessments by providing robust, rapid estimates.

Importance

Wastewater monitoring has a lot of potential for revealing COVID-19 outbreaks before they

happen because the virus is found in the wastewater before people have clinical symptoms.

However, application of wastewater-based surveillance has been limited by long processing

times specifically at the concentration step. Here we introduce a much faster method of

processing the samples, and show that its robustness by demonstrating direct comparisons

with existing methods and showing that we can predict cases in San Diego by a week with

excellent accuracy, and three weeks with fair accuracy, using city sewage. The automated

viral concentration method will greatly alleviate the major bottleneck in wastewater

processing by reducing the turnaround time during epidemics.

Main

Wastewater-based epidemiology (WBE) can facilitate detailed mapping of the extent

and spread of SARS-CoV-2 in a community and has seen a rapid rise in recent months owing

to its cost effectiveness as well as its ability to foreshadow trends ahead of diagnostic testing

(1-4). With over 46 million cases reported globally, 9.3 million of which are from the United

States, there is an imminent need for rapid, community-level surveillance in order to identify

potential outbreak clusters ahead of diagnostic data. Previous studies have reported high

levels of correlation between viral concentration in sewage to clinically reported cases in a

community with trends appearing 2-8 days ahead in wastewater (2, 5). A major bottleneck in

large scale wastewater surveillance is the lack of robust, high throughput viral concentration

methodology. Conventional techniques for viral concentration from wastewater typically

employ laborious or time-consuming processes, namely polyethylene glycol (PEG) based

precipitation, direct filtration or ultra-filtration methods that severely limit throughput (6). In

the present study, we employed an affinity-capture magnetic hydrogel particle (Nanotrap) -

based viral concentration method which was incorporated on the KingFisher Flex liquid-

handling robot platform robots (Thermo Fisher Scientific, USA), using a 24-plex head to

process 24 samples at once in a 40 min run. RNA is then extracted on the same Kingfisher

system for rapid sample processing. Reverse transcription-quantitative polymerase chain

reaction (RT-qPCR) targeting N1, N2, E-gene targets was used for detection and

quantification of SARS-CoV-2 RNA. Detection of all 3 genes in a sample and its replicate (at

Cq values <39) was considered positive. All steps from concentration to RT-qPCR plating

were carried hands-free and carried out by liquid handlining robots to minimize human error.

Using the above pipeline, 96 raw sewage samples were processed in a period of 4.5 hours

(concentration to RT-qPCR detection/quantification) effectively reducing the processing time

by at least 20-fold. The sensitivity of detection of SARS-CoV-2 viral RNA in wastewater by

the high-throughput pipeline (i.e. to determine if individual buildings yield sufficient

wastewater signal for high-resolution spatial studies) was established by routinely monitoring

the SARS-CoV-2 signatures in the wastewater of a San Diego hospital building housing

active COVID-19 patients (7). This site was used as a positive control to test correlations

with caseload on a daily basis. Sewage samples were collected daily for a period of 12 weeks

during which time the hospital's case load (specific to Covid-19 patients) varied between 2-

26. SARS-CoV-2 viral gene copies correlated with the daily hospital caseload (r=0.75, Suppl.

Fig. S1) suggesting that the wastewater data could at least be used to identify the peaks.

SARS-CoV-2 viral RNA was detected in wastewater on all days sampled. Furthermore, the

high-throughput protocol has been used as a part of an on-campus wastewater surveillance

for the last few months where data from 70 autosamplers covering individual buildings are

sampled and analyzed on a daily basis. The method enabled detection of cases as low as 1 in

large buildings (*manuscript in preparation, data available on request*).

The efficiency of high throughput concentration method was compared to the two

other commonly implemented concentration methods (electronegative membrane filtration

and Polyethylene glycol, PEG-based) using nine-fold serial dilutions of heat-inactivated

SARS-CoV-2 viral particles spiked into 10 mL volumes of raw sewage which was previously

verified to be from a location with no SARS-CoV-2 prevalence and verified by RT-qPCR

(Suppl. Methods). The high-throughput protocol compared favorably to the conventionally

used protocols demonstrating its potential implications for large scale sample processing

(>100 samples/day) (Suppl. Fig. S2.A, Suppl. Fig. S3, Table S1). The average viral recovery

efficiencies were 27% (SD 8%), 15% (SD 9%) and 13% (SD 8%) respectively for the high-

throughput, PEG and HA filtration protocol (Suppl. Methods S1). The improved recovery

could also be attributed in part due to the specificity of the magnetic beads in recovering viral

particles coupled with a magnetic bead-based nucleic acid extraction protocol as well. The

protocol was optimized on the KingFisher for optimal bead-binding through homogenization

(dx.doi.org/10.17504/protocols.io.bptemnje). Furthermore, the automated protocol was

hands-free and less prone to user discrepancies than the other 2 methods which were carried

out manually.

24-hour flow weighted composites were collected each day for 3 months between

July 20th-October 21st, 2020 from the influent stream of Point Loma wastewater treatment

plant. The plant processes over 175 MGD (million gallons per day) of raw sewage and is the

primary treatment center for the greater San Diego area serving over 2.3 million residents.

SARS-CoV-2 viral RNA was detected in all of the samples processed at an average

concentration of 2,010,104 gene copies/L in the influent. Over the course of the study, the

clinically reported cases in the county increased by 29,375 (Fig. 1). Peaks in the wastewater

data were frequently followed by peaks in the clinically confirmed cases at a later date. This

suggests a correlation between wastewater and the number of new cases with the caveat of a

time delay, where the wastewater data predicts future trends in the new number of cases.

Although informative, this time-lagged correlation alone is not enough for robust predictions.

This served as the main motivation to build a predictive model for forecasting the number of

new cases per day in San Diego County. In order to model the number of new reported cases,

which correlates, not only to wastewater but other complex prevalence and spreading

dynamics, we embed useful predictors as separate time series to take advantage of any side

information that may improve our forecasting results. Here, the day of the week was tracked

for each data point in a third time series to capture any weekly trends for a total of three time

series with 88 data points each. We used a data-driven approach to train a prediction model

that utilizes prior reported cases, wastewater data and temporal correlations (embedded in the

day of the week) in order to forecast the number of new positive cases in San Diego County.

The multivariate Autoregressive Integrated Moving Average (ARIMA) model [7] was

applied to build a prediction model for the number of new positive cases. The (predicted)

number of new cases consist of lagged past values from all three series (number of new cases,

wastewater data, day of the week) and each term can be thought of as the influence of that

lagged time series on the number of new cases. 65 data points corresponding to data collected

from 07/07/2020 to 09/28/2020, were used for developing the predictive model and

forecasting estimates. The remaining 24 data points, corresponding to data collected from

09/29/2020 to 10/25/2020, were reserved for validating our forecast estimates. Fig. 2B shows

the results of the model (prediction and forecast) compared to the observed data. The Pearson

correlation coefficients and root mean squared error between the observed data and the

predicted model were r = 0.84, 0.79, 0.69, 0.47, RMSE = 57, 50, 59, 70 for the trained model,

1, 2 and 3 week advance forecast values respectively (Suppl. Table S2). Our data-driven

approach obtains forecasts successfully capturing general trends on the number of new cases

(shown here up to 3 weeks in advance), ultimately reinforcing that wastewater analysis can

be expository of previously undetected SARS-CoV-2 infections in the population which

could provide useful insight for county officials for the purpose of early public health

interventions. As with most environmental samples, there are biases and caveats associated

with interpreting data from wastewater quantitatively, there are trade-offs while attempting to

scale-up the process to enable the screening of hundreds of samples on a daily basis with a

quick turn-around time. However, our data shows that we can still capture low prevalence

cases enabling studies at high spatial resolution. Our study demonstrates that high-throughput

wastewater-based surveillance can be successfully leveraged to enable creation of a rapid,

large-scale early alert system for counties/districts and could be particularly useful in

community surveillance in the more vulnerable populations.

ACKNOWLEDGEMENTS

The authors would like to thank the plant supervisor and the lab team at the Point Loma

Wastewater Treatment plant in San Diego for providing us with samples and are grateful for

their support in this effort. We thank Dr. Jack Gilbert and the Microbiome Sample Processing

Core at UC San Diego for access to qPCR equipment. We also thank Jennifer Holland and

the UC San Diego Health analytics team for generating the operational data for analysis. The

authors would also like to thank Dr. Aaron Carlin from the Division of Infectious Diseases at

UCSD for providing us with heat-inactivated SARS-CoV-2 viral particles. This work was

supported by The University of California San Diego Return to Learn program (UCSD-RTL).

FIGURE LEGENDS

Figure 1: Tracking infection dynamics in SD county. A. Map showing the San Diego

sewer mains (depicted in purple) that feed into the influent stream at the primary WWTP at

Point Loma. Overlaid are the cumulative cases recorded from the different zip codes in the

county during the course of the study. The caseload was counted by cases per zip code from

areas draining into the WWTP. The circles are proportional to the diagnostic cases reported

from each zone and the color gradient shows the cases per 100,000 residents. **B**. Daily new

cases reported by the county of San Diego. **C**. SARS-CoV-2 viral gene copies detected per L

of raw sewage determined from N1 Cq values corrected for PMMoV concentration (Pepper

mild mottle virus). All viral concentration estimates were derived from the processing of 2

sample replicates and 2 PCR replicates for each sample.

Figure 2: A. Daily caseload and wastewater viral concentration data shown for a period of 13

weeks, where a spline smoothing is applied to each time series to demonstrate general trends.

B. Predictive model showing the predicted data (yellow) compared to the observed caseload

(blue) and the 4-week forecast (red). Data collected from 07/07/2020 to 09/28/2020 were

used as the training dataset to predict the caseload for the following weeks (up to

10/25/2020). Data (wastewater + county testing data) gathered from 09/29/2020-10/21/2020

were used for model validation. MATLAB Systems Identification toolbox was used to

estimate the model order and parameters and calculate the forecasted values.

Supplemental Data

Fig. S1: Plot showing the calculated viral gene copies/L of wastewater compared to the daily

active COVID-19 caseload.

Fig. S2: A. Viral concentration method comparison. RT-qPCR N1 Cq values for nine-fold

serial dilutions of heat-inactivated SARS-CoV-2 viral particles seeded into 10 mL volumes of

raw sewage processed using the PEG concentration protocol (blue), Magnetic-bead based,

Nanotrap protocol (purple) and electronegative membrane filtration method (gray). B,C,D.

Standard curves for N1,N2 and E gene respectively for 6 fold-serial dilution of heat-

203 inactivated SARS-CoV-2 viral particles spiked into 10ml of raw sewage and concentrated

204 using the high-throughput pipeline. Results for 3 replicates shown.

206 **Fig. S3**: Average N1 Cq values for 24 samples run with all 3 concentration methods.

208 **Fig. S4**: 1D Amplitude pictures of 2019nCOV ORF1a_ FAM

210 **Table S1**: N1 Cq values for the 24 samples concentrated with the 3 methods. SD (%) shows

211 the standard deviation of the 2 replicates per sample run.

213 **Table S2**: Observed and predicted response values for the daily number of cases in San

214 Diego county.

216 **Table S3**: A. Cycling conditions for RT-qPCR used for SARS-CoV-2 viral RNA detection

217 using the multiplex Promega protocol. B. Cycling conditions for one-step ddPCR for viral

218 quantification of the ORF1ab gene in the heat-inactivated SARS-CoV-2 viral particles used

219 in recovery experiments. C. Dilution series of the heat-inactivated SARS-CoV-2 viral

220 particles used in recovery experiments.

223 **REFERENCES**

224 1. Larsen DA, Wigginton KR. 2020. Tracking COVID-19 with wastewater. Nature
225  Biotechnology 38:1151-1153.

226 2. Peccia J, Zulli A, Brackney DE, Grubaugh ND, Kaplan EH, Casanovas-Massana A,
227  Ko AI, Malik AA, Wang D, Wang M, Warren JL, Weinberger DM, Arnold W, Omer
228  SB. 2020. Measurement of SARS-CoV-2 RNA in wastewater tracks community
229  infection dynamics. Nature Biotechnology 38:1164-1167.

3.   Wu F, Xiao A, Zhang J, Moniz K, Endo N, Armas F, Bonneau R, Brown MA,
Bushman M, Chai PR, Duvallet C, Erickson TB, Foppe K, Ghaeli N, Gu X, Hanage
WP, Huang KH, Lee WL, Matus M, McElroy KA, Nagler J, Rhode SF, Santillana M,
Tucker JA, Wuertz S, Zhao S, Thompson J, Alm EJ. 2020. SARS-CoV-2 titers in
wastewater foreshadow dynamics and clinical presentation of new COVID-19 cases.
medRxiv : the preprint server for health sciences:2020.06.15.20117747.

4.   Ahmed W, Angel N, Edson J, Bibby K, Bivins A, O'Brien JW, Choi PM, Kitajima M,
Simpson SL, Li J, Tscharke B, Verhagen R, Smith WJM, Zaugg J, Dierens L,
Hugenholtz P, Thomas KV, Mueller JF. 2020. First confirmed detection of SARS-
CoV-2 in untreated wastewater in Australia: A proof of concept for the wastewater
surveillance of COVID-19 in the community. Science of The Total Environment
728:138764.

5.   Medema G, Heijnen L, Elsinga G, Italiaander R, Brouwer A. 2020. Presence of
SARS-Coronavirus-2 RNA in Sewage and Correlation with Reported COVID-19
Prevalence in the Early Stage of the Epidemic in The Netherlands. Environmental
Science & Technology Letters 7:511-516.

6.   Ahmed W, Bertsch PM, Bivins A, Bibby K, Farkas K, Gathercole A, Haramoto E,
Gyawali P, Korajkic A, McMinn BR, Mueller JF, Simpson SL, Smith WJM,
Symonds EM, Thomas KV, Verhagen R, Kitajima M. 2020. Comparison of virus
concentration methods for the RT-qPCR-based recovery of murine hepatitis virus, a
surrogate for SARS-CoV-2 from untreated wastewater. Science of The Total
Environment 739:139960.

7.   Reeves JJ, Hollandsworth HM, Torriani FJ, Taplitz R, Abeles S, Tai-Seale M, Millen
M, Clay BJ, Longhurst CA. 2020. Rapid response to COVID-19: health informatics
support for outbreak management in an academic health system. Journal of the
American Medical Informatics Association 27:853-859.
256

A

Rate Per 100K
> 4,000
2,200
< 400

Confirmed Cases
> 3,310
2,500
1,500
800
< 24

SD sewer mains

Point Loma WWTP

Ocean Outfall

0   2   4mi

B

Reported cases

C

Viral gene copies/L