Design and evaluation of mobile monitoring campaigns for air pollution exposure

assessment in epidemiologic cohorts

Magali N. Blanco,[a] Annie Doubleday,[a] Elena Austin,[a] Julian D. Marshall,[b] Edmund Seto,[a]

Timothy Larson,[a,b] Lianne Sheppard[a,c]

[a]Department of Environmental and Occupational Health Sciences, School of Public Health,

University of Washington, Hans Rosling Center for Population Health, 3980 15th Ave NE,

Seattle, WA 98195

[b]Department of Civil & Environmental Engineering, College of Engineering, University of

Washington, 201 More Hall, Box 352700, Seattle, WA 98195

[c]Department of Biostatistics, School of Public Health, University of Washington, Hans Rosling

Center for Population Health, 3980 15th Ave NE, Seattle, WA 98195

Abstract

Mobile monitoring makes it possible to estimate the long-term trends of less commonly

measured pollutants through the collection of repeated short-term samples. While many different

mobile monitoring approaches have been taken, few studies have looked at the importance of

study design when the goal is application to epidemiologic cohort studies. Air pollution

concentrations include random variability and systematic variability, and we hypothesize that

mobile campaigns benefit from temporally balanced designs that randomly sample from all

seasons of the year, days of the week, and hours of the day. We carried out a simulation study of

fixed-site monitors to better understand the role of short-term mobile monitoring design on the

prediction of long-term air pollution exposure surfaces. Specifically, we simulated three

archetypal sampling designs using oxides of nitrogen (NO_x) monitoring data from 69 California

air quality system (AQS) sites: (1) a year-around, Balanced Design, (2) a Rush Hours Design,

and (3) a Business Hours Design. We used Monte Carlo resampling to investigate the range of

possible outcomes (i.e., the resulting annual average concentration prediction) from each design

against the "truth", the actual monitoring data. We found that the Balanced Design consistently

yielded the most accurate annual averages; Rush Hours and Business Hours Designs generally

resulted in comparatively more biased estimates and model predictions. Importantly, the superior

performance of the Balanced Design was evident when predictions were evaluated against true

concentrations but less detectable when predictions were evaluated against the measurements

from the same sampling campaign since these were themselves biased. This result is important

since mobile monitoring campaigns that use their own measurements to test the robustness of the

results may underestimate the level of bias in their results. Appropriate study design is crucial for

mobile monitoring campaigns aiming to assess accurate long-term exposure in epidemiologic

cohorts. Campaigns should aim to implement balanced designs that sample during all seasons of

the year, days of the week, and all or most hours of the day to produce generally unbiased, long-

term averages. Furthermore, differential exposure misclassification could result from unbalanced

designs, which may result in misleading health effect estimates in epidemiologic investigations.

1 Introduction

A large body of evidence links long-term exposure to air pollution to adverse health effects in humans, including mortality from cardiovascular outcomes and lung cancer.[1–6] Most such studies focus on criteria air pollutants such as $PM_{2.5}$ and NO_2, in large part to use available monitoring data to estimate exposures. While air pollution cohort studies may leverage data from exposure assessment campaigns that supplement the regulatory network data, few focus on ambient air pollution exposures that are not criteria air pollutants.[7–9]

Recently, mobile monitoring campaigns have been used to estimate long-term average air pollutant levels.[10–16] Mobile monitoring campaigns typically equip a vehicle with air monitors and collect samples while in motion (mobile sampling) or while stopped (stationary sampling). A single monitoring platform can thus be used to collect samples at many locations within a relatively short period of time, making it a time and cost-efficient sampling approach. Mobile campaigns are particularly well-suited for multi-pollutant monitoring of less frequently monitored traffic-related air pollutants that require expensive instruments or instruments that need frequent attention during the sampling period.

While many recent mobile monitoring campaigns have been leveraged to map air pollution exposures and link them to health studies, there has not been any literature on the appropriate design of a mobile monitoring campaign for application to epidemiologic cohort studies. Many mobile campaigns have been short, lasting from a few weeks to months and with few repeat visits to each location spanning one to three seasons.[12,17,18] Most campaigns have conducted sampling during weekday business or rush hours, ignoring the surrounding hours, when air pollution concentrations can be drastically different.[19,20] The design of these studies may not be adequate for long-term exposure cohort studies.

The goal of this paper is to shed light on the design of a mobile monitoring campaign for application to epidemiologic cohort studies. We carry out a set of simulation studies to better understand the role of mobile monitoring design on the prediction of long-term average surfaces. We use existing monitoring data from California to compare the primary, long-term site averages when all of the data are included to subsequent analyses utilizing subsets of the data. These data provide a unique opportunity to explore how temporal sampling strategies can influence the resulting estimated annual-average concentration. Our analysis requires having a long-term,

77 comprehensive set of measurement data, which therefore necessitates using fixed-site

78 measurements rather than mobile measurements, to shed light on an aspect of study design for

79 mobile monitoring.

2   Methods

2.1   Data

We simulate three sampling designs (see below) using hourly observations for oxides of

nitrogen (NOx) collected during 2016 from regulatory Air Quality System (AQS) sites in

California. NOx was selected since it is a spatially and temporally variable traffic pollutant with

a strong diurnal pattern,[11,21,22] and it is measured at many regulatory monitoring sites in

California, providing a large enough dataset for this analysis.[23]

We required that NOx observations meet various criteria to be included in this analysis.

First, sites needed to have readings at least 66% of the time (5,797/8,784 hourly samples; 2016

was a leap year). Second, sites needed to have sampling throughout the year, such that data

collection gaps were a maximum of 45 days long. Third, sites were required to have sampled for

at least 40% of the time during various two-week periods that were used in two of our

"common" designs (described below). This sample size ensured that we could sample during

these periods without replacement. Fourth, sites were required to have positive readings (> 0

ppb) at least 60% of the time, thus ensuring that sites had sufficient variability in their

concentrations and allowing us to model annual averages on the natural log scale. Finally, sites

in rural and industrial settings (as determined by the US EPA)[24] were excluded.

2.2   Sampling Designs

We conducted simulation studies to characterize the properties of three sampling designs

(Table 1, Supplementary Information [SI] Figure S1). Each design has a long- and a short-term

sampling approach. Long-term approaches use all of the data that meet each design's definition

to estimate site annual averages and are analogous to traditional, fixed-site sampling approaches

where sampling at a given location occurs over an extended period of time. Short-term

approaches only collect 28 samples per site and are analogous to mobile monitoring campaigns

that collect a few repeat samples per site. (The cut-off of 28 samples reflects our preliminary

analyses showing that 28 hourly NOx samples are sufficient to estimate a site's annual average

within about 25% error or less [SI Figure S2].) Each design has multiple versions where samples

are collected at slightly different times. The various design versions are intended to reflect the

bias produced if only certain times are included in the measurements. We simulated each short-

term sampling approach 30 times (Monte Carlo resampling), and hereafter refer to each of these

simulations as a "campaign" since each represents a potential mobile monitoring study.

Table 1. Simulated sampling designs used to estimate site annual averages.[1]

Design	Sampling Approach and Number of Samples[2]	Sampling Seasons	Sampling Days	Sampling Hours
Year-Around "Balanced" Design	Long-term (Max 8,784 (V1), 7,320 (V2), or 4,392 (V3) hourly samples per site x 1 campaign simulation)	Winter, spring, summer, fall	Mon – Sun	<u>V1</u> (All Hours) <u>V2</u> (Most Hours): 5 AM – 12 AM <u>V3 (Truncated Hours)</u>: 6-9 AM, 1-5 PM, 8-10 PM
	Short-term (28 hourly samples per site x 30 campaign simulations)	7 samples per season	5/7 weekday samples; 2/7 weekend samples	Random hours according to V1, V2, or V3
Two-Season Weekday "Rush Hours" Design[4]	Long-term (Max 160 hourly samples per site x 1campaign	<u>V4-5:</u> winter & summer (2-wk period per season)	Mon – Fri	7-10 AM, 3-6 PM

	simulation)	V6-7: spring & fall (2-wk period per season)		
	Short-term (28 hourly samples per site x 30 campaign simulations)	14 samples per season		Random Rush Hours according to V4-5 or V6-7
Two-Season Weekday "Business Hours" Design[4]	Long-term (Max 180 hourly samples per site x 1 campaign simulation)	V4-5: winter & summer (2-wk period per season) V6-7: spring & fall (2-wk period per season)	Mon – Fri	9 AM – 5 PM
	Short-term (28 hourly samples per site x 30 campaign simulations)	14 samples per season		Random Business Hours according to V4-5 or V6-7

[1] There are three archetypal sampling designs, each with long- and short-term sampling

approaches and multiple versions. Long-term approaches are analogous to traditional, fixed-site

sampling, while short-term approaches are analogous to mobile monitoring campaigns. Short

names for the sampling design appear in quotes.

[2] Long-term approaches have 1 campaign simulation (each includes all of the available data that

meet that design's criteria), while short-term approaches have 30 campaign simulations (each

with 28 samples). Maximum hourly samples per site varied because some sites had missing

readings. Year 2016 was a leap year.

[4] See SI Table S1 for each version's exact sampling periods

The Year-Around "Balanced" Design represents an "ideal" sampling scheme: sampling is

conducted during all seasons, days of the week, and all or most hours of the day. Version 1

collects samples during all hours of the day. Versions 2-3 reduce the sampling hours to reflect

the logistical constraints of executing an extensive campaign: samples occur during most hours

of the day (5 AM – 12 AM only; "Version 2") or during 6-9 AM, 1-5 PM and 8-10 PM

("Version 3"). Estimates from the long-term Balanced Design Version 1 are analogous to what

might be collected from a traditional, year-around, fixed-site sampling scheme. For simplicity,

we interchangeably refer to these as the "true" estimates or the "gold standard" hereafter, though

we acknowledge that some error exists (e.g., due to missing hours or instrument accuracy).

The Two-Season Weekday "Rush Hours" and "Business Hours" Designs reflect common

designs in the literature. Samples are collected either during summer and winter (Versions 4-5)

or spring and fall (Versions 6-7). Sampling for each version occurs on weekdays during a two-

week period each relevant season (See SI S1 for each version's exact sampling periods).

Sampling is restricted to the hours of 7-10 AM and 3-6 PM (Rush Hours Design) or 9 AM – 5

PM (Business Hours Design). The short-term approach collects 14 random samples during each

season.

2.3 Prediction Models

We estimated site annual averages from the data collected during each campaign. We

log-transformed these before using them as the outcome variable in partial least squares (PLS)

regression models, which summarized hundreds of geographic covariate predictors (e.g., land

use, road proximity, and population density; see SI Table S2 for the covariates considered) into

two PLS components (using the `plsr` function in the `pls` package in R). We evaluated the

performance of each campaign using ten-fold cross-validated (CV) predictions on the native

scale, incorporating re-estimation of the PLS components in each fold. The cross-validation

groups were randomly selected and, importantly, fixed across all campaigns to allow for

consistent model performance comparisons across design versions.

To best understand the role of design, we present results for annual average estimates,

predictions, and model performance statistics. In descriptive analyses, we compare design-

specific annual average estimates and predictions to the gold standard (long-term Balanced

Design Version 1). We compare predicted site concentrations against predictions from the gold

standard since epidemiologic air pollution studies often rely on predicted exposure, and the gold

standard prediction represents the best possible prediction of annual-average concentrations that

a study could hope to achieve. We complement this approach with model assessment evaluations

of design-specific site predictions against two different references: an assessment against the true

averages, and a traditional model assessment evaluation against the respective design-specific

annual average estimates. The traditional assessment compares the predicted exposures to the

observed site measurements from which they were derived. This allows us to document the

quantities that would normally be available from modeling the data measured from any specific

campaign. We summarize the model performance in terms of cross-validated mean squared error

(MSE)-based R^2 (R^2_{MSE}), regression-based R^2 (R^2_{reg}), and root mean squared error (RMSE).

R^2_{MSE} reflects bias as well as variation around the one-to-one line. R^2_{reg} is based on the best fit

line between the measurements and predictions, which adjusts for bias and slopes different than

one, and is defined as the squared correlation between a measurement and a prediction. See SI

Equations 1-3 for definitions.

We repeated these analyses for nitrogen dioxide (NO_2) and nitrogen monoxide (NO),

adding a two ppb constant to all of the hourly NO readings before log-transforming to eliminate

negative and zero concentration readings.

All analyses were conducted in R (v 3.6.2, using RStudio v 1.2.5033).[25]

3   Results

181   We included the 69 of 105 California AQS sites that met our data criteria (Figure 1, SI

182   Figure S3). Sites were located in both urban and suburban settings, in residential and commercial

183   areas.

3.1 Hourly Readings

Sites had on average (SD) of 8,090 (361) hourly readings, the equivalent of 337 (15) days of full sampling (See SI Table S3). Average (SD) hourly NOx concentrations were 16 (21) ppb (See SI Table S4). Sites had seasonal, daily, and hourly concentration patterns, with trends being more pronounced at some sites than others (See SI Figure S4-S6).

3.2 Annual Average Estimates

Across the 69 monitor locations, measured annual average concentrations (long-term Balanced Design Version 1), had a median (IQR) of 14 (10 - 21) ppb and ranged from 3-56 ppb. The short-term and long-term sampling approaches resulted in similar distributions of annual averages for different design versions. Figure 2 shows the long-term and a single short-term approach for each design. Overall, the long-term and short-term approach for each design version had very similar distributions. All of the Balanced Design versions resulted in only slight differences in their medians and IQRs. The Rush Hours Design versions generally resulted in slightly higher annual averages than the true averages, with some versions being more variable and having somewhat different distributions. The Business Hours Design versions resulted in annual averages that were generally lower than the true averages and less variable than the Rush Hours Design versions. See SI Table S5 for summary statistics. SI Figure S7 shows annual average estimates for all campaigns and pollutants.

211
Figure 2. Distribution of NOx annual averages (N=69 sites) from different design versions. Showing the
one campaign for each long-term approach and one example campaign for each short-term approach.

Figure 3 shows the site-specific distributions of annual averages across designs for short-
term approaches relative to the true averages for a stratified random sample of 12 sites. Sites are
stratified by whether their true mean concentration was in the low (<25th percentile), middle
(25th-75th percentile) or high (>75th percentile) concentration category. The variation of averages
across campaigns increases with concentration in all designs. Site-specific averages are similar to
the true averages for all Balanced Design versions while there were multiple sites from the
Business Hours Design versions with averages systematically lower. The Rush Hours Design
versions also had many biased averages, although the direction of the bias varied by site and
design version. SI Figure S8 shows these biases for all sites.

Figure 3. Site-specific NOx measurement biases for short-term designs (N = 30 campaigns) as compared to the true annual average at that site (long-term Balanced Design Version 1). Showing a stratified random sample of 12 sites, stratified by whether their true concentration was in the low (<25th percentile), middle (25th-75th percentile) or high (>75th percentile) concentration category and arranged within each stratum with lower concentration sites being closer to the bottom.

3.3 Model Predictions

The PLS model of the true annual average had a root mean square error (RMSE) of 7.2 ppb and a mean square error-based coefficient of determination (R^2_{MSE}) of 0.46.

We compared PLS model predictions from each short-term design to the gold standard model predictions. SI Figure S9 shows the relative standard deviations of predictions by design version, with 1 indicating that design predictions have the same standard deviation as the gold

standard model predictions. Overall, the Balanced Design predictions have similar variability to

those of the gold standard (range: 0.87-1.28), the Rush Hours Design predictions are more

variable (range: 0.90-1.74), and the Business Hours Design predictions are mixed: some less and

some more variable (range: 0.73-1.54). Figure 4 displays these comparisons as scatterplots and

best fit lines. The scatterplots show that there are a few sites, some of which have high leverage,

that have variable predictions in all designs. From the best fit lines, we observe that all short-

term Balanced Design versions resulted in the most accurate predictions on average, as indicated

by their overlapping general trends along the one-to-one line. The Rush Hours Design versions

were more likely to have a positive general trend, while the Business Hours Design versions

were more likely to have a negative general trend, indicating, for example, that higher

concentrations were more likely to be over- or under-estimated, respectively. However, there

was heterogeneity in this overall pattern across the Rush and Business Hours Design versions.

Furthermore, there was additional heterogeneity across individual campaigns. The SI contains

comparable figures comparing design predictions to the gold standard and additional figures for

NO and NO_2 (SI Figures S10-S13).

Figure 4. Scatterplots and best fit lines of cross-validated short-term predictions for 30 campaigns vs the
gold standard predictions for NOx. Thin transparent lines are individual campaigns, colored by design
version; thicker lines are the overall version trend. (One prediction is excluded for clarity from the Rush
Hours Version 4 scatterplot at x=24 ppb, y=109 ppb [site 60731016] but included in the line plots.)

Figure 5 shows site-specific comparisons of predictions across 30 short-term campaigns

relative to the gold standard predictions for a stratified random sample of 12 sites in order to

characterize relative bias (see SI Figure S14 for all sites). Overall, the short-term Balanced

Design predictions had a median (IQR) bias of 0.2 (-1 – 1.4) ppb relative to the gold standard

predictions (see SI Table S7 for details). All Balanced Design predictions were very similar to

the gold standard predictions, though some sites frequently had larger biases. The Rush Hours

and Business Hours Design versions were more likely to consistently produce biased site

predictions, with a median (IQR) bias of 1.2 (-1.2 – 4) ppb and -3.8 (-6.6 – -1.4) ppb,

respectively. While the Rush Hours Design versions generally resulted in higher predictions

across sites (with some inconsistency across versions for a few sites), the Business Hours Design

versions resulted in predictions that were both lower and higher than the gold standard

predictions across sites. There were also a few sites that tended to have more biased and/or more

variable predictions relative to the gold standard across all designs. We observed similar patterns

when looking at estimate (rather than prediction) biases (See Figure 3, SI Figure S8).

Figure 5. Site-specific NOx prediction biases for short-term designs (N = 30 campaigns) as compared to the gold standard predictions (long-term Balanced Design Version 1). Showing a stratified random sample of 12 sites, stratified by whether true concentrations were in the low (Conc < 0.25), middle (0.25 ≤ Conc ≤ 0.75) or high (Conc > 0.75) concentration quantile and arranged within each stratum with lower concentration sites closer to the bottom.

3.4 Model Assessment

Figure 6 shows the out-of-sample prediction performances relative to the observations from the true averages (left column) and the specific design (right column), for both the long-term and short-term approaches. The boxplots quantify the distribution of performance statistics across all 30 short-term campaigns while the squares show the performance for the long-term approach of the same design version. When assessed against the true averages, all the Balanced Design versions generally perform better than either the Rush Hours or Business Hours Design versions with higher CV R^2_{MSE} and CV R^2_{reg}, and lower CV RMSE estimates. This is particularly apparent for the long-term approach. Furthermore, within design the performance for the long-term approach is better than the majority of the short-term campaigns. There is considerable heterogeneity in performance across the Rush Hours and Business Hours Design versions. In contrast, when assessed against observations from the same design, as would typically be done in practice, the role of sampling design on prediction performance is not as evident. The superior performance of the Balanced Design is not as apparent, and some of the Rush Hours and Business Hours Design versions appear to perform better. There are also a few campaigns that show poor performance, even under the Balanced Design. SI Figure S15-S16 show similar results for NO_2 and NO, with NO showing more variability and some lower performing statistics.

Figure 6. Model performances (MSE-based R2, Regression-based R2, and RMSE), as determined by each campaign's cross-validated predictions relative to: a) the true averages (long-term Balanced Version 1), and b) its respective campaign averages. Boxplots are for short-term approaches (30 campaigns), while squares are for long-term approaches (1 campaign).

3.5   NO and NO$_2$

310   We found similar results for NO and NO$_2$ (See the SI).

4   Discussion

In this paper we have used existing regulatory monitoring data to deepen our

understanding of the importance of mobile monitoring study design for application to

epidemiologic cohort studies. Others have shown that short-term data can be used to estimate

long-term averages.[11,12] What has been missing from the literature until now, however, is the

impact of mobile monitoring study design on the accuracy and precision of long-term exposure

estimates and model predictions, particularly when the goal is to produce predictions for an

epidemiologic study. Our results indicate that for designs with a sufficient number of short-term

samples (about 28 or more), the design rather than the sampling approach (short- vs long-term)

has the largest impact on the estimated long-term averages. We focus the rest of this discussion

on the short-term approaches for each design, which resemble mobile monitoring, though the

long-term approaches produced similar results.

In terms of specific design, we found that all of the Balanced Design versions resulted in

similar annual averages as the true averages (long-term Balanced Version 1), while the Rush

Hours and Business Hours Design versions were more likely to result in more biased and more

or less variable annual average estimates. Specifically, the Rush Hours Design was more likely

to overestimate, while the Business Hours Design was more likely to underestimate site

averages. This result was likely because the Balanced Design captured much of NOx's temporal

variability by allowing for samples to be collected during each season, day of the week, and all

or most times of the day, all periods during which meteorology and traffic activity patterns

impact air pollution concentrations (SI Figure S4-S6). The Rush Hours Design, on the other

hand, was restricted to two sampling seasons and was more likely to sample during high

concentration times of day and days of the week. The Business Hours Design had similar

limitations though it was more likely to sample during low concentration times.

We found a similar pattern with the predictions: similar predictions across all Balanced

Design versions, while most of versions in the Rush Hours tended to overpredict and those in the

Business Hours tended to underpredict. However, this varied by design version, suggesting that

the particular four weeks of sampling are an important source of heterogeneity in the results. The

predictions were more variable for all Rush Hours Design versions and one Business Hours

Design version (SI Figure S9). One Business Hours Design version was less variable, while two

versions were about the same relative to the gold standard predictions.

The similarity in annual averages and predictions across all of the Balanced Design

versions suggests that campaigns with slightly reduced sampling hours (for example, due to

logistical constraints) should to a large degree still produce unbiased annual averages at most

sites. On the other hand, campaigns that follow more temporally restricted sampling designs such

as the Rush Hours and Business Hours Designs may produce systematically biased results, with

the degree and direction of error being heavily impacted by the sampling window that happens to

be selected.

At the site level, we saw that while any individual study campaign had the potential to

produce biased estimates and predictions, the Rush Hours and Business Hours Designs were

more likely to do so than the Balanced Design. The direction and magnitude of the bias varied by

site and depended upon the sampling design and the typical seasonal, day of week, and time of

day patterns of pollution at that site. This suggests that a simple correction factor (e.g., the ratio

of the true annual average concentration relative to the resulting concentration from a given

design) is unlikely to appropriately adjust for bias at the site level. Given that higher

concentration sites were more likely to have greater degrees of bias and variation (Figure 4 –

Figure 5), non-balanced designs may misrepresent some sites more than others and lead to

differential exposure misclassification in epidemiologic studies. Thus, while non-balanced

design may be appropriate for non-epidemiologic purposes including characterizing the spatial

impact of traffic related air pollutants during peak hours for urban planning and policy purposes,

these could be misleading in epidemiologic applications.

In this study we were able to evaluate prediction model performance against the true

annual average exposure as well as against the observations typically available for model

performance assessment. Performance assessment against the true averages indicates that the

Balanced Design is clearly the best, and that there is little degradation in performance across

design versions. This means that it is possible to design high quality mobile monitoring studies

that accommodate some measure of logistical feasibility, for example, by not requiring sampling

in the middle of the night. In contrast, the performance of the Rush Hours and Business Hours

Designs is comparatively worse, indicating that the logistically appealing approach that samples

only four weeks during two seasons, during daytime hours, and only during weekdays is

inadequate for providing high quality estimates of annual averages. Further, the performance of

these designs varies considerably and unpredictably depending upon the specific pair of two-

week periods that were selected for sampling. Additionally, comparison of the two R^2 estimates

(R^2_{MSE} and R^2_{reg}) indicates that not all of their poor performance is due to the inability to predict

the same value as the truth (R^2_{MSE}), but due to systematic bias in the design.

Further, it is notable that the standard approach to model assessment, comparing model

predictions to observations collected during the sampling campaign, doesn't clearly reveal the

superior performance of the Balanced Design or the inherent flaws of the Rush Hours and

Business Hours Designs. In fact, some of the Rush Hours and Business Hours Design versions

perform better than the Balanced Design when evaluated against the campaign's observations.

This is because the evaluation doesn't take into account that the observations are biased because

of the sampling design.

It is notable that the performance of our short-term campaigns was fairly consistent with,

though generally slightly worse than, the performance observed in the long-term campaign for

each design version (Figure 6). However, occasionally there was an "unlucky" short-term

campaign with meaningfully poorer performance than the other campaigns of the same design.

This is true even for the Balanced Design versions where 1-2 of the 30 campaigns (~3-6%) had

notably worse performance as quantified by R^2. It may be possible that this result is driven by a

few high-leverage outlier sites that impact the prediction model performance. In practice, mobile

monitoring study investigators are likely to investigate high-leverage sites and address their

influence in their prediction modeling.

Our study focused on short-term campaigns with 28 repeat samples per site. We did not

consider campaigns with fewer or more visits. As evident in SI Figure S2, the percent error in

estimating the annual average from fewer than 25 visits skyrockets, suggesting that site estimates

will be considerably noisier in mobile campaigns with few repeat visits, regardless of the study

design. Prediction model performance is thus likely to decrease as the number of visits per site

decrease. Logistically, it is also difficult to achieve balance in sampling over time across season,

day of week, and time of day with fewer than 28 samples per site. Furthermore, we note that this

study focused on a few generalizable, common designs in the literature, though many other

approaches have been taken. We expect that the variety of mobile campaign designs that have

been implemented will all produce slightly different results.

In putting these results in context, it is important to recognize that in this simulation study

we are using existing regulatory monitoring data that has been through extensive quality

assurance and quality control processes to approximate the data that might be collected by

mobile monitoring campaigns. For instance, we used hourly averages to approximate much

shorter-term sampling durations (e.g., a few minutes or less) that would be collected during a

mobile campaign. Shorter duration sampling will affect the noise in the data, to an amount that

depends on the environment (e.g., temporal patterns in the concentrations of the pollutant being

measured) and the instruments. (For comparison, however, our additional evaluations of minute-

level data suggest that the decrease in percent error in going from two-minute to hour-long

samples is at most a few percent.) Further, our study took place throughout California, a large,

geographically diverse area with varying climate profiles.[26] This may explain the moderate

model performance of the gold standard campaign. While such a large sampling domain would

be challenging for a real-world mobile monitoring campaign, the overall conclusions of this

study are likely generalizable given that traffic-related air pollution concentrations in generally

exhibit temporal patterns that vary by location. While we observed moderate model

performances, campaigns with smaller, less spatially heterogenous study areas may see higher

performances.

There are several other differences between our study and a typical mobile monitoring

study. By definition, mobile monitoring campaigns collect non-stationary (mobile)

measurements, which are subject to jostling inherent with on-road sampling, even if some of the

sampling occurs while the vehicle is stationary. Further, mobile samples may be less precise than

what we observed from fixed, regulatory monitoring sites due to differences in instrumentation,

instrument quality, and maintenance. Mobile sampling platforms are more likely to be

immediately near another vehicle (e.g., in a traffic queue while stopped at a traffic signal) than a

fixed-site monitor. Another distinction is that while we sampled measurements within sites at

random, mobile campaigns typically sample from sites along a fixed route or in a designated

area. This induces some spatial correlation in the mobile monitoring results that is not part of our

simulations. Furthermore, we did not consider the importance of the distribution of sampling

locations in this study, which is particularly relevant when the exposure assessment goal is an

epidemiologic application. Selecting sites that are representative of the target cohort's residence

locations will ensure the spatial compatibility assumption is met, which is an important way to

reduce the role of exposure measurement error in epidemiologic inference.[27] This consideration

is especially relevant for mobile monitoring near major sources (e.g., airports, marine activity,

and industry),[11,12,28–34] which may or may not represent a study cohort of interest.

Our evaluation focused on NOx, NO, and NO_2, which are quickly and moderately

decaying air pollutants (concentrations reach background levels approximately 400-600 m from

roadway sources).[21] Campaigns that measure these pollutants may be more susceptible to

sampling design than campaigns that measure less spatially- and/or temporally-variable

pollutants such as $PM_{2.5}$.[21] We selected NOx, NO, and NO_2 because these are often measured in

short-term campaigns, and data for these pollutants are more widely available. Non-criteria

pollutants, for example ultrafine particulates (UFP), however, have also received increasing

attention in recent years given their emerging link to adverse health effects.[7,35–37] Still, high-

quality information about their spatial distribution is essentially absent, and most studies have

implemented short-term mobile sampling approaches[34] that may not be temporally balanced and

potentially be misleading.

An important next step in this work is to understand whether the differences in exposure

estimates that we observed across study designs have a meaningful impact on epidemiologic

inferences. This is of particular interest considering that year-around, balanced designs are

resource-intensive and rare, while shorter, more convenient campaigns are more common in the

literature. More research is needed to better understand how and whether unbalanced mobile

monitoring campaigns may contribute high quality exposure assessments for epidemiology.

Regardless of design, we expect that the predictions from all of the campaigns will result in both

classical-like and Berkson-like error.[27,38–40] Specifically, the predictions capture only part of the

true long-term exposure (Berkson-like error), while the parameters in the prediction model are

inherently noisy (classical-like error). However, these measurement error methods have not to

date considered exposure assessment study design, beyond considering the importance of spatial

compatibility, i.e., that distribution of monitoring locations is the same as the distribution of

participant locations. Our work suggests that deeper understanding of the role of exposure

assessment design on epidemiologic inference is an important area of research.

4.1 Conclusions and Recommendations for Mobile Monitoring Campaigns
464

Mobile monitoring study design should be an important consideration for campaigns

aiming to assess long-term exposure in an epidemiologic cohort. Given the temporal trends in air

pollution, campaigns should implement balanced designs that sample during all seasons of the

year, days of the week, and hours of the day in order to produce unbiased long-term averages.

Nonetheless, restricting the sampling hours in balanced designs, for example due to logistical

considerations, will still generally produce unbiased estimates at most sites. On the other hand,

unbalanced sampling designs like those often seen in the literature are more likely to produce

biased long-term estimates, with some sites being more biased than others. And while

predictions from these restricted designs may at times perform similarly to balanced designs (or,

more problematically, may erroneously *appear* to perform similarly when evaluated against

measurements which are themselves biased samples), this performance may strongly depend on

the exact sampling period chosen and may thus be difficult or impossible to anticipate prior to

conducting a new sampling campaign. Furthermore, the differential exposure misclassification

that may result from these designs may be problematic in epidemiologic investigations. Finally,

studies that implement unbalanced sampling designs may have hidden exposure misclassification

given that both the observations and model predictions may be systematically incorrect. By

implementing a balanced sampling design, campaigns can thus increase their likelihood of

capturing accurate long-term exposure averages.

5 Funding
485

This work was funded by the Adult Changes in Thought – Air Pollution (ACT-AP) Study

(National Institute of Environmental Health Sciences [NIEHS], National Institute on Aging

[NIA], R01ES026187), and BEBTEH: Biostatistics, Epidemiologic & Bioinformatic Training in

Environmental Health (NIEHS, T32ES015459).

Research described in this article was conducted under contract to the Health Effects

Institute (HEI), an organization jointly funded by the United States Environmental Protection

Agency (EPA) (Assistance Award No. CR-83998101) and certain motor vehicle and engine

manufacturers. The contents of this article do not necessarily reflect the views of HEI, or its

sponsors, nor do they necessarily reflect the views and policies of the EPA or motor vehicle and

engine manufacturers.

6 References

1. Hoek, G. *et al.* Long-term air pollution exposure and cardio- respiratory mortality: a review. *Environ. Health* **12**, 43 (2013).

2. Kampa, M. & Castanas, E. Human health effects of air pollution. *Environ. Pollut.* **151**, 362–367 (2007).

3. Rückerl, R., Schneider, A., Breitner, S., Cyrys, J. & Peters, A. Health effects of particulate air pollution: a review of epidemiological evidence. *Inhal. Toxicol.* **23**, 555–592 (2011).

4. Schwartz, J. Air pollution and daily mortality: a review and meta analysis. *Environ. Res.* **64**, 36–52 (1994).

5. Chen, H., Goldberg, M. & Villeneuve, P. A systematic review of the relation between long-term exposure to ambient air pollution and chronic diseases. *Rev. Environ. Health* **23**, 243–298 (2008).

6. Pope, C. A., Dockery, D. W. & Schwartz, J. Review of epidemiological evidence of health effects of particulate air pollution. *Inhal. Toxicol.* **7**, 1–18 (1995).

7. Weichenthal, S. *et al.* Within-city Spatial Variations in Ambient Ultrafine Particle Concentrations and Incident Brain Tumors in Adults. *Epidemiology* **31**, (2020).

8. Weichenthal, S. *et al.* Long-term exposure to ambient ultrafine particles and respiratory disease incidence in in Toronto, Canada: a cohort study. *Environ. Health* **16**, 64 (2017).

9. Downward, G. S. *et al.* Long-term exposure to ultrafine particles and incidence of cardiovascular and cerebrovascular disease in a prospective study of a Dutch cohort. *Environ. Health Perspect.* **126**, 127007 (2018).

10. Hankey, S. & Marshall, J. D. Land Use Regression Models of On-Road Particulate Air

Pollution (Particle Number, Black Carbon, PM2.5, Particle Size) Using Mobile Monitoring.

Environ. Sci. Technol. **49**, 9194–9202 (2015).

11. Apte, J. S. *et al.* High-Resolution Air Pollution Mapping with Google Street View Cars:

Exploiting Big Data. *Environ. Sci. Technol.* **51**, 6999–7008 (2017).

12. Hatzopoulou, M. *et al.* Robustness of Land-Use Regression Models Developed from Mobile

Air Pollutant Measurements. *Environ. Sci. Technol.* **51**, 3938–3947 (2017).

13. Patton, A. P. *et al.* Spatial and temporal differences in traffic-related air pollution in three

urban neighborhoods near an interstate highway. *Atmos. Environ.* (2014)

doi:10.1016/j.atmosenv.2014.09.072.

14. Van den Bossche, J. *et al.* Mobile monitoring for mapping spatial variation in urban air

quality: Development and validation of a methodology based on an extensive dataset. *Atmos.*

Environ. (2015) doi:10.1016/j.atmosenv.2015.01.017.

15. Kerckhoffs, J. *et al.* Comparison of ultrafine particle and black carbon concentration

predictions from a mobile and short-term stationary land-use regression model. *Environ. Sci.*

Technol. **50**, 12894–12902 (2016).

16. Xie, X. *et al.* A Review of Urban Air Pollution Monitoring and Exposure Assessment

Methods. *ISPRS International Journal of Geo-Information* vol. 6 (2017).

17. Weichenthal, S. *et al.* A land use regression model for ambient ultrafine particles in

Montreal, Canada: A comparison of linear regression and a machine learning approach.

Environ. Res. **146**, 65–72 (2016).

18. Minet, L., Gehr, R. & Hatzopoulou, M. Capturing the sensitivity of land-use regression

models to short-term mobile monitoring campaigns using air pollution micro-sensors.

Environ. Pollut. **230**, 280–290 (2017).

19. Batterman, S., Cook, R. & Justin, T. Temporal variation of traffic on highways and the

development of accurate temporal allocation factors for air pollution analyses. *Atmos.*

Environ. **107**, 351–363 (2015).

20. Saha, P. K. *et al.* Quantifying high-resolution spatial variations and local source impacts of

urban ultrafine particle concentrations. *Sci. Total Environ.* **655**, 473–481 (2019).

21. Karner, A. A., Eisinger, D. S. & Niemeier, D. A. Near-roadway air quality: Synthesizing the

findings from real-world data. *Environ. Sci. Technol.* **44**, 5334–5344 (2010).

22. Riley, E. A. *et al.* Multi-pollutant mobile platform measurements of air pollutants adjacent to

a major roadway. *Atmos. Environ.* **98**, 492–499 (2014).

23. US EPA. Air Quality System (AQS). *US Environmental Protection Agency*

https://www.epa.gov/aqs (2019).

24. US EPA. AirData Pre-Generated Data Files. *US Environmental Protection Agency*

https://aqs.epa.gov/aqsweb/airdata/download_files.html (2019).

25. R Core Team. R: A Language and Environment for Statistical Computing. *R Foundation for*

Statistical Computing https://www.r-project.org (2019).

26. Li, L. *et al.* Ensemble-based deep learning for estimating PM2.5 over California with

multisource big data including wildfire smoke. *Environ. Int.* **145**, 106143 (2020).

27. Szpiro, A. A. & Paciorek, C. J. Measurement error in two-stage analyses, with application to

air pollution epidemiology. *Environmetrics* (2013) doi:10.1002/env.2233.

28. Dodson, R. E., Houseman, E. A., Morin, B. & Levy, J. I. An analysis of continuous black

carbon concentrations in proximity to an airport and major roadways. *Atmos. Environ.* **43**,

3764–3773 (2009).

29. Riley, E. A. *et al.* Correlations between short-term mobile monitoring and long-term passive

sampler measurements of traffic-related air pollution. *Atmos. Environ.* **132**, (2016).

30. Austin, E. *et al. Mobile ObserVations of Ultrafine Particles: The MOV-UP study report.*

(2019).

31. Hudda, N., Gould, T., Hartin, K., Larson, T. V. & Fruin, S. A. Emissions from an

international airport increase particle number concentrations 4-fold at 10 km downwind.

Environ. Sci. Technol. **48**, 6628–6635 (2014).

32. Lack, D. A. & Corbett, J. J. Black carbon from ships: a review of the effects of ship speed,

fuel quality and exhaust gas scrubbing. *Atmospheric Chem. Phys.* **12**, (2012).

33. Kozawa, K. H., Fruin, S. A. & Winer, A. M. Near-road air pollution impacts of goods

movement in communities adjacent to the Ports of Los Angeles and Long Beach. *Atmos.*

Environ. **43**, 2960–2970 (2009).

34. Riffault, V. *et al.* Fine and Ultrafine Particles in the Vicinity of Industrial Activities: A

Review. *Crit. Rev. Environ. Sci. Technol.* **45**, 2305–2356 (2015).

35. Kilian, J. & Kitazawa, M. The emerging risk of exposure to air pollution on cognitive decline

and Alzheimer ' s disease e Evidence from epidemiological and animal studies. *Biomed. J.*

41, 141–162 (2018).

36. Lane, K. J. *et al.* Association of modeled long-term personal exposure to ultrafine particles

with inflammatory and coagulation biomarkers. *Environ. Int.* **92–93**, 173–182 (2016).

37. US EPA. Integrated science assessment (ISA) for particulate matter (final report, Dec 2019).

US Environ. Prot. Agency (2019).

38. Gryparis, A., Paciorek, C. J., Zeka, A., Schwartz, J. & Coull, B. A. Measurement error

caused by spatial misalignment in environmental epidemiology. *Biostatistics* **10**, 258–274

(2009).

39. Szpiro, A. A., Sheppard, L. & Lumley, T. Efficient measurement error correction with

spatially misaligned data. *Biostatistics* **12**, 610–623 (2011).

40. Sheppard, L. *et al.* Confounding and exposure measurement error in air pollution

epidemiology. *Air Qual. Atmosphere Health* **5**, 203–216 (2012).