Simplified point-of-care full SARS-CoV-2 genome sequencing using nanopore technology

Anton Pembaur[1],*, Erwan Sallard[2],*, Patrick Philipp Weil[1], Jennifer Ortelt[3], Parviz Ahmad-Nejad[3], Jan

Postberg[1],†

*both authors contributed equally

†corresponding author

[1]Clinical Molecular Genetics and Epigenetics, Faculty of Health, Centre for Biomedical Education &

Research (ZBAF), Witten/Herdecke University, Alfred-Herrhausen-Str. 50, 58448 Witten, Germany

[2]Institute of Virology and Microbiology, Faculty of Health, Centre for Biomedical Education &

Research (ZBAF), Witten/Herdecke University, Stockumer Str. 10, 58453 Witten, Germany

[3]HELIOS University Hospital Wuppertal, Institute of Medical Laboratory Diagnostics, Centre for

Clinical & Translational Research (CCTR), Witten/Herdecke University, Heusnerstr. 40, 42283

Wuppertal, Germany

E-Mail addresses:

Anton Pembaur: anton.pembaur@uni-wh.de

Erwan Sallard: erwan.sallard@uni-wh.de

Patrick Philipp Weil: patrick.weil@uni-wh.de

Jennifer Ortelt: jennifer.ortelt@helios-gesundheit.de

Parviz Ahmad-Nejad: parviz.ahmad-nejad@helios-gesundheit.de

Jan Postberg: jan.postberg@uni-wh.de

Abstract

Background: The scale of the ongoing SARS-CoV-2 pandemic warrants the urgent establishment of a

global decentralized surveillance system to recognize local outbreaks and the emergence of novel

variants-of-concern. Among available deep-sequencing technologies, nanopore-sequencing could be

an important cornerstone, since it is mobile, scalable and costs-effective. Therefore, streamlined

nanopore-sequencing protocols need to be developed and optimized for SARS-CoV-2 variants

identification.

Results: We adapted and simplified existing workflows using the 'midnight' 1,200 bp amplicon split

primer sets for PCR, which produce tiled overlapping amplicons covering almost the entire SARS-

CoV-2 genome. Subsequently, we applied Oxford Nanopore Rapid Barcoding and the portable

MinION Mk1C sequencer combined with the interARTIC bioinformatics pipeline. We tested a

simplified and less time-consuming workflow using SARS-CoV-2-positive specimens from clinical

routine and identified pre-analytical parameters, which may help to decrease sequencing failures rates.

Complete pipeline duration was approx. 7 hrs for one specimen and approx. 11 hrs for 12 multiplexed

barcoded specimens.

Conclusions: The adapted protocol contains less processing steps and can be completely conducted

within one working-day. Diagnostic CT values are principal criteria for specimen selection.

Keywords

(+)RNA genome sequencing, COVID-19 surveillance, variant-of-concern (VOC)

Background

To face the ongoing SARS-CoV-2 pandemic, a global decentralized warning system is being

established to recognize local outbreaks and the emergence of novel variants-of-concern (VOC). A

particular focus is given to the identification of VOCs with accelerated transmission rates, increased

infectivity or immune escape mutations, since these variants would warrant adaptations in containment

and vaccination strategies (Cobey, Larremore et al. 2021, Gupta 2021, Harvey, Carabelli et al. 2021,

Winger and Caspari 2021). Moreover, the search for the zoonotic origin of SARS-CoV-2 from

comparative analyses of genomic data is an ongoing issue with relevance for the early recognition of

future outbreak scenarios (Andersen, Rambaut et al. 2020, V'Kovski, Kzel et al. 2021).

Among the available deep-sequencing technologies, nanopore-sequencing could be an important

cornerstone, since it is mobile, scalable and acquisition investments are comparably low. Further,

nanopore sequencing devices do not require large-scale IT infrastructure. In the past they were already

involved actions of genome surveillance, e.g. the 2015 Ebola outbreak in Liberia, Guinea and sierra

Leone (Quick, Loman et al. 2016), and since then there has been a substantial technological progress.

However, at least for smaller hospital laboratories with lower throughput, it is desirable to develop

protocols as streamlined as possible.

Nanopore sequencing allows the sequencing of either DNA or RNA (Garalde, Snell et al. 2018), and

does not require PCR amplification. Furthermore the technique has the potential of producing very

long, continuous reads, which theoretically allows to sequence in only one read the 29.903nt long

(+)RNA genome of SARS-CoV-2 (Taiaroa, Rawlinson et al. 2020), or its deriving cDNA after reverse

transcription (Figure 1).

With the aims of facilitating implementation in routine diagnostics with lower specimens throughput

and of simplifying the workflow, we tested modifications of existing ARTIC protocols for SARS-

CoV-2 full length (+)RNA genome sequencing (Freed, Vlkova et al. 2020, Li, Wang et al. 2020,

Tyson, James et al. 2020). Furthermore, we tested the simplified and less time-consuming workflow

on confirmed SARS-CoV-2-positive specimens from clinical routine and identified pre-analytical

parameters, which may help to decrease the rate of sequencing failures.

Methods

Nucleic acids isolation

Specimens included nasopharyngeal swabs (Xebios Diagnostics), which underwent routine COVID-19

diagnostic testing. For the collection and use after routine diagnostics procedures we obtained

approval of the Witten/Herdecke University Ethics board (No. 160/2020 [For more details, see

'declarations' below.]). RNA purification was performed via magnetic beads (Seegene

NIMBUS/Tanbead). Alternatively, total RNA was purified from 250 µL liquid specimen using 750 µL

QIAzol lysis reagent (Qiagen, Cat. No. 158845) upon manufacturer's recommendations, or using silica

columns (QiaAmp Viral Mini Kit, Qiagen).

RT-PCR, quality assessments and library preparation

The 'midnight' split primer set from the ARTIC protocol was used for SARS-CoV-2 cDNA

amplification in 2 multiplex PCR reactions. To avoid overlaps during multiplex PCR, each single-tube

PCR reaction generates consecutively tiled, non-overlapping 1,200 bp amplicons. Mixed together after

PCR, both resulting complementary amplicon mixtures cover almost the entire SARS-CoV-2 genome

(Freed, Vlkova et al. 2020).

Combined reverse transcription and amplification of multiple 1,200 bp amplicons (RT-PCR) was

performed in single tube 20 µL reactions using the Luna One-Step RT-qPCR Kit (NEB; E3005). For

RT-PCR, 8 µL of purified template RNA were used for each reaction. From 100 µM primer pools, 1

µL was used in each reaction. Reverse transcription was performed at 55°C for 30 minutes, followed

by incubation at 95°C for one minute. Then 34 cycles (pool 1) or 30 cycles (pool 2) of denaturation at

95°C for 20 seconds and annealing and extension in one step at 60°C for 210 seconds were performed.

A final extension was performed at 65°C. During the implementation phase amplicon sizes and DNA

concentrations were routinely checked by agarose gels or by microvolume electrophoresis (Agilent

Bioanalyzer, Agilent DNA 12000 kit). Thereafter, amplicons from primer pools 1 and 2 were

quantified by fluorimetry (Promega Quantus) and then mixed at equal concentrations. Library

preparation was done using the Rapid Barcoding Sequencing Kit (Oxford nanopore; SQK-RBK004)

upon manufacturers recommendations.

Nanopore sequencing

Sequencing was performed on a MinION Mk1C with the options 'basecalling' and 'demultiplexing'

being enabled. As output format, FAST5 and FASTQ files were chosen. Sequencing time was set for

72 hours as default. Sequencing was stopped after reaching at least 10 megabases for each barcode.

Bioinformatics

Consensus sequences were built from the barcode-sorted, quality-filtered FAST5 and FASTQ files

containing sequencing reads, using the interARTIC pipeline. Except otherwise stated, the

'Nanopolish' algorithm was routinely used.

Installation and usage of interARTIC pipeline was done following the developers' instructions:

https://psy-fer.github.io/interARTIC/installation/. For faster analysis, all available threads were

activated in the advanced settings. The interARTIC pipeline performs read filtering, alignments and

returns a consensus FASTA file as well as coverage charts for visualization (Figure 2B-H).

Consensus FASTA files were uploaded to the Nextstrain webapp (https://clades.nextstrain.org) to

perform phylogenetic analyses (Hadfield, Megill et al. 2018).

Data availability

FASTQ files and assembled FASTA formatted consensus sequences are available

(https://t1p.de/minion-seqdata)

Results and Discussion

We defined milestones to simplify the protocol and decrease hands-on sample time and working step

numbers. 1. We tested whether specimens can be directly taken from residual diagnostic specimens

extracted from 96-deepwell-plates using magnetic beads (Seegene NIMBUS/Tanbead). For

comparison we applied RNA purification protocols using silica columns (QiaAmp Viral Mini Kit,

Qiagen) or guanidinium isothiocyanate (GITC) for RNA extraction (QIAzol lysis reagent, Qiagen). 2.

We tested whether reverse transcription can be successfully primed by SARS-CoV-2-specific primers,

which are subsequently used for multiplex 1,200 bp amplicon amplification. Purified RNA from the

different extraction protocols of milestone 1 was used for cDNA synthesis and successive multiplex

PCR with the 2 'midnight' split 1,200 bp amplicon primer pools in single tube reactions 3. We aimed

at improving the efficiency of the nanopore sequencing workflow by using the onboard Guppy

basecalling capability of the Oxford Nanopore MinION Mk1C device. Moreover, implementation of

the interARTIC interface should help to avoid command line-based bioinformatics analyses as much

as possible in order to provide a user-friendly and efficient analysis pipeline.

Protocol implementation considering differences in viral loads and influences of RNA extraction

protocols

Sequencing was performed from serially diluted specimens of purified RNA from patients' samples,

which exhibited low cycle threshold (CT) value (CT=16-18) after routine diagnostics RT-qPCR (N

gene, RdRP gene; Seegene). Using the quantitative reference sample Ch07470 for calibration we

determined that a CT=25 (respectively 16 and 18) corresponded to a SARS-CoV-2 copy number of

$1.0x\ 10^6$ (respectively $5.12x\ 10^8$ and $1.28x\ 10^8$). Routinely used dilution factors were 2^0-2^{-10} in order to

cover several CT value magnitudes and to simulate different amounts of viral loads. In terms of RNA

yield and 1,200 bp amplicon PCR performance the magnetic beads-based RNA purification protocol

outperformed slightly the GITC method as well as the column-based protocol, but we did not observe

differences in read and coverage quality between these different isolation methods (Figure S1). Since

direct sampling from 96-deepwell plates allowed us to directly exploit residual specimens, which

remained after routine RT-qPCR diagnostics, we decided to focus on magnetic beads-based RNA

purification during further protocol development. Moreover, it shortened and simplified the workflow.

After semiquantitative or quantitative RT-PCR using multiplex primer pools 1 and 2 in separate single

tube reactions for combined reverse transcription of the SARS-CoV-2 (+)RNA and amplification of

1,200 bp amplicons, band intensities exhibited strong dependence on viral loads. Moreover, after 32

PCR cycles band intensities using primer pool 1 were weaker when compared with primer pool 2

(Figure S2). We determined that 34 PCR cycles for primer pool 1 and 30 cycles for primer pool 2 were

a good compromise. Therefore, reverse transcription can be successfully primed by the 'midnight'

primers.

Surveillance of multiplex nanopore sequencing and multiple reuses of flow cells

Using the Rapid Barcoding Kit (SQK-RBK004, Oxford Nanopore) enabled us to barcode the PCR

products without purification steps and sequence them immediatley. As a standard, we used 12

barcoded libraries for multiplex sequencing on R9 flow cells. In contrast to the Oxford Nanopore

MinION Mk1B, the MinION Mk1C device features onboard guppy basecalling. In combination with

the Rapid Barcoding Kit, we exploited this opportunity for real-time surveillance of basecalling and

demultiplexing for each of the 12 multiplexed samples per run. This enabled us to recognize the exact

time point at which a reading depth of approx. 10 Mbp per barcode was achieved. The time to reach

this threshold depended heavily on the viral load (simulated by serially diluted samples). Decreased

viral loads let to a considerable decrease of passed reads (Figure 2A). A manual stop of sequencing

followed by flow cell washing (Flow Cell Wash Kit, EXP-WSH004, Oxford Nanopore) allowed us to

reuse a single flow cell for a series of 3 sequencing runs, each using 12 multiplexed barcoded libraries.

This specific scenario resulted in costs of approx. 40 USD per sample. Theoretically, the possible

number of reuses depends largely on the duration of the sequencing, which itself depends mainly on

the number of used barcodes. Further, if a MinION Mk1B is considered for this purpose, a similar

surveillance functionality could be achieved using RAMPART (https://github.com/artic-

network/rampart) on a dedicated LINUX environment.

Assembly of full SARS-CoV-2 genomes and pathogen genome data analyses

For mapping and full length SARS-CoV-2 genome assembly, we used the FASTQ files resulting from

Guppy basecalling in order to generate FASTA formatted consensus sequence files. We used the

ARTIC pipeline through a graphical user interface (interARTIC; https://github.com/Psy-

Fer/interARTIC). Once installed, this is an easy to use and relatively fast pipeline with only five

minutes hands-on time, which enables the use of the 'Nanopolish' or 'Medaka' algorithms for

simultaneous analyses of multiplexed barcoded samples. As an example, Figure 2B shows the

complete and deep coverage of the complete SARS-CoV-2 genome after the combination of pools 1

(light blue) and 2 (pink). This demonstrates that all contained 1,200 bp amplicon were specifically and

efficiently amplified during the combined RT-PCR reaction (Figure 2B).

To compare the interARTIC and Geneious Prime pipelines, we used exactly the same FASTQ file

from the same sample shown in Figure 2B (https://go.geneious.com/video/how-to-assemble-

coronavirus-genomes). Phylogenetic analyses with Nextstrain using the FASTA consensus files

obtained from the interARTIC or the Geneious Prime pipelines resulted in considerably different

phylogenetic distances in clade 20I, showing that the bioinformatics pipeline influences the result

(Figure S3). The interARTIC pipeline proved superior in terms of coverage and sequencing depth.

Notably, within the interARTIC pipeline both options, the 'Nanopolish' and 'Medaka' algorithms

performed equally well with respect to consensus sequence quality, but 'Medaka' was considerably

faster.

We observed that the consensus sequences returned by the 'Nanopolish' and 'Medaka' algorithms

contain numerous unsolved regions (for which only 'N's are indicated). Interestingly, the regions

unsolved by one algorithm were generally solved by the other, so we assumed that the two consensus

sequences could be combined to produce a 'super-consensus' with improved variant prediction value.

We developed a Python code that merges the 'Nanopolish' and 'Medaka' consensus sequences and

generates the corresponding variant calling file. As expected, the 'super-consensus' contained less

unsolved regions when compared with the 'Nanopolish' and 'Medaka' consensus sequences alone

(Figure 4B). In addition, it retained the high quality mutations, which were identified by both

algorithms, while removing most false-positives probably caused by sequencing and alignment errors

(Figure 4A). Consequently, our consensus-merging code improves the quality of variant calling and

highlights the complementarity of 'Nanopolish' and 'Medaka' for nanopore-sequencing of SARS-

CoV-2 and others. Nevertheless, this quality increase comes at the cost of information loss such as the

number of reads per variant or other metadata which were initially generated by 'Nanopolish' and

'Medaka' and are not transferred to the 'super-consensus'.

Serial input RNA dilutions or, respectively, viral load influenced the depth of sequencing (Figure 2C-

H). For the output of high-quality consensus sequences in the FASTA file format a coverage threshold

of 20 was used as default. We generally observed that this could be reached when a SARS-CoV-2 titer

of $4x\ 10^6$ was given. Viral copy numbers lower than $4x\ 10^6$ were associated with incompletely

assembled SARS-CoV-2 genomes. Thus, we provide here a convincing line of evidence that the copy

number-normalized CT values of diagnostic RT-qPCR can be used as the criterion of sequencing

success.

Single or batch high-quality consensus FASTA formatted sequences were used for phylogenetic tree

visualization and variant calling using the Nextstrain webapp (https://clades.nextstrain.org) (Hadfield,

Megill et al. 2018). In our hands, the obtained sequences could faithfully be assigned to specific clades

in the reference tree (Figure 3). Again, an influence of viral load was observed. However, despite

incomplete coverage in those cases enough informative sequence data could be obtained for

phylogenetic analyses from several low copy number samples. As a result of serial sample dilutions,

we observed deviating phylogenetic distances within the clade, wherein specimens classification

occurred (Figure 3A), which eventually could lead to incorrect clade association. The use of

specimens from diagnostic routine with viral copy numbers higher than approx. $4x\ 10^6$ apparently led

to their faithful association with different clades, which were clades 20I and 19A in the shown

example (Figure 3B). The 'Nanopolish' and 'Medaka' consensus as well as the merged super-

consensus could be reliably associated to the corresponding clade (20I in the shown example). The

'Medaka' consensus mapped at a greater distance than the 'Nanopolish' consensus, probably because

'Medaka' algorithm does not correct frameshifts, while the super-consensus had an intermediary

distance between the two other consensus (Figure 4C).

Taken together, the main achievements of an optimized workflow are: 1. Purified RNA from SARS-

CoV-2-positive patients can be directly taken from residual diagnostic specimens in 96-deepwell-

plates; 2. cDNA synthesis and successive multiplex PCR with 2 split primer pools can be performed in

single tube reactions. Since cDNA synthesis is primed by SARS-CoV-2-specific primers for 1,200 bp

amplicon amplification, there is no need for use of unspecific hexanucleotide priming. 3. Onboard

Guppy basecalling with the Oxford Nanopore MinION Mk1C device and implementation of the

interARTIC led to a further reduction of working steps and hands-on time (Figure 5). Implementation

in smaller hospital laboratories with lower specimens' throughput can be easily done at moderate

costs.

We provide a detailed protocol for all steps here, which includes the Python code (Supplementary
Information 1) and corresponding command line: dx.doi.org/10.17504/protocols.io.bwhppb5n
257
258
259 **Conclusions**
260 The adapted protocol contains less processing steps. Diagnostic CT values are the principal criteria for
261 specimen selection. After diagnostic qRT-PCR, multiplex library preparation, quality controls,
262 nanopore sequencing and the bioinformatic pipeline can be completely conducted within one working-
263 day.
264
265 **List of abbreviations**
266 (+)RNA (sense polarity [single-stranded] ribonucleic acid), RdRP (RNA-dependent RNA
267 polymerase), RT-qPCR (reverse transcription-quantitative polymerase chain reaction, SARS-CoV-2
268 (severe acute respiratory syndrome coronavirus 2)
269
Declarations
Ethics approval and consent to participate
For the collection and use of specimens from clinical routine at Helios University Hospital Wuppertal
(North Rhine-Westphalia, Western Germany) we obtained approval of the Witten/Herdecke University
Ethics board (No. 160/2020). The positive ethics vote included the use of routinely sampled and
SARS-CoV-2-confirmed specimens, which underwent COVID-19 RT-qPCR diagnostics procedures
even for cases, where informed written consent could not be asked for. When possible, we obtained
informed written consent from hospitalized patients or legal guardians. All work has been conducted
according to the principles expressed in the Declaration of Helsinki.
279
280 **Competing interests**
281 There are no conflicting interests for none of the authors, which need declaration.
282
283 **Funding**
284 The study was financed by own institutional means.
285
286 **Authors' contributions**
287 AP prepared libraries for nanopore-seq and conducted the sequencing. PAN and JO collected
288 specimens and conducted diagnostic SARS-CoV-2 qPCR. AP and PPW performed nucleic acids
289 quality controls. AP, ES and JP contributed to the bioinformatics analyses. ES developed the Python
290 code. PAN and JP designed the sudy. AP, ES, PPW and JP wrote the paper.
291

References

Andersen, K. G., A. Rambaut, W. I. Lipkin, E. C. Holmes and R. F. Garry (2020). "The proximal origin of SARS-CoV-2." Nat Med **26**(4): 450-452.

Cobey, S., D. B. Larremore, Y. H. Grad and M. Lipsitch (2021). "Concerns about SARS-CoV-2 evolution should not hold back efforts to expand vaccination." Nat Rev Immunol **21**(5): 330-335.

Freed, N. E., M. Vlkova, M. B. Faisal and O. K. Silander (2020). "Rapid and inexpensive whole-genome sequencing of SARS-CoV-2 using 1200 bp tiled amplicons and Oxford Nanopore Rapid Barcoding." Biol Methods Protoc **5**(1): bpaa014.

Garalde, D. R., E. A. Snell, D. Jachimowicz, B. Sipos, J. H. Lloyd, M. Bruce, N. Pantic, T. Admassu, P. James, A. Warland, M. Jordan, J. Ciccone, S. Serra, J. Keenan, S. Martin, L. McNeill, E. J. Wallace, L. Jayasinghe, C. Wright, J. Blasco, S. Young, D. Brocklebank, S. Juul, J. Clarke, A. J. Heron and D. J. Turner (2018). "Highly parallel direct RNA sequencing on an array of nanopores." Nat Methods **15**(3): 201-206.

Gupta, R. K. (2021). "Will SARS-CoV-2 variants of concern affect the promise of vaccines?" Nat Rev Immunol **21**(6): 340-341.

Hadfield, J., C. Megill, S. M. Bell, J. Huddleston, B. Potter, C. Callender, P. Sagulenko, T. Bedford and R. A. Neher (2018). "Nextstrain: real-time tracking of pathogen evolution." Bioinformatics **34**(23): 4121-4123.

Harvey, W. T., A. M. Carabelli, B. Jackson, R. K. Gupta, E. C. Thomson, E. M. Harrison, C. Ludden, R. Reeve, A. Rambaut, C.-G. U. Consortium, S. J. Peacock and D. L. Robertson (2021). "SARS-CoV-2 variants, spike mutations and immune escape." Nat Rev Microbiol **19**(7): 409-424.

Li, J., H. Wang, L. Mao, H. Yu, X. Yu, Z. Sun, X. Qian, S. Cheng, S. Chen, J. Chen, J. Pan, J. Shi and X. Wang (2020). "Rapid genomic characterization of SARS-CoV-2 viruses from clinical specimens using nanopore sequencing." Sci Rep **10**(1): 17492.

Quick, J., N. J. Loman, S. Duraffour, J. T. Simpson, E. Severi, L. Cowley, J. A. Bore, R. Koundouno, G. Dudas, A. Mikhail, N. Ouedraogo, B. Afrough, A. Bah, J. H. Baum, B. Becker-Ziaja, J. P. Boettcher, M. Cabeza-Cabrerizo, A. Camino-Sanchez, L. L. Carter, J. Doerrbecker, T. Enkirch, I. G. G. Dorival, N. Hetzelt, J. Hinzmann, T. Holm, L. E. Kafetzopoulou, M. Koropogui, A. Kosgey, E. Kuisma, C. H. Logue, A. Mazzarelli, S. Meisel, M. Mertens, J. Michel, D. Ngabo, K. Nitzsche, E. Pallash, L. V. Patrono, J. Portmann, J. G. Repits, N. Y. Rickett, A. Sachse, K. Singethan, I. Vitoriano, R. L. Yemanaberhan, E. G. Zekeng, R. Trina, A. Bello, A. A. Sall, O. Faye, O. Faye, N. Magassouba, C. V. Williams, V. Amburgey, L. Winona, E. Davis, J. Gerlach, F. Washington, V. Monteil, M. Jourdain, M. Bererd, A. Camara, H. Somlare, A. Camara, M. Gerard, G. Bado, B. Baillet, D. Delaune, K. Y. Nebie, A. Diarra, Y. Savane, R. B. Pallawo, G. J. Gutierrez, N. Milhano, I. Roger, C. J. Williams, F. Yattara, K. Lewandowski, J. Taylor, P. Rachwal, D. Turner, G. Pollakis, J. A. Hiscox, D. A. Matthews, M. K. O'Shea, A. M. Johnston, D. Wilson, E. Hutley, E. Smit, A. Di Caro, R. Woelfel, K. Stoecker, E. Fleischmann, M. Gabriel, S. A. Weller, L. Koivogui, B. Diallo, S. Keita, A. Rambaut, P. Formenty, S. Gunther and M. W. Carroll (2016). "Real-time, portable genome sequencing for Ebola surveillance." Nature **530**(7589): 228-232.

Taiaroa, G., D. Rawlinson, L. Featherstone, M. Pitt, L. Caly, J. Druce, D. Purcell, L. Harty, T. Tran, J. Roberts, M. Catton, D. Williamson, L. Coin and S. Duchene (2020). "Direct RNA sequencing and early evolution of SARS-CoV-2." bioRxiv: 2020.2003.2005.976167.

Tyson, J. R., P. James, D. Stoddart, N. Sparks, A. Wickenhagen, G. Hall, J. H. Choi, H. Lapointe, K. Kamelian, A. D. Smith, N. Prystajecky, I. Goodfellow, S. J. Wilson, R. Harrigan, T. P. Snutch, N. J. Loman and J. Quick (2020). "Improvements to the ARTIC multiplex PCR method for SARS-CoV-2 genome sequencing using nanopore." bioRxiv: 2020.2009.2004.283077.

V'Kovski, P., A. Kratzel, S. Steiner, H. Stalder and V. Thiel (2021). "Coronavirus biology and replication: implications for SARS-CoV-2." Nat Rev Microbiol **19**(3): 155-170.

Weil, P. P., J. Hentschel, F. Schult, A. Pembaur, B. Ghebremedhin, O. Mboma, A. Heusch, A. C. Reuter, D. Muller, S. Wirth, M. Aydin, A. C. W. Jenke and J. Postberg (2021). "Combined RT-qPCR and pyrosequencing of a Spike glycoprotein polybasic cleavage motif can uncover pediatric SARS-CoV-2 infections associated with heterogeneous presentation." Mol Cell Pediatr **8**(1): 4.

Winger, A. and T. Caspari (2021). "The Spike of Concern-The Novel Variants of SARS-CoV-2." Viruses **13**(6).

Figures and Figure legends

Figure 1. Nanopore sequencing options (2-6) compatible with diagnostic qPCR pipelines (1). The

pyrosequencing option in path (6) requires biotin-tagged primers for qPCR (Weil, Hentschel et al.

2021).

Figure 2. Surveillance using nanopore sequencing (A.), and effects of specimens dilution on the

SARS-CoV-2 genome coverage (B.), whereby viral copy numbers were $1.28x\ 10^6$ (B.); $5.12x\ 10^8$ (C.);

$2.56x\ 10^8$ (D.); $4x\ 10^6$ (E.); $2x\ 10^6$ (F.); $1x\ 10^6$ (G.); $5x\ 10^5$ (H.). In (A.) increasing barcode numbers

(X-axis) correspond to decreasing viral titers.

Figure 3. Comparison on the evolutionary distance calculation, when data from the same specimen was processed by 2 different bioinformatics pipelines. Phylogenetic tree visualization was done using the Nextstrain open-source platform for pathogen genome data analyses (Hadfield, Megill et al. 2018). We used serial dilutions of identical specimens (A.), or a selection of samples from different individuals from clinical routine (B.) for phylogenetic analyses. Below the trees a magnification of clade 20I is shown, wherein most specimens grouped (A.,B.).

Figure 4. Comparison of the consensus sequences returned by 'Nanopolish' and 'Medaka' algorithm
and the merged consensus for a nanopore sequencing run corresponding to a viral load of 1.28x10**6.

(A.) Alignment of the 'Nanopolish' and 'Medaka' consensus as well as the merged consensus on the
SARS-CoV-2 reference genome by the Nextstrain program. The merged consensus conserved all of
the high quality mutations that mapped to the known variant 20I (shown in colour or light grey), while
most non-matching mutations (in dark grey, likely sequencing errors) of the 'Nanopolish' or 'Medaka'
consensus were lost. **(B.)** Comparison of variant solving by 'Nanopolish', 'Medaka' and our code. The
multiple alignment was performed by MAFFT online tool with the three consensus sequences and the
SARS-CoV-2 reference genome (MN908947.3). Contrary to the 'Nanopolish' and 'Medaka'
consensus, the merged consensus solved the entire region and led to accurate variant calling. **(C.)**
Clade mapping and phylogenetic distances calculated by Nextstrain for the three consensus sequences.
380

SARS-CoV-2 (+)RNA whole genome nanopore sequencing

***Li, J., Wang, H., Mao, L. et al. Rapid genomic characterization of SARS-CoV-2 viruses from clinical specimens using nanopore sequencing. Sci Rep 10, 17492 (2020). https://doi.org/10.1038/s41598-020-74656-y

Figure 5. Comparison of a rapid SARS-CoV-2 whole (+)RNA genome nanopore sequencing pipeline

(Freed, Vlkova et al. 2020) with the novel simplified workflow, whose main achievements are: 1.

Purified RNA from SARS-CoV-2-positive patients can be directly taken from residual diagnostic

specimens in 96-deepwell-plates; 2. cDNA synthesis and successive multiplex PCR with 2 primer

pools can be performed in single tube reactions. Since cDNA synthesis is primed by SARS-CoV-2-

specific primers for 1,200 bp amplicon amplification, there is no need for use of unspecific

hexanucleotide priming. 3. Onboard Guppy basecalling with the Oxford Nanopore MinION Mk1C

device and implementation of the interARTIC led to a further reduction of working steps and hands-on

time.