How an election can be safely planned and conducted during a pandemic: Decision support based on a discrete event model

Nadine Weibrecht[2,❂,*], Matthias Rößler[1,❂], Štefan Emrich[1], Niki Popper[1, 2, 3]

1 dwh GmbH, dwh simulation services, Austria, Neustiftgasse 57-59, 1070 Vienna
2 Association for Decision Support for Health Policy and Planning (DEXHELPP), Austria, Neustiftgasse 57-59, 1070 Vienna
3 Institute for Information Systems Engineering, TU Wien, Vienna, Austria

❂These authors contributed equally to this work.
* nadine.weibrecht@dexhelpp.at

Abstract

In 2020, the ongoing COVID-19 pandemic caused major limitations for any aspect of social life and in specific for all events that require a gathering of people. While most events of this kind can be postponed or cancelled, democratic elections are key elements of any democratic regime and should be upheld if at all possible. Consequently, proper planning is required to establish the highest possible level of safety to both voters and scrutineers. In this paper, we present the novel and innovative way how the municipal council and district council elections in Vienna were planned and conducted using an agent-based simulation model. Key target of this process was to avoid queues in front of polling stations to reduce the risk of related infection clusters. In cooperation with a hygiene expert, we defined necessary precautions that should be met during the election in order to avoid the spread of COVID-19. In a next step, a simulation model was established and parametrized and validated using data from previous elections. Furthermore, the planned conditions were simulated to see whether excessive queues in front of any polling stations could form, as these could on the one hand act as an infection herd, and on the other hand, turn voters away. Our simulation identified some polling stations where long queues could emerge, however, splitting up these electoral branches resulted in a smooth election across all of Vienna. Looking back, the election did not lead to a significant increase of COVID-19 incidences. Therefore, it can be concluded that careful planning led to a safe election, despite the pandemic.

Author summary

Why was this study done?

- The ongoing COVID-19-Pandemic poses a risk for elections, as these could lead to another spread of the disease.

- Additional hygiene measures, which are inevitable if the election is conducted, could lead to long queues in front of the polling stations on election day.

What did the researchers do and find?

- We describe the defined additional hygiene measures.

- We modeled the whole election process, including the new hygiene concept, to show where extensive queues could form on the election day.

- We show that thanks to the additional hygiene measures, the election actually did not cause a temporary upswing of the epidemic.

What do these findings mean?

- Thanks to careful planning, it is possible to safely hold an election during such a pandemic.

- Our simulation contributed to a safe and smooth election.

- However, it should be stated, that these findings hold for elections in Austria, where long queues in front of polling stations are comparably rare and short.

Introduction   1

In 2020, the COVID-19-Pandemic affected almost every area of daily life, including   2
elections. On the one hand, elections necessarily cause a gathering of people, on the   3
other hand, elections are an essential part of vital democratic societies and are not   4
easily canceled or postponed. Consequently, proper planning is required to enable the   5
election process, provide the highest possible level of safety to all participants, and to 6
avoid that the election stokes the spread of the disease.   7
    In Vienna, the municipal council and district council elections were scheduled for   8
October 11^{th} 2020. By this time, SARS-CoV-2 case numbers in Austria, especially in   9
Vienna, were on the rise and the risk of infections was high [28]. So the planning   10
committee consulted modeling and simulation experts to help them increasing the level   11
of safety to voters and scrutineers. The key question of the planning process was how to   12
avoid the development of long waiting queues in front of the polling stations, since these 13
may potentially lead to infection clusters.   14
    To avoid (excessive) epidemic spread clusters forming at the polling stations, the   15
first approach was one independent of modeling and simulation. Encouraging voters to   16
use postal election was a simple but effective measure to reduce the amount of people   17
turning up at polling stations. However, not all voters can or want to vote via mail.   18
Hence, it is neither possible nor legitimate to hold elections via mail only, without the 19
option to vote in person.   20
    To avoid negative impact on the spread of COVID-19 in this process, a hygiene   21
concept was developed. This hygiene concept, however, includes additional tasks during   22
the election, such as wearing a face mask which has to be removed and put back on for   23
identification, and will therefore extend the duration of the election process.   24
Consequently, next to developing the hygiene concept, it was necessary to ensure that   25
the whole process is not extended in a way such that long queues form in front of the   26
polling booths, as these would create an additional infection risk and furthermore could   27
turn voters away. [1, 2]   28
    It must be stated, that, compared to other countries, waiting queues in front of   29
polling stations are comparably rare and short in Austria. Unfortunately, to the   30
authors' knowledge, there is no data on polling queues as of now. Nevertheless, in 2017, 31
when national elections took place in Austria, an article in the "Wiener Zeitung"   32
("Vienna newspaper") stated that "there was even a short wait in front of the cabins at   33
11 a.m.", indicating that usually there are hardly any waiting queues in Austria [4].   34
This is a desirable condition which should be preserved, in particular thinking about   35
infection risks in queues. Yet, since additional hygienic measures, which might slow   36

down the voting process, were required for the election in October, election planners were afraid that it might be different this time.

To ensure that the hygiene measures don't cause long waiting queues, a discrete event simulation (DES) model was developed to simulate the voting process including the hygiene concept in each electoral branch. Thus, possible problematic districts could be identified, so that additional measures like additional voting booths for these districts could be applied.

In January 2020 our group developed an agent-based COVID-19 epidemic model [6,7], which is still in heavy use for counseling of political decision makers in Austria [8]. The present question revealed an interesting new chance for us. While the epidemic model concentrates on the overall spread of the disease throughout the Austrian population, it models the places where infections take place, like households, schools, work places, or leisure facilities as chance encounters. This is of course necessary due to the much larger population size. The COVID-19 model analyses the spread of the disease for the whole Austrian population, and therefore uses nearly 9 million agents. In contrast, there were about 1.4 million people eligible to vote at the present elections, from which we expected 30 - 60 % to turn up at polling stations and the rest to use postal votes or not vote at all. Moreover, the COVID-19 investigates a much longer time frame. It predicts the spread of the virus over a time frame ranging from several weeks to months, while the election takes place over the course of 10 hours. The concise character of the presented problem enabled us to model the election process in more detail.

In this work we show, how this DES model contributes to enabling safe election processes in times of epidemics. We describe the model in detail, explain its parametrization and validation process and describe how it detects potential bottlenecks in an election process with respect to emergence of long queues. Furthermore, we reevaluate the municipal council and district council elections in Vienna in Fall 2020 which have been planned using the simulation tool and identify the benefits of the usage of the model. The aim of this work is to demonstrate how modelling and simulation can help optimizing election processes with respect to avoiding queues and consequently also avoiding infection clusters in epidemic situations.

Materials and methods

This section describes the COVID-related methodological background, followed by a description of the boundary conditions and a comparison to an already developed agent-based COVID-19 epidemic model. Finally, the last subsection deals with the details of the discrete event model.

Additional hygiene measures due to COVID-19

Vienna consists of 23 districts, which are split up into 1456 voting districts (at the time of the elections 2020). Each voting district contains a polling station with an average number of 937 persons being entitled to vote. [27] These voting districts are visualized in Figure 1, colored by the number of persons entitled to vote.

The planning process for the municipal council and district council elections in October 2020 started in June and at this time, the further course of the COVID-pandemic was not clear. While the number of cases was rather low in June, the actual number was hard to predict, and a higher number of cases was to be expected for October. To be prepared for every scenario, different hygiene measures were developed in collaboration with hygiene experts, as elections usually would bear an infection risk. These measures could come into effect depending on the number of COVID-cases active

during the election. These concepts affected every task during the election, including the training of election personnel, the setup of polling stations, and the counting process. To minimize the risk of election-caused COVID-19 clusters, external measures such as more dates for training, more allocated time for the setup and more rooms and personnel for the counting were applied. It was agreed that these measures would suffice for these contexts. _{85 86 87 88 89 90}

Fig 1. Map of Vienna, indicating the polling districts and the number of people entitled to vote in each district. Each polling district has exactly one polling station.

The assessment of measures of the actual voting process is more complex, as it not only involves the voting personnel, which can be trained, but also the voters, whose number is not known in advance. While the adherence to the measures within polling stations can be monitored by the staff, a problem lies in the emerging queues. _{91 92 93 94}

Most hygiene measures that were developed for everyday life (like providing hand sanitizer, keeping distance and wearing a face mask) could be applied to the election too. Furthermore, the election workers didn't only wear a face mask, but also a face shield. However, each voter needs to be identified before casting the vote, and this contradicts with wearing a face mask during the whole process. In order to identify the voters without putting anyone at risk to infect with COVID-19, two possible hygiene strategies were defined (see also [5]): _{95 96 97 98 99 100 101}

- Strategy A: Each voter is asked to maintain a safety distance to the election workers, take off their face mask in order to be identified, and to put it right back on afterwards. _{102 103 104}

- Strategy B: Each voter is asked to go into a perspex booth, take off the mask there, wait to be identified, put the mask back on and leave the perspex booth. _{105 106}

It goes without saying that hygiene strategy B is safer than A, but also takes more time. ₁₀₇

Clearly, both of the defined hygiene strategies might cause long queues in front of the polling station, as due to them, the voting process will take longer in total. Hereby, counter measures could be applied, if potential bottlenecks are known upfront: _{108 109 110}

If only few problematic polling stations were to be identified, one could think about applying additional measures to these stations directly, like offering an additional polling booth. Also merging or splitting of voting districts is possible.

Therefore, modeling and simulating the voting process and estimating the length of the queue for each voting district before the actual election takes place was deemed to be of great importance.

Boundary conditions and comparison

Answering the key question of the planning process, namely how to avoid the development of long waiting queues in front of the polling stations, with the help of a simulation model requires to define the observed system's borders — a task which in this case proves quite challenging. In principle, there are two possibilities to tackle the problem: First, the task can be analyzed from a *microscopic* point of view regarding all processes within one single polling station. Hereby, we need to analyze and reduce the risk of infection in a single building. Second, the problem can be regarded on a *macroscopic* level, considering the election process in the whole city and all interactions involved.

Clearly, the microscopic point of view would neglect the pandemic nature of the phenomenon. Since these elections are taking place in an urban area with a heterogeneous population (in terms of population density as well as demographic features – which means different infection risks) at several hundred polling stations, the macroscopic perspective is hard to neglect.

As the election takes place in a very limited time-frame only, i.e the 10 hours during which the polling stations are open, it was possible to decouple these perspectives and we subsequently split the problem into two: the *socio-demographic aspect* which assesses the general epidemic situation for the Vienna metropolitan area and the *logistical aspect* which deals with the local risks of infection at the polling stations.

With the former being not only harder to control (until today, policy makers are struggling with getting a grip on the epidemic) but also much slower to affect, we chose to incorporate it as a *"prognosis of boundary conditions"* within which the logistic part of the problem had to be solved.

Modeling and analyzing the queuing times for the election, the natural choice of modeling approach is a discrete event based queuing system, where the voters are the entities that run through a system of servers and queues that represent the different stations during the voting process. While a more detailed model using agents and their individual (locally optimal) paths would have been possible (see for example [9,10] or also [11,12]), an agent-based approach was deemed too detailed because of the sequential nature of the voting system, as there is no prioritization within the waiting voters and always the first in the queue is the next to vote (i.e. there is no overtaking, and therefore the individual paths of the voters are not that important).

The queuing system is typically analyzed either with classical steady state analysis or with stochastic simulation. However, considering steady state analysis, the system doesn't fulfill all conditions, that are required to yield reasonable results (see also discussion). Therefore, the system is analyzed using stochastic simulation.

Discrete event model

The following section deals with the implementation of the discrete event model. First, an overview over the model is provided. Next, the implemented scenarios and the calibration process are described. Finally, a dashboard is shortly introduced which visualizes the simulation results and helps with the decision making process.

Modelling process ₁₅₉

Our discrete event simulation model (DES) can be considered as the interface between ₁₆₀ epidemiology, which is the reason for our research, and logistic, which is the solution. ₁₆₁ Considering the different strategies of hygiene measures and assessing their impact on ₁₆₂ waiting times and queues, it was necessary to extend the established models. While the ₁₆₃ hygiene measures A (taking off the mask for identification with safety distance) and B ₁₆₄ (taking of the mask for identification in a perspex booth) mainly affect the service times ₁₆₅ for the different voting processes, the need of social distancing and the limitation of ₁₆₆ voters allowed inside the polling station at any given time revealed a new challenge. ₁₆₇ After entering the polling room, the voters must identify themselves at the electoral ₁₆₈ commission and collect their ballot card. They then proceed to the polling booth. ₁₆₉ Thereafter, they deposit their ballot card at the electoral commission before leaving the ₁₇₀ polling room. This process is depicted in Figure 2. As most polling stations are located ₁₇₁ in schools or other public buildings and the used rooms often only have one ₁₇₂ entrance/exit, voters had to wait until one of the previous voters left the room. This ₁₇₃ fact was taken into account by adding another server to the model that represents the ₁₇₄ entrance/exit, which created the desired blocking effect. ₁₇₅

Fig 2. Depiction of server queue model for voter flow

The model consists of two parts, the voters and the polling stations, which can be ₁₇₆ interpreted as entities and as systems of servers and queues, respectively. ₁₇₇
A voter has the following possible attributes, which are considered by our model: ₁₇₈

- Limited Mobility: If a voters mobility is impaired, their voting process takes more ₁₇₉ time. Additional time is required for every step of the process. ₁₈₀

- Brings voting information: If a voter brings their voting information, they are ₁₈₁ found faster in the system and therefore the identification is faster. ₁₈₂

- Uses preferential voting: If a voter uses preferential voting, their election takes ₁₈₃ more time. ₁₈₄

For a polling station, we considered the following attributes: ₁₈₅

- The number of people entitled to vote in this polling station. ₁₈₆

- The size of the polling station: We distinguish between *Hall* and *Room*, the ₁₈₇ election process in a hall takes more time because of the longer ways. ₁₈₈

- The number of polling booths: Usually, if there are less than 1000 voters entitled ₁₈₉ to a polling station, it has 2 polling booths, otherwise 3. ₁₉₀

- The age distribution in the polling station's district, as the age of a voter [191] influences the probability of their mobility being impaired. [192]

During the simulated election process, voters appear at the polling station at [193] random following a distribution that was based on insights from previous elections and [194] pass different places within the station. These places are visualized in Figure 2. In each [195] place, the voter spends a certain amount of time, which corresponds to an exponentially [196] distributed random number. The parameters for these random numbers are fitted in a [197] calibration process (see below). [198]

Calibration and validation [199]

As also encouraged in the literature, and in order to derive useful recommendations for [200] actions, we made substantial efforts to calibrate the model as well as possible, i.e. to set [201] the parameters reasonably. [202]

The parameters for the arrival times of the voters are chosen according to the arrival [203] times of past elections [23, 24]. The age distribution for the district of each polling [204] station is drawn from statistical data [25, 26]. The amount of voters bringing their [205] voting information and using preferential voting corresponds to 67% and 10%, [206] respectively, according to the experts from the magistrale department 62, which is [207] responsible for elections. [208]

The times each voter needs at each place in a polling station (to walk to the [209] electoral commission, to be identified, to vote) are drawn from an exponential [210] distribution. The parameters of these distributions were initially estimated by election [211] workers of past elections. Afterwards, these estimations were calibrated assuming a [212] voter turnout of 75% with 250,000 postal voters, voters with limited mobility according [213] to prevalence and no hygiene strategy. This scenario corresponds approximately to the [214] conditions during the last election in Austria, which was the national council election in [215] 2019. Within this scenario, the parameters were carefully adjusted using a bisection [216] algorithm, until the simulation yielded reasonable waiting queues. However, as data [217] from queues have not been measured so far, "reasonable waiting queues" were in fact [218] hard to quantify; the magistrale department 62 could not provide any data on this, [219] either. But due to their experience, they stated that the longest queue forming in front [220] of a polling station during the election day never exceeded 15 persons. Therefore, we [221] looked for a parametrization of the model such that the longest queue was lower or [222] equal to 15 in every polling station. [223]

Via the bisection algorithm, we found a calibration which yielded maximum queues [224] of 15 people or less in 1439 of the 1456 voting districts (i.e., 98, 70%). In the remaining [225] 17 stations, however, extensive queues of up to 132 persons would emerge, which clearly [226] made a closer inspection of these stations with the magistrale department 62 necessary. [227] This inspection showed that these stations were already known as potential risk stations [228] and were thus under observation. These stations, for example, belong to districts with [229] care homes; therefore, the average age is comparatively high, and the voters need [230] accordingly long to vote in the simulation. In reality, care homes offer almost [231] exclusively postal voting, which is why these stations are actually no risk stations. The [232] other stations belong to known big voting districts, and were already planned to be split [233] up into two smaller voting districts. [234]

Via careful inspection from the planning experts using the implemented dashboard [235] (see below), the model passed general face validity tests. Since the model properly [236] displayed already known bottlenecks of a standard election process without additional [237] hygiene measures, the simulation model achieved a certain level of quantitative validity [238] as well. Note, that there is no data about queue lengths of previous elections available [239] that would allow a more detailed validation process. [240]

Scenarios

The model allows the simulation of several scenarios and strategies. First, the amount of voters and the number of postal voters were varied, as well as the amount of people with limited mobility and the number of additional polling booths. Additionally, the different hygiene strategies were simulated. Table 1 provides an overview over the varied values.

Parameter	Values
Voter turnout	65%, 70%, 75%, 80%
Number of postal votes	250,000, 300,000, 350,000, 400,000, 450,000, 500,000
Voters with limited mobility	According to prevalence, under prevalence, above prevalence
Hygiene Strategy	No strategy, strategy A, strategy B
Additional polling booths	0, 1, 2

Table 1. Scenarios covered by our simulation

The impact of the scenarios on the queues can be seen in Figure 3. Based on the above mentioned baseline scenario, each of the parameters has been varied, and the longest queue, that appears throughout the day in one of the polling stations in each district, has been calculated. Considering these results, the following observations can be made:

- The number of people appearing at the polling stations has a crucial impact on the queues. A high voter turnout is generally desirable, but the number of postal voters can be increased. For example, having 300,000 instead of 250,000 postal voters reduces the maximum emerging queue in some districts by half. Thus, using postal votes should be further encouraged.

- The amount of voters with limited mobility has hardly any impact on the queue lengths. Therefore, in the following analysis, only "limited mobility according to prevalence" will be considered.

- The difference from "no hygiene strategy" to "hygiene strategy A" is larger than the difference from "hygiene strategy A" to "hygiene strategy B". Seeing this, hygiene strategy B should be preferred, as it is safer without having that much impact on the waiting queues.

- It happens, when comparing two scenarios, that the maximum queue is longer in a scenario, where a shorter queue would have been excepted, or vice versa. For example, considering the maximum queues for different values of limited mobility, the maximum queues are not necessarily increasing with increasing limited mobility. This happens especially in smaller districts, due to random fluctuation.

Dashboard

In order to visualize the scenarios and thus, to improve the decision making process, a dashboard containing the simulation results was implemented. In this dashboard, it is possible to set a scenario according to the values shown in Table 1. As measure of interest, for each scenario and for each district, the longest queue forming at one point of the election day in front of the polling station was chosen. These values are visualized in a choropleth map of Vienna, in order to identify polling stations with a need for action, see also Figure 4.

Fig 3. Impact of different voter turnouts, postal voters, limited mobility (LM) and hygiene scenarios on the maximum queue in each district in Vienna. The baseline uses a voter turnout of 75%, 250,000 postal votes, limited mobility according to prevalence and no additional hygienic measures.

Results

Considering the goal of the analysis, there are two kinds of results that can be considered: queue lengths, meaning both simulated results from our model and reported waiting queues at the election day, and SARS-CoV-2 infection numbers, measured a few days after the election.

Model results

Together with the magistrale department 62, the following baseline election scenario was defined for the upcoming election: A voter turnout of 70%, 300,000 postal votes, voters with limited mobility according to prevalence and hygiene strategy B. Based on this election scenario, the voter turnout and the amount of postal voters has again been varied, as can be seen in Figure 5. It still holds for this scenario, that the maximum queues are crucially influenced by these parameters, and that postal voting should be encouraged.

For these assumptions, our model identified 41 polling stations as potential risk stations, meaning that in front of these stations queues of 15 people or more could emerge. 17 of these stations (actually almost the top 17), however, correspond to the already mentioned known stations that are treated separately. Therefore, these stations are excluded from the following investigations.

This left 24 new potential risk stations, all of which have comparatively many people entitled to vote. Based on this, two new simulations were run, with one and two additional polling booths in each polling station, respectively. The simulation runs showed, that additional voting booths in these stations don't alleviate the queues sufficiently (i.e. maximum queues of 15 persons or less), as it can also be seen in Figure

Fig 4. Simulated waiting queues by the model. Left: Baseline Scenario (17 risk stations), Right: Hygiene strategy B added to baseline (351 risk stations)

5. This can be explained with the actual bottleneck of the election being the entrance, not the voting process itself. At the entrance sits the election commission. This is a group of local politicians and volunteers, that look over the whole election process. At a time, only one voter can enter the voting station, as they keep all members of the election commission busy. Plus, entering is the only part of the election whose duration is extended due to the hygienic measures, as they lead to prolonged ID checking. Two additional voting boxes hardly had any impact.

Splitting up a polling station into two stations, on the other hand, results in less people being entitled to vote in the respective station, and thus, in shorter waiting queues. Therefore, the magistrale department 62 decided to split up some of the risk stations. In total 32 polling stations were split up into two stations.

Actual election participation results

Unfortunately, our attempts to gather queue length data for proper reevaluation of the model results were not successful for different administrative and data privacy reasons. Nevertheless, the complete absence of negative news about crowded polling booths – in particular in times in which almost any mass gathering of persons causes a COVID-19–news headliner – provides some evidence that the combination of the strategies have successfully prevented crowding.

Of the $1,362,789$ people that were eligible to vote, $786,777$ people cast their vote, yielding a voting turnout of 57.73%. The turnout is significantly lower than in 2015, having a turnout of 65.79%. This might not only be explained by COVID-19, but also by some domestic affairs. Of all voters, 339.445 (43.14%) used postal votes. This is a comparably high number, as in 2015, only 159.226 voters (12.00%) used postal voting [27]. Thus, it can be stated that the effort of motivating the people to vote postally was successful.

Reported COVID-19 case numbers

Still, 447.332 persons voted in person, bearing an increased infection risk for the election day. Indeed, infection numbers in Austria strongly increased by the middle of October, which coincides with the days after the election. However, a closer inspection of the incidences in the single federal states shows, that the incidences in Vienna were

Fig 5. Impact of different voter turnouts, postal voters and additional polling booths on the length of the maximal queue in each district in Vienna, neglecting the already known risk stations.

comparably low; actually, incidences in Vienna were the only descending ones in Austria, see also Figure 6. While the election can not be held responsible for the decreasing numbers in Vienna, it can at least be stated, that it has not contributed to an increase of incidences. [28]

Discussion and conclusion

Our work shows, that the usage of our discrete event simulation model can help to point out polling stations where long queues in urban elections could develop. In combination with proper hygiene concepts, it contributes to allow safe elections even in times of epidemics. However, it is important not to underestimate the risks that occur from the pandemic, and to take appropriate precautions.

The decision to model the voting process as a queuing model corresponds to the findings of the available literature on this topic. The question of how to model the voting process and analyze the queue lengths during this process was predominantly investigated in the US [3,13–20] but also in other countries like Nigeria [21] or Hong Kong [22]. Most of these papers, especially the ones from the US, focus on the optimal distribution of voting machines. This is due to the widespread use of such machines there. Hence, the scarcity of these resources presents the biggest bottleneck during the US voting process. Additionally, different waiting times in different voting precincts are a major problem. Other papers [19,21,22] are more concerned on optimizing the actual voting process by providing more resources such as voting booths or identification desks. Big differences between the models are mainly due to varying voting processes, for example in Nigeria the overall process is split into two phases, where the voters have to get accredited in the morning and the actual vote is performed in the afternoon. Technologically, the queuing system is typically analyzed in one of two ways. The first approach is classical steady state analysis [15,19], but using steady state analysis

Fig 6. Incidences in Austria and in each federal state before and after the election date according to official data [28]. The vertical line denotes the election day.

creates a number of problems and inaccuracies for the analysis:

- Using steady state analysis requires the system to be in a steady state. Due to the relatively short voting time, it is not always possible to ensure that the system even reaches this state.

- If the arrival rate is greater than the servicing rate of the system, the queues become unbounded, and therefore a steady state can never be reached.

- Queuing systems base their analysis on arrival rates and service times that are randomly distributed, but the underlying distribution cannot change over time. This restriction is particularly limiting for the consideration of voting processes, as the arrival rates are typically dependent on the time of day, and the actual voting times depend heavily on the type of voter. For example, disabilities lead to higher voting times, but also voters that use preferential voting take longer than voters who only vote for a political party.

These problems show that steady state analysis is not a feasible method for studying voting processes, which is acknowledged in most of the literature. The second approach for analyzing queuing systems is stochastic simulation, which is also the preferred method in most of literature [13, 14, 16–18, 21, 22]. This ansatz enables not only a more detailed stochastic analysis, but also the possibility to vary parameters over time and describe voters with different time requirements. Basically all of the presented papers agree, that carefully estimated arrival rates, that can vary throughout the day and servicing times for the different processes are key for a sophisticated prediction of waiting times and queue lengths.

However, the limitations of our study need to be stated. For our simulation model, the following simplifications had to be made:

- No reneging: Voters don't leave the queue if the wait is too long. This could limit the application to other elections where queues are typically longer.

- No precise approximation of persons with limited mobility in each district: Our estimation of the amount of people with limited mobility relies solely on the age distribution in this district.

- No realistic distribution of postal voters: Our model assumes that the amount of postal voters is the same across all age groups. This is, for example, not true for people living in care homes, as they use postal voting almost exclusively. This yielded unreliable results in districts with large care homes. Furthermore, the amount of postal votes depends on the socioeconomic population structure and varies within the districts. And finally, it is possible to order postal voting and nevertheless enter a polling station in order to deposit the vote. This is done, for example, when a voter wants to vote in a different polling district than their home district. This wasn't considered either by the model.

Additionally, we had limited data for both parametrization and validation. Queue-data have not been measured and collected so far, and thus, the calibration process could only be validated visually, instead of quantitatively. As this work focused on identifying those stations, where long queues could emerge, instead of on the actual queue lengths of the single stations, the visual validation was sufficient. However, if a more precise study with reliable queue length numbers is required, more data would be necessary to parametrize and validate the model correctly.

In general we showed that modeling and simulation is a valid way to test new conditions in an election. In this case, the precautions, that were taken in order to avoid a new spread of COVID, lead to an unavoidable prolongation in the voting process. The simulation showed, however, that the process was not prolonged in a way such that long queues formed in front of the polling stations. Nevertheless, the model can easily be adapted to simulate any other changes in the voting scheme as well.

Altogether the established strategy resulted in an election which can be considered as "smooth". It should however be taken into account that this is usually the case in Austria. It rarely happens, that queues in front of polling stations form at all, and if, these are mostly short ones. Still, it is worth acknowledging that this condition was threatened by the additional measures, but could be upheld.

Finally, the analysis of the reported case numbers in the city of Vienna indicated that the election did not cause a temporary upswing of the epidemic. Surely, there are many factors that might have prevented additional infections such as wearing face-mask, large and well ventilated polling rooms, keeping the distance in the queues, low voter turnout, campaigns for mail voting, or simply because voting is a quick process that does not require talking. Nevertheless, it is legit to assume that the preventive measures against queuing bottlenecks that were detected by the simulation model contributed to avoid election related infection clusters – and this was, essentially, the uppermost goal of the simulation study.

Acknowledgments

This work was supported by "Stadt Wien - Wahlen und verschiedene Rechtsangelegenheiten (MA 62)" ("City of Vienna - Elections and various legal matters, magistrale department 62") by means of data acquisition and validation.

References

1. Clark A. Public Administration and the Integrity of the Electoral Process in British Elections. Public Adm. 2015;93(1):86–102. doi: 10.1111/padm.12106.

2. Smith M, Monfort S, Blumberg E. Improving Voter Experience Through User Testing and Iterative Design. J Usability Stud. 2015 Sep;10(4):116–128.

3. Belenky AS, Larson RC. To Queue or Not to Queue. OR/MS Today. 2006;33:30–34.

4. Warteschlangen vor den Wahllokalen. German. Wiener Zeitung. 2017 Oct 15 [Cited 2021 April 15]. Available from: `https://www.wienerzeitung.at/nachrichten/wahlen/nationalratswahl-2019/nationalratswahl-2017/923105-Warteschlangen-vor-den-Wahllokalen.html`.

5. Wien-Wahl 2020: Sicher wählen am Wahltag. German. 2020 Oct 2 [Cited 2021 April 15]. Available from: `https://www.wien.gv.at/presse/2020/10/02/wien-wahl-2020-sicher-waehlen-am-wahltag`.

6. Bicher M, Rippinger C, Urach C, Brunmeir D, Siebert U, Popper N. Evaluation of Contact-Tracing Policies against the Spread of SARS-CoV-2 in Austria: An Agent-Based Simulation. Medical Decision Making. 2021 May;p. 0272989X2110133.

7. Rippinger C, Bicher M, Urach C, Brunmeir D, Weibrecht N, Zauner G, et al. Evaluation of undetected cases during the COVID-19 epidemic in Austria. BMC Infect Dis. 2021;21(1):70. doi: 10.1186/s12879-020-05737-6

8. Bicher M, Zuba M, Rainer L, Bachner F, Rippinger C, Ostermann H, et al. Supporting Austria through the COVID-19 Epidemics with a Forecast-Based Early Warning System. medRxiv: 2020.10.18.20214767 [Preprint]. 2020 [posted 2020 Oct 20; cited 2021 April 15]. Available from: `http://medrxiv.org/lookup/doi/10.1101/2020.10.18.20214767`. doi: 10.1101/2020.10.18.20214767

9. Tauböck S, Breitenecker F, Wiegand D, Popper N. The <morespace> Project: Modelling and Simulation of Room Management and Schedule Planning at University by Combining DEVS and Agent-Based Approaches. Simulation News Europe SNE. 2011;21(1):11–20.

10. Bruckner M, Tauböck S, Popper N, Emrich S, Roszenich B, Alkilani S. Modelling and Simulation of Student Pedestrian Traffic at University Campus. Simulation News Europe SNE. 2012;22(2):95–100.

11. Glock B, Wurzer G, Breitenecker F, Popper N. Reverse Engineering Hospital Processes Out of Visited Nodes. In: Al-Begain K, Al Dabass D, Orsoni A, Cant R, Zobel R, editors. EUROSIM 2013 8th EUROSIM Congress on Modelling and Simulation. Cardiff 2013. p. 312–317.

12. Wurzer G, Lorenz WE, Rößler M, Hafner I, Glock B, Bruckner M, et al. MODYPLAN: Early-Stage Hospital Simulation Based on Treatment Chains. IFAC-PapersOnLine. 2015;48(1):868–873.

13. Grant FH. Reducing Voter Waiting Time. Interfaces (Providence). 1980;10(5):19–25.

14. Edelstein WA. New Voting Systems for NY— Long Lines and High Cost. Nov 14 2006 [Cited 2021 April 15]. In: New Yorkers for Verified Voting; 2006. Available from: `https://nyvv.org/voterlines.shtml`

15. Allen T, Bernshteyn M. Mitigating Voter Waiting Times. Chance (N Y). 2006;19:25–34. doi: 10.1080/09332480.2006.10722812

16. Yang M, Fry MJ, Kelton WD. Are All Voting Queues Created Equal? In: Proceedings of the 2009 Winter Simulation Conference (WSC); 2009. p. 3140–3149.

17. Yang M, Allen TT, Fry MJ, Kelton WD. The Call for Equity: Simulation Optimization Models to Minimize the Range of Waiting Times. IIE Trans. 2013;45(7):781–795. doi: 10.1080/0740817X.2012.721947

18. Yang M, Fry MJ, Kelton WD, Allen TT. Improving Voting Systems through Service-Operations Management. Prod Oper Manag. 2014;23(7):1083–1097. doi: 10.1111/poms.12088

19. Stewart III C. Managing Polling Place Resources. Caltech/MIT Voting Technology Project; 2015.

20. Wang XJ, Yang M, Fry MJ. Efficiency and Equity Tradeoffs in Voting Machine Allocation Problems. J Oper Res Soc. 2015;66(8):1363–1369. doi: 10.1057/jors.2014.107

21. Olabisi UO. Modeling and Analysis of the Queue Dynamics in the Nigerian Voting System. The Open Operational Research Journal. 2012;6(1):9–22.

22. Au CH, Xu Z, Wang L, Fung WSL. Establishing a Three-Step Model of Designing the Polling Stations for Shorter Queue and Smaller Waiting Time: A Case Study Using Computer Simulation. Journal of Information Technology Case and Application Research. 2017;19(4):225–245. doi: 10.1080/15228053.2017.1433494

23. Detailergebnisse der Geimenderatswahl 2015. German. [Cited 2021 April 15] Available from: `https://www.wien.gv.at/wahl/NET/GR151/GR151-109.htm`.

24. Detailergebnisse der Nationalratswahl 2017. German. [Cited 2021 April 15] Available from: `https://www.wien.gv.at/wahlergebnis/de/NR171/index.html`.

25. Bevölkerung nach Altersgruppen, Geschlecht und Gemeindebezirken 2019. German. [Cited 2021 April 15] Available from: `https://www.wien.gv.at/statistik/bevoelkerung/tabellen/bevoelkerung-alter-geschl-bez.html`.

26. Ausgewählte Ergebnisse aus der Abgestimmten Erwerbsstatistik und der Arbeitsstättenzählung 2018 Gebietsstand 2020). German. [Cited 2021 April 15] Available from: `https://www.statistik.at/wcm/idc/idcplg?IdcService=GET_PDF_FILE&RevisionSelectionMethod=LatestReleased&dDocName=079497`.

27. Gemeinderatswahlen 2020. German. [Cited 2021 April 15] Available from: `https://www.wien.gv.at/wahlergebnis/de/GR201/index.html`.

28. AGES Dashboard COVID19. German. [Dashboard] [Cited 2021 April 15] Available from: `https://covid19-dashboard.ages.at/dashboard.html`.