Title: The COMBAT-TB Workbench: Making powerful TB bioinformatics accessible

Running title: COMBAT-TB Workbench - *M.tuberculosis* analysis

Peter van Heusden[a*], Ziphozahe Mashologu[a], Thoba Lose[a], Robin Warren[b], Alan Christoffels[a,c*]

[a]South African Medical Research Council Bioinformatics Unit, South African National Bioinformatics Institute, University of the Western Cape, South Africa

[b]DSI-NRF Centre of Excellence for Biomedical Tuberculosis Research, South African Medical Research Council Centre for Tuberculosis Research, Division of Molecular Biology and Human Genetics, Faculty of Medicine and Health Sciences, Stellenbosch University, Cape Town, South Africa

[c]Africa Centres for Disease Control and Prevention, African Union Headquarters, Addis Ababa W21K19, Ethiopia

[*] Corresponding authors: pvh@sanbi.ac.za, alan@sanbi.ac.za

Abstract (250 word limit)

Whole Genome Sequencing (WGS) is a powerful method for detecting drug resistance, genetic diversity and transmission dynamics of *Mycobacterium tuberculosis*. Implementation of WGS in public health microbiology laboratories is impeded by a lack of user-friendly, automated and semi-automated pipelines. We present the COMBAT-TB workbench, a modular, easy to install application that provides a web based environment for *Mycobacterium tuberculosis* bioinformatics. The COMBAT-TB Workbench is built using two main software components: the IRIDA Platform for its web-based user interface and data management capabilities and the Galaxy bioinformatics workflow platform for workflow execution. These components are combined into a single easy to install application using Docker container technology. We implemented two workflows, for *M. tuberculosis* sample analysis and phylogeny, in Galaxy. Building our workflows involved updating some Galaxy tools (Trimmomatic, snippy and snp-sites) and writing new Galaxy tools (snp-dists, TB-Profiler, tb_variant_filter and TB Variant Report). The irida-wf-ga2xml tool was updated to be able to work with recent versions of Galaxy and was further developed into IRIDA plugins for both workflows. In the case of the *M. tuberculosis* sample analysis an interface was added to update the metadata stored for each sequence sample with results gleaned from the Galaxy workflow output. Data can be loaded into the COMBAT-TB Workbench via the web interface or via the command line IRIDA uploader tool. The COMBAT-TB Workbench application deploys IRIDA, the

24   COMBAT-TB IRIDA plugins, the MariaDB database and Galaxy using Docker

25   containers (https://github.com/COMBAT-TB/irida-galaxy-deploy).

28 Importance (150 word limit, non-technical explanation)

While the reduction in cost of WGS is making sequencing more affordable in Lower and

Middle Income Countries, public health laboratories in these countries seldom have

access to bioinformaticians and system support engineers adept at using the Linux

command line and complex bioinformatics software. The COMBAT-TB Workbench

provides an open source, modular, easy to deploy and use environment for managing

and analysing *M. tuberculosis* WGS data and thereby makes WGS usable in practice in

the LMIC context.

Introduction

Tuberculosis (TB) until recently the world's deadliest infectious disease, infecting an estimated 10 million people in 2019 and killing 1.4 million people(1). Whole Genome Sequencing (WGS) of *Mycobacterium tuberculosis*, the bacterium that causes TB, is increasingly being used, at least in high income countries(2), for species and lineage identification, drug resistance profiling and outbreak investigation. Increasing the use of Whole Genome Sequencing in low and middle income countries (LMICs) requires reducing the cost of both sequencing and bioinformatics analysis of sequencing results and reducing the time and effort involved in going from sequence to analysis results(3).

This cost takes the form of equipment, consumables and expertise. The command line tools whose use is prevalent in bioinformatics (4) require skills not readily accessible outside of specialist labs. On the other hand, web based tools such as TB-Profiler (5) and the NIAID TB Portals(6) are restricted to the analyses provided by their authors and often lack features for bulk analysis. Finally platforms like Galaxy(7), while customisable do not provide a data management and analysis user interface specific for common *M. tuberculosis* analysis tasks.

To address these deficiencies, the computational bacterial analytical toolkit for Tuberculosis research (COMBAT-TB) was developed. The COMBAT-TB Workbench (downloadable from https://github.com/COMBAT-TB/irida-galaxy-deploy) represents a

modular and accessible open source workbench for storing and analysing *M.*

tuberculosis and other microbial WGS data.

Results

Design and implementation

The COMBAT-TB Workbench is built using two main software components: the

Integrated Rapid Infectious Disease Analysis (IRIDA) platform (8) for its web-based user

interface and data management capabilities and the Galaxy bioinformatics workflow

platform for workflow execution. These components are combined into a single easy to

install application using Docker container technology.

Data management & User interface

The IRIDA platform, a project of the Public Health Agency of Canada (PHAC-NML), is a

web application written in Java, that provides a user-friendly web-interface for

sequencing data and metadata storage, workflow execution and results visualisation.

We adopted IRIDA as the basis of the COMBAT-TB workbench because of its

integration with the Galaxy platform, its proven track record in public health

bioinformatics (PHAC-NML has analysed over 200,000 pathogen samples using IRIDA

(44)) and the fact that it is open source.

IRIDA stores sequence samples on disk and sample metadata in a MariaDB database

(9). Sequence data is shared between IRIDA and the Galaxy analysis platform

(reducing data duplication).

Scientific workflows and IRIDA plugins

The Workbench uses Galaxy for its bioinformatics workflow composition and execution.

Two workflows, for *M. tuberculosis* sample analysis and phylogeny, were implemented

in Galaxy. Building workflows in Galaxy involves connecting Galaxy tools to construct

an analysis workflow where the Galaxy tools (also known as tool wrappers) themselves

connect command line bioinformatics tools to the Galaxy framework. Building our

workflows involved updating some Galaxy tools (Trimmomatic (10), snippy (11) and

snp-sites (12)) and writing new Galaxy tools (snp-dists (13), TB-Profiler (5),

tb_variant_filter (14) and TB Variant Report (15)). In addition to the work on Galaxy

tools, the command line tb_variant_filter and TB Variant Report tools were created as

part of the COMBAT-TB project.

The irida-wf-ga2xml tool (16) was updated to be able to work with recent versions of

Galaxy and it was used to build IRIDA plugin skeletons. These plugin skeletons were

further developed into IRIDA plugins for both workflows, in the case of the *M.*

tuberculosis sample analysis involving the addition of an interface between the Galaxy

workflow output and the metadata stored for each sequence sample. The *M.*

tuberculosis Sample Report and *M. tuberculosis* Phylogeny plugins are hosted in Github

repositories (https://github.com/COMBAT-TB/irida-plugin-tb-sample-report and

https://github.com/COMBAT-TB/irida-plugin-tb-phylogeny respectively) and deployed

into IRIDA as part of COMBAT-TB Workbench deployment process.

Deployment

The COMBAT-TB Workbench application (available at: https://github.com/COMBAT-TB/irida-

galaxy-deploy) deploys IRIDA, the COMBAT-TB IRIDA plugins, the MariaDB database IRIDA

uses for metadata storage and Galaxy using Docker containers (17). The Docker containers are

orchestrated using docker-compose (18). This allows the entire Workbench to be installed by

users without advanced Linux systems administration knowledge and hides the complexity of

the underlying software from the user.

Integration with external data storage

Data can be loaded into the COMBAT-TB Workbench via the web interface or via the

command line IRIDA uploader tool. This allows data from external storage (for example

the storage of a sequencing facility) to be loaded into the Workbench in bulk.

Figure 1. COMBAT-TB Workbench Technical Layout

Comparison to other similar open source software

At the time of writing we found two systems, Innuendo (19) and the IRIDA project (8)

that were comparable to the COMBAT-TB Workbench.

Innuendo is a web interface to sequence storage and Nextflow (20) workflow execution

aimed at analysis of food-borne pathogens. It is oriented around common tasks in the

food-borne pathogens surveillance terrain such as molecular typing of pathogens. The

platform is strongly tied to the workflows of a food-borne pathogen surveillance lab, and

adding additional species to the analysis system requires modifying the underlying

database and adding a wgMLST scheme. As such, Innuendo is addressing a different

challenge to the one the COMBAT-TB project is tackling.

IRIDA is the official bioinformatics platform for public health genomics within the Public

Health Agency of Canada. It has been in use since 2016 by Canada's provincial and

national public health laboratories for genomic investigations of foodborne disease

outbreaks, as part of PulseNet Canada's foodborne disease surveillance activities.

While it is more flexible than Innuendo, as it allows deployment of a wide variety of

Galaxy workflows and is not species specific, it is complex to deploy, with the

installation guide assuming knowledge of deployment of both Galaxy and the Tomcat

Java Servlet system (21). The COMBAT-TB Workbench, by contrast, is straightforward

to deploy with a single Linux command.

Use Case

For the purpose of these analyses we installed the COMBAT-TB Workbench on a virtual

machine with 8 virtual CPUs, 32 GB RAM and 3000 GB hard disk space, running

Ubuntu 18.04 with Docker version 19.03.14 and docker-compose version 1.27.4.

The COMBAT-TB Workbench user interface is organised around Projects and

Analyses. Projects store sequence samples, are associated with a reference genome

and allow controlling sharing and access to samples. Samples can be selected from a

project and added to a Cart. Once samples are in the Cart, selecting the Cart displays a

Workflow selection screen from which Analyses can be started (Figure 2):

Figure 2. COMBAT-TB Workbench: Workflow selection screen

Selecting one of the Workflows allows the workflow parameters to be set and the analysis to be

started. Workflows can either be per-sample, in which case a workflow instance is started for

each sample, or multi-sample (for example phylogenies) in which case the samples are

analysed as a group. Once a workflow has been executed it creates a new entry visible via the

Analyses interface. This interface allows monitoring the status of workflow execution and

visualization of workflow analysis results.

Analysis of data from MDR *M. tuberculosis* in Indonesia

Tania et al (22) collected *M. tuberculosis* samples from 30 patients with confirmed

pulmonary tuberculosis treated in four hospitals in the Western region of the Indonesian

island of Java. Phenotypic drug susceptibility testing (DST) was performed on the

cultured samples and DNA was isolated, sequenced and deposited in the NCBI

Sequence Read Archive (SRA) with BioProject access number PRJNA633244. Thirty

samples were retrieved from EBI European Nucleotide Archive (ENA) and uploaded to

the COMBAT-TB Workbench using the irida-uploader (23) command line tool. Per

sample quality control was performed automatically (using FastQC(24)) after sample

upload. Uploading and quality control took 9 and 3 minutes respectively.

The inferred ancestral *M. tuberculosis* reference genome produced by Comas et al (25)

was downloaded from Zenodo (26) and uploaded to the COMBAT-TB Workbench as

the default reference genome for the sequencing project. While the H37Rv reference

genome can be used, we used the *M. tuberculosis* inferred ancestral reference as Goig

et al (27) have previously shown that this genome is equidistant, in terms of sequence

variants, from all known *M. tuberculosis* lineages and thus provides a superior reference

to H37Rv (NC_000962.3) for variant calling, especially if that variant calling is going to

be used for phylogeny construction.

Per sample reporting

The *M. tuberculosis* Sample Report pipeline (see Materials and Methods) was run on

all 30 samples. Detailed output from this pipeline is made available in a per-sample

analysis report (Supplementary Figure 1) that includes a full report on variants identified

in the sample (annotated using information from the COMBAT-TB NeoDB (28)), drug

resistance prediction (from TB-Profiler) and quality control information on read mapping.

The pipeline updated the metadata associated with each sample, with the result that

after pipeline completion each sample was annotated with percentage of reads mapped

to genome, drug resistance prediction, drug resistance associated variants and lineage

assigned (Figure 3).

Figure 3: Sample Line List

Examining the read mapping outputs shows that only 9.63% and 1.47% of reads from

samples SRR12416824 and SRR12416842 respectively mapped against the *M.*

tuberculosis genome. Further investigation with kraken2 (29) using the Standard

database from 14 April 2020 showed that the majority (63.55%) of reads from

SRR12416824 were classified as belonging to the *Mycobacterium avium* complex

(MAC) and the majority of reads (75.39%) from SRR12416842 were classified as the

non-tubercular mycobacterium *Mycolicibacterium fortuitum*. These samples were thus

excluded and not used in subsequent analyses.

As shown in Table 1, the results were broadly concordant with those found by Tania et

al. Some small differences are likely a result of different versions of the TB-Profiler

software used. Without our own analysis, updating the TB-Profiler version from 2.8.4 to

version 3.0.6 reduced the discordance between streptomycin resistance predicted by

the COMBAT-TB Workbench and that predicted by MGIT by 2 samples. This illustrates

the evolution of drug resistance prediction from WGS data. As noted previously, the

COMBAT-TB Workbench pipeline uses snippy for mapping and variant calling and

applies TB-Profiler only to the results of the mapping step. Our results are, however,

wholly concordant with running the complete TB-Profiler pipeline.

Drug	Concordant MGIT	Discordant MGIT Resistant	Discordant MGIT Susceptible	Concordant Tania et al TB-Profiler	Discordant Tania et al Resistant
Isoniazid	24/28 (85.71%)	2	2	23/28 (82.14%)	1

Rifampicin	27/28 (96.43%)	0	1	27/28 (96.43%)	0
Ethambutol	17/28 (60.71%)	0	11	18/28 (64.29%)	1
Streptomycin	25/28 (85.71%)	2	1	23/28 (82.14%)	2
Table 1: Drug Resistance predictions from COMBAT TB Workbench & Tania et al					

The lower degree of concordance found between WGS and MGIT resistance testing for

ethambutol can be explained by the presence of variants impacting amino acid 306 of

the embB gene in 7 out of the 11 samples that were reported as resistant by WGS but

susceptible by MGIT. These variants (M306V in 2 and M306I in 5) lead to a change in

the MIC of ethambutol (30).

Phylogeny on all samples

The 28 samples that previously passed quality control were selected in the web

interface and submitted to the *M. tuberculosis* phylogeny pipeline

(https://github.com/COMBAT-TB/irida-plugin-tb-phylogeny). This pipeline computes a

Maximum Likelihood Phylogeny using the single nucleotide variants identified in each

sample (Figure 4).

　Figure 4: COMBAT TB Workbench phylogeny viewer

The IRIDA Advanced Visualization view (Figure 5) allows metadata from the sequence

analysis project's sequencing store to be associated with tips (i.e. samples) in the

phylogeny view. In addition to the metadata computed by the *M. tuberculosis* Sample

Report pipeline, an Excel spreadsheet was generated associating each sample ID with

the sample IDs and hospital collection sites identified in the Tania et al. paper. This

spreadsheet was used to load additional metadata into the IRIDA project.

The distance between hospital sites varied from 10km (Mampang Prapatan Hospital,

Jakarta to Cempaka Putih Islamic Hospital, Jakarta) to 107km (Drajat Prawiranegara

Hospital, Serang to M. Goenawan Partowidigdo Pulmonary Hospital, Bogor). When

visualised this way it was apparently that there was no clear relationship between

phylogenetic relationship (and thus lineage) and hospital site, illustrating that the

outbreaks occurring in the region were circulating in areas broader than hospital

catchment areas.

Figure 5: Advanced Phylogeny Visualisation with Metadata columns

Analysis of runtimes

The runtimes of the steps in the analyses are listed in Table 2. Galaxy scheduled the

execution of analysis steps in parallel when data dependencies allowed. The similarities

of the runtimes between the sample processing and the phylogeny pipelines are to

some extent due to the fact that IRIDA currently starts all analyses from sequence reads

rather than from assembled genomes. This limitation is currently being addressed by

the IRIDA development community. (31)

Dataset	Processing Step	Running Time
Tania et al (30 samples, 25GB)	Upload	9 minutes
	Sample processing	3 hours 23 minutes
	Phylogeny	3 hours 43 minutes
Xu et al (117 samples, 42GB)	Upload	21 minutes
	Sample processing	6 hours
	Phylogeny	8 hours 4 minutes
Table 2: Runtime of analyses in COMBAT TB Workbench		

Analysis of data from *M. tuberculosis* in Spain

Xu et al (32) collected *M. tuberculosis* samples from 117 patients and analysed them to

understand dynamics of TB transmission in the Valencia Region, in Spain. While the

key element of their analysis is identifying individual transmission patterns, their work

also provides a convenient larger dataset to examine the performance of the COMBAT-

TB Workbench

Uploading of the 117 samples took 21 minutes. Per sample analysis of the 117 samples

took a total of 6 hours. A phylogeny was computed using the samples. Phylogeny

generation took just over 8 hours and visualisation with the advanced phylogeny viewer

revealed clustering by *M. tuberculosis* lineage (Figure 7) as expected. Unfortunately Xu

et al did not include the output of their phylogeny construction in their results, so a direct

comparison of the computed phylogenetic trees is not possible.

Figure 7: Advanced Phylogeny viewer with Xu et al data (metadata shows lineage)

270 Discussion

The COMBAT-TB Workbench makes routine *M. tuberculosis* WGS sample storage and

bioinformatics analysis accessible in an extensible framework. The IRIDA platform on

which it is built allows pipelines to be added as needed, and the use of Docker container

technology means that installation on a machine (with the required Docker and docker-

compose software) is a straightforward process not requiring advanced systems

administration skills.

By making this project, developed using open source best practices, available the cost

of use of WGS can be reduced, increasing opportunities for *M. tuberculosis* WGS

deployment in low and middle income countries. As the capabilities of the underlying

IRIDA and Galaxy platforms continue to evolve, the COMBAT-TB workbench will

naturally acquire additional features in addition to the features being added by the

authors.

Materials and Methods

Implementation of the COMBAT-TB Workbench

IRIDA and Galaxy are both server environments, and IRIDA relies on a MariaDB

database. The COMBAT-TB Workbench executes each of these servers in Docker

containers and the execution of the COMBAT-TB Workbench as a whole is orchestrated

using docker-compose. The COMBAT-TB Workbench is deployed on any machine that

runs Docker and docker-compose by fetching its code from Github

(https://github.com/COMBAT-TB/irida-galaxy-deploy) and running a single command

("docker-compose up --build -d"). Updates to the Workbench are similarly applied using

a single command. The COMBAT-TB Workbench updates its IRIDA plugins from their

repositories on Github on startup.

Implementation of the *M. tuberculosis* Sample Report pipeline

The TB sample report workflow starts by running Trimmomatic (v. 0.38.1) with the

Sliding Window trimmer, truncating reads when the average quality within a four base

window drops below quality score 30, followed by the Minimum length trimmer that

discards reads shorter than 20 bases. Only reads which remain in read pairs after

quality trimming are used in subsequent analysis.

After quality trimming, sequence reads are mapped to a user supplied reference

genome. The workflow requires a genome with the same coordinate scheme as the *M.*

tuberculosis H37Rv reference (RefSeq NC000962). Mapping and variant calling is done

using snippy (v. 4.4.5), a Perl-based pipeline that combines the bwa-mem (v. 0.7.17)

(33) mapper and the freebayes (v. 1.3.2) (34) variant caller. Snippy has been shown

(35) to produce good quality variant calls in *M. tuberculosis* when run with default

parameters. Samtools (v. 1.9) (36) flagstat is run to provide an overview of statistics

from the mapping process.

After variant calling, variants are annotated with SnpEff (v. 4.3) (37) using the H37Rv

reference genome annotation. Variants are then filtered using tb_variant_filter (v. 0.1.3).

While snippy performs quality based filtering of the variants it predicts, this tool offers a

variety of filtering options commonly used in *M. tuberculosis* variant filtering. In our

workflow it filters out variants in the PE/PPE gene regions (38), in the repetitive and

insertion section regions identified by UVP (39) and those with lower than 30 supporting

reads or within 5 base pairs of an indel. These filtering options like all tool options in the

workflow can optionally be altered by the user.

In parallel to the SnpEff annotation and variant filtering steps, the mapped reads are

provided to TBProfiler (v. 2.8.4) which performs its own variant calling and lineage and

drug resistance prediction.

Finally the filtered, annotated variants and the TBProfiler results are fed to tb_vcf_report

(v. 0.1.7) which produces a report further annotated with information from the COMBAT-

TB eXplorer database (28) in both text and HTML formats.

The final reports provided to the user are the variant reports from tb_vcf_report, text and

JSON format reports from TBProfiler, variants in VCF format from SnpEff and mapping

statistics from samtools flagstats. These reports include both user readable and raw

data suitable for further downstream analysis. The metadata stored in the sample line

list is updated with mapping %, *M. tuberculosis* lineage and spoligotype information and

drug resistance information.

Implementation of the *M. tuberculosis* Phylogeny pipeline

The workflow in the phylogeny module starts with quality filtering of samples using fastp

(v. 0.19.5) (40) with default settings. The filtered reads are then aligned to the user

provided reference using snippy and predicted variants are filtered with tb_variant_filter

as described above. In addition, only single nucleotide variants (SNVs) are retained as

the phylogeny software used in the workflow cannot extract meaningful information from

indels.

For each sample, the identified sequence variants are inserted into the reference

genome, yielding one sequence per sample, of the same length as the reference but

with variants from the sample inserted. These are concatenated into a multiple

sequence alignment (MSA), which is used as input to snp_dists (v. 0.6.3). Variant and

constant sites are identified using snp_sites (v. 2.5.1) and the multiple sequence

alignment is filtered to retain only variant sites. A phylogeny is then built using IQ-TREE

(v. 1.5.5.1) (41–43).

The final report includes the SNP distance matrix and (Newick format) tree. The tree is

also visualised in a phylogeny viewer and can also be displayed with associated sample

metadata.

The SNP distance matrix, the phylogeny and the filtered variants (in VCF format) are

presented to the user as output.

Funding

357 This work was supported by The South African Research Chairs Initiatives of the

358 Department of Science and Technology and National Research Foundation of South

359 Africa grant UID 64751, and the South African Medical Research Council flagship

360 programme MRC-RFA-UFSP-01-2013/ COMBAT-TB.

References

1.   World Health Organization. 2020. Global tuberculosis report 2020. World Health

Organization.

2.   Meehan CJ, Goig GA, Kohl TA, Verboven L, Dippenaar A, Ezewudo M, Farhat MR,

Guthrie JL, Laukens K, Miotto P, Ofori-Anyinam B, Dreyer V, Supply P, Suresh A, Utpatel

C, van Soolingen D, Zhou Y, Ashton PM, Brites D, Cabibbe AM, de Jong BC, de Vos M,

Menardo F, Gagneux S, Gao Q, Heupink TH, Liu Q, Loiseau C, Rigouts L, Rodwell TC,

Tagliani E, Walker TM, Warren RM, Zhao Y, Zignol M, Schito M, Gardy J, Cirillo DM,

Niemann S, Comas I, Van Rie A. 2019. Whole genome sequencing of Mycobacterium

tuberculosis: current standards and open issues. Nat Rev Microbiol 17:533–545.

3.   Mahomed S, Naidoo K, Dookie N, Padayatchi N. 2017. Whole genome sequencing for the

management of drug-resistant TB in low income high TB burden settings: Challenges and

implications. Tuberculosis 107:137–143.

4.   Joppich M, Zimmer R. 2019. From command-line bioinformatics to bioGUI. PeerJ 7:e8111.

5.   Phelan JE, O'Sullivan DM, Machado D, Ramos J, Oppong YEA, Campino S, O'Grady J,

McNerney R, Hibberd ML, Viveiros M, Huggett JF, Clark TG. 2019. Integrating informatics

tools and portable sequencing technology for rapid detection of resistance to anti-

tuberculous drugs. Genome Med 11:41.

6.   Rosenthal A, Gabrielian A, Engle E, Hurt DE, Alexandru S, Crudu V, Sergueev E,

Kirichenko V, Lapitskii V, Snezhko E, Kovalev V, Astrovko A, Skrahina A, Taaffe J, Harris

M, Long A, Wollenberg K, Akhundova I, Ismayilova S, Skrahin A, Mammadbayov E,

Gadirova H, Abuzarov R, Seyfaddinova M, Avaliani Z, Strambu I, Zaharia D, Muntean A,

Ghita E, Bogdan M, Mindru R, Spinu V, Sora A, Ene C, Vashakidze S, Shubladze N,

Nanava U, Tuzikov A, Tartakovsky M. 2017. The TB Portals: an Open-Access, Web-Based

Platform for Global Drug-Resistant-Tuberculosis Data Sharing and Analysis. J Clin

Microbiol 55:3267–3282.

7.   Afgan E, Baker D, Batut B, van den Beek M, Bouvier D, Čech M, Chilton J, Clements D,

Coraor N, Grüning BA, Guerler A, Hillman-Jackson J, Hiltemann S, Jalili V, Rasche H,

Soranzo N, Goecks J, Taylor J, Nekrutenko A, Blankenberg D. 2018. The Galaxy platform

for accessible, reproducible and collaborative biomedical analyses: 2018 update. Nucleic

Acids Res 46:W537–W544.

8.   Matthews TC, Bristow FR, Griffiths EJ, Petkau A, Adam J, Dooley D, Kruczkiewicz P,

Curatcha J, Cabral J, Fornika D, Winsor GL, Courtot M, Bertelli C, Roudgar A, Feijao P,

Mabon P, Enns E, Thiessen J, Keddy A, Isaac-Renton J, Gardy JL, Tang P, Consortium

TI, Carrico JA, Chindelevitch L, Chauve C, Graham MR, McArthur AG, Taboada EN, Beiko

RG, Brinkman FS, Hsiao WW, Domselaar GV. 2018. The Integrated Rapid Infectious

Disease Analysis (IRIDA) Platform. bioRxiv 381830.

9.   MariaDB Foundation. 2021. MariaDB.org.

10. Bolger AM, Lohse M, Usadel B. 2014. Trimmomatic: a flexible trimmer for Illumina

sequence data. Bioinformatics 30:2114–2120.

11. Seemann T. 2020. snippy: Rapid haploid variant calling and core genome alignment. Perl.

12. Page AJ, Taylor B, Delaney AJ, Soares J, Seemann T, Keane JA, Harris SRY 2016. SNP-

sites: rapid efficient extraction of SNPs from multi-FASTA alignments. Microb Genomics

2:e000056.

13. Seemann T. 2021. snp-dists: Convert a FASTA alignment to SNP distance matrix. C.

14. Peter van Heusden. 2021. tb_variant_filter: A tool for filtering VCF files (relative to M.

tuberculosis H37Rv). Python.

15. Thoba Lose, Peter van Heusden. 2021. tbvcfreport: Generate an interactive HTML-based

report from M. tuberculosis SnpEff annotated VCF(s). Python.

16. Jeffrey Thiessen, Dan Fornika, Peter Kruczkiewicz, Aaron Petkau, Peter van Heusden.

2021. irida-wf-ga2xml: Create an IRIDA workflow from a Galaxy workflow file. Clojure,

National Microbiology Laboratory.

17. Docker. Docker Web Page.

18. Docker. 2021. Overview of Docker Compose. Docker Doc.

19.   Llarena A-K, Ribeiro-Gonçalves BF, Silva DN, Halkilahti J, Machado MP, Silva MSD,

Jaakkonen A, Isidro J, Hämäläinen C, Joenperä J, Borges V, Viera L, Gomes JP, Correia

C, Lunden J, Laukkanen-Ninios R, Fredriksson-Ahomaa M, Bikandi J, Millan RS, Martinez-

Ballesteros I, Laorden L, Mäesaar M, Grantina-Ievina L, Hilbert F, Garaizar J, Oleastro M,

Nevas M, Salmenlinna S, Hakkinen M, Carriço JA, Rossi M. 2018. INNUENDO: A cross-

sectoral platform for the integration of genomics in the surveillance of food-borne

pathogens. EFSA Support Publ 15:1498E.

20.   Di Tommaso P, Chatzou M, Floden EW, Barja PP, Palumbo E, Notredame C. 2017.

Nextflow enables reproducible computational workflows. Nat Biotechnol 35:316–319.

21.   Apache Software Foundation. Apache Tomcat®.

22.   Tania T, Sudarmono P, Kusumawati RL, Rukmana A, Pratama WA, Regmi SM,

Kaewprasert O, Chaiprasert A, Chongsuvivatwong V, Faksri K 2020. Whole-genome

sequencing analysis of multidrug-resistant Mycobacterium tuberculosis from Java,

Indonesia. J Med Microbiol 69:1013–1019.

23.   Jeffrey Thiessen, Darian Hole, Peter Kruczkiewicz, Peter van Heusden, Tom Matthews.

2021. IRIDA Uploader: Sequence file uploader for IRIDA. Python, National Microbiology

Laboratory.

24.   Simon Andrews. 2019. FastQC A Quality Control tool for High Throughput Sequence Data.

Babraham Bioinforma.

25.   Comas I, Chakravartti J, Small PM, Galagan J, Niemann S, Kremer K, Ernst JD, Gagneux

S. 2010. Human T cell epitopes of Mycobacterium tuberculosis are evolutionarily

hyperconserved. Nat Genet 42:498–503.

26.   Comas I. 2019. Genome of the inferred most recent common ancestor of the

Mycobacterium tuberculosis complex. Zenodo.

27.   Goig GA, Blanco S, Garcia-Basteiro A, Comas I. 2018. Pervasive contaminations in

sequencing experiments are a major source of false genetic variability: a

meta-analysis https://doi.org/10.1101/403824.

28.   Lose T, van Heusden P, Christoffels A. 2020. COMBAT-TB-NeoDB: fostering tuberculosis

444   research through integrative analysis using graph database technologies. Bioinforma Oxf

445   Engl 36:982–983.

446   29.   Wood DE, Lu J, Langmead B. 2019. Improved metagenomic analysis with Kraken 2.

447   Genome Biol 20:257.

448   30.   Starks AM, Gumusboga A, Plikaytis BB, Shinnick TM, Posey JE. 2009. Mutations at embB

449   codon 306 are an important molecular indicator of ethambutol resistance in Mycobacterium

450   tuberculosis. Antimicrob Agents Chemother 53:1061–1066.

451   31.   IRIDA Project. 2018. Add ability to use the results of an assembly workflow/assembled

452   genome as input to other workflows · Issue #57 · phac-nml/irida. GitHub.

453   32.   Xu Y, Cancino-Muñoz I, Torres-Puente M, Villamayor LM, Borrás R, Borrás-Máñez M,

454   Bosque M, Camarena JJ, Colomer-Roig E, Colomina J, Escribano I, Esparcia-Rodríguez

455   O, Gil-Brusola A, Gimeno C, Gimeno-Gascón A, Gomila-Sard B, González-Granda D,

456   Gonzalo-Jiménez N, Guna-Serrano MR, López-Hontangas JL, Martín-González C,

457   Moreno-Muñoz R, Navarro D, Navarro M, Orta N, Pérez E, Prat J, Rodríguez JC, Ruiz-

458   García MM, Vanaclocha H, Colijn C, Comas I. 2019. High-resolution mapping of

459   tuberculosis transmission: Whole genome sequencing and phylogenetic modelling of a

460   cohort from Valencia Region, Spain. PLOS Med 16:e1002961.

461   33.   Li H. 2013. Aligning sequence reads, clone sequences and assembly contigs with BWA-

462   MEM. ArXiv13033997 Q-Bio.

463   34.   Garrison E, Marth G. 2012. Haplotype-based variant detection from short-read sequencing.

464   ArXiv12073907 Q-Bio.

465   35.   Bush SJ, Foster D, Eyre DW, Clark EL, De Maio N, Shaw LP, Stoesser N, Peto TEA,

466   Crook DW, Walker AS. 2020. Genomic diversity affects the accuracy of bacterial single-

467   nucleotide polymorphism–calling pipelines. GigaScience 9.

36. Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N, Marth G, Abecasis G, Durbin

R, 1000 Genome Project Data Processing Subgroup. 2009. The Sequence Alignment/Map

format and SAMtools. Bioinformatics 25:2078–2079.

37. Cingolani P, Platts A, Wang LL, Coon M, Nguyen T, Wang L, Land SJ, Lu X, Ruden DM.

2012. A program for annotating and predicting the effects of single nucleotide

polymorphisms, SnpEff. Fly (Austin) 6:80–92.

38. Fishbein S, Wyk N van, Warren RM, Sampson SL. 2015. Phylogeny to function: PE/PPE

protein evolution and impact on Mycobacterium tuberculosis pathogenicity. Mol Microbiol

96:901–916.

39. Ezewudo M, Borens A, Chiner-Oms Á, Miotto P, Chindelevitch L, Starks AM, Hanna D,

Liwski R, Zignol M, Gilpin C, Niemann S, Kohl TA, Warren RM, Crook D, Gagneux S,

Hoffner S, Rodrigues C, Comas I, Engelthaler DM, Alland D, Rigouts L, Lange C, Dheda K,

Hasan R, McNerney R, Cirillo DM, Schito M, Rodwell TC, Posey J. 2018. Integrating

standardized whole genome sequence analysis with a global Mycobacterium tuberculosis

antibiotic resistance knowledgebase. Sci Rep 8:15382.

40. Chen S, Zhou Y, Chen Y, Gu J. 2018. fastp: an ultra-fast all-in-one FASTQ preprocessor.

Bioinformatics 34:i884–i890.

41. Minh BQ, Schmidt HA, Chernomor O, Schrempf D, Woodhams MD, von Haeseler A,

Lanfear R. 2020. IQ-TREE 2: New Models and Efficient Methods for Phylogenetic

Inference in the Genomic Era. Mol Biol Evol 37:1530–1534.

42. Hoang DT, Chernomor O, von Haeseler A, Minh BQ, Vinh LS. 2018. UFBoot2: Improving

the Ultrafast Bootstrap Approximation. Mol Biol Evol 35:518–522.

43. Kalyaanamoorthy S, Minh BQ, Wong TKF, von Haeseler A, Jermiin LS. 2017.

ModelFinder: fast model selection for accurate phylogenetic estimates. Nat Methods

14:587–589.

44. Thomas Matthews. 2021. Number of pathogen samples processed by PHAC-NML using

IRIDA.

499   Supplemental Figures

Supplementary Figure 1: Drug Resistance Report