LightOCT: Exploring the depth for Retinal disease detection

Amandeep Kaur[1], Vinayak Singh[2] and Gargi Chakraverty[2]

[1]Department of Information Technology, Indira Gandhi Delhi Technical University for Women, St. James Church,Kashmere Gate, New Delhi, 110018, Delhi, India.
[2]School of Computer Engineering, KIIT Deemed to be University, Bhubaneswar, 751024, Odisha, India.

Contributing authors: amandeep022btit18@igdtuw.ac.in; vinayaksooryavanshi@gmail.com; gargichakraverty2@gmail.com;

Abstract

With the advancement in technology and computation capabilities, identifying retinal damage through state-of-the-art CNNs architectures has led to the speedy and precise diagnosis, thus inhibiting further disease development. In this study, we focus on the classification of retinal damage caused by detecting choroidal neovascularization (CNV), diabetic macular edema (DME), DRUSEN, and NORMAL in optical coherence tomography (OCT) images. The emphasis of our experiment is to investigate the component of depth in the neural network architecture. We introduce a shallow convolution neural network - LightOCT, outperforming the other deep model configurations, with the lowest value of LVCEL and highest accuracy (+98% in each class). Next, we experimented to find the best fit optimizer for LightOCT. The results proved that the combination of LightOCT and Adam gave the most optimal results. Finally, we compare our approach with transfer learning models, and LightOCT outperforms the state-of-the-art models in terms of computational cost, least training time and gives comparable results in the criteria of accuracy. We would direct our future work to improve the accuracy metrics with shallow models such that the trade-off between training time and accuracy is reduced.

Keywords: OCT, neural network, CNN, medical-imaging

Fig. 1 Representative optical coherence tomography (OCT) images. (a) CNV - Choroidal neovascularization, (b) DME - Diabetic Macular Edema, (c) DRUSEN, (d) Normal Retina

1 Introduction

In the domain of healthcare, several imaging methods are deployed to scan the patient's modalities. In the era of deep learning and computer vision-based methods augmenting the efforts of radiologists, this domain is yet to utilize the full potential of the state-of-the-art proposed techniques in clinical settings. Non-invasive imaging methods like optical coherence tomography (OCT) have shown resolute images of retinal structures. Retinal image study plays a vital role in identifying and further classifying the damage in the retina. OCT images can penetrate through and detect the presence of edema, disruptions in the vasculature of the retina, or the collection of dangerous fluids, which could lead to loss of vision if not treated in the anticipated time. With the advancement in technology and computation powers, identifying retinal damage through state-of-the-art CNNs architectures has led to early and accurate diagnosis, thus preventing further disease development. We focus on the classification of retinal damage caused by detecting choroidal neovascularization (CNV), diabetic macular edema (DME), DRUSEN, and NORMAL in optical coherence tomography (OCT) image. We propose LightOCT, a lightweight architecture that can classify the OCT images accurately with their corresponding labels with 98% accuracy in each class. Compared to all other architectures, LightOCT had the least loss, the highest accuracy, and the shortest training time.

The main contributions of this paper are as follows:

- We propose a shallow convolution neural network - LightOCT, for the classification of retinal diseases, with regularization techniques to accelerate convergence and improve accuracy. LightOCT outperformed the other deep model configurations, with the lowest value of Least Validation Cross-Entropy Loss(LVCEL) as 0.2018 and the highest accuracy for each class.
- We experimented to find the best fit optimizer for LightOCT. Adam and RMSProp give comparable results, but the F1 score of the former is better than RMSProp. Thus, the combination of Adam and LightOCT is selected for analysis.
- Next, a comparative analysis of the state-of-the-art transfer learning models and our architecture is conducted. Our model proves to be computationally efficient and requires the least training time.

2 Related Work

Lemaître et al. [1]introduced a technique based on local binary pattern feature extraction from OCT images and bag of words model for DME detection, with a sensitivity of 81.2% and specificity of 93.7%. But, the effects of pre-processing differ depending on the classifier and feature configuration. Deep learning was applied by Gulshan et al. [2] to detect diabetic retinopathy and DME, achieving a sensitivity of 90.3% and specificity 98.1% on the EyePACS-1 dataset and 87.0% sensitivity and 98.5% specificity on the Messidor-2 dataset. But the drawback is that they are computationally expensive. Alsaih et al. [3]used a support vector machine(SVM) to categorize normal retina and DME with an 87.5% specificity and sensitivity for experimentation on a proprietary dataset. But the limitation is the relatively small dataset used for analysis. Karri et al.[4] proposed a transfer learning based on an Inception network to categorize retinal OCT images into AMD, DME, and Normal with a mean prediction accuracy of 89%, 86%, and 99% respectively. Accuracy should not be recognized as the sole evaluation metric. The paper emphasized only two retinal diseases, but in clinical settings, multi-categorical abnormalities have more commonplace. For many medical imaging tasks, machine learning techniques have given state-of-the-art results. Hussain et al. [5]propose to use a random forest classifier for classifying healthy OCT images from infected ones with a mean accuracy of 96%. However, in the presence of severe pathologies, the model may fail to detect the retinal layers.

Srinivasan et al.[6] used histogram of oriented gradients (HOG) descriptors and SVM classifiers for detecting AMD, DME, and normal retina, attaining accuracies nearly 100%, 100%, and 88.87% respectively. One major drawback of such approaches is their reliance on features/markings defined by ophthalmologists, which may lead to delayed and inefficient generalization, further questioning the feasibility of this approach on larger datasets. Ten et al.[7] using a ten-fold cross-validation strategy and deep convolution neural network(CNN), detected AMD with a mean accuracy of 95.45%, the sensitivity of 96.43%, and specificity of 93.75%. Lu et al. [8] proposed to detect and differentiates multi-categorical abnormalities from OCT images automatically; in their work, the image dataset is randomly divided into train, validation, and test at the image level, which may lead to a bias, as multiple images from the same eye could be present in different partitions. Though their mean accuracy is 95.9%, with 97.3% specificity and 94.0% sensitivity, the model's performance is partial. Li et al.[9] use the VGG-16 network to obtain the classification results on AMD and DME, with 98.6% accuracy, a 97.8% sensitivity, a 99.4% specificity, but since the validation set of 1000 images was used as the testing set, the results of the model may be biased. Kermany et al. [10] used the Inception V3 network to report an accuracy of 96.6%, with a sensitivity of 97.8%, and specificity of 97.4%, by performing occlusion, they tried to detect the areas contributing richly to the neural net's final prediction. But the model suffers a vanishing gradient problem, which could affect the results. Fauw et

4   *LightOCT: Exploring the depth for Retinal disease detection*

Table 1 Literature review: Details and results of the existing methods for retinal disease detection using OCT

Ref	Method	Results	Limitation
[1]	BoW and local binary pattern feature	Sensitivity of 81.2%, specificity of 93.7% for DME detection	Effects of pre-processing differ depending on the classifier and feature configuration
[2]	Deep learning	Sensitivity of 90.3% and specificity 98.1% on the EyePACS-1 dataset and 87.0% sensitivity and 98.5% specificity on the Messidor-2 dataset	Computationally expensive
[3]	Support Vector Machine(SVM)	Sensitivity and specificity of 87.5% to categorize normal retina and DME on a proprietary dataset	Small dataset used for analysis
[4]	Transfer learning based on an Inception network	AMD, DME, and Normal with a mean prediction accuracy of 89%, 86%, and 99% respectively	Paper emphasized only two retinal diseases
[5]	Random forest classifier	Mean accuarcy 96%	In severe pathologies, detection of the retinal layers may fail
[6]	Histogram of oriented gradients (HOG) descriptors and SVM classifiers	Attaining accuracies for Detecting of AMD, DME, and normal retina as 100%, 100%, and 88.87% respectively	Delayed and inefficient generalization
[7]	Deep Convolution Neural Network(CNN)	Detected AMD with mean accuracy of 95.45%, sensitivity of 96.43%, and specificity of 93.75%	Small dataset used for analysis
[8]	Convolution Neural Network(CNN) - ResNet 101	Mean accuracy is 95.9%, with 97.3% specificity and 94.0% sensitivity	Performance of the model is partial as tested on validation test set
[9]	Convolution Neural Network(CNN) - VGG 16	Classification results on AMD and DME, with 98.6% accuracy, a 97.8% sensitivity, a 99.4% specificity	Performance of the model is partial as tested on validation test set
[10]	Inception V3 network, performed occlusion	Accuracy of 96.6%, with a sensitivity of 97.8%, and a specificity of 97.4%	Model suffers a vanishing gradient problem
[11]	Ensemble of U-net and DenseNet	Accuracies on the testing dataset 1 (Device Type 1) was 94.5% and on the testing dataset 2 (Device Type 2) was 96.6%	Time complexity

al. [11] developed an ensemble of segmentation(U-net) and classification networks(DenseNet) to detect OCT scans. The accuracy of testing dataset 1 was 94.5%, and on the testing dataset 2 was 96.6%. The major drawback was the time complexity. Table 1 summarizes the existing methods.

3 Methodology

3.1 Convolution Neural Networks (CNNs)

Convolution Neural Networks (CNNs) have proven to be the top-performing architectures for visual data, especially in the field of computer vision. CNN's have shown exemplary performance in image classification, segmentation, detection, and related tasks, Cirega et al.[12] The use of this technology ranges beyond academia, with big corporates(Microsoft, Meta, Google, AT&T) having their research groups actively exploring the benefits of CNNs. The most prominent feature of CNN is its ability to utilize spatial as well as temporal correlation data. Introduced through the work of LeCun et al. [13], CNN learns through the back-propagation algorithm during the training phase, with the architecture containing alternate layers of convolution and pooling, succeeded by the final layers, which are fully connected.

The following subsections detail the internal structures of various layers in the CNN.

3.1.1 Convolutional Layer

The convolutional layer is made up of a set of kernels with each neuron acting as a kernel.[14]. These kernels further divide the image into small patches called receptive fields. Finally, features are extracted from these fields. The kernel convolves through the image with weights by multiplying its elements with the corresponding parts of the receptive field, Bouvrie et al.[15]

$$C_l^k(p, q) = \sum_c \sum_{x,y} i_c(x, y) \cdot e_l^k(u, v)$$

where $i_c(x, y)$ is an element of the input image tensor I_C, which is element wise multiplied by $e_l^k(u, v)$ index of the k th convolutional kernel k_l of the l th layer. Whereas output feature-map of the k th convolutional operation can be expressed as $\mathbf{C}_l^k = \left[c_l^k(1, 1), \ldots, c_l^k(p, q), \ldots, c_l^k(P, Q) \right]$

3.1.2 Pooling layer

The use of the pooling operation aids in the extraction of a combination of features that are insensitive to translational shifts and minor distortions, Huang et al. [16]

$$\mathbf{Z}_l^k = g_p \left(\mathbf{C}_l^k \right)$$

Equation (2) shows the pooling operation in which $\mathbf{Z}_l^k$ represents the pooled featuremap of l th layer for k th input feature-map $\mathbf{C}_l^k$, whereas $g_p(.)$ defines the type of pooling operation.

3.1.3 Activation function

The activation function acts as a decision function and aids in the learning of complex patterns.

$$\mathbf{O}_l^k = g_a \left(\mathbf{C}_l^k \right)$$

In the above equation, $\mathbf{O}_l^k$ is an output of a convolution, which is assigned to activation function $g_a(.)$ that adds non-linearity and returns a transformed output $\mathbf{O}_l^k$ for l th layer.

3.1.4 Batch normalisation

Batch normalisation is used to solve problems caused by internal covariance shifts in feature-maps.

$$\mathbf{N}_l^k = \frac{\mathbf{C}_l^k - \mu_B}{\sqrt{\sigma_B^2 + \varepsilon}}$$

Where $\mathbf{N}_l^k$ represents normalized feature-map, $\mathbf{C}_l^k$ is the input feature-map, μ_B and σ_B^2 depict mean and variance of a feature-map for a mini batch respectively. In order to avoid division by zero, ε is added for numerical stability.

By setting the distribution of feature-map values to zero mean and unit variance, batch normalisation unifies their distribution, as stated by Szegedy et al.[17]

3.2 Optimizer

Optimizers are responsible for changing the attributes of a neural network, such as the hyperparameters like learning rate and weight, for reducing the loss. We experimented to find the best fit optimizer for the proposed architecture - LightOCT. For our experiments, we tried various optimizers as shown in Fig 2.

- **Adam**
  Kingma et al.[18] proposed Adam stands for adaptive moment estimation. Instead of the classical gradient descent procedure, it is based on the adaptive analysis of first and second-order moments. It combines the advantages of two other extensions of stochastic gradient descent; SGD with momentum and RMSProp, providing an optimization algorithm that can handle sparse gradients on noisy problems.

$$W = W - \alpha \frac{v_{dW}^{\text{corrected}}}{\sqrt{s_{dW}^{\text{corrected}} + \varepsilon}} \tag{1}$$

  Here W is the weight of matrix, α is the learning rate, v_{dW} is the exponentially weighted average of past gradients and s_{dW} is the exponentially weighted average of past squares of gradients with ε as a small value to avoid dividing by zero.

  In our experiment, Adam gives the least LVCEL value with maximum MVA with LightOCT, as seen in Table 4.

- **RMSProp**
  Geoff Hinton proposed RMSprop, which stands for Root Mean Square Propagation. It is a gradient-based optimization technique for mini-batch learning. It deals with the issue of vanishing gradients in very complex

Fig. 2   Various optimizers used

functions of neural networks by using a moving average of squared gradients to normalize the gradient. RMS-Prop combines momentum with AdaGrad.

$$W = W - \alpha \frac{\frac{\partial J}{\partial W}}{\sqrt{s_{dW}^{\text{corrected}}} + \varepsilon} \tag{2}$$

Here, W is the weight tensor, $\frac{\partial J}{\partial W}$ refers to the cost gradient wrt to current W, and s_{dW} is the exponentially weighted average of past squares of gradients with ε as a small value to avoid dividing by zero.

With the proposed model, RMSProp gave the second highest MVA and second least LVCEL value. The results are comparable with Adam, but the F1 score for Adam is better than RMSProp. Refer Table 4.

- **SGD**
  Stochastic gradient descent (SGD), an iterative optimization technique, gives a stochastic approximation. It is used in high-dimensional optimization problems to reduce the computational burden and achieve faster iterations in trade for a lower convergence rate.

$$w_{t+1} = w_t - \alpha \frac{\partial L}{\partial w_t} \tag{3}$$

Here, $\frac{\partial L}{\partial w}$ refers the gradient of L, the loss function to minimise, w.r.t. to w, α as the learning rate, t, the time step and w is the weight/parameter which needs to be updated where the subscript t indexes the weight at time step t.

SGD result on MVA is close to 91% but it's LVCEL value is higher than the former two optimizers.

- **AdaGrad**
  Adagrad(short for adaptive gradient) is an optimizer wherein learning rates are parameter-specific. Learning rates are adapted relative to how frequently a parameter gets updated during training and are inversely proportional to the sum of the square of all the previous gradients of the parameter.

$$w_{t+1} = w_t - \frac{\alpha}{\sqrt{v_t + \epsilon}} \cdot \frac{\partial L}{\partial w_t}$$

where

$$v_t = v_{t-1} + \left[\frac{\partial L}{\partial w_t}\right]^2$$

$\frac{\partial L}{\partial w}$ is the gradient of L, the loss function to minimise, w.r.t. to w, α is the learning rate, t implies the time step, w is the weight/parameter which we want to update where the subscript t indexes the weight at time step t, additionally, v is the cumulative sum of current and past squared gradients(upto time t), initialized to o and ε is a small floating point value to ensure that we will never have to come across division by zero.

AdaGrad reaches an MVA of just 83% with a 2 times increase in LVCEL value as compared to RMSProp.

- **AdaDelta**

  Matthew D. Zeiler [19] proposed Adadelta, which is an optimization algorithm that was created with the goal of addressing two drawbacks of the Adagrad method: the decaying learning rate problem throughout training and the need to select a global learning rate manually. Instead of accumulating all past squared gradients, Adadelta adapts the learning rate by limiting the accumulated previous gradients using a moving window of fixed size. We express Adadelta's equation as

$$w_t = w_{t-1} - \eta'_t \frac{\partial L}{\partial w_{t-1}} \tag{4}$$

  where w is the weight tensor,

  $\eta'_t = \frac{\eta}{\sqrt{\alpha_t + \varepsilon}}$, $\alpha_t = \sum_{i=1}^{t} \left(\frac{\partial L}{\partial w_{t-1}} \right)^2$ summation of gradient square and ε is a small + ve number to avoid divisibilty by 0.

  AdaDelta managed to reach an MVA of 71% with a 4 times increase in value of LVCEL when compared to Adam.

3.2.1 Loss Function

Loss functions can be defined as a prediction error of neural networks. Gradients are used to update the weights of a neural net, and the Loss is used to calculate them. For our experiment, we tried two loss functions - sparse categorical cross-entropy and Square-hinge loss.

- **Sparse categorical cross-entropy**

  Cross-entropy loss is used when adjusting model weights during training. Mathematically, it is defined as:

$$L_{CE} = -\sum_{i=1}^{n} t_i \log (p_i), \text{ for n classes} \tag{5}$$

  where t_i is the truth label and p_i is the Softmax probability for the i^{th} class.

  Sparse categorical cross-entropy has the same loss function as defined in the above equation and is used when we have integers instead of categorical vectors as targets.

- **Square-hinge**

  The hinge loss function primarily developed with Support Vector Machine (SVM) models encourages examples to have the correct sign and assign more error when there is a difference in the sign between the predicted and actual class values. It smoothens the surface of the error function, thus making it numerically easier to work with. It has many extensions-Squared hinge loss, which calculates the square of the score hinge loss. Like the hinge loss function, we must modify the target variable to have values in the set [-1, 1]. Hinge loss of the prediction y is defined as :

$$\ell(y) = \max(0, 1 - t \cdot y) \tag{6}$$

  Here y should be the 'raw' output of the classifier's decision function,not the predicted class label. For squared Hinge loss we calculate the square of the above score hinge loss.

$$L(y, \hat{y}) = \sum_{i=0}^{N} \left(\max\left(0, 1 - y_i \cdot \hat{y}_i\right)^2 \right) \tag{7}$$

  where is the $\hat{y}$ the predicted value and y is either 1 or -1

3.3 Proposed Approach

We implemented various configured CNN architectures in which base models were classified into three categories - LightOCT, MediumOCT, and Heavy-OCT, the configurations of those are listed in Table 2. Compared to the other two architectures, LightOCT had the fewest parameters, resulting in less training time. As a result of the relationship, we can conclude that parameters are directly proportional to training time. Because LightOCT had the fewest parameters, the proposed model also reduced training time. For training and selecting the best-configured architecture, the Adam optimizer was used as a base optimizer. HeavyOCT had 2.4 million parameters, which required more training time. We also tried regularization techniques - batch normalization and dropouts for the models. Adam optimizer was used for the initial implementation, and we found the optimal learning rate as $1.00e - 05$.

   We selected LightOCT as our final model for further analysis. In LightOCT, we used batch normalization to accelerate convergence and improve accuracy.

Table 2 Configuration of CNN architectures

Model Name	CL[1]	AL[2]	Parameters	Optimizer Used	Learning Rate of Optimizer	BN [3]	DO [4]	FD[5]	DL [6]	KS [7]	PS [8]
LightOCT	3	2	240,820	Adam	1.00E-05	✓	×	(32,64,128)	{16,32}	(3,3,3)	(2,2,2)
MediumOCT	4	3	426,388	Adam	1.00E-05	×	✓	(32,64,64,128)	{16,64,128}	(3,3,3,6)	(2,2,2,4)
HeavyOCT	6	6	2,406,788	Adam	1.00E-05	✓	✓	(32,32,64, 64,128,128)	{16,16,64, 128,256, 256}	(3,3,3,6,9,9)	(2,2,2, 2,2,2)

[1]Convolution Layer, [2]Artificial Layer, [3]Batch Normalisation, [4] Dropout,[5] Feature Detected, [6]Dense Layer, [7]Kernel Size, [8]Pooling Size

Fig. 3 Architecture of proposed model - LightOCT

As seen in Fig. 3, our model consists of 3 convolution layers with varying kernel sizes, followed by a 2 x 2 max-pooling layer and 2 fully connected dense layers, predicting the output for the 4 classes, with Adam as the optimizer.

3.4 Comparative analysis with Transfer learning

Transferring learning is an essential technique in deep learning because it produces accurate models in a short period. Rather than starting from scratch, the model in this technique learns from patterns previously used to solve a different problem. We employ pre-trained models that have been trained on benchmark data sets such as ImageNet [20], CIFAR-10 Dataset [21], PASCAL VOC Dataset [22], and others. This section provides an overview of the pre-trained models that were used in our analysis.

- VGG
  Simonyan and Zisserman [23] introduced the revolutionary VGG Network, which is a Spatial Exploitation based CNN. A 224 x 224 RGB image is used as the input to the VGG-based convNet. The preprocessing layer subtracts the mean image values (derived for the entire ImageNet training set) from the RGB image (with pixel values in the range of 0–255). After preprocessing, the input images are passed through these weight layers. The training images are passed through a stack of convolution layers. In the VGG16 architecture, there are a total of 13 convolutional layers and three fully connected layers. Instead of having large filters, VGG features smaller filters (3 x 3) with more depth. It has the same effective receptive field as if only one 7×7 convolutional layers were used. Another VGGNet variant has 19 weight layers (16 convolutional layers and three fully connected layers) and five pooling layers. Two fully connected layers with 4096 channels each, followed by another fully connected layer with 1000 channels to predict 1000 labels are present in both variations of VGGNet(VGG19 and VGG16). The softmax layer is used for classification in the last fully connected layer. VGG performed well in both image classification and localization problems. VGG finished second in the 2014-ILSVRC competition but rose to prominence

Fig. 4 Residual Learning: A building block

due to its simplicity, homogeneous topology, and increased depth. The use of 138 million parameters was the main limitation of VGG, making it computationally expensive and difficult to deploy on low-resource systems.

- ResNet
  He et al. [24] introduced ResNet50, which features a four-stage architecture. ResNet is depth-based and multi-path-based CNN. This architecture is widely used; even with many layers, training can be done easily without an increase in error percentage. Another advantage is that by using identity mapping, ResNets aid in addressing the vanishing gradient problem. The input image supplied to the network has height, width as multiples of 32, and a channel width of 3. The input size is typically 224 x 224 x 3. This design uses 7 x 7 and 3 x 3 kernel sizes to perform initial convolution and max-pooling. The first stage of the network consists of three Residual blocks as shown in Fig 4, each with three layers. The kernel sizes for the convolution process in stage 1's three layers are 64, 64, and 128. The Residual Block's convolution operation uses a stride of 2, which means that the input size is reduced to half in terms of height and width, but the channel width is doubled. Each stage doubles the width of the channel while the input size gets reduced to half. Deeper networks, such as ResNet 50, ResNet101, and ResNet152, incorporate bottleneck design. A Bottleneck Residual Block is a form of a residual block that creates a bottleneck using 1x1 convolutions. To increase the depth and decrease parameters, we make residual blocks as thin as feasible. For each residual function F, the three layers with 1 x 1, 3 x 3, and 1 x 1 convolutions are stacked one on top of the other. An Average Pooling layer, followed by a fully connected layer, completes the network. ResNet won the 2015-ILSVRC competition with its 152-layer deep CNN proposal.

- Inception
  The computational efficiency of training more extensive networks was of special interest to the authors of Inception [25]. Inception has width-based multi-connection CNN architecture. Inception modules perform many different transformations over the same input map, concatenating the results into a single output. In other words, Inception does a 5 x 5 convolutional

transformation, a 3 x 3, and a max-pool for each layer. And the next layer of the model gets to decide if (and how) to use each piece of information. For dimensionality reduction, 1 x 1 convolutions are used. 1 x 1 convolutions are used to "filter" the outputs' depth to solve the computational bottleneck. A 1 x 1 convolution only looks at one value simultaneously, but it can extract spatial information and compress it down to a lower dimension when used across multiple channels. The authors of Inception were able to stack different layer transformations in parallel by reducing the number of input maps, resulting in nets that were both deep (many layers) and "wide" (many parallel operations).

- Xception
  Chollet [26] introduced Xception which stands for "Extreme Inception". And, as the name implies, it takes Inception's principles to an extreme. Instead of partitioning input data into many compressed chunks, Xception maps the spatial correlations for each output channel separately, then performs a 1 x 1 depthwise convolution to capture cross-channel correlation. On the ImageNet dataset, Xception slightly outperforms Inception V3 but vastly outperforms it on a more extensive image classification dataset with 17,000 classes. It also has the same number of model parameters as Inception, implying a greater computational efficiency. As stated in [27], Xception simplifies computation by convolving each feature-map separately across spatial axes, which is succeeded by pointwise convolution (1 x 1 convolutions) to perform cross-channel correlation.

4 Experimental Setup

4.1 Dataset

The present research used 84,495 optical coherence tomography (OCT) images collected by Kermany et al. in[28] from various tertiary hospitals [Beijing Tongren Eye Center, California Retinal Research Foundation, Shiley Eye Institute of the University of California San Diego, Shanghai First People's Hospital, Medical Center Ophthalmology Associates] between July 1, 2013, and March 1, 2017. The data set has been clinically approved. Each OCT image was graded using a multi-tiered system. The initial grading round was completed by undergraduate and medical students who had completed an OCT review course. This group discarded any OCT images with artifacts or poor image resolution. The images passed on by the first group were approved or disapproved by the next tier of four ophthalmologists. They detected the presence or absence of various pathologies visible on the OCT based on their level of expertise. The truth labels for each image were validated by the final tier, which consisted of two retinal specialists with over 20 years of clinical experience. In addition, to account for human error in grading, a validation subset of 993 OCT images was verified by two additional ophthalmologist graders. The

Table 3 Metric Evaluation of CNN models

Model Name	MVA	LVCEL	Class	Testing Accuracy	Testing Precision	Testing Recall	Testing F1 Score	Confusion Matrix			
LightOCT	0.9357	0.2018	CNV	0.9876	0.99	0.96	0.98	240	2	0	0
			DME	0.9907	0.97	0.99	0.98	6	235	1	0
			DRUSEN	0.9845	0.98	0.96	0.97	4	0	238	0
			NORMAL	0.9897	0.96	1.0	0.98	0	0	10	232
MediumOCT	0.7986	0.5583	CNV	0.8791	0.98	0.68	0.80	236	6	0	0
			DME	0.9008	0.72	0.86	0.78	24	175	3	40
			DRUSEN	0.7965	0.20	0.94	0.33	87	22	48	85
			NORMAL	0.9897	0.96	1.0	0.98	0	0	10	232
HeavyOCT	0.8421	0.4405	CNV	0.9566	0.98	0.87	0.92	236	5	1	0
			DME	0.9442	0.91	0.87	0.89	3	221	1	17
			DRUSEN	0.8874	0.56	0.99	0.71	33	27	135	47
			NORMAL	0.9329	1.0	0.79	0.88	0	1	0	241

Table 4 Metric evaluation of LightOCT with different optimizers

Optimizer	MVA	LVCEL	Class	Testing Accuracy	Testing Precision	Testing Recall	Testing F1 Score	Confusion Matrix			
Adam	0.9357	0.2018	CNV	0.9876	0.99	0.96	0.98	240	2	0	0
			DME	0.9907	0.97	0.99	0.98	6	235	1	0
			DRUSEN	0.9845	0.98	0.96	0.97	4	0	238	0
			NORMAL	0.9897	0.96	1.0	0.98	0	0	10	232
RMSProp	0.9248	0.2248	CNV	0.9421	0.98	0.82	0.89	238	0	0	4
			DME	0.8337	0.33	1.0	0.50	29	81	1	131
			DRUSEN	0.9587	0.84	1.0	0.91	23	0	203	16
			NORMAL	0.8440	1.0	0.62	0.76	0	0	0	242
SGD	0.9079	0.2694	CNV	0.8122	0.69	0.61	0.65	167	75	0	0
			DME	0.5810	1.0	0.37	0.54	0	242	0	0
			DRUSEN	0.7750	0.10	0.96	0.19	107	110	25	0
			NORMAL	0.7730	0.091	1.0	0.17	0	220	0	22
AdaGrad	0.8384	0.4535	CNV	0.9132	0.98	0.75	0.85	236	5	1	0
			DME	0.9494	0.88	0.92	0.90	10	212	0	20
			DRUSEN	0.8688	0.48	0.98	0.65	68	13	117	44
			NORMAL	0.9318	0.99	0.79	0.88	0	1	1	240
AdaDelta	0.7112	0.8020	CNV	0.8347	0.96	0.61	0.74	233	4	0	5
			DME	0.8068	0.31	0.78	0.45	62	76	4	100
			DRUSEN	0.7655	0.079	0.83	0.14	88	17	19	118
			NORMAL	0.7686	1.0	0.52	0.68	1	0	0	241

final dataset contains 37,205 class CNV, 11,348 showing DME, 8616 showing drusen, and 26,315 standard images. The test data has 242 images from each class.

5 Results and Evaluation

According to Table 3, LightOCT performed exceptionally well, achieving the highest accuracy for each class on test data. LightOCT had a minimum LVCEL of 0.2018 as well. Compared to other architectures, MediumOCT had the lowest validation accuracy while the recall value gained by each class of LightOCT was extremely high. A comparitive analysis of performance between the different configurations tried is shown in the Fig. 5. As a result, we chose LightOCT as the most suitable architecture for further consideration.

Next, we tested various optimizers to find the best fit for our LightOCT architecture. Table 4 shows that the results obtained by default Adam were very high when compared to other optimizers. AdaDelta produced inferior results, and LVCEL was more significant with the least value of MVA. As a result, we withdraw from using Adadelta for our LightOCT. RMSProp was a close competitor for Adam, with RMSprop gaining 0.9248 accuracies and Adam trailing by 0.9357. When Adam was used in conjunction with LightOCT, F1 scores in each class were extremely high. We finally chose the combination of Adam and LightOCT to be the best optimal condition for detecting Retinal disease

Table 5 Comparative analysis of Light with transfer learning models

Model	MVA	LVCEL	Class	Testing Accuracy	Testing Precision	Testing Recall	Testing F1 Score	Confusion Matrix			
VGG16	0.8595	0.3665	CNV	0.9220	0.99	0.77	0.86	242	1	0	1
			DME	0.9435	0.79	0.98	0.87	12	192	1	39
			DRUSEN	0.9148	0.66	0.99	0.80	62	2	162	18
			NORMAL	0.9405	1.0	0.81	0.89	0	0	0	242
VGG19	0.7117	0.5798	CNV	0.8088	1.0	0.57	0.72	242	1	0	0
			DME	0.8906	0.57	0.99	0.73	24	142	6	76
			DRUSEN	0.8149	0.29	0.92	0.44	162	0	70	13
			NORMAL	0.9090	1.0	0.73	0.84	0	0	0	242
ResNet50	0.9524	0.1326	CNV	0.9888	1.0	0.96	0.98	242	0	0	0
			DME	0.9959	0.98	1.0	0.99	4	242	0	0
			DRUSEN	0.9928	0.97	1.0	0.99	7	0	242	0
			NORMAL	1.0000	1.0	1.0	1.0	0	0	0	242
ResNet101	0.9225	0.1791	CNV	0.9291	1.0	0.78	0.88	242	0	0	0
			DME	0.9969	0.99	1.0	0.99	2	242	0	1
			DRUSEN	0.9260	0.70	1.0	0.83	67	0	172	5
			NORMAL	0.9938	1.0	0.98	0.99	0	0	0	242
ResNet152	0.9576	0.1166	CNV	0.9598	1.0	0.86	0.93	242	1	0	0
			DME	0.9897	0.97	0.99	0.98	7	232	0	1
			DRUSEN	0.9680	0.87	1.0	0.93	31	0	212	0
			NORMAL	0.9979	1.0	1.0	1.0	0	1	0	242
InceptionV3	0.5898	2.3727	CNV	0.7708	0.094	0.96	0.17	23	222	0	0
			DME	0.6012	1.0	0.38	0.56	0	242	0	0
			DRUSEN	0.8222	0.28	1.0	0.44	1	162	67	10
			NORMAL	0.9856	0.99	0.96	0.97	0	3	0	242
Xception	0.6477	2.1132	CNV	0.7933	0.18	0.98	0.31	45	202	0	0
			DME	0.6527	1.0	0.42	0.59	0	242	0	0
			DRUSEN	0.8554	0.42	1.0	0.59	0	132	102	9
			NORMAL	0.9837	0.97	0.96	0.97	0	7	0	242
LightOCT	0.9357	0.2018	CNV	0.9876	0.99	0.96	0.98	240	2	0	0
			DME	0.9907	0.97	0.99	0.98	6	235	1	0
			DRUSEN	0.9845	0.98	0.96	0.97	4	0	238	0
			NORMAL	0.9897	0.96	1.0	0.98	0	0	10	232

using OCT images. A comparitive analysis of performance between the different optimizers tried with the architecture LightOCT is shown in the Fig. 6.

The comparison of our architecture with transfer learning models is shown in Table 5. ResNet50 and ResNet152 outperformed LightOCT in terms of accuracy, but our architecture beats all other transfer learning models when it comes to low computational cost. When compared to other transfer learning models, LightOCT required the least amount of training time. The time required for training by VGG19 and VGG16 was huge, as was the computational cost. The results obtained were less-comparable. Xception had a considerable loss of 2.1132 and a short accuracy gain of 0.6477. The metric evaluation of all transfer learning models is shown in Table 5. Compared to all other architectures as seen in Fig. 7, LightOCT had the least loss, the highest accuracy gained, and the shortest training time. As a result, LightOCT proves to be the most influential architecture for detecting retinal disease using Optical Coherence Tomography images, which is computationally low in cost. Since our model performs efficiently in both time-complexity as well as computational costs, we also provide the activation of the neural network on the four classes, as shown in Fig 8 and Fig 9 to analyze more profoundly into the explainability part of the predictions.

6 Discussion and Conclusion

In the present research, we examined the depth component in CNN architecture for retinal disease detection in Optical Coherence Tomography(OCT)

Fig. 5 (a) Represents metric evaluation of the proposed architectures, LightOCT, MediumOCT and HeavyOCT, (b) Metric result with the final proposed architecture LightOCT

Fig. 6 Metric evaluation of Optimizers - Adam, RMSProp, SGD, AdaGrad, AdaDelta with proposed architecture LightOCT

Fig. 7 Metric evaluation of LightOCT with transfer learning models - VGG16, VGG19, ResNet50, ResNet101, InceptionV3 and Xception.

images. Our results prove that shallow-feed forward neural networks can learn complex features and achieve comparable accuracies when compared with deep models, even on a small clinical dataset. In our analysis, we performed three experiments to validate our hypothesis. Firstly, we compare the architectures based on their depth, parameters, and regularization techniques used. The proposed architecture - LightOCT outperformed the other deep model configurations, with the lowest value of LVCEL as 0.2018 and the highest accuracy

for each class. Secondly, we experimented to find the best fit optimizer for LightOCT. Even though Adam and RMSProp gave comparable results, the former exceeded RMSProp by an accuracy value differing a few decimal points. Finally, we chose the combination of LightOCT and Adam as the optimal architecture for our comparison. The last experiment was conducted on the comparative analysis of the state-of-the-art transfer learning models and our architecture. Even though ResNet variants outperformed LightOCT in the accuracy metric by some trailing decimal points, our proposed model is computationally efficient, and required the least training time, and gave comparable results with them. We would direct our future work to improve the accuracy metrics with shallow models such that the trade-off between training time and accuracy is reduced.

References

[1] Lemaître, G., Rastgoo, M., Massich, J., Cheung, C.Y., Wong, T.Y., Lamoureux, E., Milea, D., Mériaudeau, F., Sidibé, D.: Classification of sd-oct volumes using local binary patterns: experimental validation for dme detection. Journal of ophthalmology **2016** (2016)

[2] Gulshan, V., Peng, L., Coram, M., Stumpe, M.C., Wu, D., Narayanaswamy, A., Venugopalan, S., Widner, K., Madams, T., Cuadros, J., *et al.*: Development and validation of a deep learning algorithm for detection of diabetic retinopathy in retinal fundus photographs. Jama **316**(22), 2402–2410 (2016)

[3] Alsaih, K., Lemaitre, G., Rastgoo, M., Massich, J., Sidibé, D., Meriaudeau, F.: Machine learning techniques for diabetic macular edema (dme) classification on sd-oct images. Biomedical engineering online **16**(1), 1–12 (2017)

[4] Karri, S.P.K., Chakraborty, D., Chatterjee, J.: Transfer learning based classification of optical coherence tomography images with diabetic macular edema and dry age-related macular degeneration. Biomedical optics express **8**(2), 579–592 (2017)

[5] Hussain, M.A., Bhuiyan, A., D. Luu, C., Theodore Smith, R., H. Guymer, R., Ishikawa, H., S. Schuman, J., Ramamohanarao, K.: Classification of healthy and diseased retina using sd-oct imaging and random forest algorithm. PloS one **13**(6), 0198281 (2018)

[6] Srinivasan, P.P., Kim, L.A., Mettu, P.S., Cousins, S.W., Comer, G.M., Izatt, J.A., Farsiu, S.: Fully automated detection of diabetic macular edema and dry age-related macular degeneration from optical coherence tomography images. Biomedical optics express **5**(10), 3568–3577 (2014)

[7] Tan, J.H., Bhandary, S.V., Sivaprasad, S., Hagiwara, Y., Bagchi, A., Raghavendra, U., Rao, A.K., Raju, B., Shetty, N.S., Gertych, A., *et al.*: Age-related macular degeneration detection using deep convolutional neural network. Future Generation Computer Systems **87**, 127–135 (2018)

[8] Lu, W., Tong, Y., Yu, Y., Xing, Y., Chen, C., Shen, Y.: Deep learning-based automated classification of multi-categorical abnormalities from optical coherence tomography images. Translational vision science & technology **7**(6), 41–41 (2018)

[9] Li, F., Chen, H., Liu, Z., Zhang, X., Wu, Z.: Fully automated detection of retinal disorders by image-based deep learning. Graefe's Archive for Clinical and Experimental Ophthalmology **257**(3), 495–505 (2019)

[10] Kermany, D.S., Goldbaum, M., Cai, W., Valentim, C.C., Liang, H., Baxter, S.L., McKeown, A., Yang, G., Wu, X., Yan, F., *et al.*: Identifying medical diagnoses and treatable diseases by image-based deep learning. Cell **172**(5), 1122–1131 (2018)

[11] De Fauw, J., Ledsam, J.R., Romera-Paredes, B., Nikolov, S., Tomasev, N., Blackwell, S., Askham, H., Glorot, X., O'Donoghue, B., Visentin, D., *et al.*: Clinically applicable deep learning for diagnosis and referral in retinal disease. Nature medicine **24**(9), 1342–1350 (2018)

[12] Ciregan, D., Meier, U., Schmidhuber, J.: Multi-column deep neural networks for image classification. In: 2012 IEEE Conference on Computer Vision and Pattern Recognition, pp. 3642–3649 (2012). IEEE

[13] LeCun, Y., Boser, B., Denker, J.S., Henderson, D., Howard, R.E., Hubbard, W., Jackel, L.D.: Backpropagation applied to handwritten zip code recognition. Neural computation **1**(4), 541–551 (1989)

[14] Khan, A., Sohail, A., Zahoora, U., Qureshi, A.S.: A survey of the recent architectures of deep convolutional neural networks. CoRR **abs/1901.06032** (2019) 1901.06032

[15] Bouvrie, J.: 1 introduction notes on convolutional neural networks (2006)

[16] Ranzato, M., Huang, F.J., Boureau, Y.-L., LeCun, Y.: Unsupervised learning of invariant feature hierarchies with applications to object recognition. In: 2007 IEEE Conference on Computer Vision and Pattern Recognition, pp. 1–8 (2007). IEEE

[17] Szegedy, C., Liu, W., Jia, Y., Sermanet, P., Reed, S., Anguelov, D., Erhan, D., Vanhoucke, V., Rabinovich, A.: Going deeper with convolutions. In: Proceedings of the IEEE Conference on Computer Vision and Pattern

Recognition, pp. 1–9 (2015)

[18] Kingma, D.P., Ba, J.: Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980 (2014)

[19] Zeiler, M.D.: ADADELTA: an adaptive learning rate method. CoRR **abs/1212.5701** (2012) 1212.5701

[20] Deng, J., Dong, W., Socher, R., Li, L.-J., Li, K., Fei-Fei, L.: Imagenet: A large-scale hierarchical image database. In: 2009 IEEE Conference on Computer Vision and Pattern Recognition, pp. 248–255 (2009). https://doi.org/10.1109/CVPR.2009.5206848

[21] Krizhevsky, A., Hinton, G., et al.: Learning multiple layers of features from tiny images (2009)

[22] Everingham, M., Van Gool, L., Williams, C.K.I., Winn, J., Zisserman, A.: The pascal visual object classes (voc) challenge. International Journal of Computer Vision **88**(2), 303–338 (2010)

[23] Simonyan, K., Zisserman, A.: Very deep convolutional networks for large-scale image recognition. arXiv preprint arXiv:1409.1556 (2014)

[24] He, K., Zhang, X., Ren, S., Sun, J.: Deep residual learning for image recognition. CoRR **abs/1512.03385** (2015) 1512.03385

[25] Szegedy, C., Liu, W., Jia, Y., Sermanet, P., Reed, S.E., Anguelov, D., Erhan, D., Vanhoucke, V., Rabinovich, A.: Going deeper with convolutions. CoRR **abs/1409.4842** (2014) 1409.4842

[26] Chollet, F.: Xception: Deep learning with depthwise separable convolutions. CoRR **abs/1610.02357** (2016) 1610.02357

[27] Khan, A., Sohail, A., Zahoora, U., Qureshi, A.S.: A survey of the recent architectures of deep convolutional neural networks. Artificial Intelligence Review **53**(8), 5455–5516 (2020)

[28] Kermany, D., Zhang, K., Goldbaum, M., et al.: Labeled optical coherence tomography (oct) and chest x-ray images for classification. Mendeley data **2**(2) (2018)

Fig. 8 Results of neural Activation of CNN on (a) CNV and (b) DME

Fig. 9 Results of neural Activation of CNN on (a) DRUSEN and (b) Normal