A chronopharmacology-friendly multi-target therapeutics based on AI: the example of therapeutic hypothermia

Fei Liu[1,2,3,#]; Xiangkang Jiang[1,2,3,#], Mao Zhang[1,2,3,*,#]

Author affiliations:

1. Department of Emergency Medicine, Second Affiliated Hospital of Zhejiang University, Hangzhou 310009, Zhejiang Province, China.

2. Institute of Emergency Medicine, Zhejiang University, Hangzhou 310009, Zhejiang Province, China.

3. Key Laboratory of The Diagnosis and Treatment of Severe Trauma and Burn of Zhejiang Province, Zhejiang University, Hangzhou 310009, Zhejiang Province, China.

[#] The first 1 author is the first author.

* corresponding author: Prof. Mao Zhang

Email: z2jzk@zju.edu.cn

Telephone: +86 13757119125

Declaration

Ethics approval and consent to participate.

Not applicable.

Consent for publication

All authors allow the publication of this article.

Availability of data and materials

All the data that support the findings of this study are available for email from authors.

Competing interests

The authors have declared that they have no conflicts or interests.

Funding

The authors have stated that no such relationships exist.

Authors' contributions

FL designed the research and wrote the article. XJ drew the pictures. MZ modified the article.

38 **Acknowledge**

39 We thank Zaizai Cao, Xiangjie Lin, and Yuanyuan Hao for the algorithm discussion.

Abstract

Nowadays, the complexity of disease mechanisms and inadequacy of single-target therapies in restoring the biological system has inevitably instigated the strategy of multi-target therapeutics with the application of hybrid and chimeric drugs. However, the related method is still unable to solve the conflicts between targets or between drugs. With the release of high-precision protein structure prediction artificial intelligence (AI), large-scale high-precision protein structure prediction and docking become possible. In this article, we propose a multi-target drug discovery method. Then we take an example of therapeutic hypothermia (TH). We performed protein structure prediction for all targets of each group by AlphaFold2 and RoseTTAFold. QuickVina 2 is then used for molecular docking of the proteins and drugs. After docking, we use PageRank to get the rank of drugs and drug combinations of each group. Given the differences in the scoring of different proteins, the method can effectively avoid inhibiting beneficial proteins. So it's friendly to chronopharmacology. This method also have potential in precision medicine for its high compatibility with bioinformatics.

Keywords: multi-target therapeutics; chronopharmacology; precision medicine; Therapeutic hypothermia; virtual screening;

Introduction

At present, the common strategy of drug development is derived from the paradigm "One Drug, One Disease". Therefore, highly selective and potent molecules are being developed for a distinct target.[1] However, in the application of this strategy, the hybrid drugs or chimeric drugs could not solve the problem of interaction between drugs or targets.[2] Besides, this approach also has disadvantages when dealing with time-specific proteins. These defects limits the application of this strategy.

Take therapeutic hypothermia as an example. Therapeutic hypothermia (TH) can limit the degree of some kinds of injuries in randomized trials[3] and animal experiments[4], and is even the only effective method for some diseases especially hypoxic-ischemic encephalopathy (HIE). HIE often causes severe neurological sequelae, which is the main reason for the poor prognosis of patients with stroke, shock, carbon monoxide poisoning, cerebral hemorrhage, and cardiac arrest.[5–7]

In the research based on TH, cold shock proteins especially cold-induced RNA binding protein (CIRP) show high expression [8] and rapid response [9]. CIRP has been shown to promote the translation of genes involved in DNA repair [10,11], telomerase maintenance[12], and genes associated with the translational machinery[13].

However, if CIRP leaks to the intercellular substance with cell swelling and rupture, it will become a harmful protein. Extracellular CIRP (eCIRP) showed a strong pro-inflammatory effect, leading to a heavier hypoxic injury.[14,15] So, agonists applied with CIRP can effectively promote cell protection before CIRP leaks out of the cell. After the leakage of CIRP out of the cell, the application of the CIRP antagonist can effectively promote cell protection.

With the development of high-precise protein prediction technologies, especially AlphaFold2[16] and RoseTTAFold[17], we can obtain the structure of proteins quickly and accurately, and widespread docking becomes possible. In this article, we provide a multi-targeted drug discovery method. This method attempts to include all

96   proteins as targets for analysis. For all proteins, antagonize the negative proteins as

97   much as possible without affecting the positive ones.

Method

Experiment design

As shown in Figure 1, the representative experiment is divided into 5 processes: 1. Protein targets were calculated by bioinformatics analysis; 2. Protein and drugs 3D structure acquisition and prediction; 3. Proteins' active sites prediction; 4. Drug/molecular group evaluation with target proteins; 5. PageRank of docking results, protein logFC, and mRNA expression. The experiment of animals or cells is referred to by authors, but not forced. The biggest difference from previous studies is PageRank.

The data source of bioinformatics analysis

We retrieved the original data of mRNA expression under hypothermia treatment from the website of The National Center for Biotechnology Information (NCBI) (GSE54229). The research was reported by Sten et.al.[9] In their research, mouse embryonic fibroblasts were exposed to mild hypothermia (32°C) or normothermia (37°C) to gain the transcription response induced by hypothermia. After 0.5, 1, 2, 4, 8, and 18 hours of hypothermia, cells were collected for bioinfomatics analysis.

Expression Profile Analysis

The log2 fold-change (log2FC) and p-value were calculated for the normothermia group. Top 3 log2FC mRNA with q-value < 0.05 were selected from each group to enter the next step. If there exists mRNA with failed protein structure prediction, the mRNA would be skipped.

R 3.6.1 was used to detect differential expressed compared to matched normothermia samples. The clustering of genes was calculated by the "dist" and "hclust" function of R. The visualization of gene expression and clustering is performed by the "dendextend" package.

3D Data of proteins and small molecular drugs

All proteins were first searched on PubMed to see if there was protein clipping like cleaved caspase-3[18].

Then the 3D structures of proteins were firstly searched from Protein Data Bank

(PDB), which is used for biological-related ligand-protein interaction. In this article,

no protein structure is listed on the PDB website. All the protein structures were

predicted by AlphaFold2 and RoseTTAFold.

AlphaFold2 is developed by Google and is the champion of the 14[th] Critical

Assessment of Structure Prediction (CASP14). In August 2021, AlphaFold submitted

a structure prediction database for all proteins. RoseTTAFold is based on the Rosetta

software which is designed for macromolecular modeling, docking, and design[19]

RoseTTAFold also has good application[20] in the research of protein structure

prediction. Finally, protein structures with fewer irregular regions will be selected for

the next step.

The 3D structures of 8,697 drugs (DrugBank, 5.1.8) were downloaded from

DrugBank Online (https://go.drugbank.com/). Approved, experimental, nutraceutical,

and investigational drugs by Food and Drug Administration (FDA) are included. We

split each drug molecule into a PDBQT-format file and minimized the energy

separately for docking with proteins.

Visualize evolutionary conservation and active site prediction

Visualize evolutionary conservation was performed by the ConSurf server[21]. In a

typical ConSurf application, through BLASTed[22] against the UNIREF-90

database[23] and aligning using MAFFT[24], the evolutionarily conserved positions

are analyzed by the Rate4Site algorithm.

Then, the Consensus approach-D (COACH-D) [25] was used to predict the active site

of target proteins. The COACH-D uses five different methods to predict the binding

sites of protein ligands. Four of these methods are COFAC-TOR[26], FINDSITE[27],

TM-SITE[28], and S-SITE[28]. These methods predict binding sites by matching the

query structure and sequence with the ligand-binding template in BioLiP[29], which

is a semi-manual functional database[30] based on the PDB.

Virtual screening of potential compounds

To evaluate the hit compounds obtained from DrugBank and calculate their

interaction and binding posture in the active site of target proteins, the molecular

docking method was carried out through QuickVina 2[31]. QuickVina 2 uses the

calculation of shape and electrostatic potential similarity of binding pockets to select

molecules, which may exhibit binding patterns like those of binding pockets.

3D files of target proteins were dehydrated and hydrogenated. Then proteins were

saved as PDBQT files using AutoDock. AutoDock assisted in assigning Gasteiger

charges and adding polar hydrogen atoms to both the proteins and the compounds.

Molecular dynamics simulation

The molecular dynamics (MD) simulation was performed by Gromacs[32]. Firstly, a

protein-drug complex was prepared, including adding hydrogenation and balancing

charge. Then, we add a solvent so that the target protein and small molecules are

coated. The forcefield was Chemistry at HARvard Macromolecular Mechanics 36

(CHARMm 36). The simulation time is set as 50ns for the speed of calculation. The

simulation temperature is 309.15K (36□) and the pressure is 1 atm. Root mean square

deviation (RMSD) and root mean square fluctuation (RMSF) were calculated based

on the first frame.

Personalization-weight-PageRank

We use personalization-weight-PageRank to rank cross-level data. PageRank is a

comprehensive rank algorithm designed by Google and named after Larry Page.[33] It

is one of the most famous ranking algorithms of network nodes based on the Markov

process. PageRank has been applied in medical domains with success.[34,35]

Personalization and weight represent 3 different levels of score data. The weight of

PageRank allows all nodes to be initially assigned different weights/probabilities.[36]

In this article, the weights of rank were set to docking values of proteins and drugs.

The higher the docking value, the higher the connection rate of the complex.

Personalization of PageRank reinforces the connection intensity between the nodes,

which makes the result more personalized and realistic[37]. In this article,

personalization is influenced by protein functions. If the protein performs a negative

influence such as promoting apoptosis, the personalization will be calculated by

2^(fold change) to ensure they are more than 1. Meanwhile, if the protein plays a

positive role in the group, the personalization will be set as 1/(fold change + 1) to less

than 1. The personalization values of all the drugs are set to 0 to prevent iterations of

the drugs themselves from going wrong.

The calculation process is like putting all proteins and all drugs in the solution, then

simulating the connections between all proteins and drugs by calculation. The

damping factor is set to 0.85 to simulate the metabolism of proteins and drugs.

The whole calculation is based on Python 3.8.10. The relating python libraries include

NetworkX, Pandas, and NumPy. We use Pandas and NumPy to import all the docking

data into a matrix for PageRank calculating. The protein expression value is then

imported by the PageRank personalization parameter of NetworkX. Lastly, we can get

a comprehensive ranking of drugs.

Prediction and Rank of combined pharmacotherapy

In addition to the comprehensive ranking of drugs, we also try to generate the rank of

drug combinations. Similarly, the calculation places all drugs of combination and

target proteins in a solution to bind free.

First, all drugs will be grouped according to the docking results of drugs in each

combination. In this article, to reduce the amount of calculation, we selected the

TOP20 drugs of each protein to include in the drug combination pool. Then, all the

combinations were performed personalization-weight-PageRank against all protein

targets. The sum of each score of all drugs in the combination is the final score of the

combination. Lastly, we get the rank of combinations.

To make the distribution of combinations clear, we propose drug-protein-expression

fit score (DPEFS) to show the data distribution pattern. The calculation is as follows:

The PageRank values of all proteins were summed by multiplying logFC, then

divided by the total PageRank values of drugs, and finally divided by the PageRank

values of specific proteins for standardized calculation. It is used for standardized

calculation for comparing different combinations.

DPEFS evaluates the combination by referring to the protein expression trend. The

higher the DPEFS, the better the fitness. In actual drug design, DPEFS is relatively

high and PageRank score is relatively low, indicating that drugs of combination are

relatively moderate, which suggests a negative outcome. All code can be found on

GitHub (https://github.com/FeiLiuEM/PageRank-weight-drug).

Result

Expression analysis and clustering of hypothermia

Figure 2 shows the expressions of different mRNA of different groups after hypothermia. From the inside to the outside, the rings were divided into hypothermia 0.5h group, hypothermia 1H group, hypothermia 2H group, hypothermia 4H group, hypothermia 8h group, and hypothermia 18h group.

As shown in Table 1, in each group, we selected the top 3 expression protein targets. In the Hypothermia 0.5h group, the target proteins are circadian-associated transcriptional repressor (CIART), Glutathione-specific gamma-glutamylcyclotransferase 1 (CHAC1), and Uridine diphosphate glucose pyrophosphatase nudix hydrolase 22 (NUDT22). The target proteins of the Hypothermia 1h group are CHAC1, corneodesmosin (CDSN), and Nuclear receptor subfamily 1 group D member 1 (NR1D1). The target proteins of the Hypothermia 2h group are cold-induced RNA-binding protein (CIRP), armadillo repeat-containing X-linked protein 5 (ARMCX5), and coiled-coil domain-containing protein 122 (CCDC122). The target proteins of the Hypothermia 4h group are CIRP, receptor activity-modifying protein 3 (RAMP3), and carcinoembryonic antigen-related cell adhesion molecule 1 (CEACAM1). The target proteins of the Hypothermia 4h group are the same: CIRP, RAMP3, and NAD(P)H dehydrogenase [quinone] 1 (NQO1).

Within the targets, CHAC1 could enhance apoptosis[38]. NUDT22 is an Mg^{2+}-dependent UDP-glucose and UDP-galactose hydrolase[39], while high glucose shows a negative effect in HIE like stroke[40]. CCDC122 potentially pro-inflammatory[41]. CIRP can effectively reduce cell death in the early stage of hypothermia therapy. However, it has a strong pro-inflammatory effect outside the cell, leading to cell killing. There is no definitive research on the timing of this shift. Referring to the previous article[42], we conservatively believed that CIRP could be identified as a negative protein from the 8H group. CEACAM1[43] and NQO1[44] promote apoptosis. All the other targets are shown protective effects or don't have enough data. The personalization values were calculated in Table 1. All the structures of target proteins in Figure 3 were obtained by the rules in the section of Materials and Methods.

Visualize evolutionary conservation and Structure-Function Relationship-Based

Binding Site Prediction

The conservation analysis of all the target proteins was listed in Figure 4A-K. The

redder the amino acid, the higher possibility of the amino acid sequence with function.

Then we identified its structure-function relationship by the COACH-D server. The

results showed a familiar result of conservation analysis listed in Figure 4L-V. As

shown in Table 2, the range around 3-5 Å of the active site was used for the setting of

the receptor pocket of the target proteins that were used for virtual screening.

Virtual Screening of target proteins' Antagonists

We utilized the virtual screening technique to identify potential antagonists exhibiting

an adequate binding a⬚nity. We started with a chemical database consisting of 8,697

drug molecules and isolated a set of compounds satisfying the threshold of a high

docking score. The results of the best match complexes are shown in Figure 5 and all

the results are listed in the Additional file Table 1.

MD Simulations and Binding Free Energy Analysis

We performed the MD simulation of 11 complexes to measure the stability of the

protein-ligand complex. RMSD (root-mean-square deviation) profiles of the protein

are shown in Figure 6A, which indicates that all systems were relatively stable during

the entire simulation run. Moreover, RMSF profiles of protein are measured to

evaluate the moving of each amino acid. All proteins are available for further analysis

(Figure 6B).

The RMSD of drug atoms was also conducted to predict the stability of the atoms in

docked complexes (Figure 6C). Most compounds exhibited a consistently low RMSD,

suggesting that these compounds formed stable complexes.

Drug rank of TH in different groups

We rank all drugs by PageRank. First, we PageRank all the drugs and get the results

in table3. The higher the rank, the protective effect in TH. The lower the rank is, the

more damaging it is in TH.

2-drug-combinations are ranked in Table 4 and 3-drug-combinations in the additional

file Table 2. For comprehensive rank, the results of PageRank were listed. For drug-

combination ranks, the percentages of each drug's value in the combination were

calculated. And DPEFS was calculated for analyzing the distribution differences of

drug combinations.

Discussion

In this report, a chronopharmacology-friendly multi-target drug discovery method is proposed by taking TH as example. This is the first application of PageRank and first attempt of AI protein prediction in the field of multi-target drug discovery.

In this paper, due to the high compatibility of PageRank, except for basic mRNA expression differences, the analysis of Weighted Gene Coexpression Network Analysis (WGCNA)[45] or Gene Regulatory Networks (GRN)[46] will be better because they could provide numerical results of all proteins. For the same reason, PageRank has good compatibility with existing pharmacological techniques such as pharmacophore models[47] and Quantitative Structure-Activity Relationship (QSAR)[48].

AlphaFold2 and RoseTTAFold were used for protein structure prediction. And the number of selected proteins predicted by AlphaFold2 in this research was close to that of RoseTTAFold. During the process of protein structure prediction, we found that for some proteins, the structures predicted by RoseTTAFold have less irregular structure than that of AlphaFold2. This may be due to the 2D distance map level being transformed and integrated by RoseTTAFold during neural network training[17], while AlphaFold2 only paired structure database and genetic database[16]. We also find a phenomenon that the predicted protein structures were relatively unstable under molecular dynamics simulation than preview reports of other protein structures detected by X-ray.

We use the PageRank algorithm to rank all the drugs and combinations. The application of PageRank is suitable. The combination of drug molecules is a memoryless stochastic process, which meets the qualifications of the Markov process. The comprehensive analysis involves free docking of proteins with all drugs. Drug combination analysis is to put proteins and related drugs into the solution for docking. Besides, the method has good compatibility with the wide compatibility of PageRank. In theory, all the technologies with numerical results can be ranked by the method. In addition, due to the charastic of PageRank, we can adjust the weight of different proteins to suppress the negative proteins with minimal impact on the positive ones. This property is very beneficial for chronopharmacology. It is difficult for one

administration to affect the effect of the next one.

The new method brings new ideas for clinical drug development. For tumors, it is

possible to effectively antagonize most of abnormally expressed proteins while

limiting the affection of normal proteins. Given this approach's close association with

bioinformatics, bioinformatics can predict the most suitable drug for every patient in

most diseases.

This research has some defects. 1: For the speed of calculating, we only choose the

top 3 mRNAs for docking and the top 1 complex for MD simulation. Furthermore, the

duration of molecular dynamics simulation is set to 50ns. These operations mitigate

the rationality of the results relatively; 2. Theoretically, pharmacophore modeling has

a better improvement under PageRank. But considering lacking related copyright and

the purpose of the article, we chose to dock FBI-approved drugs with target proteins

to explore the interaction between proteins and drugs.

In summary, this paper proposes a new method through protein structure predicting

and PageRank. The results provide medical clues for the treatment of TH. This

method takes a new attempt at drug discovery, which might make a little bit of a

difference in pharmacology.

346 **Reference**

1. Rodríguez-Soacha DA, Scheiner M, Decker M. Multi-target-directed-ligands acting as enzyme inhibitors and receptor ligands. Eur J Med Chem. 2019;180:690–706.

2. Bawa P, Pradeep P, Kumar P, Choonara YE, Modi G, Pillay V. Multi-target therapeutics for neuropsychiatric and neurodegenerative disorders. Drug Discov Today. 2016;21:1886–914.

3. Lascarrou J-B, Merdji H, Le Gouge A, Colin G, Grillet G, Girardie P, et al. Targeted Temperature Management for Cardiac Arrest with Nonshockable Rhythm. N Engl J Med. 2019;381:2327–37.

4. Kim JY, Kim JH, Park J, Beom JH, Chung SP, You JS, et al. Targeted Temperature Management at 36 °C Shows Therapeutic Effectiveness via Alteration of Microglial Activation and Polarization After Ischemic Stroke. Transl Stroke Res. 2021;

5. Hosseini M, Wilson RH, Crouzet C, Amirhekmat A, Wei KS, Akbari Y. Resuscitating the Globally Ischemic Brain: TTM and Beyond. Neurother J Am Soc Exp Neurother. 2020;17:539–62.

6. Hazinski MF, Nolan JP, Aickin R, Bhanji F, Billi JE, Callaway CW, et al. Part 1: Executive Summary: 2015 International Consensus on Cardiopulmonary Resuscitation and Emergency Cardiovascular Care Science With Treatment Recommendations. Circulation. 2015;132:S2-39.

7. Lemiale V, Dumas F, Mongardon N, Giovanetti O, Charpentier J, Chiche J-D, et al. Intensive care unit mortality after cardiac arrest: the relative contribution of shock and brain injury in a large cohort. Intensive Care Med. 2013;39:1972–80.

8. Rosenthal L-M, Leithner C, Tong G, Streitberger KJ, Krech J, Storm C, et al. RBM3 and CIRP expressions in targeted temperature management treated cardiac arrest patients-A prospective single center study. PloS One. 2019;14:e0226005.

9. Ilmjärv S, Hundahl CA, Reimets R, Niitsoo M, Kolde R, Vilo J, et al. Estimating differential expression from multiple indicators. Nucleic Acids Res. 2014;42:e72.

10. Yang R, Zhan M, Nalabothula NR, Yang Q, Indig FE, Carrier F. Functional significance for a heterogenous ribonucleoprotein A18 signature RNA motif in the 3'-untranslated region of ataxia telangiectasia mutated and Rad3-related (ATR) transcript. J Biol Chem. 2010;285:8887–93.

11. Haley B, Paunesku T, Protić M, Woloschak GE. Response of heterogeneous ribonuclear proteins (hnRNP) to ionising radiation and their involvement in DNA damage repair. Int J Radiat Biol. 2009;85:643–55.

12. Zhang Y, Wu Y, Mao P, Li F, Han X, Zhang Y, et al. Cold-inducible RNA-binding protein CIRP/hnRNP A18 regulates telomerase activity in a temperature-dependent manner. Nucleic Acids Res. 2016;44:761–75.

13. Zhong P, Huang H. Recent progress in the research of cold-inducible RNA-binding protein. Future Sci OA. 2017;3:FSO246.

14. Sakurai T, Kashida H, Watanabe T, Hagiwara S, Mizushima T, Iijima H, et al. Stress response protein cirp links inflammation and tumorigenesis in colitis-associated cancer. Cancer Res. 2014;74:6119–28.

15. Sakurai T, Kashida H, Komeda Y, Nagai T, Hagiwara S, Watanabe T, et al. Stress Response Protein RBM3 Promotes the Development of Colitis-associated Cancer. Inflamm Bowel Dis. 2017;23:57–65.

16. Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, et al. Highly accurate protein structure prediction with AlphaFold. Nature. 2021;596:583–9.

17. Baek M, DiMaio F, Anishchenko I, Dauparas J, Ovchinnikov S, Lee GR, et al. Accurate prediction of protein structures and interactions using a three-track neural network. Science. 2021;373:871–6.

18. Kothakota S, Azuma T, Reinhard C, Klippel A, Tang J, Chu K, et al. Caspase-3-generated fragment of gelsolin: effector of morphological change in apoptosis. Science. 1997;278:294–8.

19. Leman JK, Weitzner BD, Lewis SM, Adolf-Bryfogle J, Alam N, Alford RF, et al. Macromolecular modeling and design in Rosetta: recent methods and frameworks. Nat Methods. 2020;17:665–80.

20. Humphreys IR, Pei J, Baek M, Krishnakumar A, Anishchenko I, Ovchinnikov S, et al. Computed structures of core eukaryotic protein complexes. Science. 2021;eabm4805.

21. Ashkenazy H, Abadi S, Martz E, Chay O, Mayrose I, Pupko T, et al. ConSurf 2016: an improved methodology to estimate and visualize evolutionary conservation in macromolecules. Nucleic Acids Res. 2016;44:W344-350.

22. Biegert A, Söding J. Sequence context-specific profiles for homology searching. Proc Natl Acad Sci U S A. 2009;106:3770–5.

23. Suzek BE, Wang Y, Huang H, McGarvey PB, Wu CH, UniProt Consortium. UniRef clusters: a comprehensive and scalable alternative for improving sequence similarity searches. Bioinforma Oxf Engl. 2015;31:926–32.

24. Katoh K, Standley DM. MAFFT multiple sequence alignment software version 7: improvements in performance and usability. Mol Biol Evol. 2013;30:772–80.

25. Wu Q, Peng Z, Zhang Y, Yang J. COACH-D: improved protein-ligand binding sites prediction with refined ligand-binding poses through molecular docking. Nucleic Acids Res. 2018;46:W438–42.

26. Roy A, Yang J, Zhang Y. COFACTOR: an accurate comparative algorithm for structure-based protein function annotation. Nucleic Acids Res. 2012;40:W471-477.

27. Brylinski M, Skolnick J. A threading-based method (FINDSITE) for ligand-binding site prediction and functional annotation. Proc Natl Acad Sci U S A. 2008;105:129–34.

28. Yang J, Roy A, Zhang Y. Protein-ligand binding site recognition using complementary binding-specific substructure comparison and sequence profile alignment. Bioinforma Oxf Engl. 2013;29:2588–95.

29. Yang J, Roy A, Zhang Y. BioLiP: a semi-manually curated database for biologically relevant ligand-protein interactions. Nucleic Acids Res. 2013;41:D1096-1103.

30. Rose PW, Prlić A, Altunkaya A, Bi C, Bradley AR, Christie CH, et al. The RCSB protein data bank: integrative view of protein, gene and 3D structural information. Nucleic Acids Res. 2017;45:D271–81.

31. Alhossary A, Handoko SD, Mu Y, Kwoh C-K. Fast, accurate, and reliable molecular docking with QuickVina 2. Bioinforma Oxf Engl. 2015;31:2214–6.

32. Van Der Spoel D, Lindahl E, Hess B, Groenhof G, Mark AE, Berendsen HJC. GROMACS: fast, flexible, and free. J Comput Chem. 2005;26:1701–18.

33. Page L, Brin S, Motwani R, Winograd T. The PageRank Citation Ranking: Bringing Order to the Web. [Internet]. Stanford InfoLab; 1999 Nov. Report No.: 1999–66. Available from: http://ilpubs.stanford.edu:8090/422/

34. Kalecky K, Cho Y-R. PrimAlign: PageRank-inspired Markovian alignment for large biological networks. Bioinforma Oxf Engl. 2018;34:i537–46.

35. Chen L, Heikkinen L, Wang C, Yang Y, Sun H, Wong G. Trends in the development of miRNA bioinformatics tools. Brief Bioinform. 2019;20:1836–52.

36. Xing W, Ghorbani A. Weighted PageRank algorithm. Proc Second Annu Conf Commun Netw Serv Res 2004. 2004. p. 305–14.

37. Haveliwala T, Kamvar S, Jeh G. An Analytical Comparison of Approaches to Personalizing PageRank [Internet]. Stanford; 2003 Jun. Report No.: 2003–35. Available from: http://ilpubs.stanford.edu:8090/596/

38. Mungrue IN, Pagnon J, Kohannim O, Gargalovic PS, Lusis AJ. CHAC1/MGC4504 is a novel proapoptotic component of the unfolded protein response, downstream of the ATF4-ATF3-CHOP cascade. J Immunol Baltim Md 1950. 2009;182:466–76.

39. Carter M, Jemth A-S, Carreras-Puigvert J, Herr P, Martínez Carranza M, Vallin KSA, et al. Human NUDT22 Is a UDP-Glucose/Galactose Hydrolase Exhibiting a Unique Structural Fold.

Struct Lond Engl 1993. 2018;26:295-303.e6.

40. Zhang S, Zuo W, Guo X-F, He W-B, Chen N-H. Cerebral glucose transporter: the possible therapeutic target for ischemic stroke. Neurochem Int. 2014;70:22–9.

41. Leturiondo AL, Noronha AB, Mendonça CYR, Ferreira C de O, Alvarado-Arnez LE, Manta FS de N, et al. Association of NOD2 and IFNG single nucleotide polymorphisms with leprosy in the Amazon ethnic admixed population. PLoS Negl Trop Dis. 2020;14:e0008247.

42. Denning N-L, Yang W-L, Hansen L, Prince J, Wang P. C23, an oligopeptide derived from cold-inducible RNA-binding protein, suppresses inflammation and reduces lung injury in neonatal sepsis. J Pediatr Surg. 2019;54:2053–60.

43. Zhao C, Dang Z, Sun J, Yuan S, Xie L. Up-regulation of microRNA-30b/30d cluster represses hepatocyte apoptosis in mice with fulminant hepatic failure by inhibiting CEACAM1. IUBMB Life. 2020;72:1349–63.

44. Feng Y, Cui R, Li Z, Zhang X, Jia Y, Zhang X, et al. Methane Alleviates Acetaminophen-Induced Liver Injury by Inhibiting Inflammation, Oxidative Stress, Endoplasmic Reticulum Stress, and Apoptosis through the Nrf2/HO-1/NQO1 Signaling Pathway. Oxid Med Cell Longev. 2019;2019:7067619.

45. Langfelder P, Horvath S. WGCNA: an R package for weighted correlation network analysis. BMC Bioinformatics. 2008;9:559.

46. Alexiou A, Chatzichronis S, Perveen A, Hafeez A, Ashraf GM. Algorithmic and Stochastic Representations of Gene Regulatory Networks and Protein-Protein Interactions. Curr Top Med Chem. 2019;19:413–25.

47. Sliwoski G, Kothiwale S, Meiler J, Lowe EW. Computational methods in drug discovery. Pharmacol Rev. 2014;66:334–95.

48. Muratov EN, Bajorath J, Sheridan RP, Tetko IV, Filimonov D, Poroikov V, et al. QSAR without borders. Chem Soc Rev. 2020;49:3525–64.

Table 1. The target proteins of different groups.

Group	Target	logFC	Harmful for cell	Personalization	Expression/nstart
0.5h	CIART	0.46	×	0.42	8.02
	CHAC1	0.43	√	1.34	9.64
	NUDT22	0.40	√	1.32	9.40
1h	CDSN	0.52	×	0.41	8.17
	NR1D1	0.50	×	0.41	10.66
	CHAC1	0.50	√	1.41	9.71
2h	CIRP	0.80	×	0.36	9.43
	ARMCX5	0.66	×	0.39	5.97
	CCDC122	0.49	√	1.41	8.06
4h	CIRP	1.17	×	0.31	9.80
	RAMP3	0.91	×	0.35	9.05
	CEACAM1	0.87	√	1.82	7.11
8h	CIRP	1.57	√	2.97	10.20
	RAMP3	1.33	×	0.28	9.47
	NQO1	1.18	√	2.27	10.87
18h	CIRP	1.71	√	3.27	10.34
	NQO1	1.55	√	2.93	11.25
	RAMP3	1.32	×	0.29	9.46

Table 2. The docking parameters of target proteins.

Protein name	protein source	X	Y	Z	LEN-X	LEN-Y	LEN-Z
ARMCX5	RoseTTAFold	-7.06	31.20	-43.05	29.25	28.50	24.75
CDSN	RoseTTAFold	51.80	53.51	31.17	39.75	20.25	21.00
CEACAM1	AlphaFold2	-41.13	3.42	5.67	39.75	22.50	22.50
CHAC1	AlphaFold2	-3.04	-0.53	0.22	23.25	25.50	35.25
CIART	RoseTTAFold	36.79	-16.59	-36.23	28.50	38.25	22.50
CIRP	RoseTTAFold	14.48	2.86	-9.56	17.25	15.00	19.50
NQO1	AlphaFold2	-1.86	-16.32	-9.20	29.25	29.25	28.50
NR1D1	RoseTTAFold	0.34	35.70	10.28	39.75	25.50	24.75
NUDT22	AlphaFold2	10.08	-12.04	14.09	17.25	38.25	22.50
RAMP3	AlphaFold2	0.00	-10.93	-5.29	24.00	24.00	21.00
CCDC122	RoseTTAFold	119.27	23.34	8.09	36.00	47.25	47.25

Table 3. The comprehensive rank of drugs at different groups.

Group	Drug	weighted_personalized_PageRank ($*10^{-4}$)
h0.5h	Fluzoparib	0.81
	Lorecivivint	0.80
	Vactosertib	0.80
h1h	Lorecivivint	0.81
	AC-430	0.81
	Raltegravir	0.80
h2h	Phthalocyanine	0.90
	Vazegepant	0.87
	Bemcentinib	0.86
h4h	Phthalocyanine	0.85
	3-(2-AMINOQUINAZOLIN-6-YL)-4-METHYL-N-[3-(TRIFLUOROMETHYL)PHENYL]BENZAMIDE	0.84
	Bemcentinib	0.84
h8h	Phthalocyanine	0.87
	MK-3207	0.86
	Lifirafenib	0.85
h18h	Phthalocyanine	0.87
	MK-3207	0.86
	Lifirafenib	0.85

Table 4. Rank of 2 drug combinations of different group.

	drug1	drug2	PageRank value of drug1	percentage	PageRank value of drug2	percentage	personalized_weight_PageRank	Drug-protein-expression fit score
h0.5h	Lorecivivint	Fluzoparib	0.41	49.85	0.42	50.15	0.83	2.30
	Vactosertib	Fluzoparib	0.41	49.56	0.42	50.44	0.83	2.33
	2'-deoxy-N-(naphthalen-1-ylmethyl)guanosine 5'-(dihydrogen phosphate)	Fluzoparib	0.41	49.68	0.42	50.32	0.83	2.32
h1h	Lorecivivint	AC-430	0.41	49.67	0.42	50.33	0.83	4.36
	Lorecivivint	Raltegravir	0.42	50.12	0.41	49.88	0.83	4.40
	Lorecivivint	Vactosertib	0.42	50.21	0.41	49.79	0.83	4.37
h2h	Phthalocyanine	Vazegepant	0.42	51.42	0.40	48.58	0.82	4.65
	Phthalocyanine	Bemcentinib	0.43	51.84	0.40	48.16	0.82	4.71
	Phthalocyanine	Lifirafenib	0.43	52.28	0.39	47.72	0.82	4.64
h4h	3-(2-AMINOQUINAZOLIN-6-YL)-4-METHYL-N-[3-(TRIFLUOROMETHYL)PHENYL]BENZAMIDE	CD564	0.41	50.25	0.41	49.75	0.82	1.60

	Adapalene	3-(2-AMINOQUINAZOLIN-6-YL)-4-METHYL-N-[3-(TRIFLUOROMETHYL)PHENYL] BENZAMIDE	0.41	49.90	0.41	50.10	0.82	1.60
	3-(2-AMINOQUINAZOLIN-6-YL)-4-METHYL-N-[3-(TRIFLUOROMETHYL)PHENYL] BENZAMIDE	Phthalocyanine	0.42	50.52	0.41	49.48	0.82	1.60
h8h	Phthalocyanine	MK-3207	0.41	49.91	0.41	50.09	0.83	3.94
	Phthalocyanine	Lifirafenib	0.42	50.17	0.41	49.83	0.83	3.93
	Lifirafenib	MK-3207	0.41	49.75	0.42	50.25	0.83	3.94
h18h	Phthalocyanine	MK-3207	0.41	49.91	0.41	50.09	0.83	4.95
	Lifirafenib	MK-3207	0.41	49.77	0.42	50.23	0.83	4.95
	Phthalocyanine	Lifirafenib	0.42	50.14	0.41	49.86	0.83	4.94

Figure 1. Representative workflow for bioinfo-pharmacology drug design.

Figure 2. Circular visualization of expression patterns and clustering of hypothermia treatment. Red indicates gene upregulation and blue indicates downregulation.

Figure 3. The 3D structures of target proteins. A. ARMCX5; B. CCDC; C. CDSN; D. CEACAM1; E. CHAC1; F. CIART; G. CIRP; H. NQO1; I. NR1D1; J. NUDT22; K. RAMP3.

Figure 4. The ConSurf analysis and predicted active sites of target proteins. The upper 11 pictures are ConSurf analysis results. The last 11 pictures are predicted active sites. A&L. ARMCX5; B&M. CCDC; C&N. CDSN; D&O. CEACAM1; E&P. CHAC1; F&Q. CIART; G&R. CIRP; H&S. NQO1; I&T. NR1D1; J&U. NUDT22; K&V. RAMP3. The redder the amino acid, the more conservative it is. The greener the color, the less conservative it is.

Figure 5. The best docking molecular for each protein. A. ARMCX5; B. CCDC; C. CDSN; D. CEACAM1; E. CHAC1; F. CIART; G. CIRP; H. NQO1; I. NR1D1; J. NUDT22; K. RAMP3.

Figure 6. The RMSD and RMSF of MD simulation. A. The RMSD of proteins. B. The RMSF of proteins. C. The RMSD of each molecular of proteins.