

Multi-task learning for activity detection in neovascular age-related macular degeneration

Murat Seçkin Ayhan^{1,§}, Hanna Faber^{1,2,§}, Laura Kühlewein^{1,2}, Werner Inhoffen², Gulnar Aliyeva², Focke Ziemssen^{2,3}, and Philipp Berens^{1,4,‡}

¹*Institute for Ophthalmic Research, University of Tübingen, Tübingen, Germany*

²*University Eye Clinic, University of Tübingen, Tübingen, Germany*

³*University Eye Clinic, University of Leipzig, Leipzig, Germany*

⁴*Tübingen AI Center, Tübingen, Germany*

[‡]*Corresponding author: philipp.berens@uni-tuebingen.de*

[§]*Equal contribution*

November 23, 2022

Meeting Presentation: The manuscript was presented as poster presentation (ID PDo04-01) at the 120. Congress of the DOG (Deutsche Ophthalmologische Gesellschaft), 29.09.–02.10.2022, Berlin, Germany

Financial Support: Financial support was provided by German Ministry of Science and Education (BMBF) through the Tübingen AI Center (FKZ 01IS18039A) and the German Science Foundation for funding through a Heisenberg Professorship (BE5601/4-2) and the Excellence Cluster "Machine Learning – New Perspectives for Science" (EXC 2064, project number 390727645), the Junior Clinician Scientist Program of the Faculty of Medicine, Eberhard Karls University of Tübingen, Germany (application number 463-0-0) (HF) and the Novartis AG. The sponsor or funding organization had no role in the design or conduct of this research.

Conflict of Interest: FZ has received consulting fees from Allergan, Bayer HealthCare, Boehringer-Ingelheim, Novo Nordisk, MSD and Novartis and speaker fees from Alimera, Allergan, Bayer HealthCare and Novartis. FZ was involved in research funded by grants from Bayer Healthcare, Biogen, Clearside, Ionis, Kodiak, Novartis, Opthea, Regeneron and Roche/Genentech. LK receives, via third-party accounts of the University Eye Hospital, research funding and honoraria from Novartis and research funding from the Tistou and

NOTE: This preprint reports new research that has not been certified by peer review and should not be used to guide clinical practice.

25 Charlotte Kerstan Foundation. HF received medical training event costs from Novartis. MSA, WI and GA
26 declare no competing interest.

27 **Short Title:** Multi-task learning for activity detection in nAMD

28 **Word Count:** 4087

29 **Section Code:** RE

30 **Keywords:** machine-learning, age-related macular degeneration, anti-VEGF treatment, multi-task learn-
31 ing, saliency maps

32 **Address for preprints:** Prof. Dr. rer. nat. P. Berens, Werner Reichardt Centre for Integrative Neuroscience
33 (CIN) Institute for Ophthalmic Research, University of Tübingen, Otfried-Müller-Str. 25, D-72076 Tübingen,
34 Germany. Phone: +49 (0)7071 29-88833, philipp.berens@uni-tuebingen.de

Abstract

Purpose:

Comparison of performance and explainability of a multi-task convolutional deep neuronal network to single-task networks for activity detection in neovascular age-dependent macular degeneration.

Methods:

From n = 70 patients (46 female, 24 male) who attended the University Eye Hospital Tübingen 3762 optical coherence tomography B-scans (right eye: 2011, left eye: 1751) were acquired with Heidelberg Spectralis, Heidelberg, Germany. B-scans were graded by a retina specialist and an ophthalmology resident, and then used to develop a multi-task deep learning model to predict disease activity in neovascular age-related macular degeneration along with the presence of sub- and intraretinal fluid. We used performance metrics for comparison to single-task networks and visualized the DNN-based decision with t-distributed stochastic neighbor embedding and clinically validated saliency mapping techniques.

Results:

The multi-task model surpassed single-task networks in accuracy for activity detection (94.2). Furthermore, compared to single-task networks, visualizations via t-distributed stochastic neighbor embedding and saliency maps highlighted that multi-task networks' decisions for activity detection in neovascular age-related macular degeneration were highly consistent with the presence of both sub- and intraretinal fluid.

Conclusions:

Multi-task learning increases the performance of neuronal networks for predicting disease activity, while providing clinicians with an easily accessible decision control, which resembles human reasoning.

Translational Relevance:

By improving nAMD activity detection performance and transparency of automated decisions, multi-task DNNs can support the translation of machine learning research into clinical decision support systems for nAMD activity detection.

60 1 Introduction

61 Neovascular age-related macular degeneration (nAMD) is a sight-threatening disease and a common cause
62 of vision loss worldwide.¹⁻³ Among the basic features of nAMD are subretinal fluid (SRF) and intraretinal
63 fluid (IRF), which serve as surrogate markers of nAMD activity and can be monitored using optical coher-
64 ence tomography (OCT)^{4,5} (Fig. 1).

65 In nAMD, increased levels of vascular endothelial growth factor (VEGF) lead to formation of new ves-
66 sels from the choroidal and/or retinal vasculature. If leakage from these vessels exceeds local clearance
67 rates, fluid builds up, leading to IRF and SRF.⁴ IRF is assumed to originate from vascular leakage from in-
68 traretinal neovascularisation and/or retinal vasculature or from diffusion through the outer retina due to
69 changes within the external limiting membrane.⁴ In contrast, SRF formation likely results from malfunction
70 of the retinal pigment epithelium with reduced removal rates.⁴ Due to the partially different pathophysi-
71 ology, IRF and SRF can occur both simultaneously and independently from each other.^{4,6} In addition, the
72 characterisation of the lesion based on IRF and SRF could help to determine visual outcome.⁷

73 Treatment with intravitreal anti-VEGF agents efficiently restores the balance between fluid formation
74 and retinal removal and is standard of care, when IRF or SRF in nAMD is detected via OCT.⁵ Prompt treat-
75 ment initiation is necessary to prevent vision loss.⁸⁻¹⁰ Additionally, this chronic disease demands high-
76 frequent therapy monitoring, which has put considerable burden on patients, their families and ophthal-
77 mological care since its initial approval in 2006.¹¹⁻¹⁴ Since the number of patients suffering from AMD is
78 thought to rise from 196 million in 2020 to 288 million in 2040, the care needed will also rise.² Hence,
79 automated solutions making the diagnostic processes more efficient have considerable appeal. For exam-
80 ple, deep neural networks (DNNs) have been used for automatic referral decisions¹⁵ and predicting disease
81 conversion to nAMD.¹⁶ Automated algorithms could detect both SRF and IRF more reliably than retinal
82 specialists especially in less conspicuous cases.¹⁷ Ideally, such automated tools serve to support retinal
83 specialists in their decision making. In collaboration, a retina specialist assisted by an artificial intelligence
84 (AI) tool can outperform the model alone, e.g., for the task of diabetic retinopathy grading.¹⁸ To this end,
85 computational tools need to explain their decisions and communicate their uncertainty to the treating oph-
86 thalmologist.^{19,20}

87 Here, we develop a convolutional deep learning model based on the concept of multi-task learning.^{21,22}
88 Multi-task learning is a generalization of the widely used single-task learning, where models are trained
89 for multiple input-output mappings simultaneously (Fig. 2). For instance, multi-task models can be used
90 to capture different characteristics of dry AMD, such as drusen area, geographic atrophy, increased pig-




Figure 1: Exemplary retinal images (B-scans) with neovascular age-related macular degeneration (nAMD). Solid and dotted arrows indicate subretinal and intraretinal fluid, respectively. **(a)**: no nAMD activity. **(b)**: nAMD activity due to subretinal fluid (SRF). **(c)**: nAMD activity due to intraretinal fluid (IRF). **(d)**: nAMD activity due to both SRF and IRF.

91 ment, and depigmentation, to combine these outputs into final AMD diagnosis w.r.t. a 9-step severity
92 scale.²³ Multi-task learning has also shown prognostic value when applied to survival analysis via two si-
93 multaneous prediction tasks: drusen and pigmentation grading.²⁴ In a similar vein, our multi-task model
94 detects SRF, IRF and nAMD activity in parallel. However, it generates distinct outputs for each of these
95 tasks and offers well-calibrated uncertainty estimates for each of them, which is unique to our study. As
96 the fluid compartment plays a decisive role in the treatment outcome²⁵⁻²⁷ with the simultaneous pres-
97 ence of IRF and SRF being associated with the worst prognosis,⁹ we visualize the representation driving
98 the DNN-based decisions using t-distributed stochastic neighbor embedding (t-SNE)^{28,29} and investigate
99 the model's decisions using clinically validated saliency mapping techniques.³⁰ Thus, together with well-
100 calibrated uncertainty reports, our work provides an interpretable tool for the ophthalmologist to rapidly
101 access the neural network's decision process on both population-based and individual-patient levels as a
102 prerequisite for clinical application.

103 2 Methods

104 2.1 Data Collection

105 This study included 70 patients (46 females, 24 males) with nAMD at least in one eye, seen by an ophthal-
106 mologist resident (AG) in the Macula clinic at the University Eye Hospital Tübingen. Exclusion criteria were
107 any other cause of neovascularisation, any coexisting retinal pathology (e.g. epiretinal membrane, macular
108 hole, diabetic retinopathy), glaucoma and media opacity preventing sufficient image quality.

109 3762 B-scans (2011 right eye, 1751 left eye) of 440 x 512 pixels with Heidelberg Spectralis OCT (Heidelberg
110 Engineering, Heidelberg, Germany) were included in the study. A retina specialist of the same hospital (IW)
111 assessed disease activity and presence of IRF and SRF on each individual B-Scan. (Fig. 1). Disease activity

Table 1: OCT Data distribution of subretinal fluid (SRF), intraretinal fluid (IRF) and active nAMD in B-Scans in training, validation and test sets, respectively. Absolute and relative numbers are shown.

	Training			Validation			Test		
	<i>Subretinal fluid</i>	<i>Intraretinal fluid</i>	<i>Active nAMD</i>	<i>Subretinal fluid</i>	<i>Intraretinal fluid</i>	<i>Active nAMD</i>	<i>Subretinal fluid</i>	<i>Intraretinal fluid</i>	<i>Active nAMD</i>
Yes	639 (0.232)	286 (0.104)	848 (0.308)	69 (0.170)	58 (0.143)	101 (0.248)	161 (0.267)	153 (0.253)	269 (0.445)
No	2112 (0.768)	2465 (0.896)	1903 (0.692)	338 (0.830)	349 (0.857)	306 (0.752)	443 (0.733)	451 (0.747)	335 (0.555)

Table 2: Agreement of task-specific labels across training, validation and test sets, measured via Cohen's kappa statistic, which is essentially a number between -1 and 1. While 1 indicates a full agreement, lower scores mean less agreement. Negative scores indicate disagreement.

	Training			Validation			Test		
	<i>Subretinal fluid</i>	<i>Intraretinal fluid</i>	<i>Active nAMD</i>	<i>Subretinal fluid</i>	<i>Intraretinal fluid</i>	<i>Active nAMD</i>	<i>Subretinal fluid</i>	<i>Intraretinal fluid</i>	<i>Active nAMD</i>
<i>Subretinal fluid</i>	-	-0.02	0.79	-	0.26	0.75	-	-0.02	0.59
<i>Intraretinal fluid</i>	-0.02	-	0.37	0.26	-	0.65	-0.02	-	0.57

112 was also graded by a resident (AG). B-scans were assigned to a training, validation or test set (Table 1). All
 113 images of one patient were assigned to one set to avoid information leakage. The study was conducted
 114 in accordance with the tenets of the Declaration of Helsinki and approved by the local institutional ethics
 115 committee of the University of Tübingen, which waived the requirement for patient consent due to the
 116 study's retrospective character.

117 2.2 Diagnostic Tasks, Network Architecture and Model Development

118 We developed a multi-task DNN to detect the presence of SRF and IRF as well as the nAMD activity from
 119 OCT B-scans (Fig. 2). As backbone, we used the InceptionV3 architecture³¹ via Keras,³² which was pre-
 120 trained on ImageNet³³ for 1000-way classification via a softmax function. We used the InceptionV3 DNN's
 121 convolutional stack as is but linked max pooling and average pooling layers to the end of convolutional
 122 stack and concatenated their outputs to obtain 4096-dimensional feature vectors. These were followed
 123 by a dense layer, which yielded a shared representation with 1024 features. To this, we added task-specific
 124 heads with 256 units, which specialized into their respective tasks. Then, task-specific binary decisions
 125 were achieved by single units equipped with sigmoid functions. For training our DNNs in both single and
 126 multi-task scenarios, we resorted to the retina specialist's set of labels.




Figure 2: A deep neural network for simultaneous detection of subretinal and intraretinal fluid as well as the nAMD activity from OCT B-scans. Given a B-scan, convolutional stack of the InceptionV3 architecture extracts 2048 feature maps. These are average and max pooled, and fed into a fully connected (dense) layer with 1024 units for shared representation. Then, task-specific heads specialize into individual tasks and single units with sigmoid function achieve binary classification based on 256 task-specific features.

127 We trained our networks with equally weighted cross-entropy losses for all tasks on the training images:
 128 $\mathcal{D} = \{\mathbf{x}_n, \mathbf{y}_n\}_{n=1}^N$, where \mathbf{y}_n was a vector of binary labels indicating nAMD activity and the presence of IRF
 129 or SRF in an image \mathbf{x}_n . Parameterized by θ , a DNN $f_\theta(\cdot)$ was optimized with respect to the total cross-
 130 entropy on the training data:

$$\mathcal{L}(\mathcal{D}, f_\theta(\cdot)) = \frac{1}{N} \sum_{n=1}^N l(\mathbf{y}_n, f_\theta(\mathbf{x}_n)), \text{ where} \quad (1)$$

$$l(\mathbf{y}_n, f_\theta(\mathbf{x}_n)) = - \sum_{t=1}^T \mathbf{y}_{n,t} \log p_{n,t} + (1 - \mathbf{y}_{n,t}) \log (1 - p_{n,t}), \quad (2)$$

131 $p_{n,t}$ was a probability estimated via the sigmoid function for a task indicated by t , and T was the total
 132 number of tasks. For $T = 1$, multi-task learning was reduced to single-task learning based on the same
 133 architecture but with only one task head. We also developed a 2-task model to perform the SRF and IRF
 134 detection tasks ($T = 2$), while eliminating the redundancy of the nAMD activity detection task, which is, in
 135 principle, a function of the former two.

136 To address the class imbalance (Table 1), we used random oversampling (see Section 2.2.2 for de-
 137 tails). We trained the DNN using Stochastic Gradient Descent (SGD) with Nesterov's Accelerated Gradients
 138 (NAG)^{34,35} minibatch size of eight, a momentum coefficient of 0.9, an initial learning rate of $5 \cdot 10^{-4}$, a decay
 139 rate of 10^{-6} and a regularization constant of 10^{-5} for 120 or 150 epochs (see Section 2.2.1 for longer training).
 140 During the first five epochs, the convolutional stack was frozen and only dense layers were trained. Then,

141 all layers were fine-tuned to all tasks. The best models were selected based on total validation loss after
142 each epoch and used for inference on the test set.

143 2.2.1 Data augmentation and preprocessing

144 We used *mixup*³⁶ for data augmentation during training. Mixup generates artificial examples through the
145 convex combinations of randomly sampled data points. We adapted *mixup* to our multi-task learning
146 scenario as follows:

$$\hat{\mathbf{x}} = \lambda \mathbf{x}_i + (1 - \lambda) \mathbf{x}_j, \quad \hat{\mathbf{y}} = \lambda \mathbf{y}_i + (1 - \lambda) \mathbf{y}_j, \quad \lambda \in [0, 1]. \quad (3)$$

147 Mixing was controlled by $\lambda \sim \text{Beta}(\alpha, \alpha)$, where $\alpha \in (0, \infty)$. For $\alpha = 0$, λ is either 0 or 1, and there is
148 no mixing. We used 0, 0.05, 0.1, and 0.2 for α and trained networks for 120 epochs when not mixing and
149 150 epochs when mixing. Also, to allow for a warm-up period when mixing,³⁶ we set $\alpha = 0$ for the first
150 five epochs.

151 In addition, we applied common data augmentation operations such as adjustment of brightness within
152 $\pm 10\%$, horizontal and vertical flipping, up and down scaling within $\pm 10\%$, translation of pixels horizontally
153 and vertically within ± 30 positions and random rotation within ± 45 degrees. After all data augmentation
154 operations, we used an appropriate preprocessing function¹ from the Keras API.³²

155 2.2.2 Quantification of uncertainty via *mixup* and Deep Ensembles

156 DNNs often do not generate well-calibrated and reliable uncertainty estimates for their decision.³⁷⁻⁴¹ How-
157 ever, quantification of diagnostic uncertainty is crucial for treatment decisions since proper management
158 can minimize diagnostic errors, delays or excess healthcare utilization.⁴² *mixup*³⁶ improves the calibration
159 of DNN outputs by smoothing labels through their convex combinations (Eq. 3).⁴³ In addition, we used Deep
160 Ensembles³⁹ consisting of multiple DNNs with different random initializations.^{39,44} This can improve upon
161 the single network performance both in accuracy and calibration, even with small numbers of DNNs.^{39,44-46}
162 We used ensembles with three DNNs, for which we enforced diversity by a specialized oversampling strat-
163 egy: for each DNN, we oversampled training images with respect to one of the task's labels. This enabled
164 DNNs to train on a balanced dataset while also learning about other tasks, even though the data were not
165 balanced for these. We then used the ensemble's mean output for predictions and quantified uncertainty

¹`keras.applications.inception_v3.preprocess_input`

Table 3: Accuracy of ensembles for various degrees of mixing (indicated by α). Gray row indicates the ensemble of choice for further analysis based on the validation performance for the activity detection task. In the 2-task scenario, the average validation accuracy of SRF and IRF detection tasks was used for model selection.

	Single task								
	Training			Validation			Test		
	Subretinal fluid	Intraretinal fluid	Active nAMD	Subretinal fluid	Intraretinal fluid	Active nAMD	Subretinal fluid	Intraretinal fluid	Active nAMD
$\alpha = 0$	1.000	1.000	1.000	0.988	0.971	0.958	0.924	0.950	0.914
$\alpha = 0.05$	0.983	0.994	0.975	0.971	0.963	0.951	0.906	0.919	0.909
$\alpha = 0.1$	0.978	0.994	0.948	0.948	0.919	0.929	0.868	0.891	0.856
$\alpha = 0.2$	0.983	0.991	0.851	0.975	0.946	0.853	0.881	0.909	0.702
Multiple tasks									
SRF and IRF									
$\alpha = 0$	0.999	1.000	-	0.968	0.961	-	0.902	0.937	-
$\alpha = 0.05$	1.000	0.999	-	0.983	0.966	-	0.927	0.919	-
$\alpha = 0.1$	0.999	0.999	-	0.983	0.973	-	0.911	0.924	-
$\alpha = 0.2$	0.999	1.000	-	0.983	0.963	-	0.917	0.932	-
SRF, IRF and nAMD activity									
$\alpha = 0$	1.000	0.995	0.998	0.973	0.973	0.961	0.914	0.935	0.940
$\alpha = 0.05$	0.999	0.998	1.000	0.971	0.971	0.966	0.917	0.937	0.942
$\alpha = 0.1$	1.000	0.997	0.998	0.983	0.968	0.966	0.916	0.957	0.939
$\alpha = 0.2$	1.000	0.998	1.000	0.971	0.966	0.966	0.894	0.937	0.906

166 in terms of entropy, given the average predictive probabilities.

167 2.3 Low-dimensional embedding of images

168 We used t-SNE²⁸ to obtain further insights into the decision-making process of our ensemble model. t-
169 SNE is a non-linear dimensionality reduction method, that embeds high-dimensional data points into a
170 low-dimensional space. We concatenated features from ensemble members' predetermined read-out
171 layers and performed t-SNE based on them, embedding each B-scan into the two-dimensional plane. We
172 used *openTSNE*⁴⁷ with PCA initialization to better preserve the global structure of the data and improve the
173 reproducibility.²⁹ A perplexity of 200 for 1500 iterations with an early exaggeration coefficient of 12 for the
174 first 500 iterations was used according to best-practice strategies.²⁹ Similarities between data points were
175 measured by Euclidean distance in the feature space.




Figure 3: Performance curves of the selected models on the test images. Area under the curve (AUC) values given for models also summarize the overall performance into one number (higher is better). **(a)** Receiver Operating Characteristics (ROC) curves. **(b)** Precision-recall curves.

176 2.4 Saliency Maps

177 We used Layer-wise Relevance Propagation (LRP)⁴⁸ to compute saliency maps highlighting the regions in
178 the OCT images which contributed to the DNN decisions, as it provides most clinically relevant tasks.³⁰
179 We created three saliency maps for each OCT slice: subretinal (cyan), intraretinal (magenta) and disease
180 activity in nAMD (yellow) (Fig. 5). To improve the visualization of the salient regions, saliency maps were
181 postprocessed.³⁰ Saliency maps were only shown for predictions with an estimated probability greater
182 than 0.5 since previous work has shown, that especially in absence of disease, saliency maps can lead
183 physicians to overdiagnosis.¹⁸

184 3 Results

185 We developed an ensemble of three multi-task DNNs to simultaneously detect SRF, IRF and activity of
186 nAMD on OCT B-scans (Fig. 1). Each DNN consisted of a shared convolutional core combined with pool-
187 ing operations and a fully connected (dense) layer (Fig. 2). The resulting shared representation served as
188 the basis for the decisions of the three task-specific heads. The idea behind this approach is that the DNN
189 can benefit from the shared representation induced by combining information from different tasks. We
190 compared the performance of the multi-task model with more specialized single-task models, where we
191 constructed three DNNs for each task, which did not share any representation but were trained indepen-
192 dently. In addition, we also used a 2-task model that simultaneously detected only SRF and IRF, without
193 the nAMD activity detection head.

194 All DNNs were trained on the same dataset (see Table 1 and Methods), which was graded according
195 to the nAMD activity by a retina specialist (IW) and an ophthalmologist resident (AG) with high inter-
196 grader agreement on disease activity (Cohen's kappa = 0.86). In a second step, the retina specialist further
197 examined the data for the presence of IRF and SRF. The two retinal fluid types occurred largely indepen-
198 dently, while there was natural overlap of both with the active AMD label (Table 2).

199 We selected the 3-task model with the best accuracy for the activity detection task on the validation
200 set and report accuracy values computed on an independent test set (Table 3). The 3-task model was well
201 calibrated on the test set (Adaptive expected calibration error⁴¹ of 0.0147 for SRF, 0.0104 for IRF and 0.0263
202 for active nAMD).

203 We found that the performance of the 3-task model surpassed the single-task model performance




Figure 4: Visualization of data via t-SNE of ensemble-based representations. Only the test data are shown. **(a)** Low dimensional embedding of images based on the 1024-dimensional features from the penultimate layers of single-task networks. Colored with respect to the task-specific labels. **(b)** Same as in (a) but w.r.t. 1024 features from the shared representation layer of multi-task networks. **(c)** Same map as in (b) but colored w.r.t. correct and wrong predictions. **(d)** Same map as in (b) but colored w.r.t. uncertainty min-max normalized to $[0, 1]$.

204 in disease activity detection, reaching an accuracy of 94.2 % for the multi-task model vs. 91.4% for the
205 single task model (Table 3, Fig. 3). This 3-task model optimized for AMD activity detection performed
206 slightly worse than the single-task models for SRF and IRF detection (SRF: accuracy of 0.917 vs. 0.924 for
207 multi-task vs. single-task; IRF: 0.937 vs. 0.950). For the 2-task scenario, we selected the model with the
208 highest average validation accuracy across the SRF and IRF detection tasks. Interestingly, the 2-task model
209 performed worse than the single-task and 3-task models. This highlights the importance of the explicit
210 nAMD activity detection head in the 3-task model.

211 We then further studied the representations learned by the models to gain insight into their decision
212 making-process. To this end, we extracted the representations of individual OCT scans from both single-
213 task and multi-task models and created two-dimensional embeddings of these via t-SNE (Fig. 4. In these
214 visualizations, each point represents an individual OCT scan. Scans which are similar to each other accord-
215 ing to the learned representation are mapped to nearby points. Of note, distances and in particular the size
216 of white space between clusters in t-SNE plots should be carefully interpreted.^{29,49}

217 We labeled individual points according the evidence for SRF or IRF and overall AMD activity. In the
218 single-taks DNNs, well-separated clusters were found, indicating only the learned task-label (Fig. 4a). For
219 example, OCT scans with SRF present formed a single cluster, clearly distinct from the OCT scans without
220 this label. In contrast, in the multi-task network subclusters within the active nAMD data points were
221 observed (Fig. 4a, b): OCT scans labeled with SRF formed a well-separated cluster at the bottom right, as
222 did scans with IRF labels at the top right (Fig. 4b). Interestingly, there was a small cluster in between these
223 two which contained scans labeled with both. This suggests that multi-task DNNs learned a representation
224 which could differentiate between the two fluid types. The few incorrectly classified OCT scans could be
225 found within their clusters to be placed close towards other clusters (Fig. 4c) in areas where we also found
226 examples with high classifier uncertainty (Fig. 4d).

227 We next studied how the multi-task representations emerged through processing in the network (Ap-
228 pendix, Fig. 7). While in the initial layers data points representing active nAMD were still uniformly dis-
229 tributed (Fig. 7, a-c), a clear separation of active nAMD cases developed gradually in later layers of the
230 DNN (Fig. 7, d-g), leading to best separation in the shared representation (Fig. 7, h). The decision head for
231 active AMD refined this representation only very little (Fig. 7, i).

232 We finally analyzed the saliency maps of the multi-task DNNs and asked whether the saliency maps for
233 the subtasks of SRF and IRF detection obtained from the multi-task model allowed reasoning about evi-
234 dence specific to these tasks. We generated saliency maps on four exemplary OCT scans using LRP⁴⁸ (Fig-
235 ure 5). For an OCT scan with clearly active AMD and both SRF and IRF present (Figure 5a), we found that the

236 active AMD saliency map focused on intraretinal fluids, which were also clearly visible in the task-specific
237 saliency map, and faintly highlighted regions with SRF. The SRF saliency map, however, clearly highlighted
238 SRF. In two further example scans with either IRF or SRF, respectively, active AMD saliency maps clearly
239 corresponded to the individual task maps (Figure 5b,c). We also identified a rare failure case of the ob-
240 tained saliency maps (Fig. 5d), where an OCT scan was falsely classified positive for SRF with a confidence
241 of 0.614 due to the misclassification of IRF to SRF. We hypothesize that the DNN misclassified the superior
242 border of the IRF as photoreceptor layer detached from the retinal pigment epithelium. The assumption
243 that the DNN primarily recognizes contrast-rich interfaces such as SRF and IRF is further supported by the
244 false labeling of cystoid spaces within choroid in Fig. 5b and d, while in a smoother, lower-contrast choroid
245 saliency maps do not highlight any structures (Fig. 5. Comparison with saliency maps from the single-task
246 DNNs (Fig.6) to those generated from the multi-task models shows that those single-task saliency maps
247 appear slightly more defined, but generally highlight similar areas.

248 4 Discussion

249 In this study, we developed a multi-task learning model to simultaneously detect SRF, IRF as well as disease
250 activity in OCT B-scans of nAMD patients. We showed that a 3-task model, which takes the presence of IRF
251 and SRF into account to detect disease activity in nAMD, surpassed a single task model regarding accuracy
252 in the activity detection task. Furthermore, our visualization of the multi-task model's decision-making
253 process via t-SNE showed that inactive and active nAMD B-scans formed different clusters. Among active
254 AMD B-scans, three distinct clusters were observed, which contained OCT B-scans with either SRF, IRF or
255 both fluid types. This separation could not be seen in the single-task models. Saliency maps of exemplary
256 B-scans further corroborate that task-relevant information can be extracted from the multi-task networks.

257 Thus, multi-task DNN could serve as a basis for an explainable clinical decision support system for
258 nAMD activity, providing support for clinicians in detecting active AMD, but would also allow clinicians to
259 identify evidence in the relevant sub-tasks of finding SRF and IRF. A recent meta-analysis has provided evi-
260 dence of varying influences of SRF and IRF on the visual outcome in nAMD patients.⁵⁰ Stable SRF might not
261 affect visual outcome, while fluctuations in IRF during treatment seem to negatively influence visual acu-
262 ity.⁵⁰ For this reason, treatment decisions in nAMD solely on a yes/no basis may not meet future treatment
263 guidelines, which might rather require a sophisticated decision depending on the present fluid type and its
264 variation in volume for or against an anti-VEGF injection.

265 Ophthalmology has recently seen a development of various artificial intelligence systems, yet their use in




Figure 5: Exemplary saliency maps for four optical coherence tomography (OCT) images. The first column displays the OCT B-scan with the corresponding labeling of a retinal specialist. Second to fourth column show saliency maps and the network's confidence for active nAMD (yellow), subretinal fluid (SRF) (cyan) and intraretinal fluid (IRF) (magenta). Note, that saliency maps are only shown in case of confidence > 0.5.




Figure 6: Exemplary saliency maps as in Fig. 5 but results were obtained from single-task models.

266 clinical routine remains rare with only few systems available on the market.^{51,52} One big barrier is potential
267 harm of the patient-physician relationship going hand in hand with the lack of trust in those systems.⁵³
268 Here, we combined multi-task DNNs with different visualization methods to give an insight into the DNNs'
269 reasoning and increase transparency. First, we used t-SNE as visualization method for high-dimensional
270 data^{28,29} (Fig. 4) to present the decision-making process of the model. This form of visualization provides
271 an intuitively interpretable rationale for how OCT B-scans were graded by visualizing which other B-scans
272 are similar. The results visualization may also increase an ophthalmologist's confidence in the model since
273 it illustrates shows that model's decision making reasoning resembles their own (Fig. 7). In the future, the
274 multi-task system could be extended for other signs of active nAMD such as hard exsudates, pigment
275 epithelial detachment, subretinal hyperreflective materia or hyperreflective foci.⁴

276 We further analyzed the multi-task model's decision on saliency maps of individual OCT-scans. Saliency
277 maps highlight critical regions for the model's decision and thus allow a quick visual control of its reasoning.
278 This may be important in cases of advanced AMD, where fluid is due to degeneration rather than exudation
279 to avoid overtreatment. However, different methods of saliency map agree to differing degrees with clinical
280 annotations^{30,54,55} and saliency maps can lead to overdiagnosis.¹⁸ Therefore we used the saliency map
281 technique with the best clinical relevance for AMD activity³⁰ and displayed saliency maps in case of a
282 confidence of the algorithm > 0.5 . Compared to saliency maps of single task DNNs, multi-task saliency
283 maps seem to draw slightly less sharp contours, however, we found good overlap between regions used
284 for active AMD detection and those for SRF and IRF.

285 Future studies will need to assess how well these multi-task learning results transfer from this data
286 sample acquired at a tertiary center in Germany. It would be desirable to perform similar analysis with
287 larger and more diverse data sets, to test also the generalization to other populations, different recording
288 qualities as well as OCT devices (including mobile devices). Further, performance could be potentially
289 increased by combining the multi-task network with a segmentation layer,¹⁵ which could reduce false
290 positive cases. Additionally, in clinical routine, activity decision is made on a whole volume not a single
291 B-scan, which could technically be implemented by combining the results from individual B-scans, e.g. by
292 majority voting or uncertainty propagation.

293 While the approval of anti-VEGF has decreased economic and overall treatment burden of nAMD mea-
294 sured in disability-adjusted life,^{56,57} a large number of patients still discontinues treatment.⁵⁸ Patients
295 named the need for assistance, either in the form of a travel companion or a family member, as the main
296 reason for discontinuation.¹⁴ Additionally, recurrence of quiescent disease requiring prompt treatment is
297 common, making life-long monitoring necessary.⁵⁹ For these reasons, automated solutions allowing moni-

298 toring close home or even at home are promising technologies:^{60,61} They provide easier access and reduce
299 the disease burden on the individual.⁶² Automated solutions for fluid detection have further gained popu-
300 larity during the Covid-19 pandemic, which showed the devastating effects of delay or interruption of nAMD
301 treatment on visual function.^{9,59} Despite promising results in laboratory settings, real-world data revealed
302 significantly lower performance rates of home-based OCT with in particular SRF being overlooked by the
303 system.⁶³ This shows the necessity of further developments on the machine learning side to guarantee
304 reliable use, with multi-task learning as suggested in this study being a viable option.

305 5 Acknowledgments

306 We thank the German Ministry of Science and Education (BMBF) for funding through the Tübingen AI Cen-
307 ter (FKZ 01IS18039A) and the German Science Foundation for funding through a Heisenberg Professorship
308 (BE5601/4-2) and the Excellence Cluster "Machine Learning – New Perspectives for Science" (EXC 2064,
309 project number 390727645). H. Faber thanks the Faculty of Medicine, Eberhard Karls University of Tue-
310 bingen, Germany (application number 463-0-0) for additionally funding her research through the Junior
311 Clinician Scientist Program (application number 463-0-0). We further thank Novartis AG for funding part
312 of the research. The funding bodies did not have any influence in the study planning and design.

313 Author contribution statement

314 MSA, HF and PB designed the research. MSA performed the experiments. GA, WI, FZ, LK were involved in
315 data acquisition. FZ, HF, GA, LK and WI provided medical advice. MSA, HF and PB wrote the manuscript
316 with input from all authors. All authors approved the final version of the manuscript and agreed on being
317 accountable for the work.

318 References

- 319 1. W. H. Organization, *et al.* (2019).
- 320 2. W. L. Wong, *et al.*, *The Lancet Global Health* **2**, e106 (2014).
- 321 3. F. L. Ferris, S. L. Fine, L. Hyman, *Archives of ophthalmology* **102**, 1640 (1984).

- 322 4. R. F. Spaide, *et al.*, *Ophthalmology* **127**, 616 (2020).
- 323 5. P. J. Rosenfeld, *Investigative ophthalmology & visual science* **57**, OCT14 (2016).
- 324 6. S. Riedl, W.-D. Vogl, S. M. Waldstein, U. Schmidt-Erfurth, H. Bogunovi, *Ophthalmology Retina* **6**, 291
325 (2022).
- 326 7. S. M. Waldstein, *et al.*, *Ophthalmology* **123**, 1521 (2016).
- 327 8. F. G. Holz, *et al.*, *British Journal of Ophthalmology* **100**, 1623 (2016).
- 328 9. A. Valverde-Megías, *et al.*, *Journal of Clinical Medicine* **10**, 3551 (2021).
- 329 10. C. Arruabarrena, *et al.*, *Journal of clinical medicine* **10**, 3281 (2021).
- 330 11. S. Day, K. Acquah, P. P. Lee, P. Mruthyunjaya, F. A. Sloan, *American journal of ophthalmology* **152**, 1014
331 (2011).
- 332 12. A. Almony, *et al.*, *Journal of managed care & specialty pharmacy* **27**, 1260 (2021).
- 333 13. J. M. Ruiz-Moreno, L. Arias, M. J. Abrales, J. Montero, P. Udaondo, *International ophthalmology* **41**,
334 3427 (2021).
- 335 14. B. Sobolewska, M. Sabsabi, F. Ziemssen, *Clinical Ophthalmology (Auckland, NZ)* **15**, 4317 (2021).
- 336 15. J. De Fauw, *et al.*, *Nature medicine* **24**, 1342 (2018).
- 337 16. J. Yim, *et al.*, *Nature Medicine* **26**, 892 (2020).
- 338 17. T. D. Keenan, *et al.*, *Ophthalmology* **128**, 100 (2021).
- 339 18. R. Sayres, *et al.*, *Ophthalmology* **126**, 552 (2019).
- 340 19. T. Grote, P. Berens, *Journal of medical ethics* **46**, 205 (2020).
- 341 20. T. Grote, P. Berens, *Bioethics* **36**, 134 (2022).
- 342 21. R. Caruana, *Machine learning* **28**, 41 (1997).
- 343 22. Y. Wang, *et al.*, *CoRR* **abs/2008.05808** (2020).
- 344 23. Q. Chen, *et al.*, *AMIA Summits on Translational Science Proceedings* **2019**, 505 (2019).
- 345 24. G. Ghahramani, *et al.*, *AMIA Annual Symposium Proceedings (American Medical Informatics Association,*
346 *2021)*, vol. 2021, p. 506.
- 347 25. S. Sharma, *et al.*, *Ophthalmology* **123**, 865 (2016).

- 348 26. S. Llorente-González, *et al.*, *Acta Ophthalmologica* (2021).
- 349 27. M. Saenz-de Viteri, *et al.*, *Acta Ophthalmologica* **99**, 861 (2021).
- 350 28. L. Van der Maaten, G. Hinton, *Journal of machine learning research* **9** (2008).
- 351 29. D. Kobak, P. Berens, *Nature communications* **10**, 1 (2019).
- 352 30. M. S. Ayhan, *et al.*, *Medical Image Analysis* p. 102364 (2022).
- 353 31. C. Szegedy, V. Vanhoucke, S. Ioffe, J. Shlens, Z. Wojna, *Proceedings of the IEEE conference on computer*
354 *vision and pattern recognition* (2016), pp. 2818–2826.
- 355 32. F. Chollet, *et al.*, Keras (2015).
- 356 33. O. Russakovsky, *et al.*, *International journal of computer vision* **115**, 211 (2015).
- 357 34. Y. E. Nesterov, *Dokl. akad. nauk Sssr* (1983), vol. 269, pp. 543–547.
- 358 35. I. Sutskever, J. Martens, G. E. Dahl, G. E. Hinton, *ICML (3)* **28**, 5 (2013).
- 359 36. H. Zhang, M. Cisse, Y. N. Dauphin, D. Lopez-Paz, *6th International Conference on Learning Representations (ICLR)* (2018), pp. 1–13.
- 360 37. C. Guo, G. Pleiss, Y. Sun, K. Q. Weinberger, *Proceedings of the 34th International Conference on Machine Learning–Volume 70 (JMLR. org, 2017)*, pp. 1321–1330.
- 361 38. A. Kendall, Y. Gal, *Advances in Neural Information Processing Systems* (2017), pp. 5580–5590.
- 362 39. B. Lakshminarayanan, A. Pritzel, C. Blundell, *Advances in Neural Information Processing Systems* (2017),
363 pp. 6405–6416.
- 364 40. A. Malinin, M. Gales, *Advances in Neural Information Processing Systems* (2018), pp. 7047–7058.
- 365 41. Y. Ding, J. Liu, J. Xiong, Y. Shi, *arXiv preprint arXiv:1903.02050* (2019).
- 366 42. V. Bhise, *et al.*, *Journal of general internal medicine* **33**, 103 (2018).
- 367 43. S. Thulasidasan, G. Chennupati, J. A. Bilmes, T. Bhattacharya, S. Michalak, *Advances in Neural Information Processing Systems* **32** (2019).
- 368 44. S. Fort, H. Hu, B. Lakshminarayanan, *arXiv preprint arXiv:1912.02757* (2019).
- 369 45. Y. Ovadia, *et al.*, *Advances in Neural Information Processing Systems* (2019), pp. 13991–14002.
- 370 46. M. S. Ayhan, *et al.*, *Medical Image Analysis* p. 101724 (2020).
- 371
- 372
- 373

- 374 47. P. G. Poliar, M. Stražar, B. Zupan, *bioRxiv* (2019).
- 375 48. S. Bach, *et al.*, *PloS one* **10**, e0130140 (2015).
- 376 49. J. N. Böhm, P. Berens, D. Kobak, *Journal of Machine Learning Research* **23**, 1 (2022).
- 377 50. U. Chakravarthy, *et al.*, *Eye* **35**, 2983 (2021).
- 378 51. M. D. Abramoff, P. T. Lavin, M. Birch, N. Shah, J. C. Folk, *NPJ digital medicine* **1**, 1 (2018).
- 379 52. A. Olvera-Barrios, *et al.*, *British Journal of Ophthalmology* **105**, 265 (2021).
- 380 53. J. J. Hatherley, *Journal of Medical Ethics* **46**, 478 (2020).
- 381 54. A. Singh, *et al.*, *Ophthalmic Medical Image Analysis*, H. Fu, M. K. Garvin, T. MacGillivray, Y. Xu, Y. Zheng,
382 eds. (Springer International Publishing, Cham, 2020), pp. 21–31.
- 383 55. T. Van Craenendonck, B. Elen, N. Gerrits, P. De Boever, *Translational vision science & technology* **9**, 64
384 (2020).
- 385 56. X. Xu, *et al.*, *BMC Public Health* **20**, 1 (2020).
- 386 57. K. Mulligan, *et al.*, *JAMA ophthalmology* **138**, 40 (2020).
- 387 58. I. Westborg, *et al.*, *Acta Ophthalmologica* **95**, 787 (2017).
- 388 59. S. Aslanis, U. Amrén, C. Lindberg, D. Epstein, *Ophthalmology Retina* **6**, 15 (2022).
- 389 60. F. A. Sloan, G. Picone, D. S. Brown, P. P. Lee, *Journal of the American Geriatrics Society* **53**, 1867 (2005).
- 390 61. E. Y. Chew, *et al.*, *Contemporary clinical trials* **37**, 294 (2014).
- 391 62. K. Nahen, G. Benyamini, A. Loewenstein, *Klinische Monatsblätter für Augenheilkunde* **237**, 1410 (2020).
- 392 63. Y. Liu, N. L. Holekamp, J. S. Heier, *Ophthalmology Retina* (2022).

393 Appendix




Figure 7: Layer-wise visualization of test data via t-SNE. Starting just before the first Inception module (a) and reading out feature representations yielded by every other module (b-f) along with the last Inception module (g), the shared representation layer (h) and the nAMD activity detection head's penultimate layer (i), we performed t-SNE with the aforementioned settings. Useful representations emerged towards the end of convolutional stack and the task-specific representation allowed the best separation of nAMD active cases from those inactive. Exact read-out locations can be found in Fig. 8.




Figure 8: Read-out locations within the convolutional stack of the InceptionV3 architecture (indicated by big black arrows). In addition to these, we used the shared representation layer and task-specific layers of our multi-task networks (see Fig. 2). Base figure was obtained from <https://cloud.google.com/tpu/docs/inception-v3-advanced>.