Fast and Accurate Maximum-Likelihood Estimation of Multi-Type Birth-Death Epidemiological Models from Phylogenetic Trees

Anna Zhukova[1,2,3,4,*], Frédéric Hecht[5], Yvon Maday[5,6], and Olivier Gascuel[1,7,*]

[1] *Unité Bioinformatique Evolutive, Institut Pasteur, Université de Paris, Paris, France*

[2] *Bioinformatics and Biostatistics Hub, Institut Pasteur, Université de Paris, Paris, France*

[3] *Epidémiologie et modélisation de la résistance aux antimicrobiens, Institut Pasteur, Université de Paris, Paris, France*

[4] *Université Paris-Saclay, UVSQ, Inserm, CESP, Villejuif, France*

[5] *Sorbonne Université, CNRS, Université Paris Cité, Laboratoire Jacques-Louis Lions (LJLL), Paris, France*

[6] *Institut Universitaire de France*

[7] *Institut de Systématique, Evolution, Biodiversité (ISYEB) - URM 7205 CNRS,*
Muséum National d'Histoire Naturelle, SU, EPHE & UA, Paris, France

*Corresponding authors: anna.zhukova@pasteur.fr (AZ), olivier.gascuel@mnhn.fr (OG)

Abstract

Multi-type birth-death (MTBD) models are phylodynamic analogies of compartmental models in classical epidemiology. They serve to infer such epidemiological parameters as the average number of secondary infections R_e and the infectious time from a phylogenetic tree (a genealogy of pathogen sequences). The representatives of this model family focus on various aspects of pathogen epidemics. For instance, the birth-death exposed-infectious (BDEI) model describes the transmission of pathogens featuring an incubation period (when there is a delay between the moment of infection and becoming infectious, as for Ebola and SARS-CoV-2), and permits its estimation along with other parameters.

With constantly growing sequencing data, MTBD models should be extremely useful for unravelling information on pathogen epidemics. However, existing implementations of these models in a phylodynamic framework have not yet caught up with the sequencing speed. Computing time and numerical instability issues limit their applicability to medium data sets (≤ 500 samples), while the accuracy of estimations should increase with more data.

We propose a new highly parallelizable formulation of ordinary differential equations for MTBD models. We also extend them to forests to represent situations when a (sub-)epidemic started from several cases (e.g. multiple introductions to a country). We implemented it for the BDEI model in a maximum likelihood framework using a combination of numerical analysis methods for efficient equation resolution. Our implementation estimates epidemiological parameter values and their confidence intervals in four minutes on a phylogenetic tree of 10 000 samples. Comparison to the existing implementations on simulated data shows that it is not only 30 000 times faster, but also more accurate. An application of our tool to the 2014 Ebola epidemic in Sierra-Leone is also convincing, with very fast calculation and precise estimates. Phylodynamics, Epidemiology, Mathematical modelling, Ordinary Differential Equations, Birth-Death models, Ebola

The interaction of epidemiological and evolutionary processes leaves a footprint in pathogen genomes. Phylodynamics leverages this footprint to estimate epidemiological parameters, such as the average number of secondary infections, R_e (Grenfell et al., 2004; Volz et al., 2013). It relies on models that bridge the gap between traditional epidemiology and sequence data. Under these models, the parameter inference is drawn from topology and branch lengths of pathogen phylogenetic trees (i.e. genealogies of the pathogen population, approximating the transmission trees) combined with metadata on the samples. This is particularly useful for emerging epidemics, for which not enough data (e.g. incidence curves) might yet be gathered for accurate estimations with classical epidemiological methods. Rapidly growing genetic data coupled with phylodynamic estimations can provide valuable insights at an early stage of the epidemic spread and help prevent it (e.g. accurate estimation of R_e is crucial for adjusting potential non-pharmaceutical interventions, such as lockdowns).

Phylodynamic models can be classified into two main families: coalescent (Volz et al., 2009; Drummond et al., 2005; Pybus et al., 2000) and birth-death (BD) (Kendall, 1948; Maddison et al., 2007; Stadler, 2009, 2010). Coalescent models are often preferred for estimating deterministic population dynamics, however BD models are better adapted for highly stochastic processes, such as the dynamics of emerging pathogens (Macpherson et al., 2021). In BD models, births represent pathogen transmission events, while deaths correspond to becoming non-infectious (e.g. due to healing, self-isolation, starting a treatment, or death). Models of the BD

family are phylodynamic analogies of compartmental models in classical epidemiology (e.g. SIR, Susceptible-Infectious-Recovered (Hethcote, 2000)). Many extensions of the classical BD model with incomplete sampling (BDS (Stadler, 2009)) were developed over time, including multi-type birth-death (MTBD) models (Stadler and Bonhoeffer, 2013). They add a population structure to the classical birth-death process by allowing for different types of individuals. A particularly useful representative of the MTBD family is the birth-death exposed-infectious (BDEI) model (Stadler et al., 2014). It was designed for pathogens featuring an incubation period between the moments of infection and of becoming infectious, e.g. Ebola and SARS-CoV-2. It is closely related to the SEIR (Susceptible-Exposed-Infectious-Recovered (Hethcote, 2000)) model, widely used in classical epidemiology.

In MTBD framework, the evolution of a transmission tree is described with a system of master differential equations with respect to global time. The model parameters can be estimated with maximum-likelihood (Stadler and Bonhoeffer, 2013) or Bayesian methods (Bouckaert et al., 2019) by exploring the likelihood (or posterior probability) landscape of trees. However, the closed form solution of the master equations exists only for the initial BDS model (Stadler, 2009), while for its extensions (like the BDEI model and MTBD models in general) the master equations for likelihood calculation need to be resolved with numerical methods. The complexity of the master equations and their boundary conditions (which recursively depend on the tree evolution later in time), make their numerical resolution challenging and time consuming (Scire et al., 2022; Voznica et al., 2022).

The trade-off between the complexity of the biological questions a model can address and the computational speed for its parameter estimation is crucial in phylodynamics. On one hand, denser sampling should improve the accuracy of parameter estimations with complex models. On the other hand, denser sampling leads to larger data sets (thousands of samples), while computational issues often limit model applicability to medium or small ones (hundreds of samples). Calculations become time-consuming and numerically challenging (e.g. due to underflow issues) as tree size increases, resulting in numerical instability and inaccuracy (Scire et al., 2022; Voznica et al., 2022). Existing likelihood-based implementations of the BDEI model (Stadler and Bonhoeffer, 2013; Bouckaert et al., 2019; Scire et al., 2022) can handle trees of medium size. In (Voznica et al., 2022) we proposed PhyloDeep, a likelihood-free deep-learning-based solution to the numerical instability issue. While being very efficient and accurate at the prediction stage, this approach however requires a computationally heavy training stage: Millions of trees covering a wide parameter range (where the real data is expected to fall) need to be simulated for training the deep learning predictor.

In this study we fix the computational bottleneck and extend the applicability of MTBD models by proposing a likelihood-based approach that improves the accuracy and reduces the likelihood computation time. We propose a new formulation of the MTBD master equations that (i) removes the recursive dependency between child and parent nodes in the tree, hence permitting their parallel computation, and (ii) avoids numerical issues that could arise from very small boundary condition values. In the general MTBD case, a tree likelihood is calculated by combining the results of parallel equation resolutions for different tree nodes. This step is performed in a computationally light but recursive way. However, we identified a subclass of MTBD models (including the BDEI model) whose likelihood formulae can be expressed in a non-recursive manner.

We applied our findings to the BDEI model and implemented its parameter estimator PyBDEI, employing targeted numerical analysis methods for accurate and fast resolution of its equations. We show the accuracy and speed of PyBDEI on simulated data and compare it to the gold standard Bayesian tool BEAST2 (Bouckaert et al., 2019) and the deep-learning-based tool PhyloDeep (Voznica et al., 2022). We find that our approach outperforms the competitors and makes the BDEI model applicable to very large data sets. Lastly, we apply PyBDEI to infer the epidemiological parameters that shaped the Ebola epidemic in Sierra-Leone in 2014. Our estimator is freely available at `github.com/evolbioinfo/bdei`.

1 MTBD models and their special case, the BDEI model

In a pathogen transmission tree $\mathscr{T}$ (approximated by a time-scaled pathogen phylogeny) the tips represent sampled pathogens, patient state transitions occur along the branches, and bifurcations (i.e. internal nodes) correspond to transmissions (Fig. 1). The tree branch lengths are measured in units of time, where T is the time that passed between the tree root (the beginning of the (sub-)epidemic) and the last sampled tip.

The basic BDS model (Stadler, 2009) has only one state: *infectious I*. An individual in state I can transmit their pathogen to another individual (whose state will be also I) at a constant average rate λ, or stop being infectious at a constant average rate ψ (due to treatment start, healing, self-isolation or death). After stopping being infectious, the individual and their pathogen exit the study, at which point the pathogen might get sampled with a probability ρ. The sampling is incomplete: an infectious individual may be removed from the system without being sampled (i.e. unobserved in the transmission tree), for example due to healing. The BDS model permits inference of such important epidemiological parameters as:

- *effective reproduction number* $R_e = \frac{\lambda}{\psi}$, expected number of individuals directly infected by an infectious case;

- *infectious time* $\frac{1}{\psi}$, time during which an infectious individual can further spread the epidemic.

The BDS model is asymptotically unidentifiable (see Remark 3.4 in (Stadler, 2009)), but to become identifiable it requires one of the parameters to be fixed.

MTBD models (Stadler and Bonhoeffer, 2013) add population structure by allowing different individual states, transmissions between them and state changes. A general MTBD model with d individual states has $2d^2 + d$ parameters: An individual in state k ($k \in \{1, \ldots, d\}$) can be removed at a constant average rate ψ_k (with pathogen sampling probability ρ_k), change their state to state l ($l \in \{1, \ldots, d\}$) at a constant average rate μ_{kl} (where $\mu_{kk} = 0$), and transmit their pathogen to an individual in state l at a constant average rate λ_{kl}. The time between events of the same type is hence modelled with exponential distribution.

The BDEI model (Stadler et al., 2014) (Fig. 2), for example, is a special case of MTBD models that adds a second possible state to the state I: *exposed* E, an individual who is already infected but not yet infectious (cannot transmit), and will eventually become infectious.

Under the BDEI model, the only allowed transmissions are from I to E: At the moment of a transmission, the transmitter is always in state I, while the recipient is in state E. Hence the only non-zero transmission rate is $\lambda_{IE} = \lambda$, while the other 3 transmission rates are trivial: $\lambda_{II} = \lambda_{EI} = \lambda_{EE} = 0$. As we typically do not have the information to distinguish a transmitter from a recipient in a phylogenetic tree (which approximates the transmission tree), we have to consider both possibilities during parameter estimation. For the MTBD models where multiple states can transmit, the number of possibilities increases combinatorially.

Under the BDEI model, we assume that only the individuals in state I can exit the study (at rate $\psi_I = \psi$) and be detected and sampled (with a probability $\rho_I = \rho$): For instance, for many pathogens with an incubation period, the detection is triggered by the onset of symptoms, which in turn happens in the infectious state. Hence all the BDEI tree tips are in state I, and $\psi_E = \rho_E = 0$.

In addition to R_e and infectious time, the BDEI model permits inference of a third epidemiological parameter:

- *incubation period* $\frac{1}{\mu}$, time between the infection and becoming infectious.

The incubation period can be expressed via becoming infectious rate $\mu_{EI} = \mu$, corresponding to a state transition from E to I. The inverse state change is not allowed: $\mu_{IE} = 0$.

MTBD models, as extensions of the BDS model, are asymptotically unidentifiable and require one of their parameters to be fixed in order to become identifiable. In practice, it is often the sampling probability, as it may be approximated from epidemiological data (e.g. the proportion of sampled cases among the declared ones) or the infectious time (estimated from observations of infected cases).

1.1 Master equations

In the standard MTBD master equations proposed by Stadler and Bonhoeffer (2013), time goes backward from the last sampling event (the most recent tip in the tree) till the beginning of the epidemic. These equations permit calculation of the likelihood density of the data (observed tree) given the model parameter values Θ. In the general MTBD case, the observed tree, reconstructed from sampled pathogen genomes, differs from the real transmission tree: the states of its internal nodes (corresponding to transmissions) are unknown, we cannot distinguish between the transmitter and the recipient branches, the moments of state changes are also unknown, and due to incomplete sampling some parts of the real transmission tree are unobserved in the reconstructed tree. We therefore need to integrate over all possibilities while calculating the likelihood. The BDEI model is a slightly simpler case as only infectious individuals can transmit or get sampled, hence all the node states are known (I). For the BDEI model $\Theta = \{\mu, \lambda, \psi, \rho\}$.

In System (1) we show the MTBD master equations, however presenting them with the time t going forward from the time of the root ($t = 0$) to the time of the last sampled tip ($t = T$). These equations describe the likelihood density functions (LDFs) $L_s^{(i)}(t)$ of evolving as in the reconstructed tree, starting at time t in state s (for the BDEI model $s \in \{E, I\}$) on a branch connecting a node i to its parent, and till the end of the sampling period. The boundary condition is defined at time $t = t_i$ (i.e. at the node i). To account for incomplete sampling, the system also includes the probabilities $U_s(t)$ of evolving unobserved till the time T, starting at time t in state s.

From now on, we use the following notation: the id of the root node is 0; the ids of its children are 00 and 01; and, by extension, the children of a node i (if they exist) have ids $i0$ and $i1$ (as in Fig. 1). Additionally if the state of a node i is known, then we will name it si. (For example for the BDEI model $si = I \; \forall i$.)

Figure 1: A transmission tree $\mathcal{T}$ with $n = 5$ external nodes (i.e. tips, which correspond to sampling events: $0000, 0001, 001, 010, 011$), $n - 1 = 4$ internal nodes (which correspond to transmissions: 0 (the root) and $00, 01, 000$) and $2n - 2 = 8$ branches (plus the root branch of zero length). Time t starts at the root of the tree ($t = 0$) and goes till the last sampled tip. The times of the nodes are shown on the left, e.g. t_{0001} is the time of tip 0001 (when 0001's pathogen was sampled). T corresponds to the end of the sampling period (when the most recent tip, 0000, was sampled).

Figure 2: The BDEI model. An individual in exposed state E becomes infectious at a rate μ. An infectious individual I transmits the pathogen at a rate λ (hence creating a new exposed individual E), and gets removed at a rate ψ (decreasing the number of infectious individuals I). Upon removal, the individual's pathogen might be observed with a probability ρ. Note, that the BDEI model does not include a susceptible state S (as for example SEIR) and makes the assumption that the susceptible population is unlimited (as for example in the beginning of an epidemic, or when the removed individuals could get reinfected).

$$
\begin{cases}
\dot{L}_s^{(i)}(t) = & \Big(\sum\limits_{k=1}^{d} \mu_{sk} + \sum\limits_{k=1}^{d} \lambda_{sk} + \psi_s\Big) L_s^{(i)}(t) \leftarrow \textit{no event in the next infinitesimal time } \Delta t \\[6pt]
& - \sum\limits_{k=1}^{d} \mu_{sk} L_k^{(i)}(t) \leftarrow \textit{change of the state, followed by evolution from the new state} \\[6pt]
& - \sum\limits_{k=1}^{d} \lambda_{sk} L_s^{(i)}(t) U_k(t) \leftarrow \textit{transmissions, where the recipient subtree stayed unsampled} \\[6pt]
& - \sum\limits_{k=1}^{d} \lambda_{sk} L_k^{(i)}(t) U_s(t) \leftarrow \textit{transmissions, where the transmitter subtree stayed unsampled} \\[6pt]
L_s^{(i)}(t_i) = & C_s^{(i)} = \begin{cases} 0, & \textit{if } i \textit{ cannot be in state } s \\ \psi_s \rho_s, & \textit{if } i \textit{ is a sampled tip in state } s \\ \sum\limits_{k=1}^{d} \lambda_{sk}\Big(L_s^{(i0)}(t_i)L_k^{(i1)}(t_i) + L_k^{(i0)}(t_i)L_s^{(i1)}(t_i)\Big), & \textit{if } i \textit{ is internal, in state } s \end{cases} \\[6pt]
\dot{U}_s(t) = & \Big(\sum\limits_{k=1}^{d} \mu_{sk} + \sum\limits_{k=1}^{d} \lambda_{sk} + \psi_s\Big) U_s(t) \leftarrow \textit{no event in the next infinitesimal time } \Delta t \\[6pt]
& - \sum\limits_{k=1}^{d} \mu_{sk} U_k(t) \leftarrow \textit{change of the state, folowed by unsampled evolution from the new state} \\[6pt]
& - \sum\limits_{k=1}^{d} \lambda_{sk} U_s(t) U_k(t) \leftarrow \textit{transmission, then unsampled evolutions of transmitter and recipient subtrees} \\[6pt]
& - \psi_s(1 - \rho_s) \leftarrow \textit{removal without sampling} \\[6pt]
U_s(T) = & 1 \leftarrow \textit{the probability to stay unsampled over time 0 is 1}
\end{cases}
\tag{1}
$$

1.2 Tree likelihood density

The likelihood density of a tree $\mathscr{T}$ for given parameter values Θ is then calculated as the LDF at time $t = 0$ on the root, whose id is 0 and whose state is $s0$:

$$
L(\mathscr{T}|\Theta) = L_{s0}^{(0)}(0) \tag{2}
$$

So far, we assumed that the epidemic started directly with the first transmission, however we can relax this assumption. The root of the tree in Figure 1 is placed at $t = 0$, and does not have a branch (its length is zero). Allowing for a non-zero root branch corresponds to an epidemic start some time before the first transmission. This implies that the state of the individual represented by the root branch at time $t = 0$ is unknown, and all possible states should be considered (Eq. (3)). The same formula applies to cases where the root state is unknown. Assuming that the relative number of individuals in each state is at equilibrium, we can calculate the weight π_s of each possible state s (derived in (Stadler et al., 2013) for the general MTBD case and in Equation (14) for the BDEI model).

$$
L(\mathscr{T}|\Theta) = \sum_{s=1}^{d} \pi_s L_s^{(0)}(0) \tag{3}
$$

Root's LDF *recursively* depends on the LDFs of the child node branches via the boundary condition $C_s^{(0)}$, and hence is calculated with a pruning algorithm (Felsenstein, 1973) while climbing the tree from tips till the root. Therefore when parallelized to maximum, it still requires $O(h_{\mathscr{T}})$ consecutive steps, where $h_{\mathscr{T}}$ stands for the height of the tree $\mathscr{T}$ and depends on its topology: (balanced tree) $log(n) \leq h_{\mathscr{T}} \leq n$ (ladder-like tree). At each step System (1) needs to be resolved for the corresponding nodes. Moreover, the values of $L_s^{(i)}(t)$ at internal nodes and their boundary conditions $C_s^{(i)}$ progressively become smaller as getting deeper in the tree, due to successive additions and multiplications of the LDF values. In trees with many tips, this might lead to numerical underflow, and hence such measures as rescaling need to be taken (Berger and Stamatakis, 2009; Defour, 2010; Scire et al., 2022).

1.3 Extension to forests

In some cases, the assumption that a (sub-)epidemic started with one infected individual might be too constraining. For instance, there could be multiple pathogen introductions to a country of interest (e.g. while in China the SARS-CoV-2 epidemic is commonly assumed to have started with one case, there were multiple

independent introductions to other countries (Zhukova et al., 2020)). Another example is a change of health policies leading to a change in parameter values (e.g. sampling). Such a change corresponds to a new stage of the epidemic, starting from several infected cases from the previous stage. In Bayesian settings, the situations when the system behaviour (and parameters) change over time, are modelled via skyline methods. Stadler et al. (2013) developed the one-state Bayesian birth-death skyline plot that divides the time into intervals and allows for different piecewise constant rates on them. Kühnert et al. (2016) combined the MTBD model with the skyline to allow for both piecewise-constant rate changes over time and multiple individual types. The skyline approach therefore relies on a single tree, but estimates a separate set of parameters for each time interval, all under the same model. As the number of parameters increases with multiple skyline intervals, MTBD-skyline models therefore require more data and computational time for their accurate estimation, and are more prone to numerical instability than the classical MTBD models.

We propose a simpler alternative, where the (sub-)epidemic starts with multiple individuals (not necessarily at the same time) and leads to a forest $\mathscr{F}$ of f observed trees: $\mathscr{T}_1, \ldots, \mathscr{T}_f$. If all the trees started at the same time (e.g. due to health policy change), the information on the number of declared cases (m) at the start of the (sub-)epidemic might be available. If this number is larger than the number of observed trees ($m > f$), it implies that the other $u = m - f$ trees stayed unobserved as none of their tips got sampled. This can be incorporated in the likelihood calculation. Forest likelihood formula hence combines the likelihoods of f observed and u hidden trees, and can be represented in logarithmic form (4). Tree likelihood formula is its special case, where $f = 1$ and $u = 0$. As our application to Ebola data (see Application) shows, u is an important parameter: while the results are not very sensible to slight u variations, ignoring it completely (e.g. using $u = 0$ instead of $u \approx 500$ in our example) can change the inferences.

$$logL(\mathscr{F}|\Theta, u) = u \, log\Big(\sum_{s=1}^{d} \pi_s U_s(0) \Big) + \sum_{j=1}^{f} logL(\mathscr{T}_j|\Theta) \tag{4}$$

In Equation (4) we assumed that all the $f + u$ sub-epidemics in the forest $\mathscr{F}$ started at the same time ($t = 0$). This condition can be easily relaxed by replacing zeros with the corresponding starting times (for unobserved trees and for root branch evolutions).

Using forests permits estimation of the model parameters on the last skyline interval without the restriction that the epidemic followed the same model before this interval (i.e. the top part of the tree, which includes the common ancestors of the forest roots). It reduces the number of parameters to those of the last interval, and informs the inference with the number of declared cases at the start of the sub-epidemic. It also permits estimation of parameters for a (sub-)epidemic that started with several individuals but not at the same time (e.g. due to multiple introductions to a country).

2 Avoiding numerical problems and parallelizing calculations

In this section we introduce a way to rewrite LDFs in System (1) that permits (i) obtaining simpler boundary conditions to avoid potential numerical issues during resolution of equations; and (ii) removing recursion and resolving equations for each tree node in parallel, hence speeding up the calculations.

System (1) has several properties. First of all, its subsystem that defines unobserved probabilities ($U_1(t), \ldots, U_d(t)$) is self-defined, and hence can be calculated independently from the rest. Secondly, in the subsystem that defines observed LDFs ($L_1^{(i)}(t), \ldots, L_d^{(i)}(t)$) the right-hand side of the differential equations is a sum where each element is linear with respect to one of the $L_s^{(i)}(t)$ ($s \in \{1, \ldots, d\}$), and this sum does not contain any free term. This condition implies that if we rescale $L_1^{(i)}(t), \ldots, L_d^{(i)}(t)$ by a common factor, the differential equations will not change. Moreover, if the boundary conditions for all states but one are zero ($C_s^{(i)} = 0 \; \forall s \neq si; \; C_{si}^{(i)} > 0$), the rescaling will change the boundary condition only for $L_{si}^{(i)}(t)$. The latter is the case when tree node states are known, for example for the BDEI model, under which all nodes are in state I.

Assuming the state of the node i is known (si), let us define $p_{s,si}^{(i)}(t)$ as:

$$p_{s,si}^{(i)}(t) = L_s^{(i)}(t)/C_{si}^{(i)}. \tag{5}$$

Then the differential equations for $p_{s,si}^{(i)}(t)$ will only differ from those for $L_s^{(i)}(t)$ in the boundary condition for $s = si$, which is $p_{si,si}^{(i)}(t_i) = 1$ (the other boundary conditions stay zero). Conceptually, $p_{s,si}^{(i)}(t)$ is a probability of an individual evolving as on an observed branch that connects a node i to its parent, starting at time t in state s on this branch and finishing at time t_i in state si (without taking into account i's subtree and the event at node i).

Solving the master equations for $p_{s,si}^{(i)}(t)$ instead of $L_s^{(i)}(t)$ permits us to both (i) remove the recursive dependency between child and parent nodes; and (ii) avoid numerical issues that could arise from very small values of the boundary condition of $L_{si}^{(i)}(t)$, which is particularly pertinent for large trees. The calculation of $p_{si}^{(i)}(t)$ can be done in parallel for each node i. Hence if distributed between $2n-2$ (number of non-root tree nodes) cores, the number of parallel master equation resolutions becomes constant. If tree node states are unknown, all the possibilities ($si = k \; \forall k \in \{1,\dots,d\}$) for each node i can be considered separately and in parallel.

In the case where all node states are known (e.g. from metadata or due to model itself, as for the BDEI case), using $p_{s,si}^{(i)}(t)$ instead of $L_s^{(i)}(t)$ also permits us to express tree likelihood for model parameters Θ in a non-recursive way, and easily transform it to a logarithmic form (6) (to avoid underflow issues while multiplying small numbers). In Materials and Methods we show its equivalence to the recursive representation (2).

$$
\begin{aligned}
logL(\mathscr{T}|\Theta) = & \sum_{i \in tips} log(\psi_{si}\rho_{si}) \quad \leftarrow \textit{sampling of n tips} \\
& + \sum_{i \in \substack{internal \\ nodes}} log\Big(\sum_{k=1}^{d} \lambda_{si,k} \qquad\qquad\qquad \leftarrow \textit{n} - 1 \textit{ transmission events} \\
& \qquad\qquad \cdot \big(p_{si,si0}^{(i0)}(t_i)p_{k,si1}^{(i1)}(t_i) + p_{k,si0}^{(i0)}(t_i)p_{si,si1}^{(i1)}(t_i) \big) \Big) \leftarrow \textit{i's child branch evolutions}
\end{aligned}
$$

$$(6)$$

For the general case, the combination of different internal node state configurations into tree likelihood formula need to be performed with a pruning algorithm (Felsenstein, 1973). The likelihood-combining tree traversal starts from the tips and climbs the tree till the root, while calculating a subtree LDF $L_k^{(i)}(t_i)$ for each visited node i for each possible state k:

$$
L_k^{(i)}(t_i) = \begin{cases}
0, & \textit{if i cannot be in state k} \\
\psi_k\rho_k, & \textit{if i is a tip whose state can be k} \\
\sum\limits_{l=1}^{d} \lambda_{kl}, & \textit{if i is an internal node whose state can be k} \\
\cdot \Big(\sum\limits_{s=1}^{d} p_{ks}^{(i0)}(t_i)L_s^{(i0)}(t_{i0}) \cdot \sum\limits_{s=1}^{d} p_{ls}^{(i1)}(t_i)L_s^{(i1)}(t_{i1}) \\
\quad + \sum\limits_{s=1}^{d} p_{ks}^{(i1)}(t_i)L_s^{(i1)}(t_{i1}) \cdot \sum\limits_{s=1}^{d} p_{ls}^{(i0)}(t_i)L_s^{(i0)}(t_{i0}) \Big)
\end{cases}
$$

$$(7)$$

Note that unlike the known-tree-node-state likelihood (Eq. (6)), the recursive unknown-tree-node-state likelihood (Eq. (7)) does not allow for an easy logarithmic representation, and hence is prone to underflow issues (as the original MTBD representation). Its calculation on large trees therefore requires additional small number rescaling techniques as recently described in (Scire et al., 2022) and common in phylogenetic inference. However, unlike in the original MTBD representation, master equation resolutions (for $p_{ks}^{(i0)}(t_i)$ and $p_{ls}^{(i1)}(t_i) \; \forall i \; \forall k,l,s \in \{1,\dots,d\}$) can be performed independently, in parallel, and avoiding underflow issues for boundary conditions.

Overall, the PDF reconditioning technique can be applied to any model of the MTBD family, and facilitates its parameter estimation by separating master equation resolution (non-recursive and parallelizable) from likelihood calculation (recursive, but negligible in time cost compared to equation resolution). Recursive likelihood calculation can be performed with a standard pruning algorithm and rescaling techniques to control for potential underflow. For parameter estimation on trees with known node states (e.g. from metadata, or because they were generated by an MTBD process in which only one state can transmit or get sampled, like the BDEI model), tree likelihood can be calculated with a non-recursive formula in a logarithmic form (Eq. (6)), avoiding underflow.

2.1 Efficient parameter and CI estimation for the BDEI model

We applied our theoretical findings to implement a fast and efficient parameter estimator for the BDEI model (which we called PyBDEI). It estimates the BDEI model parameters $\Theta = (\mu,\lambda,\psi,\rho) \in \mathbb{R}^4$ for a forest $\mathscr{F}$ (comprising $f \geq 1$ observed and $u \geq 0$ unobserved trees) in the maximum-likelihood framework, where one of the parameters in Θ is fixed (for identifiability reasons).

Once the optimal parameter values are found, we calculate their confidence intervals (CIs) using Wilks' method (Wilks, 1938). For each non-fixed parameter $p \in \Theta$, we calculate its 95%-CI as including the values $\tilde{p}$ such that $logL(\mathscr{F}|\Theta_{opt|p=\tilde{p}}) > logL(\mathscr{F}|\Theta_{opt}) - \chi_1^2(0.95)/2$, where $\chi_1^2(0.95)$ is the value of chi-squared distribution with 1 degree of freedom corresponding to the significance level of 0.95 (i.e., ~ 3.84). $\Theta_{opt|p=\tilde{p}}$ corresponds to the maximum-likelihood value for the other non-fixed parameters when $p = \tilde{p}$.

2.2 Performance on simulated data and comparison to other tools

To assess the performance of our maximum-likelihood estimator PyBDEI, we used the simulated data from (Voznica et al., 2022), where we generated 100 medium trees with 200–500 tips under the BDEI model, with the parameter values sampled uniformly at random within the following boundaries: incubation period $\frac{1}{\mu} \in [0.2, 50]$, $R_e = \frac{\lambda}{\psi} \in [1, 5]$, infectious time $\frac{1}{\psi} \in [1, 10]$. These trees were evaluated with the gold standard Bayesian method BEAST2 (Bouckaert et al., 2019) and the deep learning-based estimator PhyloDeep (detailed configurations are described in Materials and Methods). Additionally 100 large trees (5 000–10 000 tips) were generated for the same parameter values, and assessed with PhyloDeep in (Voznica et al., 2022). PhyloDeep's maximal pre-trained tree size is 500 tips, however for larger trees it estimates BDEI parameters by (i) extracting the largest non-intersecting set of subtrees of sizes covered by the pre-trained set (50–500 tips), (ii) estimating parameters on each of the subtrees independently, and (iii) averaging each parameter's estimate over the subtrees (weighted by subtree sizes).

We applied PyBDEI to these data sets (for the large data set, both to full trees and to forests of subtrees produced by PhyloDeep), and compared the results to those reported for BEAST2 and PhyloDeep in (Voznica et al., 2022). We calculated the relative error (normalized distance between the estimated and the target values: $\frac{|estimated-target|}{target}$) and the relative bias ($\frac{estimated-target}{target}$) for each parameter on each tree. Average relative errors for PyBDEI were $\leq 13\%$ on the medium trees and $\leq 2\%$ on the large trees (hence decreasing with the data set size, as expected), and well centred around zero (i.e. unbiased), as shown in Figure 3. The relative 95%-CI width ($\frac{CI_{97.5\%}-CI_{2.5\%}}{target}$) also decreased: from ~ 0.5 on the medium data set to ~ 0.1 on the large one. The target values of rates μ, λ and ψ were within the estimated CIs in correspondingly 92%, 89%, and 98% of cases on the medium data set, and in 96%, 90% and 94% of cases on the large one.

In terms of accuracy, on the medium data set PyBDEI was at least as accurate as PhyloDeep and more accurate than BEAST2: p-value < 0.05 (based on two-sided z-test) for all the parameters but R_0. For R_0 all the methods performed in a comparable way, see Fig. 3. For 2 trees in this data set, BEAST2 did not converge after 10^6 Markov Chain Monte Carlo (MCMC) steps: The corresponding estimations were set to the median of the parameter subspace used for simulations (as in (Voznica et al., 2022)). On the large data set BEAST2 was inapplicable due to computation times (57 CPU hours were already required for each medium tree, on average), while PyBDEI was more accurate than PhyloDeep, both using full trees and forests (p-value < 0.01 for all the parameters, see Fig. 3).

In terms of time, on the medium data set PyBDEI needed on average 6 seconds per tree on 1 CPU, and converged in 909 iterations (including CI calculation). BEAST2 required on average 57 CPU hours for 10^6 MCMC steps. As BEAST2 performs a Markov Chain Monte Carlo (MCMC) parameter space exploration instead of looking for the optimum (as PyBDEI does), it requires many more steps. However, implementing likelihood calculation with our new MTBD formulation and targeted numerical analysis methods, could be helpful in Bayesian context as well: comparing time per iteration (which is roughly time per likelihood calculation), our optimiser required ~ 0.01 CPU seconds, while BEAST2 took one order of magnitude longer: ~ 0.2 CPU seconds. Using several CPUs would allow for an even larger gain. PhyloDeep took 0.2 CPU seconds per tree, which is faster than our method's time but does not include the training time of deep learning predictors (hundreds of hours). To our knowledge, the only other available maximum-likelihood estimator for BDEI is implemented in the TreePar package (Stadler and Bonhoeffer, 2013). However, as it suffers from underflow issues for BDEI already on trees of small size, its developers suggest using BEAST2 instead (private communication).

The average time of PyBDEI convergence on the large data set was 3 minutes and 53 seconds on 1 CPU, and required 990 iterations. Parallelization on 2 CPUs reduced it to 2 minutes and 2 seconds (1.9 times faster). The speed up is close to the number of cores, which shows the efficiency of parallelization of master equation resolution despite the pre- and post-processing steps (tree reading, distribution of jobs between the threads, combining their results), which are always performed on one CPU. This suggests that our estimator will be easily applicable to much larger trees.

As the BDEI model requires one of the parameters to be fixed in order to become asymptomatically identifiable (Stadler, 2009), we fixed ρ to the real value, both in (Voznica et al., 2022) and in the comparison described above. However, to assess PyBDEI performance with other parameters fixed, we estimated parameters for trees in the large data set under three additional settings: with (1) μ, (2) λ, or (3) ψ fixed to its real value. The results are shown in Fig. S1. Average relative errors were $\leq 4\%$ for all parameters when μ was fixed to the real value, $\leq 3\%$ when λ was fixed, $\leq 2\%$ when ψ or ρ were fixed. For estimates of ρ we calculated absolute errors $|estimated-target|$ instead of relative ones: their average was 0.02 for fixed μ or λ, and 0.01 for fixed ψ. Hence, the estimations can be successfully performed with any of the parameters being fixed, but fixing ψ might be particularly useful. Moreover, ψ is relatively easy to estimate from other data (e.g. patient observations).

The assessment of our maximum-likelihood estimator on simulated data shows that it opens new possibilities to fast and efficient analyses of extremely large data sets, while being flexible with respect to parameter settings (e.g. the parameter to be fixed).

Figure 3: Comparison of inference accuracy of different methods on the medium (200-500 tips, top) and large (5 000–10 000 tips, bottom) data sets. For the medium data set BEAST2 (in orange), PhyloDeep (in green) and our estimator (PyBDEI, in blue) are compared. For large trees (> 500 tips), PhyloDeep extracts the largest non-intersecting set of subtrees of 50–500 tips, estimates parameters on each of the subtrees independently, and averages each parameter's estimate over the subtrees (weighted by subtree sizes). We assessed our method both on full trees (dark-blue) and forests of subtrees extracted by PhyloDeep (light-blue). We show the swarmplots (coloured by method) of relative errors for each test tree and parameter, which are measured as the normalized distance between the median a posteriori estimate by BEAST2 or a point estimate by PhyloDeep/PyBDEI and the real value. Average relative error (and in parentheses average bias, calculated on normalized values) are displayed for each parameter and method below their swarmplot. The accuracy of the methods is compared by a paired z-test; $p < 0.05$ are shown above each method pair; non-significant p-values are not shown.

3 Application: Ebola in Sierra-Leone

Using PyBDEI, we analysed the 2014 Ebola epidemic in Sierra-Leone (SLE). Ebola virus features an incubation period (reported by the World health Organisation (WHO) to take between 2 and 21 days (WHO, 2021)). Using statistical methods based on time series of reported Ebola cases, the incubation period of Ebola during the 2014 SLE epidemic was previously estimated to be around 10–11 days, the infectious time around 4–5 days, and the reproduction number to decrease from around 2 in the beginning of the epidemic to values close to 1 by late 2014 (due to control measures) (Team, 2014, 2015; Rivers et al., 2014) (see also (Van Kerkhove et al., 2015) for a review).

Sequence data could improve and complement these estimates. However, the existing phylodynamic study of these parameters was limited by the data set size: Stadler and Bonhoeffer (2013) applied the BDEI model to the early spread of Ebola in SLE by analysing 72 Ebola samples from late May to mid June 2014 (sequences from Gire et al. (2014)). They estimated the expected length of the incubation period to be 4.9 days (median; 95% HPD 2.1-23.2), and the infectious time of 2.6 days (median; 95% HPD 1.2-7).

To show the power of phylodynamic analyses on larger data sets, we took the 1 610-sequence alignment and metadata (sampling times and countries) that were used in the study by Dudas et al. (2017), who analysed the factors that spread the 2014–2016 Ebola epidemic in West Africa. Using these data, we reconstructed a time-tree of the Ebola epidemic in West Africa, which we then used to extract a forest of time-subtrees representing the Ebola epidemic in SLE between July 30, 2014 (when the SLE government began to deploy troops to enforce quarantines (News24, 2014)) and September 12, 2015 (the last SLE sample in the data set). This was done to obtain a forest of subtrees with a homogenous health policy (after July 30). The details on the forest reconstruction are given in Materials and Methods. To check for robustness of the estimates, forest reconstruction was performed 10 times, obtaining slightly different trees.

We estimated the BDEI parameters on these 10 forests, fixing the total number of trees to $m = 533$ (the declared number of cases in SLE by July 31, 2014 (CDC, 2020)), and hence the number of unobserved trees to $m - f$, where f was the number of trees in the corresponding forest (f varied between 55 and 70). To check the robustness of the predictions with respect to m, we additionally estimated the parameter values assuming 50% more cases (i.e. $m = 800$), and assuming no unobserved trees ($m = f$, $u = 0$). As the BDEI model requires one of the parameters to be fixed for identifiability (Stadler, 2009), we performed the estimations fixing the infectious time (to 2.6 and to 5 days, i.e. the estimates from the previous studies).

The results for $m = 533$ and $m = 800$ were compatible, with intersecting CIs (see Table S1): R_e was between 0.94 and 0.98 in all the settings and forests, suggesting a contained epidemic (which is in a good agreement with the quarantine measures and the end of the epidemic in early 2016), the incubation period was estimated between 10 and 15 days. These estimates are fully compatible with the previous studies and allow to narrow down the WHO incubation period estimate (2–21 days, non-specific to the SLE epidemic). The sampling probability ρ was estimated between 0.09 and 0.17. This number corresponds quite well to the proportion of cases represented by our forests (711–779) with respect to the total number of people infected during the SLE 2014 Ebola outbreak (8 704) reported by the WHO: $750/8 704 \approx 0.09$.

The results for $m = f$, $u = 0$, however, were different (see Table S2) and in disagreement with other sources of information: R_e between 1.11 and 1.18 (corresponding to a slowly spreading epidemic), incubation period between 22 and 25 days (larger than the one declared by the WHO), and sampling probability of 0.35-0.51 (unreasonably high, however in agreement with the hypothesis of having no unobserved trees (i.e., $u = 0$)). This result highlights the importance of using case data for parameter inference when a large proportion of sub-epidemics is unobserved.

Overall, the analysis took ~ 1 hour for the forest reconstruction and ~ 5 seconds for the BDEI parameter estimation.

This application shows the advantages of PyBDEI not only in terms of calculation times, but also in terms of flexibility of input settings (parameter to be fixed, extracting information from multiple trees and using data on declared but unobserved cases).

4 Discussion

We proposed a new highly parallelizable formulation of master equations for MTBD models. We also extended their application to forests, to tackle situations where health policies change over time (providing a flexible alternative to the Bayesian skyline), as well as situations of multiple (not necessarily simultaneous) pathogen introductions to a country of interest. The peculiar properties of original MTBD equations permitted us to rewrite them in a branch-specific way. This representation features simple boundary conditions with 0 or 1 values, and avoids numerical and underflow problems that could occur in the original system due to very small positive values of the boundary conditions. Even more importantly, our branch-specific representation removes the recursive dependency between the equations corresponding to parent and child tree nodes, and permits their

time-consuming resolution to be performed in parallel and independently. The results can then be combined into tree likelihood with a nearly standard pruning algorithm. While the likelihood-combining step in the most general MTBD case remains recursive, its time cost is negligible in comparison with the recursive master equation resolution used in previous studies. Moreover, for cases where tree node states are known we obtained an explicit likelihood formula, which can be represented in a logarithmic form (Eq. 6) to avoid potential underflow issues during calculations. Tree node states could be known from metadata, or because they were generated by an MTBD process in which only one state can transmit or get sampled.

We implemented our findings in a maximum likelihood parameter and CI estimator for the BDEI model. The BDEI model is a special case of MTBD models, which is targeted to pathogens that feature an incubation period. Under this model tree node states are known, as only the infectious individuals can transmit their pathogen or get detected (after symptom onset). Our parameter estimator, PyBDEI, drastically increases parameter optimisation performance, accuracy and speed with respect to previously available estimators.

We applied our estimator to the 2014 Ebola epidemic in Sierra Leone, after the introduction of quarantine measures. The analysis took < 2 hours (the majority of which was the tree reconstruction). The obtained estimates of epidemiological parameters are in perfect agreement with what we now know about this epidemic. In particular, the estimate of R_e, slightly below 1, suggests a contained epidemic, and indeed Sierra Leone was declared Ebola-free in early 2016, a few months after the sampling date (9 Dec 2015) of the most recent Ebola sequence in our data set.

The accuracy of estimations improves with the data set size (as expected, see our simulations). In the world of rapidly growing sequencing data sets (Hodcroft et al., 2021), we can gain important insights on epidemic spreads by harvesting all available information. PyBDEI is applicable to very large data sets (4 minutes on a 10 000-tip tree), making parameter and CI estimation instantaneous with respect to phylogenetic tree reconstruction times (hours). Our approach could be easily used in a Bayesian setting as well, and could potentially be implemented in BEAST2.

5 Materials and Methods

5.1 Equivalence between Equations (2) and (6)

The likelihood Equation (2) for a tree $\mathscr{T}$ is recursive, and when using $L_s^{(i)}(t)$ ($s \in \{1, \ldots, d\}$) needs to be resolved with a pruning algorithm while climbing the tree. However, for a tree with known node states, we can transform it into a non-recursive Equation (6) with $p_{s,si}^{(i)}(t)$, by alternating *replacement* and *unfolding* steps. A replacement step consists in replacing $L_s^{(i)}(t)$ with $p_{s,si}^{(i)}(t) \cdot C_{si}^{(i)}$ and is followed by an unfolding step. An unfolding step either (if i is a tip) unfolds $C_{si}^{(i)}$ into $\psi_{si}\rho_{si}$ and stops; or (if i is an internal node) unfolds $C_{si}^{(i)}$ into $\sum_{k=1}^{d} \lambda_{si,k}\left(L_{si}^{(i0)}(t_i)L_k^{(i1)}(t_i) + L_k^{(i0)}(t_i)L_{si}^{(i1)}(t_i)\right)$ and proceeds with replacements. In Equation (8) we show the transformation process.

$$
\begin{aligned}
L(\mathscr{T}|\Theta) &= L_{s0}^0(0) \qquad \leftarrow \textit{Equation (2)} \\
&= p_{s0}^{(0)}(0) \cdot C_{s0}^{(0)} \quad \leftarrow \textit{replacement} \qquad \textit{(note that } p_{s0}^{(0)}(0) = 1 \textit{ as the root branch is of length zero)} \\
&= \sum_{k=1}^{d} \lambda_{s0,k} \left(L_{s0}^{(00)}(t_0) L_k^{(01)}(t_0) + L_k^{(00)}(t_0) L_{s0}^{(01)}(t_0) \right) \qquad \leftarrow \textit{unfolding of } C_{s0}^{(0)} \\
&= \sum_{k=1}^{d} \lambda_{s0,k} \left(p_{s0,s00}^{(00)}(t_0) p_{k,s01}^{(01)}(t_0) + p_{k,s00}^{(00)}(t_0) p_{s0,s01}^{(01)}(t_0) \right) \quad \leftarrow \textit{replacement} \\
&\quad \cdot C_{s00}^{(00)} C_{s01}^{(01)} \quad \textit{(note that } C_{s00}^{(00)} \textit{ and } C_{s01}^{(01)} \textit{ do not depend on } k, \textit{ and can be put outside of the sum)} \\
&= \sum_{k=1}^{d} \lambda_{s0,k} \left(p_{s0,s00}^{(00)}(t_0) p_{k,s01}^{(01)}(t_0) + p_{k,s00}^{(00)}(t_0) p_{s0,s01}^{(01)}(t_0) \right) \\
&\quad \cdot \begin{cases} \psi_{s00}\rho_{s00}, \quad \textit{if left child of root is a tip} \\ \sum_{x=1}^{d} \lambda_{s00,x} \left(p_{s00,s000}^{(000)}(t_{00}) p_{x,s001}^{(001)}(t_{00}) + p_{x,s000}^{(000)}(t_{00}) p_{s00,s001}^{(001)}(t_{00}) \right) \quad \leftarrow \textit{unfolding of } C_{s00}^{(00)} \\ \qquad \cdot C_{s000}^{(000)} C_{s001}^{(001)}, \textit{ otherwise } \quad \textit{(note that } C_{s\ldots}^{(\ldots)} \textit{ do not depend on } x) \end{cases} \\
&\quad \cdot \begin{cases} \psi_{s01}\rho_{s01}, \quad \textit{if right child of root is a tip} \\ \sum_{y=1}^{d} \lambda_{s01,y} \left(p_{s01,s010}^{(010)}(t_{01}) p_{y,s011}^{(011)}(t_{01}) + p_{y,s010}^{(010)}(t_{01}) p_{s01,s011}^{(011)}(t_{01}) \right) \quad \leftarrow \textit{unfolding of } C_{s01}^{(01)} \\ \qquad \cdot C_{s010}^{(010)} C_{s011}^{(011)}, \textit{ otherwise } \quad \textit{(note that } C_{s\ldots}^{(\ldots)} \textit{ do not depend on } y) \end{cases} \\
&= \ldots \quad \leftarrow \textit{keep unfolding and replacing} \\
&= \prod_{j \in tips} \psi_{sj}\rho_{sj} \prod_{\substack{i \in intern. \\ nodes}} \sum_{k=1}^{d} \lambda_{si,k} \left(p_{si,si0}^{(i0)}(t_i) p_{k,si1}^{(i1)}(t_i) + p_{k,si0}^{(i0)}(t_i) p_{si,si1}^{(i1)}(t_i) \right) \leftarrow \textit{non-log Eq. (6)} \qquad (8)
\end{aligned}
$$

Reconditioned BDEI master equations

$$
\begin{cases}
\dot{p}_E^{(i)}(t) = & \mu p_E^{(i)}(t) \leftarrow \textit{no event in the next infinitesimal time } \Delta t \\
& -\mu p_I^{(i)}(t) \leftarrow \textit{becoming infectious, followed by evolution from state } I \\
\dot{p}_I^{(i)}(t) = & (\lambda + \psi) p_I^{(i)}(t) \leftarrow \textit{no event in the next infinitesimal time } \Delta t \\
& -\lambda p_I^{(i)}(t) U_E(t) \leftarrow \textit{transmission, where the recipient subtree stayed unsampled} \\
& -\lambda p_E^{(i)}(t) U_I(t) \leftarrow \textit{transmission, where the transmitter subtree stayed unsampled} \\
p_I^{(i)}(t_i) = & 1 \leftarrow \textit{the probability to evolve from } I \textit{ to } I \textit{ over zero time is 1} \\
p_E^{(i)}(t_i) = & 0 \leftarrow \textit{an individual in state } E \textit{ cannot change their state to } I \textit{ instanteniously} \\
\dot{U}_E(t) = & \mu U_E(t) \leftarrow \textit{no event in the next infinitesimal time } \Delta t \\
& -\mu U_I(t) \leftarrow \textit{becoming infectious, followed by unsampled evolution from state } I \\
\dot{U}_I(t) = & (\lambda + \psi) U_I(t) \leftarrow \textit{no event in the next infinitesimal time } \Delta t \\
& -\lambda U_I(t) U_E(t) \leftarrow \textit{transmission, then unsampled evolutions of transmitter and recipient subtrees} \\
& -\psi(1 - \rho) \leftarrow \textit{removal without sampling} \\
U_E(T) = & U_I(T) = 1 \leftarrow \textit{the probability to stay unsampled over zero time is 1}
\end{cases} \qquad (9)
$$

Stationary distribution

Stationary state distribution $\Pi = \{\pi_E, \pi_I\} : \pi_E + \pi_I = 1$ corresponds to the ratios of states E and I at a given time t after these ratios stopped changing (assuming that this may happen). $\pi_s = \frac{N_s(t)}{N(t)}$, where $N_s(t)$ is the number of individuals of type $s \in \{E, I\}$ and $N(t)$ is the total number of infected (infectious or not) individuals at time t. Hence, the derivative of the number of individuals of type s is proportional to the derivative of the total number of infected individuals:

$$
dN_s(t) = \pi_s dN(t). \qquad (10)
$$

The number of individuals in state I increases due to becoming infectious of individuals in state E and decreases due to removal, while the number of individuals in state E decreases due to becoming infectious and

increases due to transmissions:

$$\begin{cases} dN_I(t) & = \mu N_E(t) - \psi N_I(t) \\ dN_E(t) & = -\mu N_E(t) + \lambda N_I(t) \end{cases}. \tag{11}$$

Becoming infectious changes the corresponding individual's state but does not affect the total number of infected individuals, transmissions increase the total number, and removal decreases it. Note that only individuals in state I can transmit or be removed:

$$dN(t) = \lambda N_I(t) - \psi N_I(t). \tag{12}$$

Combining [11] and [12] we rewrite [10] as a system of multivariate algebraic equations:

$$\begin{cases} \mu \pi_E - \psi \pi_I = \pi_I^2 (\lambda - \psi) \\ \pi_E + \pi_I = 1 \end{cases}, \tag{13}$$

from which we derive a quadratic equation for π_I: $\pi_I^2(\lambda - \psi) + \pi_I(\mu + \psi) - \mu = 0$, and the following stationary distribution:

$$\begin{cases} \pi_I & = \begin{cases} \frac{\mu}{\mu + \psi}, & if \ \lambda = \psi \\ \frac{-(\mu + \psi) + \sqrt{(\mu - \psi)^2 + 4\mu\lambda}}{2(\lambda - \psi)}, & otherwise \end{cases} \\ \pi_E & = 1 - \pi_I \end{cases} \tag{14}$$

PyBDEI, its code and data availability

Parameter estimation starts with a preprocessing step of reading the input trees, calculating the time t_i at each node i and memorising the association between each node and its child nodes: $i \rightarrow (i0, i1)$. This step requires one tree traversal, and its time is negligible with respect to the numerical master equation resolution performed in the next steps.

The estimation then proceeds with a search for the optimal parameter set $\Theta_{opt} = \arg\max_{\Theta \in \mathcal{Q}} L(\mathscr{F}|\Theta)$, where $\mathcal{Q}$ is the set of admissible parameter values. We use the globally-convergent method of moving asymptotes (Svanberg, 2002) for the optimisation. At each optimisation step k the corresponding likelihood $L(\mathscr{F}|\Theta_k)$ needs to be calculated, which implies calculating $p_{II}^{(i0)}(t_i), p_{EI}^{(i0)}(t_i), p_{II}^{(i1)}(t_i), p_{EI}^{(i1)}(t_i)$ for each of the $n - f$ observed internal nodes of $\mathscr{F}$, and combining them as in the forest likelihood formula (Eq. (4)). The reconditioned version of BDEI master equations (9) for the parameter values Θ_k can be resolved in parallel for each of the $2n - f$ observed forest nodes (differing in the times t_i of their boundary conditions).

To resolve these master equations numerically, we start by separating the self-defined subsystem for the unknowns $U_E(t)$ and $U_I(t)$ from the rest of System (9), and calculate it independently. Taking into account the fact that the equations in System (9) are either linear (for $p_{EI}^{(i)}(t)$ and $p_{II}^{(i)}(t)$) or quadratic (for $U_E(t)$ and $U_I(t)$) the use of an implicit scheme is simple. We chose implicit schemes with an automatic computation of the time step, such that the error is less than a given tolerance. In our implementation, we used the implicit Euler scheme (Butcher, 2016) for solving the linear equations and the Crank-Nicolson implicit scheme (Crank and Nicolson, 1947) for the non-linear ones. This permits us to avoid possible stability time restrictions and only choose the time steps for precision.

The core of our estimator is implemented in C++ and uses the NLopt library (Johnson) for non-linear optimization. The parallelization is achieved with the C++ `thread_pool` tools (Williams, 2012). To facilitate the use of our estimator in Python and perform additional validation of input trees, we wrapped the core estimator into a Python 3 library PyBDEI. PyBDEI uses ETE 3 framework for tree manipulation (Huerta-Cepas et al., 2016) and NumPy package for array operations (Harris et al., 2020).

Our estimator is available as a command-line program and a Python 3 library via PyPi (`pypi.org/project/pybdei`), and via Docker/Singularity (`hub.docker.com/r/evolbioinfo/bdei`). Its source code, the simulated and real data used for its assessment, as well as the Snakemake (Köster and Rahmann, 2012) data analysis pipelines, and the installation and usage documentation are available on GitHub at `github.com/evolbioinfo/bdei`. BEAST2 xml files and command lines are available at `github.com/evolbioinfo/phylodeep/tree/main/data_publication`.

BEAST2 and PhyloDeep settings

BEAST2 (v2.6.2 with package bdmm (Scire et al., 2022) v1.0) was configured for 10^6 MCMC steps with the following priors: $\mu \in U(0.02, 5.0)$, $\psi \in U(0.1, 1.0)$, and ρ fixed to the real value. The initial values in the MCMC were set to the medians used in the PhyloDeep training set, namely $\mu = 2.51$, $\psi = 0.55$, and $R_0 = 3$. The tree

was fixed to the real tree. For each tree, the Effective Sample Size (ESS) on all parameters was evaluated, and the median of a posteriori values was reported, corresponding to all recorded steps (i.e. actual MCMC steps spaced by 1 000) past the 10% burn-in. For simulations for which BEAST2 did not converge (2%) after 10^6 MCMC steps, the median of the parameter distribution used for tree simulations was reported instead.

PhyloDeep (v0.2.51) was run with ρ fixed to the real value and Convolutional Neural Networks trained on the Compact Bijective Ladderized Vector full tree representation (CNN-CBLV).

The visualisations of the analyses of simulated data were performed with the Python 3 library seaborn (Waskom, 2021; Hunter, 2007).

Tree reconstruction for Ebola SLE epidemic analysis

We reconstructed a maximum-likelihood phylogeny of 1 610 tips for the Ebola samples from (Dudas et al., 2017) with RAxML-NG (v1.0.2, GTR+G4+FO+IO) (Kozlov et al., 2019), and rooted it based on sampling dates using LSD2 (v1.10) (To et al., 2016). As Ebola's mutation rate is slower than its transmission rate, the initial phylogeny contained 246 polytomies (i.e. multiple transmissions, which happened faster than the virus acquired a mutation, hence making them undistinguishable in the phylogeny). The BDEI model, on the other hand, assumes a binary tree. We therefore resolved these polytomies randomly (10 times, to check for robustness of the estimates) using a coalescent approach.

We then dated each of the 10 trees with LSD2 (To et al., 2016) (v1.10: `github.com/tothuhien/lsd2/tree/v1.10`, under strict molecular clock with outlier removal) using tip sampling dates, and reconstructed the ancestral characters for country with PastML (Ishikawa et al., 2019) (v1.9.34, MPPA+F81).

Lastly, we extracted 10 SLE forests from these trees to represent the Ebola epidemic in SLE between July 30 2014 (when the SLE government began to deploy troops to enforce quarantines (News24, 2014)) and September 12 2015 (the last SLE sample in our dataset) by (1) cutting each tree on July 30 2014 to remove the more ancient part (with a different health policy); (2) among the July-31-on trees, picking those whose root's predicted character state for country was SLE (light-green branches at the level of July 31 2014 in Figure S2); (3) removing the non-SLE subtrees (indicated with other colours in Figure S2) from the selected July-31-on SLE trees to focus on the epidemic within the country, without further reintroductions.

The reconstruction took 1 hour for the phylogeny, 10 minutes for tree dating, and 1 minute for country ancestral character prediction.

6   Funding

O.G. was supported by PRAIRIE (ANR-19-P3IA-0001). Y.M. was supported by European Research Council (ERC) under the European Union's Horizon 2020 research and innovation program (grant agreement No 810367), project EMC2.

7   Acknowledgements

The authors thank Dr Jakub Voznica for valuable discussions.

8   Author Contributions

O.G. initiated the project; A.Z. conceived the new master equation representation, extension to forests, applications to Ebola and simulated data, and coordinated the project; F.H. and Y.M. conceived the numerical approach for fast and efficient parameter optimisation; F.H. implemented the numerical approach; A.Z. wrote the manuscript with input from all the authors; all authors discussed the intermediate and final results.

References

Berger SA, Stamatakis A. 2009. Accuracy and Performance of Single versus Double Precision Arithmetics for Maximum Likelihood Phylogeny Reconstruction. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics). 6068 LNCS:270–279.

Bouckaert R, Vaughan TG, Barido-Sottani J, Duchêne S, Fourment M, Gavryushkina A, Heled J, Jones G, Kühnert D, De Maio N, Matschiner M, Mendes FK, Müller NF, Ogilvie HA, Du Plessis L, Popinga A, Rambaut A, Rasmussen D, Siveroni I, Suchard MA, Wu CH, Xie D, Zhang C, Stadler T, Drummond AJ. 2019. BEAST 2.5: An advanced software platform for Bayesian evolutionary analysis. PLoS Computational Biology. 15.

Butcher JC. 2016. Numerical methods for ordinary differential equations. 3 edition. Wiley.

CDC. 2020. 2014–2016 ebola outbreak in west africa: Case counts. Available at `https://www.cdc.gov/vhf/ebola/history/2014-2016-outbreak/case-counts.html`.

Crank J, Nicolson P. 1947. A practical method for numerical evaluation of solutions of partial differential equations of the heat-conduction type. Mathematical Proceedings of the Cambridge Philosophical Society. 43:50–67.

Defour D. 2010. Accuracy of a Maximum Likelihood Phylogeny Reconstruction. Technical report. LIRMM. Available at `https://hal.archives-ouvertes.fr/hal-00726409`.

Drummond AJ, Rambaut A, Shapiro B, Pybus OG. 2005. Bayesian coalescent inference of past population dynamics from molecular sequences. Molecular Biology and Evolution. 22:1185–1192.

Dudas G, Carvalho LM, Bedford T, Tatem AJ, Baele G, Faria NR, Park DJ, Ladner JT, Arias A, Asogun D, Bielejec F, Caddy SL, Cotten M, D'Ambrozio J, Dellicour S, Di Caro A, Diclaro JW, Duraffour S, Elmore MJ, Fakoli LS, Faye O, Gilbert ML, Gevao SM, Gire S, Gladden-Young A, Gnirke A, Goba A, Grant DS, Haagmans BL, Hiscox JA, Jah U, Kugelman JR, Liu D, Lu J, Malboeuf CM, Mate S, Matthews DA, Matranga CB, Meredith LW, Qu J, Quick J, Pas SD, Phan MVT, Pollakis G, Reusken CB, Sanchez-Lockhart M, Schaffner SF, Schieffelin JS, Sealfon RS, Simon-Loriere E, Smits SL, Stoecker K, Thorne L, Tobin EA, Vandi MA, Watson SJ, West K, Whitmer S, Wiley MR, Winnicki SM, Wohl S, Wölfel R, Yozwiak NL, Andersen KG, Blyden SO, Bolay F, Carroll MW, Dahn B, Diallo B, Formenty P, Fraser C, Gao GF, Garry RF, Goodfellow I, Günther S, Happi CT, Holmes EC, Kargbo B, Keïta S, Kellam P, Koopmans MPG, Kuhn JH, Loman NJ, Magassouba N, Naidoo D, Nichol ST, Nyenswah T, Palacios G, Pybus OG, Sabeti PC, Sall A, Ströher U, Wurie I, Suchard MA, Lemey P, Rambaut A. 2017. Virus genomes reveal factors that spread and sustained the Ebola epidemic. Nature. 544:309–315.

Felsenstein J. 1973. Maximum Likelihood and Minimum-Steps Methods for Estimating Evolutionary Trees from Data on Discrete Characters. Systematic Biology. 22:240–249.

Gire SK, Goba A, Andersen KG, Sealfon RS, Park DJ, Kanneh L, Jalloh S, Momoh M, Fullah M, Dudas G, Wohl S, Moses LM, Yozwiak NL, Winnicki S, Matranga CB, Malboeuf CM, Qu J, Gladden AD, Schaffner SF, Yang X, Jiang PP, Nekoui M, Colubri A, Coomber MR, Fonnie M, Moigboi A, Gbakie M, Kamara FK, Tucker V, Konuwa E, Saffa S, Sellu J, Jalloh AA, Kovoma A, Koninga J, Mustapha I, Kargbo K, Foday M, Yillah M, Kanneh F, Robert W, Massally JL, Chapman SB, Bochicchio J, Murphy C, Nusbaum C, Young S, Birren BW, Grant DS, Scheiffelin JS, Lander ES, Happi C, Gevao SM, Gnirke A, Rambaut A, Garry RF, Khan SH, Sabeti PC. 2014. Genomic surveillance elucidates Ebola virus origin and transmission during the 2014 outbreak. Science. 345:1369–1372.

Grenfell BT, Pybus OG, Gog JR, Wood JLN, Daly JM, Mumford JA, Holmes EC. 2004. Unifying the Epidemiological and Evolutionary Dynamics of Pathogens. Science. 303.

Harris CR, Millman KJ, van der Walt SJ, Gommers R, Virtanen P, Cournapeau D, Wieser E, Taylor J, Berg S, Smith NJ, Kern R, Picus M, Hoyer S, van Kerkwijk MH, Brett M, Haldane A, del Río JF, Wiebe M, Peterson P, Gérard-Marchant P, Sheppard K, Reddy T, Weckesser W, Abbasi H, Gohlke C, Oliphant TE. 2020. Array programming with NumPy. Nature. 585:357–362. Publisher: Nature Publishing Group.

Hethcote HW. 2000. The mathematics of infectious diseases. SIAM review. 42:599–653.

Hodcroft EB, De Maio N, Lanfear R, MacCannell DR, Minh BQ, Schmidt HA, Stamatakis A, Goldman N, Dessimoz C. 2021. Want to track pandemic variants faster? Fix the bioinformatics bottleneck. Nature. 591:30–33.

Huerta-Cepas J, Serra F, Bork P. 2016. ETE 3: Reconstruction, Analysis, and Visualization of Phylogenomic Data. Molecular Biology and Evolution. 33:1635–1638.

Hunter JD. 2007. Matplotlib: A 2D graphics environment. Computing in Science & Engineering. 9:90–95.

Ishikawa SA, Zhukova A, Iwasaki W, Gascuel O. 2019. A fast likelihood method to reconstruct and visualize ancestral scenarios. Molecular biology and evolution. 36:2069–2085.

Johnson SG. . The nlopt nonlinear-optimization package. Accessed: 2021-01-26.

Kendall DG. 1948. On the generalized "birth-and-death" process. Ann. Math. 19:1–15.

Köster J, Rahmann S. 2012. Snakemake-a scalable bioinformatics workflow engine. Bioinformatics. 28:2520–2522.

Kozlov AM, Darriba D, Flouri T, Morel B, Stamatakis A. 2019. RAxML-NG: a fast, scalable and user-friendly tool for maximum likelihood phylogenetic inference. Bioinformatics. 35:4453–4455.

Kühnert D, Stadler T, Vaughan TG, Drummond AJ. 2016. Phylodynamics with Migration: A Computational Framework to Quantify Population Structure from Genomic Data. Molecular biology and evolution. 33:2102–16.

Macpherson A, Louca S, Mclaughlin A, Joy JB, Pennell MW. 2021. Unifying Phylogenetic Birth-Death Models in Epidemiology and Macroevolution. Systematic Biology. 71.

Maddison W, Midford P, Otto S. 2007. Estimating a Binary Character's Effect on Speciation and Extinction. Systematic Biology. 56:701–710.

News24. 2014. Sierra leone, liberia deploy troops for ebola. Available at `https://www.news24.com/Africa/News/Sierra-Leone-Liberia-deploy-troops-for-Ebola-20140804`.

Pybus OG, Rambaut A, Harvey PH. 2000. An integrated framework for the inference of viral population history from reconstructed genealogies. Genetics. 155:1429–1437.

Rivers CM, Lofgren ET, Marathe M, Eubank S, Lewis BL. 2014. Modeling the Impact of Interventions on an Epidemic of Ebola in Sierra Leone and Liberia. PLoS Currents. 6.

Scire J, Barido-Sottani J, Kühnert D, Vaughan TG, Stadler T. 2022. Robust phylodynamic analysis of genetic sequencing data from structured populations. Viruses. 14.

Stadler T. 2009. On incomplete sampling under birth-death models and connections to the sampling-based coalescent. Journal of Theoretical Biology. 261:58–66.

Stadler T. 2010. Sampling-through-time in birth-death trees. J. Theor. Biol. 267:396–404.

Stadler T, Bonhoeffer S. 2013. Uncovering epidemiological dynamics in heterogeneous host populations using phylogenetic methods. Philosophical Transactions of the Royal Society B: Biological Sciences. 368:20120198–20120198.

Stadler T, Kühnert D, Bonhoeffer S, Drummond AJ. 2013. Birth-death skyline plot reveals temporal changes of epidemic spread in HIV and hepatitis C virus (HCV). Proceedings of the National Academy of Sciences of the United States of America. 110:228–33.

Stadler T, Kühnert D, Rasmussen DA, du Plessis L. 2014. Insights into the Early Epidemic Spread of Ebola in Sierra Leone Provided by Viral Sequence Data. PLoS Currents. 6.

Svanberg K. 2002. A class of globally convergent optimization methods based on conservative convex separable approximations. SIAM Journal on Optimization. 12:555–573.

Team WER. 2014. Ebola Virus Disease in West Africa — The First 9 Months of the Epidemic and Forward Projections. N Engl J Med. 371:1481–1495.

Team WER. 2015. West African Ebola Epidemic after One Year — Slowing but Not Yet under Control. N Engl J Med. 372:584–587.

To TH, Jung M, Lycett S, Gascuel O. 2016. Fast Dating Using Least-Squares Criteria and Algorithms. Systematic biology. 65:82–97.

Van Kerkhove MD, Bento AI, Mills HL, Ferguson NM, Donnelly CA. 2015. A review of epidemiological parameters from Ebola outbreaks to inform early public health decision-making. Scientific Data. 2:1–10.

Volz EM, Koelle K, Bedford T, Bhattacharya T, Delaporte E. 2013. Viral Phylodynamics. PLoS Computational Biology. 9:e1002947.

Volz EM, Kosakovsky Pond SL, Ward MJ, Leigh Brown AJ, Frost SD. 2009. Phylodynamics of infectious disease epidemics. Genetics. 183:1421–1430.

Voznica J, Zhukova A, Boskova V, Saulnier E, Lemoine F, Moslonka-Lefebvre M, Gascuel O. 2022. Deep learning from phylogenies to uncover the transmission dynamics of epidemics. Nature Communications. 13:3896.

Waskom ML. 2021. seaborn: statistical data visualization. Journal of Open Source Software. 6:3021.

WHO. 2021. Ebola virus disease [fact sheet]. Available at `https://www.who.int/news-room/fact-sheets/detail/ebola-virus-disease`.

Wilks SS. 1938. The Large-Sample Distribution of the Likelihood Ratio for Testing Composite Hypotheses. The Annals of Mathematical Statistics. 9:60–62.

Williams A. 2012. C++ concurrency in action: practical multithreading; 1st ed. Shelter Island, NY: Manning Publ.

Zhukova A, Blassel L, Lemoine F, Morel M, Voznica J, Gascuel O. 2020. Origin, evolution and global spread of SARS-CoV-2. Comptes Rendus. Biologies. 0:1–20.

9 Appendix

Fig. S 1: Comparison of inference accuracy on 100 test trees of 500–10 000 tips from (Voznica et al., 2022), with (blue) μ fixed to the real value, (yellow) λ fixed to the real value, (green) ψ fixed to the real value, (orange) ρ fixed to the real value. We show the swarmplots of relative errors for each test tree and parameter. Average relative error (and in parentheses average relative bias) are displayed for each parameter and setting below their swarmplot. For ρ, absolute errors and bias are shown instead of the relative ones.

Table S 1: Parameters estimated for SLE 2014 Ebola epidemic, taking the declared number of cases into account.

forest	tips	trees	hidden trees	infectious time $\frac{1}{\psi}$ (fixed)	R_e	incubation period $\frac{1}{\mu}$	ρ
1	779	56	477	2.6	0.97 [0.92 − 1.03]	15.0 [13.2 − 17.0]	0.15 [0.12 − 0.18]
1	779	56	477	5.0	0.98 [0.92 − 1.04]	14.7 [12.6 − 16.8]	0.17 [0.14 − 0.20]
1	779	56	744	2.6	0.95 [0.90 − 0.99]	12.6 [10.9 − 14.4]	0.10 [0.08 − 0.12]
1	779	56	744	5.0	0.95 [0.90 − 0.99]	11.6 [9.8 − 13.5]	0.11 [0.09 − 0.14]
2	762	68	465	2.6	0.97 [0.91 − 1.02]	14.6 [12.8 − 16.6]	0.14 [0.11 − 0.17]
2	762	68	465	5.0	0.96 [0.91 − 1.03]	14.3 [12.3 − 16.4]	0.17 [0.14 − 0.19]
2	762	68	732	2.6	0.94 [0.90 − 0.99]	12.2 [10.6 − 14.0]	0.10 [0.08 − 0.12]
2	762	68	732	5.0	0.94 [0.89 − 0.99]	11.3 [9.5 − 13.3]	0.11 [0.09 − 0.13]
3	764	70	463	2.6	0.97 [0.91 − 1.02]	15.1 [13.4 − 17.0]	0.15 [0.12 − 0.17]
3	764	70	463	5.0	0.97 [0.91 − 1.03]	14.8 [12.9 − 17.0]	0.17 [0.14 − 0.21]
3	764	70	730	2.6	0.94 [0.90 − 0.99]	12.7 [11.1 − 14.6]	0.10 [0.08 − 0.12]
3	764	70	730	5.0	0.94 [0.89 − 0.99]	11.8 [9.9 − 13.7]	0.11 [0.09 − 0.14]
4	759	63	470	2.6	0.97 [0.91 − 1.02]	14.8 [13.0 − 16.8]	0.14 [0.11 − 0.17]
4	759	63	470	5.0	0.97 [0.91 − 1.03]	14.5 [12.5 − 16.6]	0.16 [0.13 − 0.19]
4	759	63	737	2.6	0.94 [0.90 − 0.99]	12.5 [10.7 − 14.2]	0.10 [0.08 − 0.12]
4	759	63	737	5.0	0.94 [0.89 − 0.99]	11.5 [10.0 − 13.5]	0.11 [0.09 − 0.13]
5	711	55	478	2.6	0.96 [0.91 − 1.02]	13.6 [11.9 − 15.7]	0.13 [0.10 − 0.16]
5	711	55	478	5.0	0.96 [0.90 − 1.02]	13.2 [11.7 − 15.2]	0.15 [0.13 − 0.18]
5	711	55	745	2.6	0.94 [0.90 − 0.99]	11.3 [9.8 − 13.2]	0.09 [0.07 − 0.11]
5	711	55	745	5.0	0.94 [0.89 − 0.99]	10.2 [8.8 − 11.6]	0.10 [0.08 − 0.12]
6	770	62	471	2.6	0.97 [0.92 − 1.02]	14.7 [12.8 − 16.7]	0.14 [0.12 − 0.16]
6	770	62	471	5.0	0.97 [0.91 − 1.03]	14.4 [12.4 − 16.5]	0.17 [0.14 − 0.20]
6	770	62	738	2.6	0.95 [0.90 − 0.99]	12.4 [10.7 − 14.2]	0.10 [0.08 − 0.12]
6	770	62	738	5.0	0.94 [0.90 − 0.99]	11.4 [9.6 − 13.4]	0.11 [0.09 − 0.14]
7	765	65	468	2.6	0.97 [0.92 − 1.02]	14.5 [12.6 − 16.5]	0.14 [0.12 − 0.16]
7	765	65	468	5.0	0.97 [0.91 − 1.03]	14.1 [12.4 − 16.1]	0.16 [0.13 − 0.20]
7	765	65	735	2.6	0.95 [0.90 − 0.99]	12.1 [10.5 − 13.9]	0.10 [0.08 − 0.12]
7	765	65	735	5.0	0.94 [0.89 − 0.99]	11.1 [9.5 − 13.1]	0.11 [0.09 − 0.13]
8	759	64	469	2.6	0.97 [0.92 − 1.02]	15.1 [13.3 − 17.2]	0.14 [0.11 − 0.17]
8	759	64	469	5.0	0.97 [0.91 − 1.03]	14.7 [12.8 − 16.9]	0.16 [0.13 − 0.19]
8	759	64	736	2.6	0.95 [0.90 − 0.99]	12.7 [10.9 − 14.5]	0.09 [0.08 − 0.12]
8	759	64	736	5.0	0.94 [0.90 − 0.99]	11.6 [9.7 − 13.7]	0.11 [0.09 − 0.13]
9	755	68	465	2.6	0.97 [0.92 − 1.02]	14.2 [12.3 − 16.2]	0.13 [0.11 − 0.16]
9	755	68	465	5.0	0.97 [0.91 − 1.02]	13.9 [12.3 − 16.1]	0.15 [0.13 − 0.18]
9	755	68	732	2.6	0.95 [0.90 − 0.99]	11.8 [10.3 − 13.5]	0.09 [0.07 − 0.11]
9	755	68	732	5.0	0.94 [0.90 − 0.99]	10.8 [8.9 − 12.8]	0.10 [0.08 − 0.12]
10	759	70	463	2.6	0.96 [0.91 − 1.02]	14.6 [12.9 − 16.7]	0.14 [0.11 − 0.17]
10	759	70	463	5.0	0.96 [0.90 − 1.02]	14.6 [12.6 − 16.7]	0.17 [0.14 − 0.19]
10	759	70	730	2.6	0.94 [0.90 − 0.99]	12.3 [10.7 − 14.0]	0.09 [0.08 − 0.12]
10	759	70	730	5.0	0.94 [0.89 − 0.99]	11.5 [9.9 − 13.3]	0.11 [0.09 − 0.13]

Fig. S 2: Ebola $2014 - 2016$ epidemic time-scaled tree (data from (Dudas et al., 2017), polytomies are resolved as in forest 1) coloured by country predicted by PastML (Ishikawa et al., 2019): Guinea (GIN) is light-blue, Liberia (LBR) is dark-blue, Sierra-Leone (SLE) is light-green. The bottom colourstrip shows the samples kept for the SLE 2014 epidemic analysis (forest 1): SLE samples that are directly related to the SLE epidemic of 31 July 2014 (start of quarantine) and sampled after this date. The SLE samples that were later reintroduced to SLE via other countries (e.g. in the indicated GIN-rooted subtree) were not included in the analysis.

Table S 2: Parameters estimated for SLE 2014 Ebola epidemic, without taking the declared number of cases into account.

forest	tips	trees	hidden trees	infectious time $\frac{1}{\psi}$ (fixed)	R_e	incubation period $\frac{1}{\mu}$	ρ
1	779	56	0	2.6	1.15 [1.05 − 1.26]	22.8 [20.6 − 25.4]	0.41 [0.35 − 0.46]
1	779	56	0	5.0	1.22 [1.10 − 1.35]	24.4 [21.9 − 27.3]	0.51 [0.45 − 0.58]
2	762	68	0	2.6	1.12 [1.02 − 1.23]	22.1 [19.8 − 24.6]	0.38 [0.33 − 0.44]
2	762	68	0	5.0	1.16 [1.04 − 1.28]	23.8 [21.5 − 26.7]	0.49 [0.42 − 0.56]
3	764	70	0	2.6	1.13 [1.03 − 1.24]	22.8 [20.6 − 25.4]	0.40 [0.35 − 0.46]
3	764	70	0	5.0	1.17 [1.05 − 1.30]	24.5 [22.0 − 27.2]	0.51 [0.44 − 0.57]
4	759	63	0	2.6	1.12 [1.03 − 1.23]	22.7 [20.3 − 25.2]	0.39 [0.33 − 0.44]
4	759	63	0	5.0	1.18 [1.06 − 1.31]	24.2 [21.7 − 27.0]	0.49 [0.43 − 0.56]
5	711	55	0	2.6	1.13 [1.03 − 1.24]	21.6 [19.3 − 24.2]	0.38 [0.33 − 0.44]
5	711	55	0	5.0	1.17 [1.05 − 1.30]	23.3 [20.7 − 26.1]	0.49 [0.43 − 0.56]
6	770	62	0	2.6	1.14 [1.04 − 1.25]	22.4 [20.2 − 24.8]	0.39 [0.34 − 0.45]
6	770	62	0	5.0	1.18 [1.07 − 1.31]	24.1 [21.6 − 26.8]	0.50 [0.44 − 0.56]
7	765	65	0	2.6	1.13 [1.03 − 1.23]	22.0 [19.8 − 24.6]	0.38 [0.33 − 0.44]
7	765	65	0	5.0	1.17 [1.06 − 1.30]	23.6 [21.1 − 26.4]	0.48 [0.42 − 0.55]
8	759	64	0	2.6	1.13 [1.03 − 1.24]	23.0 [20.7 − 25.6]	0.38 [0.33 − 0.44]
8	759	64	0	5.0	1.18 [1.06 − 1.31]	24.6 [22.1 − 27.3]	0.48 [0.42 − 0.55]
9	755	68	0	2.6	1.11 [1.02 − 1.21]	21.6 [19.5 − 24.2]	0.35 [0.30 − 0.42]
9	755	68	0	5.0	1.14 [1.03 − 1.26]	23.4 [21.0 − 26.2]	0.46 [0.40 − 0.52]
10	759	70	0	2.6	1.11 [1.01 − 1.22]	22.2 [20.0 − 24.7]	0.38 [0.32 − 0.43]
10	759	70	0	5.0	1.14 [1.03 − 1.27]	24.3 [21.9 − 27.1]	0.50 [0.43 − 0.56]