Real-world federated learning for the brain imaging scientist

Stijn Denissen[1,2,*], Jorne Laton[1], Matthias Grothe[3], Manuela Vaneckova[2], Tomáš Uher[4], Matěj Kudrna[2], Dana Horáková[4], Johan Baijot[1], Iris-Katharina Penner[5], Michael Kirsch[6], Jiří Motýl[4], Maarten De Vos[7,8], Oliver Y. Chén[9,10], Jeroen Van Schependom[1,11], Diana Maria Sima[1,12], and Guy Nagels[1,13]

[1] AIMS Lab, Center for Neurosciences, UZ Brussel, Vrije Universiteit Brussel, Brussels, Belgium
[2] Department of Radiology, First Faculty of Medicine, Charles University, General University Hospital, Prague, Czech Republic
[3] Department of Neurology, University Medicine Greifswald, Greifswald, Germany
[4] Department of Neurology and Center of Clinical Neuroscience, First Faculty of Medicine, Charles University, General University Hospital, Prague, Czech Republic
[5] Department of Neurology, Inselspital, Bern University Hospital, University of Bern, Bern, Switzerland
[6] Institute for Diagnostic Radiology and Neuroradiology, University Medicine of Greifswald, Greifswald, Germany
[7] Department of Electrical Engineering (ESAT), KU Leuven, Leuven, Belgium
[8] Development & Regeneration, KU Leuven, Leuven, Belgium
[9] Département Médecine de Laboratoire et Pathologie (DMLP), Centre Hospitalier Universitaire Vaudois (CHUV), Lausanne, Switzerland
[10] Faculté de Biologie et de Médecine (FBM), Université de Lausanne, Lausanne, Switzerland
[11] Department of Electronics and Informatics (ETRO), Vrije Universiteit Brussel, Brussels, Belgium
[12] icometrix, Leuven, Belgium
[13] St Edmund Hall, University of Oxford, Oxford, UK

*Correspondence: Stijn Denissen (stijn.denissen@vub.be, Twitter: @StijnDenissen)

Abstract

Background. Federated learning (FL) could boost deep learning in neuroimaging but is rarely deployed in a real-world scenario, where its true potential lies. Here, we propose FLightcase, a new FL toolbox tailored for brain research. We tested FLightcase on a real-world FL network to predict the cognitive status of patients with multiple sclerosis (MS) from brain magnetic resonance imaging (MRI).

Methods. We first trained a DenseNet neural network to predict age from T1-weighted brain MRI on three open-source datasets, IXI (586 images), SALD (491 images) and CamCAN (653 images). These were distributed across the three centres in our FL network, Brussels (BE), Greifswald (DE) and Prague (CZ). We benchmarked this federated model with a centralised version. The best-performing brain age model was then fine-tuned to predict performance on the Symbol Digit Modalities Test (SDMT) of patients with MS (Brussels: 96 images, Greifswald: 756 images, Prague: 2424 images). Shallow transfer learning (TL) was compared with deep transfer learning, updating weights in the last layer or the entire network respectively.

Results. Centralised training outperformed federated training, predicting age with a mean absolute error (MAE) of 6.00 versus 9.02. Federated training yielded a Pearson correlation (all $p < .001$) between true and predicted age of .78 (IXI, Brussels), .78 (SALD, Greifswald) and .86 (CamCAN, Prague). Fine-tuning of the centralised model to SDMT was most successful with a deep TL paradigm (MAE = 9.12) compared to shallow TL (MAE = 14.08), and respectively on Brussels, Greifswald and Prague predicted SDMT with an MAE of 11.50, 9.64 and 8.86, and a Pearson correlation between true and predicted SDMT of .10 ($p = .668$), .42 ($p < .001$) and .51 ($p < .001$).

Conclusion. Real-world federated learning using FLightcase is feasible for neuroimaging research in MS, enabling access to a large MS imaging database without sharing this data. The federated SDMT-decoding model is promising and could be improved in the future by adopting FL algorithms that address the non-IID data issue and consider other imaging

55 modalities. We hope our detailed real-world experiments and open-source distribution of

56 FLightcase will prompt researchers to move beyond simulated FL environments.

58 **Keywords:** Federated Learning | BIDS | Brain | Deep Learning | Multiple Sclerosis |

59 Cognition | Brain age

Introduction

Deep learning is gaining traction as a tool to study the brain's function and structure (1,2). Since the comprehensive Nature review by Yann Lecun, Yoshua Bengio and Geoffrey Hinton on the topic in 2015 (3), the curiosity of brain researchers has clearly been sparked; over 10.000 papers were published on the topic in the last decennium, while just over 600 were published at the end of 2014.

Deep learning has led to major breakthroughs in brain analysis. Brain structures can now be accurately quantified using segmentation models (4,5), aiding doctors in diagnosis and evaluating treatment effect. Deep neural networks furthermore reduce the error in predicting age from brain MRI to the order of 2 years (6). This yields accurate biological aging clocks that capture deviations from healthy aging patterns and efficient communication tools; brain damage can be expressed in terms of "how much older the brain looks". Deep learning models can indeed capture the brain's complexity by creating high-dimensional, data-driven representations beyond human understanding. Yet there is a catch. To create reliable representations, deep learning models require big training datasets; usually in the order of tens of thousands of images (6). As many dedicated researchers put significant effort in collecting datasets, we need to reconsider how they can be reused and combined to unlock the full potential of deep learning in brain image analysis.

The conventional way to train deep learning models is to centralize datasets. This is feasible for certain domains like brain age, as it relies on healthy control data sets that are publicly shared. Indeed, age-labelled T1-weighted images are widely available via initiatives such as the UK Biobank (7) and many repositories in OpenNeuro (8). In most other domains however, especially when working with sensitive patient data, data sharing is difficult. Barriers to data sharing can be plentiful in technical, motivational, economic, political, legal, and ethical terms (9). Especially barriers in the latter three domains apply

for centralizing neuroimaging data. A first conditio sine qua non is trust; "In the absence of

trust, providers could anticipate potential misinterpretation, misuse or intentional abuse of

the data" (9). Second, the Global Data Protection Regulation (GDPR) enforces strict

guidelines to data sharing. This either complicates the procedure, lowering the incentive to

do so, or blocks it entirely. This is especially true for the type of data brain scientists work

with, as faces could be reconstructed from MR images. Lastly, data sharing is relatively

static. Especially data from routine clinical practice is continuously generated, and sharing

those periodically is time-consuming and inefficient.

This conventional, centralized view on machine learning was challenged by McMahan and

colleagues in 2017 (10). They introduced the concept of Federated Learning (FL), in which a

model is trained by sending it to the data in local institutions, where they are trained locally.

Instead of data, models are shared. Moreover, the computational load and data storage is

spread across multiple centres. In the following years, (brain) researchers started

experimenting with the idea in simulated settings, mainly on open-source data. New

algorithms were suggested (11), performance with respect to centralised training was

explored (12) and federated learning toolboxes were designed (13). Yet while FL in principle

solves all previously mentioned issues, it generates new challenges that hinder brain

scientists to deploy it in a real-world setting. Among those are financial boundaries (e.g.

graphical processing units (GPU)), hardware and software differences, connectivity issues

and data heterogeneity. Indeed, only few succeeded to date, mainly in brain tumour

segmentation (14,15), where access to bigger datasets boosted model performance (15).

While other real-world examples exist, it is often unclear from the methods section of

papers whether it concerned a simulation or real-world FL on geographically distributed

data.

In this work, we aspired to pioneer real-world FL in our own modelling domain, decoding

cognitive performance from structural brain MRI in multiple sclerosis (MS) on data from

three international centres in Brussels (BE), Greifswald (DE) and Prague (CZ). When starting

the practical setup in early 2023, the most pressing issue was the lack of software orchestrating real-world federated learning in our neuro-imaging context, not to mention handling data loading of clinical datasets that differed widely in format. Hence, we designed a simple, glass-box FL framework that allows easy real-world deployment in an international context: "FLightcase". FLightcase is designed to work with the Brain Imaging Data Structure (BIDS (16)), which became the standard data organisation format for brain researchers in the past decade (17). BIDS is enforced by data sharing platforms such as OpenNeuro (8), and we aspired to continue this trend. In this way, we hope to encourage brain AI researchers to consider decentralised model training and leverage their modelling to larger, multi-institutional datasets to boost generalisability.

The contributions of this paper are therefore the following:

- The introduction of FLightcase, a simple, open-source, BIDS-compliant FL toolbox in neuroimaging.
- Proving the real-world readiness of FLightcase on a real-world FL network with geographically distributed data in Brussels (BE), Greifswald (DE) and Prague (CZ). The modelling goal was to predict cognitive function from brain MRI in MS using transfer learning from a pre-trained brain age model. In doing so, we addressed two research questions:
    1. Does federated match centralised training in terms of model performance? This question was addressed in the brain age modelling, as it relies on open-source data that can be centralised.
    2. Does deep transfer learning (updating all network weights) outperform shallow learning (updating only the weights of the fully connected layer) for predicting cognitive impairment in MS?
- Discussing challenges and solutions in setting up a real-world federated learning network to encourage the method in the field.

144 Methods

145 FLightcase in brief

FLightcase is a federated learning toolbox that was specifically designed to work with the

Brain Imaging Data Structure (BIDS) (16). We thereby aim to facilitate model training for

brain researchers and stimulate researchers to use this data structure. Its basic

communication relies on sending 2 files after each other. The first contains the machine

learning information to be transmitted, the second is a text file marking transmission

completion. Files are sent between computers via secure copy protocol (SCP) and

therefore require all computers to be UNIX-based. In the remainder of this paper, we will

refer to "computer" or "node" interchangeably. The SCP command requires two localisers:

• The IP address of the receiving computer. An example of a secure network where

computers are assigned an IP address, and are therefore reachable, is a virtual

private network (VPN). This was used in our real-world example (cfr. infra).

• The location within the computer to write the file to. To facilitate this, we use the

concept of an "FL workspace". The FL workspace is a folder dedicated to the

federated learning experiment.

These and other settings (cfr. infra) are stored in a JavaScript Object Notation (JSON) file

per computer, which are different for clients and server. For example, the client settings

define the location of the BIDS dataset, the server settings define the clients to expect. To

orchestrate the FL process, the server moreover stores an "FL plan" JSON file containing

training preferences (e.g. number of FL rounds). Lastly, the server defines the model

architecture that will be trained in a separate Python file.

For a more in-depth overview of the FLightcase software, we refer to the "FLightcase

unpacked" section of the supplementary material. FLightcase is publicly available in our

AIMS-VUB GitHub repository (https://github.com/AIMS-VUB/FLightcase) and deployed on

the Python Package Index (PyPI, https://pypi.org) for easy installation. The federated

experiments in this study relied on FLightcase v0.1.8. FLightcase can be tested using the

simulation explained in the supplementary material, section "How to test FLightcase".

FLightcase v0.1.8 depends on the following Python modules: torch v2.5.1 (18), pandas

v2.2.3 (19), monai v1.4.0 (20), scikit-learn v1.6.0 (21), tqdm v4.67.1 (22), nibabel v5.3.2

(23), paramiko v3.5.0 (24), scp v0.15.0 (25), matplotlib v3.10.0 (26), scipy v1.14.0 (27),

numpy v1.26.4 (28), click v8.1.8 (29), twine v6.0.1 (30).

180   The federated learning network

To prove the real-world effectiveness of FLightcase, we tested it in an FL network between

our AIMS lab in Brussels (BE), the Greifswald University Hospital (DE) and the General

University Hospital Prague (CZ). The network (figure 1) consists of 4 computers, of which

one is the server that coordinates the project, and the other three serve as clients on which

models are trained using the local data. The two Brussels computers were in the same

office and connected to the network of the department of electronics and informatics

(ETRO) of the VUB. The computers in Greifswald and Prague were connected to this

network via a Virtual Private Network (VPN). Models were shared via secure copy protocol

(SCP) with secure shell (SSH).

All client computers were equipped with a graphical processing unit (GPU); Brussels:

NVIDIA GeForce RTX 4090 (24GB), Greifswald: NVIDIA GeForce RTX 3090 (24GB) and

Prague: NVIDIA GeForce RTX 4090 (24GB). The operating system of each computer (server

and clients) was Debian GNU/Linux 12 ("bookworm"), and Python version 3.11.2 was used

consistently.

Figure 1. The Federated Learning network for the real-world experiment. The computer with

the "sigma" symbol is the server, whereas computers with an "update" symbol are clients.

Abbreviations: SCP = Secure Copy Protocol; VPN = Virtual Private Network.

Real-world FLightcase testing

This section explains the two steps to test FLightcase on the real-world FL network

explained above. Step 1 involved training a DenseNet convolutional network architecture

(31) to predict age from T1-weighted brain MRI, analogous to the work of James Wood and

colleagues (32). As step 1 modelled on open-source data and thus allowed centralising

data, federated training was benchmarked against centralised training (explained at the

end of the methods section). Step 2 involved transfer learning of the best brain age model

from step 1 (lowest overall test mean absolute error (MAE)) to predict cognitive impairment

in people with multiple sclerosis (MS). The FL plans for training the brain age and SDMT

models were included as supplementary table S4.

Ethics

The "Commissie Medische Ethiek" (CME) of the UZ Brussel judged this retrospective study to be exempt from ethical approval (B.U.N. 1432022000303). For the MS data at each center in this study, ethical approval was obtained prior to data acquisition (Brussels: B.U.N. 143201423263, Greifswald: BB159/18, Prague: 113/22 S-IV and 28/17). Healthy control data used to train the brain age model was obtained from open-source datasets.

Data

To train the brain age network (step 1), we used three open-source data sets: the Cambridge Centre for Ageing and Neuroscience (Cam-CAN) dataset (33), the Information eXtraction from Images (IXI) dataset (34) and the Southwest University Adult Lifespan Dataset (SALD) (35). The Cam-CAN dataset was stored on the Prague computer, the IXI dataset in Brussels and the SALD dataset in Greifswald. The datasets contain T1-weighted MRI, sex and age from healthy subjects. The data is summarised in table 2.

The cognition prediction network (step 2) was trained on three MS datasets at the Vrije Universiteit Brussel (VUB), the general university hospital Prague (VFN) and Greifswald university hospital. The data were organised locally in the BIDS format, and contained T1 weighted MR images, demographic and clinical information. This entailed sex, age, expanded disability status scale (EDSS (36), physical disability), , disease duration, MS subtype (relapsing versus progressive onset) and the symbol digit modalities test (SDMT (37)), i.e., the target to predict. In this test, a subject is presented a list of symbols that need to be converted to numbers using a key on the top of the page, matching symbols with numbers. In 90 seconds, the subject must convert as many symbols to numbers as possible, each time saying the number out loud for the test administrator to write down. The SDMT is a measure of information processing speed.

The T1-weighted MR images were preprocessed using the pipeline by Wood et al. 2022 (32), which includes skull-stripping, registration to Montreal Neurosciences Institute (MNI) 152 space (1mm isotropic) and cropping to an isotropic resolution of 130 voxels. These steps

242   are defined in their "pre_process.py" script, for which we included an updated version in

243   our GitHub repository with permission of the authors (32).

	Open-source (step 1)			Closed-source (step 2)		
	Cam-CAN	**IXI**	**SALD**	**Brussels**	**Greifswald**	**Prague**
N	653	586	491	96	338	916
N image – SDMT pairs	653	586		96	756	2424
sex (m:f)	323:330	258:328	185:306	27:69	110:228	275:641
Age at scan (M ± SD)	54.3 ± 18.6	49.4 ± 16.7	45.2 ± 17.5	47.9 ± 9.9	43.5 ± 12.1	42.2 ± 9.5
SDMT (M ± SD)	/	/	/	48.0 ± 11.6	51.7 ± 15.3	58.9 ± 12.0
EDSS (Med; IQR)	/	/	/	3; 2	2; 2	2.5; 2
Disease duration (M ± SD)	/	/	/	15.5 ± 8.5	9.2 ± 6.9	13.2 ± 8.1
Type MS	/	/	/	CIS: 2 RRMS: 81 SPMS: 6 PPMS: 7	CIS: 7 RRMS: 680 SPMS: 41 PPMS: 23 RIS: 5	*CIS: 448, RRMS: 1566, SPMS: 363, PPMS: 38, PRMS: 6*
T1w MR images:						
Manufacturer	Siemens	Philips, GE	Siemens	Philips	Siemens	Siemens
Model	TrioTim	Philips: Intera,	TrioTim	Achieva: 31	Verio	Skyra

		Gyroscan Intera		Ingenia: 65		
Echo time (ms)	2.98	4.603	2.52	2.303; 2.287	2.58	2.96
Repetition time (ms)	2.25	9.600; 9.813	1.9	4.952; 5.189	1.900	2.300
Slice thickness (mm)	1	/	/	1.0	0.90	1
Flip angle (degrees)	9	8	9	8	9	9
Field strength (T)	3	3 and 1.5	3	3	3	3

Table 2. Dataset characteristics. Abbreviations: n = sample size, m = male, f = female, M = mean, SD = standard deviation, SDMT = symbol digit modalities test, EDSS = expanded disability status scale, GE = General Electric. Notes: [1] Variable distributions are calculated across all image-SDMT pairs. [2] missing values: 14 EDSS (Prague), 3 disease course (Prague) and 15 disease duration (Greifswald). [3] The MR image acquisition info was extracted from a single subject per scanner model and might therefore deviate among subjects. For IXI, which was acquired at three different sites, MRI acquisition info was obtained from the website: https://brain-development.org/ixi-dataset/ (accessed 10 March 2025). Detailed scanner info was only available for the Philips scanners.

The data was split randomly in 80% train and 20% test data on each client. To prevent data leakage, multiple images of a single subject were collected in either train or test set. Each FL round, the training data was moreover bootstrapped 5 times, with 75% train and 25% validation data. This results in a train/validation/test split of 60/20/20 (cfr. supplementary table S4).

The 3D DenseNet model

The 3D Dense Convolutional Network (DenseNet) (31) was used during the initial brain age task (step 1) and the transfer learning task to SDMT (step 2). DenseNet outperformed other

network architectures in a medical imaging context (38) and is unique for directly

connecting all layers inside the network with each other (31). Each layer therefore takes all

previous feature maps, outputs of previous layers, as input. Hence, the propagation of

features throughout the network is improved. The DenseNet architecture moreover

reduces the "vanishing gradient" problem, where the gradient used to update weights in

the network gradually approaches zero during backpropagation to earlier layers. Lastly, it

reduces the number of parameters in the network (31). The 3D DenseNet model in this

paper has 11243649 updatable parameters and is described schematically in figure 2.

For the brain age prediction task, all layers in the network were unfrozen, whereas for the

SDMT prediction task, two transfer learning methods were explored. In the "shallow TL"

task, only the fully connected layer, consisting of 1025 parameters (1024 weights and 1

bias), was updated during training (cfr. figure 2); the other layers, i.e. the feature extractor

part of the network, was frozen. In the "deep TL" task, all layers of the network were

updated. Figure 2 also summarises the transfer learning methodology in the box on top.

Figure 2. DenseNet architecture and training methodology (top panel). Avg = Average, AAvg

= Adaptive Average. The "Label" is chronological age for the initial brain age prediction task,

and the SDMT for the shallow and deep transfer learning (TL).

Evaluation

The final performance of all models was evaluated on the test data set per client by the mean absolute error (MAE) and Pearson correlation. The overall model performance was moreover calculated with equation 1:

$$MAE_{test,overall} = \sum_{i=0}^{m} \frac{MAE_{test,i} * n_i}{N}$$

Equation 1: Overall test MAE calculation, with m the number of clients and N the total sample size across clients.

Benchmarking: centralised brain age training

As a benchmark model, we additionally updated the brain age model on a centralised version of the three open-source datasets. The same test dataset was used as in the federated setting. During training however, the random train/validation splits (5 per epoch) were performed on the entire training dataset (80%). The training dataset therefore included samples of all three datasets, while these were separated in the federated setting. As the centralised setting had access to all test results together, the test MAE was calculated across all subjects simultaneously instead of the per-client approach in equation 1.

Results

Step 1: predicting brain age

Real-world federated training

The total FL process took 2 hours, 22 minutes, and 50 seconds to complete. The model reached a minimum after 48 rounds and training stopped early after 68 rounds. The final network achieved an overall test MAE of 9.02, and an MAE of 8.86, 8.45 and 9.92 on the test

datasets of CamCAN, IXI and SALD respectively. Pearson correlation for the respective

datasets was 0.78 (p < .001), 0.78 (p < .001) and 0.86 (p < .001). The training process is

visualised in figure 3, whereas scatterplots between true and predicted age (brain age) are

displayed in figure 4.

Figure 3: Federated training of the brain age network. The red (train) and blue (validation)

lines represent the average train and validation MAE respectively, and the shaded red and

blue areas represent the 95% confidence interval, all calculated across 5 bootstraps per FL

round. The right lower panel show the average validation MAE across the clients in the

aggregation, calculated on the server side.

Figure 4. Scatterplots between true and predicted age (brain age) on the test datasets of

CamCAN (stored in Prague), IXI (stored in Brussels) and SALD (stored in Greifswald). The

grey dashed line indicates the perfect prediction line where Age = Brain Age.

Centralised benchmark

Centralised training on the three open-source data sets took 10 hours and 8 seconds. The

model reached a minimum after 108 rounds and was stopped early after 128 rounds. The

model achieved an overall test MAE of 6.00 and a Pearson correlation of 0.91 (p < .001). The

results are displayed visually in supplementary figure S2 (loss figure) and S3 (test results

scatterplot).

Step 2: predicting SDMT

Figure 5 shows the training process for training the SDMT models using shallow TL (left) and

deep TL (right), starting from the centralised brain age model. Figure 6 shows the results of

applying the final model to the test set of each centre.

Shallow TL took 1 hour, 49 minutes and 42 seconds. The model reached a minimum

average validation MAE after the first FL round and achieved an overall test MAE of 14.08

SDMT points. The per-client test performance in terms of MAE was 11.91 (Brussels), 13.26

(Greifswald) and 14.43 (Prague), whereas Pearson correlation was -0.25 (p=0.283), -0.39

(p<.001) and -0.47 (p < .001) respectively.

For the deep TL model (right), training took 8 hours, 30 minutes and 4 seconds. The model reached a minimum at FL round 54 and achieved an overall test MAE of 9.12 SDMT points. The per-client test performance in terms of MAE was 11.50 (Brussels), 9.64 (Greifswald) and 8.86 (Prague), whereas Pearson correlation was 0.10 (p=0.668), 0.42 (p<.001) and 0.51 (p < .001) respectively.

Figure 5. Loss figure of fine-tuning the brain age model to predict SDMT using shallow (left) and deep (right) transfer learning. Abbreviations: FL = federated learning, MAE = mean absolute error, avg = average. The lower panels show the average validation MAE across the clients in the aggregation, calculated on the server side.

Figure 6. Scatterplots visualising test performance of the SDMT model trained with shallow

TL (upper row) and deep TL (lower row).

Discussion

In this manuscript, we introduced FLightcase, a Federated Learning toolbox specifically designed to promote real-world, decentralised machine learning for brain scientists. We then proved the real-world readiness of FLightcase by training models to predict SDMT from T1-weighted brain MRI images, using transfer learning from a brain age model. During brain age modelling, centralised training outperformed federated training. During transfer learning, a deep paradigm where all network weights were trained outperformed shallow learning, where solely the last network layer was updated. The final model predicted SDMT with an average error of 9.12 points and performed especially well on the Greifswald and Prague dataset.

Decentralised brain age modelling

The final federated brain age model predicted age from T1w MRI of healthy controls with an

average error of 9.02 years across datasets. Strong correlations were furthermore observed

on each client test dataset, indicating that federated learning successfully sensitised the

model to individual differences in brain structure. Nonetheless, centralised training

outperformed the federated approach with a test MAE reduction of 3.02 years. This

contrasts findings from an FL simulation by Basodi et al. 2022, finding similar performance

of brain age models trained on decentralised and centralised datasets (12). Besides a

larger dataset of over 10.000 images from 2 sources, data from each source was

distributed across 6 simulated centres, contrasting our design with one source per centre.

Our brain age models might suffer low generalisability by nature of the open-source

datasets, containing both Caucasian (Cam-CAN and IXI) and Chinese (SALD) brains that

are known to differ in structure (39,40). The model indeed had a higher test MAE in SALD

(9.92) compared to CamCAN (8.86) and IXI (8.45). The overfitting behaviour on the IXI

dataset was moreover visible in the average validation loss in the aggregation sample at the

server side; valleys coincided with IXI being in the sample. This zigzagging pattern was

especially clear in the last rounds (figure 3). This underlines the importance to consider

alternative client sampling schemes such as FedSampling (41). Lastly, the combined size

of the decentralised dataset was 1730 images, while the best model reported in a

comprehensive review on brain age model performance (6) was trained by Han Peng and

colleagues on 14.503 T1-weighted brain images (42). Enlarging our dataset would likely

have resulted in improved brain age prediction performance, as well as a lower discrepancy

between centralised and federated training such as in Basodi et al. 2022 (12).

Transfer learning to SDMT

Deep transfer learning from the centralised brain age model outperformed shallow transfer learning with an overall MAE of 9.12 versus 14.08. This indicates that the latent feature representation for the brain age task was incompatible with the SDMT prediction task, requiring an update of the feature extractor part of the network.

Although deep TL indeed improved performance substantially, the model had difficulty decoding SDMT performance on the Brussels dataset. While training and validation loss as well as confidence intervals gradually decreased in Greifswald and Prague, loss increased in the Brussels dataset. Not unlike federated brain age modelling (cfr. supra), this translates in heavy loss fluctuations on the server side, depending on which centre models are in the aggregation sample. Valleys coincided with the local models of Greifswald and Prague in the aggregation sample. We hypothesise two factors to underly this behaviour.

First, the Greifswald and Prague datasets were larger. The contributions of their local models in each round were therefore bigger than the Brussels local model, causing the model to learn less from the Brussels dataset. This is an inherent problem of the conventional FedAvg paradigm, which is why solutions for equality of local model updates start to emerge. An example of this is q-FedAvg, which "reweights" the loss by a parameter q (43). The result is that client models with higher loss receive a higher weight in the aggregation.

Second, the behaviour nicely illustrates the non-IID problem in federated learning, meaning that we cannot assume that data points are drawn from the same underlying sample (44). This violates an important assumption in machine learning (45). Indeed, MS centres work with different equipment and workflows, which can be expected to increase across country borders. As illustrated in table 1, different MRI scanners were used across different centres, and MS samples differed, most prominently in the SDMT ground truth distribution. This raises awareness for the importance of data harmonisation and gaining

422 insights in between-centre differences in for example test administration. It is therefore

423 encouraging to observe the emergence of open-source federated harmonisation toolboxes

424 like FedHarmony [45], which should be considered in future research for optimal model

425 performance.

The road ahead for real-world FL in neuroimaging

Federated learning offers a compelling alternative to centralised machine learning. It

distributes computational load and addresses data sharing as one of the major

impediments for international scientific collaborations (47). The promises for federated

learning in the medical field are big indeed, and especially come from cancer research.

One of the first large-scale real-world FL demonstrations was in 2022 by Sarthak Pati and

colleagues (15). In a global federated learning setting with 71 institutions, they updated a

publicly available algorithm to detect glioblastoma boundaries and obtained a

considerable gain in the validation Dice score across clients of about 25%. The authors

mention "It is the use of FL that successfully enabled (i) access to such an unprecedented

dataset of the most common and fatal adult brain tumour, and (ii) meaningful ML training to

ensure the generalizability of models across out-of-sample data.". Indeed, although Vo et

al. 2024 confirms that comparable results can be obtained in centralised contexts in ideal

scenarios (48), the key benefit of FL is that it can still achieve these results when this is not

the case. Similarly, technical advances enable addressing data heterogeneity across

institutions in a federated setting, such as tackling the non-IID issue by a combination of

distributed gradient blending and proximity-aware client weighting (49). Considering these

medical FL breakthroughs, it is even more surprising that literature appears to ignore the

very first step to achieve these results: how to build an FL network across clinical

institutions. This practical step appears to be an assumption, as literature focusses on

challenges after a network has been established (50). In our experience however, building a

real-world FL network is the key roadblock between the compelling idea of federated

learning and its practical realisation, and should be the key focus to start an era of real-

world decentralised machine learning beyond simulation.

Collaboration. A first prerequisite is a minimal trust between all partners in the FL network. With malicious intent, source data could for example be shared between computers via VPN. The team should moreover be multidisciplinary, containing both medical experts and technical experts in terms of information technology (IT) and data science. Real-world federated learning poses unique IT challenges in terms of communication and encryption on top of other existing technical challenges in deep learning research. On the other hand, medical expertise is required in preprocessing and interpreting the data, as well as understanding the model and its output.

Hardware. Besides sufficient storage, updating neural networks like the DenseNet model (over 11 million parameters) requires processing units like a graphical (GPU) or tensor processing unit (TPU) on each client computer. In our network, all client computers were equipped with a GPU of 24GB random access memory (RAM).

Software. There is a lack of FL toolboxes that are rigorously tested in real-world circumstances, and most are designed as general frameworks not specifically tailored to medical data needs. We started designing FLightcase in early 2023 when real-world FL examples in neuroimaging just started to emerge (15). Although some toolboxes such as Flower (13) and OpenFL (51) were distributed open source, we experienced difficulties in real-world deployment on our own network. We therefore set out to design a framework relying on a simple but stable connection between computers, focussing on the core needs of our methodology, i.e., compliance with BIDS, supporting loading anatomical brain images and focussing on the original and most popular FL algorithm FedAvg. In the meantime, toolboxes such as Flower have further developed into communities with peer support. Awareness on the difficulty of real-world FL is rising, reflected by companies facilitating deployment such as ScaleOut, and forces are joined to allow tailoring toolboxes to the specific needs of different modelling domains. Almost a decade after the pioneering work of Sergey M. Plis and colleagues (52) on standardised analysis of decentralised neuroimaging data, FL software approaches a technology readiness level where

centralised workflows can seamlessly be converted to federated ones. For FLightcase

specifically, we in the meantime reconsidered the basic communication layer, allowing file

sharing by uploading to and downloading from a Flask web server.

Connectivity and remote access. All computers in our network are connected to locally

available internet providers. This introduces new centre-specific difficulties pertaining to

local security settings. Blocking web addresses such as Teamviewer for example

complicated remote access in our case. Combined with limited scalability due to a

maximum number of remote computers in TeamViewer, we switched to tmate (cfr.

methods). The drawback of this approach is that there is no graphical interface available; a

remote computer is operated via command line.

Financial. Ensuring the aforementioned requirements comes with a price tag. Especially

the hardware for each client with expensive GPUs imposes additional financial restraints,

limiting the feasibility of setting up a network.

Data and code availability

The source code is available in the GitHub repository of the AIMS lab

(https://github.com/AIMS-VUB/FLightcase)(53), whereas FLightcase was also distributed

via the Python Package Index (PyPI). Data underlying the real-world and simulated brain

age experiments is open source available.

Author contributions

Conceptualization: SD, JL, MDV, OYC, JVS, DMS, GN; Data curation: SD; Formal Analysis:

SD; Funding acquisition: SD, MV, DH, JB, JVS, DMS, GN; Investigation: SD, MG, MV, TU, JL,

MKu, DH, JB, IKP, MKi, JM, JVS, DMS, GN; Methodology: SD, JL, MKu, JB, OYC, JVS, DMS, GN;

Project administration: TU, MV, DH, OYC, JVS, DMS, GN; Resources: MG, MV, TU, MKu, DH,

IKP, MKi, JM, JVS, GN; Software: SD, JL; Supervision: JVS, DMS, GN; Validation: SD;

Visualization: SD; Writing – original draft: SD; Writing – review & editing; all but SD.

Declaration of competing interests

This work was partly performed during the industrial PhD project of Stijn Denissen in collaboration with icometrix. Guy Nagels reports a relationship with icometrix that includes: equity or stocks. Diana Sima reports a relationship with icometrix that includes: employment. Manuela Vaneckova reports a relationship with Biogen Idec that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Manuela Vaneckova reports a relationship with Novartis that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Manuela Vaneckova reports a relationship with Roche that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Manuela Vaneckova reports a relationship with Merck that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Manuela Vaneckova reports a relationship with Teva that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Tomas Uher reports a relationship with Biogen that includes: speaking and lecture fees and travel reimbursement. Tomas Uher reports a relationship with Novartis that includes: speaking and lecture fees and travel reimbursement. Tomas Uher reports a relationship with Sanofi that includes: funding grants and travel reimbursement. Tomas Uher reports a relationship with Roche that includes: speaking and lecture fees and travel reimbursement. Tomas Uher reports a relationship with Merck Serono that includes: travel reimbursement. Tomas Uher reports a relationship with Biogen Idec that includes: funding grants. Dana Horakova reports a relationship with Biogen Idec that includes: consulting or advisory, funding grants, speaking and lecture fees, and travel reimbursement. Dana Horakova reports a relationship with Novartis that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Dana Horakova reports a relationship with Merck that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Dana Horakova reports a relationship with Bayer that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement. Dana Horakova reports a relationship with Sanofi Genzyme that includes: consulting or advisory, speaking and lecture fees, and travel reimbursement.

Dana Horakova reports a relationship with Roche that includes: consulting or advisory,

speaking and lecture fees, and travel reimbursement. Dana Horakova reports a relationship

with Teva that includes: consulting or advisory, speaking and lecture fees, and travel

reimbursement. Jiri Motyl reports a relationship with Sanofi Genzyme that includes:

speaking and lecture fees and travel reimbursement. Jiri Motyl reports a relationship with

Biogen that includes: speaking and lecture fees and travel reimbursement. Jiri Motyl

reports a relationship with Novartis that includes: speaking and lecture fees and travel

reimbursement. Jiri Motyl reports a relationship with Merck that includes: speaking and

lecture fees and travel reimbursement.

544   Acknowledgements

This study was funded by a personal industrial PhD grant (Baekeland, HBC.2019.2579)

appointed by Flanders Innovation and Entrepreneurship to Stijn Denissen, a personal travel

grant (V412023N) appointed by the "Fonds Wetenschappelijk Onderzoek" (FWO) to Stijn

Denissen for his stay in Prague in the context of this study, a grant (SRP85) from the Vrije

Universiteit Brussel and a junior post-doctoral grant (12A6U25N) from the FWO Flanders.

This project was furthermore funded by an IOF-POC grant (IOFPOC57) from the Vrije

Universiteit Brussel (VUB), by an ITEA grant (20030 HeKDisco, HBC.2021.0500) from

Flanders Innovation and Entrepreneurship, by an institutional support from the Czech

Ministry of Health (RVO-VFN 64165) and by the National Institute for Neurological

Research, Czech Republic, Programme EXCELES, ID Project No. LX22NPO5107, funded by

the European Union – Next Generation EU. Guy Nagels is a senior clinical research fellow of

the FWO Flanders (1805620N).

We would like to thank Jelle Laton and Robert Malinowski for their help in the setup and

maintenance of the hardware present in the federated learning network. We also thank

André Vital Serafim Silva for the insights in centralised brain age modelling generated in his

master thesis. The following tools were used for figure creation: the Mac desktop version of

draw.io (https://www.draw.io/), adapted icons from JGraph (https://github.com/jgraph,

licensed under CC BY 4.0 (https://creativecommons.org/licenses/by/4.0/)), flag icons from

flagcolorcodes (https://www.flagcolorcodes.com/) and the Python package GADM v0.0.3

(54).

References

1. Hirano R, Asai M, Nakasato N, Kanno A, Uda T, Tsuyuguchi N, et al. Deep learning based automatic detection and dipole estimation of epileptic discharges in MEG: a multi-center study. Sci Rep. 2024 Oct 19;14(1):24574.

2. Joo Y, Namgung E, Jeong H, Kang I, Kim J, Oh S, et al. Brain age prediction using combined deep convolutional neural network and multi-layer perceptron algorithms. Sci Rep. 2023 Dec 16;13(1):22388.

3. LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015 May;521(7553):436–44.

4. Ranjbarzadeh R, Bagherian Kasgari A, Jafarzadeh Ghoushchi S, Anari S, Naseri M, Bendechache M. Brain tumor segmentation based on deep learning and an attention mechanism using MRI multi-modalities brain images. Sci Rep. 2021 May 25;11(1):10930.

5. Simarro J, Meyer MI, Van Eyndhoven S, Phan TV, Billiet T, Sima DM, et al. A deep learning model for brain segmentation across pediatric and adult populations. Sci Rep. 2024 May 22;14(1):11735.

6. Tanveer M, Ganaie MA, Beheshti I, Goel T, Ahmad N, Lai KT, et al. Deep Learning for Brain Age Estimation: A Systematic Review. Information Fusion. 2023 Aug;96:130–43.

7. Sudlow C, Gallacher J, Allen N, Beral V, Burton P, Danesh J, et al. UK biobank: an open access resource for identifying the causes of a wide range of complex diseases of middle and old age. PLoS Med. 2015 Mar;12(3):e1001779.

8. Markiewicz CJ, Gorgolewski KJ, Feingold F, Blair R, Halchenko YO, Miller E, et al. The OpenNeuro resource for sharing of neuroscience data. Elife. 2021 Oct 18;10:e71774.

9. van Panhuis WG, Paul P, Emerson C, Grefenstette J, Wilder R, Herbst AJ, et al. A systematic review of barriers to data sharing in public health. BMC Public Health. 2014 Nov 5;14(1):1144.

10. McMahan B, Moore E, Ramage D, Hampson S, Arcas BA y. Communication-Efficient Learning of Deep Networks from Decentralized Data. In: Proceedings of the 20th International Conference on Artificial Intelligence and Statistics [Internet]. PMLR; 2017 [cited 2023 Jul 4]. p. 1273–82. Available from: https://proceedings.mlr.press/v54/mcmahan17a.html

11. Li T, Sahu AK, Zaheer M, Sanjabi M, Talwalkar A, Smith V. Federated Optimization in Heterogeneous Networks [Internet]. arXiv; 2020 [cited 2025 Feb 7]. Available from: http://arxiv.org/abs/1812.06127

12. Basodi S, Raja R, Ray B, Gazula H, Sarwate AD, Plis S, et al. Decentralized Brain Age
Estimation Using MRI Data. Neuroinform. 2022 Oct 1;20(4):981–90.

13. Beutel DJ, Topal T, Mathur A, Qiu X, Fernandez-Marques J, Gao Y, et al. Flower: A
Friendly Federated Learning Research Framework [Internet]. arXiv; 2022 [cited 2023 Jul
3]. Available from: http://arxiv.org/abs/2007.14390

14. Lee EH, Han M, Wright J, Kuwabara M, Mevorach J, Fu G, et al. An international study
presenting a federated learning AI platform for pediatric brain tumors. Nat Commun.
2024 Sep 2;15(1):7615.

15. Pati S, Baid U, Edwards B, Sheller M, Wang SH, Reina GA, et al. Federated learning
enables big data for rare cancer boundary detection. Nat Commun. 2022 Dec
5;13(1):7346.

16. Gorgolewski KJ, Auer T, Calhoun VD, Craddock RC, Das S, Duff EP, et al. The brain
imaging data structure, a format for organizing and describing outputs of neuroimaging
experiments. Scientific data. 2016;3(1):1–9.

17. Poldrack RA, Markiewicz CJ, Appelhoff S, Ashar YK, Auer T, Baillet S, et al. The past,
present, and future of the brain imaging data structure (BIDS). Imaging Neuroscience.
2024 Mar 8;2:1–19.

18. Paszke A, Gross S, Massa F, Lerer A, Bradbury J, Chanan G, et al. PyTorch: An Imperative
Style, High-Performance Deep Learning Library [Internet]. arXiv; 2019 [cited 2023 Jul 3].
Available from: http://arxiv.org/abs/1912.01703

19. team T pandas development. pandas-dev/pandas: Pandas [Internet]. Zenodo; 2024
[cited 2025 Feb 7]. Available from: https://zenodo.org/records/13819579

20. Cardoso MJ, Li W, Brown R, Ma N, Kerfoot E, Wang Y, et al. MONAI: An open-source
framework for deep learning in healthcare [Internet]. arXiv; 2022 [cited 2025 Feb 7].
Available from: http://arxiv.org/abs/2211.02701

21. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn:
Machine Learning in Python. Journal of Machine Learning Research. 2011;12:2825–30.

22. Casper da Costa-Luis, Stephen Karl Larroque, Kyle Altendorf, Hadrien Mary,
richardsheridan, Mikhail Korobov, et al. tqdm: A fast, Extensible Progress Bar for Python
and CLI [Internet]. Zenodo; 2024 [cited 2025 Feb 7]. Available from:
https://zenodo.org/doi/10.5281/zenodo.595120

23. Brett M, Markiewicz CJ, Hanke M, Côté MA, Cipollini B, Papadopoulos Orfanos D, et al.
nipy/nibabel: 5.3.1 [Internet]. Zenodo; 2024 [cited 2025 Feb 7]. Available from:
https://zenodo.org/records/13936989

24. Zadka M. Paramiko. In 2019. p. 111–9.

25. scp: scp module for paramiko [Internet]. [cited 2025 Feb 7]. Available from:
https://github.com/jbardin/scp.py

26. Hunter JD. Matplotlib: A 2D graphics environment. Computing in Science &
Engineering. 2007;9(3):90–5.

27. Virtanen P, Gommers R, Oliphant TE, Haberland M, Reddy T, Cournapeau D, et al. SciPy
1.0: Fundamental Algorithms for Scientific Computing in Python. Nature Methods.
2020;17:261–72.

28. Harris CR, Millman KJ, Walt SJ van der, Gommers R, Virtanen P, Cournapeau D, et al.
Array programming with NumPy. Nature. 2020 Sep;585(7825):357–62.

29. click: Composable command line interface toolkit.

30. twine: Collection of utilities for publishing packages on PyPI [Internet]. [cited 2025 Feb
7]. Available from: https://twine.readthedocs.io/

31. Huang G, Liu Z, van der Maaten L, Weinberger KQ. Densely Connected Convolutional
Networks [Internet]. arXiv; 2018 [cited 2023 Jul 3]. Available from:
http://arxiv.org/abs/1608.06993

32. Wood DA, Kafiabadi S, Busaidi AA, Guilhem E, Montvila A, Lynch J, et al. Accurate brain-
age models for routine clinical MRI examinations. Neuroimage. 2022 Apr 1;249:118871.

33. Shafto MA, Tyler LK, Dixon M, Taylor JR, Rowe JB, Cusack R, et al. The Cambridge Centre
for Ageing and Neuroscience (Cam-CAN) study protocol: a cross-sectional, lifespan,
multidisciplinary examination of healthy cognitive ageing. BMC Neurol. 2014 Oct
14;14:204.

34. IXI Dataset – Brain Development [Internet]. [cited 2025 Feb 21]. Available from:
https://brain-development.org/ixi-dataset/

35. Wei D, Zhuang K, Ai L, Chen Q, Yang W, Liu W, et al. Structural and functional brain
scans from the cross-sectional Southwest University adult lifespan dataset. Sci Data.
2018 Jul 17;5(1):180134.

36. Kurtzke JF. Rating neurologic impairment in multiple sclerosis: an expanded disability
status scale (EDSS). Neurology. 1983 Nov;33(11):1444–52.

37. Benedict RH, DeLuca J, Phillips G, LaRocca N, Hudson LD, Rudick R. Validity of the
Symbol Digit Modalities Test as a cognition performance outcome measure for multiple
sclerosis. Mult Scler. 2017 Apr;23(5):721–33.

38. Zhong Z, Zheng M, Mai H, Zhao J, Liu X. Cancer image classification based on DenseNet
model. J Phys: Conf Ser. 2020 Nov 1;1651(1):012143.

39. Lou Y, Zhao L, Yu S, Sun B, Hou Z, Zhang Z, et al. Brain asymmetry differences between
Chinese and Caucasian populations: a surface-based morphometric comparison
study. Brain Imaging Behav. 2020 Dec;14(6):2323–32.

40. Tang Y, Zhao L, Lou Y, Shi Y, Fang R, Lin X, et al. Brain structure differences between
Chinese and Caucasian cohorts: A comprehensive morphometry study. Hum Brain
Mapp. 2018 May;39(5):2147–55.

41. Qi T, Wu F, Lyu L, Huang Y, Xie X. FedSampling: A Better Sampling Strategy for Federated
Learning [Internet]. arXiv; 2023 [cited 2025 Mar 21]. Available from:
http://arxiv.org/abs/2306.14245

42. Peng H, Gong W, Beckmann CF, Vedaldi A, Smith SM. Accurate brain age prediction
with lightweight deep neural networks. Medical Image Analysis. 2021 Feb 1;68:101871.

43. Li T, Sanjabi M, Beirami A, Smith V. Fair Resource Allocation in Federated Learning
[Internet]. arXiv; 2020 [cited 2025 Aug 22]. Available from:
http://arxiv.org/abs/1905.10497

44. Iyer VN. A review on different techniques used to combat the non-IID and
heterogeneous nature of data in FL [Internet]. arXiv; 2024 [cited 2025 Aug 22]. Available
from: http://arxiv.org/abs/2401.00809

45. Yoo JH, Jeong H, Lee J, Chung TM. Open problems in medical federated learning.
International Journal of Web Information Systems. 2022 Sep 20;18(2/3):77–99.

46. Dinsdale NK, Jenkinson M, Namburete AIL. Deep learning-based unlearning of dataset
bias for MRI harmonisation and confound removal. NeuroImage. 2021 Mar
1;228:117689.

47. Matthews KRW, Yang E, Lewis SW, Vaidyanathan BR, Gorman M. International scientific
collaborative activities and barriers to them in eight societies. Accountability in
Research. 2020 Nov 16;27(8):477–95.

48. Vo VTT, Shin T ho, Yang HJ, Kang SR, Kim SH. A comparison between centralized and
asynchronous federated learning approaches for survival outcome prediction using
clinical and PET data from non-small cell lung cancer patients. Computer Methods and
Programs in Biomedicine. 2024 May 1;248:108104.

49. Borazjani K, Khosravan N, Ying L, Hosseinalipour S. Multi-Modal Federated Learning for
Cancer Staging Over Non-IID Datasets With Unbalanced Modalities. IEEE Transactions
on Medical Imaging. 2025 Jan;44(1):556–73.

50. Wen J, Zhang Z, Lan Y, Cui Z, Cai J, Zhang W. A survey on federated learning: challenges
and applications. Int J Mach Learn & Cyber. 2023 Feb 1;14(2):513–35.

51. Foley P, Sheller MJ, Edwards B, Pati S, Riviera W, Sharma M, et al. OpenFL: the open
federated learning library. Phys Med Biol. 2022 Oct 19;67(21):214001.

52. Plis SM, Sarwate AD, Wood D, Dieringer C, Landis D, Reed C, et al. COINSTAC: A Privacy
Enabled Model and Prototype for Leveraging and Processing Decentralized Brain
Imaging Data. Front Neurosci. 2016;10:365.

53. FLightcase GitHub [Internet]. 2025 [cited 2025 Jan 23]. Available from:
https://github.com/AIMS-VUB/FLightcase

54. gadm: package to get boundaries data from GADM, the database of global
Administrative Areas. [Internet]. [cited 2025 Feb 7]. Available from:
https://github.com/xmba15/gadm