DATABASES

A Compressed Large Language Model Embedding Dataset of ICD 10 CM Descriptions

Michael J. Kane[1*], Denise Esserman[1], Nancy K. Latham[2], Erich J. Greene[1] and David A. Ganz[3]

*Correspondence:
michael.kane@yale.edu
[1]Department of Biostatistics,
School of Public Health, Yale
University, New Haven, USA
Full list of author information is
available at the end of the article

Abstract

This paper presents novel datasets providing numerical representations of ICD-10-CM codes by generating description embeddings using a large language model and applying autoencoders for dimensionality reduction. The embeddings serve as informative input features for machine learning models by capturing relationships among categories and preserving inherent information. The model generating the data was validated in two ways. Firstly, the dimension reduction was validated using an autoencoder, and secondly, a supervised model was created to estimate the ICD-10-CM hierarchical categories. Results show that the dimension of the data can be reduced to as few as 10 dimensions while maintaining the ability to reproduce the original embeddings, with the fidelity decreasing as the reduced-dimension representation decreases. Multiple compression levels are provided, allowing users to choose as per their requirements. The readily available datasets of ICD-10-CM codes are anticipated to be highly valuable for researchers in biomedical informatics, enabling more advanced analyses in the field. This approach has the potential to significantly improve the utility of ICD-10-CM codes in the biomedical domain.

Keywords: large language model; autoencoder; ICD-10-CM; electronic health records; EHR; NLP

Background

The International Classification of Diseases, 10th Revision, Clinical Modification (ICD-10-CM) [1] is a standardized classification system for categorizing diseases, disorders, and health conditions. ICD-10 was developed by the World Health Organization (WHO) and adapted for use in the United States as ICD-10-CM by the National Center for Health Statistics (NCHS) [2]. The standard plays a crucial role in the analysis of electronic medical records (EMRs) or electronic health records (EHRs) for several reasons:

1 Consistency and Standardization: The ICD-10-CM allows for a consistent and standardized method of coding and documenting medical conditions across healthcare providers and facilities. This helps to ensure accurate and uniform data exchange, analysis, and comparison.

2 Data Analysis and Research: The ICD-10-CM codes can be used to analyze patient data for clinical research, epidemiological studies, and public health surveillance. It helps to identify trends and patterns in diseases, monitor the effectiveness of treatments, and develop better prevention and management strategies.

3   Quality Measurement and Improvement: ICD-10-CM codes can be used to evaluate the quality of care provided by healthcare facilities, monitor patient outcomes, and identify areas for improvement. This information can be used to enhance the overall healthcare delivery system.

4   Reimbursement and Billing: ICD-10-CM codes play a vital role in healthcare reimbursement by providing a standardized method to classify and report medical conditions. Insurance companies and other payers use these codes to determine appropriate payments for medical services rendered.

5   Health Policy and Planning: ICD-10-CM codes help health authorities and policymakers to identify population health needs, allocate resources, and develop targeted healthcare policies and interventions.

While ICD-10-CM codes do provide a consistent and comprehensive set of categories, their incorporation into statistical and machine learning analyses can be challenging for several reasons. First, in the 2019 version of the standard there are 71,932 categories with that number increasing in the 2022 version to 72,750 categories. As a result, analyses using these codes, where the set of codes is not restricted to smaller set, must take into account their high dimensionality or will require a large number of training samples in order to fit consistent models. Second, categorical variables are usually incorporated into analyses with a contrast encoding such as treatment, one-hot, helmert, etc. Contrast numeric representations are orthogonal or, under appropriate statistical assumptions, independent. However, ICD-10-CM codes represent a hierarchical structure, where codes are organized into chapters, blocks, and categories based on the type and anatomical location of the diseases or conditions. Applying traditional contrast encoding methods (one-hot, treatment, etc.) may not fully capture this hierarchical information, potentially resulting in a loss of valuable context and relationships between codes.

Researchers have considered alternative encoding methods or feature extraction techniques that can better represent the hierarchical structure of ICD-10-CM codes. However, incorporating both hierarchical structure and other contextual information in a general way can be difficult. The previous generation of word embeddings, which provide vector-encodings of words, were shown effective for these types of tasks, with models like `med2vec` [3] providing improved abilities to predict patient mortality; `inpatient2vec` [4] to predict clinical events; and `EHR2Vec` [5] to help analyze sequences of patient visits. Despite their advantages, word embeddings also have certain limitations. First, word embeddings are typically generated at the word or code level, which may not always be sufficient for capturing the hierarchical structure of ICD-10-CM codes. Second, the quality and representativeness of the word embeddings depend on the training data used to generate them. If the training data does not adequately cover the entire spectrum of medical conditions or encounters, the embeddings may not capture all relevant relationships or information. Third, many word embeddings do not account for the specific context in which a word appears. This can limit their ability to capture the nuances of medical conditions and the relationships between them.

Large language models (LLMs) address some of the shortcomings of traditional word embeddings through a combination of advanced techniques and architectures.

Unlike traditional word embeddings that generate static representations, LLMs generate contextualized embeddings. These embeddings take into account the surrounding words or tokens, allowing for a more nuanced representation of words and codes in different contexts. This helps in capturing the semantic relationships between codes more effectively. These models are pre-trained on vast amounts of text data, allowing them to learn general language representations before being fine-tuned for specific tasks. This pre-training enables the models to leverage existing knowledge and adapt more effectively to new tasks, even with limited task-specific data. LLMs can be incrementally updated or fine-tuned with new data, allowing them to adapt to evolving medical knowledge and practices more effectively than static word embeddings. And, while not explicitly designed for hierarchical data like ICD-10-CM codes, LLMs can implicitly learn hierarchical relationships through their deep architectures and the context in which codes appear. This can help capture different levels of granularity and relationships between codes more effectively than traditional word embeddings.

This paper describes data sets provided as `.csv` files, which are available online, ICD-10-CM codes to embeddings (a numeric vector of values), based on their descriptions. The embeddings were generated using the BioGPT LLM [6],which was trained on the biomedical literature including PubMed [7], PubMed Central [8], and clinical notes from MIMIC-III [9]. This model was shown to do a better job of encoding context and relational information than competitors in the medical domain. Since the dimension of the embedding LLM is of high dimension (42,384), we provide dimension-reduced versions in 1,000, 100, 50, and 10 dimensions. The model generating the data were validated in two ways. The first way validates the dimension reduction. The embedding data were compressed using an auto-encoder. The out-of-sample accuracy of a validation set is examined as well as the performance of the model for other versions (by year) of the ICD-10-CM specification. Our results show that we can reduce the dimension of the data down to as few as 10 dimensions while maintaining the ability to reproduce the original embeddings, with the fidelity decreasing as the reduced-dimension representation decreases. The second way validates the conceptual representation by creating a supervised model to estimate the ICD-10-CM hiearchical categories. Again we see as the dimension of the compressed representation decreases the model accuracy decreases. Since multiple compression levels are provided, users are free to choose whichever suits their needs, allowing them to trade off accuracy for dimensionality.

The paper proceeds as follows. The next section provides a high-level description of the BioGPT and the embedding along with the construction of the autoencoder used to reduce the dimension of the embedding representation. That section then provides validation for both the dimension reduction as well as the representation. The third section provides an example of how to use the dataset to cluster ICD-10-CM codes using the R programming environment [10]. The final section provides a broader look at the incorporation of LLM approaches to these types of data.

The data sets and code to generate them are available in a public repository on Github [1]. The data are licensed under the Creative Commons Attribution

---

[1]https://github.com/kaneplusplus/icd-10-cm-embedding

NonCommercial ShareAlike 4.0 International License [2]. The code is licensed under GPL-v2 [3].

Construction and content

The provided data are generated by embedding ICD-10-CM descriptions using the BioGPT-Large model, which comprises 1.5 billion parameters and is accessible via the Hugging Face model repository, [4] and then performing a dimension reduction using an autoencoder. The embedding process involves tokenizing textual phrases into tokens (words, subwords, or characters) and mapping them to unique vocabulary IDs. Token IDs are passed through an embedding layer, resulting in a sequence of continuous embedding vectors. Positional encodings are added element-wise to these vectors, enabling the model to capture token order and relative positions. The embeddings are then contextualized by passing them through the model's layers. An attention mask selectively controls information flow in the attention mechanism, allowing the model to weigh the importance of input tokens when generating contextualized embeddings in a 42,384 dimensional space.

The embedding is then compressed using an autoencoder. The autoencoder used here is a series of fully connected layers where the number of hidden nodes is approximately one order of magnitude smaller than the previous layer and then an order of magnitude larger until the output layer. For example, the autoencoder compressing to 10 dimensions has layers of size 42,384, 1,000, 100, 50, 10, 50, 100, 1,000, 42,384. Models whose dimension is large use the same structure while retaining only the appropriate layers.

Validating the dimension reduction

The autoencoder compressing the LLM embedding was fit on the 2019 ICD-10-CM descriptions for 20 epochs, with batch sizes 64, 128, and 256, mean-square error loss between the embedding and autoencoder estimate, and a validation data set comprised of random subset of 10% of the samples. The model performance is shown in Table 1. Based on these results the models with the best validation loss for each of the compressed embedding dimensions selected for further validation and eventual distribution.

In addition to the 2019 validation the models selected for distribution were tested on the 2020-2022 data sets to ensure their performance is comparable over years. The results are shown in Table 2. It should be noted that the ICD-10-CM codes do not vary much from one year to the the next, so we should not expect large differences. As expected, the mean square error and coefficients of determination are similar to the 2019 data.

Validating the embedding representation

As a final step in the validation process, we use the fact that in addition to the description, the ICD-10-CM codes themselves carry hierarchical information, which can be used to ensure that conceptual relationships are preserved in the compressed

---

[2]https://creativecommons.org/licenses/by-nc-sa/4.0/legalcode
[3]https://www.gnu.org/licenses/old-licenses/gpl-2.0.en.html
[4]https://hugginface.co

embeddings. In particular, the leading letter and two numeric values categorize codes. For example, codes A00-B99 correspond to infectious and parasitic diseases, C00-D49 correspond to neoplasms, etc. We can therefore ensure that at least some of the relevant relationships are preserved in the compressed embedding representation by confirming that the categories can be estimated at a rate higher than chance using a supervised model. Furthermore, we can quantify how much relevant predictive information is lost in lower-dimensional representations.

The training data consists of a one-hot encoding of the ICD-10-CM categories as the dependent variable and the compressed embedding values as the values. The model consists of two hidden layers with 100 nodes each. The loss function selected was categorical cross-entropy. The model was trained using 30 epochs and a validation data set comprised of 10% of samples, chosen at random. The performance in terms of both the accuracy and the balanced accuracy is shown in Table 3. As with most problems of this type, compression of the data corresponds to a decrease predictive information.

Of note, the goal in presenting these results is not to necessarily to maximize the prediction accuracy. Rather, it is to show that the embedding retains the hierarchical information in the ICD-10-CM codes. Some of the codes correspond to conditions that could be classified in several ways, and as a result coding for at least some of the conditions might be considered non-systematic. Based on this criterion, we can conclude the embedding does retain much of the structural and conceptual information denoted in the descriptions, at least in terms of mapping to key categories of diseases and conditions.

Utility and discussion

To illustrate the utility of the data, we present a simple example of how one might use the embedding information in the R programming environment and making use of the `dplyr` [11], `ggplot2` [12], `readr` [13], `Rtsne` [14], and `stringr` [15] packages. Suppose we would like to visualize the ICD-10-CM codes beginning with G (diseases of the nervous system), I (diseases of the circulatory system), J (diseases of the respiratory system), and K (diseases of the digestive system) to better understand the contextual relationships between these categories or specific conditions in the the 50-dimensional embedding. For convenience, the projects page includes an `.rds` file containing the available embeddings along with their URLs, which can be retrieved from the R console. The code categories can then be visualized by performing another dimension reduction (in this case we will use the `Rtsne` package), to 2 dimensions that can be presented as a scatter plot.

```
library(dplyr)
library(ggplot2)
library(readr)
library(Rtsne)
library(stringr)

# Download the locations of the embeddings.
dl = readRDS(
  paste0("https://github.com/kaneplusplus/",
```

```
                "icd-10-cm-embedding/blob/main/icd10_dl.rds")
   )

 # Read in the specified injury codes.
icd10s = dl$url[dl$year == 2019 & dl$emb_dim == 50] |>
   read_csv()|>
   filter(str_detect(code, "^(G|I|J|K)")) |>
   mutate(desc = tolower(desc)) |>
   filter(str_detect(desc, "^unspecified")) |>
   mutate('Leading Letter' = str_sub(code, 1, 1)) |>
   distinct(pick(starts_with("V")), .keep_all = TRUE)

# Fit tSNE to the embedding.
tsne_fit = icd10s |>
   select(starts_with("V")) |>
   scale() |>
   Rtsne(perplexity = 10)

# Bind the tSNE values to the data set.
icd10p = bind_cols(
   icd10s |>
   select(-starts_with("V")),
   tsne_fit$Y |>
     as.data.frame() |>
     rename(tSNE1="V1", tSNE2="V2") |>
     as_tibble()
)

# Visualize the results.
ggplot(icd10p, aes(x = tSNE1, y = tSNE2, color = 'Leading Letter')) +
   geom_point() +
   theme_minimal()
```

The output visualization is presented in Figure 1 and shows that a subset of the circulatory diseases (I) and nervous system diseases (G) are well-differentiated from other conditions. It also shows overlap between other conditions related to K (digestive diseases), J (respiratory diseases), and I (circulatory).

Conclusions

This paper presents novel datasets offering numerical representations of ICD-10-CM codes by generating description embeddings using a large language model and applying autoencoders for dimensionality reduction. The approach is versatile, capable of handling categorical variables with numerous categories across various domains. By capturing relationships among categories and preserving inherent information, the embeddings serve as informative input features for machine learning models. The readily available datasets are anticipated to be highly valuable for researchers incorporating ICD-10-CM codes into their analyses, retaining contextual information.

This approach has the potential to significantly improve the utility of ICD-10-CM codes in biomedical informatics and enable more advanced analyses in the field.

Funding

This work was supported by the National Institute on Aging of the National Institutes of Health (NIH) through a grant to Yale University (1R01AG071528). The organizations funding this study had no role in the design or conduct of the study; in the collection, management, analysis, or interpretation of the data; or in the preparation, review, or approval of the manuscript. The content of this publication is solely the responsibility of the authors and does not necessarily represent the official views of the National Institutes of Health, the Department of Veterans Affairs, or the United States government.

This work was also partially supported by the Yale Clinical and Translational Science award (UL1 TR001863) and the Yale Claude D. Pepper Center (P30AG021342).

Availability of data and materials

All data and code presented here along with documentation for reproducing presented materials is available at https://github.com/kaneplusplus/icd-10-cm-embedding.

Competing interests

The authors declare that they have no competing interests.

Author details

[1]Department of Biostatistics, School of Public Health, Yale University, New Haven, USA. [2]Research Program in Men's Health: Aging and Metabolism, Boston Claude D. Pepper Older Americans Independence Center for Function Promoting Therapies Brigham and Women's Hospital, Boston, USA. [3]Department of Medicine VA Greater Los Angeles/UCLA, Los Angeles, USA.

References

1. DiSantostefano, J.: International classification of diseases 10th revision (icd-10). The Journal for Nurse Practitioners **5**(1), 56–57 (2009)
2. The Center for Disease Control and Prevention (CDC): ICD-10-CM. Accessed: 2023-04-15. https://www.cdc.gov/nchs/icd/icd-10-cm.htm
3. Choi, E., Bahadori, M.T., Searles, E., Coffey, C., Thompson, M., Bost, J., Tejedor-Sojo, J., Sun, J.: Multi-layer representation learning for medical concepts. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 1495–1504 (2016)
4. Wang, Y., Xu, X., Jin, T., Li, X., Xie, G., Wang, J.: Inpatient2vec: Medical representation learning for inpatients. In: 2019 IEEE International Conference on Bioinformatics and Biomedicine (BIBM), pp. 1113–1117 (2019). IEEE
5. Wang, L., Wang, Q., Bai, H., Liu, C., Liu, W., Zhang, Y., Jiang, L., Xu, H., Wang, K., Zhou, Y.: Ehr2vec: representation learning of medical concepts from temporal patterns of clinical notes based on self-attention mechanism. Frontiers in Genetics **11**, 630 (2020)
6. Luo, R., Sun, L., Xia, Y., Qin, T., Zhang, S., Poon, H., Liu, T.-Y.: Biogpt: generative pre-trained transformer for biomedical text generation and mining. Briefings in Bioinformatics **23**(6) (2022)
7. White, J.: Pubmed 2.0. Medical reference services quarterly **39**(4), 382–387 (2020)
8. Roberts, R.J.: Pubmed central: The genbank of the published literature. Proceedings of the National Academy of Sciences **98**(2), 381–382 (2001)
9. Johnson, A.E., Pollard, T.J., Shen, L., Lehman, L.-w.H., Feng, M., Ghassemi, M., Moody, B., Szolovits, P., Anthony Celi, L., Mark, R.G.: Mimic-iii, a freely accessible critical care database. Scientific data **3**(1), 1–9 (2016)
10. R Core Team: R: A Language and Environment for Statistical Computing. R Foundation for Statistical Computing, Vienna, Austria (2023). R Foundation for Statistical Computing. https://www.R-project.org/
11. Wickham, H., François, R., Henry, L., Müller, K., Vaughan, D.: Dplyr: A Grammar of Data Manipulation. (2023). R package version 1.1.1. https://CRAN.R-project.org/package=dplyr
12. Wickham, H.: Ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag, New York (2016). https://ggplot2.tidyverse.org
13. Wickham, H., Hester, J., Bryan, J.: Readr: Read Rectangular Text Data. (2023). R package version 2.1.4. https://CRAN.R-project.org/package=readr
14. Krijthe, J.H.: Rtsne: T-Distributed Stochastic Neighbor Embedding Using Barnes-Hut Implementation. (2015). R package version 0.16. https://github.com/jkrijthe/Rtsne
15. Wickham, H.: Stringr: Simple, Consistent Wrappers for Common String Operations. (2023). https://stringr.tidyverse.org, https://github.com/tidyverse/stringr

Figures

Figure 1 The tSNE plot of the codes.

Tables

Table 1 The autoencoder parameters and performance ordered by increasing validation loss.

Embedding Dimension	Batch Size	Training Loss	Validation Loss
100	64	0.534	0.339
100	128	0.487	0.381
50	256	0.403	0.392
1000	64	0.542	0.402
100	256	0.556	0.444
1000	128	1.073	0.486
10	256	0.599	0.594
10	128	0.628	0.609
10	64	0.679	0.641
50	64	1.134	0.699
1000	256	30.435	0.803
50	128	1.053	0.894

Table 2 The autoencoder validation performance ordered by year.

Year of Published ICD-10-CM Code	Embedding Dimension	Mean Square Error	Coef. of Determination
2019	10	0.593	0.086
2019	50	0.388	0.056
2019	100	0.336	0.049
2019	1000	0.400	0.058
2020	10	0.593	0.086
2020	50	0.388	0.056
2020	100	0.336	0.049
2020	1000	0.400	0.058
2021	10	0.594	0.086
2021	50	0.389	0.056
2021	100	0.337	0.049
2021	1000	0.401	0.058
2022	10	0.595	0.086
2022	50	0.390	0.056
2022	100	0.338	0.049
2022	1000	0.402	0.058

Table 3 The supervised models' performance ordered by increasing embedding dimension.

Embedding Dimension	Accuracy	Balanced Accuracy
10	0.815	0.698
50	0.925	0.873
100	0.935	0.891
1000	0.960	0.927