CONORM: Context-Aware Entity Normalization for Adverse Drug Event Detection

Anthony Yazdani[1,*], Hossein Rouhizadeh[1], Alban Bornet[1], and Douglas Teodoro[1]

[1]Department of Radiology and Medical Informatics, University of Geneva, Geneva, Switzerland

[*]Corresponding author: anthony.yazdani@unige.ch

Keywords: Adverse Drug Events, Named Entity Recognition, Entity Normalization, Entity Resolution, Large Language Models

Abstract

Adverse drug events (ADEs) are a critical aspect of patient safety and pharmacovigilance, with significant implications for patient outcomes and public health monitoring. The increasing availability of electronic health records, social media, and online patient forums provides valuable yet challenging unstructured data sources for ADE surveillance. To address these challenges, we introduce CONORM, a novel framework that integrates named entity recognition (NER) and entity normalization (EN) for ADE extraction across diverse textual domains. CONORM comprises two components: CONORM-NER, a subword-aware, transformer-based model for ADE detection, and CONORM-EN, an entity normalization module using dual-encoder embeddings and dynamic context refining. CONORM was evaluated on SMM4H 2023 (tweets), CADEC (forum posts), and TAC (product labels), where it consistently outperformed existing methods. It achieved end-to-end F1-scores of 63.86% on SMM4H, 72.45% on CADEC, and 84.99% on TAC, surpassing existing solutions by an average margin of 35%. The results demonstrate CONORM's adaptability across informal, semi-formal, and formal text sources. Stratified analyses showed stronger results for well-represented system organ classes (SOCs) and moderate-to-long contexts. CONORM offers a scalable and reproducible solution for real-world pharmacovigilance, with pre-computed target embeddings enhancing inference efficiency for large medical ontologies. Its generalization capabilities across diverse text domains establish it as a robust tool for ADE surveillance. To support reproducibility, all source code is publicly available at https://github.com/ds4dh/CONORM. Future work will explore multilingual capabilities, rare SOC data augmentation, and optimizations for long-form narratives.

Introduction

Adverse drug events (ADEs) are unintended injuries resulting from medication use, whether appropriate or inappropriate, and they represent a substantial portion of adverse events in healthcare[1,2]. ADEs pose a significant public health issue, leading to considerable morbidity and hospitalization[3]. They are among the leading causes of hospital-related complications in developed countries, and their impact is expected to increase due to aging populations and rising medication use[4–6]. The economic burden of ADEs is substantial, since it involves increased healthcare utilization, prolonged hospital stays, and lost productivity[7]. For example, in the United Kingdom, ADEs cost the national health service approximately £99 million per year and account for over 181,000 bed-days and more than 1,700 deaths annually[8]. In the United States, estimates from the 1990s placed the costs of serious ADEs between $30 billion and $137 billion annually[9], amounts that have more than doubled since then[10]. These statistics highlight the need for effective pharmacovigilance strategies to identify ADEs to support drug-related morbidity and mortality prevention.

Named entity recognition (NER) and entity normalization (EN) are important natural language processing techniques in pharmacovigilance and play a significant role in ADE information extraction. NER involves

identifying entities such as drug names, symptoms, and conditions within unstructured text, which is necessary for extracting potential ADE mentions from vast data sources like electronic health records (EHRs) and social media platforms [11–13]. EN focuses on standardizing these identified entities to controlled vocabulary terms, such as those in medical ontologies, like the Medical Dictionary for Regulatory Activities (MedDRA) (https://www.meddra.org/). This normalization ensures that diverse expressions of the same ADE are uniformly represented to facilitate accurate aggregation and analysis, as well as semantic interoperability.

Traditional methods for documenting ADEs are limited by under-reporting [14,15]. In contrast, a more comprehensive understanding of ADEs can be achieved by considering diverse data sources, which range from highly informal social media posts to formal clinical narratives [11–13,16,17]. Social media provide real-time, patient-generated insights into ADEs that might otherwise go unreported, while clinical narratives in EHRs offer detailed information from healthcare professionals. However, both types of sources present challenges for ADE detection due to their unstructured nature and variability in language. Social media data is often marked by slang, abbreviations, misspellings, and colloquial expressions [18], whereas clinical narratives rely on specialized medical terminology [19–21]. Despite the progress made in text normalization techniques, the dynamic language of social media and the complexity of medical jargon in clinical texts still require continuous refinement. Hence, there is a need for advanced methods capable of generalizing and accurately extracting and normalizing ADE mentions from unstructured text across varying levels of formality.

In response to these challenges, we introduce CONORM, a context-aware entity normalization framework that provides an end-to-end solution for ADE detection and normalization across various text domains. CONORM integrates a fine-tuned discriminative language model for ADE recognition with dynamic context refining (DCR), a novel mechanism that enhances entity normalization by dynamically balancing isolated and contextual embeddings. The framework leverages transformer-based models to capture linguistic nuances and leverages embedding pre-computation for scalable inference. This approach effectively handles the variability and complexity of language in unstructured text sources, including highly informal social media posts, semi-formal patient forums, and formal clinical narratives. CONORM is designed to overcome key limitations of existing methods: *i)* the inability to generalize across varying text formalities; *ii)* challenges in scaling to large medical ontologies like MedDRA; and *iii)* maintaining state-of-the-art performance. By addressing these challenges, CONORM enhances pharmacovigilance efforts, enabling more accurate detection and normalization of ADE mentions in unstructured texts. Our results demonstrate that CONORM advances the state-of-the-art in ADE extraction and normalization, offering a robust, efficient, and generalizable framework for improving drug safety monitoring.

Early tools in biomedical text processing, such as MetaMap [22], were developed to map biomedical text to concepts in the Unified Medical Language System (UMLS). MetaMap uses linguistic and symbolic processing to identify medical concepts from text. While it has been widely used for biomedical text mining, MetaMap faces significant limitations when dealing with informal language, slang, and large datasets due to its reliance on lexical lookup and rule-based methods. Its performance decreases in unstructured or colloquial text, such as social media posts, and it struggles with scalability issues when processing large volumes of data [23,24]. To overcome some of MetaMap's limitations, researchers developed tools like MedCAT [25], an open-source medical concept annotation toolkit. MedCAT leverages unsupervised machine learning and ontologies like SNOMED-CT and UMLS to annotate medical concepts in unstructured text. It has shown improved performance in extracting concepts from EHRs and supports customization through an annotation interface.

The advent of transformer architectures advanced natural language processing, with models like BERT [26] introducing attention-based contextual embeddings that capture rich bidirectional language patterns. In the biomedical domain, BioBERT [27] extended this approach by pre-training on large-scale biomedical corpora to enhance the model's understanding of complex biomedical language. These models have demonstrated promising results in ADE extraction tasks [28], enabling more accurate identification of medical entities in unstructured text. Researchers have also effectively applied transformer-based models to social media texts. DeepADEMiner [29], for instance, is a multi-step pipeline based on RoBERTa [30] for filtering ADE-related tweets and on BERT-based models for span extraction and normalization. This approach has shown success in handling informal language and extracting ADEs from social media data. Hybrid approaches have also been explored, integrating models like *mcn-en-smm4h* with DeepADEMiner's span extraction to improve normalization of ADE mentions to MedDRA terms [31]. Additionally, the use of text-to-text transformer models

like T5 [32] has been investigated for tweet-based ADE extraction by framing the task as a sequence-to-sequence problem. Kanagasabai *et al.* [33] complemented this approach with cosine similarity-based retrieval using sentence transformers [34] for normalizing ADE spans. Together, these studies highlight the versatility of transformer architectures and pre-trained language models in both extraction and normalization tasks.

Scalability is another critical concern in ADE normalization efforts. To address this issue, Ul Haq *et al.* [35] developed a scalable, production-ready NLP pipeline capable of processing ADEs from vast amounts of unstructured text, including social media data. Their approach combines a state-of-the-art NER model for ADE extraction with two relation extraction models, one of which is based on BioBERT. Their pipeline, implemented in Apache Spark [36], emphasizes scalability and enables the processing of large datasets. To improve computational efficiency, the JNRF model [37] was proposed as an end-to-end solution for ADE NER and relation extraction in variable-length documents. JNRF is based on weight-shared Fourier networks for low-complexity token mixing, which reduces computational costs and memory consumption. While it demonstrates faster training times and reduced resource usage, JNRF primarily addresses clinical text and may face limitations when applied to informal or highly variable text sources like social media.

Traditional NER systems are often restricted to predefined entity types, limiting their flexibility and pre-training potential. GLiNER [38] addresses this limitation by using a bidirectional transformer encoder to extract arbitrary entity types. By matching entity embeddings with textual spans in a shared latent space, GLiNER enables open NER, outperforming large language models like ChatGPT in zero-shot evaluations [38]. However, GLiNER's joint encoding of text and entities can lead to computational overhead, particularly when dealing with large ontologies like MedDRA. To overcome these limitations, GLiNER-bi [39] introduces a bi-encoder architecture that decouples text and entity encodings into separate transformers. This approach allows for the pre-computation of entity embeddings to reduce computational overhead and improve inference efficiency.

To further address the complexities of ADE normalization in informal texts, Remy *et al.* [40] proposed using a general-purpose model initialization via BioLORD and to fine-tune the model with semantic text similarity. This approach leverages both general-domain and domain-specific pre-training to improve ADE normalization in social media contexts. Their approach outperformed models pre-trained exclusively on biomedical corpora. The success of BioLORD-STS, particularly in zero-shot scenarios, highlights the potential of combining diverse pre-training strategies to handle variability and informality in language. Similarly, in our previous work [41], we presented a two-stage pipeline for ADE resolution that ranked first in the Social Media Mining for Health Research and Applications (SMM4H) 2023 shared task 5 [13]. First, we fine-tuned BERTweet [42] for NER to extract ADE mentions from tweets. In a second stage, we combine similarity rankings from multiple general-domain and specialized sentence transformers using a zero-shot normalization approach based on reciprocal-rank fusion [43,44].

Materials and methods

Datasets

In this study, we used three benchmark datasets to evaluate the effectiveness of CONORM, focusing specifically on continuous ADE entities. These datasets were chosen to cover a wide spectrum of text formality and complexity, ensuring a robust assessment of our solution. The datasets included are the Social Media Mining for Health (SMM4H) 2023 shared task 5 [13], the CSIRO Adverse Drug Event Corpus (CADEC) [16], and the Text Analysis Conference (TAC) 2017 dataset [17], each presenting unique challenges and use cases for our model. Evaluation for each dataset is conducted at the preferred term (PT) level, which represents the most granular level of distinct concepts within the MedDRA ontology. System organ classes (SOCs) provide the highest-level groupings of these PTs. To maximize readability, we adopt abbreviated versions of the official SOC names throughout this work. Together, these datasets enable a comprehensive evaluation of ADE extraction and normalization across diverse linguistic, structural, and domain-specific contexts.

SMM4H 2023: The main challenge of the SMM4H 2023 dataset is its informal nature, including slang, misspellings and abbreviations. This dataset is widely used for the normalization of ADEs in English tweets

and serves as a standard benchmark for resolving ADE mentions to their corresponding MedDRA terms. It comprises approximately 18,000 labeled tweets for training and 10,000 for testing. The evaluation metrics assess system performance across all MedDRA PTs and the model's generalization to out-of-distribution ADEs. To ensure robust model evaluation, the test set labels remain undisclosed. Participants submit their predictions through CodaLab[45] for evaluation. For our experiments, we split the official training data into separate training (90%) and validation (10%) sets, using the official validation set as our internal test set. We used the official test tweets to evaluate our model on the undisclosed labels via CodaLab. Detailed statistics for the SMM4H 2023 dataset are presented in Table 1. The average tweet length across the splits is approximately 20 words, with each tweet typically comprising a single sentence. However, the low entity-to-sentence ratio (0.06 in the training set) highlights the sparsity of ADE mentions, posing challenges for entity resolution within noisy and unrelated content. Moreover, the dataset's SOC distribution reveals significant skewness, with a high prevalence of *Psychiatric* and *Nervous system* disorders, whereas categories like *Blood and lymphatic* disorders are absent.

Table 1. Summary statistics of the SMM4H 2023 dataset, including descriptive metrics and the distribution of entities across the top 5 and least 5 system organ classes (SOCs) in the training, validation, and test sets.

Metric	Train	Validation	Test
Total entities	1572	139	87
Average word count	19.67	19.72	19.47
Average sentence count	1.69	1.69	1.70
Average entity-to-sentence ratio	0.06	0.05	0.07
Entities at SOC level			
Top 5 SOCs			
Psychiatric	667	66	39
General	488	47	20
Nervous system	467	41	31
Musculoskeletal	104	10	3
Gastrointestinal	88	8	8
Least 5 SOCs			
Blood and lymphatic	0	0	0
Pregnancy	0	0	0
Product issues	0	1	0
Congenital	1	0	0
Neoplasms	2	0	0

CADEC: The CADEC dataset comprises annotated medical forum posts detailing patient-reported ADEs. These posts, written in colloquial language, often deviate from formal grammar and punctuation. Annotations link ADE mentions to MedDRA PTs. The dataset consists of 1,250 files, which we split into 875 files for training, 187 for validation, and 188 for testing. CADEC's semi-formal text provides a middle ground between the highly informal SMM4H 2023 and the formal TAC datasets, which allows to test our models in a varied linguistic environment. Detailed statistics for CADEC are shown in Table 2. The average word count of posts (99 in the training set) is significantly higher than that of SMM4H 2023, offering richer context for ADE resolution. Additionally, the high entity-to-sentence ratio (e.g., 0.96 in the training set) reflects a dense annotation scheme, emphasizing normalization challenges. The SOC distribution highlights a strong dominance of *Musculoskeletal* and *Nervous system* disorders. In contrast, SOCs such as *Blood and lymphatic* disorders are scarcely represented.

Table 2. Summary statistics of the CADEC dataset, showing descriptive metrics and the distribution of entities across the top 5 and least 5 system organ classes (SOCs) in the training, validation, and test sets.

Metric	Train	Validation	Test
Total entities	4087	718	834
Average word count	99.14	85.09	94.03
Average sentence count	6.28	5.70	5.87
Average entity-to-sentence ratio	0.96	0.88	0.94
Entities at SOC level			
Top 5 SOCs			
Musculoskeletal	1184	199	187
Nervous system	1002	159	195
General	793	164	159
Psychiatric	618	107	124
Gastrointestinal	446	87	93
Least 5 SOCs			
Congenital	0	0	0
Pregnancy	0	0	0
Surgical/medical	0	0	0
Blood and lymphatic	3	0	1
Neoplasms	1	6	0

TAC: The TAC dataset is designed to evaluate information extraction performance from structured product labels (SPLs). In contrast with the informal language of social media posts, this dataset is valuable for assessing the model's performance on medical texts. The training set includes 101 SPLs, and the test set 99 SPLs. We used 90 of the official training SPLs for training and 11 for validation. The structured and formal nature of the TAC dataset provides a stringent test for our model's capability to handle formal medical terminologies and well-structured documents. As shown in Table 3, the average length of SPLs is significantly longer than the other datasets, with word counts exceeding 1,000 per sample. The dense nature of these texts is reflected in the high entity-to-sentence ratio (e.g., 1.73 in the training set), underscoring the need for the model to handle frequent ADE mentions. The SOC distribution is more balanced compared to SMM4H 2023 and CADEC, with categories such as *Gastrointestinal*, *Nervous system*, and *General* disorders predominating. This balance ensures a comprehensive evaluation of the model across diverse clinical contexts. However, rare categories like *Congenital* and *Surgical*-related conditions remain underrepresented, similar to the other datasets.

Table 3. Summary statistics of the TAC dataset, presenting descriptive metrics and the distribution of entities across the top 5 and least 5 system organ classes (SOCs) in the training, validation, and test sets.

Metric	Train	Validation	Test
Total entities	10716	1736	11215
Average word count	1073	1267	1097
Average sentence count	33	40	34
Average entity-to-sentence ratio	1.73	1.88	1.56
Entities at SOC level			
Top 5 SOCs			
Nervous system	1541	166	1610
General	1412	222	1540
Gastrointestinal	1294	256	1480
Vascular	1275	116	1272
Skin/subcutaneous	1063	156	976
Least 5 SOCs			
Surgical/medical	0	0	0
Social circumstances	4	2	4
Congenital	15	0	39
Ear and labyrinth	46	1	40
Pregnancy	57	11	89

CONORM-NER: named entity recognition

NER is a key component of end-to-end entity resolution. In our study, CONORM-NER is responsible for identifying ADEs from text data, which is necessary for accurate normalization, especially when multiple ADE mentions are present in a text. An overview of CONORM-NER is shown in Figure 1A.

We start by splitting raw texts into words and punctuation symbols using regular expressions. These pre-tokenized texts are then processed through the tokenizer of the transformer encoder backbone. We adopt this two-stage tokenization strategy to ensure that our labeling method aligns closely with the annotated dataset. Each text passage is labeled using the BIOX scheme, "B" for the beginning of an ADE mention, "I" for the inside, "O" for the outside, and "X" for continuation sub-words, regardless of their relation to an ADE[41].

Given an input sequence x, CONORM-NER generates a sequence of hidden states:

$$h = \text{encoder}(x). \tag{1}$$

To mitigate overfitting, we apply a 10% dropout layer to these hidden states:

$$h_{drop} = D_{10\%}(h). \tag{2}$$

Sub-words pose a unique challenge during classification. When a word is segmented into multiple sub-words, we distinguish the leading sub-word from the continuation sub-words. Leading sub-words are labeled as "B", "I", or "O", while all continuation sub-words are labeled as "X". The labels of continuation sub-words are deterministic based on the tokenization process. However, these sub-words must be retained during the forward pass for proper contextualization of the input sequence.

To prevent the model from learning to identify continuation sub-words from deep features (a deterministic task), we introduce a dummy variable s. This variable is set to 1 for continuation sub-words and 0 for all other token types. Each token's contextual embedding is then concatenated with its respective dummy variable before being fed into the classification layer:

$$h_{concat} = \text{concatenate}(h_{drop}, s), \tag{3}$$
$$y = \text{classification}(h_{concat}). \tag{4}$$

CONORM-NER employs a two-phase learning strategy. During the first epoch, only the classification layer weights are trained, leaving the pre-trained parameters unchanged. This allows the model to refine the randomly initialized layers before back-propagating errors to the pre-trained weights. From the second epoch onwards, all parameters are available for gradient updates.

CONORM-EN: entity normalization

The challenge of extracting ADEs from textual data goes beyond entity recognition. It is also crucial to map recognized entities to standardized terminologies in medical databases for a unified understanding and further analysis. CONORM-EN, shown in Figure 1B, is our dedicated sub-model for this entity normalization task.

In CONORM-EN, the context is defined as the sentence containing the target entity to normalize. However, for sufficiently short documents that fit within the model's input size, the entire document may be used as context. Our approach uses two transformer tokenizers, one for context and another for isolated entities. This two-tokenizer strategy is integral to CONORM-EN's architecture. One sentence transformer interprets the broader context surrounding the identified entity, while the second focuses solely on the entity itself. We introduce special tokens, $[S]$ for start and $[E]$ for end, to mark the boundaries of target entities within their context. These tokens highlight the target entity, especially in the presence of non-target entities in the context. They are integrated into the context tokenizer's vocabulary and are assigned unique embeddings in the context sentence transformer's embedding matrix.

Consider a text t describing an ADE in context, such as "Experiencing *relentless headaches* after taking XYZ". Using CONORM-NER, an ADE passage p_{ade} is extracted and identified from t, i.e., "relentless headaches". Then, the text t is transformed for CONORM-EN to encapsulate the ADE passage with special tokens, creating a new tagged text c_{ade}, i.e., "Experiencing [S] relentless headaches [E] after taking XYZ". The context tokenizer processes the entire tagged text c_{ade}, while the isolated entity tokenizer only processes the ADE passage p_{ade}:

$$x_{\text{context}} = \text{tokenizer}_{\text{context}}(c_{ade}), \tag{5}$$

$$x_{\text{isolated}} = \text{tokenizer}_{\text{isolated}}(p_{ade}). \tag{6}$$

Dynamic context refining

CONORM-EN constructs a representation of the target entity using dynamic context refining (DCR). Contextual and isolated entity embeddings are integrated in a late fusion stage supported by a simplified attention mechanism with constant $\mathcal{O}(d)$ time and space complexity, where d is the embedding dimensionality. Given a token sequence from a context c_{ade}, i.e., x_{context} and a token sequence from an isolated entity p_{ade}, i.e., x_{isolated}, we compute their respective embedding vectors by averaging the hidden states from two sentence transformers, S_{context} and S_{isolated}, as follows:

$$e_{\text{context}} = \frac{\sum S_{\text{context}}(x_{\text{context}})}{|x_{\text{context}}|}, \tag{7}$$

$$e_{\text{isolated}} = \frac{\sum S_{\text{isolated}}(x_{\text{isolated}})}{|x_{\text{isolated}}|}. \tag{8}$$

DCR then refines e_{isolated} by incorporating insights from e_{context}, as follows:

$$e'_{\text{isolated}} = \lambda \cdot e_{\text{isolated}} + \mu \cdot e_{\text{context}}. \tag{9}$$

Here, λ and μ are weights derived using a softmax function:

$$\lambda = \frac{\exp(a)}{\exp(a) + \exp(b)}, \quad \mu = \frac{\exp(b)}{\exp(a) + \exp(b)}, \tag{10}$$

where $\lambda > 0$, $\mu > 0$, and $\lambda + \mu = 1$. The parameters a and b that influence λ and μ are defined as:

$$a = \frac{e_{\text{isolated}}^T \cdot M_K \cdot M_Q \cdot e_{\text{isolated}}}{\sqrt{d}}, \tag{11}$$

$$b = \frac{e_{\text{context}}^T \cdot M_K \cdot M_Q \cdot e_{\text{isolated}}}{\sqrt{d}}. \tag{12}$$

In CONORM-EN, the context sentence transformer S_{context} and the M matrices (i.e., M_K and M_Q) are trainable parameters, allowing the model to learn and adapt to task-specific patterns. Conversely, the isolated entity sentence transformer S_{isolated} remains frozen with deactivated dropout layers, ensuring consistent operation in inference mode, even during model training. The coefficients λ and μ act as dynamic weighting factors, determining the influence of the respective embeddings. Specifically, λ represents the model's reliance on the isolated entity embedding, capturing static semantic knowledge from the pre-trained transformer, while μ dictates the contribution of the contextual embedding, incorporating task-specific information. The learnable matrices M_K and M_Q facilitate these interactions through a simplified attention mechanism, using the embeddings as values. Together, this architecture enables CONORM-EN to dynamically balance static general knowledge and task-specific contextual information.

Scalable inference

CONORM-EN achieves efficient ADE normalization by pre-computing target embeddings and decoupling the forward pass from the target vocabulary. We pre-compute embeddings for the target vocabulary using S_{isolated}, which eliminates the need for runtime recomputation and significantly reduces computational costs. During inference, CONORM-EN's forward pass focuses solely on input text, operating independently of the vocabulary. This decoupled architecture supports integration with vector databases, enabling efficient retrieval through techniques such as locality-sensitive hashing, random projection, and quantization.

The inference process begins with embedding each ADE mention, i.e., $e'_{\text{isolated},j}$, identified by CONORM-NER. These embeddings are compared to the pre-computed target embeddings $\{m_k\}_{k=1}^K$, where K is the total number of concepts in the vocabulary. The cosine similarity is then used to quantify the alignment between an ADE mention and each target embedding:

$$c(e'_{\text{isolated},j}, m_k) = \frac{e'_{\text{isolated},j} \cdot m_k}{\|e'_{\text{isolated},j}\|_2 \cdot \|m_k\|_2}. \tag{13}$$

Here, $e'_{\text{isolated},j}$ is the embedding of the j-th ADE mention, and m_k is the embedding of the k-th target concept. For each mention, we compute a similarity score vector:

$$\text{scores}_j = \{c(e'_{\text{isolated},j}, \ldots, c(e'_{\text{isolated},j}, m_K)\}. \tag{14}$$

The concept corresponding to the highest similarity score in this vector is selected as the predicted normalization for the ADE mention.

Robust training

To train CONORM-EN, we generate dissimilar pairs through balanced negative sampling. In this context, a positive pair refers to a combination $(e'_{\text{isolated}}, m_k)$ where m_k is the correct concept embedding for the target entity passage p_{ade}. The number of positive pairs is dictated by the annotations available in the training set, which specify the correct mappings for each ADE. Conversely, a negative pair consists of $(e'_{\text{isolated}}, m_k)$ where m_k is not the gold label for p_{ade}. Negative pairs are created using negative sampling, which involves randomly selecting a label from the set of all possible labels that are not explicitly marked as correct. The quality of these negative pairs is uncertain because the sampling process is uniform, meaning that we might

sample a label that is semantically similar to the true label. For example, in MedDRA, "Headache" might be closely related to "Migraine," leading to ambiguity in the negative sampling process.

To address this challenge, we use the cosine embedding loss L, which is less sensitive to noisy negative examples:

$$L = \begin{cases} 1 - \cos(e'_{\text{isolated}}, m_k) & \text{if positive,} \\ \max(0, \cos(e'_{\text{isolated}}, m_k)) & \text{if negative.} \end{cases} \quad (15)$$

For positive pairs, the loss function ensures that the cosine similarity between e'_{isolated} and its corresponding concept embedding m_k approaches 1.0. For negative pairs, the loss function only contributes if the cosine similarity is greater than 0.0, accommodating the potential overlap between true and sampled negative labels. During training, we use balanced negative sampling, ensuring that each mini-batch contains an equal number of positive and negative pairs. This approach facilitates robust model training by balancing the learning of true associations with the challenge of distinguishing potentially semantically ambiguous negatives.

Figure 1. Schematic overview of the CONORM framework: (A) CONORM-NER for named entity recognition and (B) CONORM-EN for entity normalization, illustrating the integration of dynamic context refining (DCR) and dual-encoder architectures.

Experiments

We evaluated the performance of CONORM across three datasets: SMM4H 2023, CADEC, and TAC. The experiments conducted for model evaluation were as follows:

1. **NER model training and evaluation**: We trained and assessed the performance of the CONORM-NER component specifically for ADE extraction on the SMM4H 2023, CADEC, and TAC datasets. For the SMM4H 2023 dataset, we employed *BERTweet*[42] as the model backbone. For the CADEC dataset, we used *mpnet-base*[46], and for the TAC dataset, we used *Clinical-Longformer*[47]. We benchmarked the performance of CONORM-NER against state-of-the-art approaches, including MetaMap, MedCAT, GLiNER, GLiNER-bi, and JNRF.

2. **End-to-end NER and EN model training and evaluation**: We combined CONORM-NER and CONORM-EN models into an end-to-end pipeline for ADE resolution (CONORM). In the EN component, we used different pre-trained sentence transformers to generate embeddings of isolated entities and their contexts. For SMM4H 2023 and CADEC, we used *multi-qa-mpnet*[34] for isolated entity embeddings and *all-mpnet-base*[34] for context embeddings. For the TAC dataset we used *all-mpnet-base-v2* for isolated entities and *multi-qa-mpnet* for context embeddings. The performance was evaluated against MetaMap, MedCAT, and GLiNER-bi.

3. **Evaluation on undisclosed test data**: To ensure robust evaluation, we tested CONORM on undisclosed test data from the SMM4H 2023 dataset using the CodaLab platform. We compared its performance against the top-performing system from the SMM4H 2023 ADE normalization shared task[41], DeepADEMiner[29], and the average and median results of other shared task participants[13].

Results are reported using precision, recall, and F1-score metrics for both exact and lenient matching strategies. Performance comparisons between models were conducted using paired t-tests on per-document lenient F1-scores, with p-values < 0.05 considered statistically significant. This parametric approach is justified by the approximately normal distribution of score differences and the greater sensitivity of t-tests to detect mean differences when parametric assumptions are met. For each dataset, CONORM was systematically compared against the best-performing baseline in both NER and end-to-end NER and EN tasks. Statistical tests could not be performed for the undisclosed test data due to the unavailability of true labels.

Results

The performance of CONORM was evaluated on three datasets — SMM4H 2023, CADEC, and TAC — each presenting varying degrees of language formality. CONORM consistently demonstrates strong performance across these diverse datasets, outperforming other state-of-the-art approaches in terms of F1-score for the end-to-end NER and EN task, with an average F1-score of 73.77% across the three datasets and the highest F1-score (50.20%) in the SMM4H undisclosed test set. Moreover, it achieved the highest average F1-score for both lenient and strict matching NER evaluation strategies (85.75% and 73.17%, respectively).

Named entity recognition

Table 4 presents the NER performance of CONORM compared to state-of-the-art zero-shot (ZS) and fine-tuned (FT) systems across the SMM4H 2023, CADEC, and TAC datasets, including MetaMap, MedCAT, GLiNER-L, GLiNER-bi-L, and JNRF. On the SMM4H 2023 dataset, CONORM achieves lenient and exact F1-scores of 78.31% and 62.65%, respectively, significantly outperforming GLiNER-L (FT), which achieves F1-scores of 54.40% and 49.60% (p-value < 0.001). For the CADEC dataset, CONORM demonstrates its adaptability to semi-formal text with the highest lenient F1-score of 89.10% and an exact F1-score of 70.40%, showing a significant improvement over GLiNER-L (FT), which achieves 85.08% and 74.43% (p-value = 0.001). On the TAC dataset, which features formal medical documents, CONORM reaches lenient and exact F1-scores of 89.85% and 86.45%, performing competitively with GLiNER-L (FT), which achieves 90.24% and 87.99%, with no statistically significant difference observed (p-value > 0.05). Macro-averaged across all datasets, CONORM achieves the highest lenient and exact F1-scores among ZS and FT models, demonstrating superior generalization across diverse linguistic contexts compared to state-of-the-art methods.

Table 4. Performance comparison of CONORM and state-of-the-art systems on named entity recognition (NER) tasks across the SMM4H 2023, CADEC, and TAC datasets, evaluated using lenient and exact precision, recall, and F1-score metrics.

Dataset	Model	Type	Lenient			Exact		
			Prec.	Rec.	F1	Prec.	Rec.	F1
SMM4H	MetaMap	ZS	7.14	37.93	12.02	5.84	31.03	9.84
	MedCAT	ZS	15.46	17.24	16.30	15.46	17.24	16.30
	GLiNER-L	ZS	17.89	25.29	20.95	7.44	10.34	8.65
	GLiNER-bi-L	ZS	4.88	2.30	3.12	2.44	1.15	1.56
	GLiNER-L	FT	89.47	39.08	54.40	81.58	35.63	49.60
	GLiNER-bi-L	FT	**90.91**	11.49	20.41	**90.91**	11.49	20.41
	JNRF	FT	26.80	29.89	28.26	11.34	12.64	11.96
	CONORM	FT	82.28	**74.71**	**78.31**	65.82	**59.77**	**62.65**
CADEC	MetaMap	ZS	63.20	79.50	70.42	39.59	50.60	44.42
	MedCAT	ZS	78.74	39.09	52.24	46.49	23.02	30.79
	GLiNER-L	ZS	71.75	30.46	42.76	47.66	19.54	27.72
	GLiNER-bi-L	ZS	55.63	9.47	16.19	39.72	6.71	11.49
	GLiNER-L	FT	**87.17**	83.09	85.08	**76.16**	72.78	**74.43**
	GLiNER-bi-L	FT	85.57	83.21	84.38	72.37	70.98	71.67
	JNRF	FT	75.12	90.53	82.11	52.08	64.51	57.63
	CONORM	FT	84.98	**93.65**	**89.10**	66.67	**74.58**	70.40
TAC	MetaMap	ZS	50.91	81.83	62.77	45.54	72.87	56.05
	MedCAT	ZS	61.96	39.14	47.97	51.98	32.67	40.13
	GLiNER-L	ZS	59.19	41.81	49.01	45.55	31.45	37.21
	GLiNER-bi-L	ZS	59.34	26.16	36.31	49.23	21.22	29.66
	GLiNER-L	FT	88.25	**92.32**	**90.24**	86.09	**89.97**	**87.99**
	GLiNER-bi-L	FT	**89.25**	90.62	89.93	87.35	88.59	87.96
	JNRF	FT	70.46	70.54	70.50	60.28	60.73	60.50
	CONORM	FT	88.53	91.20	89.85	85.09	87.85	86.45
Average	MetaMap	ZS	40.42	66.42	48.40	30.32	51.50	36.77
	MedCAT	ZS	52.05	31.82	38.84	37.98	24.31	29.07
	GLiNER-L	ZS	49.61	32.52	37.57	33.55	20.44	24.53
	GLiNER-bi-L	ZS	39.95	12.64	18.54	30.46	9.69	14.24
	GLiNER-L	FT	88.30	71.50	76.57	81.28	66.13	70.67
	GLiNER-bi-L	FT	**88.58**	61.77	64.91	**83.54**	57.02	60.01
	JNRF	FT	57.46	63.65	60.29	41.23	45.96	43.36
	CONORM	FT	85.26	**86.52**	**85.75**	72.53	**74.07**	**73.17**

End-to-end entity resolution

Table 5 presents the end-to-end NER and EN performance of CONORM compared to state-of-the-art ZS and FT methods across the SMM4H 2023, CADEC, and TAC datasets. In this evaluation, we focus on computationally tractable models for large-scale entity normalization, as in the case of the MedDRA ontology. JNRF, although highly efficient, was excluded from this comparison since it is designed for NER and relation extraction rather than EN. On the SMM4H 2023 dataset, CONORM achieves an F1-score of 63.86%, significantly outperforming GLiNER-bi-L (FT), which achieves 20.63% (p-value < 0.001). This substantial improvement highlights CONORM's ability to effectively process and normalize ADEs in noisy and unstructured text environments. For the CADEC dataset, CONORM attains an F1-score of 72.45%, outperforming MetaMap by 23% (p-value < 0.001). On the TAC dataset, consisting of formal medical documents, CONORM achieves the highest F1-score of 84.99%, with a 28% improvement over MetaMap (p-value < 0.001). When macro-averaged across all datasets, CONORM achieves an F1-score of 73.77%, demonstrating its superior adaptability and performance across diverse text domains compared to

state-of-the-art systems.

Table 5. End-to-end performance comparison of CONORM and state-of-the-art systems on adverse drug event (ADE) detection and normalization tasks across the SMM4H 2023, CADEC, and TAC datasets, evaluated using precision, recall, and F1-score metrics.

Dataset	Model	Type	Prec.	Rec.	F1
SMM4H	MetaMap	ZS	5.19	27.59	8.74
	MedCAT	ZS	13.40	14.94	14.13
	GLiNER-bi-L	ZS	0.18	3.45	0.34
	GLiNER-bi-L	FT	33.33	14.94	20.63
	CONORM	FT	**67.09**	**60.92**	**63.86**
CADEC	MetaMap	ZS	44.17	56.35	49.53
	MedCAT	ZS	58.35	28.90	38.65
	GLiNER-bi-L	ZS	0.66	1.44	0.91
	GLiNER-bi-L	FT	36.59	22.42	27.81
	CONORM	FT	**68.71**	**76.62**	**72.45**
TAC	MetaMap	ZS	46.07	73.72	56.70
	MedCAT	ZS	50.75	31.92	39.19
	GLiNER-bi-L	ZS	0.19	0.35	0.25
	GLiNER-bi-L	FT	46.12	38.93	42.22
	CONORM	FT	**83.66**	**86.37**	**84.99**
Average	MetaMap	ZS	31.81	52.55	38.32
	MedCAT	ZS	40.83	25.25	30.66
	GLiNER-bi-L	ZS	0.34	1.75	0.50
	GLiNER-bi-L	FT	38.68	25.43	30.22
	CONORM	FT	**73.15**	**74.64**	**73.77**

End-to-end entity resolution: undisclosed test data

To further validate the effectiveness of CONORM in real-world settings, we evaluated our model on the undisclosed test set of the SMM4H 2023 dataset using the CodaLab platform. Table 6 presents the comparative performance of CONORM against other leading systems, including the previous top-performing system from the SMM4H 2023 ADE normalization shared task[41] and DeepADEMiner[29]. The table details both the overall and the out-of-distribution performance metrics. CONORM achieved an overall F1-score of 50.20%, which outperforms both the previous top system and DeepADEMiner. Importantly, CONORM achieves the highest precision (53.50%). This means that our model can identify ADEs with fewer false positives as compared to top-performing models. Although DeepADEMiner achieved a slightly higher recall, CONORM's balanced precision and recall led to a superior F1-score (5% improvement). In terms of out-of-distribution performance, which evaluates the model's ability to generalize to ADEs not seen during training, CONORM again outperforms other systems with an F1-score of 39.40% and a precision of 53.10%. These results demonstrate that CONORM achieves state-of-the-art performance for ADE resolution in informal tweet data, particularly in terms of precision and generalization to out-of-distribution cases.

Table 6. Performance comparison of CONORM, DeepADEMiner [29], the top-performing system from the SMM4H 2023 ADE normalization shared task 5 [41], and the mean and median results of shared task participants [13] on the SMM4H 2023 undisclosed test set. Metrics include overall and out-of-distribution precision, recall, and F1-score.

Model	Overall			Out-of-distribution		
	Prec.	Rec.	F1	Prec.	Rec.	F1
Mean	29.30	42.24	32.94	15.08	36.02	20.16
Median	24.90	40.50	32.20	12.80	35.40	19.50
Top system [41]	44.90	40.50	42.60	24.90	35.40	29.20
DeepADEMiner [29]	40.70	**50.80**	45.20	33.50	**39.50**	36.30
CONORM	**53.50**	47.30	**50.20**	**53.10**	31.40	**39.40**

End-to-end entity resolution: performance across SOCs and context lengths

Assessing the performance of ADE detection and normalization models across different medical categories and varying textual contexts is crucial for understanding their practical utility in pharmacovigilance. MedDRA's SOCs encompass diverse medical conditions, each with unique linguistic features and terminological complexities. Similarly, the length of the textual context surrounding an ADE mention can influence a model's ability to accurately recognize and normalize the entity. To explore these factors, we conducted a detailed analysis of CONORM's end-to-end performance, stratifying the results by SOC and context length. The TAC dataset was chosen for this analysis because it provides a wide range of SOCs and context lengths.

As presented in Table 7, CONORM's performance varies across different SOCs. It achieves an F1-score equal to or above 80% on 18 out of 27 categories present in the dataset, including cases above 90%, i.e., *Gastrointestinal* (94.26%) and *Ear and labyrinth* (90.24%) disorders. In contrast, lower F1-scores are observed in SOCs, such as *Social circumstances* (40.00%) and *Congenital* (67.42%) disorders. Regarding context length, the analysis reveals that CONORM's performance generally improves with increasing context length up to a certain point. The highest F1-score (89.98%) is achieved in the context length range of 983 to 1356 words.

Table 7. Stratified performance of CONORM on end-to-end entity resolution for the TAC dataset, evaluated by system organ class (SOC) and context length, with F1-scores and support counts.

System organ class (SOC)	F1	Support
Blood and lymphatic	89.29	667
Cardiac	84.45	745
Congenital	67.42	39
Ear and labyrinth	90.24	40
Endocrine	82.06	233
Eye	82.83	275
Gastrointestinal	94.26	1480
General	87.95	1540
Hepatobiliary	75.91	294
Immune	83.85	748
Infections	85.45	821
Injury/poisoning	79.87	586
Investigations	71.79	945
Metabolism	85.95	633
Musculoskeletal	88.48	489
Neoplasms	74.85	235
Nervous system	82.73	1610
Pregnancy	80.98	89
Psychiatric	81.02	758
Renal/urinary	83.09	262
Reproductive	75.62	97
Respiratory	87.61	808
Skin/subcutaneous	86.56	976
Social circumstances	40.00	4
Surgical/medical	0.00	0
Vascular	86.20	1272
Context length		
(0, 296)	79.82	519
(296, 590)	82.83	938
(590, 983)	83.23	1712
(983, 1356)	89.98	3025
(1356, +)	83.50	4980

Discussion

We introduced CONORM, a context-aware entity normalization framework specifically designed for the detection and normalization of ADEs from unstructured text sources. Leveraging techniques such as the BIOX annotation scheme, subword-aware classification, dynamic context refining (DCR), and a robust sampling loss function, CONORM addresses key challenges in processing informal, semi-formal, and formal text domains. Our comprehensive evaluation across three benchmark datasets—SMM4H 2023, CADEC, and TAC—demonstrated that CONORM consistently achieves superior or competitive performance compared to state-of-the-art methods in both NER and end-to-end ADE resolution tasks. These results position CONORM as a robust and versatile solution for ADE detection and normalization, capable of adapting to diverse textual domains and linguistic complexities.

In the NER task, CONORM exhibited strong performance across all datasets. The difference between lenient and exact F1-scores provides insights into the model's precision in boundary detection. On the informal SMM4H dataset, CONORM achieved a lenient F1-score of 78.31% but a lower exact F1-score of 62.65%. This gap highlights the challenges in identifying ADE boundaries in texts with slang, abbreviations, and misspellings. In contrast, the formal TAC dataset showed a smaller difference between lenient (89.85%)

and exact (86.45%) F1-scores, reflecting the relatively simpler boundary detection in structured medical documents. Compared to rule-based models like MetaMap, CONORM's transformer-based architecture captures contextual information, enabling better generalization to diverse expressions of ADEs. Rule-based systems rely on predefined vocabularies and patterns, making them less adaptable to non-standard expressions and contextual cues.

When comparing our NER results to related work, CONORM demonstrates competitive performance. On the CADEC dataset, CONORM achieved an exact F1-score of 70.40%, slightly lower than the 72.99% reported by Ul Haq *et al.*[35], who used micro-averaged metrics across both drug and ADE entities. However, CONORM focuses solely on continuous ADE mentions, making a direct comparison challenging. CONORM outperformed in lenient F1-score (89.10%) compared to Ul Haq *et al.*'s 86.88%, indicating its strength in maintaining high recall and precision, particularly in semi-formal texts. For the TAC dataset, CONORM achieved an exact F1-score of 86.45%, comparable to the 85.20% reported by UTH CCB[17], which focused on all ADE mentions. Although UTH CCB did not report lenient metrics, CONORM's lenient F1-score (89.85%) underscores its effectiveness in formal text environments.

In the end-to-end entity resolution task, CONORM demonstrated its efficacy in both extracting ADE mentions and accurately normalizing them to MedDRA terms. The model consistently outperformed other systems across all datasets, with particular improvements on the SMM4H 2023 dataset. An F1-score as high as 63.86% in an informal text domain indicates CONORM's robustness to deal with challenging linguistic environments. On the undisclosed test data from SMM4H 2023, CONORM also achieved the highest overall and out-of-distribution F1-scores (50.20% and 39.40%, respectively), outperforming previous top systems. The model's improved precision scores highlight its ability to effectively reduce false positives, which is critical for clinical applications where over-reporting may result in unnecessary interventions.

Comparing our end-to-end results to related work further highlights CONORM's effectiveness. Remy *et al.*[40] focused solely on entity normalization and reported an F1-score of 60.28% on the CADEC dataset using BioLORD-STS. In contrast, CONORM addresses both NER and EN in an end-to-end pipeline and achieves an F1-score of 72.45%. On the TAC dataset, UTH CCB[17] achieved a precision of 84.17%, recall of 89.84%, and F1-score of 86.91% by combining NER and EN; however, their evaluation process only required one correct detection and normalization per unique entity per document to count as a true positive, regardless of how many times that entity appeared. In contrast, we evaluated every occurrence of each entity, making our evaluation stricter. Under this criterion, CONORM achieved a precision of 83.66%, recall of 86.37%, and F1-score of 84.99%.

The stratified analysis by SOC and context length provides insight into CONORM's performance dynamics and highlights important considerations for ADE detection and normalization. The variation in performance across SOCs may be attributed to differences in the complexity of medical terminology, condition specificity, and the linguistic expressions used to describe these categories. CONORM achieves notably high performance for SOCs such as *Gastrointestinal* and *Blood and lymphatic* disorders, suggesting that these more frequently discussed ADE are easier to detect and normalize. Conversely, performance is lower in less common SOCs such as *Social circumstances* and *Congenital* disorders, which may receive less coverage in training data and exhibit more heterogeneous expressions. Examining context length further illuminates the role of surrounding text in boosting or hindering ADE resolution. Our analysis shows that sufficient context helps the model resolve entities more effectively up to a certain point. While Clinical-Longformer is designed for extended contexts, excessively long documents may introduce noise, making it harder for the model to process information accurately. Overall, our stratified evaluation underscores the importance of ensuring adequate training samples for underrepresented SOCs.

Although CONORM has demonstrated high performance across informal, semi-formal, and formal text domains, there are limitations to this work that warrant consideration. First, the SMM4H dataset had relatively few ADE annotations, restricting the diversity of examples available for model training. Nonetheless, the aggregated number of samples across SMM4H, CADEC, and TAC remains robust, supporting a comprehensive evaluation. Second, each model was tailored to its respective dataset to enable fair comparisons with reported baselines, yet a single unified model that simultaneously learns from all three datasets might further improve generalization. We leave this exploration for future research. Finally, as all datasets are in English, any

extension of CONORM to other languages would require additional adaptation and training, underscoring an avenue for broader multilingual applications.

Future work could address these limitations in several ways. First, developing or collecting augmented and synthetic data may alleviate the scarcity of instances in underrepresented SOCs, improving resolution performance. Second, investigating alternative architectures or hierarchical approaches might mitigate performance degradation in very long contexts. Third, extending CONORM to handle multilingual corpora would enhance the framework's relevance for global pharmacovigilance. Additionally, deploying CONORM on streaming social media data could enable near real-time monitoring, making it useful for rapid ADE detection during public health crises or newly released drugs. Finally, improving computational efficiency, such as through model quantization, could facilitate low-latency inference in resource-constrained environments.

Conclusion

In this work, we introduced CONORM, a context-aware entity normalization framework that integrates named entity recognition with dynamic context refining to improve adverse drug event (ADE) detection and normalization. By leveraging transformer-based models and a novel dual-encoder architecture, CONORM effectively addresses the challenges posed by unstructured, variable language in ADE mentions. Comprehensive evaluations on informal tweets, semi-formal patient forums, and formal product labels show that our approach delivers state-of-the-art or competitive performance across different text domains, including robust recognition of ADE boundaries and normalization to MedDRA terms. CONORM's ability to process distinct linguistic styles, together with its scalable inference methodology, makes it a promising choice for large-scale pharmacovigilance. Although our experiments highlight strong general performance, future research could refine the framework for multilingual scenarios, low-resource system organ classes, and extreme document lengths to further broaden its utility. By improving the accuracy of ADE resolution, CONORM can help advance drug safety monitoring, informing public health strategies and clinical decision-making processes aimed at reducing medication-related harm.

Code and data availability

The datasets supporting the results of this article are available as follows: The CADEC[16] dataset can be accessed at https://data.csiro.au/collection/csiro:10948. The TAC[17] dataset is available at https://bionlp.nlm.nih.gov/tac2017adversereactions/. The SMM4H 2023 dataset[13] is available upon request at https://codalab.lisn.upsaclay.fr/competitions/12941participate-get-data. All datasets are provided in their raw formats, and preprocessing scripts to replicate our experiments and prepare the data for the CONORM framework are available at https://github.com/ds4dh/CONORM. The MedDRA files used for entity normalization and data preprocessing can be obtained upon request from https://www.meddra.org/. Specifically, we used MedDRA English version 16.0 for CADEC, version 24.0 for SMM4H 2023, and version 18.1 for TAC, ensuring consistency with the original dataset annotations.

Author contributions

AY and DT contributed to the study's conceptualization. AY, HR, and AB developed the methodology. AY carried out the experiments and wrote the original draft. AB, HR, and DT reviewed and edited the manuscript, with supervision provided by DT.

Competing interests

The authors declare that they have no competing interests.

Acknowledgment

This work was funded by the Innosuisse - project no.: 55441.1 IP ICT.

References

1. Leape LL, Brennan TA, Laird N, Lawthers AG, Localio AR, Barnes BA, et al. The nature of adverse events in hospitalized patients: results of the Harvard Medical Practice Study II. New England journal of medicine. 1991;324(6):377-84.

2. Bates DW, Cullen DJ, Laird N, Petersen LA, Small SD, Servi D, et al. Incidence of adverse drug events and potential adverse drug events: implications for prevention. Jama. 1995;274(1):29-34.

3. Zhou L, Rupa AP. Categorization and association analysis of risk factors for adverse drug events. European Journal of Clinical Pharmacology. 2018;74(4):389-404.

4. Angamo MT, Chalmers L, Curtain CM, Bereznicki LR. Adverse-drug-reaction-related hospitalisations in developed and developing countries: a review of prevalence and contributing factors. Drug safety. 2016;39(9):847-57.

5. Sarkar U, López A, Maselli JH, Gonzales R. Adverse drug events in US adult ambulatory medical care. Health services research. 2011;46(5):1517-33.

6. Crockett AB. Use of prescription drugs: rising or declining? Nursing Clinics. 2005;40(1):33-49.

7. Jatau AI, Shitu Z, Khalid GM, Yunusa I, Awaisu A. Understanding adverse drug-related emergency department visits: development of a conceptual model through a systematic review. Therapeutic advances in drug safety. 2019;10:2042098619852552.

8. Elliott RA, Camacho E, Jankovic D, Sculpher MJ, Faria R. Economic analysis of the prevalence and clinical and economic burden of medication error in England. BMJ Quality & Safety. 2021;30(2):96-105.

9. Johnson J, Booman L. Drug-related morbidity and mortality. Journal of Managed Care Pharmacy. 1996;2(1):39-47.

10. Ernst FR, Grizzle AJ. Drug-related morbidity and mortality: updating the cost-of-illness model. Journal of the American Pharmaceutical Association (1996). 2001;41(2):192-9.

11. Henry S, Buchan K, Filannino M, Stubbs A, Uzuner O. 2018 n2c2 shared task on adverse drug events and medication extraction in electronic health records. Journal of the American Medical Informatics Association. 2020;27(1):3-12.

12. Jagannatha A, Liu F, Liu W, Yu H. Overview of the first natural language processing challenge for extracting medication, indication, and adverse drug events from electronic health record notes (MADE 1.0). Drug safety. 2019;42(1):99-111.

13. Klein AZ, Banda JM, Guo Y, Schmidt AL, Xu D, Flores Amaro I, et al. Overview of the 8th Social Media Mining for Health Applications (# SMM4H) shared tasks at the AMIA 2023 Annual Symposium. Journal of the American Medical Informatics Association. 2024;31(4):991-6.

14. Nadkarni PM. Drug safety surveillance using de-identified EMR and claims data: issues and challenges. Journal of the American Medical Informatics Association. 2010;17(6):671-4.

15. Classen DC, Resar R, Griffin F, Federico F, Frankel T, Kimmel N, et al. 'Global trigger tool'shows that adverse events in hospitals may be ten times greater than previously measured. Health affairs. 2011;30(4):581-9.

16. Karimi S, Metke-Jimenez A, Kemp M, Wang C. Cadec: A corpus of adverse drug event annotations. Journal of biomedical informatics. 2015;55:73-81.

17. Roberts K, Demner-Fushman D, Tonning JM. Overview of the TAC 2017 Adverse Reaction Extraction from Drug Labels Track. In: TAC; 2017. .

18. Zhou L, Zhang D, Yang CC, Wang Y. Harnessing social media for health information management. Electronic commerce research and applications. 2018;27:139-51.

19. Li I, Pan J, Goldwasser J, Verma N, Wong WP, Nuzumlalı MY, et al. Neural natural language processing for unstructured data in electronic health records: a review. Computer Science Review. 2022;46:100511.

20. Weng WH, Chung YA, Szolovits P. Unsupervised clinical language translation. In: Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining; 2019. p. 3121-31.

21. Gu Y, Tinn R, Cheng H, Lucas M, Usuyama N, Liu X, et al. Domain-specific language model pretraining for biomedical natural language processing. ACM Transactions on Computing for Healthcare (HEALTH). 2021;3(1):1-23.

22. Aronson AR, Lang FM. An overview of MetaMap: historical perspective and recent advances. Journal of the American Medical Informatics Association. 2010;17(3):229-36.

23. Tu H, Ma Z, Sun A, Wang X. When MetaMap Meets Social Media in Healthcare: Are the Word Labels Correct? In: Information Retrieval Technology: 12th Asia Information Retrieval Societies Conference, AIRS 2016, Beijing, China, November 30–December 2, 2016, Proceedings 12. Springer; 2016. p. 356-62.

24. Demner-Fushman D, Rogers WJ, Aronson AR. MetaMap Lite: an evaluation of a new Java implementation of MetaMap. Journal of the American Medical Informatics Association. 2017;24(4):841-4.

25. Kraljevic Z, Searle T, Shek A, Roguski L, Noor K, Bean D, et al. Multi-domain clinical natural language processing with MedCAT: The Medical Concept Annotation Toolkit. Artif Intell Med. 2021 Jul;117:102083.

26. Devlin J, Chang MW, Lee K, Toutanova K. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In: Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers). Minneapolis, Minnesota: Association for Computational Linguistics; 2019. p. 4171-86. Available from: https://aclanthology.org/N19-1423.

27. Lee J, Yoon W, Kim S, Kim D, Kim S, So CH, et al. BioBERT: a pre-trained biomedical language representation model for biomedical text mining. Bioinformatics. 2020;36(4):1234-40.

28. Li Y, Tao W, Li Z, Sun Z, Li F, Fenton S, et al. Artificial intelligence-powered pharmacovigilance: A review of machine and deep learning in clinical text-based adverse drug event detection for benchmark datasets. Journal of Biomedical Informatics. 2024:104621.

29. Magge A, Tutubalina E, Miftahutdinov Z, Alimova I, Dirkson A, Verberne S, et al. DeepADEMiner: a deep learning pharmacovigilance pipeline for extraction and normalization of adverse drug event mentions on Twitter. Journal of the American Medical Informatics Association. 2021;28(10):2184-92.

30. Liu Y, Ott M, Goyal N, Du J, Joshi M, Chen D, et al. Roberta: A robustly optimized bert pretraining approach. arXiv preprint arXiv:190711692. 2019.

31. Guellil I, Wu J, Wu H, Sun T, Alex B. Edinburgh_UCL_Health@ SMM4H'22: From GKraljevic2021-lnlove to Flair for handling imbalanced healthcare corpora related to Adverse Drug Events, Change in medication and self-reporting vaccination. In: Proceedings of COLING. International Conference on Computational Linguistics. vol. 2022. Europe PMC Funders; 2022. p. 148.

32. Raffel C, Shazeer N, Roberts A, Lee K, Narang S, Matena M, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. Journal of machine learning research. 2020;21(140):1-67.

33. Kanagasabai R, Veeramani A. A generic NLI approach for classification of sentiment associated with therapies. arXiv preprint arXiv:231203737. 2023.

34. Reimers N, Gurevych I. Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks. In: Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing. Association for Computational Linguistics; 2019. Available from: http://arxiv.org/abs/1908.10084.

35. Haq HU, Kocaman V, Talby D. Mining adverse drug reactions from unstructured mediums at scale. In: Multimodal AI in healthcare: A paradigm shift in health intelligence. Springer; 2022. p. 361-75.

36. Spark A. Apache spark. Retrieved January. 2018;17(1):2018.

37. Yazdani A, Proios D, Rouhizadeh H, Teodoro D. Efficient Joint Learning for Clinical Named Entity Recognition and Relation Extraction Using Fourier Networks: A Use Case in Adverse Drug Events. In: Proceedings of the 19th International Conference on Natural Language Processing (ICON); 2022. p. 212-23.

38. Zaratiana U, Tomeh N, Holat P, Charnois T. GLiNER: Generalist Model for Named Entity Recognition using Bidirectional Transformer; 2023.

39. Engineering K. Meet the new zero-shot NER architecture — blog.knowledgator.com;. [Accessed 02-10-2024]. https://blog.knowledgator.com/meet-the-new-zero-shot-ner-architecture-30ffc2cb1ee0.

40. Remy F, Scaboro S, Portelli B. Boosting Adverse Drug Event Normalization on Social Media: General-Purpose Model Initialization and Biomedical Semantic Text Similarity Benefit Zero-Shot Linking in Informal Contexts. In: Proceedings of the 11th International Workshop on Natural Language Processing for Social Media; 2023. p. 47-52.

41. Yazdani A, Rouhizadeh H, Alvarez DV, Teodoro D. DS4DH at# SMM4H 2023: Zero-Shot Adverse Drug Events Normalization using Sentence Transformers and Reciprocal-Rank Fusion. arXiv preprint arXiv:230812877. 2023.

42. Nguyen DQ, Vu T, Tuan Nguyen A. BERTweet: A pre-trained language model for English Tweets. In: Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations. Online: Association for Computational Linguistics; 2020. p. 9-14. Available from: https://aclanthology.org/2020.emnlp-demos.2.

43. Cormack GV, Clarke CL, Buettcher S. Reciprocal rank fusion outperforms condorcet and individual rank learning methods. In: Proceedings of the 32nd international ACM SIGIR conference on Research and development in information retrieval; 2009. p. 758-9.

44. Teodoro D, Ferdowsi S, Borissov N, Kashani E, Vicente Alvarez D, Copara J, et al. Information retrieval in an infodemic: the case of COVID-19 publications. Journal of medical Internet research. 2021;23(9):e30161.

45. CodaLab;. Available from: https://codalab.org/.

46. Song K, Tan X, Qin T, Lu J, Liu TY. Mpnet: Masked and permuted pre-training for language understanding. Advances in neural information processing systems. 2020;33:16857-67.

47. Li Y, Wehbe RM, Ahmad FS, Wang H, Luo Y. A comparative study of pretrained language models for long clinical text. Journal of the American Medical Informatics Association. 2023;30(2):340-7.