Validation of Left Ventricular High Frame Rate Echo-Particle Image Velocimetry against 4D Flow MRI in Patients

Yichuang Han*[†], Daniel J. Bowen[†], Bernardo Loff Barreto[†], Robert. R. Zwaan[†], Mihai Strachinaru[‡†], Rob J. van der Geest[¶], Alexander Hirsch[†§], Annemien E. van den Bosch[†], Johan G. Bosch[†] and Jason Voorneveld[†]

[†]Department of Cardiology, Cardiovascular Institute, Thorax Center, Erasmus MC, Rotterdam, the Netherlands

[‡]Department of Cardiology, Brussels University Hospital - Erasme Hospital, Brussels, Belgium

[§]Department of Radiology and Nuclear Medicine, Erasmus MC, Rotterdam, the Netherlands

[¶]Department of Radiology, Leiden University Medical Center, Leiden, the Netherlands

*Yichuang Han: y.han@erasmusmc.nl

Abstract

Background

Accurately measuring blood flow patterns in the heart could provide insights in the pathophysiology of cardiac disease, and may provide additional diagnostic and prognostic information. This study aims to validate Echo-Particle Image Velocimetry (echoPIV) for *in-vivo* left ventricular intracardiac flow imaging by comparing it with 4D flow MRI.

Methods

We acquired HFR contrast-enhanced ultrasound images from three standard apical views of 26 patients who required cardiac MRI. 4D flow MRI was obtained for each patient. Only echo image planes with sufficient quality and alignment with MRI were included for the validation. Regional velocity, kinetic energy and viscous energy loss were compared between modalities using normalized mean absolute error, cosine similarity and Bland-Altman analysis.

Results

Among 24 included apical view acquisitions, we observed good correspondence between echoPIV and MRI regarding spatial flow patterns and vortex traces. The velocity profile at the cross-section at the base level (mitral valve) had cosine similarity of 0.92 ± 0.06 and normalized mean absolute error of $14 \pm 5\%$. Peak of spatial mean velocity showed a difference of 3 ± 6 cm/s in systole and 6 ± 10 cm/s in diastole. The kinetic energy and rate of energy loss also revealed a high level of cosine similarity (0.89 ± 0.09 and 0.91 ± 0.06) with normalized mean absolute error of $23 \pm 7\%$ and $52 \pm 16\%$.

Conclusions

Given good B-mode image quality, echoPIV can provide a reliable estimation of left ventricular flow, as compared with 4D flow MRI, providing comparable spatial-temporal velocity distributions. There are advantages and disadvantages for both modalities. EchoPIV captured inter-beat variability and had higher temporal resolution, while MRI was more robust to patient BMI and anatomy.

CLINICAL PERSPECTIVE

We validated the results of high-frame-rate (HFR) 2D Echo-Particle Image Velocimetry (echoPIV) flow estimation against three-dimensional time-resolved phase-contrast cardiovascular magnetic resonance (4D flow MRI) imaging on three standard apical views of the left ventricle (LV) with sufficient B-mode

image quality and plane correspondence.

The flow results obtained with HFR 2D echoPIV showed good agreement with the velocities obtained with 2D projections of 4D flow MRI. We found that velocities and kinetic energy were comparable between the two modalities, but echoPIV measured higher viscous energy losses than 4D flow MRI. HFR echoPIV was able to capture intra-beat variability in flow patterns, which is not possible with 4D flow MRI, however the left ventricular outflow tract was often not captured in HFR echoPIV. Thus HFR echoPIV can be used to accurately assess flow in the LV and may provide an extra tool in the arsenal of cardiologists for the future study of cardiac disease.

Introduction

Comprehensive quantification of blood flow patterns in the heart may reveal crucial information for diagnosing and understanding various cardiac conditions, and for assessing their underlying pathophysiology. Such information can be helpful for risk assessment, including predicting thrombus formation and gauging treatment effectiveness, as well as for informing potential future treatment options. Recent studies suggested that cardiac hemodynamics are correlated to different types of cardiomyopathy [1, 2, 3, 4], including dilated cardiomyopathy[5][6]. At present, 4D flow MRI is considered the gold standard of intracardiac flow imaging. It offers detailed 3D velocity vectors throughout the cardiac cycle, allowing for comprehensive quantification and visualization of cardiac blood flow patterns. However, it has practical limitations such as high costs, long scan durations, and incompatibility with certain patient conditions or implants.

Echocardiography, on the other hand, is a readily accessible, real-time imaging technique used extensively in clinical practice. Doppler ultrasound techniques enable the measurement of blood flow velocity through the valves, as well as tissue motion[7][8]. However, it only provides velocity information along the direction of the ultrasound beam, limiting its ability to capture complex, multi-directional flow patterns.

Echo-Particle Image Velocimetry (echoPIV) provides a more detailed, 2D velocity field, allowing for a comprehensive view of blood flow patterns and velocities within the heart[9][10]. EchoPIV based on conventional (low frame rate) imaging has been used to investigate the relationship between flow and heart diseases, but it has been unable to quantify the full spectrum of velocities within the heart due to its frame-rate limitations[11][12][13]. High frame rate (HFR) echoPIV is a more recent technique that uses HFR contrast-enhanced ultrasound imaging to estimate blood flow patterns. HFR imaging, using diverging wave transmissions and software beamforming, allows imaging at $100\times$ the frame rate of conventional echocardiography[14].

In previous studies, echoPIV has been compared with optical PIV (*in vitro*)[15] and pulse-wave Doppler (*in vivo*)[6][16][17]. However, an *in vivo* validation for the whole intracardiac velocity field was still absent. Therefore, the primary objective of this study is to validate 2D echoPIV against 4D flow MRI for

the purpose of *in vivo* intracardiac flow imaging within the left ventricle (LV). Additionally, we examine the advantages and disadvantages of both imaging modalities. Finally, we report disturbed flow patterns in a patient with a severely dilated left ventricle and another one with left bundle branch block.

Methods

Setup of Study and Patient Selection

FIGURE 1. Overview of the experimental setup, signal processing and flow analysis pipeline

Patients referred for a cardiac MRI for screening of cardiomyopathy or determining the underlying etiology of a cardiomyopathy were selected. Exclusion criteria were hypertrophic cardiomyopathy, non-sinus rhythm, and poor acoustic windows in conventional echocardiography. The HFR echoPIV was acquired on the same day as the cardiac MRI (except for one patient). This study was approved by the Erasmus MC Medical Ethic Review Committee (Rotterdam, the Netherlands), and written informed consent was obtained from all patients (METC-2018-057, NL63755.078.18). The corresponding author had full access to all the data in the study.

4D Flow MRI

Image acquisition was performed on a 1.5 T clinical MRI scanner (SIGNA Artist, GE Healthcare, Milwaukee, WI, USA) using an anterior phased-array coil. The protocol included breath-hold balanced steady state free precession (bSSFP) cine images in the three standard long-axis views and a contiguous stack of short-axis images, all with 30 phases per cardiac cycle. Furthermore, a free-breathing,

retrospectively ECG-gated 4D flow sequence was acquired directly after administration of gadolinium contrast agent (Gadovist 0.2 mmol/kg) prescribed in the axial plane covering the whole heart. The 4D flow parameters were set as follows: HyperKat acceleration technique utilized with a factor of 6, complemented by compressed sensing; arrhythmia rejection 30%; respiratory compensation 20%; number of excitations 4; field of view 380 mm; phase field of view 60-100%; repetition time 4.2 msec; flip angle 15 degrees; VENC 150 cm/s; acquired resolution $2.4 \times 2.4 \times 2.4 \text{mm}^3$ and reconstructed number of phases per cardiac cycle of 30.

The 4D flow processing was performed using MASS software (Leiden University Medical Center, Leiden, the Netherlands)[18]. A second-order plane fit was applied as a static-tissue interpolation offset correction to correct for phase-offset errors. The contours of the LV were delineated on 2D anatomical MRI sequences. To ensure precise alignment, the anatomical positions of these 2D slices were extracted from the DICOM data and were used to define matching cut-planes in the 4D Flow MRI volume. Flow data corresponding to these planes were subsequently exported from the 4D sequence and further processed using Matlab (R2019a, MathWorks, Natick, MA, USA).

Echocardiography

The echocardiographic protocol consisted of two parts: a standard clinical protocol using a clinical ultrasound machine (EPIQ 7 with probe X5-1, Philips Healthcare, Best, The Netherlands); and the HFR contrast-enhanced ultrasound recordings using a research ultrasound machine (Vantage256, Verasonics, Kirkland, WA, USA) with a phased-array probe (P4-1, ATL, Bothell, WA, USA). The setup overview is shown in FIGURE 1. For the standard clinical protocol, B-mode and colour Doppler were acquired in the apical two, three and four-chamber (A2C, A3C & A4C) views. Pulsed-wave Doppler measurements were also taken at the mitral valve tips and the LV outflow tract (LVOT).

Following the clinical imaging protocol, a diluted solution of ultrasound contrast agent (SonoVue, Bracco Imaging SpA, Milan, Italy) was intravenously infused (1ml/min) using a continuous infusion pump (VueJect BR-INF 100, Bracco Imaging SpA). Upon verification of contrast agent arrival in the LV, the imaging system was switched to the research ultrasound machine for HFR imaging. HFR data were obtained with the setup described by Voorneveld et al.[16], where four repeated diverging-wave acquisitions with two alternating polarity transmits (pulse inversion) at two different angles $(-7°, +7°)$ were used. The pulse repetition frequency was chosen to reach the physical limitation of imaging depth $(3553 - 6012\text{Hz})$. Each acquisition captured a total of 3000 frames of data (~ 2.5 seconds), allowing for the recording of at least two cardiac cycles.

The saved RF data after pulse inversion summation was filtered at the second harmonic with a fourth-order Butterworth bandpass filter (2.6–3.8 MHz) to remove any residual fundamental frequency component and then beamformed onto a polar coordinate grid using the Verasonics software beamformer off-line. Singular Value Decomposition with automatic low-rank selection[19] and truncation was applied as a

wall-filter.

EchoPIV Processing

EchoPIV was performed using custom Matlab code (R2022a, MathWorks, Natick, MA, USA) and, in brief, involved subdividing each image into smaller blocks and tracking the HFR contrast-enhanced ultrasound speckle pattern over time to obtain the velocity information in each block. A more in-depth description of the technique is provided in supplemental material and is also described in Voorneveld et al.[15][16]. The final frame rate (after pulse inversion, compounding and ensemble averaging) of the velocity data was ~ 122.5 frames per second. The vector field obtained by echoPIV was interpolated onto a uniform cartesian grid for flow analysis.

Registration

For an accurate comparison of MRI and ultrasound flow fields, spatial and temporal registration between two scans is required. Temporal registration involved up-sampling the time series of MRI measurements (30 frames/cardiac cycle) to match the frame rate of the ultrasound images (~100 frames/cardiac cycle). The R peaks of the ECG signals were used to separate echocardiographic acquisitions into cycles and to synchronise them with the retrospectively ECG-gated MRI data.

Spatial registration refers to aligning the anatomical landmarks of the LV as seen in MRI sequences with those in the echocardiographic images. LV endocardial contours were manually drawn on the standard bSSFP long-axis cine images in each phase of the cardiac cycle using MASS software (Leiden, the Netherlands)[18]. These contours were then spatially registered (manually) to the ultrasound B-mode image by determining the best rigid transformation to align the MRI contours with the ultrasound image coordinates. The same rigid transformation was also applied to the vector field of the 4D flow measurement. The 3D vectors measured by MRI were projected onto the 2D ultrasound plane, considering that ultrasound imaging was performed in 2D. Spatial interpolation was used for 4D flow measurement to ensure vector alignment on the same grid as the ultrasound data.

Goodness of registration was quantitatively evaluated using the Dice coefficient between the end-diastolic LV endo contours derived from MRI and ultrasound. However, planar correspondence also requires thorough visual examination for potential issues of foreshortening and plane mismatch, the methods of which are described in the following section.

Feasibility and Assessment of Registration

We established two levels of inclusion criteria for flow analysis. Firstly, we evaluated B-mode image quality indicating the clinical feasibility of echoPIV for flow estimation. Acquisitions with poor

contrast/signal-to-noise ratio, blurred point spread function, or bubble signal loss in the basal region were considered unfeasible and excluded from flow comparison. Secondly, to enable a more reliable comparison with 4D flow MRI, we only included images that were sufficiently aligned between the two modalities. To select the sufficiently aligned images, we first excluded the acquisitions with severe foreshortening to mitigate its impact on flow comparison by setting a threshold of Dice coefficient > 0.85. Subsequently, we performed a visual assessment of all views by multiple independent observers (YH, JV, JGB) followed by a consensus session selection. This evaluation involved a careful visual comparison between the two modalities of key anatomical landmarks (the apical shape, septal wall, mitral valve and aortic valve, LVOT, and the position of papillary muscles) and the possible plane mismatch. The flowchart of the validation inclusion process is shown as part of FIGURE 1.

Comparison of Flow Between EchoPIV and 4D Flow MRI

We evaluated the spatial-temporal agreement of the two techniques using their velocity profiles, and two commonly derived regional flow parameters: kinetic energy (KE), rate of energy loss (ĖL) and circulation, which are defined in the supplemental material.

The LV was split into basal, mid, and apical regions by first selecting two basal points on the mitral anulus (on either side of the mitral valve) and a third point on the LV apex. The apex and the mid-point of the two basal points define the LV long axis. Two lines parallel to the line connecting the two basal points were then constructed that trisected the LV long axis, effectively dividing the LV into three segments: the base, mid, and apex regions. In addition to these, we identified another parallel line at 1/9 of the LV long axis length for the mitral valve inflow. A demonstration of the regional partition is shown in FIGURE 1. The velocity profiles were evaluated on the three parallel lines mentioned above - inflow, mid, and apex. The flow comparison was performed over the whole LV as well as locally (in the basal, mid, and apical regions of the LV). Two quantitative measures were used for comparison: Cosine Similarity (to assess similarity in the temporal progression of each parameter between modalities) and Normalized Mean Absolute Error (NMAE, to assess absolute differences between parameters measured by each modality).

Statistical Analysis

Statistics were analyzed using Matlab Statistics and Machine Learning Toolbox. To evaluate the clinical characteristics of all study participants against those of the comparison group, a Student's t-test was conducted for the continuous data and a Fisher's exact test was conducted for the categorical data. Statistical significance was assessed if the p-value < 0.05. The Student's t-test was also applied to compare the differences in Dice coefficient across three apical views. Bias and limits of agreement for temporal peak velocities between modalities, during systole and diastole, were estimated using Bland-Altman analysis[20], and these were reported with 95% confidence intervals (95% CI).

Results

Feasibility and assessment of registration

FIGURE 2. Flow chart for patient inclusion for quantitative flow comparison

As shown in FIGURE 2, among 78 standard apical view HFR acquisitions from 26 patients, 61 (78%) had good enough B-mode image quality for echoPIV flow estimation and thus could be considered clinically feasible for echoPIV processing.

The mean Dice coefficient for all 78 acquisitions was 0.88 ± 0.05, indicating a high degree of similarity between the end-diastolic echocardiographic and MRI masks. P-values from Student's t-tests of Dice coefficient for A4C, A3C and A2C (v.s. all views) were 0.23, 0.09 and 0.69, which indicated no differences among the three types of standard apical views.

After removal of acquisitions that did not meet the stringent alignment criteria (examples of removed acquisitions are shown in supplemental material as MOVIE S.6, S.7 and S.8), ultimately, 24 acquisitions from 16 patients were selected for the quantitative flow comparison. These included 12 apical four-chamber views, 6 apical three-chamber views, and 6 apical two-chamber views.

Hemodynamic and Echocardiographic Data

General clinical information, conventional echocardiographic and MRI findings for all patients and those selected for comparison are displayed in TABLE 1. No significant differences were found between the comparison group and the total patient group.

Flow Comparison: An Exemplary Case

FIGURE 3 shows the flow estimation results of echoPIV and 4D flow MRI for one exemplary patient. FIGURE 3.A and FIGURE 3.B show the flow streamlines during the formation of the vortex ring at ejection and early filling respectively (the corresponding movie of flow pathlines is shown in MOVIE S.1).

The comparison of the traces of the main vortices is shown in FIGURE 3.C and movies showing the

TABLE 1   *Clinical Information of the patients*

Parameters	All patients (n = 26)	Comparison group (n = 16)	p-value
General characteristics			
Age	46 [19-76]	39 [21-77]	0.28
Sex (Male/Female)	17/9	9/7	0.74
BMI	24.8 (20.7-27.1)	24.8 (20.2-26.7)	0.69
Heart rate(bpm)	66 (57-74)	72 (65-78)	0.28
Systolic blood pressure(mmHg)	123 (118-135)	125 (118-136)	0.63
Diastolic blood pressure(mmHg)	73 (67-79)	74 (67-77)	0.84
Echocardiographic characteristics			
2D LV end-diastolic volume (ml)	187 (148-230)	180 (133-198)	0.93
2D LV end-systolic volume (ml)	96 (72-128)	81 (58-96)	0.88
LV end-diastolic diameter (mm)	58 (54-62)	56 (48-62)	0.65
Peak velocity E (m/s)	0.7 (0.6-0.8)	0.8 (0.6-0.9)	0.19
Peak velocity A (m/s)	0.6 (0.5-0.7)	0.6 (0.5-0.7)	0.57
E/A	1.0 (0.8-1.4)	1.3 (1.0-1.5)	0.25
E/e'	7.5 (6.4-10.0)	7.1 (6.4-11.5)	0.92
Peak velocity LVOT (m/s)	1.0 (0.6-1.3)	1.0 (0.6-1.3)	0.84
LV ejection fraction (%)	53 (40-56)	55 (49-59)	0.33
MRI characteristics			
LV end-diastolic volume (ml)	204 (166-239)	195 (164-226)	0.92
LV end-systolic volume (ml)	120 (72-128)	81 (68-122)	0.92
LV ejection fraction (%)	52 (41-55)	52 (46-58)	0.47
LV ejection < 45% (n)	10	4	0.51
LV Mass (gr)	126 (104-155)	121 (93-137)	0.45

[1] Data are expressed as median (interquartile range) or number, except for age, which is expressed as number (range).

[2] LV=left ventricular; LVOT=left ventricular outflow tract; BMI=body mass index

formation and propagation of vortices for echocardiography and MRI within a cardiac cycle are included in the supplemental materials as Movie S.2. Figure 3.D and E show the spatial mean velocity and the spatial velocity profile at peak injection along the inflow line (the red dashed line at the mitral valve in Figure 3.A). The parameters derived from the velocity field (KE, EL and circulation in the detected vortex region) are shown in Figure 3.F, with ECG R peak as a time reference and with star and diamonds marking the ejection and early filling.

Agreement between Echocardiographic- and MRI- Flow Parameters

The velocity profile analysis for the comparison group (Figure 4.A and C), indicated a good agreement across all three levels.

FIGURE 3. (A) Flow streamlines of EchoPIV (left) and MRI (right) at $t = 88ms$ (ejection phase). (B) Flow streamlines of EchoPIV (left) and MRI (right) at $t = 537ms$ (early filling). (C) Vortex traces of EchoPIV (left) and MRI (right). (D) Mean velocity at a plane at the level of mitral valve. (E) Velocity along the line through mitral valve at peak of early filling. (F) Derived flow parameters of the full left ventricle(kinetic energy, rate of energy loss, circulation), ECG as time reference

Analysis of the Bland-Altman plot of peak spatial-mean velocity (FIGURE 4.B) revealed that echoPIV measured, on average, 0.06 m/s (95% CI -0.25 to 0.14 m/s) higher velocities than MRI during diastole; and 0.03 m/s (95% CI -0.11 to 0.17 m/s) slower during systole. Moreover, echoPIV exhibited higher velocities in apex than MRI.

The results of energy-based flow parameters are shown in FIGURE 5. The median cosine similarity for regional KE and EL lay in the range of (0.82,0.91) and (0.88,0.92). The NMAE exhibited higher values than those of velocity analysis, with its median lying in the range of (0.22,0.36) and (0.45,0.53) for KE and EL. The apical region exhibited a larger difference between echo and MRI than the whole LV, characterized by a lower cosine similarity and higher NMAE.

The results of velocity profile and energy-based flow parameters for all 61 clinically feasible acquisitions are shown in supplemental materials as FIGURE S.1 and S.2 for comparative purposes. When comparing FIGURE S.1 to FIGURE 4, a more sparsely distributed Bland-Altman analysis is observed. For velocity profiles and energy-based parameters, cosine similarities decreased while NMAEs rose, both accompanied by a broader interquartile range.

FIGURE 4. (A) Box plot of cosine similarity and normalized mean absolute error of the spatial mean velocity magnitude profile through lines at mitral valve (MV) inflow, mid and apex level. Black lines in the middle indicate median, boxes extend to 25th and 75th percentiles, and whiskers indicate the range excluding samples outside of 1.5 times the interquartile range. (B) Bland-Altman plot of the peak spatial mean velocity through lines at MV inflow, mid and apex level (as demonstrated in Fig 1.A) during systole and diastole. (C) Table summarizing the box plot in Fig. 4.A, data are expressed in median(25th and 75th percentiles)

Inter-beat Variability

Ultrasound allowed an inter-beat variability analysis. Note that we only included patients with sinus rhythm in order to ensure high-quality MRI results. Despite that, we still observed, in some cases, considerable inter-beat variability in the hemodynamics observed with echoPIV between cardiac cycles for certain patients.

FIGURE 6 provides a representative illustration of a patient with inter-beat variability. Specifically, FIGURE 6.A (corresponding movie shown in supplemental material as MOVIE S.3) depicts the variability observed in flow streamlines at the peak of late filling over three consecutive cardiac cycles. Notably, the third cycle displayed a distinct vortex, while the second cycle exhibited two smaller vortices. Furthermore, FIGURE 6.B shows varying inflow jet velocities across the three heartbeats, which corresponds to different levels of KE. The MRI seems to show the averaged total of the different echoPIV beats with distinctly lower peaks.

n=24	Cosine Similarity		Normalized Mean Absolute Error	
	Kinetic Energy	Rate of Energy Loss	Kinetic Energy	Rate of Energy Loss
Base	0.91 (0.83,0.93)	0.91 (0.88,0.92)	0.22 (0.18,0.29)	0.45 (0.35,0.52)
Mid	0.87 (0.80,0.94)	0.88 (0.86,0.94)	0.29 (0.18,0.35)	0.53 (0.41,0.64)
Apex	0.82 (0.71,0.88)	0.89 (0.85,0.94)	0.36 (0.22,0.48)	0.53 (0.46,0.69)
LV	0.91 (0.87,0.95)	0.92 (0.91,0.94)	0.26 (0.17,0.29)	0.52 (0.40,0.64)

FIGURE 5. Box plot of cosine similarity and normalized mean absolute error of kinetic energy and energy loss rate in base, mid, apex regions and the whole left ventricle (LV). Black lines in the middle indicate median, boxes extend to 25th and 75th percentiles, and whiskers indicate the range excluding samples outside of 1.5 times the interquartile range. Data are expressed in median(25th and 75th percentiles)

Discussion

For 78% of the patients with sufficient image quality, using the echoPIV flow estimation, we can obtain 2D vector velocity field information equivalent to 4D flow MR. Combined with echo's low cost plus its ability to assess inter-beat variability, HFR echoPIV may enable clinicians to do follow-up examinations on patients and guide their choice of treatment.

Qualitative Comparison

Qualitatively, similar flow patterns were observed between echoPIV and MRI, especially during diastole where there was striking resemblance between the filling flow patterns and velocity magnitudes. In systole there was a weaker agreement, where the outflow jet velocities were underestimated in many echoPIV acquisitions (see FIGURE 4.B). This underestimation has also been observed in previous studies[16][21] and may be due to several reasons: 1) slight deviations of echo imaging plane from the LVOT plane, 2) signal decorrelation occurring during the pulse inversion process, 3) strong spatial velocity gradients in the LV outflow tract[22].

Overall 4D flow MRI resulted in a smoother flow field than echoPIV. It is likely that MRI captures a beat-averaged version of the instantaneous flow dynamics (as the flow data is reconstructed using multiple heart cycles and multiple averages), whereas echoPIV's estimate captures the true time-resolved flow dynamics but is partially corrupted by noise from the imaging and speckle tracking processes. Using physics-informed smoothing algorithms may help form a more accurate middle-ground between the two

FIGURE 6. Example of inter-beat variability captured by echoPIV: (A) Streamline of the blood flow at peak late filling of each cycle of echoPIV and MRI measurement. (B) Kinetic energy and rate of energy loss in the whole left ventricle of each cycle of echoPIV and MRI measurement

extremes in the future[23].

Another observation was that echoPIV captured finer flow details in the apex than 4D flow MRI. This is due partly to MRI's low sensitivity to slow flow because of the VENC setting used in this study, which results in a lower signal-to-noise ratio when measuring low velocities. But also because of the higher spatial resolution of ultrasound close to the transducer (and higher temporal resolution in general). We also noted the flip side of the coin: the low ultrasound spatial resolution in the basal region (due to the sector-scan) resulted in seemingly wider filling jets than those captured with MRI.

EchoPIV's improved temporal resolution also allowed for the assessment of dynamic changes in flow pattern over multiple cardiac cycles. In FIGURE 6 we observed that intra-beat variability in diastolic filling timing caused 4D flow MRI to largely underestimate the KE associated with early and late filling, as compared with echoPIV.

Quantitative Comparison

The results of the quantitative comparative analysis of the velocity profiles and the derived flow parameters (FIGURE 4 & 5) show a good correspondence between echoPIV and 4D flow MRI. The Bland-Altman analysis showed MRI recorded higher velocities during systole, while echocardiography measured higher velocities during diastole. It has previously been shown that echoPIV underestimated the

filling and ejection velocities compared to pulsed-wave Doppler by 0.12m/s and 0.22m/s, respectively[6]. This indicates that both echoPIV and 4D flow MRI are similarly biased towards lower velocities than pulsed-wave Doppler. In addition, research comparing 4D flow MRI with traditional transthoracic pulse-wave Doppler echocardiography for the measurement of mitral inflow peak diastolic velocities reported that MRI underestimated peak diastolic velocities by 0.05 m/s (95% CI -0.37 to 0.46 m/s)[24]. Thus, the differences between echoPIV and 4D-flow MRI found in this study are comparable with previous inter-modality studies.

When compared to the velocity profiles, the derived parameters, KE and $\dot{E}L$ exhibited a higher level of cosine similarity, which indicates good correspondence of temporal patterns. However, a higher NMAE was seen, indicating offsets in the absolute values, especially for $\dot{E}L$ (calculated using derivatives of the velocity field) is more susceptible to noise and smoothing(FIGURE 3.F).

From the comparison of results from clinically feasible group and well-aligned group, we observed an increase in variance, indicating plane alignment is important for consistent estimation of the flow field. Therefore, sonographers should be critical of selecting the standard planes, especially for follow-up studies.

Interpretation of Flow Features

In order to highlight the potential clinical benefit of HFR echoPIV we present two specific cases in FIGURE 7. In FIGURE 7.A (MOVIE S.4), the flow in a severely dilated left ventricle and reduced ejection fraction (LV ejection fraction 21%) is depicted, characterized by a single large vortex that swirls blood inside the whole ventricle. This pathological condition is associated with a reduced relative energy loss ($\dot{E}L$/KE), as the KE is well preserved within the large vortex, which is confirmed in FIGURE 7.B[25]. FIGURE 7.C (MOVIE S.5) and D depict abnormal apical flow in a patient with left bundle branch block. The presence of an aberrant flow pattern is associated with irregular relaxation of the septal wall. Notably, this anomaly is not readily discernible through conventional echocardiographic measurements but is evident when examining the flow pattern.

Challenges

In order to measure high-velocity flows within the heart, HFR ultrasound inevitably sacrifices some image quality compared to conventional focused ultrasound imaging. Furthermore, patients presenting with cardiac pathologies frequently exhibit comorbidities such as obesity or lung disease, which bring further challenges to acquiring sufficient-quality echocardiographic images.

Other factors limiting the clinical feasibility are rib shadowing and deviations from standard imaging plane. The quality and accuracy of echocardiographic images are highly operator-dependent, potentially leading to variability in each acquisition. In this study, we used a probe with a relatively large footprint

FIGURE 7. (A) Example of the flow pattern at peak early filling for a patient with severely dilated left ventricle and reduced ejection fraction. (B) Relative energy loss (energy Loss normalized by kinetic energy) for each included patient (the patient case shown in (A) is marked in red). (C) Example of the flow pattern at three filling phases for a patient with left bundle branch block. (D) Flux at base line and apical line (marked in (C)) for this patient.

size for HFR, which also presented a challenge for our sonographers in avoiding ribs. This also made precise acquisition of the standard apical views difficult, especially for apical two-chamber view, where there are few landmarks to locate the plane. An example (FIGURE S.3) is shown in supplemental materials, in which echocardiographic imaging plane is severely foreshortened and deviated from the standard apical 2 chamber view.

Limitations

In our study, we primarily included patients undergoing cardiac MRI for cardiomyopathy screening or etiology determination, but we specifically excluded those with hypertrophic cardiomyopathy, non-sinus rhythm, and poor acoustic windows. This focused patient cohort might reduce the generalizability of our findings to a broader array of patient populations. Our research was confined to analyzing left ventricular flow, suggesting a potential avenue for future studies to apply echoPIV to other cardiac chambers. Furthermore, the comparison of the 2D velocity field from echoPIV with the projected 3D velocity field from 4D flow MRI might lead to discrepancies in flow measurement and interpretation.

Conclusions

EchoPIV was feasible for 78% of the acquisitions. EchoPIV demonstrated the capability to accurately quantify flow within the LV, providing reliable spatial-temporal velocity distribution and magnitude measurement compared to 4D flow MRI as the reference standard. Both modalities have their benefits. MRI is more robust to patient-related factors that may influence the echocardiographic image quality. On the other hand, echoPIV, offers the advantage of capturing inter-beat variability and has a much higher temporal resolution.

Acknowledgments

We thank Dr. Ing Han Gho for his assistance in the contrast-enhanced ultrasound image acquisition.

Funding

The work described in this article was funded by the Medical Delta program "Ultrafast Ultrasound for the Heart and Brain"; the project X-Flow of the research program Ultra-X-Treme (P17-32), which is financed by the Dutch Research Council (NWO); and the Dutch Heart Foundation (Hartstichting) as part of project number 03-004-2022-0044.

Disclosures

A. Hirsch received a research grant and consultancy fees from GE Healthcare and speaker fees from GE Healthcare and Bayer. He is also a member of the medical advisory board of Medis Medical Imaging Systems and was MRI corelab supervisor of Cardialysis BV until 2022.

REFERENCES

1. Bissell MM, Raimondi F, Ait Ali L, Allen BD, Barker AJ, Bolger A, Burris N, Carhäll C-J, Collins JD, Ebbers T, et al. 4D Flow cardiovascular magnetic resonance consensus statement: 2023 update. *Journal of Cardiovascular Magnetic Resonance.* 2023;25:40.

2. Garg P, Crandon S, Swoboda PP, Fent GJ, Foley JRJ, Chew PG, Brown LAE, Vijayan S, Hassell M, Nijveldt R, et al. Left ventricular blood flow kinetic energy after myocardial infarction - insights from 4D flow cardiovascular magnetic resonance. *J Cardiovasc Magn Reson.* 2018;20:61.

3. Demirkiran A, Hassell M, Garg P, Elbaz MSM, Delewi R, Greenwood JP, Piek JJ, Plein S, van der Geest RJ, Nijveldt R. Left ventricular four-dimensional blood flow distribution, energetics, and vorticity in chronic myocardial infarction patients with/without left ventricular thrombus. *Eur J Radiol.* 2022;150:110233.

4. Hsu S, Fang JC, Borlaug BA. Hemodynamics for the Heart Failure Clinician: A State-of-the-Art Review. *Journal of Cardiac Failure.* 2022;28:133-148.

5. Mele D, Smarrazzo V, Pedrizzetti G, Capasso F, Pepe M, Severino S, Luisi GA, Maglione M, Ferrari R. Intracardiac Flow Analysis: Techniques and Potential Clinical Applications. *J Am Soc Echocardiogr.* 2019;32:319-332.

6. Strachinaru M, Voorneveld J, Keijzer LBH, Bowen DJ, Mutluer FO, Cate FT, de Jong N, Vos HJ, Bosch JG, van den Bosch AE. Left ventricular high frame rate echo-particle image velocimetry: clinical application and comparison with conventional imaging. *Cardiovasc Ultrasound.* 2022;20:11.

7. Appleton CP, Hatle LK, Popp RL. Demonstration of restrictive ventricular physiology by Doppler echocardiography. *J Am Coll Cardiol.* 1988;11:757-768.

8. Ommen SR, Nishimura RA, Appleton CP, Miller FA, Oh JK, Redfield MM, Tajik AJ. Clinical Utility of Doppler Echocardiography and Tissue Doppler Imaging in the Estimation of Left Ventricular Filling Pressures. *Circulation.* 2000;102:1788-1794.

9. Agati L, Cimino S, Tonti G, Cicogna F, Petronilli V, De Luca L, Iacoboni C, Pedrizzetti G. Quantitative analysis of intraventricular blood flow dynamics by echocardiographic particle image velocimetry in patients with acute myocardial infarction at different stages of left ventricular dysfunction. *European Heart Journal - Cardiovascular Imaging.* 2014;15:1203-1212.

10. Pedrizzetti G, Martiniello AR, Bianchi V, D'Onofrio A, Caso P, Tonti G. Changes in electrical activation modify the orientation of left ventricular flow momentum: novel observations using echocardiographic particle image velocimetry. *European Heart Journal - Cardiovascular Imaging.* 2015;17:203-209.

11. Kheradvar A, Houle H, Pedrizzetti G, Tonti G, Belcik T, Ashraf M, Lindner JR, Gharib M, Sahn D. Echocardiographic particle image velocimetry: a novel technique for quantification of left ventricular blood vorticity pattern. *J Am Soc Echocardiogr.* 2010;23:86-94.

12. Prinz C, Faludi R, Walker A, Amzulescu M, Gao H, Uejima T, Fraser AG, Voigt J-U. Can echocardiographic particle image velocimetry correctly detect motion patterns as they occur in blood inside heart chambers? A validation study using moving phantoms. *Cardiovascular Ultrasound.* 2012;10:24.

13. Gao H, Claus P, Amzulescu M-S, Stankovic I, D'hooge J, Voigt J-U. How to optimize intracardiac blood flow tracking by echocardiographic particle image velocimetry? Exploring the influence of data acquisition using computer-generated data sets. *European Heart Journal - Cardiovascular Imaging.* 2011;13:490-499.

14. Cikes M, Tong L, Sutherland GR, D'hooge J. Ultrafast Cardiac Ultrasound Imaging: Technical Principles, Applications, and Clinical Benefits. *JACC: Cardiovascular Imaging.* 2014;7:812-823.

15. Voorneveld J, Muralidharan A, Hope T, Vos HJ, Kruizinga P, van der Steen AFW, Gijsen FJH, Kenjeres S, de Jong N, Bosch JG. High Frame Rate Ultrasound Particle Image Velocimetry for Estimating High Velocity Flow Patterns in the Left Ventricle. *IEEE Trans Ultrason Ferroelectr Freq Control.* 2018;65:2222-2232.

16. Voorneveld J, Keijzer LBH, Strachinaru M, Bowen DJ, Mutluer FO, van der Steen AFW, Cate FJT, de Jong N, Vos HJ, van den Bosch AE, et al. Optimization of Microbubble Concentration and Acoustic Pressure for Left Ventricular High-Frame-Rate EchoPIV in Patients. *IEEE Trans Ultrason Ferroelectr Freq Control.* 2021;68:2432-2443.

17. Voorneveld J, Keijzer LBH, Strachinaru M, Bowen DJ, Goei JSL, Cate FT, Steen AFWvd, Jong Nd, Vos HJ, Bosch AEvd, et al. High-Frame-Rate Echo-Particle Image Velocimetry Can Measure the High-Velocity Diastolic Flow Patterns. *Circulation: Cardiovascular Imaging.* 2019;12:e008856.

18. van der Geest RJ, Buller VGM, Jansen E, Lamb HJ, Baur LHB, van der Wall EE, de Roos A, Reiber JHC. Comparison Between Manual and Semiautomated Analysis of Left Ventricular Volume Parameters from Short-Axis MR Images. *Journal of Computer Assisted Tomography.* 1997;21:756-765.

19. Baranger J, Arnal B, Perren F, Baud O, Tanter M, Demene C. Adaptive Spatiotemporal SVD Clutter Filtering for Ultrafast Doppler Imaging Using Similarity of Spatial Singular Vectors. *IEEE Trans Med Imaging.* 2018;37:1574-1586.

20. Altman DG, Bland JM. Measurement in Medicine: The Analysis of Method Comparison Studies. *Journal of the Royal Statistical Society Series D (The Statistician).* 1983;32:307-317.

21. Mawad W, Lovstakken L, Fadnes S, Gronli T, Segers P, Mertens L, Nyrnes SA. Right Ventricular Flow Dynamics in Dilated Right Ventricles: Energy Loss Estimation Based on Blood Speckle Tracking Echocardiography-A Pilot Study in Children. *Ultrasound Med Biol.* 2021;47:1514-1527.

22. Voorneveld J, Bosch JG. The Effect of Spatial Velocity Gradients on Block-Matching Accuracy for Ultrasound Velocimetry. *IUltrasound Med Biol.* 2023;

23. Grønli T, Wigen M, Segers P, Lovstakken L. A Fast 4D B-Spline Framework for Model-Based Reconstruction and Regularization in Vector Flow Imaging. Paper/Poster presented at: *2018 IEEE International Ultrasonics Symposium (IUS);* 22-25 Oct. 2018, 2018;

24. Assadi H, Li R, Grafton-Clarke C, Uthayachandran B, Alabed S, Maiter A, Archer G, Swoboda PP, Sawh C, Ryding A, et al. Automated 4D flow cardiac MRI pipeline to derive peak mitral inflow diastolic velocities using short-axis cine stack: two centre validation study against echocardiographic pulse-wave doppler. *BMC Cardiovascular Disorders.* 2023;23:24.

25. Han QJ, Witschey WR, Fang-Yen CM, Arkles JS, Barker AJ, Forfia PR, Han Y. Altered Right Ventricular Kinetic Energy Work Density and Viscous Energy Dissipation in Patients with Pulmonary Arterial Hypertension: A Pilot Study Using 4D Flow MRI. *PLoS One.* 2015;10:e0138365.

26. Yiu BY, Lai SS, Yu AC. Vector projectile imaging: time-resolved dynamic visualization of complex flow patterns. *Ultrasound Med Biol.* 2014;40:2295-2309.

Supplemental Material

EchoPIV processing

The EchoPIV processing is described in detail in Voorneveld et al.[15][16]. In short, to estimate the displacements between subsequent frames, the image area was divided into equally sized blocks with overlap. Normalized cross correlation (NXCC) was then computed in the frequency domain for each block, and the peak of the correlation function, obtained through subpixel fitting, provided the displacement between the frames per block. The algorithm iteratively performed the blockwise NXCC step multiple times, using the displacements from the previous iteration to deform the target frame and reduce the displacement between frames towards zero. The window size was progressively reduced between iterations to enhance resolution and minimize displacement estimation bias.

Instead of coherent compounding of angled plane wave acquisitions, correlation compounding was employed. This involved performing blockwise normalized cross correlation between frames with similar angles and averaging the resulting correlation maps across different angles. Additionally, correlation averaging was applied across an ensemble of ten frames to further reduce noise.

Postprocessing steps included the application of a 2-D Gaussian spatial smoothing filter (with standard deviation of 0.5 and filter size of 3) and ensemble temporal moving average filter with a length of 10 frames to the computed velocity fields. Finally, the velocity data were scan converted to cartesian coordinates for visualization using the vector projectile imaging technique[26].

Equations for agreement assessment and flow analysis

The Dice coefficient is computed as:

$$\text{Dice coefficient} = \frac{2|A_{\text{echo contour}} \bigcap A_{\text{mri contour}}|}{|A_{\text{echo contour}}| + |A_{\text{mri contour}}|} \tag{1.1}$$

where A = Area enclosed by contour.

Cosine similarity employs the cosine of the angle between two profile vectors, yielding a similarity that ranges from -1 to 1. In our analysis, a cosine similarity close to 1 indicates a high degree of similarity between the temporal profiles obtained from the two imaging techniques.

$$\text{cosine similarity} = \frac{\mathbf{V_m}^{echo}(t) \cdot \mathbf{V_m}^{mri}(t)}{\|\mathbf{V_m}^{echo}(t)\|\|\mathbf{V_m}^{mri}(t)\|} \tag{1.2}$$

where $\|\mathbf{V_m}\|$ is the Euclidean norm of vector $\mathbf{V_m}(t)$, defined as $\sqrt{\sum_t^{N_t} V_m(t)^2}$. Note that Cosine Similarity represents the similarity in pattern shape, and can be high even if the norms are very different.

NMAE was used to quantify the average discrepancy between the velocity magnitudes measured by the two methods, providing insights into the accuracy of the absolute velocity measurements. It was calculated as the mean absolute difference between the measured (echoPIV) and the reference (MRI) velocities, normalized by their maximum.

$$\text{NMAE} = \frac{\sum_t^{N_t} |V_m{}^{echo} - V_m{}^{mri}|}{N_t \cdot \max(\max V_m{}^{echo}, \max V_m{}^{mri})} \tag{1.3}$$

where N_t is the number of frames.

Kinetic energy was computed from the velocity vectors, $\vec{v} = v_x \hat{x} + v_y \hat{y} + v_z \hat{z}$, as

$$\text{KE} = \frac{1}{2} \cdot \rho \cdot \int v_x{}^2 + v_y{}^2 + v_z{}^2 dxdydz \tag{1.4}$$

where $\rho = 1060 kg/m^3$ is the blood density, and the integral is over the region of interest. For a 2D acquisition, we assume an infinitely thin layer in through-plane direction (y-direction) and $v_y = 0$, thus Eq. 1.4 can be written as:

$$\text{KE} = \frac{1}{2} \cdot \rho \cdot \int v_x{}^2 + v_z{}^2 dxdz \tag{1.5}$$

Rate of energy loss was estimated from the viscous dissipation, which considers the velocity gradients in the flow:

$$\dot{\text{EL}} = \nu \int 2\left(\frac{\partial v_x}{\partial x}\right)^2 + 2\left(\frac{\partial v_z}{\partial z}\right)^2 + \left(\frac{\partial v_x}{\partial z} + \frac{\partial v_z}{\partial x}\right)^2 dxdz \tag{1.6}$$

where $\nu = 0.004 Pa.s$ is the kinematic viscosity of blood.

Circulation Γ within a vortex of blood flow was calculated as:

$$\Gamma = \oint_C \vec{v} \, dl \tag{1.7}$$

$$= \int_S (\nabla \times \vec{v}) \cdot dS \tag{1.8}$$

$$= \int_S \omega \cdot dS \tag{1.9}$$

with the line integral taken over a closed circuit C around a vortex region in counter-clockwise sense.

Extra figures

FIGURE S.1. (A) Box plot of cosine similarity and normalized mean absolute error of the spatial-temporal velocity magnitude profile through lines at base, mid and apex level (for all feasible acquisitions). Black lines in the middle indicate median, boxes extend to 25th and 75th percentiles, and whiskers indicate the range excluding samples outside of 1.5 times the interquartile range. (B) Bland-Altman plot of the peak spatial mean velocity through lines at base, mid and apex level (as demonstrated in Fig 1.A) during systole and diastole. (C) Table summarizing the box plot in Fig. S.1.A, data are expressed in median(25th and 75th percentiles). MV=mitral valve

FIGURE S.2. Box plot of cosine similarity and normalized mean absolute error of kinetic energy and energy loss rate in base, mid, apex regions and the whole left ventricle (LV) for all feasible acquisitions (n=61) and for the ones with good alignment (n=24). Black lines in the middle indicate median, boxes extend to 25th and 75th percentiles, and whiskers indicate the range excluding samples outside of 1.5 times the interquartile range. Data are expressed in median(25th and 75th percentiles)

n=24	Cosine Similarity		Normalized Mean Absolute Error	
	Kinetic Energy	Rate of Energy Loss	Kinetic Energy	Rate of Energy Loss
Base	0.91 (0.83,0.93)	0.91 (0.88,0.92)	0.22 (0.18,0.29)	0.45 (0.35,0.52)
Mid	0.87 (0.80,0.94)	0.88 (0.86,0.94)	0.29 (0.18,0.35)	0.53 (0.41,0.64)
Apex	0.82 (0.71,0.88)	0.89 (0.85,0.94)	0.36 (0.22,0.48)	0.53 (0.46,0.69)
LV	0.91 (0.87,0.95)	0.92 (0.91,0.94)	0.26 (0.17,0.29)	0.52 (0.40,0.64)

n=61	Cosine Similarity		Normalized Mean Absolute Error	
	Kinetic Energy	Rate of Energy Loss	Kinetic Energy	Rate of Energy Loss
Base	0.85 (0.74,0.92)	0.89 (0.83,0.91)	0.28 (0.19,0.36)	0.48 (0.39,0.62)
Mid	0.83 (0.76,0.92)	0.90 (0.85,0.94)	0.35 (0.25,0.44)	0.58 (0.47,0.78)
Apex	0.82 (0.73,0.89)	0.90 (0.84,0.94)	0.39 (0.33,0.51)	0.60 (0.49,0.77)
LV	0.88 (0.82,0.93)	0.91 (0.88,0.94)	0.29 (0.21,0.36)	0.57 (0.44,0.72)

FIGURE S.3. (A) Flow streamlines of EchoPIV (up) and MRI (bottom) at $t = 223ms$ (ejection phase), $t = 546ms$ (early filling) and $t = 1008ms$ (late filling). (B) Flux at a plane at the level of mitral valve, with zero flux marking with red dashed line.

Extra movies

MOVIE S.1. Pathlines of the flow field (EchoPIV on the left and MRI on the right) for the exemplary case shown in Figure 3.A.

MOVIE S.2. Vortex formation and propagation (EchoPIV on the left and MRI on the right) for the exemplary case shown in Figure 3.C.

MOVIE S.3. Pathlines of the flow field of the three distinct cardiac cycles for the example of inter-beat variability captured by echoPIV shown in Figure 6

MOVIE S.4. Pathlines of the flow field (EchoPIV on the left and MRI on the right) for the example of severely dilated left ventricle shown in Figure 7.A

MOVIE S.5. Pathlines of the flow pattern for the example of a patient with LBBB and have three apical level filling phases shown in Figure 7.C.

MOVIE S.6. Pathlines of the flow pattern for an example whose echo imaging plane was severely foreshortened and was thus excluded from flow comparison.

MOVIE S.7. Pathlines of the flow pattern for an example whose echo imaging plane was severely rotated from MRI imaging plane and was thus excluded from flow comparison.

MOVIE S.8. Pathlines of the flow pattern for an example whose echo imaging plane was severely foreshortened and rotated from MRI imaging plane and was thus excluded from flow comparison.