A Novel Question-Answering Framework for Automated Abstract Screening Using Large Language Models

Corresponding Author:
Xiaorui Jiang
Centre for Computational Science and Mathematical Modelling
Coventry University
Innovation Village 10
Coventry
United Kingdom
CV1 2TL
Doctor of Philosophy
E-mail: xiaorui.jiang@coventry.ac.uk
Telephone Number: (+44) 7399564629

Co-Author:
Opeoluwa Akinseloyin
Centre for Computational Science and Mathematical Modelling
Coventry University
Coventry United Kingdom

Co-Author:
Vasile Palade
Centre for Computational Science and Mathematical Modelling
Coventry University
Coventry United Kingdom
Doctor of Philosophy

Keywords:
Automated Systematic Review, Abstract Screening, GPT, Zero-Shot Ranking, Question Answering

Word Count: 5631

A Novel Question-Answering Framework for Automated Abstract Screening Using Large Language Models

Opeoluwa Akinseloyin,[1] Xiaorui Jiang[1] and Vasile Palade[1]

[1]Centre for Computational Science and Mathematical Modelling, Coventry University, Puma Way, CV1 2TT, Coventry, United Kingdom

*Xiaorui Jiang. xiaorui.jiang@coventry.ac.uk

Abstract

Objective: This paper aims to address the challenges in abstract screening within Systematic Reviews (SR) by leveraging the zero-shot capabilities of large language models, particularly GPT-3.5.

Methods: We employ GPT-3.5 as a zero-shot ranker to prioritize candidate studies by aligning abstracts with the selection criteria outlined in an SR protocol. abstract screening was transformed into a novel question-answering (QA) framework, treating each selection criterion as a question addressed by GPT-3.5. The framework involves breaking down the selection criteria into multiple questions, properly prompting GPT-3.5 to answer each question, scoring and re-ranking each answer, and combining the responses to make nuanced inclusion or exclusion decisions.

Results: Large-scale validation was performed on the benchmark of CLEF eHealth 2019 Task 2: Technology-Assisted Reviews in Empirical Medicine. Across 31 datasets of four categories of SRs, the proposed QA framework consistently outperformed other zero-shot ranking models. Compared with our QA-based approach exhibited a clear advantage over traditional models and bespoke BERT-family models that were fine-tuned for ranking tasks (i.e., from the BERT to PubMedBERT), underscoring their high potential in facilitating abstract screening.

Conclusion: Investigation justified the indispensable value of leveraging selection criteria to improve the performance of automated abstract screening. GPT-3.5 demonstrated proficiency in prioritizing candidate studies for abstract screening using the proposed QA framework. Significant performance improvements were obtained by re-ranking answers using the semantic alignment between abstracts and selection criteria. This further highlighted the pertinence of utilizing selection criteria to enhance abstract screening.

Key words: Automated Systematic Review, Abstract Screening, GPT, Zero-Shot Ranking, Question Answering

Introduction

A Systematic Review (SR) in medical research is the highest form of knowledge synthesis of all available medical evidence from relevant publications on a specific topic. SR follows a principled pipeline, including candidate study retrieval, primary study selection, quality assessment, data extraction, data synthesis, meta-analysis, and reporting [1]. Because of its thoroughness and reliability, SR underpins evidence-based medicine [2]. It shapes medical research and practice by informing researchers of the state-of-the-art knowledge and knowledge gaps as well as health practitioners and policymakers of the best clinical practice [3].

SR also faces tremendous challenges at each step. For instance, it is time-consuming, expensive and resource-intensive to select primary studies, a.k.a. *citation screening*, due to the massive volume of retrieved candidate studies, often at tens of thousands [4, 5]. It is

further worsened by involving multiple human annotators, which is required to reduce bias and disparities [6]. This compound complexity calls for innovative solutions to automate or semi-automate abstract screening [1] to minimize the time delays and costs of this manual screening tasks [7], which is the focus of the current paper. Figure 1 shows an example of abstract screening, where the abstract of an included study is matched against the selection criteria defined in the SR protocol.

Machine learning has been the focus of research in automating abstract screening [1, 7, 8]. Firstly, a small set of studies is selected for human annotation, and then a classifier is trained. Typically, active learning is adopted to improve the classifier iteratively. Obviously, the quality of the initial annotations plays an important role. However, choosing initial annotations is a problem of zero-shot setting and has not been explored at all. Another disadvantage is that this approach is not generalisable, and each SR topic requires training a bespoke classifier from scratch.

An alternative perspective was to treat abstract screening as a ranking problem a.k.a. *reference prioritisation* [7], incorporating approaches from the information retrieval (IR) community [9, 10, 11, 12, 13, 14, 15, 16]. One advantage of this approach is that it can utilise additional information about an SR converted into queries to enhance screening performance. Such information could be review title [9, 10], original Boolean queries (for candidate study retrieval) [17], research objectives [18, 16], or a set of seed studies [15, 19]. Another advantage is the possibility of training a cross-topic ranker to generalise to diverse SR topics.

The above analysis motivated us to explore the emerging capabilities of Large Language Models (LLMs), particularly GPT-3.5 (GPT hereafter when the context is clear), to facilitate abstract screening. LLMs, with their robust zero-shot capabilities [20], offer the potential to act as AI-based reviewers, streamlining the abstract screening process by either replacing at least one human reviewer or suggesting an initial set of abstracts for human verification and classifier training, both significantly reducing the workload for human reviewers .

In addition, we witness a severe lack of study about using selection criteria in automated abstract screening. Indeed, the selection criteria set up the grounds for human reviewers' decision-making. Unfortunately, only a few studies initiated similar attempts [21, 22, 23], but neither the effectiveness of their methods nor the comprehensiveness of their experiments could provide convincing conclusions about the feasibility of LLMs in this task. The current paper presents a pioneering LLM-based framework for facilitating automated abstract screening to fill this gap.

Our contributions can be summarised in three folds. (1) We proposed the first comprehensive LLM-assisted question-answering framework to facilitate automated abstract screening in a zero-shot setting. (2) We developed the first generalisable approach to utilising selection criteria to enhance abstract screening efficiency. (3) Our study marks the first comprehensive exploration of leveraging LLMs for reference prioritization in abstract screening, utilizing a well-known benchmark dataset to showcase the method's high potential.

Background Study

Automation in Abstract Screening

Efforts to automate systematic reviews using machine learning have surged recently. Kitchenham and Charters' presented a good survey of such attempts in software engineering [24]. In evidence-based medicine, Cohen et al. was the seminal work of abstract screening using machine learning [25], while Marshall and Wallace advocated active learning techniques for abstract screening [26]. Examples like RobotReviewer [27, 28] and TrialStreamer [29] showcased the power of integrating AI into the review process, with RobotReviewer claiming to reach accuracy comparable to human reviewers. Despite the progress, challenges persist, including labour-intensive labelling

and the risk of overlooking relevant studies [30]. Acknowledging the limitation of full automation, tools like Rayyan and Abstracker leverage natural language processing (NLP) algorithms to partially automate article screening [31].

Machine Learning for Abstract Screening

The biggest challenge is handling large document volumes, particularly in non-randomized controlled trials lacking database filters [32]. For instance, EPPI-Centre reviews often screen over 20,000 documents, necessitating more efficient approaches [33]. Efforts include refining search queries, balancing precision and recall, and leveraging resource-efficient recall-maximizing models with NLP [34].

The initial approach involves training a classifier to make explicit include/exclude decisions [25, 34, 35, 36, 37, 38, 39]. Many classifiers using this approach inherently generate a confidence score indicating the likelihood of inclusion or exclusion (similar to the ranking in the second approach). Generally, this approach requires a labelled dataset for training, hindering the assessment of work reduction until after manual screening. Research within this paradigm primarily focuses on enhancing feature extraction methods [25, 37] and refining classifiers [38]. Van Dinter et al. [8] analyzed 41 studies in medicine and software engineering, revealing Support Vector Machines and Bayesian Networks as standard models and Bag of Words and TF-IDF as prevalent natural language processing techniques. Despite advancements, a dearth of deep neural network models explicitly designed for the systematic review screening phase is noted. The most prominent challenges include handling extreme data imbalance favouring (at least close to) total recall of relevant studies.

Ranking Approaches to Abstract Screening

The second approach entails utilizing a ranking or prioritization system [9, 10, 11, 12, 13, 14, 15, 16, 33, 40]. This approach might necessitate manual screening by a reviewer until a specified criterion is met. This approach can also reduce the number of items needed to be screened when a cut-off criterion is properly established [33, 40, 41]. In addition to reducing the number needed to screen, other benefits of this approach include enhancing reviewers' understanding of inclusion criteria early in the process, starting full-text retrieval sooner, and potentially speeding up the screening process as confidence in relevance grows [7]. This prioritization approach also aids review updates, enabling quicker assimilation of current developments. Various studies reported benefits from prioritization for workflow improvement, emphasizing efficiency beyond reducing title and abstract screening workload [42, 43].

Active learning in Abstract Screening

It's crucial to note that the last approach, active learning, aligns with both strategies above [34, 33, 44]. This involves an iterative process to enhance machine predictions by interacting with reviewers. The machine learns from an initial set of include/exclude decisions human reviewers provide. Reviewers then judge a few new samples, and the machine adapts its decision rule based on this feedback. This iterative process continues until a specified stopping criterion is met. While the classifier makes final decisions for unscreened items, human screeners retain control over the training process and the point at which manual screening concludes. Wallace et al. implement active learning-based article screening using Support Vector Machines [34]. Notable tools include Abstrackr [36] and ASReview [45]. Various active learning strategies existed [7]. For instance, Marshall and Wallace [26] proposed a variant based on certainty, continuously training the classifier on manually screened articles and reordering unseen articles based on predicted relevance.

Large Language Models for Abstract Screening

Recent advancements in LLMs, notably demonstrated by ChatGPT (GPT-3.5 or 4.0), have brought about a revolutionary paradigm shift across disciplines [46, 47]. LLMs have shown impressive generalisability across diverse domains and strong zero-/few-shot reasoning capabilities [46, 48]. Leveraging LLMs holds promise for SRs, which, however, remains underexplored [7, 8]. This gap underscores the need for a comprehensive investigation into LLMs' potential in automating SRs, e.g., abstract screening in the current paper.

There are some initial attempts to evaluate ChatGPTs in automated SR, such as automating search queries [49]. Alshami et al. [50] leveraged GPT to automate the SR pipeline, yet their methodology diverges from conventional abstract screening practices, rendering it distinct from traditional approaches. The application of GPT in abstract screening has been scarcely explored. Only two studies tried to address it [51, 52]. However, these studies failed to achieve a high recall rate (preferably total or close to total recall, say 95% in most studies), a critical factor for practical applicability, and thus may cause a significant amount of missed information in the SR. In addition, these studies performed limited empirical studies on a small number of in-house datasets that were neither public nor common in the research community, making it even harder to do reliable effectiveness evaluations. In contrast, our paper introduces a novel approach by applying GPT for reference prioritization across a substantially larger dataset, significantly enhancing the method's applicability and effectiveness in systematic reviews.

Materials and Methods

Fig. 1: Illustration of LLM-assisted automated abstract screening.

Overview

Our framework utilizes GPT-3.5's zero-shot learning to assess if a candidate study's abstract aligns with the SR protocol's selection criteria. These criteria outline aspects of the selected studies. Figure 1 illustrates the idea using an example. The inclusion criteria contain four parts (in different colours). Each can be answered by matching the relevant information in the abstract (in corresponding colours). For instance, the selection criterion "We included qualitative studies" is answered by the text evidence "We conducted a qualitative study" (both in red). Theoretically, all inclusion criteria should be met for the study to be included in the SR.

The current paper frames automated abstract screening as a question-answering (QA) task and proposes to use LLMs like GPT-3.5 to solve it. LLMs have showcased impressive question-answering abilities across diverse domains and tasks, including encoding clinical knowledge and achieving success in medical licensing exams [53, 54, 55, 56]. Initially, we experimented with condensing the entire selection criteria into a single, comprehensive question, as depicted in Figure 2a. This method quickly showed its limitations, as LLMs are notably more adept at addressing well-defined, focused questions. Recognizing the critical need for high recall—95% or higher—to preserve the comprehensive integrity of the SR, we shifted our strategy. In our refined approach, each selection criterion is treated as a question to be addressed using LLMs. For example, the four selection criteria in Figure 1 are converted into questions $Q1$ to $Q4$ (by the LM-based Query Generator component in Figure 1). Subsequent prompts are directed to LLMs to get individual answers (from the LM-based Question Answerer), which are then combined into the final decision (through the Answer Scorer and Ensembler). Note that, in this example, $Q5$ is basically a useless, redundant question because we hard-coded ChatGPT to generate five questions.

Figure 2b formally defines our proposed QA framework for abstract screening. The following subsections will detail each component. We begin with a Question Generator to convert the selection criteria into a set of questions. Question generation is done by LLM. Optionally, question analysis may be done to analyse the logic between questions for the purpose of correctly combining question answers. Considering, for instance, that answers A_1 and A_2 for questions Q_1 and Q_2 represent an inclusion and exclusion criterion, respectively, and the correct combination is $A_1 \cap \neg A_2$. Subsequently, each question is addressed by a trained Question Answerer to determine if the corresponding selection criterion is met. Question answering is also done by LLM. Each question answer is converted into a numeric score, and question-level re-ranking will be applied to improve answer scores. While the current paper tried some primitive but effective ways for answer re-ranking, the framework is flexible enough to plug in more advanced re-ranking methods. Finally, the Decision Engine ensembles the answers to all questions (by aggregating answer scores), followed by an optional criteria-level re-ranking step to calibrate the final score for decision-making.

(a) Naive approach for LLM-based automated abstract screening using selection criteria

(b) An aspect-based approach for LLM-assisted automated abstract screening using selection criteria

Fig. 2: Methodological framework for LLM-assisted automation screening.

Question Generation

A substantial body of research exists on automated question generation from natural language text [57]. These methods often rely on manually crafted rules or a trained model, typically a fine-tuned pre-trained language model. While these question generation models have demonstrated utility in domain-specific tasks, such as generating questions about product descriptions for matching purchase inquiries [58] or creating questions about academic materials to assess learning outcomes [59], generalizing them to the vast diversity of SR topics presents challenges. Therefore, we entrust the question generation task to GPT-3.5.

A naive approach to question generation is to prompt GPT-3.5 to generate questions from the selection criteria paragraph. However, this uncontrolled method often generates numerous questions, many subsumed by others or deemed too trivial to be meaningful.

To enhance the quality of generated questions, we constrained GPT-3.5 to produce no more than K questions, aiming to minimize redundancy. Based on an analysis of the lengths of selection criteria in our datasets, $K = 5$ proved sufficient for most SRs. Each sentence in the selection criteria often aligns with a distinct criterion. In rare cases with more than 5 sentences, GPT-3.5 intelligently combined two sentences into one question. Figure 3a depicts the utilized prompt, and an example is shown in Figure 1.

Role: You are a researcher screening titles and abstracts of scientific papers.

Task: Using the inclusion criteria in the brackets generate 5 unique yes or no questions which encompasses the entire inclusion criteria without any duplicate or unneccessary questions to ascertain if papers meets the inclusion criteria!

Criteria:`{criteria}`

(a) Prompt for question generation

Role: You are a researcher screening titles and abstracts of scientific papers for the systematic review '{review_title}'

Task: Analyse the abstract below within the brackets and answer the question below. Taking a step-by-step approach towards reasoning and answering the question. The answer should be in either a positive, neutral, or negative sentiment format.

Abstract: `{abstract}`

Question: `{question}`

(b) Prompt for question answering

Fig. 3: Prompt design for LLM-assisted automated abstract screening

Question Answering

The Question Answerer evaluates the relevance of each abstract to every selection criterion, formulated as Yes/No questions. We prompt GPT-3.5 to return three types of responses Figure 3b:

- **Positive:** The abstract explicitly addresses the question, offering information that aligns with the criteria posed by the question.
- **Neutral:** The information in the abstract is inadequate or too ambiguous for GPT-3.5 to derive a confirmative answer.
- **Negative:** A clear NO answer to the question, indicating irrelevance to the specified criteria.

Answer Scoring

To address the challenge of interpreting GPT-3.5's occasionally lengthy responses, especially when abstracts lack sufficient information for clear answers, we converted answers into numeric representations using BART as a zero-shot sentiment scorer [60]. This adaptation reframes the question-answering task as a sentiment analysis problem: positive sentiment is assigned to "YES" answers, negative sentiment to "NO" answers, and neutral sentiment when the abstract provides inadequate information for a definitive answer. We formalise the problem as follows. Suppose the set of candidate studies are $D = \{d_i\}|_{d=1}^N$. The system review protocol defines a set of selection criteria (questions) $Q = \{Q_k\}|_{k=1}^K$. Given each candidate study d_i, the set of answers are $A_i = \{A_{i,k}\}|_{k=1}^K$.

Given a candidate study d_i and each question answer $A_{i,k}$, we defined two methods, namely the Hard Answer and Soft Answer, to assign the answer score, denoted as $score(d_i, A_{i,k})$, using BART, which reflects the likelihood of an abstract meeting a selection criterion.

- **Hard Answer:** In the Hard Answer method, BART classifies GPT-3.5's responses into three distinct categories: Positive, Neutral, and Negative, and accordingly we assign a fixed score 1, 0.5, and 0 to each category, denoted by $score(d_i, A_{i,k})$. Thus,

$$score(d_i, A_{i,k}) = \begin{cases} 1.0 & \text{if BART assigns a Positive sentiment to } A_{i,k} \\ 0.5 & \text{if BART assigns a Neutral sentiment to } A_{i,k} \\ 0.0 & \text{if BART assigns a Negative sentiment to } A_{i,k} \end{cases} \tag{1}$$

- **Soft Answer:** In the Soft Answer method, each answer is scored by the probability of its sentiment being positive, which is calculated by BART. Thus,

$$score(d_i, A_{i,k}) = Prob_{\text{BART}}(\text{Positive}|A_{i,k}). \tag{2}$$

Question-level Re-ranking

To enhance screening further, a significant contribution involves re-ranking candidate studies based on how well abstracts are semantically aligned with the selection criteria. We utilize cosine similarity to gauge the congruence between each abstract and the posed questions, thus augmenting the relevance assessment for each selection criterion. For each Yes/No query, the cosine similarity between the query and the abstract is computed based on their GPT-3.5 embeddings [61], and averaged with the original answer score, producing K re-ranked scores. The re-ranked score for each answer is defined by

$$score^*(d_i, A_{i,k}) = \frac{1}{2}(score(d_i, A_{i,k}) + cos(d_i, Q_k)), \tag{3}$$

where $cos(d_i, Q_k)$ is the cosine similarity between (the abstract of) the candidate study d_i and one selection criterion question Q_k.

Decision Engine

Ensemble

Given a candidate study d_i, the answer scores for each selection criterion are "averaged" as the score for the candidate study, denoted by $score(d_i)$:

$$score(d_i) = \frac{1}{K} \sum_{k=1}^{K} score^*(d_i, A_{i,k}). \tag{4}$$

Criteria-level Re-ranking

criteria-level re-ranking is done by averaging the score for candidate study d_i with the cosine similarity between its abstract and the selection criteria Q. Note that, here, we use the original selection criteria paragraph in the review protocol for calculation, instead of the questions generated from it. Thus, the re-ranked score for d_i, denoted by $score^*(d_i)$, is calculated by

$$score^*(d_i) = \frac{1}{2}(score(d_i) + cos(d_i, Q)), \tag{5}$$

where $cos(d_i, Q)$ is the cosine similarity between the candidate study and the complete selection criteria.

This final score provides a quantitative representation of the relevance of the abstract, based on which candidate studies are ranked in descending order.

Experimental Setup

Dataset and Evaluation Metrics

This study utilized the widely-used benchmark for evaluation: CLEF eHealth 2019 Task 2: Technology-Assisted Reviews in Empirical Medicine (TAR2019) [62]. This benchmark provides valuable insights into the prevailing scientific consensus on various topics, making it a suitable resource for evaluating re-ranking methodologies in systematic reviews [63]. We employed the TAR2019 test set comprising 31 SRs grouped into four topic categories: 20 about clinical intervention trials (Intervention), 8 about diagnostic technology assessment (DTA), 2 for qualitative studies (Qualitative), and 1 for Prognosis. Appendix A in the online supplementary material contains detailed statistics of the SRs in each category. We refrained from using the training set provided by TAR2019, aiming to highlight the effectiveness of our zero-shot methodology that eliminates the need for prior training [64, 23]. Selection criteria for each SR are included in TAR2019.

Seven evaluation metrics were employed, including the rank position of the last relevant document (L_Rel), Mean Average Precision (MAP), Recall at $k\%$ ($R@k\%$, $k = 5, 10, 20, 30$), and Work Saved Over Sampling (WSS) at $k\%$ ($WSS@k\%$, $k = 95, 100$). Notably, $WSS@k\%$ measures the screening workload saved by halting the examination process once $k\%$ of relevant documents are identified, compared to screening the entire document set [25]. For each SR, we calculated the performance metrics. They were averaged over all the SRs in each category.

Prompt Design

The model used for this methodology was "GPT-3.5-Turbo-16K" with the temperature set at 0.2. The creation of our prompts (Figure 3) was meticulously designed, utilizing three randomly selected topics from the Intervention training set of the TAR2019 benchmark. This approach safeguarded against any potential information leakage during the prompt development phase, ensuring the integrity of our methodology. Appendix B in the online supplementary material contains all the questions generated from the corresponding selection criteria for all SRs.

Baseline Models

We compared our methods against a number of zero-short baselines, including Sheffield University's submission [17] to TAR2019 and the six BERT-based ranking models by Wang et al. [23]. To comprehensively assess performance, we implemented two IR baselines of our own. One is cosine similarity between selection criteria and abstract based on GPT embeddings [61], named `GPT_Cos_Sim_Criteria`. The other is the classical IR approach `BM25` [65], using selection criteria as a query to rank candidate studies. The variants of our own approach are summarised below:

- `sheffield-baseline`: The zero-shot IR baseline submitted by the University of Sheffield to TAR2019.

- `QLM`: Another IR baseline in the Query Likelihood Model. See Wang et al. [23] for details.

- `BERT/BERT-M/BioBERT/BlueBERT/PubMedBERT`: Use BERT-family models as neural rankers, including BERT [66], BERT-M (BERT fine-tuned on the MS MARCO machine reading comprehension dataset) [67], and BERT models tailed to biomedical domains, such as BioBERT [68], BlueBERT [69] and PubMedBERT [70].

Results and Discussions

Effectiveness of Selection Criteria

Our first experiments aimed to evaluate the effectiveness of selection criteria for abstract screening. We used the cosine similarity between selection criteria and the candidate study's abstract (concatenated with the title) for ranking. For comparison, we also used review title and search queries, both included in the TAR2019 benchmark, for ranking in a similar way.

The initial results in Table 1 demonstrate that selection criteria contain indispensable information for abstract screening. For example, on the *Intervention* and *DTA* datasets, the top 5% ranked results covered 40.1% and 47.7% included studies, respectively, while the top 30% covered 79.7% and 85.1% included studies, respectively. This means selection criteria help to push a significant number of included studies to the front of the ranking lists, demonstrating its potential for prioritising candidate studies. The $WSS@95\%$ values mean that at most 52.2% and 60% manual screening time can be saved to achieve a 95% recall of included studies. On *Qualitative* datasets, $R@10\%$ was 47.8%, still very high, but the WSS values were not as good as on *Intervention* and *DTA*. $R@k\%$ started to stagnate when k grew (e.g., beyond 30%). This motivated the current paper to look for smarter ways of using selection criteria for abstract screening.

Dataset	Models	L_Rel	MAP	R@5%	R@10%	R@20%	R@30%	R@50%	WSS@95%	WSS@100%
Intervention	Review Title	927	0.344	0.441	0.596	0.758	0.836	0.929	0.560	0.519
	Search Query	1248	0.200	0.241	0.424	0.602	0.725	0.889	0.449	0.416
	Selection Criteria	920	0.315	0.401	0.544	0.722	0.797	0.797	0.522	0.499
DTA	Review Title	1379	0.170	0.283	0.497	0.678	0.807	0.926	0.525	0.446
	Search Query	1593	0.203	0.228	0.412	0.658	0.781	0.909	0.473	0.417
	Selection Criteria	1154	0.271	0.477	0.628	0.782	0.851	0.851	0.600	0.513
Qualitative	Review Title	1992	0.113	0.200	0.278	0.609	0.650	0.950	0.506	0.406
	Search Query	2221	0.046	0.105	0.173	0.255	0.591	0.923	0.369	0.329
	Selection Criteria	2256	0.082	0.173	0.478	0.559	0.618	0.618	0.303	0.289
Prognosis	Review Title	2983	0.136	0.147	0.258	0.495	0.668	0.837	0.247	0.106
	Search Query	3017	0.200	0.237	0.400	0.605	0.768	0.900	0.311	0.096
	Selection Criteria	3160	0.178	0.200	0.305	0.495	0.647	0.832	0.239	0.053

Table 1. The results of using three types of queries to match abstracts of candidate studies: selection criteria, review titles, and search queries.

Dataset	Papers	Models	L_Rel	MAP	R@5%	R@10%	R@20%	R@50%	WSS@95%	WSS@100%
Prognosis	Sheffield [17]	sheffield-baseline	2990	0.126	0.146	0.255	0.448	—	0.247	0.112
	Ours	GPT_Cos_Sim_Criteria	3160	0.178	0.200	0.305	0.495	0.832	0.239	0.053
		BM25	3337	0.074	0.089	0.132	0.279	0.605	0.020	0.000
		GPT_QA_Soft_Both_ReRank	2373	0.430	0.400	0.653	0.800	0.984	0.543	0.289
		GPT_QA_Hard_Both_ReRank	2333	0.429	0.400	0.642	0.789	0.984	0.555	0.301
Qualitative	Sheffield [17]	sheffield-baseline	3031	0.051	0.265	0.451	0.619	—	0.135	0.082
	Ours	GPT_Cos_Sim_Criteria	2256	0.082	0.173	0.478	0.559	0.682	0.303	0.289
		BM25	2704	0.037	0.078	0.146	0.191	0.623	0.135	0.135
		GPT_QA_Soft_Both_ReRank	1682	0.159	0.505	0.600	0.673	0.978	0.576	0.507
		GPT_QA_Hard_Both_ReRank	1684	0.157	0.514	0.600	0.678	0.978	0.601	0.507
DTA	Sheffield [17]	sheffield-baseline	2250	0.175	0.220	0.336	0.525	—	0.451	0.338
	Wang et al. [23]	BM25	2723	0.119	0.213	0.329	0.528	—	0.314	0.208
		QLM	2318	0.122	0.216	0.327	0.534	—	0.347	0.248
		BERT	2514	0.092	0.132	0.238	0.391	—	0.258	0.210
		BERT-M	3234	0.096	0.079	0.198	0.379	—	0.263	0.123
		BioBERT	3264	0.081	0.129	0.229	0.337	—	0.137	0.095
		BlueBERT	3771	0.069	0.026	0.053	0.105	—	0.023	0.016
		PubMedBERT	3330	0.104	0.123	0.214	0.312	—	0.202	0.098
	Ours	GPT_Cos_Sim_Criteria	1154	0.271	0.477	0.628	0.782	0.941	0.600	0.513
		BM25	2461	0.164	0.334	0.472	0.654	0.858	0.351	0.233
		GPT_QA_Soft_Both_ReRank	1136	0.315	0.438	0.593	0.766	0.941	0.556	0.506
		GPT_QA_Hard_Both_ReRank	1176	0.322	0.450	0.595	0.791	0.938	0.536	0.491
Intervention	Sheffield [17]	sheffield-baseline	1276	0.245	0.220	0.334	0.507	—	0.470	0.386
	Wang et al. [23]	BM25	1716	0.211	0.305	0.399	0.554	—	0.351	0.296
		QLM	1724	0.212	0.279	0.385	0.511	—	0.340	0.294
		BERT	1399	0.160	0.210	0.328	0.504	—	0.362	0.333
		BERT-M	1836	0.177	0.195	0.355	0.527	—	0.323	0.266
		BioBERT	1833	0.146	0.135	0.198	0.307	—	0.159	0.163
		BlueBERT	2057	0.046	0.028	0.051	0.107	—	0.008	0.036
		PubMedBERT	1974	0.078	0.050	0.091	0.275	—	0.121	0.094
	Ours	GPT_Cos_Sim_Criteria	920	0.315	0.401	0.544	0.722	0.920	0.552	0.499
		BM25	1545	0.146	0.191	0.300	0.497	0.837	0.270	0.238
		GPT_QA_Soft_Both_ReRank	801	0.450	0.526	0.697	0.816	0.959	0.600	0.526
		GPT_QA_Hard_Both_ReRank	825	0.447	0.527	0.697	0.808	0.962	0.592	0.519

Table 2. Overview and comparisons of model performances on four systematic review categories. Note that the baselines did not report $R@50\%$.

It is also observed that selection criteria significantly outperformed search query in ranking candidate studies on the *Intervention* and *DTA* datasets, according to most performance metrics, except for $R@50\%$. Overall, the review title seems to be most valuable for screening candidate studies, so it is also part of our prompt design (Fig. 3b). The Search query was less effective than the other two methods. Indeed, the impreciseness of search queries resulted in a large number of studies being screened. The only exception was *Prognosis* but the fact that the *Prognosis* category contains just one SR does not allow us to overturn the afore-made overall statements.

Acknowledging such contextual variability inherent in the initial results is crucial. The nature of the dataset appears to play a substantial role in the effectiveness of selection criteria. For instance, datasets with more specific interventions or defined methodologies, like *DTA*, may inherently align more closely with selection criteria, enhancing the performance of this query type in prioritisation. In conclusion, the above evidence advocates for the integration of selection criteria in citation screening automation tools. The findings also encourage further exploration into hybrid models that might integrate the strengths of various query types, with a particular emphasis on adapting the approach according to the specificity and context of the dataset being analysed.

Effectiveness of the Question-Answering Framework

In this subsection, we summarise the main findings from the experimental results. Table 2 compares our QA-based approaches (i.e., the `GPT_QA_Soft_Both_ReRank` and `GPT_QA_Hard_Both_ReRank` two rows) against other zero-shot baselines. "Both_ReRank" means both re-raking methods were used. The `GPT_Cos_Sim_Criteria` rows copy the baseline results using selection criteria in Table 1. Consistent with the baselines, we reported the average performances of each metric for each topic category. Appendix C contains the results for each

individual SR. On four topic categories, our approaches outperformed almost all baselines across a multitude of metrics. Specifically, our approaches scored substantially better in L_Rel (the lower the better) and MAP (the higher the better), indicating the potential for pruning irrelevant studies more efficiently and accurately. Moreover, $WSS@95\%$ and $WSS@100\%$ both significantly outperformed the baselines, except `Cosine_Similarity_Criteria` on DTA, indicating the potential for saving more work from human reviewers who seek a total or close-to-total recall of included studies.

The recall values at various percentages ($R@5\%$, $R@10\%$, $R@20\%$) were particularly encouraging. Notably, $R@5\%$ shows that the top-5% ranked results covered more than 40% (40%-52.7%) of included studies (e.g., by `GPT_QA_Hard_Both_ReRank` 52.7% on *Intervention*, 45% on *DTA*, 51.4% on *Qualitative* and 40% on *Prognosis*). When increased to top-10%, roughly 60-70% of included studies were returned (e.g., 69.7%, 59.5%, 60% and 64.2% respectively). This result is of great significance. On the one hand, human reviewers could obtain 60% of included studies by verifying only 10% of candidate studies, a five times saving compared to random sampling. This allows for **creating a large-enough annotated dataset more efficiently** to train a robust classifier for automated screening [25]. On the other hand, $R@50\%$ achieved 95% recall on average. This roughly means that the 50% of candidate studies ranked in the second half can be safely discarded, which essentially means treating **LLM as the second reviewer**, or be delegated to automated screening, both resulting in a 50% saving in manual annotation. Future work is needed for validating the proposal of LLM as second reviewer on more SRs of a wider range of topics.

In summary, our QA-based approach exhibited a clear advantage over traditional models and bespoke BERT-family models that were fine-tuned for ranking tasks (i.e., from the BERT to PubMedBERT rows in Table 2). They showed not only a higher precision in retrieving relevant studies but also a substantial increase in efficiency, demonstrated by lower L_Rel and higher WSS values. This indicates that the proposed approach has the potential to significantly improve the efficiency and reduce the costs for systematic reviews by alleviating much of the manual annotation burden from human reviewers.

Ablation Studies

Models	MAP					WSS@95%				
	Prognosis	Qualitative	DTA	Intervention	Average	Prognosis	Qualitative	DTA	Intervention	Average
GPT_Cos_Sim_Criteria	0.178	0.082	0.271	0.315	0.286	0.239	0.303	0.600	0.552	0.536
GPT_Cos_Sim_Question	0.188	0.074	0.233	0.261	0.239	0.269	0.283	0.554	0.456	0.464
GPT_Cos_Sim_Both	0.191	0.084	0.261	0.309	0.278	0.252	0.310	0.602	0.544	0.534
GPT_QA_Soft	0.350	0.157	0.255	0.411	0.352	0.434	0.599	0.408	0.486	0.471
GPT_QA_Hard	0.315	0.110	0.228	0.356	0.306	0.417	0.650	0.364	0.466	0.450
GPT_QA_Soft_Criteria_ReRank	0.417	0.159	0.301	0.440	0.385	0.523	0.595	0.473	0.534	0.522
GPT_QA_Hard_Criteria_ReRank	0.417	0.200	0.310	0.443	0.392	0.543	0.608	0.454	0.532	0.517
GPT_QA_Soft_Question_ReRank	0.441	0.161	0.287	0.435	0.379	0.252	0.599	0.452	0.509	0.492
GPT_QA_Hard_Question_ReRank	0.452	0.156	0.297	0.435	0.382	0.501	0.633	0.441	0.516	0.503
GPT_QA_Soft_Both_ReRank	0.430	0.159	0.315	0.450	0.396	0.543	0.576	0.556	0.600	0.585
GPT_QA_Hard_Both_ReRank	0.429	0.157	0.322	0.447	0.395	0.555	0.601	0.536	0.592	0.577

Table 3. Results of ablation study by removing one or several components from the processed question-answering framework.

Recall from Figure 2b that there are several components in our proposed framework. Question generation, question answering, question-level re-ranking and criteria-level re-ranking. Table 2 shows the results of `GPT_QA_Soft/Hard_Both_ReRank`, which uses all these components. This subsection investigates the impact of each component through a quasi-ablation study. We removed the one or both re-ranking components, and then further removed the question answering and question generation components, and compared the performances of the resulting methods. Thus in addition to `GPT_QA_Soft/Hard_Both_ReRank`, we tested the following variants.

- `GPT_QA_Soft/Hard_Question_ReRank`: Criteria-level re-ranking component was removed. Mathematically, this is equivalent to removing $cos(d_i, Q_k)$ from Eq. (3).

- `GPT_QA_Soft/Hard_Criteria_ReRank`: Question-level re-ranking component was removed. Mathematically, this is equivalent to removing $cos(d_i, Q)$ from Eq. (5).

- `GPT_QA_Soft/Hard`: Both question-level and criteria-level re-ranking components were removed.

- `GPT_Cos_Sim_Both`: Questions were generated but the question answering component was removed. Both the question-level and criteria-level cosine similarities were used in scoring candidate studies. Mathematically, this means removing $score(d_i, A_{i,k})$ from Eq. (3).

- `GPT_Cos_Sim_Question`: In addition to question answering, the criteria-level re-ranking component was also removed. This is equivalent to removing both $cos(d_i, Q)$ from Eq. (5) and $score(d_i, A_{i,k})$ from Eq. (3).

- `GPT_Cos_Sim_Criteria`: The question generation component was removed, thus no questions were generated. Implicitly, the question answering and question-level re-ranking components disappeared too. This means retreating to match each candidate study against the selection criteria. Mathematically, this is equivalent to removing $(score(d_i)$ from Eq. (5).

Table 3 shows the results of the ablation study. Due to space limit, we focused on three metrics: MAP, $R@50\%$ and $WSS@95\%$. From the `GPT_QA_Soft/Hard` rows we can see that our QA framework resulted in good performances, improving significantly over the non-QA baselines (first three rows) on *Intervention*, *Qualitative* and *Prognosis*. The last six rows are the performances of our framework by using either one or two re-ranking methods. Comparing them against `GPT_QA_Soft/Hard`, we see that re-ranking was key to significant performance improvement, although it is less conclusive which re-ranking method is consistently better. To gain better insights into the latter question, we averaged the performance metrics across all 31 SRs, resulting in the "Average" columns in the table. It looks that criteria-level re-ranking is in overall stronger than question-level re-ranking (by comparing the `GPT_QA_Soft/Hard_Criteria_ReRank` rows against the `GPT_QA_Soft/Hard_Question_ReRank` rows). By comparing the `GPT_QA_Soft/Hard_Both_ReRank` rows against the four rows using one re-ranking methods, we are more or less able to conclude that both re-ranking methods may have their own values in prioritising candidate studies towards facilitating systematic reviews. Meanwhile, we point out that more experiments need be done on more SRs of the *Qualitative* and *Prognostic* categories to draw more convincing conclusions on the effectiveness of the two methods of answer re-ranking, which is one of our directions for future work. Surprisingly, we found that the non-QA baselines (i.e., the `GPT_Cos_Sim_Criteria/Question/Both` rows) worked extremely well on *DTA*, beating the baseline QA approaches (i.e., the `GPT_QA_Soft/Hard` rows). After analysing the qualities of generated questions for the *DTA* SRs, we guess the cause was the quality or complexity of generated questions of this SR categor (more discussions in the "Quality of Question Generation" subsection). Nevertheless, re-ranking methods and QA approaches complement each other. This is proved by the significantly improved performances obtained by `GPT_QA_Soft/Hard_Both_ReRank` (i.e., the last two rows).

Quality of Question Generation

We manually checked the question qualities and found notable strengths and occasional challenges of GPTs in question generation. Figure 4a illustrates how GPT-3.5 translated a lengthy exclusion criterion into two relevant questions, Q_4 and Q_5. The exclusion criterion sentence (in purple and blue) was automatically reworded by GPT-3.5 (see the underlined words) in a way that a POSITIVE response consistently signifies compliance with a selection criterion. Occasionally, GPT-3.5 failed to generate completely independent questions, such as Q_5 in Figure 1. This led to redundant or overlapped questions, introducing possible biases in combining answer scores.

(a) Handling exclusion criteria.

(b) Problems with "OR" clauses.

Fig. 4: Examples of strengths and challenges of GPT-3.5 in question generation.

To avoid these issues, question generation may be done by human. Less radically, it may be practical for human to separate the selection criterion sentences and use each sentence to generate questions one by one. Humans may also manually decide how to convert a long selection criterion sentence into several questions. Part of our future work is to investigate the impact of these choices on the quality of question generation and whether GPTs can still correctly form questions for exclusion criteria in these circumstances.

Notably, GPT-3.5 also displayed difficulties with complex "OR" clauses in a long selection criterion sentence, erroneously splitting them into separate questions and complicating the scoring process. In such cases, matching one question should give a POSITIVE score, but the NEGATIVE answers to other questions generated from the OR clause might underestimate the score. Figure 4b shows an example. A single selection criterion sentence with three conditions connected by "OR" logic was split into three questions Q_2 to Q_4. Suppose a candidate study "evaluated the accuracy of the NEXUS criteria" and three questions are correctly answered. This result in one POSITIVE answer for Q_2 (scored 1) and two NEGATIVE answers for Q_3 and Q_4 (scored 0). The ensemble score is 1, lower than that by rejecting to answer Q_3 and Q_4 (two NEUTRAL answers, each scored 0.5, lead to a final score of 2), which is obviously suboptimal. This granularity of analysis points toward a need for enhancing the model's ability to discern and maintain the integrity of compound logical structures within questions. We postulate that a viable solution is to train a good question generator and analyzer to tackle these issues.

To somehow provide a quantitative evaluation of the quality of question generation, we manually annotated the "correctness" of all generated questions for all 31 SRs. The simple guidelines for scoring generated questions are as follows: 2 marks assigned to perfect question (e.g., Q_1 to Q_4 in Figure 1); 1 mark assigned to incomplete question, i.e., a question missing some information from the corresponding selection criterion; 1 mark assigned to each question generated from an "OR" clause (e.g., Q_2 to Q_4 in Figure 2b); 0 mark assigned to meaningless/redundant question (e.g., Q_5 in Figure 1); and -1 mark to wrong question, i.e., a question twisted the original meaning of the corresponding criterion, which never happened in our datasets though. Table 4 shows the four topic categories' mean question scores, which should range between -1 (all questions are wrong) to 2 (all questions are perfect). *DTA* recorded the lowest

score 1.50, which might be the cause the under-performance of our QA framework to our own cosine similarity baseline using selection criteria, due to the reasons stated in the last paragraph. Nevertheless, the mean score is still very high, indicating no or few meaningless questions. *Prognosis* scored perfectly in question generation. However, it's crucial to note that this category comprised only a single SR, potentially causing bias evaluation. We argue that the findings underscore the possibility of delegating question generation to LLMs like GPT-3.5, though the quality may be further improved by human intervention as a quality control measure. Besides it is of high potential to refine GPT-3.5 through training a targeted question generator and analyser that can adeptly handle the intricacies of SR criteria and understand the logic of complex questions.

Datasets	Mean Question Score
Prognosis	2.00
Qualitative	1.60
DTA	1.50
Intervention	1.57

Table 4. Quality evaluation of the automatically generated selection criterion questions by GPT-3.5.

While the focus thus far has been on producing straightforward answers, the integration of explanatory narratives into GPT-3.5's responses is advocated for future iterations. As per literature [71, 72], revealing the model's reasoning could not only bolster transparency but also build user trust, pivotal for the adoption of automated abstract screening tools. Enabling the model to provide rationales for its answers encourages a constructive feedback loop, where user responses can inform continuous model refinement. Such an iterative process is essential for fostering a collaborative user-model relationship, ultimately enhancing the technology's robustness and acceptability.

Conclusion

This paper proposed an effective LLM-assisted question-answering framework to facilitate abstract screening and advance automated systematic review. Our framework starts with converting selection criteria to binary questions, answering and scoring questions using LLMs like GPT-3.5, adjusting answer scores using both question-level and criteria-level re-rankings, and combining answer scores to prioritise candidate studies. Extensive experiments emphasized the particular pertinence of selection criteria of included studies to automated abstract screening and GPT-3.5's proficiency in understanding and utilizing selection criteria to prioritize candidate studies, significantly outperforming other zero-shot baselines. Specifically, GPT-3.5 was able to handle the complexity of a mixture of inclusion and exclusion criteria by correctly phrasing the questions. The overall quality of question generation was very high based on human verification. However, it faces some challenges when formulating several juxtaposed criteria with a logical OR relationship. The positive results of L_{Rel} (position of the last relevant study), $R@5\%$ (recall at top 5%), $R@10\%$, $WSS@95\%$ (Workload Saved over Sampling at 95% recall level), and $WSS@100\%$ not only showed the competency of the proposed framework as a zero-shot abstract screening methodology but also indicated its potential use in reducing human effort in building a high-quality dataset for training a abstract screener. Thanks to the high $R@95\%$ (mostly $> 95\%$), we conjecture that LLMs can replace the second reviewer by more or less safely cutting 50% from human reviewing, although large-scale validation studies are needed.

Funding Statement

Opeoluwa Akinseloyin is fully funded by a PhD scholarship at Coventry University. Xiaorui Jiang is partially supported by the National Planning Office of Philosophy and Social Science of China (18ZDA238), the International Exchange Scheme of the Royal Society of the United Kingdom (IESR1231175), and the Research Excellence Development Framework award of Coventry University (Nov 2023—July 2024).

Competing Interests Statement

There are no competing interests to declare.

Contributorship Statement

According to the CRediT tool, the author's contribution is as follows. Opeoluwa Akinseloyin: Conceptualization, Methodology, Software, Validation, Investigation, Data Curation, Writing - Original Draft, Writing - Review & Editing. Xiaorui Jiang: Conceptualization, Resources, Writing - Original Draft, Visualization, Supervision, Project administration, Funding acquisition, Writing - Review & Editing. Vasile Palade: Conceptualization, Supervision, Writing - Original Draft, Writing - Review & Editing.

Data Availability statement

The benchmark on which the experiments were done is publicly available at https://github.com/CLEF-TAR/tar/tree/master/2019-TAR/Task2. The data underlying this article are available in the article and in its online supplementary material.

References

1. Guy Tsafnat, Paul Glasziou, Miew Keen Choong, Adam Dunn, Filippo Galgani, and Enrico Coiera. Systematic review automation technologies. *Systematic reviews*, 3:1–15, 2014.

2. S Gopalakrishnan and P Ganeshkumar. Systematic reviews and meta-analysis: understanding the best evidence in primary healthcare. *Journal of family medicine and primary care*, 2(1):9, 2013.

3. Hamideh Moosapour, Farzane Saeidifard, Maryam Aalaa, Akbar Soltani, and Bagher Larijani. The rationale behind systematic reviews in clinical medicine: a conceptual framework. *Journal of Diabetes & Metabolic Disorders*, 20:919–929, 2021.

4. Ian Shemilt, Nada Khan, Sophie Park, and James Thomas. Use of cost-effectiveness analysis to compare the efficiency of study identification methods in systematic reviews. *Systematic reviews*, 5:1–13, 2016.

5. Matthew Michelson and Katja Reuter. The significant cost of systematic reviews and meta-analyses: a call for greater involvement of machine learning to assess the promise of clinical trials. *Contemporary clinical trials communications*, 16:100443, 2019.

6. Julian PT Higgins, Sally Green, et al. Cochrane handbook for systematic reviews of interventions. 2008.

7. Alison O'Mara-Eves, James Thomas, John McNaught, Makoto Miwa, and Sophia Ananiadou. Using text mining for study identification in systematic reviews: a systematic review of current approaches. *Systematic reviews*, 4(1):1–22, 2015.

8. Raymon van Dinter, Bedir Tekinerdogan, and Cagatay Catal. Automation of systematic literature reviews: A systematic literature review. *Information and Software Technology*, 136:106589, 2021.

9. Amal Alharbi, William Briggs, and Mark Stevenson. Retrieving and ranking studies for systematic reviews: University of sheffield's approach to clef ehealth 2018 task 2. In *CEUR workshop proceedings*, volume 2125. CEUR Workshop Proceedings, 2018.

10. Amal Alharbi and Mark Stevenson. Ranking abstracts to identify relevant evidence for systematic reviews: The university of sheffield's approach to clef ehealth 2017 task 2. In *Clef (working notes)*, 2017.

11. Gordon V Cormack and Maura R Grossman. Technology-assisted review in empirical medicine: Waterloo participation in clef ehealth 2017. *CLEF (working notes)*, 11, 2017.

12. Gordon V Cormack and Maura R Grossman. Systems and methods for conducting a highly autonomous technology-assisted review classification, March 12 2019. US Patent 10,229,117.

13. Maura R Grossman and Gordon V Cormack. Technology-assisted review in e-discovery can be more effective and more efficient than exhaustive manual review. *Richmond Journal of Law & Technology*, 17(3):11, 2011.

14. Maura R Grossman, Gordon V Cormack, and Adam Roegiest. Automatic and semi-automatic document selection for technology-assisted review. In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 905–908, 2017.

15. Grace E Lee and Aixin Sun. Seed-driven document ranking for systematic reviews in evidence-based medicine. In *The 41st international ACM SIGIR conference on research & development in information retrieval*, pages 455–464, 2018.

16. Harrisen Scells, Guido Zuccon, Anthony Deacon, and Bevan Koopman. Qut ielab at clef ehealth 2017 technology assisted reviews track: initial experiments with learning to rank. In *Working Notes of CLEF 2017-Conference and Labs of the Evaluation Forum [CEUR Workshop Proceedings, Volume 1866]*, pages 1–6. Sun SITE Central Europe, 2017.

17. Amal Alharbi and Mark Stevenson. Ranking studies for systematic reviews using query adaptation: University of sheffield's approach to clef ehealth 2019 task 2 working notes for clef 2019. In *Working Notes of CLEF 2019-Conference and Labs of the Evaluation Forum*, volume 2380. CEUR Workshop Proceedings, 2019.

18. Harrisen Scells, Guido Zuccon, Bevan Koopman, Anthony Deacon, Leif Azzopardi, and Shlomo Geva. Integrating the framing of clinical questions via pico into the retrieval of medical literature for systematic reviews. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management*, pages 2291–2294, 2017.

19. Shuai Wang, Harrisen Scells, Ahmed Mourad, and Guido Zuccon. Seed-driven document ranking for systematic reviews: A reproducibility study. In *European Conference on Information Retrieval*, pages 686–700. Springer, 2022.

20. Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

21. Oana Frunza, Diana Inkpen, Stan Matwin, William Klement, and Peter O'blenis. Exploiting the systematic review protocol for classification of medical abstracts. *Artificial intelligence in medicine*, 51(1):17–25, 2011.

22. Kentaro Matsui, Tomohiro Utsumi, Yumi Aoki, Taku Maruki, Masahiro Takeshima, and Takaesu Yoshikazu. Large language model demonstrates human-comparable sensitivity in initial screening of systematic reviews: A semi-automated strategy using gpt-3.5. *Available at SSRN 4520426*.

23. Shuai Wang, Harrisen Scells, Bevan Koopman, and Guido Zuccon. Neural rankers for effective screening prioritisation in medical systematic review literature search. In *Proceedings of the 26th Australasian Document Computing Symposium*, pages 1–10, 2022.

24. Barbara Kitchenham and Pearl Brereton. A systematic review of systematic review process research in software engineering. *Information and software technology*, 55(12):2049–2075, 2013.

25. Aaron M Cohen, William R Hersh, Kim Peterson, and Po-Yin Yen. Reducing workload in systematic review preparation using automated citation classification. *Journal of the American Medical Informatics Association*, 13(2):206–219, 2006.

26. Iain J Marshall and Byron C Wallace. Toward systematic review automation: a practical guide to using machine learning tools in research synthesis. *Systematic reviews*, 8:1–10, 2019.

27. Iain J Marshall, Joël Kuiper, Edward Banner, and Byron C Wallace. Automating biomedical evidence synthesis: Robotreviewer. In *Proceedings of the conference. Association for Computational Linguistics. Meeting*, volume 2017, page 7. NIH Public Access, 2017.

28. Iain J Marshall, Joël Kuiper, and Byron C Wallace. Robotreviewer: evaluation of a system for automatically assessing bias in clinical trials. *Journal of the American Medical Informatics Association*, 23(1):193–201, 2016.

29. Iain J Marshall, Benjamin Nye, Joël Kuiper, Anna Noel-Storr, Rachel Marshall, Rory Maclean, Frank Soboczenski, Ani Nenkova, James Thomas, and Byron C Wallace. Trialstreamer: A living, automatically updated database of clinical trial reports. *Journal of the American Medical Informatics Association*, 27(12):1903–1912, 2020.

30. Carlos Francisco Moreno-Garcia, Chrisina Jayne, Eyad Elyan, and Magaly Aceves-Martins. A novel application of machine learning and zero-shot classification methods for automated abstract screening in systematic reviews. *Decision Analytics Journal*, page 100162, 2023.

31. Mourad Ouzzani, Hossam Hammady, Zbys Fedorowicz, and Ahmed Elmagarmid. Rayyan—a web and mobile app for systematic reviews. *Systematic reviews*, 5:1–10, 2016.

32. Tanja Bekhuis and Dina Demner-Fushman. Screening nonrandomized studies for medical systematic reviews: a comparative study of classifiers. *Artificial intelligence in medicine*, 55(3):197–207, 2012.

33. Ian Shemilt, Antonia Simon, Gareth J Hollands, Theresa M Marteau, David Ogilvie, Alison O'Mara-Eves, Michael P Kelly, and James Thomas. Pinpointing needles in giant haystacks: use of text mining to reduce impractical screening workload in extremely large scoping reviews. *Research Synthesis Methods*, 5(1):31–49, 2014.

34. Byron C Wallace, Thomas A Trikalinos, Joseph Lau, Carla Brodley, and Christopher H Schmid. Semi-automated screening of biomedical citations for systematic reviews. *BMC bioinformatics*, 11(1):1–11, 2010.

35. Stan Matwin, Alexandre Kouznetsov, Diana Inkpen, Oana Frunza, and Peter O'Blenis. A new algorithm for reducing the workload of experts in performing systematic reviews. *Journal of the American Medical Informatics Association*, 17(4):446–453, 2010.

36. Byron C Wallace, Kevin Small, Carla E Brodley, Joseph Lau, and Thomas A Trikalinos. Deploying an interactive machine learning system in an evidence-based practice center: abstrackr. In *Proceedings of the 2nd ACM SIGHIT international health informatics symposium*, pages 819–824, 2012.

37. Georgios Kontonatsios, Sally Spencer, Peter Matthew, and Ioannis Korkontzelos. Using a neural network-based feature extraction method to facilitate citation screening for systematic reviews. *Expert Systems with Applications: X*, 6:100030, 2020.

38. Raymon van Dinter, Cagatay Catal, and Bedir Tekinerdogan. A decision support system for automating document retrieval and citation screening. *Expert Systems with Applications*, 182:115261, 2021.

39. Xiaonan Ji, Alan Ritter, and Po-Yin Yen. Using ontology-based semantic similarity to facilitate the article screening process for systematic reviews. *Journal of biomedical informatics*, 69:33–42, 2017.

40. David Martinez, Sarvnaz Karimi, Lawrence Cavedon, and Timothy Baldwin. Facilitating biomedical systematic reviews using ranked text retrieval and classification. In *Australasian document computing symposium (adcs)*, pages 53–60, 2008.

41. James Thomas and Alison O'Mara-Eves. How can we find relevant research more quickly? *NCRM Newsletter: MethodsNews*, 2011.

42. Aaron M Cohen, Kyle Ambert, and Marian McDonagh. Cross-topic learning for work prioritization in systematic review creation and update. *Journal of the American Medical Informatics Association*, 16(5):690–704, 2009.

43. Aaron M Cohen, Kyle Ambert, and Marian McDonagh. Studying the potential impact of automated document classification on scheduling a systematic review update. *BMC medical informatics and decision making*, 12:1–11, 2012.

44. Byron C Wallace, Kevin Small, Carla E Brodley, Joseph Lau, Christopher H Schmid, Lars Bertram, Christina M Lill, Joshua T Cohen, and Thomas A Trikalinos. Toward modernizing the systematic review pipeline in genetics: efficient updating via data mining. *Genetics in medicine*, 14(7):663–669, 2012.

45. Rens Van De Schoot, Jonathan De Bruin, Raoul Schram, Parisa Zahedi, Jan De Boer, Felix Weijdema, Bianca Kramer, Martijn Huijts, Maarten Hoogerwerf, Gerbrich Ferdinands, et al. An open source machine learning framework for efficient and transparent systematic reviews. *Nature machine intelligence*, 3(2):125–133, 2021.

46. Murray Shanahan. Talking about large language models. *arXiv preprint arXiv:2212.03551*, 2022.

47. Ce Zhou, Qian Li, Chen Li, Jun Yu, Yixin Liu, Guangjing Wang, Kai Zhang, Cheng Ji, Qiben Yan, Lifang He, et al. A comprehensive survey on pretrained foundation models: A history from bert to chatgpt. *arXiv preprint arXiv:2302.09419*, 2023.

48. Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*, 55(9):1–35, 2023.

49. Shuai Wang, Harrisen Scells, Bevan Koopman, and Guido Zuccon. Can chatgpt write a good boolean query for systematic review literature search? *arXiv preprint arXiv:2302.03495*, 2023.

50. Ahmad Alshami, Moustafa Elsayed, Eslam Ali, Abdelrahman EE Eltoukhy, and Tarek Zayed. Harnessing the power of chatgpt for automating systematic review process: Methodology, case study, limitations, and future directions. *Systems*, 11(7):351, 2023.

51. Eugene Syriani, Istvan David, and Gauransh Kumar. Assessing the ability of chatgpt to screen articles for systematic reviews. *arXiv preprint arXiv:2307.06464*, 2023.

52. Eddie Guo, Mehul Gupta, Jiawen Deng, Ye-Jean Park, Mike Paget, and Christopher Naugler. Automated paper screening for clinical reviews using large language models. *arXiv preprint arXiv:2305.00844*, 2023.

53. Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. *Advances in neural information processing systems*, 35:22199–22213, 2022.

54. Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744, 2022.

55. Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, et al. Large language models encode clinical knowledge. *arXiv preprint arXiv:2212.13138*, 2022.

56. Aidan Gilson, Conrad W Safranek, Thomas Huang, Vimig Socrates, Ling Chi, Richard Andrew Taylor, David Chartash, et al. How does chatgpt perform on the united states medical licensing examination? the implications of large language models for medical education and knowledge assessment. *JMIR Medical Education*, 9(1):e45312, 2023.

57. Ruqing Zhang, Jiafeng Guo, Lu Chen, Yixing Fan, and Xueqi Cheng. A review on question generation from natural language text. *ACM Transactions on Information Systems (TOIS)*, 40(1):1–43, 2021.

58. Yang Deng, Wenxuan Zhang, Qian Yu, and Wai Lam. Product question answering in e-commerce: A survey. *arXiv preprint arXiv:2302.08092*, 2023.

59. Xiangjue Dong, Jiaying Lu, Jianling Wang, and James Caverlee. Closed-book question generation via contrastive learning. *arXiv preprint arXiv:2210.06781*, 2022.

60. Nehal Muthukumar. Few-shot learning text classification in federated environments. In *2021 Smart Technologies, Communication and Robotics (STCR)*, pages 1–3. IEEE, 2021.

61. Ryan Greene, Ted Sanders, Lilian Weng, and Arvind Neelakantan, Dec 2022.

62. Evangelos Kanoulas, Dan Li, Leif Azzopardi, and Rene Spijker. Clef 2019 technology assisted reviews in empirical medicine overview. In *CEUR workshop proceedings*, volume 2380, page 250, 2019.

63. Giorgio Maria Di Nunzio and Evangelos Kanoulas. Special issue on technology assisted review systems, 2023.

64. Alessio Molinari and Evangelos Kanoulas. Transferring knowledge between topics in systematic reviews. *Intelligent Systems with Applications*, 16:200150, 2022.

65. Stephen Robertson, Hugo Zaragoza, et al. The probabilistic relevance framework: Bm25 and beyond. *Foundations and Trends® in Information Retrieval*, 3(4):333–389, 2009.

66. Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

67. Luyu Gao, Zhuyun Dai, and Jamie Callan. Rethink training of bert rerankers in multi-stage retrieval pipeline. In *Advances in Information Retrieval: 43rd European Conference on IR Research, ECIR 2021, Virtual Event, March 28–April 1, 2021, Proceedings, Part II 43*, pages 280–286. Springer, 2021.

68. Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. Biobert: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240, 2020.

69. Yifan Peng, Shankai Yan, and Zhiyong Lu. Transfer learning in biomedical natural language processing: an evaluation of bert and elmo on ten benchmarking datasets. *arXiv preprint arXiv:1906.05474*, 2019.

70. Yu Gu, Robert Tinn, Hao Cheng, Michael Lucas, Naoto Usuyama, Xiaodong Liu, Tristan Naumann, Jianfeng Gao, and Hoifung Poon. Domain-specific language model pretraining for biomedical natural language processing. *ACM Transactions on Computing for Healthcare (HEALTH)*, 3(1):1–23, 2021.

71. Annette M O'Connor, Guy Tsafnat, James Thomas, Paul Glasziou, Stephen B Gilbert, and Brian Hutton. A question of trust: can we build an evidence base to gain trust in systematic review automation technologies? *Systematic reviews*, 8(1):1–8, 2019.

72. Xiaorui Jiang. Trustworthiness of systematic review automation: An interview at coventry university. 2022.