MOLGENIS VIP: an open-source and modular pipeline for high-throughput and integrated DNA variant analysis

Authors

W.T.K. Maassen[1,2], L.F. Johansson[1,2], B. Charbon[1,2], D. Hendriksen[1,2], S. van den Hoek[1,2], M.K. Slofstra[1,2], R. Mulder[2], M.T. Meems-Veldhuis[2], R. Sietsma[1,2], H.H. Lemmink[2], C.C. van Diemen[2], M.E. van Gijn[3], M.A. Swertz[1,2], K.J. van der Velde[1,2]

Affiliations

1. Genomics Coordination Center, University of Groningen and University Medical Center Groningen, Antonius Deusinglaan 1, 9713 AV, Groningen, The Netherlands.
2. Department of Genetics, University of Groningen and University Medical Center Groningen, Antonius Deusinglaan 1, 9713 AV, Groningen, The Netherlands.
3. Amsterdam UMC Genome Diagnostics (AGDx), Dept of Human Genetics, Amsterdam UMC, AGDx, Meibergdreef 9, 1105 AZ Amsterdam, Department of Genetics, University Medical Centre Groningen, University Groningen, Groningen, Netherlands.

Abstract

In silico variant interpretation pipelines are an integral part in research and genome diagnostics. However, challenges still remain for automated variant interpretation and candidate shortlisting. For instance, reliability is affected by variability in input data caused by different sequencing platforms, erroneous nomenclature and changing experimental conditions. Similarly, differences in predictive algorithms could result in discordant results and scalability is essential to accommodate large amounts of input data, such as Whole Genome Sequencing (WGS). To accelerate causal variant detection and innovation in genome diagnostics and research, we developed the MOLGENIS Variant Interpretation Pipeline (VIP). VIP is a flexible and open-source computational pipeline to generate interactive reports of variants in Whole Exome Sequencing (WES) and WGS data for expert interpretation. VIP is applicable to short- and long-read data from different platforms and offers tools for increased sensitivity. For this purpose, a configurable decision tree, filters based on Human Phenotype Ontology (HPO) and gene inheritance can be used to pinpoint disease-causing variants or to finetune a query for specific variants. Additionally, we present a step-by-step protocol describing how to use VIP to annotate, classify and filter genetic variants of patients with a rare disease that has a suspected genetic cause. Finally, we demonstrate how VIP performs using 25,664 previously classified variants from the Data Sharing initiative of the Vereniging van Klinisch Genetische Laboratoriumdiagnostiek (VKGL), a cohort of 18 patients from routine diagnostics and a cohort of 41 patients with a rare diseases (RD) that were not diagnosed in routine diagnostics but were solved within the EU wide project to solve rare diseases (EU-Solve-RD) using novel omics approaches. The protocol requires bioinformatic knowledge to configure and afterwards every diagnostic professional is able to perform an analysis within 5 hours.

Introduction

The field of clinical genetics focuses on the identification of genetic variants that cause disease. By understanding the pathogenesis of genetic diseases, we can provide patients with a prognosis and appropriate treatment[1-3]. Worldwide, around 350 million people are affected by one of 4440 RDs with a known genetic cause[4]. Pinpointing the causative RD variants amongst all detected variants in targeted-enrichment sequencing, such as adaptive sampling and WES, or even WGS data, is not a trivial task and cannot be performed using a single strategy[2,5-7]. Several *in silico* pipelines have been created to combine published tools into a single solution[2,5]. One example of a commercially developed tool in genome diagnostics is Alissa Interpret, but open-source alternatives are also available, such as Kipoi and Scout[8-10].

Although the rapid growth of Next Generation Sequencing (NGS) technologies also accelerated the development of *in silico* pipelines, many challenges remain. To ensure reliability and reproducibility, pipelines must deal with variability in quality and types of input data, caused by different sequencing platforms and experimental conditions. Pipelines also need to accommodate different sources of information with different nomenclatures and ontologies, such as reference genomes, DNA annotation files and knowledge bases[2,11-15]. Variability in prediction algorithms, originating from inherent biases in the datasets used for the development and training of these tools, often causes discordant results[2,16].

Additionally, the increasing volumes of sequencing data resulting from advancements in NGS, such as long-read and WGS, require large-scale translation of results into the clinic[17]. To accomplish this, scalability must be ensured. Pipelines are also required to adapt to the continuous emergence of new bioinformatic methods and knowledge bases. Ideally, they also include tools to interpret variants according to the American College of Medical Genetics (ACMG) guidelines[5,6,18], which helps to accommodate more advanced variant interpretation and prioritization methods[17,19].

Finally, because variant interpretation pipelines involve different algorithms and resources, their installation and operation can require bioinformatic expertise. Most pipelines are restricted to individual institutions or are bound to specific hardware configurations[17]. Solutions exist that solve these problems by making use of containerization and parallelization of the processes within the pipelines, but these are far from perfect[17]. Another example that often requires some level of bioinformatic expertise is the presentation and visualization of the results. This is typically of poor quality and difficult to understand, which negatively affects the interpretation and translation towards the clinic[20].

To accelerate causative variant detection and innovation in genome diagnostics and research, we present the MOLGENIS Variant Interpretation Pipeline (VIP). VIP is a flexible and open-source pipeline to generate self-contained, interactive reports of variants in WES, WGS, targeted NGS (tNGS) and adaptive sampling data for expert interpretation. To our knowledge, VIP is the only pipeline able to incorporate the aforementioned into a single solution. It features integrated best-in-practice algorithms and protocols from routine diagnostics to facilitate classification of coding and non-coding variants according to the ACMG guidelines. VIP applies experience from the VKGL, the EU wide project to solve rare diseases (EU-Solve-RD), the European Joint Program on Rare Diseases (EJP-RD,) and European infrastructural collaboration to accelerate access and sharing of research data (CINECA) (table 1)[12,21]. We containerized and parallelized VIP for straightforward deployment and large-scale data analysis. VIP is easily modified by updating its tools, annotations, and classification trees. Results are presented in coherent and interactive reports for expert interpretation. So far, VIP has already been used in several studies, such as the curation and

expansion of HPO for systemic autoinflammatory diseases and to study the use of a targeted gene panel in Dutch NGS-based newborn screening[22,23].

Here, we explain the different capabilities of MOLGENIS VIP and how to use them. These include integrated best-in-practice annotation sources, such as our variant pathogenicity predictor CAPICE, and a step-by-step protocol for the analysis of NGS sequencing data, supporting researchers and diagnostic professionals in variant interpretation and classification. We demonstrate VIPs ability to classify and report any clinically relevant germline variants. Additionally, we demonstrate the classification of causative variants in representative cohorts of RD patients from the University Medical Centre Groningen (UMCG) and the EU-Solve-RD project[21].

MOLGENIS VIP

VIP supports short- and long-read WGS, WES and otherwise targeted-enrichment WGS data from different sequencing platforms: PacBio HiFi long-read sequencing, Oxford Nanopore Tech (ONT) long-read sequencing, and Illumina short-sequencing (table 1). To annotate coding and non-coding variants, VIP integrates different algorithms and knowledge bases and is divided into four modules: pre-processing, annotation, filtering, and interactive reporting (figure 1). Depending on the input format, VIP starts one of four workflows: the FASTQ (raw human readable sequencing output) workflow, the CRAM/BAM (Compressed Reference-oriented Alignment Map/Binary Alignment Map) workflow, the gVCF (Genomic Variant Call Format) or the VCF (Variant Call Format) workflow (figure 1). The sequence of the preprocessing steps is different for each workflow. However, after arriving at a VCF file, they share the steps performed by the remaining modules. From here, all variants are annotated using the different algorithms, knowledge bases, known genotype-phenotype relationships and inheritance patterns (figure 1; supplementary table 1). Finally, all variants are filtered using a user-specified decision tree and inheritance modes, resulting in an interactive report containing a prioritized shortlist of classified variants of interest. Possible classifications are likely benign (LB), benign (B), variant of unknown significance (VUS), likely pathogenic (LP) and pathogenic (P). The raw output with the different annotations is also available as an unfiltered VCF file.

VIP is developed in a combination of Java, JavaScript, Python, Perl and Shell scripting and runs on the command line. All processes performed by VIP are implemented using the workflow manager Nextflow, allowing parallel processing per chromosome to maximize performance. Apptainer is used for containerization, ensuring straightforward installation and reproducible deployment in different research or diagnostic environments[24,25]. Nextflow also creates intermediate files, allowing users to stop and resume the pipeline at any time during a run. Additionally, this feature allows users to analyze large amounts of data step-by-step and helps to accurately follow and reproduce all processes.

Figure 1 **Summary of modules in VIP.** As input, VIP requires a sample sheet in which the patient information is specified. In module 1 the input is validated and pre-processed resulting in a VCF file. The workflow can be started from all indicated points in the pre-processing step. Module 2 provides the variants in the VCF file with annotations from bioinformatic tools and resources (supplementary table 1). Module 3 filters the variants using a customizable decision tree and inheritance information from the previous modules. Finally, in module 4, VIP generates an interactive report in which users can apply clinically relevant filtering and in which the logic for the classifications is explained. Diagnosticians and researchers can use this report for further interpretation of the variants and sharing of the results.

Application of the method

With VIP we aim to provide a complete computational procedure to align reads, followed by calling, annotating, classifying and finally filtering genetic variants in research and diagnostics of patients

suffering from a rare disease with a suspected genetic cause. VIP offers tools to increase the sensitivity for finding previously unsolved or unknown variants or to finetune a query to find specific variants. The annotation module and decision tree can be altered or expanded to incorporate new annotation tools or resources. Therefore, we encourage users to develop and validate their own decision trees and to expand VIP for their own needs.

Description of the workflow

Input

Diagnosticians and researchers can provide a sample sheet in the tab-separated values (TSV) format in which each row represents a sample taken from an individual. It contains the location of the sequencing data and the metadata associated to the sample, such as the location of maternal and paternal sequencing data, phenotypic information, specified reference genome and used sequencing method. VIP supports several standard input formats for sequencing data produced by next generation sequencing (NGS): FASTQ, CRAM, BAM, VCF and gVCF files (table 1)[26-28]. Additionally, phenotypic information can be provided using terms from the HPO system[29].

Module 1: pre-processing

When sequencing data is provided in the FASTQ format, VIP initiates the FASTQ workflow and maps the files to the specified reference genome using Minimap2[30]. Next, BAM files are aligned and indexed by Samtools. Structural tandem repeats (STRs) are detected, using ExpansionHunter for short read data and Straglr for long-read data[31,32]. Single nucleotide variants (SNVs), and insertions and deletions (indels) are detected by DeepVariant. GLnexus is used to merge proband, maternal and paternal VCF files into one single VCF for further processing[33]. Finally, structural variants (SVs) are detected using Manta and cuteSV[34,35]. Sequencing data generated with the following platforms are supported: Illumina short-read (single and paired-end), ONT long-read sequencing and PacBio HiFi long-read sequencing (table 1).

Module 2: annotation

Next, the detected variants are annotated with different levels of information. Examples are allele frequencies from GnomAD, known gene-phenotype relationships from the HPO database and classifications that are validated by the VKGL. In addition, VIP also integrates our powerful CAPICE machine learning based variant pathogenicity predictor with other best in class annotation sources, such as Ensembl Variant Effect Predictor (VEP) and SpliceAI. Supplementary table 1 shows a complete list of default tools and knowledge bases, including references, that VIP uses to annotate variants. These annotations will be used to classify variants and display variants in the interactive report. We use the plugin framework of Ensembl VEP to extend the existing functionality with new tools and annotations[36].

Two main annotation tools are CAPICE and SpliceAI. CAPICE is a machine learning (ML) based method to predict the pathogenicity of SNVs and indels using diverse genomic features, such as genetic context, gene model annotations and evolutionary constraints. We chose CAPICE as it outperforms other similar pathogenicity predictors, such as CADD and REVEL[37]. Based on the study performed by Li et al. we updated and re-trained CAPICE. Our benchmark study showed that a cut-off value of 0.5 results in a recall rate of 0.95, which we used in our decision tree. SpliceAI is a ML based method that exploits the sequence surrounding a variant to determine the likelihood that the position in the pre-mRNA transcript is a splice donor or acceptor site[38]. SpliceAI outperforms most

splice variant predictors. Based on a study in which we performed sensitivity and specificity analysis on published splice variants, we chose a cut-off value of 0.42 as this resulted in the highest specificity (supplementary data 1).

Module 3: filtering

Inheritance matcher

To study families, for which genotypic and phenotypic information is available, diagnosticians can evaluate if variants segregate with disease or if they occurred *de novo*. This provides an additional level of evidence to determine if a variant is disease-causing. Therefore, VIP uses pedigree information consisting of trios (proband, mother and father) to check if variant segregation matches disease affected status, of course taking into consideration the genotype of the disease-causing gene according to known inheritance modes in the Clinical Genomic Database (CGD)[39]. Users can also provide VIP with known inheritance modes from the Online Mendelian Inheritance in Men (OMIM) database or other sources[39,40]. Both maternal and paternal genetic information can be specified in the sample sheet. VIP supports X-linked recessive, X-linked dominant, Y-linked recessive, Y-linked dominant, MT, autosomal recessive, autosomal dominant and *de novo* inheritance modes. Additionally, VIP supports compound recessive inheritance patterns and inheritance with incomplete penetrance.

Best-practices customizable decision tree

VIP uses a decision tree to filter variants that are collected in an interactive report based on the predicted classification. Users can compose a decision tree to fit their diagnostic workflow or research question. The decision tree is specified in a Javascript object notation (JSON) formatted file. It can be customized by editing the different objects within this file. Each object represents criteria that ultimately lead to the predicted variant classification by VIP. VIP also produces intermediate files, so that classification and filtering can repeatedly be performed using different decision trees. Figure 2 shows the default decision tree that is based on the guidelines of the VKGL and the Association for Clinical and Genetic Science (ACGS) and on the collaboration with experts from genome diagnostics at the genetics department of the UMCG[12,41,42].

Figure 2 **Default decision tree.** This is a schematic version of the default decision tree. The green blocks and bold arrows represent the general sequence of filtering steps and the values that are evaluated for each variant (see legend). Each value is calculated in the annotation module (supplementary table 1). The small arrows represent the decisions for the consequence classifications by VIP. VIP classifies the different consequences as P, LP, VUS, LB or B. After a variant is classified by VIP, it exits the filter tree. Variants with incorrect contigs, genes and low quality are removed (RM). Using the JSON format, the components in the decision tree can be customized or expanded to fit the workflow of the user.

Module 4: interactive report

The final set of variants that have passed through the decision tree is provided as a self-contained, interactive hypertext markup language (HTML) report that can be opened in any recent internet browser (figure 3). This report contains the filtered list of annotated variants. Diagnosticians can use these annotations to navigate the report and study the criteria that were used to classify the variants. Additionally, basic information, such as the genomic position, the reference and alternative alleles, the consequence, and the gene in which the variant is located, are provided. A more detailed view of all available annotations for each transcript is also available. Experts can perform diagnostic relevant filtering, such as hiding variants with a genotype quality <= 20, allelic imbalance, and all predicted Likely Benign (LB) and Benign (B) variants. Similarly, by using the HPO match filter button,

variants that are not located in a gene associated to the provided HPO terms are hidden. Variants that do not match known monogenic inheritance patterns or variants that are not *de novo* can be hidden using the inheritance match buttons. The report is also provided as a raw VCF file as input for other tools. For the FASTQ and BAM workflows, a genome viewer is available to view the reads that overlap with a variant.

Figure 3 **Interactive report**. This figure shows an example of the base view of the interactive report. The interactive report opens in the sample screen (A). Here all the individuals within a family are shown. To navigate to the list of variants with their predicted class, users can navigate to the variant view by clicking one of the family members (C). The default variant view shows the variants and the consequence of the transcript with the highest CAPICE score. The variants in the list can be filtered using different filters, such as HPO filters, inheritance filters and predicted class filters (B). The report also contains more detailed views to show all annotations for each transcript and to show which criteria were used to classify a specific variant. When the BAM workflow is used, the built-in genome viewer can be used to study the context of variants within reads that were mapped to the reference genome.

Expertise needed

We advise that installation, configuration, and customization of the decision tree is done by a bioinformatician or system administrator. Afterwards, the protocol can be followed by any diagnostician or researcher.

Materials

Software

VIP has been developed for GNU-based Linux (e.g. Ubuntu, Windows Subsystem for Linux with x86_64 architecture with installed versions of Bash (version 3.2 or higher), Java (version 11 or higher), Apptainer (version 3.18 or higher) and Nextflow (version 23.10.0). An installation of Git is required to download and install VIP (table 1).

Hardware

To install the version of VIP that is described in this paper (7.4.0), 220 GB (gigabytes) of free diskspace is required. A multicore computer with at least 4 Central Processing Units (CPU) and 8 GB of Random Access Memory (RAM) is advised, allowing parallel processing per chromosome to optimize performance. However, for the FASTQ and BAM workflow, the required computing resources are heavily dependent on the number of input files and the read depth. Similarly, the required resources for the VCF workflow heavily depend on the number of VCF files and the number of variants per sample. To install the most recent version of VIP, we refer to table 1.

Procedure

Below we describe the procedure to download, install and run the VCF workflow and analyze the results. The same procedure applies to the FASTQ and BAM workflow. For detailed information on running the FASTQ and BAM workflow, refer to the online VIP documentation.

Installation (1-2 hours)

1. Open a command-line Unix-like terminal, define a directory in which VIP will be installed and navigate to that directory. Download VIP using the following command: git clone https://github.com/molgenis/vip.git. Execute bash vip/install to install VIP. The install process creates a directory vip with all files required to run the application.

Optional configuration (1 hour)

2. The default configuration files are stored in the directory vip/config. These files specify values for the different parameters in JSON format. For each workflow a custom configuration file can be created to overwrite values in the default configuration. All parameters that are not hardcoded in the config files can be overwritten. Our experience is that the most frequently adjusted parameters are the process parameters for allocating RAM, CPU and processing time limits to specific sub workflows, the reference genome parameters to specify the used reference genome, and filter parameters to specify which variants are shown in the interactive report. Additionally, users can specify the decision tree that they want to use. For a detailed description of all parameters with default and example values, refer to the online VIP documentation (table 1). The custom configuration file used to run the VCF workflow for the demonstration data set is available in supplementary data 2.
3. The file containing the default decision tree in a JSON formatted file is stored in the directory vip/resources. The decision tree can be customized by creating a copy of the default decision tree file and by editing or changing the order of the different parameters. For a description of the parameters that can be edited, we refer to the online VIP documentation (table 1).

Create samplesheet (1 hour)

1. Create a sample sheet containing the information of the individuals within each family. The required and default values are shown in table 2 and the online VIP documentation (table 1). When performing a trio analysis, we recommend providing the family identifier, individual identifier of the proband, the paternal and maternal identifiers, the affected status of the individuals, HPO terms of the proband, the used sequencing method (WES or WGS), the used reference assembly (GRCh37 or GRCh38) and location of the stored VCF files. Examples of sample sheets used to run the VCF workflow for the demonstration data set are available in supplementary tables 5, 6 and 7.

Running the pipeline (4 hours)

2. To run the VCF workflow, navigate to the installation folder vip and execute vip –workflow vcf –input <path_to_directory>/<sample_sheet_name>.tsv –output <path_to_directory>/<output_folder_name>. Add -config <path_to_directory>/<config_file_name>.cfg in case custom configuration values are provided. The progress of the pipeline is displayed in the standard output of the terminal. After VIP has performed a quality check on the sample sheet, it will run the pre-processing, annotation, filtering, and interactive report modules. The filtered VCF file, intermediate files, supporting files and interactive reports are stored in the respective output folders (table 3). An interactive report is created for each project specified in the sample sheet. Check table 4 for potential problems and suggestions for troubleshooting potential errors.

Navigating the interactive report

3. To interpret the results, download and open an interactive report <project_id>.html from your output directory in a locally installed web browser. Navigate to the 'samples tab' and the proband of interest (figure 3a). Clicking 'variants' opens the base view, displaying all the effects of a variant on each possible transcript (figure 3c). Each line represents the effect of a variant with the highest CAPICE score. To show all effects for each variant, press the arrow next to an effect. By default, only the gene symbol, expected inheritance pattern, matching HPO terms, HGVS notations, CAPICE scores, VKGL and ClinVar classifications, GnomAD allele frequencies, the predicted classifications by VIP and links to available literature are displayed. To display all available annotations, click 'Variants' in the header to open a detailed view of all annotations. To use a different sorting method, select an annotation by which to sort in the top right corner.

4. In the base view, use the filters on the left side of the report to filter the list (figure 3b). By default, the read quality, read depth and allelic imbalance filters are applied. To also view low quality variant calls, deselect these filters.

5. In case VIP is run using the FASTQ or BAM workflow, click a chromosomal position in the base view to show the genomic context and the reads overlapping the variant for the different transcripts.

6. In the base view, click on an effect to navigate to a list of all annotations for the specific effect. All the annotations added by VIP are displayed in the left panel in the 'consequence section'. The path through the decision tree is displayed in the right panel. This information can be used to verify what information VIP used to predict a class for a variant. Record and sample specific information, such as the chromosomal position and the known inheritance mode, is shown in the bottom panel.

7. In the base view, click on a gene symbol to open the gene in a webpage of the HUGO Gene Nomenclature Committee (HGNC) with links to related genomic, clinical, and proteomic information[43].

8. If available, click on the citation in the base view to navigate to the related research article in PubMed.

9. In the base view, click on an HPO term in the variant screen to navigate to a webpage of the HPO database. This contains a description of the phenotype, its ontology and its associations to diseases and genes.

10. In the base view, click on the ClinVar classification to navigate the associated webpage of ClinVar. This webpage contains detailed information about the variant and the submitted interpretations and evidence for its classifications[44].

Reanalysis

11. To re-analyze data from a previous run, VIP can be restarted from the filter module. This is useful when, for example, applying a different decision to classify variants, without having to annotate all variants again. To rerun VIP, the basic procedure remains the same. In addition, the correct intermediate files should be provided in the sample sheet and the module from which to start should be added in the custom configuration file using the parameter vcf.start. For detailed instructions to restart VIP from a different module, refer to the online VIP documentation (table 1).

Timing

Using VIP version 7.4.0, 16 GB of memory and 4 CPUs, the average runtime for WES data in VCF format for 20 samples (average size ~216 megabytes) was 4 hours. However, the performance highly depends on the size of the dataset, the workflow used and the number of available CPUs and RAM.

Preparation (once):
- Step 1, installation of MOLGENIS VIP: 1-2 hours.
- Step 2-3, creating custom configuration file and decision tree: 1 hour. When the default configuration and decision tree is used, this step can be skipped.

For each analysis:
- Step 4, creating the sample sheet: 1 hour.
- Step 5, running the pipeline: 4 hours (waiting for output)

Adding additional annotation source

We also provide bioinformaticians and system administrators with the ability to develop their own plugins to add new annotations sources. We use the VEP plugin framework to develop new plugins for VIP. The /vip/resources/vep/plugins directory contains examples with existing plugins. After a plugin is developed, the /vip/modules/vcf/templates/annotate.sh needs to be expanded with the newly developed plugin.

Anticipated results

To demonstrate how VIP performs and how VIP can be used to interpret clinically relevant germline data we used version 7.4.0, 4 CPUs, and 16 GB of RAM to analyze variants from the VKGL database and two anonymized patient cohorts. The total runtime was 4 hours.

Input data

Previously classified variants

We collected 25,664 variants previously classified by experts as LP or P based on the consensus between the different Dutch genome diagnostic laboratories within the VKGL. For this demonstration we used the LP and P variants in VKGL release 2023-11 and all newly added LP and P variants (added between release 2023-11 and 2024-2) to showcase how VIP classifies previously classified variants (table 1).

Routine diagnostic cohort

To demonstrate VIP in diagnostics, we created two anonymized patient cohorts. The first cohort was created to demonstrate how VIP is applied in routine diagnostics at the UMCG. This routine diagnostic cohort contained 18 patients with a molecular genetic diagnosis (supplementary table 2). These patients were selected out of a total of 70 interpretation requests by a clinical geneticist. These numbers represent the monthly amount of data that is analyzed using virtual gene panels. The panels were used to home in on potential disease-causing variants in known genes and to prevent incidental findings. The panels consisted of genes specific for developmental delay, dilated cardiomyopathy, and the clinical exome. For all patients HPO terms, WES data and maternal and paternal WES data was available.

Solve-RD research cohort

The second cohort contained 41 patients with rare diseases that were not diagnosed in routine diagnostics but solved within the EU-Solve-RD project, using novel omics approaches [21]. These patients were selected based on the availability of a molecular diagnosis, HPO terms, and maternal and paternal WES data. The resulting patient selection originated from three different European reference networks (ERNs): the ERN for neuromuscular disorders (ERN-EURO NMD), the ERN for rare neurological diseases (ERN-RND) and the ERN for rare malformation syndromes, intellectual and other neurodevelopmental disorders (ERN-ITHACA)[21]. The verified causative variants were extracted from the Genome Phenome analysis platform (GPAP) on 12-2-2024[45] (supplementary table 3).

Comparing number of candidate variants, recall rate and ranking

Create sample sheets

First, we created a sample sheet containing one file with all LP and P variants in VKGL release 2024-2, including variants that are part of the used version of VIP. Another sample sheet was created containing only newly added variants that are not part of the used version of VIP (supplementary table 4).

Following this step, we created one sample sheet with the patients from the routine diagnostic cohort and one sample sheet containing the patients from the Solve-RD research cohort. Both sample sheets specified the used HPO terms, affected status, reference genomes, sequencing types, and the proband, maternal and paternal WES data (supplementary table 5, 6).

Run VIP and analysis of results

VIP was used with the three sample sheets and the default decision tree to create an interactive report for each case. By default, variants with a genotype quality <= 20 and allelic imbalance and all LB and B variants were filtered out. We then collected the number of candidate variants when applying the HPO match filter, inheritance match filter and finally both the HPO and inheritance match filter.

Subsequently, we studied the number of candidate variants per patient and the total number of confirmed molecular diagnoses that were found to compare the recall rates for the previously classified variants, the routine diagnostic cohort, and the Solve-RD research cohort. To see how well VIP was able prioritize the molecular diagnoses and to demonstrate the added value for clinical geneticists, we also compared the assigned rank with the number of candidate variants.

Expectation

Because the variants of VKGL release 2023-11 were used by VIP in the VKGL and CAPICE annotation steps, we expect a 100% recall rate for these known variants (supplementary table 1). To showcase how VIP classifies known VKGL variants that were not part of the VKGL release used by VIP, we used the variants added between release 2023-11 and 2024-2. Because these are also known variants, we expect a recall rate of almost 100%.

The VCF files for the routine diagnostic cases are pre-filtered based on a virtual gene panel. Therefore, we expect that the average number of candidate variants in the interactive report for the routine diagnostic cohort will be smaller than for the rare complex cohort. We also expect that the filtering based on VUS, LP and P variants, HPO term matches, and inheritance matches, results in the highest ranking of the causative variants. However, this could lead to a decreased recall rate. Not all genes in the HPO database are equally well annotated with HPO terms and phenotypic features could have been missed when the patient's phenotype was described in the clinic[22]. Similarly, not all genomic positions for the proband are also covered for both parents, resulting in a missing inheritance match.

The patients from the Solve-RD research cohort that we collected were initially unsolved by the individual expertise centers. For this reason, they were submitted to the Solve-RD project to be analyzed using novel omics methods, such as gene expression analysis and RNA sequencing, instead of only relying on NGS. We expect that the recall rate for this cohort is lower when compared to the routine diagnostic cohort.

Results

Previously classified variants

Figure 4 shows the number of recalled known variants. As expected, 100% (25,664/25,664) of these variants were detected by VIP. In addition, VIP recalled 558 out of 597 (93.47%) of the newly added variants. Variants were missed because 21 were classified as LB based on the CAPICE scores. Two

variants were missed because one was classified as LB in the ClinVar database and another variant had a gnomAD minor allele frequency (MAF) higher than 0.02. Finally, 16 variants were missed because they had a SpliceAI score between 0.13 and 0.42.

Routine diagnostic cohort

Figure 5a shows the average number of candidate variants per patient and the total number of recalled molecular diagnoses for the routine diagnostic cohort. When LB and B variants are filtered out, VIP returned an average of 338 candidate variants per patient and recalled 18/18 molecular diagnoses. Applying the HPO match and inheritance match filters resulted in an average of 8 and 18 candidate variants per patient and a total of 14/18 and 15/18 recalled molecular diagnoses, respectively. The most significant decrease in the number of candidate variants is shown after applying both the HPO match and inheritance match filters simultaneously, resulting in 4 candidate variants per patient. However, the recall rate decreased to 11/18.

Solve-RD research cohort

Figure 5b shows the same results for the Solve-RD research cohort. When LB and B variants are filtered out, VIP returned an average of 349 candidate variants per patient and recalled 34/41 molecular diagnoses. Applying the HPO match and inheritance match filters resulted in an average of 33 and 20 candidate variants per patient and a total of 31/41 and 12/41 recalled molecular diagnoses, respectively. The most significant decrease in the number of candidate variants is shown after applying both the HPO match and inheritance match filters simultaneously, resulting in 8 candidate variants per patient. However, the recall rate decreased to 11/41.

Missed variants

In the Solve-RD research cohort, VIP missed 7 molecular diagnoses as result of CAPICE score that did not meet the cut-off value specified in the default decision tree (figure 2). The decrease in recall rate after applying the HPO match filter can be explained by the fact that in the routine diagnostic and the Solve-RD research cohorts 14 and 36 patients, respectively, were annotated with HPO terms that do not match the gene in which the molecular diagnosis is located. As expected, and described by W. Maassen et al., a possible explanation is that not every patient's phenotype is equally well described in HPO terms or that the gene is not annotated with HPO terms in the HPO database[22]. The decrease in recall rate after applying the inheritance match filter for patients in the routine diagnostic and the Solve-RD research cohort can be explained by the fact that for 3 and 29 patients, respectively, next generation sequencing did not cover both alleles for at least 1 parent.

Assigned rank versus number of candidate variants

In figure 6 the average rank of the molecular diagnoses was compared with the number of candidate variants per patient in the routine diagnostic and Solve-RD research cohort. This figure shows that the average rank increased and that the average number of candidate variants per patient decreased when the different filters were applied. This shows that VIP was better able to discriminate causative variants from other variants when the number of candidate variants decreases. The lowest number of candidate variants was returned when the HPO as well as the inheritance match filter was applied. For the routine diagnostic and Solve-RD research cohort, this resulted in an average rank of 2 and 4, respectively.

Figure 6 **Number of candidate variants per patient and rank of molecular diagnoses.** In panel a and b, the average numbers of candidate variants per patient is plotted versus the average rank of the molecular diagnosis for the patients in the routine diagnostic and Solve-RD research cohorts, respectively. Patients for which the molecular diagnoses was not found after applying the different filters, are not included.

Data availability

The previously classified variants from the VKGL can be downloaded from https://vkgl.molgeniscloud.org/. The routine diagnostic cohort contains patient data from patients within the UMCG and can therefore only be shared upon request. The Solve-RD research cohort is available as a dataset (EGAD50000000390) in the European Genome-Phenome Archive (EGA) and can be accessed by sending a data access request to the DAC (Data Access Committee) of the Solve-RD project.

Ethics statement

The studies involving humans were approved by the ethical committee of the University Medical Centre Groningen. The studies were conducted in accordance with the local legislation and institutional requirements. Written informed consent from the 18 UMCG patients for sharing their WES data was obtained. To access patient data from the Solve-RD project, we received confirmation from the Solve-RD Data Access Committee.

Code availability

MOLGENIS VIP is publicly available at https://github.com/molgenis/vip under the GNU Lesser General Public License v3.0. See https://github.com/molgenis/vip/blob/main/LICENSE for details. VIP is an aggregate work of many individual tools, each covered by their own license(s). Therefore, the individual license(s) of the relevant tools should also be considered.

Acknowledgements

This study has been performed with the support of the members of the UMCG Genomics Coordination Centre, the MOLGENIS VIP development team and the Development and Innovation team at the Genetics Department of the UMCG. We want to thank all members and patients participating in the Solve-RD project for access to the Solve-RD database and the use of the GPAP analysis software. Finally, we would like to thank Kate McIntyre for editorial assistance.

This study received funding from the EU projects Solve-RD, EJP-RD and CINECA Project (H2020 779257, H2020 825575, H2020 825775, respectively) and NWO grant numbers 917.164.455 and 184.034.019.

Conflict of interest

All authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

References

Claussnitzer, M. *et al.* A brief history of human disease genetics. *Nature* **577**, 179-189, doi:10.1038/s41586-019-1879-7 (2020).

Liu, Y., Yeung, W. S. B., Chiu, P. C. N. & Cao, D. Computational approaches for predicting variant impact: An overview from resources, principles to applications. *Front Genet* **13**, 981005, doi:10.3389/fgene.2022.981005 (2022).

The Lancet Diabetes, E. Spotlight on rare diseases. *Lancet Diabetes Endocrinol* **7**, 75, doi:10.1016/S2213-8587(19)30006-3 (2019).

Nguengang Wakap, S. *et al.* Estimating cumulative point prevalence of rare diseases: analysis of the Orphanet database. *Eur J Hum Genet* **28**, 165-173, doi:10.1038/s41431-019-0508-0 (2020).

He, X. *et al.* DIVIS: Integrated and Customizable Pipeline for Cancer Genome Sequencing Analysis and Interpretation. *Front Oncol* **11**, 672597, doi:10.3389/fonc.2021.672597 (2021).

Liu, Z. *et al.* Annotation Query (AnnoQ): an integrated and interactive platform for large-scale genetic variant annotation. *Nucleic Acids Res* **5**, 50(W51):W57-W65, doi:10.1093/nar/gkac418 (2022).

Weilguny, L. *et al.* Dynamic, adaptive sampling during nanopore sequencing using Bayesian experimental design. *Nat Biotechnol* **41**, 1018-1025, doi:10.1038/s41587-022-01580-z (2023).

Exome Enrichment using Agilent SureSelect Human All Exon V8 Panel and Agilent Alissa Clinical Informatics Platform (ed Agilent Technologies) (2023).

Avsec, Z. *et al.* The Kipoi repository accelerates community exchange and reuse of predictive models for genomics. *Nat Biotechnol* **37**, 592-600, doi:10.1038/s41587-019-0140-0 (2019).

Stranneheim, H. *et al.* Integration of whole genome sequencing into a healthcare setting: high diagnostic rates across multiple clinical entities in 3219 rare disease patients. *Genome Med* **13**, 40, doi:10.1186/s13073-021-00855-5 (2021).

Léon, A. & Pastor, O. Enhancing Precision Medicine: A Big Data-Driven Approach for the Management of Genomic Data. *Big Data Research* **26**, 100253, doi:https://doi.org/10.1016/j.bdr.2021.100253 (2021).

Fokkema, I. *et al.* Dutch genome diagnostic laboratories accelerated and improved variant interpretation and increased accuracy by sharing data. *Hum Mutat* **40**, 2230-2238, doi:10.1002/humu.23896 (2019).

Koboldt, D. C. Best practices for variant calling in clinical sequencing. *Genome Med* **12**, 91, doi:10.1186/s13073-020-00791-w (2020).

Cheng, C., Fei, Z. & Xiao, P. Methods to improve the accuracy of next-generation sequencing. *Front Bioeng Biotechnol* **11**, 982111, doi:10.3389/fbioe.2023.982111 (2023).

Rehm, H. L. & Fowler, D. M. Keeping up with the genomes: scaling genomic variant interpretation. *Genome Med* **12**, 5, doi:10.1186/s13073-019-0700-4 (2019).

Kim, Y. E., Ki, C. S. & Jang, M. A. Challenges and Considerations in Sequence Variant Interpretation for Mendelian Disorders. *Ann Lab Med* **39**, 421-429, doi:10.3343/alm.2019.39.5.421 (2019).

Field, M. A. Bioinformatic Challenges Detecting Genetic Variation in Precision Medicine Programs. *Front Med (Lausanne)* **9**, 806696, doi:10.3389/fmed.2022.806696 (2022).

Ghosh, R., Oak, N. & Plon, S. E. Evaluation of in silico algorithms for use with ACMG/AMP clinical variant interpretation guidelines. *Genome Biol* **18**, 225, doi:10.1186/s13059-017-1353-5 (2017).

Hamzeh, A. R., Andrews, T. D. & Field, M. A. Detecting Causal Variants in Mendelian Disorders Using Whole-Genome Sequencing. *Methods Mol Biol* **2243**, 1-25, doi:10.1007/978-1-0716-1103-6_1 (2021).

Schrijver, I. *et al.* Opportunities and challenges associated with clinical diagnostic genome sequencing: a report of the Association for Molecular Pathology. *J Mol Diagn* **14**, 525-540, doi:10.1016/j.jmoldx.2012.04.006 (2012).

Zurek, B. *et al.* Solve-RD: systematic pan-European data sharing and collaborative analysis to solve rare diseases. *Eur J Hum Genet* **29**, 1325-1331, doi:10.1038/s41431-021-00859-0 (2021).

Maassen, W. *et al.* Curation and expansion of the Human Phenotype Ontology for systemic autoinflammatory diseases improves phenotype-driven disease-matching. *Front Immunol* **14**, 1215869, doi:10.3389/fimmu.2023.1215869 (2023).

Kiewiet, G. *et al.* Future of Dutch NGS-Based Newborn Screening: Exploring the Technical Possibilities and Assessment of a Variant Classification Strategy. *Int J Neonatal Screen* **10**, doi:10.3390/ijns10010020 (2024).

Di Tommaso, P. *et al.* Nextflow enables reproducible computational workflows. *Nat Biotechnol* **35**, 316-319, doi:10.1038/nbt.3820 (2017).

Kurtzer, G. M., Sochat, V. & Bauer, M. W. Singularity: Scientific containers for mobility of compute. *PLoS One* **12**, e0177459, doi:10.1371/journal.pone.0177459 (2017).

Cock, P. J., Fields, C. J., Goto, N., Heuer, M. L. & Rice, P. M. The Sanger FASTQ file format for sequences with quality scores, and the Solexa/Illumina FASTQ variants. *Nucleic Acids Res* **38**, 1767-1771, doi:10.1093/nar/gkp1137 (2010).

Danecek, P. *et al.* The variant call format and VCFtools. *Bioinformatics* **27**, 2156-2158, doi:10.1093/bioinformatics/btr330 (2011).

Li, H. *et al.* The Sequence Alignment/Map format and SAMtools. *Bioinformatics* **25**, 2078-2079, doi:10.1093/bioinformatics/btp352 (2009).

Robinson, P. N. *et al.* The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet* **83**, 610-615, doi:10.1016/j.ajhg.2008.09.017 (2008).

Li, H. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics* **34**, 3094-3100, doi:10.1093/bioinformatics/bty191 (2018).

Dolzhenko, E. *et al.* ExpansionHunter: a sequence-graph-based tool to analyze variation in short tandem repeat regions. *Bioinformatics* **35**, 4754-4756, doi:10.1093/bioinformatics/btz431 (2019).

Chiu, R., Rajan-Babu, I. S., Friedman, J. M. & Birol, I. Straglr: discovering and genotyping tandem repeat expansions using whole genome long-read sequences. *Genome Biol* **22**, 224, doi:10.1186/s13059-021-02447-3 (2021).

Yun, T. *et al.* Accurate, scalable cohort variant calls using DeepVariant and GLnexus. *Bioinformatics* **36**, 5582-5589, doi:10.1093/bioinformatics/btaa1081 (2021).

Chen, X. *et al.* Manta: rapid detection of structural variants and indels for germline and cancer sequencing applications. *Bioinformatics* **32**, 1220-1222, doi:10.1093/bioinformatics/btv710 (2016).

Jiang, T., Liu, S., Cao, S. & Wang, Y. Structural Variant Detection from Long-Read Sequencing Data with cuteSV. *Methods Mol Biol* **2493**, 137-151, doi:10.1007/978-1-0716-2293-3_9 (2022).

Hunt, S. E. *et al.* Annotating and prioritizing genomic variants using the Ensembl Variant Effect Predictor-A tutorial. *Hum Mutat* **43**, 986-997, doi:10.1002/humu.24298 (2022).

Li, S. *et al.* CAPICE: a computational method for Consequence-Agnostic Pathogenicity Interpretation of Clinical Exome variations. *Genome Med* **12**, 75, doi:10.1186/s13073-020-00775-w (2020).

Jaganathan, K. *et al.* Predicting Splicing from Primary Sequence with Deep Learning. *Cell* **176**, 535-548 e524, doi:10.1016/j.cell.2018.12.015 (2019).

Solomon, B. D., Nguyen, A. D., Bear, K. A. & Wolfsberg, T. G. Clinical genomic database. *Proc Natl Acad Sci U S A* **110**, 9851-9855, doi:10.1073/pnas.1302575110 (2013).

Amberger, J., Bocchini, C. A., Scott, A. F. & Hamosh, A. McKusick's Online Mendelian Inheritance in Man (OMIM). *Nucleic Acids Res* **37**, D793-796, doi:10.1093/nar/gkn665 (2009).

Wallis, Y. *et al.* Practice Guidelines for the Evaluation of Pathogenicity and the Reporting of Sequence Variants in Clinical Molecular Genetics (ed Verenging Klinisch Genetische Laboratoriumdiagnostiek Association for Clinical Genetic Science) (2013).

Durkie, M. *et al.* ACGS Best Practice Guidelines for Variant Classification in Rare Disease 2023 (ed Association for Clinical Genetic Science) (2023).

Seal, R. L. *et al.* Genenames.org: the HGNC resources in 2023. *Nucleic Acids Res* **51**, D1003-D1009, doi:10.1093/nar/gkac888 (2023).

Landrum, M. J. *et al.* ClinVar: public archive of relationships among sequence variation and human phenotype. *Nucleic Acids Res* **42**, D980-985, doi:10.1093/nar/gkt1113 (2014).

Matalonga, L. *et al.* Solving patients with rare diseases through programmatic reanalysis of genome-phenome data. *Eur J Hum Genet* **29**, 1337-1347, doi:10.1038/s41431-021-00852-7 (2021).

A. Samples

VCF Report   Samples   Variants

Click on an individual id for detailed information for this sample. In this screen a link to the variants for this sample is available.

Family	Individual	Father	Mother	Proband	Sex	Affected	Phenotypes	VIBE
FAM20	6Va_5Pre_NX285_m_Vader_201208	0	0	False	Male	Unaffected		
FAM20	6Moe_5Pre_NX285_v_Moeder_201208	0	0	False	Female	Unaffected		
FAM20	6I_5Pre_NX285_m_Index_201208	6Va_5Pre_NX285_m_Vader_201208	6Moe_5Pre_NX285_v_Moeder_201208	True	Male	Affected	HP:0011461, HP:0001561, HP:0000308, HP:0002190, HP:0010963, HP:0002650, HP:0000773 ⬀	

B. Filter buttons

VIP
- ☐ LQ
- ☐ B
- ☐ LB
- ☐ VUS
- ☐ LP
- ☐ P

HPO
- ☐ HP:0000308
- ☐ HP:0000773
- ☐ HP:0001561
- ☐ HP:0002190
- ☐ HP:0002650
- ☐ HP:0010963
- ☐ HP:0011461
- ☐ GADO high
- ☐ GADO low

Inheritance
- ☐ Match
- ☐ Match: Possible
- ☐ De novo

Quality
- ☑ GT quality >= 20
- ☑ No allelic imbalance
- ☑ Depth >= 20

C. Variants

269 records   [1] [2] [3] ... [14] [Next]

Position	Reference	Proband	Mother	Father		Effect	Gene	Inh.Pat.	HPO	HGVS C	HGVS P	CAPICE	VIP
19:40711875	GA	GA/G	GA/GA	GA/GA		frameshift_variant	MAP3K10			c.1247del	p.Glu416GlyfsTer30	0.9996	LP
1:144915623	AG	A/AG	?/A	A/AG	⌄	frameshift_variant	PDE4DIP			c.2212del	p.Leu738CysfsTer12	0.9993	LP
6:57398270	C	C/T	C/T	C/T		stop_gained	PRIM2		❓	c.973C>T	p.Gln325Ter	0.9988	LP
17:16068343	G	G/A	G/A	G/A	⌄	stop_gained	NCOR1		ℹ	c.568C>T	p.Arg190Ter	0.9988	LP
11:48347014	G	G/A	G/A	G/A		stop_gained	OR4C3			c.441G>A	p.Trp147Ter	0.9987	LP
1:144915561	G	G/A	G/A	G/A	⌄	stop_gained	PDE4DIP			c.2353C>T	p.Arg785Ter	0.9987	LP
13:41941576	A	A/AT	A/AT	A/A		frameshift_variant	NAA16			c.1548dup	p.Glu517Ter	0.9984	LP
17:45234406	CA	CA/C	CA/C	CA/C	⌄	frameshift_variant	CDC27			c.714del	p.Val239Ter	0.9983	LP
17:26708298	A	AGC/AGC	AGC/AGC	AGC/AGC		frameshift_variant	SARM1			c.542_543insCG	p.Ser181ArgfsTer65	0.9983	LP
13:21750538	G	G/A	G/A	G/A ❗	⌄	stop_gained	SKA3			c.79C>T	p.Arg27Ter	0.9982	LP
12:40882793	TAG	T/T	TAG/TAG	TAG/TAG		frameshift_variant	MUC19			c.16039_16040del	p.Arg5347GlyfsTer26	0.9979	LP
3:10088407	AG	AG/A	AG/A ❗	AG/A ❗	⌄	splice_donor_variant	FANCD2	AR	HP:0002650 ❓	c.1278+1del		0.9971	LP
16:3119297	C	C/CG	C/CG	C/CG	⌄	frameshift_variant	IL32			c.454dup	p.Asp152GlyfsTer12	0.9969	LP
12:40881949	T	T/G	T/T	T/T		stop_gained	MUC19			c.15194T>G	p.Leu5065Ter	0.9967	LP
4:103822482	AAC	AAC/A	AAC/A	AAC/A		frameshift_variant	SLC9B1			c.1338_1339del	p.Leu447ArgfsTer47	0.9967	LP
1:12854090	T	T/A	T/A	T/A		stop_gained	PRAMEF1			c.314T>A	p.Leu105Ter	0.9964	LP
8:117779032	T	T/G	T/G	T/G		splice_donor_variant	UTP23			c.188+2T>G		0.9962	LP
7:72727122	T	T/TA	T/TA	T/TA	⌄	frameshift_variant	TRIM50			c.1258dup	p.Tyr420LeufsTer2	0.9961	LP
1:144994658	C	C/A	C/A	C/A	⌄	missense_variant	PDE4DIP			c.83G>T	p.Arg28Leu	0.9958	LP
6:29910760	GGA	GGA/G	GGA/GGA ❗	GGA/GGA		frameshift_variant	HLA-A	AD		c.301_302del	p.Asp101ProfsTer75	0.9951	LP

Resource	Link
CINECA	https://www.cineca-project.eu/
EJP RD	https://www.ejprarediseases.org/
File formats	https://gatk.broadinstitute.org/hc/en-us/articles/360035531812-GVCF-Genomic-Variant-Call-Format/
Git download	https://git-scm.com/downloads/
Illumina	https://emea.illumina.com/
Nextflow	https://www.nextflow.io/docs/
Oxford Nanopore Technology	https://nanoporetech.com/
PacBio HiFi	https://www.pacb.com/technology/hifi-sequencing/
VIP Github repository	https://github.com/molgenis/vip/
VIP online documentation	https://molgenis.github.io/vip/
VIP releases	https://github.com/molgenis/vip/releases/
VKGL	https://vkgl.molgeniscloud.org/

Category	Column	Description
General	project_id	Unique identifier for each project. Each projects can contain multipe families and family members. Default is 'vip'.
	family_id	Unique identifier for each family. A family can exit out of multiple layers of a father, mother and children. Default is 'fam_<integer>'.
	individual_id	Unique identifier for each family member. This field is mandatory.
	paternal_id	Unique identifier for each father within a family.
	maternal_id	Unique identifier for each mother within a family.
	sex	Biological sex of family member. Possible values are 'male' and 'female'. Default is 'unknown'.
	affected	Specifies whether the family member is affected by the disease phenotype. Allowed values are 'yes' or 'no'. Default is 'unknown'.
	proband	Specifies whether the family member is a proband. Allowed values are 'yes' or 'no'. If no probands are defined in the sample sheet, then all samples are considered to be probands.
	hpo_ids	Comma sperated unique identifiers from the HPO database describing the phenotypes of the family members within the sample sheet.
	sequencing_method	Specifies the sequencing method used. This determines which workflow-specific processes are used for the processing of the input data. Allowed values are 'WES' or 'WGS'. Default is 'WGS'.

Workflow specific

Category	Column	Description
FASTQ	fastq	Specifies the absolute path to the file containing raw sequencing data in FASTQ format. Only for single read files. Allowed file extensions are: fastq, fastq.gz, fq and fq.gz.
	fastq_r1	Specifiies the absolute path to the file containg raw sequencing data in FASTQ format for one of the pairs in paired-end sequencing. Allowed file extensions are: fastq, fastq.gz, fq and fq.gz.
	fastq_r2	Specifiies the absolute path to the file containg raw sequencing data in FASTQ format for one of the pairs in paired-end sequencing. Allowed file extensions are: fastq, fastq.gz, fq and fq.gz.
	sequencing_platform	Specifies the sequencing platform used. This determines which workflow-specific processes are used for the processing of the input data. Allowed values are: 'illumina', 'nanopore' or 'pacbio_hifi'. Value must be the same for all project samples.
BAM	bam	Specifiies the absolute path to the file containing sequencing data in BAM format. Allowed file extensions are: bam, cram and sam.
	sequencing_platform	Specifies the sequencing platform used. This determines which workflow-specific processes are used for the processing of the input data. Allowed values are: 'illumina', 'nanopore' or 'pacbio_hifi'. Value must be the same for all project samples.
gVCF	assembly	Identifier specifying the used build of the reference genome. Allowed values are: 'GRCh37', 'GRCh38' and 'T2T'.
	gvcf	Specifies the absolute path to the file containing the called variants in gVCF format. In case a multisample gVCF is used, the individual_id has to match one of the samples in the VCF file.
VCF	assembly	Identifier specifying the used build of the reference genome. Allowed values are: 'GRCh37', 'GRCh38' and 'T2T'.
	vcf	Specifies the absolute path to the file containing the called variants in VCF format. In case a multisample VCF is used, the individual_id has to match one of the samples in the VCF file.

File or folder[1]	Description
.nextflow[2]	Contains files with run statistics for each Nextflow run.
.nxf.home[2], .nxf.tmp[2]	Contains files and executables used by Nextflow.
.nxf.log[2]	Logfile containing history of all performed processes. Can be used to follow each run and debug failed runs.
.nxf.work[2]	Folder containing temporary files created by Nextflow for each process. Needed by Nextlfow to start subsequent processes. This folder is also used by Nextflow to resume a failed run.
nxf_report.html[2]	Self-contained interactive summary of the statstics for each process that Nextflow performed, like runtime, memory and CPU usage. Can be opend in any modern web browser.
nxf_timeline.html[2]	Self-contained schematic overview of the runtime and walltime of each Nextflow process. Can be opend in any modern web browser.
vip.html	Self-contained interactive report based on variant calls and annotations in vip.vcf.gz.
vip.vcf.gz	Compressed VCF file containing all variant calls, annotations and predicted classifications. This file can be used as input for other tools or subsequent analyses that require VCF files as input.
vip.vcf.gz.csi	Index file for vip.vcf.gz
intermediates	Compressed VCF and index files. Allows user to monitor or rerun VIP starting from pre-defined modules. For different possible rerun options, refer to the VIP documentation. Contents are dependend on the workflow started. A run of the VCF workflow containing WES data for one trio results in the following most important files: - <project_id>_<fam_id>_<individual_id>_liftover_accepted.vcf.gz - <project_id>_<fam_id>_<individual_id>_liftover_accepted.vcf.gz.csi - <project_id>_<fam_id>_<individual_id>_liftover_rejected.vcf.gz - <project_id>_<fam_id>_<individual_id>_liftover_rejected.vcf.gz.csi - <project_id>_<fam_id>_<individual_id>_annotations.vcf.gz - <project_id>_<fam_id>_<individual_id>_annotations.vcf.gz.csi - <project_id>_<fam_id>_<individual_id>_classifications.vcf.gz - <project_id>_<fam_id>_<individual_id>_classifications.vcf.gz.csi - <project_id>.sample_classifications.vcf.gz - <project_id>.sample_classifications.vcf.gz.csi

1) Path to files is specified by the user with the '--output' option when running VIP on the command line

2) For a detailed explanation, refer to the documentation of Nextflow (table 1)

Step	Problem	Possible reason	Solution
5	VIP returns unkown contig in VCF header.	Used reference genome does not match input VCF.	Edit the config file for the corresponding workflow to adjust the reference genome.
	Process runs out of memory.	Not enough memory allocated in the corresponding config file.	Edit the config file for the corresponding process to increase RAM CPU usage, and time limits for the failed process.
	VIP returns parsing error in the sample sheet validation process.	VIP has found a parsing error in the sample sheet.	Check the nxf.log output file for details about the error. Avoid special characters. Check if the columns line up with tab-separated values. Compare input with required and allowed values by using online VIP documentation and check for inconsitencies (table 1).
	VIP fails during the annotation process (no out-of-memory error).	One of the processes within the annotation module has failed.	Check the nextflow log file for details about the error. Find the working directory and locate it in the nextflow working directory. Check the command-files to pinpoint which process caused the error. Adjust your input accordingly and rerun your command by adding the resume option.