Large language models identify causal genes in complex trait GWAS

Authors: Suyash S. Shringarpure[1,*], Wei Wang[1], Sotiris Karagounis[1], Xin Wang[1], Anna C. Reisetter[2], Adam Auton[1], Aly A. Khan[1,3,4,*]

Affiliations:
[1] 23andMe Inc., 223 N Mathilda Ave, Sunnyvale, CA 94086, USA
[2] Therapeutics Division, 23andMe, 349 Oyster Point Blvd, South San Francisco, CA 94080, USA
[3] Departments of Pathology, and Family Medicine, University of Chicago, Chicago, IL 60637, USA
[4] Institute for Population and Precision Health, University of Chicago, Chicago, IL 60637, USA

[*] Corresponding authors: sshringarpure@23andme.com; aakhan@uchicago.edu

Abstract

Identifying underlying causal genes at significant loci from genome-wide association studies (GWAS) remains a challenging task. Literature evidence for disease-gene co-occurrence, whether through automated approaches or human expert annotation, is one way of nominating causal genes at GWAS loci. However, current automated approaches are limited in accuracy and generalizability, and expert annotation is not scalable to hundreds of thousands of significant findings. Here, we demonstrate that large language models (LLMs) can accurately identify genes likely to be causal at loci from GWAS. By evaluating the performance of GPT-3.5 and GPT-4 on datasets of GWAS loci with high-confidence causal gene annotations, we show that these models outperform state-of-the-art methods in identifying putative causal genes. These findings highlight the potential of LLMs to augment existing approaches to causal gene discovery.

Main

Genome-wide association studies (GWAS) have identified many regions of the genome associated with complex traits, enhancing our understanding of trait biology. However, a significant limitation of GWAS is the difficulty in pinpointing the underlying causal gene for a given association. Approaches to causal gene identification from GWAS loci use a broad range of information including functional annotation, colocalization with quantitative trait loci (QTL) datasets, biological insights, and literature evidence. Literature mining for the co-occurrence of a (disease, gene) pair in a publication potentially provides evidence for the causal role of the gene in the disease, and may recapitulate the knowledge that an expert biologist or clinician might use to identify the causal gene at a GWAS locus. However, current literature mining approaches

38 (Kafkas, Dunham, and McEntyre 2017; Tirunagari et al. 2024) for causal gene prioritization have
39 been evaluated in limited settings or through related tasks such as drug/gene entity recognition
40 and normalization, and their generalizability to all datasets is unclear.
41
Large language models (LLMs) are deep learning models trained on large text corpora,
initially to predict masked/next words from a sentence, and then subsequently trained for a large
number of tasks including text generation, summarization, and question-answering. Recent
studies have demonstrated their capability to perform biomedical tasks (Sarwal et al. 2023),
including summarizing gene function (Chen and Zou 2024), medical question answering
(Singhal et al. 2023), cell-type annotation (Hou and Ji 2024), and identifying causal genetic
factors from murine experimental data (Tu et al. 2023). We hypothesize that large language
models like GPT-3.5 (Brown et al. 2020) and GPT-4 (OpenAI et al. 2024) offer a systematic way
to mining literature and identifying causal genes at GWAS loci, as their training datasets include
scientific literature and other sources of information about genetics. This approach would enable
efficient and scalable annotation of likely causal genes at GWAS loci using literature evidence,
which is impractical through expert human annotation.
54
We performed a systematic evaluation of GPT-3.5 and GPT-4 for the task of causal
gene identification, and compared their performance to state-of-the-art computational methods
(Supplementary Figure 1). Four evaluation datasets containing 641 to 1692 GWAS loci, with
ground-truth annotations of causal genes based on different criteria, were used to test the
generalizability of the LLM-based approach (Supplementary Table 1). Given that LLMs are
trained on large undisclosed text datasets and it is hard to verify which datasets were used in
their training, we selected several well-studied benchmark datasets, including a newly curated
dataset created after the training period of GPT-3.5 and GPT-4, as well as a benchmark dataset
that is not available on the internet (referred to as GWAS catalog and Weeks et al. respectively,
Methods).
65
The input prompt to the LLMs contained a generic description of an expert geneticist
seeking to identify the causal gene, followed by the name of the GWAS phenotype and a list of
all genes within 500 kbp of the lead variant at the locus (Figure 2, Methods). Additionally, the
LLM was instructed to output the name of the causal gene, a confidence score between 0 and
1, and a short reason for the choice. We queried the LLMs using available APIs to use specific
model versions and ensure reproducibility of results (Methods).
72
For comparison, we evaluated other state-of-the-art approaches for predicting the causal
gene, including the polygenic priority score (PoPS, Weeks et al. 2023), locus-to-gene score
(L2G, Mountjoy et al. 2021), OpenTargets text-mining (Tirunagari et al. 2024), and the 'nearest
gene' method (Stacey et al. 2019), all applied on the same datasets. We evaluated all methods
based on agreement of predictions with the ground-truth annotations of causal genes in the
original dataset, using precision, recall, and F-score (the harmonic mean of precision and recall)
as performance measures.
80

We found that GPT-3.5 is competitive with existing methods, and GPT-4 outperforms
existing methods on all four datasets in F-score (Figure 2a and 2b, Supplementary Table 2 and
Supplementary Table 8, p = 8.1e-8, 3.84e-15, 8.72e-4, 1.04e-11 for a paired Wilcoxon signed-
rank test on OpenTargets, Pharmaprojects, Weeks et al., and GWAS catalog respectively, when
comparing GPT-4 with the best non-LLM approach). The performance of the LLM-based
methods correlates with a number of factors related to the GWAS locus. We observed that
prediction accuracy is negatively correlated with the number of genes in the locus, a relationship
observed for all methods (Figure 2c, Supplementary Table 2). LLM-based methods showed a
positive correlation between prediction accuracy and the number of publications for the causal
gene, and a similar correlation was observed in other methods (Figure 2d, Supplementary Table
2). Additionally, we also noticed a small number of obvious hallucinations, where the LLMs
reported a causal gene that was not included in the set of provided genes at a locus (fewer than
2% of all loci for GPT-3.5, fewer than 0.9% for GPT-4, Supplementary Table 3).
94
Next we assessed the LLM-based methods' ability to generate a confidence score
associated with their prediction. We observed that LLMs were well-calibrated at higher
confidence levels (>= 0.8), but overly optimistic in their confidence estimates at lower
confidence levels (0.5-0.7), with GPT-4 showing better calibration than GPT-3.5 (Supplementary
Figure 2, Supplementary Table 4). We found that focusing only on the high-confidence
predictions from GPT-4 (confidence >= 0.8) allowed additional improvements to precision, with
improvements from 10% to 43% across the datasets (Supplementary Figure 7).
102
We examined the purported reasoning underlying the LLMs' confidence and predictions,
which might shed light on their ability to interpret complex prompts. The reasons provided by the
LLMs for correct predictions include phrases describing the functions of genes ("is involved in",
"the regulation of", "in immune response" etc.), or their association with the phenotype ("is
associated with", "is implicated in" etc.) among others (Supplementary Table 9). Since LLMs are
sensitive to their input prompts, we tested the impact of prompt structure on our results. In our
sensitivity analysis, we found that the LLM-based methods maintained their performance even
when provided with only a minimal prompt containing the output format, task instruction,
phenotype name, and gene names, without any additional context (Supplementary Figure 3).
This suggests that the LLMs internally contained most of the information needed for the causal
gene identification task without requiring substantial context.
114
To further explore the internal model representation of genetic and phenotypic
associations, we examined the embeddings of phenotypes and genes using the "text-
embedding-3-large" model (OpenAI 2024). LLMs represent words as points in a high-
dimensional embedding space, where similarity in these representations can capture semantic
relationships (Mikolov et al. 2013). In the context of causal gene identification, we hypothesized
that causal genes are likely to be proximal to the phenotypes they influence in the embedding
space. To test this hypothesis, we use pre-computed high-dimensional embeddings of LLM-
generated gene and phenotype descriptions at a GWAS locus. The predicted causal gene at the
locus is the gene which is most similar to the phenotype in the embedding space. We found that

using similarity of pre-computed embeddings alone achieves about 75-90% of the performance
of GPT-3.5 (Supplementary Figure 4).

To illustrate the role of embeddings in prediction, we present t-SNE projections for a
locus associated with LDL cholesterol from the Weeks et al. dataset in Figure 3a. For this locus,
which has 12 candidates for the causal gene, the text embeddings of the *PCSK9* gene are
closest to those of LDL cholesterol (as measured through cosine similarity). Consequently, the
LLM-based approaches correctly nominate *PCSK9* as the causal gene at the locus.
Supplementary Figure 5 shows a barplot of the gene-phenotype similarities for this locus. Figure
3b quantifies the similarity between the causal gene and phenotype in the embedding space for
all loci in our evaluation datasets. We observe that the causal gene is most similar to the
phenotype for 40-70% of all examples, depending on the evaluation set, among all genes at the
locus. Extending this further, we find that the causal gene is among the top 5 most similar genes
to the phenotype in the embedding space for 75%-93% of all examples (Supplementary Figure
6).

Although similarity in high-dimensional embedding space explains a large proportion of
the performance of LLM-based approaches, we find that LLMs improve on these phenotype
embeddings. For instance, the GWAS catalog dataset contains 250 loci for a phenotype related
to sex differences that is only described as "Multi-trait sex score" (originally defined as the sum
of multiple quantitative traits, weighted by their respective sex-difference effect sizes). The
embedding-based approach makes incorrect predictions for most of these loci (precision for
phenotype = 0.05) while GPT-4 achieves a precision of 0.65 for the same phenotype
(Supplementary Table 5). This suggests that with the additional context of the task description
and the gene information, the LLM is correctly able to infer that the short phenotype description
refers to sexual dimorphism and sex-specific traits.

In considering the broad applicability of this approach for causal gene prediction beyond
currently published phenotypes, we found a couple of notable failure modes when examining
phenotypes where GPT-4 had very low precision. First, GPT-4 had a precision of 0.08 for the
"Total protein" phenotype. The reasons provided by the LLM suggest an incomplete
understanding of the short phenotype description, interpreting it only in terms of broad protein
levels rather than specifically about protein levels in blood (Supplementary Table 6). This
indicates that more specific phenotype descriptions could improve the performance of LLMs.

In a second instance, GPT-4 had a precision of 0.0 for the phenotype "Neonatal
circulating Complement Component 4 (C4) protein concentration". For this phenotype, all the
GWAS loci in the evaluation dataset include the *C4A* gene in the 500 kbp window around the
lead variant, though they have different causal genes based on coding variant signals. Since the
C4A gene is a major part of the complement system, the LLM-based approach always predicts
C4A as the causal gene. This suggests that combining LLMs with functional annotation data
could improve causal gene prioritization. Supplementary Table 5 shows the precision and recall
for all methods stratified by phenotype.

While we have demonstrated the potential of LLMs for causal gene identification, it is
important to consider the limitations and challenges associated with their use in our study. The
lack of disclosure regarding the training datasets for most LLMs makes it challenging to verify
whether our evaluation datasets were somehow included in their training. To mitigate this risk,
we introduced a study design using data curated after the LLM training period as well as a
benchmark dataset not available on the internet. Additionally, while LLMs return plausible
reasons along with their predictions, it is challenging to pinpoint the exact information the LLM
used to make each prediction. This is a current shortcoming, but it also points to an area of
active research in the field. As reasoning capabilities continue to improve in LLMs, we anticipate
that their ability to provide transparent and verifiable explanations will evolve rapidly.
178

Overall, our study demonstrates for the first time that LLMs can significantly enhance
causal gene identification and GWAS interpretation by systematically incorporating literature
evidence. LLM-based approaches, requiring only the location of the lead variant, can be applied
to any GWAS locus. With improved prompting, these methods could become valuable tools for
causal gene identification. Furthermore, combining LLM-based approaches with functional data
holds the potential to create even more accurate and robust methods for identifying causal
genes, advancing our understanding of genetic contributions to complex traits.
186
187
188

References

Brown, Tom B., Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal,
Arvind Neelakantan, et al. 2020. "Language Models Are Few-Shot Learners." arXiv.
https://doi.org/10.48550/arXiv.2005.14165.
Chen, Yiqun, and James Zou. 2024. "GenePT: A Simple But Effective Foundation Model for
Genes and Cells Built From ChatGPT." bioRxiv.
https://doi.org/10.1101/2023.10.16.562533.
Hou, Wenpin, and Zhicheng Ji. 2024. "Assessing GPT-4 for Cell Type Annotation in Single-Cell
RNA-Seq Analysis." *Nature Methods*, March, 1–4. https://doi.org/10.1038/s41592-024-
02235-4.
Kafkas, Şenay, Ian Dunham, and Johanna McEntyre. 2017. "Literature Evidence in Open
Targets - a Target Validation Platform." *Journal of Biomedical Semantics* 8 (1): 20.
https://doi.org/10.1186/s13326-017-0131-3.
Mikolov, Tomas, Kai Chen, Greg Corrado, and Jeffrey Dean. 2013. "Efficient Estimation of Word
Representations in Vector Space." arXiv. http://arxiv.org/abs/1301.3781.
Minikel, Eric Vallabh, Jeffery L. Painter, Coco Chengliang Dong, and Matthew R. Nelson. 2024.
"Refining the Impact of Genetic Evidence on Clinical Success." *Nature*, April.
https://doi.org/10.1038/s41586-024-07316-0.
Mountjoy, Edward, Ellen M. Schmidt, Miguel Carmona, Jeremy Schwartzentruber, Gareth Peat,
Alfredo Miranda, Luca Fumis, et al. 2021. "An Open Approach to Systematically
Prioritize Causal Variants and Genes at All Published Human GWAS Trait-Associated
Loci." *Nature Genetics* 53 (11): 1527–33. https://doi.org/10.1038/s41588-021-00945-5.
OpenAI. 2024. "New Embedding Models and API Updates." *New Embedding Models and API*
Updates (blog). January 2024. https://openai.com/index/new-embedding-models-and-

api-updates/.
OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia
Leoni Aleman, et al. 2024. "GPT-4 Technical Report." arXiv.
https://doi.org/10.48550/arXiv.2303.08774.
Sarwal, Varuni, Viorel Munteanu, Timur Suhodolschi, Dumitru Ciorba, Eleazar Eskin, Wei
Wang, and Serghei Mangul. 2023. "BioLLMBench: A Comprehensive Benchmarking of
Large Language Models in Bioinformatics." bioRxiv.
https://doi.org/10.1101/2023.12.19.572483.
Singhal, Karan, Shekoofeh Azizi, Tao Tu, S. Sara Mahdavi, Jason Wei, Hyung Won Chung,
Nathan Scales, et al. 2023. "Large Language Models Encode Clinical Knowledge."
Nature 620 (7972): 172–80. https://doi.org/10.1038/s41586-023-06291-2.
Stacey, David, Eric B Fauman, Daniel Ziemek, Benjamin B Sun, Eric L Harshfield, Angela M
Wood, Adam S Butterworth, Karsten Suhre, and Dirk S Paul. 2019. "ProGeM: A
Framework for the Prioritization of Candidate Causal Genes at Molecular Quantitative
Trait Loci." *Nucleic Acids Research* 47 (1): e3–e3. https://doi.org/10.1093/nar/gky837.
Tirunagari, Santosh, Shyamasree Saha, Aravind Venkatesan, Daniel Suveges, Annalisa
Buniello, David Ochoa, Johanna McEntyre, Ellen McDonagh, and Melissa Harrison.
2024. "Lit-OTAR Framework for Extracting Biological Evidences from Literature."
bioRxiv. https://doi.org/10.1101/2024.03.06.583722.
Tu, Tao, Zhouqing Fang, Zhuanfen Cheng, Svetolik Spasic, Anil Palepu, Konstantina M.
Stankovic, Vivek Natarajan, and Gary Peltz. 2023. "Genetic Discovery Enabled by A
Large Language Model." bioRxiv. https://doi.org/10.1101/2023.11.09.566468.
Weeks, Elle M., Jacob C. Ulirsch, Nathan Y. Cheng, Brian L. Trippe, Rebecca S. Fine, Jenkai
Miao, Tejal A. Patwardhan, et al. 2023. "Leveraging Polygenic Enrichments of Gene
Features to Predict Genes Underlying Complex Traits and Diseases." *Nature Genetics*
55 (8): 1267–76. https://doi.org/10.1038/s41588-023-01443-6.
239

Methods

Evaluation datasets

We used four datasets for evaluation (1) the OpenTargets gold-standard dataset, (2) the
Citeline Pharmaprojects dataset of drug targets and their approved indications, (3) an evaluation
set created by Weeks et al. based on proximity to fine-mapped coding variant associations, and
(4) an evaluation set we created using associations added to the GWAS catalog from
manuscripts published after April 2023.

The OpenTargets gold-standard dataset is based on GWAS loci for which there is high
confidence (through functional criteria) in the causal gene. We downloaded the OpenTargets
gold-standard dataset from https://github.com/opentargets/genetics-gold-standards/ (file:
https://github.com/opentargets/genetics-gold-
standards/blob/master/gold_standards/processed/gwas_gold_standards.191108.tsv). We
subsetted the dataset to only rows that had a high-confidence annotation (highest_confidence =
"High"). We added gene symbol annotations to the dataset with GENCODE release 43, and

excluded rows where a gene symbol was not found. This resulted in a dataset with 851 rows. To
create descriptions of the phenotypes, we combined trait information from standard trait names
and reported trait names. We appended reported trait names to standard trait names if the
reported trait names are non-redundant, and we also removed irrelevant text from reported trait
names, such as "[EA]", "non-cancer illness code, self-reported", "GWAS/Metabochip 2012" and
"conditional on rs7709212".
263
The Pharmaprojects dataset contains drug targets and indications, as well as their drug
development stage. We used the Pharmaprojects dataset released by Minikel et al. (Minikel et
al. 2024) and created additional mappings of disease indications to EFO (Supplementary
Notes). We subsetted the dataset to only rows that have a mapped MeSH or EFO term and that
correspond to launched drugs (hcat = "Launched"). We added gene symbol annotations to the
dataset with GENCODE release 43, and excluded rows where a gene symbol was not found.
This resulted in a dataset with 1692 causal gene - phenotype pairs. Since the Pharmaprojects
data does not contain GWAS information, we created synthetic GWAS hits near the target gene
for each row to mimic real GWAS hits in terms of the distance between the GWAS hit and the
underlying causal gene. More details about the methods for creation of the synthetic GWAS hits
can be found in the Supplementary Note.
275
The Weeks et al. evaluation set contains non-coding credible sets that are within 500 kbp of a
high-confidence (posterior inclusion probability > 0.5) fine-mapped coding association in the
same GWAS in UK Biobank (Weeks et al. 2023). We obtained this dataset by emailing the
authors. Since this dataset is not available directly on the internet, it is the least likely to have
been directly used for training the LLMs evaluated in our study (though the underlying GWAS
summary statistics and publication could be part of the LLM training data). We used the gene
symbol annotations provided by the authors. This resulted in a dataset with 1348 causal gene -
phenotype pairs.
284
The GWAS catalog dataset contains non-coding lead variants that are within 500 kbp of a
coding lead variant in the same GWAS study. We downloaded the GWAS catalog lead variant
file version "gwas_catalog_v1.0.2-associations_e111_r2024-03-11.tsv" from
https://www.ebi.ac.uk/gwas/docs/file-downloads (download date: 03/19/2024). To avoid the
possibility of these results being included in LLM training datasets, we subset the data to only
include associations added to the GWAS catalog for manuscripts published after April 30, 2023,
the latest reported training cutoff date among the LLMs we evaluated in our study. This resulted
in a dataset with 641 causal gene - phenotype pairs.
293

294 ## Generating LLM input from datasets

295
296 For input to the LLMs, we converted each (phenotype, lead variant, causal gene) triplet
297 corresponding to a GWAS locus to a (phenotype, list of genes in locus) pair.
298

299 For OpenTargets, Pharmaprojects, and the GWAS catalog datasets, we identified all genes
300 within 500 kbp of the lead variant (using GENCODE release 43) based on the smallest distance
301 between the gene body and the lead variant. For the Weeks et al. dataset, the dataset provided
302 by the authors included all genes within 500 kbp of the lead variant, so we used that list of
303 genes without any additional processing.
304
305 To avoid leaking information about the lead variant location or causal gene position through the
306 ordering of gene symbols by physical position, we sorted all gene symbols lexicographically
307 before including them in the prompt to the LLMs.
308
As an additional sanity check to verify that the LLM relies on phenotype information and not just
on gene information (such as location) for predictions, we randomly sampled phenotypes at the
evaluation loci and provided those as input to GPT-4. As expected, we found that LLM
performance is considerably degraded from an average precision of 63% across all datasets to
an average precision of 32%, along with an increase in number of obvious hallucinations from
8.25 to 34 (Supplementary Table 10).
315

316 LLM prompts for identifying causal genes

317
318 To query LLMs to identify the causal genes for a (phenotype, list of genes in locus) pair, we
319 used a prompt describing the task for the LLM along with the phenotype and gene list. The
320 basic prompt we used had two components, a system prompt (for general behavior), and a user
321 prompt (pair-specific). For an example pair ("Morning person",[A,B,C,D]), the prompts are
322 described below.
323
System prompt:
You are an expert in biology and genetics.
Your task is to identify likely causal genes within a locus for a given GWAS phenotype based on
literature evidence.
From the list, provide the likely causal gene (matching one of the given genes), confidence (0:
very unsure to 1: very confident), and a brief reason (50 words or less) for your choice.
Return your response in JSON format, excluding the GWAS phenotype name and gene list in
the locus. JSON keys should be 'causal_gene','confidence','reason'.
Your response must start with '{' and end with '}'.
333
334 User prompt:
335 Identify the causal gene.
336 GWAS phenotype: {Morning person}
337 Genes in locus: {A},{B},{C},{D}
338

LLMs evaluated

For our experiments, we evaluated LLMs from OpenAI, GPT-3.5 and GPT-4. For GPT-3.5, we used the model version "gpt-3.5-turbo-0125", which has been trained on data up to September 2021. For GPT-4, we tested the model version "gpt-4-1106-preview", which has been trained on data up to April 2023, and model version "gpt-4-0613", which has been trained on data up to September 2021. We found that the "gpt-4-0613" model performed comparably or better than the "gpt-4-1106-preview" model and had fewer obvious hallucinations (Supplementary Table 7), hence we report the results for "gpt-4-0613" as GPT-4 in the main text.

To make outputs reproducible, we queried all LLMs with temperature set to 0.

Post-processing of LLM results

We consider an LLM prediction to be an obvious hallucination if the predicted gene was not in the list of genes at the locus provided to the LLM. These are easily detectable, and we set such predictions to NA, excluding them from downstream evaluation.

Comparison to other methods

We compared our results to several state-of-the-art methods for each dataset. First, we evaluated the "nearest gene" method for all datasets. We evaluated text-mining on the OpenTargets and Pharmaprojects dataset, where there was sufficient overlap between the phenotypes in the dataset and phenotypes included in the text-mining scores. We also added prediction based on "locus-to-gene" (L2G) scores to the OpenTargets gold-standard dataset, and prediction based on polygenic priority score (PoPS) to the Weeks et al. evaluation dataset. Both these methods were previously evaluated to have good performance on their respective datasets.

To obtain the nearest gene prediction, we computed the distance between the genes in each locus and the lead variant (using GENCODE release 43 and reference genome hg38 for the OpenTargets, Pharmaprojects, and GWAS catalog datasets), and defined the nearest gene as the gene with the least distance from the lead variant based on gene body. For the Weeks et al. data, we directly used the nearest gene predictions provided by the authors (downloaded from https://www.finucanelab.org/data, file: https://www.dropbox.com/sh/o6t5jprvxb8b500/AACqCux_jBF9F56ozhzzkpia/results/UKB_AllMethods_GenePrioritization.txt.gz?dl=0). In the Weeks et al. data, we found that "nearest gene" nominated multiple genes at about 4% of loci (51 of 1348) due to the lead variant position being within multiple gene bodies. To simplify evaluation, we randomly chose a single gene out of all nominated genes as the prediction at such loci. We found that this had a minor impact on

precision and recall compared to that reported in the original publication (precision = 0.47 vs
previously reported 0.46, recall = 0.47 vs previously reported 0.48).

To get the text mining prediction, we first downloaded (gene,disease) co-occurrence information
and scores (Supplementary Note) from OpenTargets. We aggregated the scores of each
gene/disease pair by summing over all scores for the pair from all publications. We defined the
predicted causal gene from text mining at a locus as the gene with the largest aggregated score
in each locus for the GWAS phenotype.

The L2G score is a machine learning approach trained using fine-mapped genetics and
functional genomics data on 445 gold-standard curated GWAS loci (Mountjoy et al. 2021). The
predicted causal gene based on L2G score was defined as the gene with maximal L2G score in
each locus (indexed by the phenotype and the lead variant). We downloaded the L2G scores
from https://ftp.ebi.ac.uk/pub/databases/opentargets/genetics/latest/l2g/ (download date:
03/26/2024).

PoPS is a similarity-based gene prioritization method that leverages gene-level summary
statistics and incorporates data about genes from a variety of sources to produce a phenotype-
gene level prioritization score. We obtained PoPS scores for the 1348 evaluation loci by
emailing the authors of the original publication (Weeks et al. 2023). The predicted causal gene
based on the PoPS score was defined as the gene with the highest PoPS score in the locus.

Evaluation of predictions

For evaluation of predictions, we computed precision (proportion of predicted causal genes that
were annotated as causal in the dataset), recall (proportion of annotated causal genes identified
among predictions), and F-score (harmonic mean of precision and recall). Some methods
(nearest gene, PoPS, LLM-based approaches) made a single causal gene prediction for each
example, while others (text mining, L2G score) only made predictions at a subset of all
examples. To compute these metrics, the predictions from each method were converted to
0/1/NA, with 1 assigned if the method made a prediction and it matched the annotated causal
gene, 0 assigned if the method made a prediction but it did not match the annotated causal
gene, and NA assigned if the method did not make a prediction for an example. For all methods
except text mining, we found that NAs were only a small proportion of the predictions
(Supplementary Table 4).

Precision = (Number of predictions scored 1) / (Number of non-NA predictions)

Recall = (Number of predictions scored 1) / (Number of examples in dataset)

F-score = 2 * Recall * Precision / (Recall + Precision)

For each metric, we computed 95% confidence intervals using the bootstrap with 1,000
samples.

To compare the performance of GPT-4 to the best non-LLM approach, we used a Wilcoxon
signed rank test with continuity correction, and we report p-values for the alternative hypothesis
that the GPT-4 performance is higher than the highest non-LLM approach performance. We
also report a p-value from a McNemar test for the same comparison with the alternative
hypothesis of a difference between performance for the two methods.

Factors affecting prediction accuracy

To assess the impact of locus complexity, we used the number of genes in the locus as a
measure of its complexity, and computed the Pearson correlation between the number of genes
in the locus and whether the prediction was correct.

To assess the impact of publication count, we used publication counts for causal genes to
evaluate correlations with prediction performance. We downloaded the "gene2pubmed" file from
https://ftp.ncbi.nlm.nih.gov/gene/DATA/ (download date: January 26, 2024). We subset the file
to only include human genes (tax_id = 9606), and count the number of publications per gene.
Since many examples might share the same causal gene, for each causal gene, we computed
the proportion of loci predicted correctly. To account for the heavy-tailed distribution of
publication count by gene, we computed the Spearman correlation between the number of
publications for the causal gene and the proportion of correct predictions at loci with the
specified causal gene.

We used the bootstrap with 1,000 samples to compute 95% confidence intervals for both
correlations. We used the same resampled dataset for confidence interval calculations for
precision, recall, F-score and both correlations.

Calibration analysis

To assess calibration, we used the confidence scores provided by the LLM. We computed
precision for all predictions at a given confidence score, for any confidence score with at least 5
predictions. Supplementary Table 4 shows all unique confidence scores predicted by the LLMs,
with their counts and precision estimates. We computed a standard error for each precision by
assuming it to be the mean of a binomial distribution with size given by the number of
predictions with that score. 95% confidence intervals were calculated as precision +/- 1.96*se.

Summarizing reasons provided by the LLM for correct predictions

Across all 4 datasets, the LLMs make thousands of correct predictions. To summarize these for
easy inspection, we concatenated all reason strings provided by GPT-4 for predictions
evaluated to be correct. We then identified trigrams in the concatenated string using the ngram
package in R, and sorted them in decreasing order of frequency of occurrence to identify the
most common ones. We report the top 200 most frequent trigrams in Supplementary Table 9.
465

Sensitivity analysis for prompt structure

467
468 To examine how the prompt affects the prediction accuracy of the LLMs, we experimented with
469 replacing the prompt by a minimal alternative containing only the output format, task description,
470 and the locus information. We conducted these experiments with GPT-3.5 (model version "gpt-
471 3.5-turbo-0125"). The detailed prompt is described below, using the same example locus as
472 earlier.
473
474
475
System prompt:
From the list, provide the likely causal gene (matching one of the given genes), confidence (0:
very unsure to 1: very confident), and a brief reason (50 words or less) for your choice.
Return your response in JSON format, excluding the GWAS phenotype name and gene list in
the locus. JSON keys should be 'causal_gene','confidence','reason'.
Your response must start with '{' and end with '}'.
482
483 User prompt:
484 Identify the causal gene.
485 GWAS phenotype: {Morning person}
486 Genes in locus: {A},{B},{C},{D}
487

Embeddings for genes and phenotypes

489
490 We generated descriptions for genes and phenotypes using GPT-3.5 (model version "gpt-3.5-
491 turbo-0125") by using the prompt below.
492
493 "You are an expert in biology and genetics.
494 Your task is to provide biologically relevant information about the query below in 300 words or
495 less.
496
497 Query: {text}."
498

499   The "text" value was generated by adding the entity type (gene/phenotype) to the beginning of
500   the entity. So the value of text for the *BRCA1* gene would be "gene *BRCA1*", and that for the
501   breast cancer phenotype would be "phenotype breast cancer".
502
503   We provided the generated descriptions as input text to get embeddings using the OpenAI text
504   embedding model "text-embedding-3-large". This produced embeddings with 3,072 dimensions.
505

506   ## Embedding-based causal gene prediction

507
508   Using the computed embeddings, we provided the embedding-based causal gene prediction.
509   We calculated the dot product (identical to cosine similarity since the embeddings are
510   normalized to length 1) between the phenotype embedding and the gene embedding, and we
511   defined the predicted causal gene as the gene with the largest dot product of phenotype and
512   gene embeddings among all the genes in each loci.
513
514   To create the t-SNE plot for the *PCSK9* locus, we ran t-SNE on the 13 data points (1 phenotype
515   + 12 genes in the locus) using the Rtsne package with a perplexity of 4.
516

517   # Figures

518
519
Figure 1: Schematic illustrating the use of LLMs for identifying causal genes at GWAS loci, with
an example of an association for LDL cholesterol near the PCSK9 gene. For a GWAS locus, a
500 kbp window is extended on either side of the lead variant (indicated by the black dot), and
all genes within this window are considered as candidates. The LLM is then provided with the
phenotype name and the alphabetical list of genes and is instructed to predict the causal gene,
its confidence, and the reason for its choice. The part of the input prompt colored in orange is
the same for all loci, while the part in green is modified for each locus. For readability, output
formatting instructions are excluded from the figure.
528
529

535
536
Figure 2: Performance of LLMs and other methods on evaluation datasets, and the factors
affecting performance
a. Performance of all methods on evaluation datasets as measured by F-score (a
combination of precision and recall)
b. Precision-recall plot showing performance of all methods on each dataset
c. Impact of locus complexity on performance for all methods, measured by correlation of
prediction accuracy with number of genes at locus. All methods, including LLMs, perform
worse at loci with more candidate genes.
d. Impact of number of publications for the causal gene on performance for all methods,
measured by correlation of prediction accuracy with number of publications for causal
gene. Most methods show a positive correlation of performance with how well-studied
the causal gene is, except the nearest gene and L2G score methods.

554
555
Figure 3: Text embeddings of genes and phenotypes partially explain performance of LLMs
a) T-SNE plot to visualize text embeddings of the genes and phenotype at a locus for LDL
cholesterol in the Weeks et al. data. The causal gene *PCSK9* is closest to the LDL
cholesterol phenotype in the text embedding space as measured by cosine similarity.
b) Proportion of examples in the evaluation datasets where the causal gene is most similar
to the phenotype in the text embedding space as measured by cosine similarity.
562
563

Supplementary Tables

565
1 - Information about datasets
2 - Performance metrics for all methods and datasets
3 - Number of hallucinations per dataset for the LLM approaches
4 - Confidence scores predicted by LLMs and precision estimates for each score value
5 - Precision and recall stratified by phenotype for all methods and datasets
6 - GPT-4 provided reasons for examples about the phenotype 'Total protein' from the Weeks et
al. dataset
7 - Comparison of two GPT-4 version in number of hallucinations and performance metrics
8 - P-values from paired Wilcoxon's signed rank test and McNemar test comparing performance
of the LLM-based approach to the best non-LLM approach.
9 - Trigrams from the reasons reported by GPT-4 for correct predictions, along with their counts,
for the 200 most frequent trigrams
10 - Performance of LLMs on datasets with scrambled phenotypes
579
580
581

Acknowledgements

583 We would like to thank the employees of 23andMe for making this work possible. We would like
584 to acknowledge Elle Weeks, Hilary Finucane and Jacob Ulirsch for sharing the evaluation
585 dataset from their publication. We would also like to acknowledge David Hinds, Steve Pitts,

Data availability

We will share all processed datasets used in our analysis, as well as the prediction results from
all methods on all datasets, intermediate outputs like gene and phenotype embeddings using
Zenodo (doi: 10.5281/zenodo.11391053).

All source data were openly available. Download links:
1) OpenTargets - https://github.com/opentargets/genetics-gold-standards/
2) Pharmaprojects - https://github.com/ericminikel/genetic_support
3) Weeks et al. - https://www.finucanelab.org/data
4) GWAS Catalog - https://www.ebi.ac.uk/gwas/docs/file-downloads

Code availability

617 We will share the scripts we used to query the LLM, as well as the scripts we use to compute
618 our evaluation metrics using Zenodo (doi: 10.5281/zenodo.11391053). All prompts we used are
619 included in the manuscript or supplementary materials.