Efficient synthesis of 3D MR images for schizophrenia diagnosis classification with generative adversarial networks

Sebastian King[1,2], Yasmin Hollenbenders[1,2], Alexandra Reichenbach[1,2]*

[1]Center for Machine Learning, Heilbronn University, Heilbronn, Germany

[1]Medical Faculty Heidelberg, University of Heidelberg, Heidelberg, Germany

* Corresponding Author

Email: alexandra.reichenbach@hs-heilbronn.de

Abstract

Schizophrenia and other psychiatric disorders can greatly benefit from objective decision support in diagnosis and therapy. Machine learning approaches based on neuroimaging, e.g. magnetic resonance imaging (MRI), have the potential to serve this purpose. However, the medical data sets these algorithms can be trained on are often rather small, leading to overfit, and the resulting models can therewith not be transferred into a clinical setting. The generation of synthetic images from real data is a promising approach to overcome this shortcoming. Due to the small data set size and the size and complexity of medical images, i.e. their three-dimensional nature, those algorithms are challenged on several levels. We develop four generative adversarial network (GAN) architectures that tackle these challenges and evaluate them systematically with a data set of 193 MR images of schizophrenia patients and healthy controls. The best architecture, a GAN with spectral normalization regulation and an additional encoder (α-SN-GAN), is then extended with an auxiliary classifier into an ensemble of networks capable of generating distinct image sets for the two diagnostic categories. The synthetic images increase the accuracy of a diagnostic classifier from a baseline accuracy of around 61% to 79%. This novel end-to-end pipeline for schizophrenia diagnosis demonstrates a data and memory efficient approach to support clinical decision-making that can also be transferred to support other psychiatric disorders.

Introduction

Schizophrenia (SCZ) is a heterogeneous neurological disease characterized by a broad spectrum of symptoms including delusions, hallucinations, and disorganized thinking (1). Due to a lack of reliable diagnostic biomarkers (1, 2), psychiatrists currently diagnose SCZ based on the Diagnostic and Statistical Manual of Mental Disorders (DSM-V) (3). The disorder is connected to a variety of genetic and environmental factors and genetic, blood, as well as brain alterations have been linked to it (1, 4).

Brain imaging with structural magnetic resonance imaging (sMRI) has been explored for supporting the objective diagnosis of SCZ. Due to the widespread but subtle changes in brain matter of SCZ patients (5), multivariate approaches such as machine learning (ML) algorithms are prominently explored for automated support of objective SCZ diagnoses. ML considers a diagnosis as classification problem sorting images into the classes „healthy" or „patient". Approaches include feature extraction combined with traditional ML algorithms (5) as well as deep learning (DL) algorithms, which allow automatic feature extraction (6, 7). The latter enables SCZ classification without a priori hypotheses about specific brain regions being discriminatory for the task at hand. 3D convolutional neural networks (3D-CNNs), a type of DL algorithms for three-dimensional inputs, achieve state-of-the-art performance up to 95% accuracy for SCZ "diagnosis" based on sMRI images (7-9). However, DL algorithms tend to overfit on small data sets (10).

Training robust and reliable DL classifiers requires large training data sets, which is challenging for medical image data. Image acquisition is expensive and expert knowledge is required to label the data. Therefore, an effort is made to assemble such images in publicly available data sets to further research. However, publicly available MRI data sets from SCZ patients and healthy controls (HC) are still rather small, ranging from 50 to 600 images per class (8). To increase the robustness of

classification, data augmentation techniques have been employed to bolster small data

sets for training the classifier (11). Traditional approaches from image classification,

e.g. affine transformations or similar distortions, are less suitable for MRI images.

However, generative ML methods like generative adversarial networks (GAN) provide

promising new techniques for data augmentation (12). An added bonus of these

techniques is the generation of genuinely synthetic data, which does not underlie the

strict regulations of patient data (12, 13). The data generated with these models can

therefore be published more easily and benefit a wide crowd of researchers. GAN

architectures consist of at least two neural networks: a generator and a discriminator.

The generator tries to produce images similar to those of a reference data set by using

the feedback from the discriminator who learns to distinguish between real images and

synthetic ones. GANs in various adaptions have shown the technical capability of

synthesizing medical imaging data including the generation of brain images (13),

mainly for 2D slices but also for 3D volumes (12, 14, 15). They can also be conditioned

to produce data of a given class affiliation (12, 16, 17), i.e. patients or HC. Medical

images like sMRI volumes challenge GANs four-fold: 1) small data sets can lead to

discriminator overfit, causing the vanishing gradients problem (18, 19); 2) most

algorithms for image processing were first, or only, implemented and optimized for 2D

data; 3) complex, i.e. 3D, images tend to converge to a very small distribution of

generated images causing mode collapse (14); 4) 3D images and operations need

exponentially more memory. End-to-end generation of synthetic data from a very small

3D sMRI data set and downstream data-driven "diagnosis" classification has not yet

been demonstrated, nor have MR images for SCZ classification been produced before.

We address the previously mentioned challenges with a publicly available data set of

sMRI data consisting of 102 SCZ patients and 91 HC, furthering the development of

four 3D deep convolutional GAN (DC-GAN) architectures with various modifications,

and systematically comparing the resulting architectures. The winning architecture is

then extended by three conditional approaches to produce data from the two clinical

groups and the best combined architecture is chosen to produce synthetic data for

training a 3D-CNN SCZ "diagnosis classifier". This classifier is trained with different

ratios of real and synthetic data and then tested with real data. An increase in

classification accuracy when training with synthetic data demonstrates the added value

of this generated data. In sum, this study contributes to the data and memory-efficient

training of DL classifiers in medical imaging.

Methods

Data

The data set used in this study was obtained from the MCIC collection (20) in July 2019. The collection contains structural T1-weighted MR images of 158 adult SCZ patients and 169 demographic, age, and sex-matched HC. Four research sites were involved in the data collection process from July 2004 to July 2006. All subjects provided informed consent to participate in the study and successfully completed a questionnaire verifying that they understood the study procedures. The study protocol was approved by the human research committees at each of the sites (UNM HRRC #03-429; UMinn IRB #0404 M59124; MGH IRB# 2004P001360; UIowa IRB #1998010017). Patients had to be diagnosed with SCZ conforming to the Diagnostic and Statistical Manual of Mental Disorders, 4th Edition (DSM-IV). A differentiation between distinct types and severities of SCZ was not conducted. We included only data from sites A, C, and D because the images originating from site B were not publically released due to IRB restrictions. Furthermore, the data from nine subjects failed transformation to BIDS format (21) due to missing meta-data, leaving a subset of 102 SCZ and 91 HC for this study. Sex distribution in the remaining data set was imbalanced with 61 female (A: 20; C: 21; D: 20) and 152 male (A: 70; C: 39; D: 43) subjects. Age of the subjects ranged from 18 to 60 years (A: 18-60; C: 18-60; D: 20-57).

Data were pre-processed using the nypipe toolbox (22) for Python. First, images were skull-stripped and registered to MNI space in 1mm^3 isotropic resolution with nypipe wrapper functions for SPM12 (23). To remove outliers, we capped voxel intensity at upper and lower 1% quantile of values and then rescaled the images to the range of -1 to 1. Finally, slices containing only background were trimmed.

In order to reduce the complexity of the classification and generation problem, we tested in a pre-study whether the reduction of image size from 128^3 to 64^3 voxel

compromised the information content usable for a diagnostic classifier. Using the same

classification algorithm and training strategy as in the main study (cf. Diagnosis

classifier), we found that classification accuracy did not suffer from down sampling

(59.1±7.1% for high resolution and 60.6±7.6% for low resolution; t_8=0.29; p=.779). The

number of parameters, however, decreased around 12-fold from 90,198,561 to

7,361,057, analogously decreasing the computational resources for training the

classifier. Therefore, we proceeded with images sampled down to around 2mm^3 voxel

size with 64^3 voxel for the main study.

Experimental procedure

Four GAN architectures based on a 3D DC-GAN are adapted to address our

challenges, and evaluated for their image synthesis capabilities (**Fig 1**). Spectral

normalization regularization (SN-GAN) (24) counteracts the vanishing gradients

problem that often occurs for small sample sizes and is therefore applied for all

architectures. Additionally incorporating an encoder (α-SN-GAN) (14) helps to alleviate

mode collapse.

Fig 1   **Processing pipeline with architecture selection.** Four basic architectures are

designed to alleviate different problems during data synthesis and all four are tested with and without

additional augmentation during training (DiffAugment). The best basic architecture is then expanded by

three approaches for the generation of different clinical classes (schizophrenia patients *vs.* healthy

controls). The best conditional architecture is then used to synthesize data for training a classifier that can

be used for decision support in schizophrenia diagnosis. Abbreviations: SN (spectral normalization), GAN

(generative adversarial network), α (with encoder), HA (hierarchical amortized)

To reduce the computational cost of the training, a hierarchical approach is adapted

(HA-GAN) (15), which is also combined with the α-SN-GAN to join their advantages (α-

HA-GAN). Vanishing gradient and mode collapse are additionally addressed by

applying data augmentation during training (*DiffAugment*) (19) to all four architectures,

resulting in eight basic architectures being tested. The best architecture is selected for

further processing based on qualitative and quantitative evaluation.

Subsequently, three conditioning approaches are employed for creating images of the

two clinical groups (SZC / HC): one classifier per class, an auxiliary classifier, and a

projection discriminator. The winner architecture is then used to generate different sets

of training data with different ratios of real and synthetic data and different set sizes.

Finally, a diagnosis classifier is trained on these data sets to separate SCZ patients

from HC in a test data set consisting of real data only.

Diagnosis classifier

The purpose of generating synthetic data in this study is to train a classifier that

separates sMRI from SCZ and HC, henceforth called a diagnosis classifier. We

employed a 3D-CNN since these types of networks have shown high performance in

diagnosing schizophrenia from sMRI in previous studies (7-9, 25). The architecture is

based on the VGG16 architecture (26). In brief, the model consists of multiple 3D

convolution blocks and linear layers at the end. A 3D convolution block consists of a

convolution layer, a Rectified Linear Unit (ReLU) activation function, a batch

normalization layer, and a max pooling layer. In between the linear layers, dropout is

used. For details on the architecture, see Supplementary material Fig S1.

For the training of each classifier, we chose a stratified 5-fold cross-validation approach

with a batch size of 12. The training is executed with an AdamW optimizer (27) with a

learning rate of $5e^{-6}$ and weight decay of 0.01. Hyperparameters are based on (26) and

then tuned manually. To account for overfitting effects, all classifiers are trained past

their convergence and the classifier at the minimum validation loss of each split is

chosen.

Basic architectures for image synthetization

GAN architectures in this study are all based on the standard deep convolutional GAN

(DC-GAN) (28) architecture, sometimes also referred to as CNN-GAN. This

architecture consists of two networks. The generator network synthesizes images that

resemble real sMRI images by projecting a randomly sampled latent space of a prior

distribution z to the target distribution X. The discriminator network learns to distinguish

real sMRI images from synthetic ones, produced by the generator. The adversarial loss

consists of two different loss terms for updating the discriminator and the generator.

Despite its success, the DC-GAN architecture suffers from two major problems:

vanishing gradients (29, 30) and mode collapse (14, 24, 29, 30). Vanishing gradients

describes a phenomenon in which the discriminator network saturates quickly and in

return fails to provide a meaningful gradient to the generator. This problem is magnified

for small data sets since they are easily memorable for the discriminator. Mode

collapse occurs when the generator succeeds in creating images that are classified as

real by the discriminator but only produces a small variety of them.

All GANs were trained using the Adam optimizer with a learning rate of 0.0002, $\beta1=0.5$,

and $\beta2=0.999$ for all networks. We chose those training parameters and a latent space

size of 1000 since this size has shown to be effective in related works (14, 15). Each

GAN training was performed for 12,000 iterations with a batch size of four.

SN-GAN

A DC-GAN [23] with Spectral Normalization (SN) (24) applied (SN-GAN) is used to

alleviate the vanishing gradients problem. Two changes regarding the discriminator

regularization and the upsampling in the generator are applied to the DC-GAN

architecture to form the SN-GAN (cf. Supplementary material Figs S2 and S3). The

basic idea of regularization techniques is to avoid steep gradients and therefore fast

changes in the discriminator's weights, which lead to the vanishing gradients problem.

Spectral normalization achieves this by renormalizing the weights of a layer according

to $W_{SN} = \frac{W}{\sigma(W)}$, where σ denotes the spectral norm of the weight matrix W. This

enforces a maximum Lipschitz constant of 1 for the discriminator which results in

slower but more stable updates of the network.

SN has achieved competitive results over the application of a gradient penalty (GP)

(29), which is the successor to weight clipping in Wasserstein GANs (WGAN) (30).

Contrary to SN, GP only penalizes large gradients by adding a penalty term to the loss

function instead of enforcing a hard constraint. Due to its lower computational cost

compared to GP, SN is preferred over GP in this study for all models regardless of their

original regularization technique.

Another change compared to the original DC-GAN addresses the upsampling

technique in the generator. Instead of transposed convolutions, we used pixel-shuffle

(31) layers to increase the image size. This technique is chosen because it is

computationally more efficient while increasing the number of parameters by shifting

the upsampling process to the feature dimension. Contrary to interpolation approaches

for upsampling, pixel-shuffle allows for learned upsampling filters and therefore leads to

a higher flexibility of the network. To eliminate the occurrence of checkerboard

artefacts, we use an initialization scheme that resembles nearest-neighbour

upsampling in the early stages of the training (32). To further increase the flexibility of

the model, the leaky ReLU activation function is used in the generator as well as the

discriminator. The original DC-GAN implementation uses the ReLU activation function

only in the generator.

α-SN-GAN

To combat mode collapse, an α-WGAN-GP (14) architecture, which has been used for

medical 3D image generation on small medical data sets, is employed. We adapt the

architecture of the α-WGAN-GP with SN and replace the Wasserstein Loss (30) with

the Hinge Loss (24, 33), therefore naming the adapted architecture α-SN-GAN.

To encourage the generator not to fall into the mode collapse, its goal is changed by

introducing an encoder to the architecture (14, 34, 35) (cf. Supplementary material Fig

S4). The encoder is used to produce a latent space representation of real images,

which is used for training the generator along with the randomly sampled latent spaces.

An additional reconstruction loss term like the L1 loss encourages the generator to

produce images that cover the diversity of the whole data set (34, 35). The loss

function of the encoder is based on the Kullback-Leibler divergence (35) as distance

metric, which leads the encoder to produce a distribution close to a randomly sampled

latent space.

To counteract a common drawback of GAN architectures with encoders, blurry images,

we adapted the α-GAN approach (34) for all encoder models in this study. Our

approach introduces a code discriminator (cf. Supplementary material Fig S5)

discriminating between randomly sampled latent spaces and encoded latent spaces.

The code discriminator considers the randomly sampled latent spaces as real and the

encoded latent spaces as fake, therewith encouraging the encoder to generate latent

spaces close to the random distribution. The code discriminator used in this study

consists of linear layers with spectral normalization. It is trained with the same loss

function as the regular discriminator.

HA-GAN

To achieve resource efficiency, we leveraged the hierarchical HA-GAN (15), which was

proposed to synthesize 3D medical images computationally effectively. It achieves

shorter training times at a reduced memory consumption compared to the architectures

previously introduced.

The HA-GAN implements the hierarchical structure by splitting each of the GAN's

networks into a high-resolution and a low-resolution path (cf. Supplementary material

Fig S6). A random image sub-volume of fixed size is used to train the high-resolution

path whereas the low-resolution path is trained using a down-sampled version of the

image thus lowering the overall memory consumption. In addition to these models, both

generators share a generator that synthesizes images up to the size of the low-

resolution images, whose output is then used for the high- and low-resolution

generators. During inference mode, when no gradients need to be calculated, the high-

resolution generator synthesizes full-sized images.

We adapted the HA-GAN architecture to create 64^3 images with a sub-volume size of

8x64x64 and down-sampled images to one fourth of the original size (16^3). The HA-

GAN has been introduced for larger data sets and larger image sizes (128^3 and 256^3)

(15), on which it demonstrated improved quality compared to a WGAN and α-GAN. The

models' performance on a small data set as well as smaller image size has not yet

been tested.

α-HA-GAN

The combination of the α-SN-GAN's training scheme and the HA-GAN architecture

offers the possibility of performing a resource-efficient training of 3D GANs on small

data sets (α-HA-GAN). The α-SN-GAN's encoder is replaced with the memory-efficient

encoder (15) and in the same way the discriminator and generator are split into a high-

and low-resolution network. The high-resolution encoder produces a latent space of the

same size as the high-resolution generator's input and is trained by an L1 loss to

minimize the difference between the input image and the high-resolution generator's

reconstruction of it. A concatenation of all high-resolution encoder outputs of all non-

overlapping sub-volumes X_c of the image is fed into the low-resolution encoder, which

then is trained in the same fashion as the α-SN-GAN's encoder. The resulting network

combines all previously introduced techniques to leverage their improvements

(Supplementary material Fig S6).

Contrary to the SN-GAN and the α-SN-GAN architectures, the hierarchical ones are

trained using the standard GAN loss since the Hinge Loss led to instability in the

training.

DiffAugment

Additionally to the four architectures, we adapted DiffAugment (19) for 3D images and

applied this technique to each architecture. DiffAugment describes the application of

data augmentation in the training process of the GAN itself boosting the data set with

augmented images to counteract mode collapse as well as the vanishing gradients

problem. Augmentations are achieved with translation, masking, and colour or intensity

range bias in the images. These augmentations are applied to each input of the

discriminator. Since the generator is updated using the discriminator's feedback, its

gradients need to be able to flow through the discriminator as well as the

augmentations during the backward pass of the generator. It is therefore necessary for

the applied augmentations to be differentiable. Differentiable augmentations are

applicable for real and synthesized discriminator inputs contrary to regular

augmentations. This is necessary to prevent augmentation artefacts in the synthesized

images.

Architectures for conditional image synthetization

The purpose of data synthetization in this study is to generate training data for

diagnosis classification; therefore, we need to generate data for two classes, i.e. two

clinical groups: SCZ and HC. The most straightforward approach is to train two

separate GANs with data from each group, respectively. A complementary approach is

employed with conditional GANs (cGANs) (16) incorporating a class label in the

synthetisation process. Different approaches exist for introducing this information in the

generator and the discriminator. For the generator, we introduce the class information

by concatenating an embedding of the label to the latent space for all conditional

models. For the discriminator, we implement two different approaches.

Projection discriminator

Conditional discriminators incorporate the label in their architecture and output only the

realism score or probability of being real for a given input (16, 36-38). Three techniques

have been proposed to introduce the class label y to the discriminator: Concatenation

of the label to the input layer (16), to an intermediate layer (37, 38), or alternatively

forming the inner product to include the label information instead of the concatenation,

resulting in the projection discriminator (36). The latter has previously demonstrated the

highest performance (36) and will therefore be used in this study.

Auxiliary classifier

Auxiliary Classifier GANs (AC-GANs) (39, 40) use an additional classification to provide

feedback about the distinctness of the two data sets to the generator. They can be

approached in two ways. The first one splits the discriminator at an intermediate layer

to perform two different classifications: one for the realism of the image and one for the

class affiliation (39). The second approach involves a separate classifier (40). In the

latter, the original discriminator remains unaltered, thus its architecture is similar to a

non-conditional discriminator. In theory, this method yields better results since the

separated classifier is only trained on real images and is therefore not influenced by

generated images. Additionally, unbalanced data sets are accounted for by the

separated classifier contrary to the first approach (40). These reasons lead to the use

of only the second approach in this study. The auxiliary classifier is a 3D-CNN classifier

using the same structure as the discriminator (cf. Supplementary material Fig S3). It

was trained in advance to overfit on the real data set to ensure correct classification of

synthetic images. During the GAN training it is only used in inference mode and not

trained any further.

344   Evaluation of synthetic data

345   Quantitative evaluation

Since the goal of GAN generators is the synthesize data with a distribution similar to

the real data distribution, we utilize distance metrics to quantify the synthetization

quality. Two commonly used distance metrics are the Maximum Mean Discrepancy

(MMD) (41) and the Fréchet Inception Distance (FID) (41). Both metrics combine the

fidelity and diversity of generated images into one single score. To separate those

performance measures, precision and recall metrics (42) are additionally calculated.

Precision represents the proportion of generated images inside the target distribution

whereas recall represents the coverage of the target distribution by the generated

images.

In most image generation studies, GAN distance metrics are calculated based on

features extracted with an Inception network architecture (43) pre-trained on the

ImageNet data set (44) rather than whole images (41, 42, 45). For medical 3D MR

images, however, we could not use this pre-trained model because the Inception

network cannot process 3D image data and a classifier trained on the ImageNet data

set does not extract medically relevant features (46). To alleviate both problems, a

ResNet50 architecture pre-trained on 3D medical image data sets (47), was adapted to

perform the extraction that were then used to calculate all the distance metrics. Note

that this approach prevents the direct comparability of this study to others that use

those distance metrics based on the Inception network trained on the ImageNet data

set.

For each of the trained architectures, we generate ten data sets each containing as

many synthetic images as real images available for the respective generation model.

Qualitative evaluation

The synthetic data is evaluated qualitatively based on exemplary brain sections and the

visualization of the distribution of the two first components from a principal component

analysis (PCA) of the image features. For the PCA, the same features were extracted

as for the quantitative evaluation.

Evaluation with diagnosis classifier

Since the synthetic data was generated to improve the training of the diagnosis

classifier, the final test for the synthetic data was to serve as training data for the

classifier. The classifier was trained with a stratified 5-fold cross validation approach,

using in each fold 60% of the data for training (61 SCZ and 55 HC images), and 20% of

the real data for validation and test, respectively. Baseline classification accuracy was

established training with real data only (**Table 1**). An additional baseline was

constructed with an augmented data set of the same size as the real data training set.

Here, we used the same augmentation techniques on the real images as for the

DiffAugment step in the GAN evaluation: Random cropping of half the image size at

most, translation of 1/8 maximum in each direction, and intensity randomization from

0.7 to 1-times the original value. Each image distortion was applied with a probability of

one third.

In order to test the performance of training with synthetic data of the same size as the

real training data, we constructed two training data sets containing synthetic images.

For the mixed (small) data set, we replaced half of the real training data with synthetic

data, for the synthetic (small) data, we replaced all real training data with synthetic

images (**Table 1**).

394   **Table 1 Training data sets for the diagnosis classifier.**

Data set	Schizophrenia Patients (real / synthetic)	Healthy Controls (real / synthetic)
Real (small)	61 / -	55 / -
Augmented (small)	61 / -	55 / -
Mixed (small)	31 / 30	28 / 27
Mixed (large)	61 / 305	55 / 275
Synthetic (small)	- / 61	- / 55
Synthetic (large)	- / 367	- / 328
Synthetic (infinity)	- / 65,400	- / 56,400

Larger data sets are used for training to assess the effects of the data set size on the

classifier's performance. For the large mixed training data set, we boosted the real

training data with five times the number of synthetic samples. This data set size is

matched for the large synthetic training data set, containing synthetic images only

(**Table 1**). Lastly, an "infinite" data set is trained, which is achieved by sampling a new

random synthetic batch for each iteration. It reached its maximum performance after

4700 iterations, which equals a data set of 56,400 samples. Note that the validation

and test data always consists of real data only, i.e. we test the robustness of the

classifier to correctly classify real unknown MR images.

Statistical analyses

407   For comparison of results produced by different generative models or for different data

408   sets we use fixed-effects ANOVAs with between-subjects factors. Post-hoc tests are

409   two-tailed unpaired *t*-tests with Bonferroni correction for all possible combinations of

410   tests. Test results are reported as significant for $\alpha < .05$. Reported values denote mean

411   with distance to the upper and lower boundary of the 95% confidence interval.

Results

Basic architecture selection

All four quantitative evaluation metrics (**Fig 2**) perform sign. better without *DiffAugment* than with (all $F_{1,72}>35.21$; $p<.001$) and demonstrate sign. differences between the architectures (all $F_{3,72}>317.03$; $p<.001$). The average values of the evaluation metrics consistently show an advantage of the α-SN-GAN architecture over the three other models (Fig 2). Indeed, 10/11 out of the 12 post-hoc tests comparing this architecture to the other ones confirm a sign. better performance (all 11 tests $t_{38}>2.73$; $p<.010$; sign. on α<.05 with/without correction for multiple comparisons).

Fig 2 **Quantitative evaluation metrics for the four basic architectures.** Note that lower values indicate a better performance for MMD (a) and FID (b) while higher values indicate a better performance for precision (c) and recall (d). Error bars denote 95% confidence intervals. Abbreviations: SN (spectral normalization), GAN (generative adversarial network), α (with encoder), HA (hierarchical amortized).

Visually, the quality of the images synthesized by the SN-GAN and the α-SN-GAN is high (**Fig 3**). However, there are still limitations to fully resembling the real samples, especially regarding fine-grained structures. A clear difference between samples with and without DiffAugment is not present. The collapse of the hierarchical architectures is also visible here. Artefacts and deformations can clearly be seen in their samples. These appear stronger in the HA-GAN, which is in line with the findings of the quantitative evaluation. The illustrations of the PCA confirm these findings as well (Supplementary material Fig S7).

Fig 3 **Exemplary synthetic images of the four architectures (rows) without and with**

DiffAugment applied (columns), two of each kind. Exemplary real images are presented in the bottom

row for comparison. All sections show slice 32.

To summarize, regularization combined with incorporating an encoder (α-SN-GAN)

yields synthetic images of highest fidelity and diversity shown with both qualitative and

quantitative evaluation. The α-SN-GAN architecture without *DiffAugment* is therefore

chosen as basis for the subsequent further architecture selection and data generation

processes.

Conditional architecture selection

All four quantitative evaluation metrics (**Fig 4**) demonstrate sign. differences between

the conditional architectures $(F_{2,54}>10.06;$ $p<.001)$ as well as the clinical groups

$(F_{1,54}>11.40;$ $p=.001)$. For the clinical groups, we do not find a clear advantage of one

over the other: MMD and recall achieve a better performance for the synthetic patient

images while FID and precision favour the synthetic HC images. For the conditional

architectures, however, we find a consistent advantage of the architecture with the

auxiliary classifier across all four evaluation metrics (**Fig 4**). Indeed, 6/7 out of the 8

post-hoc tests comparing the average values of this conditional approach to the other

two confirm a sign. better performance (all 7 tests $t_{38}>2.97;$ $p<.006;$ sign. on α<.05

with/without correction for multiple comparisons).

Fig 4 **Quantitative evaluation metrics for the three conditional architectures.** Note that

lower values indicate a better performance for MMD (a) and FID (b) while higher values indicate a better

performance for precision (c) and recall (d). Error bars denote 95% confidence intervals.

Visually, the quality of the generated images is high, rather independent of the

conditional approach (**Fig 5** and Supplementary material Figs S9 and S10). The

illustrations of the PCA confirm the subtle differences found with the quantitative

evaluation (Supplementary material Fig S8).

Fig 5 **Exemplary synthetic images of the three differential conditional architectures**

based on the α-SN-GAN (rows) for the control and patient group (columns), two of each kind.

Exemplary real images are presented in the bottom row for comparison. All sections show slice 32.

To summarize, synthesizing the two clinical groups with the auxiliary α-SN-GAN yields

images of highest fidelity and diversity shown with both qualitative and quantitative

evaluation. This architecture yields precision and recall values above 95% for both

clinical groups (**Fig 4**c & d). The α-SN-GAN architecture with auxiliary classifier is

therefore chosen as basis for the subsequent data generation processes.

Diagnosis classification

Classification based on training with the real data achieves 60.6±7.6% diagnostic

accuracy, a value well above chance level (t_4=2.72; p=.026). However, this accuracy

still leaves potential for improvement. Training the diagnosis classifier on the same

amount of augmented, mixed, or synthetic data (**Fig 6**, small training data size) yields a

comparable accuracy to training on the real data ($F_{3,16}$=0.36; p=.786). Increasing the

training data 6-fold yields sign. higher classification accuracy than training with the real

data for both the mixed (t_8=3.94; p=.002) and the synthetic (t_8=4.06; p=.002) training

data (**Fig 6**, large training data). Note that the classifiers are always tested on real data

only. The strategy of the classifier is not biased towards the one or the other class

when artificial data is added or used for training (cf. additional performance metrics in

Supplementary Fig S11). Training with the 6-fold amount of synthetic data increased

the diagnostic accuracy to 78.9±4.4%, which corresponds to an average increase of

18.3% with respect to the original classification accuracy of the classifier trained with

real data only. Note that this accuracy cannot be increased further as demonstrated

with the synthetic infinity training data set (**Fig 6**, diamond).

Fig 6   **Classification accuracies for all training data sets.** Note that the classifiers are

always tested on real data only. Dotted line indicates chance level. Error bars denote 95% confidence

intervals. * comparison to real data for training (Bonferroni corr. on α<.05).

Discussion

This work demonstrates the synthesis of high-quality 3D brain sMRI data for two

clinical groups from a very small data set. A diagnostic classifier separating real sMRI

data from SCZ patients and HC can be trained with the synthetic data just as well as

with the same amount of real data. Increasing the amount of synthetic training data 6-

fold increases the performance of the diagnosis classifier by nearly 20%. This increase

suggests that the synthetic data is capable of making the algorithm more robust for

classifying the real data.

We demonstrate that regularized GANs produce high quality images even for small 3D

sMRI data sets. Creating a high diversity of images instead of falling into mode

collapse can be achieved by incorporating an encoder in the training process whereas

applying DiffAugment to the GAN training did not improve image quality. Memory

efficient processing with hierarchical architectures, however, was not successful in the

case of the small data set used in this study. The study with the original implementation

of the HA-GAN [14] used a larger data set of more than 3000 samples compared to the

193 images in this study. Considering that the HA-GAN and α-HA-GAN consist of five

and eight individual neural networks, respectively, that all need to work in an

equilibrium during the training, the low number of training samples might contribute to

an unstable training process.

Comparing GAN metrics to related works is difficult due to multiple possible

implementations of the MMD metric and additionally due to the use of a different

feature extraction network. At least visually, however, the comparison can be made.

The synthetic images in this study are on the same level as the ones of Kwon et al. [13]

with the same image size but with a larger data set of around 500 images.

The first work demonstrating the feasibility of generating 3D sMRI data with a true 3D

GAN was based on a subset of nearly thousand images (14). Since the data included

HC only, the usefulness of the data for clinical application could not be assessed. The

first work conditioning the generated data for a clinical use case utilized a 3D

architecture only for the discriminator but not for the generator, which constructed

contingent 2D slices instead of volumes (17). In the aforementioned study, the data

quality was assessed thoroughly by statistical comparison of known disease

biomarkers between the groups of generated data. A downstream diagnostic classifier,

i.e. assessing the usefulness of the generated 3D data for training an algorithm that

distinguishes between healthy and diseased persons, has not been tested yet. Indeed,

differentiated MR images for SCZ patients and HC have not yet been synthesized

either. The performance gain of the diagnosis classifier with the large synthetic data set

is in the same range as found in a study using 2D MR images (48). In that study,

classification of Alzheimer's patients and HC increased in accuracy from 63% to 83%.

However, the data set consisted of slightly above 1000 samples compared to the 193

samples in this work. Admittedly, the diagnosis classifier's performance of this study

starts at the lower end of the spectrum but rises to the middle to upper end by

augmenting with synthetic samples (8). The increase is mainly contributed to the

increased data set size combined with the high fidelity and diversity of the synthetic

images. This is especially remarkable because classifier based on large data sets often

do not reach a classification accuracy compared to small, specialized sets (10).

The systematic comparison of GAN architectures for basic training as well as for

conditioning the data on the clinical group demonstrates that the architectural choices

for the GAN are essential and the resulting data always needs to be evaluated

carefully. Even though the α-SN-GAN architecture with auxiliary classifier generated

the best synthetic data for the data set used in this study, this architecture may not be

the best one for every data set and every purpose. We therefore suggest that always

several architectural variants that address potential problems arising from the specific

data set at hand are compared and thoroughly evaluated for the purpose the data is

needed. Techniques that work for one application are not necessarily successful in

another one despite their theoretical validity. Additionally, combinations of techniques

may not be compatible.

This approach can also be adapted to bolster other imaging modalities such as

functional MRI for training multimodal classifiers that have shown promise for SCZ

diagnosis. Furthermore, the auxiliary classifier approach has the potential to reveal the

underlying structural differences between two clinical groups and might therefore aid in

the research for SCZ biomarkers. GANs are only one kind of generative DL

architecture for image synthetisation. Other DL architectures such as transformers (49)

have risen the past years and demonstrated exceptional capabilities in various

domains not only language understanding and synthesis but also in medical image

synthesis (50). However, the problem of small medical data sets is even graver with

these architectures and pre-training on data of other domains might have its limitations

in medical application (51).

To conclude, generating synthetic (neuro)imaging data is a promising approach,

especially for clinical use cases with inherently small data set sizes. With this work, we

demonstrate the ability to train GANs even on a complex, small data set for a

psychiatric disorder such as SCZ that lacks objective diagnostic tools. Importantly, the

generated data enables a more robust training of a downstream diagnostic classifier.

References

1.   Jablensky A. The diagnostic concept of schizophrenia: its history, evolution, and future prospects. Dialogues in Clinical Neuroscience. 2010;12(3):271-87.

2.   Shepherd AM, Laurens KR, Matheson SL, Carr VJ, Green MJ. Systematic meta-review and quality assessment of the structural brain alterations in schizophrenia. Neuroscience & Biobehavioral Reviews. 2012;36(4):1342-56.

3.   Tandon R, Gaebel W, Barch DM, Bustillo J, Gur RE, Heckers S, et al. Definition and description of schizophrenia in the DSM-5. Schizophrenia research. 2013;150(1):3-10.

4.   Mohammadi A, Rashidi E, Amooeian VG. Brain, blood, cerebrospinal fluid, and serum biomarkers in schizophrenia. Psychiatry research. 2018;265:25-38.

5.   de Filippis R, Carbone EA, Gaetano R, Bruni A, Pugliese V, Segura-Garcia C, et al. Machine learning techniques in a structural and functional MRI diagnostic approach in schizophrenia: a systematic review. Neuropsychiatric disease and treatment. 2019:1605-27.

6.   Qureshi MNI, Oh J, Lee B. 3D-CNN based discrimination of schizophrenia using resting-state fMRI. Artificial intelligence in medicine. 2019;98:10-7.

7.   Oh J, Oh B-L, Lee K-U, Chae J-H, Yun K. Identifying schizophrenia using structural MRI with a deep learning algorithm. Frontiers in psychiatry. 2020;11:16.

8.   Sadeghi D, Shoeibi A, Ghassemi N, Moridian P, Khadem A, Alizadehsani R, et al. An overview of artificial intelligence techniques for diagnosis of Schizophrenia based on magnetic resonance imaging modalities: Methods, challenges, and future works. Computers in Biology and Medicine. 2022;146:105554.

9.   Hu M, Sim K, Zhou JH, Jiang X, Guan C, editors. Brain MRI-based 3D convolutional neural networks for classification of schizophrenia and controls. 2020 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC); 2020: IEEE.

10.   Rakić M, Cabezas M, Kushibar K, Oliver A, Lladó X. Improving the detection of autism

spectrum disorder by combining structural and functional MRI information. NeuroImage:

Clinical. 2020;25:102181.

11.   Chlap P, Min H, Vandenberg N, Dowling J, Holloway L, Haworth A. A review of medical

image data augmentation techniques for deep learning applications. Journal of Medical

Imaging and Radiation Oncology. 2021;65(5):545-63.

12.   Yi X, Walia E, Babyn P. Generative adversarial network in medical imaging: A review.

Medical image analysis. 2019;58:101552.

13.   Laino ME, Cancian P, Politi LS, Della Porta MG, Saba L, Savevski V. Generative

adversarial networks in brain imaging: A narrative review. Journal of Imaging. 2022;8(4):83.

14.   Kwon G, Han C, Kim D-s, editors. Generation of 3D brain MRI using auto-encoding

generative adversarial networks. International Conference on Medical Image Computing and

Computer-Assisted Intervention; 2019: Springer.

15.   Sun L, Chen J, Xu Y, Gong M, Yu K, Batmanghelich K. Hierarchical amortized GAN for 3D

high resolution medical image synthesis. IEEE journal of biomedical and health informatics.

2022;26(8):3966-75.

16.   Mirza M, Osindero S. Conditional generative adversarial nets. arXiv preprint

arXiv:14111784. 2014.

17.   Jung E, Luna M, Park SH. Conditional GAN with 3D discriminator for MRI generation of

Alzheimer's disease progression. Pattern Recognition. 2023;133:109061.

18.   Karras T, Aittala M, Hellsten J, Laine S, Lehtinen J, Aila T. Training generative

adversarial networks with limited data. Advances in neural information processing systems.

2020;33:12104-14.

19.   Zhao S, Liu Z, Lin J, Zhu J-Y, Han S. Differentiable Augmentation for Data-Efficient GAN

Training. 2020.

20.   Gollub RL, Shoemaker JM, King MD, White T, Ehrlich S, Sponheim SR, et al. The MCIC

collection: a shared repository of multi-modal, multi-site brain image data from a clinical

investigation of schizophrenia. Neuroinformatics. 2013;11:367-88.

21.   Gorgolewski KJ, Alfaro-Almagro F, Auer T, Bellec P, Capotă M, Chakravarty MM, et al.

BIDS apps: Improving ease of use, accessibility, and reproducibility of neuroimaging data

analysis methods. PLOS Computational Biology. 2017;13(3):e1005209.

22.   Gorgolewski K, Burns CD, Madison C, Clark D, Halchenko YO, Waskom ML, et al.

Nipype: a flexible, lightweight and extensible neuroimaging data processing framework in

python. Frontiers in neuroinformatics. 2011;5:13.

23.   Ashburner J, Barnes G, Chen C-C, Daunizeau J, Flandin G, Friston K, et al. SPM12

manual. Wellcome Trust Centre for Neuroimaging, London, UK. 2014;2464(4).

24.   Miyato T, Kataoka T, Koyama M, Yoshida Y. Spectral normalization for generative

adversarial networks. arXiv preprint arXiv:180205957. 2018.

25.   Vyškovský R, Schwarz D, Churová V, Kašpárek T. Structural MRI-Based Schizophrenia

Classification Using Autoencoders and 3D Convolutional Neural Networks in Combination with

Various Pre-Processing Techniques. Brain Sciences. 2022;12(5):615.

26.   Simonyan K, Zisserman A. Very deep convolutional networks for large-scale image

recognition. arXiv preprint arXiv:14091556. 2014.

27.   Loshchilov I, Hutter F. Decoupled weight decay regularization. arXiv preprint

arXiv:171105101. 2017.

28.   Radford A, Metz L, Chintala S. Unsupervised representation learning with deep

convolutional generative adversarial networks. arXiv preprint arXiv:151106434. 2015.

29.   Gulrajani I, Ahmed F, Arjovsky M, Dumoulin V, Courville AC. Improved training of

wasserstein gans. Advances in neural information processing systems. 2017;30.

30.   Arjovsky M, Chintala S, Bottou L, editors. Wasserstein generative adversarial networks.

International conference on machine learning; 2017 2017-12-06: arXiv.

31.   Shi W, Caballero J, Huszár F, Totz J, Aitken AP, Bishop R, et al., editors. Real-time single

image and video super-resolution using an efficient sub-pixel convolutional neural network.

Proceedings of the IEEE conference on computer vision and pattern recognition; 2016.

32.   Aitken A, Ledig C, Theis L, Caballero J, Wang Z, Shi W. Checkerboard artifact free sub-

pixel convolution: A note on sub-pixel convolution, resize convolution and convolution resize.

arXiv preprint arXiv:170702937. 2017.

33.   Lim JH, Ye JC. Geometric gan. arXiv preprint arXiv:170502894. 2017.

34.   Rosca M, Lakshminarayanan B, Warde-Farley D, Mohamed S. Variational approaches

for auto-encoding generative adversarial networks. arXiv preprint arXiv:170604987. 2017.

35.   Larsen ABL, Sønderby SK, Larochelle H, Winther O, editors. Autoencoding beyond

pixels using a learned similarity metric. International conference on machine learning; 2016:

PMLR.

36.   Miyato T, Koyama M. cGANs with projection discriminator. arXiv preprint

arXiv:180205637. 2018.

37.   Perarnau G, Van De Weijer J, Raducanu B, Álvarez JM. Invertible conditional gans for

image editing. arXiv preprint arXiv:161106355. 2016.

38.   Reed S, Akata Z, Yan X, Logeswaran L, Schiele B, Lee H, editors. Generative adversarial

text to image synthesis. International conference on machine learning; 2016: PMLR.

39.   Odena A, Olah C, Shlens J, editors. Conditional image synthesis with auxiliary classifier

gans. International conference on machine learning; 2017: PMLR.

40.   Liao C, Dong M. ACWGAN: AN AUXILIARY CLASSIFIER WASSERSTEIN GAN-BASED

OVERSAMPLING APPROACH FOR MULTI-CLASS IMBALANCED LEARNING. International Journal

of Innovative Comnputing, Information and Control. 2022;18(3):703-21.

41.   Heusel M, Ramsauer H, Unterthiner T, Nessler B, Hochreiter S. Gans trained by a two

time-scale update rule converge to a local nash equilibrium. Advances in neural information

processing systems. 2017;30.

42. Kynkäänniemi T, Karras T, Laine S, Lehtinen J, Aila T. Improved precision and recall

metric for assessing generative models. Advances in Neural Information Processing Systems.

2019;32.

43. Shmelkov K, Schmid C, Alahari K, editors. How good is my GAN? Proceedings of the

European conference on computer vision (ECCV); 2018.

44. Deng J, Dong W, Socher R, Li L-J, Li K, Fei-Fei L, editors. Imagenet: A large-scale

hierarchical image database. 2009 IEEE conference on computer vision and pattern

recognition; 2009: Ieee.

45. Salimans T, Goodfellow I, Zaremba W, Cheung V, Radford A, Chen X. Improved

techniques for training gans. Advances in neural information processing systems. 2016;29.

46. Tronchin L, Sicilia R, Cordelli E, Ramella S, Soda P, editors. Evaluating GANs in medical

imaging. Deep Generative Models, and Data Augmentation, Labelling, and Imperfections: First

Workshop, DGM4MICCAI 2021, and First Workshop, DALI 2021, Held in Conjunction with

MICCAI 2021, Strasbourg, France, October 1, 2021, Proceedings 1; 2021: Springer.

47. Chen S, Ma K, Zheng Y. Med3d: Transfer learning for 3d medical image analysis. arXiv

preprint arXiv:190400625. 2019.

48. Rejusha T, KS VK, editors. Artificial MRI image generation using deep convolutional

GAN and its comparison with other augmentation methods. 2021 international conference on

communication, Control and Information Sciences (ICCISc); 2021: IEEE.

49. Lin T, Wang Y, Liu X, Qiu X. A survey of transformers. AI open. 2022;3:111-32.

50. Pan S, Wang T, Qiu RL, Axente M, Chang C-W, Peng J, et al. 2D medical image synthesis

using transformer-based denoising diffusion probabilistic model. Physics in Medicine &

Biology. 2023;68(10):105004.

51. Singh S, Ranapurwala A, Bewoor M, Patil S, Rai S. Systematic Review of Techniques in

Brain Image Synthesis using Deep Learning. arXiv preprint arXiv:230904511. 2023.

Acknowledgements

703 We thank F. Greiner for his help in data pre-processing.

Fig 6

Fig 1

Fig 2

Fig 3

Fig 4

healthy controls　　　schizophrenia patients

projection

auxiliary

separate

real

Fig 5