AI-Enhanced Subtyping of Thymic Tumors: Attention-based MIL with Pathology-Specific feature extraction.

Haitham Kussaibi M.D.[1*]

[1]*Department of Pathology, College of Medicine, Imam Abdulrahman bin Faisal University, P.O. Box 1982, Dammam 31441, Saudi Arabia*

Corresponding Author: Email: hkussaibi@iau.edu.sa, https://orcid.org/0000-0002-9570-0768

1 ABSTRACT:

Background: The accurate classification of thymic tumors using whole slide images (WSIs) is critical for effective diagnosis and treatment. Traditional Convolutional Neural Networks (CNNs) are often employed for this task, but emerging pathology-specific models like Phikon and HistoEncoder offer promising alternatives. Additionally, a novel, self-built attention-based MIL classifier, AttenMIL, has been developed to further enhance classification performance.

Methods: We evaluated the performance of nine different deep learning models combining three feature extractors (ResNet50, HistoEncoder, and Phikon) with three multiple instance learning (MIL) classifiers (AttenMIL, TransMIL, and Chowder). A novel dataset augmentation technique, 'feature chunking', was implemented to simulate the diagnostic process of pathologists and improve the training process. The MIL classifiers were tasked with predicting slide/bag-level labels from pre-extracted features.

Results: The Phikon feature extractor consistently provided the highest accuracies, particularly when paired with the AttenMIL and Chowder classifiers. AttenMIL, a novel attention-based MIL classifier developed by the author, showed remarkable performance in combination with Phikon, achieving accuracies up to 99%. This combination significantly outperformed other feature extractor-classifier pairs. The chunking-based augmentation method proved effective for thymic tumors, which are relatively homogeneous, but its applicability to heterogeneous tumors remains to be explored.

Conclusions: The study demonstrates the potential of domain-specific feature extractors like Phikon, coupled with robust MIL classifiers such as the novel AttenMIL and Chowder, in enhancing the accuracy and reliability of thymic tumor classification. Future research should focus on addressing class imbalances, improving generalizability to different datasets, and exploring the method's effectiveness on more heterogeneous tumor types.

Keywords: Thymic Tumors, Whole slide images, Deep Learning, Self-Supervised Learning, Domain-specific extractors, Multiple Instance Learning, Attention Mechanism

2 INTRODUCTION

Histopathology is the study of diseased tissues at the microscopic level, using various staining techniques and imaging modalities. It plays a crucial role in the diagnosis and characterization of tumors, including thymic neoplasms. Histopathological examination involves analyzing cellular morphology, architectural patterns, and molecular characteristics of tumor samples obtained through biopsy or surgical resection.

Thymic tumors, a type of anterior mediastinum neoplasm, originate from the epithelial cells of the thymus gland. These tumors fall into two broad categories: thymomas and thymic carcinomas. Thymomas are typically slow-growing, while thymic carcinomas tend to be more aggressive, invasive, and prone to metastasizing. Thymomas display a diverse array of histological subtypes, formed by thymic epithelial cells with varying degrees of lymphocytic infiltration. The World Organiza-

tion (WHO) classifies five types of thymomas based on their histological features: type A (spindle epithelial cell with rare lymphocytes), type AB (mixed A & B), type B1 (lymphocyte-rich), type B2 (equal epithelial and lymphocyte count), and type B3 (epithelial-rich) (1).

Accurate diagnosis and subtyping of thymic tumors are critical for determining appropriate treatment strategies and predicting patient prognosis. However, this task can be challenging due to tumors' complexity and variability, which include a broad spectrum of overlapping histological patterns and cellular compositions. Traditional diagnostic methods, such as microscopic examination of biopsy samples, are subjective and potentially susceptible to human error, interpretation biases, and inter-observer variability among pathologists. Consequently, there is a growing interest in producing more objective and reproducible thymic tumor classification methods by leveraging the power of artificial intelligence (AI) and deep learning techniques.

Deep learning (DL), a subset of machine learning, employs artificial neural networks inspired by the structure and functionality of the human brain. These networks consist of multiple interconnected layers capable of learning hierarchical representations of data, allowing them to recognize complex patterns and make precise predictions.

DL, particularly convolutional neural networks (CNNs), has demonstrated impressive performance in various medical imaging tasks in recent years. CNNs are designed to extract relevant features from raw image data, making them well-suited for analyzing complex visual patterns and morphological characteristics present in histopathology images. These techniques have the potential to enhance diagnostic accuracy, reduce inter-observer variability, and provide quantitative analyses beneficial for clinical decision-making (2).

One challenge in applying deep learning to histopathology images is the limited availability of large datasets necessary for training complex models. To address this limitation, researchers have implemented transfer learning techniques that adapt deep learning models trained on a large dataset (such as ImageNet, a vast dataset of natural images) to a smaller, domain-specific dataset (such as histo-

pathology images). This method allows the model to utilize the low-level features learned from the larger dataset while refining its higher layers to meet the specific task requirements (3).

Furthermore, the scarcity of annotations in histopathology Whole Slide Images (WSIs) has led to the adoption of weakly-supervised approaches, such as multiple instance learning (MIL). Each WSI, a large histopathology image comprising hundreds of thousands of pixels, generates hundreds or even thousands of patches (instances). The patches of each WSI are considered a single unit (or a bag of instances) sharing the same label. MIL models are designed to predict WSI/bag-level labels. Several well-established MIL models, including attention-based MIL, have proven effective in weakly-supervised medical image classification (4-6). In our study, we introduce a novel, simple, and robust attention-based MIL model named 'AttenMIL'.

Unlike Convolutional Neural Networks (CNNs), which perform feature extraction and classification within a single model, MIL training requires pre-extracted features from a separate model. While CNNs are effective at producing high-quality features, emerging pathology-specific models like Phikon (7) and HistoEncoder (8) are proving more efficient at extracting relevant and reliable features from histopathology images.

On the other hand, to address the limited number of WSIs in weakly-supervised tasks, we propose a novel method for dataset augmentation called 'feature chunking'. In this method, WSI-derived features are split into smaller bags containing a certain number of features. This approach simulates the diagnostic process of pathologists, where a few relevant microscopic fields, rather than the entire slide, are sufficient for an accurate diagnosis.

Herein, we present a comprehensive analysis of AI-based subtyping of thymic tumors in WSIs. This analysis compares different combinations of domain-specific extractors with MIL classifiers, describing complete end-to-end weakly-supervised WSI classification pipelines. These pipelines employ the novel chunking method and AttenMIL.

3 MATERIALS AND METHOD

The DL classification pipeline (Fig. 1) included several key stages: initial dataset preparation, model training, and performance evaluation. This process began with the meticulous curation of datasets, starting with the collection of WSIs. Patches were then extracted from these images, and features were subsequently extracted from the patches using 3 different models. These extracted features were organized using chunking techniques. Three distinct classifiers were trained on the bagged features, and their performance was rigorously evaluated using unseen test images to assess their effectiveness and generalization capabilities.

Fig. 1 Flowchart illustrates the Overall Methodology (end-to-end pipeline), depicting the different stages and components involved in the AI-based classification process

3.1 DATASET PRE-PROCESSING

3.1.1 Data Acquisition and Selection:
The dataset comprised 242 histopathology WSIs of thymic epithelial tumors obtained from the publicly accessible TCGA databases. These WSIs varied in size, ranging from 51 MB to 3.4 GB. The WSIs were categorized into six distinct subtypes/classes, with slide-level labels provided; detailed tumor annotations or masks were unavailable.

3.1.2 Patch Extraction:
WSIs are huge multilayer images with tens to hundreds of thousands of pixels that necessitate splitting into small patches to fit model requirements.

As WSIs contain blank background areas, we adopted a robust technique (Yottixel) developed by KimiaLab for extracting patches from representative tissue areas of WSIs (9). Initially, Yottixel generates a tissue mask to isolate patches solely from the tissue area, maintaining a predetermined tissue-to-background ratio; patches with 30% background or more, were subsequently discarded. This method produces patches of size 250x250 pixels. Yottixel can also cluster the resulting patches, extract their features, and generate a barcode based on them to build an Image Search Engine. However, in this study, we only utilized the patch extraction part.

3.2 FEATURE EXTRACTION:
Before feature extraction, patches were standardized and resized to 224x224 pixels to comply with the requirements of extractor models.

During this phase, three distinct models were employed to extract features from patches:

ResNet50: A CNN pre-trained on ImageNet (10), and finetuned on UBC-OCEAN dataset (11-13). This dataset contains more than 500 WSIs of different types of epithelial ovarian cancers.

Histoencoder: A pathology-specific model that has been trained in a self-supervised technique on Prostate cancer tissue images to extract and cluster features from histology images (8).

Phikon: Another self-supervised learning model tailored to extract features from histology images (7). Phikon has its own preprocessing function (AutoImageProcessor), while the other 2 models needed a custom normalization function.

3.3 CONSTRUCTION OF FEATURES BAGS:
Instead of treating the whole features extracted from each WSI as a bag, and consequently getting a limited number of bags for training, a pioneering chunks-based method was introduced. This innovative approach involves the grouping of features to construct bags of uniform size, each containing 200

features. This grouping is achieved using the (torch.chunk) function. By employing this technique, bags of consistent size are generated, obviating the need for additional padding measures. This approach also augmented the size of the training dataset 10 times as shown in Table 1.

Although, this method works very well in thymic tumors, which are relatively homogeneous; however, in heterogeneous tumors, larger-sized bags or an additional tumor segmentation phase is required.

The following table presents the dataset with thymoma subtypes distribution in terms of number of WSIs, patches/features extracted, and the corresponding number of bags (of 200 features) created.

Table 1: Dataset distribution among thymoma subtypes

Subtypes	A	AB	B1	B2	B3	CA
WSIs	34	68	39	61	22	18
Patches (in thousands)	56	120	80	102	40	30
Bags	280	600	400	510	200	150

3.4 CLASSIFICATION MODELS

Given the weakly supervised nature of our approach, which involves slide/bag-level labels, the most suitable classifiers were those based on Multiple Instance Learning (MIL). In MIL, the training data is organized into bags, with each bag containing multiple instances that share a single label. In this study, we experimented with two well-known MIL models (TransMIL and Chowder), as well as a novel self-built, attention-based MIL classifier named 'AttenMIL'.

AttenMIL incorporates attention mechanisms within a MIL architecture. The attention mechanism allows the model to focus on specific regions or features within the input data, enhancing its ability to capture relevant information. This model is particularly effective in tasks where certain parts of input data are more informative than others. AttenMIL is composed of the following layers:
1. *Normalization function* ensures that the input data is on a consistent scale, which is crucial for the stability and performance of neural network models. 2.

Instance Normalization Layer normalizes the input data instance-wise, improving the model's robustness. 3. *Fully Connected Layers* with ReLU activations and dropout for regularization. 4. *Attention Mechanism* computes attention scores for instance-level predictions, allowing the model to focus on the most relevant parts of the input. 5. *Bag-Level Prediction* uses attention scores to aggregate instance-level predictions into a final bag-level output.

TransMil (Transformer based Correlated Multiple Instance Learning for WSI Classification) (5): Unlike traditional MIL methods that treat instances independently, TransMIL accounts for the correlation between different instances within a WSI. This approach uses a transformer model to capture both morphological and spatial information from images.

Chowder (14): A MIL-based classifier designed for weakly supervised learning tasks. It employs a combination of convolutional neural networks (CNNs) and MIL techniques to learn discriminative representations from bag-level labels. This involves embedding the features from individual image tiles and aggregating the most relevant positive and negative evidence tiles to make predictions.

These 3 classifiers are specifically tailored for tasks where only limited labeling is available, making them suitable choices for scenarios where annotations are provided at a higher level of granularity, such as slide/bag-level labels.

3.5 CLASSIFIER TRAINING & EVALUATION

3.5.1 Experimental Setup
Train-test Split: The dataset was partitioned into training and testing sets using an 80% train and 20% test split, ensuring a stratified distribution across classes. This approach maintained a proportional representation of each tumor subtype in both training and testing subsets, thus minimizing bias in model evaluation.

Hardware Specifications: The experiments were conducted on a robust hardware setup comprising a GPU with 12 GB of memory and 8000 CUDA cores, supplemented by 32 GB of RAM and an Intel Core i7 13th Generation processor. This high-

performance configuration enabled efficient training and evaluation of the deep learning models.

Implementation Framework: PyTorch, a widely adopted deep learning framework renowned for its flexibility and scalability, served as the primary implementation tool. Its intuitive interface and extensive library of pre-built modules facilitated seamless development and experimentation with complex neural network architectures.

Hyperparameters: Several key hyperparameters were meticulously tuned to optimize model performance. The batch size was set to 32, striking a balance between computational efficiency and model convergence. Number of epochs was set at 100. We utilized Adams as an optimizer with a learning rate scheduler (the initial learning rate was configured to start at 0.001). Additional hyperparameters fine-tuning tailored to each specific model architecture and training regimen was conducted iteratively in cross-validation training loops to maximize model efficacy and generalization capabilities.

3.5.2   Training Process

The training process involved training these deep learning architectures to effectively classify the features extracted in the preceding step and associate them with their respective tumor subtypes. This encompassed two key phases: training and validation, where meticulous attention was paid to prevent over-fitting and enhance model generalization.

Despite the relatively high number of epochs set at 100, a cautious approach was taken by incorporating early stopping with a patience of 10 into the training regimen. This strategic measure ensured that training ceased when the model's performance plateaued on the validation set, thus mitigating the risk of overfitting. By monitoring the model's performance at regular intervals during training, early stopping provided a safeguard against the potential deleterious effects of over-training, allowing the model to attain optimal performance while maintaining generalization capabilities.

The decision to employ the Adam optimizer stemmed from its proven efficacy in iteratively updating the model's parameters to minimize classification error. To further enhance its performance, the Adam optimizer was integrated with a learning rate

scheduling mechanism with patience of 3. This adaptive technique dynamically modulated the learning rate throughout the training process, thereby facilitating smoother convergence toward the optimal solution. By intelligently adjusting the learning rate based on the observed performance, the model could navigate through the optimization landscape more efficiently, ultimately enhancing its convergence speed and overall effectiveness.

Addressing the variability in class sizes, a customized loss function named **ClassWeightedCrossEntropyLoss** was utilized. This loss function assigned higher weights to less frequent classes, thereby alleviating the impact of class imbalances on model training. Furthermore, to comprehensively assess model performance and robustness, a cross-validation strategy employing 5 K-folds with an 80/20 split ratio and 32 batch size, was implemented. This technique partitioned the dataset into five equally sized folds, iteratively training the model on four folds and validating on the remaining fold to obtain reliable estimates of performance metrics.

3.5.3   Classifier Inference Procedure:

To evaluate the performance of each combination extractor-classifier on an unseen test dataset, the best-performing weight, across all the five folds of cross-validation training process, has been chosen.

3.5.4   Performance Metrics

In evaluating the efficacy of classification models for thymic tumors, a comprehensive suite of evaluation metrics has been utilized. These metrics serve as quantitative measures by which the model's predictions are compared against the ground truth labels provided by expert pathologists (dataset labels).

Evaluation metrics employed in this study include:

Accuracy: represents the overall proportion of correctly classified samples across all classes. It provides a broad assessment of the model's performance in accurately predicting tumor subtypes.

Precision, Recall, and F1-score: These metrics offer a more nuanced evaluation by quantifying the trade-off between false positives and false negatives for each class. Precision measures the proportion of correctly predicted positive samples out of all samples predicted as positive, while recall calculates the

proportion of correctly predicted positive samples out of all actual positive samples. The F1-score provides a harmonic mean of precision and recall, offering a balanced assessment of model performance. *Confusion Matrix*: A fundamental tool in performance evaluation, the confusion matrix provides a detailed breakdown of correct and incorrect classifications for each class. It offers insights into the model's strengths and weaknesses, facilitating a granular analysis of its predictive capabilities across different tumor subtypes.

4 RESULTS

4.1 EXTRACTED FEATURES:
The following table provides valuable information regarding the dimensions and storage requirements of the extracted features (Table 2).

Table 2. Extracted features by each DL model:

Extractor	Number of Features per Patch	Storage Requirement
ResNet50	2048	4.4 GB
Histoencoder	1152	2.5 GB
Phikon	768	1.6 GB

4.2 Performance metrics:
The classification accuracy of the different combinations (extractor-classifier) is shown in (Fig. 2).

Fig. 2: Classification accuracy of the different combinations (extractor-classifier)

Best Overall Performance: The combination of Phikon as the feature extractor and either AttenMIL or Chowder as classifiers demonstrates the highest performance with near-perfect scores.

Best Classifier: Chowder generally outperforms other classifiers across different extractors, particularly with ResNet50 and Phikon.

TransMIL shows slightly lower performance compared to AttenMIL and Chowder.

4.3 CONFUSION MATRIX AND ERROR ANALYSIS
The confusion matrices for each feature extractor-classifier pair provide insights into misclassification patterns and potential error sources (table 3).

ResNet50-AttenMIL model performs very well in predicting class A, B2, and CA, with 100%, 97.8%, and 97.1% accuracy respectively. It also does well on class B3, correctly predicting 95.7% of samples with 4.4% of B3 predicted as AB and B2. The model struggles most with classes AB (88.7% correct), and B1 (84.8%) with 8.7% of AB and 10.1% of B1 samples misclassified as B2.

ResNet50-TransMil also excels at predicting class A (100% accuracy). It performs well on class AB (93.2), CA (93.1%), and B3 (92.1%), while it struggles with class B1 (88.5%) and B2 (88.5%). There is some confusion between B1 and B2 (6.9% of B1 is misclassified as B2 and 4.3% of B2 is misclassified as B1).

ResNet50-Chowder performs exceptionally well on class A and CA, with 100% accuracy for both. It also does very well on classes B2 (99.3%), B1 (98.1%), and AB (97.8%). The main issue was with class B3 (93.6%) with 4.3% confused as AB.

HistoEncoder-AttenMIL achieves high accuracy for classes B3 (97.9%) and AB (97.4%). Performance is also strong for class B2 at 96.9% and Class B1 at 94.4%. However, it struggles with classes A, and CA, with accuracies of 87.5%, and 90.9% respectively. There is notable confusion between classes A with AB and B3. Furthermore, a high percentage (9.1%) of CA is weirdly misclassified as B3.

HistoEncoder-TransMil delivers the best performance on class CA at 97.7% accuracy. It also per-

forms well on classes AB (94.9%), and A (92.8%), and B2 (92.1%). However, there is more confusion with classes B1 (87.6%) and B3 (88.0%), with 8% of B3 cases misclassified as class AB.

HistoEncoder-Chowder performs extremely well for class CA, achieving 100% accuracy. It also does well on classes B3 (97.9%), and AB (97.5%). Performance on classes B1, A, and B2 is slightly lower at (96.4%, 96.4%, and 96.0% respectively). There was 6% confusion between B1 and B2 cases.

Phikon-AttenMIL (Fig. 3) performs very well at classifying class CA, with 100% accuracy. It also does well in classes A, AB, B1, and B2 with 98.5%, 98.2%, 98.9%, and 99.2% accuracy respectively. Performance is slightly lower on class B3 at 97.8% accuracy. There is very little confusion between the classes, 2.2% of B3 cases are misclassified as B2, and 1.5% of A cases are misclassified as AB.

Table 3: Accuracy of Thymic Tumor prediction by Different Extractor-Classifier Combinations for each subtype.

Class	R-A	R-T	R-C	H-A	H-T	H-C	P-A	P-T	P-C	AvgClass
A	100.0%	100.0%	100.0%	87.5%	92.8%	96.4%	98.5%	100.0%	100.0%	97.24%
AB	88.7%	93.2%	97.8%	97.4%	94.9%	97.5%	98.2%	97.4%	98.1%	95.91%
B1	84.8%	88.5%	98.1%	94.4%	87.6%	96.4%	98.9%	98.8%	100.0%	94.17%
B2	97.8%	88.5%	99.3%	96.9%	92.1%	96.0%	99.2%	97.6%	99.2%	96.29%
B3	95.7%	92.1%	93.6%	97.9%	88.0%	97.9%	97.8%	92.7%	97.7%	94.82%
CA	97.1%	93.1%	100.0%	90.9%	97.7%	100.0%	100.0%	97.3%	100.0%	97.34%
AvgCom	94.02%	92.57%	98.13%	94.17%	92.18%	97.37%	98.77%	97.30%	99.17%	

R: ResNet50, H: HistoEncoder, P: Phikon, A: AttenMIL, T: TransMil, C: Chowder AvgCom: Average accuracy for each combination across all classes.
AvgClass: Average accuracy for each class across all combinations.

Fig. 3: Confusion matrix for Phikon-AttenMIL model.

Phikon-TransMil has 100% accuracy on class A. It performs well on classes AB, B1, B2, and CA at 97.4%, 98.8%, 97.6%, and 97.3% respectively. Accuracy is lower on class B3 at 92.7%. There is more confusion compared to other two classifiers. A 7.6% of B3 cases are misclassified as AB and B2.

Phikon-Chowder (Fig. 4) achieves 100% accuracy on classes A, B1, and CA. Performance is very high on classes AB, B2, and B3 at 98.1%, 99.2%, and 97.7% respectively. There is slight confusion in

some classes with 2.3% of B3 cases misclassified as AB, and 1.3% of AB cases misclassified as B2.

Fig. 4: Confusion matrix for Phikon-Chowder model.

5 DISCUSSION

In this study, we evaluated the performance of nine different deep-learning pipelines for subtyping thymic tumors WSIs into six classes (A, AB, B1, B2, B3, CA). The pipelines were constructed by combining a pathology-specific feature extractor

(ResNet50, HistoEncoder, or Phikon) with a MIL classifier (AttenMIL, TransMil, or Chowder).

The classification performance of the proposed models is evaluated using metrics such as accuracy, precision, recall, and F1-score. By rigorously analyzing these metrics, we could gain insights into the strengths and limitations of the models, allowing for informed comparisons between approaches.

The study reports impressive results, with most combinations achieving accuracies above 0.92 and some even reaching near-perfect accuracy (0.98-0.99). Our results show that the choice of feature extractor and classifier had a significant impact on the overall model performance.

ResNet50, a well-established architecture, demonstrated high accuracy with Chowder (0.98) but lower accuracy with the other 2 classifiers (0.93, 0.92). Overall, its accuracy across all classifiers was above 0.92 which is better than a previous study that reported (AUC 0.91 and 0.9) using ResNet50-Chowder for lung tumors and lymph node metastasis classification tasks respectively (14). However, the model was only pre-trained on ImageNet in that study, while our version was finetuned on histopathology images.

ResNet50's primary weakness lies in its computational complexity and resource-intensive nature. Extracted features are of high dimensionality, leading to increased storage requirements and computational overhead during training and inference.

Histoencoder, a self-supervised learning foundation model designed to extract features from histopathology images, showed competitive performance, especially with AttenMIL and Chowder (Acc. 0.95 and 0.97). This is also better than a recent study exploring the potential of Histoencoder to classify breast cancers (Accuracy 0.89) (15). While its average performance across all the classifiers is close to ResNet50, the smaller size of extracted features compared to ResNet50 may indicate a potential trade-off between feature richness and classification performance. The current available Histoencoder is pre-trained on prostate cancer images which are different in morphology and architecture from thymoma, this might explain its modest achievement, however, Histoencoder proved its su-

periority in features clustering and tissue segmentation (8).

Phikon, another histopathology-specific self-supervised learning model, exhibits outstanding results across the board, with near-perfect metrics (0.98-0.99) for all classifiers. Phikon's ability to learn discriminative representations from histopathological data contributes to its exceptional performance. This novel approach advances the field by demonstrating the effectiveness of domain-specific self-supervised learning in capturing discriminative features for thymic tumor classification. Its extracted features, while useful, are smaller in size compared to ResNet50, and Histoencoder, possibly indicating a trade-off between feature richness and performance. However, its exceptionally high performance warrants further validation on external datasets to assess generalization and rule out overfitting.

The introduction of self-supervised learning models, especially Phikon, represents a notable improvement over the traditional CNN-based approach. These models demonstrate superior performance in tumor classification tasks, underscoring the importance of leveraging domain-specific features for enhanced accuracy and robustness.

The use of MIL classifiers in conjunction with domain-specific feature extractors further enhances performance by effectively utilizing bag-level labels in weakly supervised settings.

AttenMIL, while simple, showed impressive results when combined with the proper domain-specific feature extractor (Phikon).

Through careful hyperparameter tuning, regularization techniques, and model selection, we have optimized the performance of each approach, achieving commendable accuracy scores across different combinations of extractors and classifiers.

Analysis of Classification Performance (Confusion Matrix and Error Analysis):

The confusion matrices for each feature extractor-classifier pair provide insights into misclassification patterns and potential error sources. All the nine confusion matrices corresponding to the nine different combinations are included in the appendix.

The Phikon extractor consistently yielded the highest accuracies when paired with any of the three classifiers, with most class-level accuracies exceeding 97%. The HistoEncoder and ResNet50 extractors also performed well but had slightly lower accuracies and more inter-class confusion compared to Phikon.

Regarding classifiers, AttenMIL and Chowder generally outperformed TransMil when combined with any feature extractors. AttenMIL demonstrated the best overall performance, achieving the lowest inter-class confusion. Chowder delivered comparable results with slightly more confusion between certain classes. TransMil had lower accuracies on some classes and more misclassifications compared to the other two classifiers.

These trends suggest that Phikon paired with Chowder offers the most robust performance for thymic tumor classification, while ResNet50 and HistoEncoder also perform well but with specific areas of improvement needed.

Based on these findings, we recommend using the Phikon extractor combined with either the AttenMIL or Chowder classifier for thymic tumor classification tasks. These combinations delivered the best performance in our experiments. However, the specific choice may depend on the relative importance of accuracy versus inter-class confusion for a given use case.

Achieving high accuracy for class A, and CA is a notable strength across all combinations, indicating a relatively easier classification for this tumor subtype due to its distinct morphology from other classes.

The models struggled in correctly predicting certain types like B3 which might be explained by the low number of B3 training cases and also by a relatively close morphology with other types.

To further improve classification performance, we suggest focusing on better-differentiating types AB, B1, and B3, as those were the most commonly confused classes. Collecting more training data, especially for the rarer types like B3, may help the models learn to distinguish these challenging cases. Experimenting with other neural network architectures

and hyperparameter settings could also potentially boost performance.

Potential Biases and Limitations

While the current study demonstrates significant progress in applying deep learning techniques to the classification of thymic tumors, it is important to acknowledge potential biases and limitations in the dataset, methodology, and results.

Class imbalances, where certain thymic tumor subtypes may be underrepresented, can lead to biases and reduced performance for those classes.

Thymic tumors are relatively homogeneous, which explains the high performance of chunking-based augmentation of the dataset. However, this method might not work well with heterogeneous tumors, or WSIs that include only a focal tumor area. In such cases, using larger-sized bags or incorporating a pre-segmentation step is necessary.

The generalizability of the models to unseen data from different sources or acquired under different conditions should also be considered. Histopathology images can be affected by various artifacts, such as staining variations, tissue folds, or image quality issues, which may impact the model's performance. Ensuring robustness to these artifacts and noise is crucial for reliable classification results.

On the other hand, the interpretability of pathology-specific self-supervised models (Histoencoder & Phikon) remains a concern, as they are often perceived as "black boxes," making it difficult to understand the reasoning behind their predictions. This lack of transparency can hinder trust and acceptance among healthcare professionals.

Future Research Directions

Future work could include incorporating additional data augmentation techniques to address class imbalances, improve generalization, and enhance clinical trust and adoption. Acquiring larger, high-quality, and diverse datasets through collaborative efforts among multiple medical centers and standardized data collection protocols can improve the generalization and robustness of the models. Collaborations between AI experts and pathologists to validate findings with prospective clinical validation studies to assess real-world performance will be

crucial for translating these research advances into clinical practice and integrating them into diagnostic workflows.

Exploring multi-modal data fusion, such as incorporating radiology images, genetic information, or electronic health records, could potentially improve the accuracy and comprehensiveness of thymic tumor classification. Integrating complementary information from different data sources may provide a more holistic understanding of the disease.

Developing transparent and explainable AI systems can enhance trust among healthcare professionals and facilitate accountability. Finally, as new data becomes available and our understanding of thymic tumors evolves, developing frameworks for continuously updating and improving AI-based classification models will be necessary. This ensures that the models remain up-to-date and incorporate the latest knowledge and advancements in the field.

6 CONCLUSION

In conclusion, our study demonstrates that deep learning models can accurately classify thymic tumor histology images, but the choice of feature extractor and classifier significantly impacts performance. The Phikon extractor combined with AttenMIL or Chowder appears to be the most promising approach. With further refinements, these models could be valuable tools for assisting pathologists and informing thymic tumor treatment decisions.

Acknowledgment:

Declaration of generative AI and AI-assisted technologies in the writing process

During the preparation of this work, the author used ChatGPT in order to improve language and readability. After using this tool/service, the author reviewed and edited the content as needed and takes full responsibility for the content of the publication.

Code availability:

The full pipelines will be soon made available on (https://github.com/hkussaibi).

7 REFERENCES:

1.   Marx A, Chan JKC, Chalabreysse L, Dacic S, Detterbeck F, French CA, et al. The 2021 WHO Classification of Tumors of the Thymus and Mediastinum: What Is New in Thymic Epithelial, Germ Cell, and Mesenchymal Tumors? J Thorac Oncol. 2022;17(2):200-13.
2.   Tucci F, Laurinavicius A, Kather JN, Eloy C. The digital revolution in pathology: Towards a smarter approach to research and treatment. Tumori. 2024:3008916241231035.
3.   Chitnis SR, Liu S, Dash T, Verlekar TT, Di Ieva A, Berkovsky S, et al. Domain-Specific Pre-training Improves Confidence in Whole Slide Image Classification. Annu Int Conf IEEE Eng Med Biol Soc. 2023;2023:1-4.
4.   Del Amor R, Launet L, Colomer A, Moscardo A, Mosquera-Zamudio A, Monteagudo C, et al. An attention-based weakly supervised framework for spitzoid melanocytic lesion diagnosis in whole slide images. Artif Intell Med. 2021;121:102197.
5.   Shao Z, Bian H, Chen Y, Wang Y, Zhang J, Ji X, et al. TransMIL: Transformer based Correlated Multiple Instance Learning for Whole Slide Image Classification. In: Beygelzimer A, Dauphin Y, Liang P, Wortman Vaughan J, editors. Advances in Neural Information Processing Systems2021.
6.   Gadermayr M, Tschuchnig M. Multiple instance learning for digital pathology: A review of the state-of-the-art, limitations & future potential. Comput Med Imaging Graph. 2024;112:102337.
7.   Filiot A, Ghermi R, Olivier A, Jacob P, Fidon L, Mac Kain A, et al. Scaling Self-Supervised Learning for Histopathology with Masked Image Modeling. 2023:2023.07.21.23292757.
8.   Pohjonen J. HistoEncoder: Foundation models for digital pathology: GitHub; 2023 [Available from: https://github.com/jopo666/HistoEncoder.
9.   Kalra S, Tizhoosh HR, Choi C, Shah S, Diamandis P, Campbell CJV, et al. Yottixel - An Image Search Engine for Large Archives of Histopathology Whole Slide Images. Med Image Anal. 2020;65:101757.
10.   He K, Zhang X, Ren S, Sun J, editors. Deep Residual Learning for Image Recognition. 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR); 2016 27-30 June 2016.
11.   Farahani H, Boschman J, Farnell D, Darbandsari A, Zhang A, Ahmadvand P, et al. Deep learning-based histotype diagnosis of ovarian carcinoma whole-slide pathology images. Mod Pathol. 2022;35(12):1983-90.
12.   Bashashati A, Farahani H, Consortium O, Karnezis A, Akbari A, Kim S, et al. UBC Ovarian Cancer Subtype Classification and Outlier Detection (UBC-OCEAN). Kaggle; 2023.
13.   Asadi-Aghbolaghi M, Farahani H, Zhang A, Akbari A, Kim S, Chow A, et al. Machine Learning-driven Histotype Diagnosis of Ovarian Carcinoma: Insights from the OCEAN AI Challenge. medRxiv. 2024:2024.04.19.24306099.
14.   Courtiol P, Tramel EW, Sanselme M, Wainrib G. Classification and Disease Localization in Histopathology Using Only Global Labels: A Weakly-Supervised Approach. 2020.
15.   Baroni GL, Rasotto L, Roitero K, Tulisso A, Di Loreto C, Della Mea V. Optimizing Vision Transformers for Histopathology: Pretraining and Normalization in Breast Cancer Classification. 2024;10(5):108.