LDAK-KVIK performs fast and powerful mixed-model association analysis of quantitative and binary phenotypes

Jasper P. Hof[1] and Doug Speed[2,*]

1 Radboud University Medical Center, IQ Health Science Department, Nijmegen, The Netherlands

2 Aarhus University, Center for Quantitative Genetics and Genomics, Aarhus, Denmark

* Corresponding authors: doug@qgg.au.dk

ABSTRACT

Mixed-model association analysis (MMAA) is the preferred tool for performing a genome-wide association study, because it enables robust control of type 1 error and increased statistical power to detect trait-associated loci. However, existing MMAA tools often suffer from long runtimes and high memory requirements. We present LDAK-KVIK, a novel MMAA tool for analyzing quantitative and binary phenotypes. Using simulated phenotypes, we show that LDAK-KVIK produces well-calibrated test statistics, both for homogeneous and heterogeneous datasets. LDAK-KVIK is computationally-efficient, requiring less than ten CPU hours and 5Gb memory to analyse genome-wide data for 350k individuals. These demands are similar to those of REGENIE, one of the most efficient existing MMAA tools, and approximately ten times less than those of BOLT-LMM, currently the most powerful MMAA tool. When applied to real phenotypes, LDAK-KVIK has the highest power of all tools considered. For example, across the 40 quantitative UK Biobank phenotypes (average sample size 349k), LDAK-KVIK finds 16% more independent, genome-wide significant loci than classical linear regression, whereas BOLT-LMM and REGENIE find 15% and 11% more, respectively. LDAK-KVIK can also perform gene-based tests; across the 40 quantitative UK Biobank phenotypes, LDAK-KVIK finds 18% more significant genes than the leading existing tool. Lastly, LDAK-KVIK produces state-of-the-art polygenic scores.

INTRODUCTION

Genome-wide association studies (GWAS) have greatly advanced our understanding of the genetic basis underlying complex diseases, offering valuable insights into disease mechanisms and potential therapeutic targets.[1,2] Since the first GWAS was carried out in 2005, sample sizes have regularly increased, such that studies involving over 100,000 individuals are now common.[3–7] Initially, GWAS relied on classical linear or logistic regression to test for association between single nucleotide polymorphisms (SNPs) and phenotypes. However, in recent years, mixed-model association analysis (MMAA) has become the method of choice.[8,9] MMAA can reduce false positives by accounting for cryptic relatedness, and increase true positives by factoring in the contributions of SNPs other than the one being tested.[10]

The most effective MMAA methods are two-step.[11–14] In Step 1, they construct leave-one-chromosome-out (LOCO) polygenic scores (PGS) and estimate λ, a test statistic scaling factor. In Step 2, they regress the phenotype on the SNPs, including the LOCO PGS as an offset, then scale the resulting test statistics. The computational demands of a two-step MMAA tool depend mainly on its algorithmic design, whereas its power depends primarily on the accuracy of its LOCO PGS.[15,16] For example, REGENIE[13] tends to be faster than BOLT-LMM[12] because its algorithm for estimating SNP effect sizes is block-based instead of genome-wide. However, BOLT-LMM tends to detect more significant associations than REGENIE because it usually constructs more accurate LOCO PGS.

In this paper, we introduce LDAK-KVIK, a novel two-step MMAA tool for analyzing quantitative and binary phenotypes. We first use simulated phenotypes to show that LDAK-KVIK controls type 1 error for both homogeneous and

heterogeneous data sets, and also when analyzing highly imbalanced phenotypes (e.g., diseases with very few cases). We

then apply LDAK-KVIK to real phenotypes from the UK Biobank.[17,18] When used for single-SNP association analysis,

LDAK-KVIK finds more significant associations than BOLT-LMM,[12] REGENIE,[13] fastGWA[19] and GCTA-LOCO[10] four of

the leading existing MMAA tools. Meanwhile, when used for gene-based association analysis, LDAK-KVIK finds more

significant associations than LDAK-GBAT,[20] the leading existing tool for gene-based association testing.

RESULTS

Overview of LDAK-KVIK.

A detailed description of LDAK-KVIK is provided in the **Online Methods** and **Supplementary Notes 1-5**. Here we

highlight its key features.

LDAK-KVIK is a computationally efficient MMAA tool. Firstly, it never needs to store genotypes for more than 512

SNPs, and so has very low memory demands. Secondly, we have developed a chunk-based variational Bayes solver

(illustrated in **Supplementary Figure 1**) that requires 5-20 times fewer updates than conventional variational Bayes

solvers (**Supplementary Figure 2**).[12,21] Our solver not only estimates SNP effect sizes (required when constructing the

Step 1 PGS), but also efficiently computes terms of the form $V^{-1}A$, where V is phenotypic variance matrix and A is a vector

of genotypes or phenotypes (required when estimating heritability). Thirdly, we have developed a fast empirical algorithm

for computing the saddlepoint approximation (SPA).[22–24] Fourthly, LDAK-KVIK can analyze multiple phenotypes

simultaneously.

LDAK-KVIK increases detection power, relative to existing MMAA tools, by using more realistic models for how SNP

effect sizes vary across the genome.[25,26] Firstly, LDAK-KVIK models how per-SNP heritability depends on minor allele

frequency (MAF), whereas existing MMAA tools typically assume that per-SNP heritability is constant.[27,28] Secondly,

LDAK-KVIK uses a mixture prior distribution for SNP effect sizes that contains a Gaussian and a Laplace distribution (we

refer to this as an elastic net prior, because of its similarities to elastic net regularization[29]), whereas existing MMAA tools

generally restrict to mixtures of Gaussian distributions.[10–14]

By default, LDAK-KVIK sets $\lambda = 1$, which is the correct value when analyzing homogeneous data. However, setting

$\lambda = 1$ will result in deflated test statistics when analyzing heterogeneous datasets. Therefore, we have developed a novel

test for structure, based on the average pairwise correlation between 512 randomly-picked SNPs (the correlation is

calculated after regressing out covariates). If this test finds high structure, LDAK-KVIK sets λ so that the mean test

statistic of weakly-associated SNPs matches that obtained if we were to replace the elastic net prior distribution for SNP

effect sizes with an infinitesimal prior and estimate λ using the Grammar-Gamma formula.[11]

In addition to testing SNPs individually for association with the phenotype, LDAK-KVIK can also perform gene-based

tests. This is achieved by providing the results of the single-SNP analysis to our existing software LDAK-GBAT.[20] To avoid

confusion, we refer to our new tool as LDAK-KVIK when testing SNPs for association, and as LDAK-KVIK-GBAT when

testing genes for association.

Data.

We use genotype and phenotype data from the UK Biobank.[17,18] In total, there are 487,152 individuals, of which

approximately 95% are of European ancestry. From this we construct the following six datasets. The "white dataset"

contains 367,981 white British individuals. The "homogeneous dataset" contains 63,000 unrelated white British individuals

(no pair of individuals is closer than second-cousins). The "family dataset" contains 63,000 of the most closely related

white British individuals (including approximately 13,300 full-siblings, 2,600 parent-offspring pairs and 300 second-

degree relatives). The "twins dataset" contains 63,000 white British twins (generated by duplicating the genotypes of

31,500 individuals from the homogeneous dataset). The "British-Irish dataset" contains 63,000 unrelated white individuals,

of whom approximately 51,300 are British and 11,700 Irish. Lastly, the "multi-ancestry dataset" contains 63,000

individuals selected to maximize ethnic diversity (approximately 63%, 24% and 13% are European, African and Asian,

respectively). After restricting to autosomal, biallelic SNPs with MAF>0.001, all datasets contain 690,264 SNPs, except

for the multi-ancestry dataset which contains 639,727 SNPs.

We first analyze simulated phenotypes. When generating these, we randomly select causal SNPs from the start of each

chromosome then use the chromosome ends as null SNPs for evaluating type 1 error (illustrated in **Supplementary Figure**

3). We subsequently analyze 40 quantitative and 20 binary phenotypes from the UK Biobank. The quantitative phenotypes

are height, body mass index, 20 biochemistry measurements (e.g., cholesterol, c-reactive protein, and urate), 16 blood

measurements (e.g., haemoglobin concentration, lymphocyte percentage and platelet count) and two urine measurements

(levels of creatinine and sodium). The binary phenotypes are defined based on ICD-10 codes[30] (e.g., hypertension, obesity,

and asthma) and have prevalences ranging from 0.02% to 29%. Additional details of the data are provided in

Supplementary Note 6.

For the analyses below, we always include ten principal components as covariates; when analyzing real phenotypes, we

additionally include age, sex, age^2 and age*sex. LDAK-KVIK determines that the white, homogeneous, British-Irish and

multi-ancestry datasets have low structure (so sets $\lambda=1$), but that the family and twins datasets have high structure (so

LDAK-KVIK estimates λ). While it may appear surprising that the multi-ancestry dataset is judged to have low

structure, this reflects that we include principal components as covariates (if these are excluded, our test finds extremely

high structure).

Existing tools.

For single-SNP association testing, we compare LDAK-KVIK with classical linear and logistic regression, and with five

existing MMAA tools: BOLT-LMM,[12] REGENIE,[13] fastGWA[19], GCTA-LOCO[10] and SAIGE[14] (a summary of each tool is

provided in **Supplementary Note 7**). Note that REGENIE and fastGWA are designed for both quantitative and binary

phenotypes, whereas BOLT-LMM and GCTA-LOCO are designed for quantitative phenotypes, while SAIGE is designed

for binary phenotypes. For gene-based association testing, we compare LDAK-KVIK-GBAT with our existing tool LDAK-

GBAT,[20] which we previously found to be consistently more powerful than five alternative tools (including MAGMA[31] and

fastBAT[32]).

Heritability models.

We consider heritability models of the form $E\left[h_j^2\right] \propto \left[f_j\left(1-f_j\right)\right]^{1+\alpha}$, where $E\left[h_j^2\right]$ is the expected heritability

contributed by SNP j, and f_j is its MAF. When $\alpha=-1$ all SNPs are expected to contribute equal heritability, whereas

$\alpha>-1$ $\left(\alpha<-1\right)$ implies that SNPs with higher MAF are expected to contribute more (less) heritability than SNPs

with lower MAF. All five existing MMAA tools assume $\alpha=-1$ throughout their operations (e.g., REGENIE assumes

$\alpha=-1$ when constructing the Step 1 PGS, while BOLT-LMM assumes $\alpha=-1$ both when constructing the Step 1 PGS

and when estimating λ). By contrast, LDAK-KVIK estimates α from the data.

LDAK-KVIK controls type 1 error.

We simulate quantitative and binary phenotypes for the homogeneous, family and twins datasets. For each dataset, we

consider 12 different scenarios, obtained by varying the heritability (0.2 or 0.5), the number of causal SNPs (5k or 20k),

and for binary phenotypes, also the prevalence (10% or 1%). When generating causal SNP effect sizes, we assume

$\alpha=-1$ (all causal SNPs are expected to contribute equal heritability). We perform single-SNP analysis using LDAK-

KVIK, then measure type 1 error based on the average $\chi^2(1)$ test statistic of null SNPs, and the proportions of null SNPs

with p-values below 0.05, 0.001 and 5x10⁻⁵. **Figure 1** and **Supplementary Figure 4** show that LDAK-KVIK controls type

1 error for all 12 scenarios across all three datasets. This remains the case when we instead perform a gene-based analysis

(**Supplementary Figure 5**).

Figure 1. Type 1 error and power of MMAA tools for quantitative phenotypes. We generate ten quantitative phenotypes

for each of the homogeneous, family and twins datasets (each dataset contains 63k individuals). Each phenotype has

heritability 0.5 and 5k causal SNPs, with causal SNP effect sizes sampled assuming $\alpha=-1$. We perform single-SNP

association analysis using BOLT-LMM, REGENIE, fastGWA, GCTA-LOCO and LDAK-KVIK. Panels report the mean

$\chi^2(1)$ test statistic of null SNPs (top) and causal SNPs (bottom) for each replicate. The three horizontal lines in each box

mark the median and inter-quartile range. Note that in the top panels, the horizontal solid and dashed lines mark,

respectively, the expected value if a tool is well-calibrated and approximate 95% confidence intervals, while in the bottom

panels, values are reported relative to the results from fastGWA.

For comparison, **Supplementary Figures 6-11** provide results from analyzing the simulated phenotypes using the existing

MMAA tools BOLT-LMM, REGENIE, fastGWA, GCTA-LOCO and SAIGE. In general, each of the five tools controls

type 1 error for all scenarios considered, except that REGENIE can produce inflated test statistics for common binary

phenotypes (e.g., when analyzing the 40 binary phenotypes with prevalence 10% for the homogeneous dataset, the average

$\chi^2(1)$ test statistic is 1.03), while SAIGE can produce inflated test statistics for rare binary phenotypes when there is high

structure (e.g., when analyzing the 20 binary phenotypes with prevalence 1% and heritability 0.5 for the twins dataset, the

average $\chi^2(1)$ test statistic is 1.10).

For **Supplementary Figure 12** we switch to the British-Irish dataset, showing that LDAK-KVIK continues to control type

1 error when applied to phenotypes with fine-scale population structure (specifically, phenotypes where citizenship

explains 20% of the total variance). Meanwhile, **Supplementary Figures 13 & 14** report results for the multi-ancestry

dataset. These show that LDAK-KVIK also controls type 1 error when applied to phenotypes with ancestry-specific

genetic architectures (e.g., if we generate phenotypes where either the causal SNPs or assumed value of α vary across

ancestries[33]).

LDAK-KVIK is computationally efficient.

Table 1 compares the runtime and memory requirements of LDAK-KVIK with existing MMAA tools when testing for

association 690k directly-genotyped SNPs, using either the homogeneous or white datasets (63k and 368k individuals,

respectively). For quantitative phenotypes, LDAK-KVIK and REGENIE have similar demands, typically requiring 5-10

CPU hours and less than 16 Gb memory to analyze phenotypes for the white dataset. fastGWA is the most

computationally-efficient tool, but only if we ignore the one-off cost for constructing the genomic relationship matrix

(which for the white dataset, took approximately 760 CPU hours). By contrast, BOLT-LMM and GCTA-LOCO are

substantially more demanding. For example, BOLT-LMM takes over 100 CPU hours to analyze phenotypes for the white

dataset, while GCTA-LOCO takes over 400 CPU hours just to analyse phenotypes for the homogeneous dataset (and thus it

is not feasible for us to use GCTA-LOCO for the white dataset). The computational demands of LDAK-KVIK are similar

when we switch from quantitative to binary phenotypes (which is also the case for REGENIE and fastGWA).

The runtimes in **Table 1** come from analyzing datasets with low structure. When applied to datasets with high structure,

LDAK-KVIK is approximately 30% slower when the phenotype is quantitative, but approximately 70% faster when the

phenotype is binary (e.g., if we force LDAK-KVIK to treat the white dataset as if it has high structure, the average runtime

for quantitative phenotypes increases from 8 to 10 CPU hours, while the average runtime for binary phenotypes reduces

from 10 to 3 CPU hours).

Supplementary Figure 15 and **Supplementary Table 1** provide further details of the LDAK-KVIK runtimes and results

from additional analyses. For example, we see that LDAK-KVIK spends approximately 95% of its runtime in Step 1. This

means that if we increase the number of association analysis SNPs from 690k to 9.0M, mimicking the situation where we

perform a GWAS using imputed data, the impact on runtime is relatively modest (e.g., the average time to analyze

quantitative phenotypes for the white dataset increases from 8 to 10 CPU hours). Meanwhile, we see that performing the

gene-based association analysis (i.e., running LDAK-KVIK-GBAT as well as LDAK-KVIK) adds less than 5% to the

runtime.

Phenotypes	MMAA Tool	Homogeneous Dataset (63k individuals)		White Dataset (368k individuals)	
		CPU Hours	Memory (Gb)	CPU Hours	Memory (Gb)
Quantitative	BOLT-LMM	18	11	110	61
	REGENIE	1.3	3	5.9	16
	fastGWA	0.02 (24)	1 (1)	0.2 (760)	3 (3)
	GCTA-LOCO	480	170	Not Feasible	
	LDAK-KVIK	0.9	2	7.7	5
Binary	REGENIE	1.8	3	10	16
	fastGWA	0.1 (24)	1 (1)	1.2 (760)	3 (3)
	SAIGE	32	11	230	61
	LDAK-KVIK	0.9	2	10	5

Table 1. Computational requirements of MMAA tools. We perform GWAS for five quantitative phenotypes (glucose,
glycated haemoglobin, haemoglobin concentration, height and high-density lipoprotein) and five binary phenotypes
(asthma, atrial fibrillation, ischaemic heart disease, dental caries and haemorrhoidal skin tags). Each GWAS analyzes
690k SNPs using either the homogeneous or white dataset, which contain 63k and 368k individuals, respectively (note that
after excluding individuals with missing phenotypes, the average sample sizes are 59k and 343k, respectively). All analyses
were performed using one core of an AMD EPYC Genoa 9654 CPU processor. Values report the mean runtime and
memory usage across either the five quantitative or five binary phenotypes. We report two sets of values for fastGWA,
depending on whether we exclude or include the computation of the genomic relatedness matrix (which only needs to be
done once per dataset). It was not feasible for us to analyze phenotypes for the white dataset using GCTA-LOCO (we
estimate each analysis would take over 10,000 hours and require over 500Gb memory).

Supplementary Tables 2 & 3 show that the runtime of LDAK-KVIK can be reduced by using multiple processors and/or
analyzing multiple phenotypes simultaneously. For example, using two, four and eight CPUs reduces the runtime by
approximately a quarter, a half and two-thirds, respectively, while analyzing five phenotypes simultaneously is about 60%
faster than analyzing the same five phenotypes separately. **Supplementary Figure 16** shows that both the runtime and
memory requirements of LDAK-KVIK are approximately linear in the number of individuals, and therefore, it is feasible
to apply LDAK-KVIK to very large datasets (e.g., it took on average 25 CPU hours to analyze a dataset containing 1M
individuals).

LDAK-KVIK is powerful

Figure 1 and **Supplementary Figures 17-19** compare the power of MMAA tools when performing single-SNP analysis of
the simulated phenotypes. For the quantitative phenotypes, LDAK-KVIK and BOLT-LMM are consistently the two most
powerful MMAA tools, substantially ahead of REGENIE and GCTA-LOCO, while fastGWA generally has lowest power.
For the binary phenotypes, the four MMAA tools have very similar power, reflecting that it is challenging to construct
accurate PGS for phenotypes with low (observed-scale) heritability. **Supplementary Figure 20** shows that for gene-based
analysis, LDAK-KVIK-GBAT tends to be substantially more powerful than LDAK-GBAT for quantitative phenotypes,
while the two tools have similar power for binary phenotypes.

The benefit of modeling the relationship between per-SNP heritability and MAF.

We now generate phenotypes using values of α between -1 and 0, and compare the performance of the default version of

LDAK-KVIK (which infers α from the data), to an alternative version that forces $\alpha = -1$ (mirroring the assumptions of

the existing two-step MMAA tools). **Figure 2** shows that the advantage of the default version over the alternative version

increases with α, which reflects that the former is able to estimate α with reasonable accuracy, and use this information to

construct more accurate LOCO PGS. These results are relevant because studies of real human traits typically find

$\alpha \gg -1$.[25,27,28,34,35] For example, **Supplementary Figure 21** shows that across the 40 quantitative UK Biobank

phenotypes, the mean estimate of α is -0.23 (s.d. 0.005), with α significantly greater than -1 for all phenotypes (P<0.01).

Figure 2. Exploiting the dependency of per-SNP heritability on MAF. We generate sets of ten quantitative phenotypes for

the homogeneous dataset (63k individuals). Each phenotype has heritability 0.5 and 20k causal SNPs, with causal SNP

effect sizes sampled assuming values of α ranging from -1 to 0. We analyze the phenotypes using the default version of

*LDAK-KVIK (which estimates α from the data), and an alternative version that sets $\alpha = -1$. **a,** Points compares*

estimates of α from the default version of LDAK-KVIK to the true values, with colors indicating whether the estimate is

*correct (black) or incorrect (red). **b,** Boxes report the mean $\chi^2(1)$ test statistic of null SNPs; the horizontal solid and*

dashed lines mark, respectively, the expected value if a tool is well-calibrated and approximate 95% confidence intervals.

***c,** Boxes report the mean $\chi^2(1)$ test statistic of causal SNPs. **d,** Boxes report the number of significant SNPs (P<5x10[-8]).*

Note that the three horizontal lines in each box mark the median and inter-quartile range, while values in the bottom

panels are reported relative to the results from the alternative version of LDAK-KVIK.

245

Figure 3. Performance of MMAA tools when analyzing 40 quantitative UK Biobank phenotypes. We analyze each phenotype using BOLT-LMM, REGENIE, fastGWA, BOLT-LMM-inf and LDAK-KVIK, then count the number of independent, genome-wide significant loci (SNPs with P<5x10⁻⁸, filtered so that no pair within 1Mb has squared correlation above 0.1). Points compare the number of loci found by each tool, relative to the results from fastGWA, with the estimated SNP heritability (obtained using our software SumHer[28]). The ten phenotypes with highest SNP heritability are named, while the dashed lines are obtained by regressing the relative numbers of loci found by each tool on the estimates of SNP heritability.

Single-SNP analysis of UK Biobank phenotypes.

Figure 3 compares the number of associations found by BOLT-LMM, REGENIE, fastGWA, BOLT-LMM-inf and LDAK-KVIK when analyzing the 40 quantitative phenotypes (note that BOLT-LMM-inf is a version of BOLT-LMM that assumes the same model as GCTA-LOCO, but that can feasibly be applied to the white dataset). LDAK-KVIK identifies 17.9% more independent, genome-wide significant loci than fastGWA (SNPs with P<5x10⁻⁸, filtered so that no pair within 1Mb has squared correlation above 0.1), which is slightly higher than BOLT-LMM (17.6%), and substantially higher than REGENIE (13.5%) and BOLT-LMM-inf (12.6%). **Supplementary Figure 22** shows that ranking of MMAA tools is the same if we instead measure power based on the mean $\chi^2(1)$ test statistic of SNPs that are genome-wide significant from fastGWA.

Supplementary Figure 23 shows that when analyzing the 20 binary phenotypes, all four MMAA tools perform similarly. For example, REGENIE, fastGWA, SAIGE and LDAK-KVIK in total find 676, 649, 612 and 686 independent, genome-wide significant loci, respectively (for comparison, classical logistic regression finds 667). These results are consistent with those when analyzing the simulated phenotypes, and again reflect the difficulty of constructing accurate PGS for binary phenotypes.

Figure 4. Accuracy of Step 1 PGS and power of LDAK-KVIK-GBAT. *a,* *We applied BOLT-LMM and LDAK-KVIK to the 40 quantitative UK Biobank phenotypes. The y-axis reports the accuracy of the Step 1 PGS from each tool, measured by the squared correlation between predicted and observed phenotypes across 41k samples (distinct from those used for the association analysis). For comparison, the x-axis reports the accuracy of ridge regression PGS, which are constructed using similar assumptions to the REGENIE PGS.* *b,* *We applied LDAK-GBAT and LDAK-KVIK-GBAT to the 40 quantitative UK Biobank phenotypes; points compare the numbers of significant genes (P<0.05/17,322=2.9x10⁻⁶) found by each tool. In each panel, the diagonal line marks y=x.*

Accuracy of Step 1 PGS.

Figure 4a compares the accuracy of the Step 1 PGS constructed by LDAK-KVIK and BOLT-LMM, for each of the 40 quantitative UK Biobank phenotypes. For comparison, we also consider ridge regression PGS, which are constructed using similar assumptions to the PGS constructed by REGENIE (the latter does not report SNP effect sizes, so we can not measure the accuracy of its PGS directly). As expected, the PGS accuracies mirror the detection powers of the three MMAA tools (**Figure 3**). For example, the PGS from LDAK-KVIK tend to be slightly more accurate than the PGS from BOLT-LMM and substantially more accurate than the PGS from ridge regression, explaining why LDAK-KVIK found slightly more significant loci than BOLT-LMM and substantially more significant loci than REGENIE. **Supplementary Figure 24** shows that for the 20 binary phenotypes, the Step 1 PGS tend to have very low accuracy, explaining why the MMAA tools performed similarly to classical logistic regression.

Gene-based analysis of UK Biobank phenotypes.

We test 17,332 genes for association, defined based on RefSeq annotations.[36] **Figure 4b** and **Supplementary Figure 25** report the number of significant genes (P<0.05/17,322=2.9x10⁻⁶) from LDAK-GBAT and LDAK-KVIK-GBAT. Across the 40 quantitative phenotypes, LDAK-KVIK-GBAT finds on average 18.4% more significant genes than LDAK-GBAT. By contrast, across the 20 binary phenotypes, there is no advantage using LDAK-KVIK-GBAT instead of LDAK-GBAT (in total, the tools find 1508 and 1515 significant genes, respectively).

Enlarged analysis of 62 quantitative phenotypes

For **Supplementary Figure 26**, we increase the number of quantitative phenotypes from 40 to 62 (by adding 22 traits analyzed by the authors of fastGWA[19]), increase the total sample size from 368k to 459k (the latter represents all European UKBB individuals), and increase the number of SNPs from 690k to 9.0M (by including imputed variants). Across all 62 phenotypes, LDAK-KVIK and REGENIE find 13.3% and 9.0% more independent, genome-wide significant loci than fastGWA (if we restrict to the 22 new phenotypes, the values are 7.6% and 4.0%, respectively). Summary statistics and PGS SNP weightings for all 62 phenotypes are available at www.ldak-kvik.com/summaries.

Using LDAK-KVIK on the UK Biobank Research Analysis Platform

The LDAK-KVIK website (www.ldak-kvik.com) provides guidelines for analyzing UK Biobank data on the Research Analysis Platform (RAP). For example, it explains how to extract phenotypes and covariates, and how to prepare the genotypes for Steps 1 & 2 (for Step 1, we recommend restricting to directly-genotyped SNPs with MAF>0.01 and call-rate above 90%, while for Step 2, we recommend converting the BGEN files into PLINK BED format). Note that while LDAK-KVIK can perform quality control on-the-fly (e.g., exclude SNPs based on MAF, call-rate, variance and/or information score), we generally recommend doing this when preparing the genotypes (because it usually only needs to be performed once, regardless of the number of phenotypes being tested). Similarly, while LDAK-KVIK is able to analyze multiple phenotypes simultaneously, we generally recommend analyzing phenotypes individually. This is because we have found that when using the RAP (or other high-performance clusters), it is usually more efficient, in terms of cost, time to complete all analyses and ease of debugging, to run many low-resource jobs instead of fewer high-resource jobs (e.g., we try to restrict to jobs that only use 1-4 cores, require less than 8Gb memory, and take less than ten hours to complete).

DISCUSSION

We have presented LDAK-KVIK, a novel tool for performing single-SNP and gene-based mixed-model association analysis. We have shown that LDAK-KVIK can be validly applied to homogeneous and heterogeneous datasets, and to both quantitative and binary phenotypes. LDAK-KVIK is computationally efficient, able to analyse data for 100,000s of individuals within a few hours, and has low memory requirements. Furthermore, LDAK-KVIK is powerful; for example, when used for single-SNP analysis of quantitative phenotypes, LDAK-KVIK consistently finds more significant associations than the existing MMAA tools BOLT-LMM, REGENIE, fastGWA and GCTA-LOCO.

Compared to BOLT-LMM, the main advantage of LDAK-KVIK is its computational efficiency (e.g., when analyzing the UK Biobank phenotypes, LDAK-KVIK was at least ten times faster and required five times less memory). This is mainly due to the development of a chunk-based variational Bayes solver. **Supplementary Figure 2** shows that our variational Bayes solver can construct PGS 5-10 times faster than the standard (genome-wide) variational Bayes solver, and can compute terms of the form $V^{-1}A$ ten times faster than conjugate gradient descent. Furthermore, our variational Bayes solver has a small memory footprint (typically less than 1Gb), because it never needs to store data for more than 256 SNPs at a time.

Compared to REGENIE, the main advantage of LDAK-KVIK is its power (e.g., across the 40 quantitative UK Biobank phenotypes, LDAK-KVIK found 3.7% (s.d. 0.6%) more independent, genome-wide significant loci, and when restricted to SNPs significant from fastGWA, the test statistics from LDAK-KVIK were on average 2.7% (s.d. 0.3%) higher than those

from REGENIE). This power increase mainly reflects that LDAK-KVIK uses more realistic models for the genetic architecture of complex traits. Specifically, LDAK-KVIK models the relationship between per-SNP heritabilities and MAF, and uses an elastic net prior distribution for SNP effect sizes. As shown in **Figure 4a**, these features result in LDAK-KVIK constructing more accurate PGS in Step 1, which then increases the chance of discovering associations in Step 2.

We recognize that LDAK-KVIK can be considered much slower than fastGWA. However, there are four points to note. Firstly, LDAK-KVIK is only slower if we ignore the time fastGWA takes to compute the genomic relatedness matrix. Although a one-off cost, this can be non-trivial (e.g., when analyzing 368k individuals, this step took approximately 760 CPU hours, which is longer than the total time LDAK-KVIK required to analyse all 40 quantitative phenoptypes). Secondly, LDAK-KVIK is usually substantially more powerful than fastGWA, reflecting that fastGWA focuses on controlling type 1 error, instead of improving power relative to classical linear regression. Thirdly, fastGWA is only designed for homogeneous data, or data containing related individuals, whereas LDAK-KVIK can also be applied to datasets including individuals from multiple ancestries. Fourthly, LDAK-KVIK includes an option to perform an approximate version of fastGWA, that uses a much faster algorithm for identifying related pairs of individuals. **Supplementary Figure 27** shows that when applied to the 60 quantitative and binary UK Biobank phenotypes, our approximate version of fastGWA gives results very similar to those from the original version of fastGWA, yet on average takes under two CPU hours to analyze each trait.

We realise that LDAK-KVIK has some limitations. Firstly, our method for calculating λ is approximate, and can result in deflated test statistics (evident from the results for the family and twins datasets in Figure 1, with further details in **Supplementary Figure 28**). Therefore, LDAK-KVIK would become more powerful if an exact solution for estimating λ was found (in **Supplementary Note 8** we summarize eight different approaches we tried for estimating λ). We note that when analyzing datasets with high structure, our strategy for estimating λ has similarities to that used by BOLT-LMM (both tools compare test statistics to those obtained using LOCO ridge regression PGS). However, the key difference is that LDAK-KVIK estimates λ based on the average test statistics of weakly-associated SNPs, whereas BOLT-LMM uses the estimated intersect from LD Score Regression (LDSC). **Figure 1** indicates that the BOLT-LMM approach can be advantageous (e.g., it avoids the deflation observed for the twins dataset). However, we prefer our strategy for two main reasons. Firstly, the approach used by BOLT-LMM assumes $\alpha = -1$, and can result in substantial inflation when this assumption is inappropriate (e.g., for **Supplementary Figure 29**, we generate quantitative phenotypes for 368k individuals assuming $\alpha = -0.25$, and show that the test statistics from BOLT-LMM are inflated by on average 9%). Secondly, when running LDSC, it is necessary to make assumptions regarding the location of causal variants (as this determines how to compute LD scores), but it is hard to assess the validity of these assumptions. For example, **Supplementary Figure 30** shows that when analyzing the phenotype height, switching from external LD scores to in-sample LD scores resulted in the estimate of λ increasing from 1.01 to 1.10.

A second limitation of LDAK-KVIK is that it estimates α using a grid search, with five pre-defined values (-1, -0.75, -0.5, -0.25 and 0). While the use of pre-defined values enables high computational efficiency (because LDAK-KVIK can evaluate model fit for all five values simultaneously), we appreciate that it limits the accuracy of the algorithm. For example, when analyzing the 50 phenotypes underlying **Figure 2**, for which the true values of α were always among the five pre-defined values, LDAK-KVIK only estimated α correctly 24 times. However, while imperfect, we believe that our algorithm is a marked improvement on the status quo, which is to simply assume $\alpha = -1$.

Thirdly, we found that when analyzing binary phenotypes, LDAK-KVIK was often only slightly more powerful than

classical logistic regression. We note that this was the same for other MMAA tools. Furthermore, it partially reflects that

we have focused on non-ascertained phenotypes (e.g., the UK Biobank is a population-based sample, so the proportion of

cases for each ICD10 disease will be close to the disease's prevalence). For **Supplementary Figure 31**, we simulate

ascertained binary phenotypes. We find that LDAK-KVIK continues to have good control of type 1 error, however its

power advantage over classical logistic regression depends on the scenario considered (e.g., its advantage generally

increases when analyzing more common phenotypes, but reduces when analyzing rarer phenotypes).

A fourth limitation concerns the analysis of phenotypes for which a substantial proportion of variation is explained by

common environment. Previous work by the authors of fastGWA[19] has shown that MMAA tools that utilize SNP-based

PGS (e.g., BOLT-LMM, REGENIE and LDAK-KVIK), can produce inflated test statistics when applied to phenotypes

with a strong environmental effect. As shown in **Supplementary Figure 32,** this inflation can potentially be avoided by

using pedigree-based PGS (i.e., by using either fastGWA, or the approximate version of fastGWA contained within LDAK-

KVIK).

Fiffthly, we note that although LDAK-KVIK is able to analyze multiple phenotypes simultaneously, and doing so can

substantially reduce total runtime, the speedups are less than those achieved by REGENIE (**Supplementary Table 3**).

Therefore, while LDAK-KVIK and REGENIE have similar runtimes when analyzing a small number of phenotype (e.g.,

less than five), REGENIE can be much faster than LDAK-KVIK when analyzing many phenotypes (e.g., more than ten).

Saying this, we hope that the increased detection power of LDAK-KVIK, relative to REGENIE, will compensate for the

increased running time when analyzing many phenotypes,

Our simulations indicate that LDAK-KVIK can be validly applied to multi-ancestry datasets. Specifically, we found that

LDAK-KVIK controls type 1 error both for phenotypes whose genetic architectures are the same across ancestries, and for

phenotypes whose architectures are ancestry-specific[33] (**Supplementary Figures 13 & 14**). For **Supplementary Figure**

33, we compare results from analyzing the 40 quantitative UK Biobank phenotypes using either the full dataset (487k

individuals) or only the European individuals (462k individuals). We find there is limited benefit including the non-

European individuals (e.g., the number of independent, genome-wide significant loci increases for 23 phenotypes, and

decreases for 17 phenotypes). However, this likely reflects that almost all (95%) of the UK Biobank individuals are

European, and so it would be interesting to investigate the impact on power for more diverse datasets.

We note that it is possible to speed up LDAK-KVIK, and the other two-step MMAA tools, by reducing the number of

SNPs used in Step 1 (e.g., when analyzing UK Biobank data, the authors of SAIGE used only 94k SNPs when constructing

the PGS). **Supplementary Figure 34** shows that when analyzing simulated phenotypes for the homogeneous, family and

twins datasets, reducing the number of Step 1 SNPs from 690k to either 477k or 267k leads to a noticeable reduction in

detection power, and thus we advise against this approach.

We finish by pointing out that although designed for association testing, LDAK-KVIK also produces state-of-the-art PGS

(in addition to constructing the LOCO Step 1 PGS, it also constructs a genome-wide PGS, and reports the corresponding

SNP effect sizes). Previous works have shown that BOLT-LMM is one of the leading tools for constructing PGS.[15,26] Here

we have found that LDAK-KVIK tends to produce more accurate PGS than BOLT-LMM, and has substantially lower

computational demands.

DATA AVAILABILITY

Our study used data from UK Biobank, which we applied for and downloaded from www.ukbiobank.ac.uk. The UK Biobank has ethics approval from the North West Multi-centre Research Ethics Committee (MREC).

CODE AVAILABILITY

LDAK-KVIK is part of the software package LDAK, which can be downloaded from www.dougspeed.com. Full instructions for running LDAK-KVIK are provided at www.ldak-kvik.com.

ACKNOWLEDGMENTS

This research has been conducted using the UK Biobank Resource under Application Number 21432. The computing for this project was performed on the GenomeDK cluster (Aarhus University). We thank Anders Halager and Dan Søndergaard (Aarhus University) for programming suggestions, David Balding (University of Melbourne) for helpful comments on the manuscript, Jakub Bajzik, Al Depope and Matthew Robinson (Institute of Science and Technology Austria) for assistance with the UK Biobank Research Analysis Platform, Hamed Heydari (University of Toronto) for advice on heritability estimation, and Soumeen Jin (Karolinska Institute) for testing LDAK-KVIK. DS is supported by the Aarhus University Research Foundation (AUFF), by the Independent Research Fund Denmark (project no. 7025-00094B) and by a European Research Council Consolidator Grant (ID 101088901, acronym ClassifyDiseases).

AUTHOR CONTRIBUTIONS

JH and DS jointly developed the software, performed the analysis and wrote the manuscript.

COMPETING INTERESTS

The authors declare no competing interests.

ONLINE METHODS

Here we provide a concise description of LDAK-KVIK; please see **Supplementary Notes 1-7** for an exhaustive version, as well as details of existing MMAA tools and the UK Biobank data. Note that when describing LDAK-KVIK, we first assume the phenotype is quantitative, then later explain the changes required when the phenotype is binary.

Notation.

Suppose there are n individuals, each genotyped for m SNPs, recorded for q covariates and measured for a phenotype. Let the (n x m) matrix X' contain the genotypes, let the length-n vector Y' contain the phenotypes, and let the (n x q) matrix Z contain covariates. We use C to denote the total number of chromosomes, use X and Y to denote, respectively, the genotypes and phenotypes after regressing out the covariates, and use λ to denote the test statistic scaling factor. Without loss of generality, we assume X_j and Y are standardized to have mean zero and variance one.

LDAK-KVIK Step 1.

The main outcome of this step are C LOCO elastic net PGS, each taking the form $P_c = \sum X_j \hat{y}_j$, where $\hat{y}_j$ is the estimated effect size for SNP j, and the sum is across all SNPs not on Chromosome c. This step also estimates λ (described separately below).

LDAK-KVIK first computes $\hat{h}_j^2$, estimates of the heritability contributed by each SNP. For this, it considers heritability models of the form

$$E[h_j^2] = w_j h^2 / W, \quad \text{with} \quad w_j = [f_j(1-f_j)]^{1+\alpha} \quad \text{and} \quad W = \sum w_j$$

where f_j is the MAF of SNP j, α determines how per-SNP heritability depends on MAF and h^2 is the proportion of phenotypic variance explained by all SNPs. LDAK-KVIK estimates α and h^2 using Randomized Haseman-Elston Regression[37] and Monte Carlo restricted maximum likelihood [12] (REML), then sets $\hat{h}_j^2$ to its expected value given these estimates. Note that Monte Carlo REML must calculate terms of the form $V^{-1}Y$, $KV^{-1}Y$, $V^{-1}R$ and $KV^{-1}R$, where V is an (n x n) variance matrix, K is an (n x n) genomic relatedness matrix (GRM), and R is a length-n vector whose elements are drawn from a standard Gaussian distribution; we calculate these terms using our novel Variational Bayes solver (described below).

LDAK-KVIK then constructs C LOCO elastic net PGS, for which it assumes[29]

$$\gamma_j \sim p\,DE(a_j) + (1-p)\,N(0,b_j), \quad \text{with} \quad a_j = \sqrt{\frac{2p}{(1-F)\hat{h}_j^2}} \quad \text{and} \quad b_j = \frac{F\hat{h}_j^2}{1-p} \qquad (1)$$

where DE(a_j) denotes a double exponential distribution with rate a_j, while N(0,b_j) denotes a normal distribution with mean 0 and variance b_j. The parameters p and F determine the relative contributions of the double exponential and normal distributions. LDAK-KVIK finds suitable values for these using cross-validation (by default, LDAK-KVIK uses 90% of samples to construct genome-wide PGS corresponding to ten different pairs of values for p and F, then picks the pair that has lowest mean-squared error measured using the remaining 10% of samples). Note that all PGS are constructed using our novel variational Bayes solver (described below).

LDAK-KVIK Step 2.

LDAK-KVIK tests SNP j for association using least-squares regression with either the model $E[Y - P_c] = X_j \beta_j$ or $E[Y - P_c] = X_j{}' \beta_j$ (note that the former uses residual genotypes, so is more accurate, whereas the latter uses raw genotypes, so is faster). By default, LDAK-KVIK copies the approach used by fastGWA[19] and first tests all SNPs using the raw genotype model, then retests SNPs showing evidence of association (P<0.05) using the residual genotype model (if preferred, the user can instruct LDAK-KVIK to always use residual genotypes, or to always use raw genotypes). LDAK-KVIK then scales the resulting $\chi^2(1)$ test statistics by λ.

Novel test for structure.

LDAK-KVIK picks 512 SNPs randomly from across the genome, then computes $\hat{\rho}^2 = \bar{\rho}^2 - 1/(n-1)$, where $\bar{\rho}^2$ is the

average squared correlation between the r pairs of SNPs on different chromosomes. To test $\hat{\rho}^2$ for significance, we use

the fact that under the null hypothesis (i.e., if the data are homogeneous and so SNPs on different chromosomes are

independent), each squared correlation is beta distributed with parameters 1/2 and (n-2)/2, and so $\hat{\rho}^2$ will have

expectation 0 and variance 2(n-2)/[r(n-1)^2(n+1)]. LDAK-KVIK determines there is high structure when $n\hat{\rho}^2 > 0.1$ and the

corresponding p-value is below 0.001 (otherwise, it determines the structure is low). The required calculations are very fast

(e.g., when analyzing 368k individuals, they takes less than one minute) and have low memory demands (because it is only

necessary to store genotypes for 512 SNPs). **Supplementary Figure 35** shows that our test for structure is robust to the

choice of SNPs (e.g., its results change little if we reduce to 256 SNPs or restrict to SNPs with either high or low MAF).

Our test for structure is motivated by the fact that $n\hat{\rho}^2$ is an estimate of the maximum average inflation of test statistics

when using classical linear regression. This is based on the following logic. Suppose that we could partition the genetic

contribution to a phenotype as $G = L_j + D_j$ where L_j and D_j are the components local and distal to SNP j, respectively,

with heritability contributions h^2_{Lj} and h^2_{Dj}. Then when testing SNP j for association with the phenotype, we could write the

expected $\chi^2(1)$ test statistic from classical linear regression as $E[S_j] \approx 1 + n(l_j^2 h_{Lj}^2 + d_j^2 h_{Dj}^2)$, where

$l_j^2 = Cor(X_j L_j)^2$ and $d_j^2 = Cor(X_j D_j)^2$ are the proportions of local and distal genetic variation tagged by SNP j,

respectively. Under this partitioning, $n d_j^2 h_{Dj}^2$ can be viewed as the expected inflation of S_j due to structure. Finally, if we

assume that $\hat{\rho}^2$ is a reasonable estimator of $\bar{d}^2$, the average value of d^2_j across all SNPs, and recognize that $h_{Dj}^2 \leq 1$,

then it follows that $n\hat{\rho}^2$ is an upper bound for the average inflation of test statistics due to structure. Please note that

while $n\hat{\rho}^2$ measures the potential inflation of test statistics when using the raw phenotype, it becomes a measure of

deflation when using offset phenotypes (e.g., if $n\hat{\rho}^2 = 0.1$, this indicates that test statistics from regressing Y on X_j will

be on average up to 0.1 above their true values, but that test statistics from regressing $Y-P_c$ on X_j will be on average up to

0.1 below their true values).

Calculating the test statistic scaling factor.

If the above test finds low structure, LDAK-KVIK sets $\lambda = 1$. If it instead finds high structure, LDAK-KVIK estimates

λ as follows. First it constructs C LOCO ridge regression PGS, for which it assumes $\gamma_j \sim N(0, \hat{h}_j^2)$. It then uses least-

squares linear regression with the model $E[Y - P_c] = X_j \beta_j$ to compute two sets of (unscaled) $\chi^2(1)$ test statistics for

65,000 randomly-picked SNPs: for the first set (denoted by U_j), P_c is the LOCO elastic net PGS corresponding to SNP j,

while for the second set (denoted by T_j), P_c is the corresponding LOCO ridge regression PGS. Next, LDAK-KVIK uses the

Grammar-Gamma formula[11] to compute λ', the scaling factor corresponding to the second set of test statistics (by

default it uses 20 randomly-picked SNPs). Finally, it sets $\lambda = \lambda' \sum T_j / \sum U_j$, where the summations are across

weakly-associated SNPs, which we define as those with $\lambda U_j < 6$ and $\lambda' T_j < 6$ (because the definition of weakly-

associated depends on λ, we use an iterative approach that typically requires 2-5 iterations).

Note that are three advantages to setting $\lambda{=}1$ for datasets with low structure (instead of estimating λ like we do for

datasets with high structure). Firstly, it is more computationally efficient, because estimation of λ requires the

construction of an extra set of LOCO PGS. Secondly, when the true value of λ is very close to one, the advantage of

estimating λ is outweighed by the uncertainty of the estimate (e.g., estimates of λ for homogeneous datasets typically

have standard error 0.002). Thirdly, we observe that our estimates of λ can be slightly conservative for homogeneous

datasets (**Supplementary Figure 28**).

Binary phenotypes.

Many of the operations in LDAK-KVIK are based on a linear model of the form $Y_i{=}\sum X_{i,j}\,\gamma_j{+}e_i$. In particular, this

model is assumed (either explicitly or implicitly) when estimating h^2, when constructing PGS and when testing SNPs for

association. When the phenotype is quantitative, X_j and Y contain standardized residuals from linearly regressing X_j' and

Y', respectively, on Z, and LDAK-KVIK assumes $e_i \sim N(0, I(1-\hat{h^2}))$, where I is an (n x n) identity matrix and $\hat{h^2}$ is

the estimate of h^2. When the phenotype is binary, LDAK-KVIK first computes the length-n vector μ', which contains

estimates of the probabilities that each individual is a case given the covariates, and constructs the (n x n) diagonal matrix

D, with $D_{i,i} \propto \mu'_i(1-\mu'_i)$ and trace(D^{-1})=n. LDAK-KVIK then sets X_j to the residual from regressing X_j' on Z using

weighted linear regression with weight matrix D, sets $Y=D^{-1}(Y'-\mu')$, and assumes $e_i \sim N(0, D^{-1}(1-\hat{h^2}))$.

These changes are motivated by the observation that the estimated SNP effect size from regressing Y' on both X_j' and Z

using logistic regression is approximately equal to that from regressing Y on X_j using weighted linear regression with

weight matrix D (see **Supplementary Note 5** for a proof). Note that ensuring trace(D^{-1})=n allows us to continue to treat h^2

as a heritability (i.e., h^2 continues to represent the proportion of variance of Y explained by all SNPs).

In addition to changing from standard to weighted linear regression, LDAK-KVIK makes two further modifications when

analyzing binary phenotypes. Firstly, when it finds high structure, it switches to an approximate version of fastGWA

(described below). This is motivated by the observation that MMAA tools tend to have very similar power when analyzing

binary phenotypes, and particularly for datasets with high structure, so there is limited harm using a pedigree-based PGS

instead of LOCO SNP-based PGS (but the former is much faster). The second modification affects Step 2. When analyzing

quantitative phenotypes, LDAK-KVIK obtains the (unscaled) test statistics via a Wald Test (specifically,

$U_j{=}\hat{\beta}_j^2/Var(\hat{\beta}_j)$, the square of the estimated effect size for SNP j divided by its estimated variance). When analyzing

binary phenotypes, LDAK-KVIK first obtains U_j via a Wald Test, but if the corresponding p-value (after scaling by λ) is

below 0.05, computes a revised test statistic using our empirical SPA solver (described below).

Approximate version of fastGWA.

The LDAK-KVIK version of fastGWA differs from the original version in four main ways. Firstly, whereas fastGWA

constructs a GRM using all SNPs, our version uses only 1024 SNPs, picked semi-randomly from across the genome

(specifically, LDAK-KVIK first randomly picks 5,120 SNPs, then retains the 1024 SNPs with highest variance). Secondly,

when constructing the sparse GRM, fastGWA recommends truncating values below 0.05, whereas we truncate non-

significant values (specifically, those with P>0.1/n, which typically corresponds to pairs of individuals with estimated

relatedness below 0.15). Thirdly, we adjust estimates of relatedness for winners' curse (**Supplementary Figure 36**).

Fourthly, when analyzing a binary phenotype, we assume the null model $Y \sim N(0, \sigma^2 K_S + E^{-1})$, where K_S is the

sparse GRM and E is a diagonal matrix with $E_{i,i} = \mu'_i(1 - \mu'_i)$. Note that this represents a simplified version of the

quasi-likelihood used by fastGWA, because we set μ', and therefore also E, based only on the covariates, whereas

fastGWA updates μ' to allow for the contribution of the sparse GRM. **Supplementary Figure 27** shows that despite these

simplifications, our version of fastGWA performs similarly to the original version, both for quantitative and binary

phenotypes.

LDAK-KVIK-GBAT.

Previously, we developed LDAK-GBAT, a tool for gene-based association analysis.[20] This tests each gene using the mixed

model $Y \sim N(0, K_S \sigma_S^2 + I(1 - \sigma_S^2))$, where K_S is a local GRM computed using only SNPs within the gene, and σ_S^2 is

the corresponding variance component. LDAK-GBAT finds the maximum likelihood estimate of σ_S^2, then obtains a p-

value by testing if the estimate is greater than zero. Importantly, LDAK-GBAT requires only GWAS summary statistics and

a reference panel. Therefore, LDAK-KVIK-GBAT applies LDAK-GBAT using the association results from Step 2, and

using 5000 randomly-picked individuals from the data as an in-sample reference panel.

Overview of Variational Bayes.

This section explains the general idea of using variational Bayes to construct PGS, whereas the next section provides

specific details of our novel variational Bayes solver. Please note that a detailed description of variational Bayes is

provided in the supplementary material of the BOLT-LMM paper.[12]

When constructing PGS, LDAK-KVIK must compute $P(\gamma|Y)$, the posterior distribution of SNP effect sizes given the

data. To do this, we first construct a model likelihood $L(Y|\gamma)$ by assuming that Y has the multivariate normal

distribution $Y \sim N(X\gamma, I(1 - \hat{h}^2))$, where I is an (n x n) identity matrix. We then specify $\pi(\gamma)$, a prior distribution

for SNP effect sizes, and use variational Bayes to approximate $P(\gamma|Y)$ as the product of independent, single-parameter

posterior distributions (one for each SNP):

$$P(\gamma|Y) \propto L(Y|\gamma) \times \pi(\gamma) \approx Q(\gamma) = \prod Q_j(\gamma_j)$$

LDAK-KVIK updates $Q(\gamma)$ one SNP at a time, by replacing the current $Q_j(\gamma_j)$ with the distribution that minimizes the

difference between the estimated and true posterior distributions (measured by the Kullback-Leibler divergence). Once

convergence has been achieved, the corresponding PGS is constructed by setting $\gamma_j = \eta_j$, where η_j is the expectation of

$Q_j(\gamma_j)$.

As explained above, Step 1 of LDAK-KVIK uses variational Bayes to construct elastic net PGS, assuming the prior

distribution defined in Equation 1. In this application, each $Q_j(\gamma_j)$ is a mixture of a left truncated normal distribution, a

right truncated normal distribution, and a (non-truncated) normal distribution:

$$Q_j(\gamma) = p_{j-} N^-(\eta_{j-}, \sigma_{j-}^2) + p_{j+} N^+(\eta_{j+}, \sigma_{j+}^2) + (1 - p_{j-} - p_{j+}) N(\nu_{jn}, \sigma_{jn}^2)$$

If $P_j = \sum X_{j'} \hat{y}_{j'} - X_j \hat{y}_j$ denotes a partial PGS where the effect sizes are based on the current estimate of $Q(\gamma)$,

then $Q_j(\gamma_j)$ is updated by setting

$\eta_{j-} = \dfrac{X_j^T(Y-P_j)+(1-\hat{h}^2)a_j}{X_j^T X_j}, \quad \eta_{j+} = \dfrac{X_j^T(Y-P_j)-(1-\hat{h}^2)a_j}{X_j^T X_j}, \quad \sigma_{j-}^2 = \sigma_{j+}^2 = \dfrac{1-\hat{h}^2}{X_j^T X_j}$

$\eta_{jn} = \dfrac{X_j^T(Y-P_j)}{X_j^T X_j + (1-\hat{h}^2)/b_j}, \quad \sigma_{jn}^2 = \dfrac{1-\hat{h}^2}{X_j^T X_j + (1-\hat{h}^2)/b_j}, \quad p_{j-} = \dfrac{v_{j-}}{v_{j-}+v_{j+}+v_{jn}}, \quad p_{j+} = \dfrac{v_{j+}}{v_{j-}+v_{j+}+v_{jn}}$

where $v_{j-} = \dfrac{p}{2}a_j\sqrt{2\pi\sigma_{j-}^2}\,\Phi\!\left(\dfrac{-\eta_{j-}}{\sqrt{\sigma_{j-}^2}}\right)\exp\!\left(\dfrac{\eta_{j-}^2}{2\sigma_{j-}^2}\right), \quad v_{j+} = \dfrac{p}{2}a_j\sqrt{2\pi\sigma_{j+}^2}\,\Phi\!\left(\dfrac{-\eta_{j+}}{\sqrt{\sigma_{j+}^2}}\right)\exp\!\left(\dfrac{\eta_{j+}^2}{2\sigma_{j+}^2}\right)$

and $v_{jn} = (1-p)\sqrt{\dfrac{\sigma_{jn}^2}{b_j}}\exp\!\left(\dfrac{\eta_{jn}^2}{2\sigma_{jn}^2}\right)$

Novel variational Bayes solver.

The variational Bayes solver implemented in BOLT-LMM uses sequential genome-wide scans.[12] This means that on each

scan, it updates $Q_j(\gamma_j)$ once for each SNP in the genome (i.e., it first updates $Q_1(\gamma_1)$, then $Q_2(\gamma_2)$, and so on until

$Q_m(\gamma_m)$). BOLT-LMM performs multiple scans, continuing until LL, the approximate log likelihood, changes by less

than a specified tolerance (by default, 0.0005). Typically, BOLT-LMM requires 50-150 scans (convergence is slowest when

analyzing highly-heritable traits with very large sample sizes).

By contrast, our variational Bayes solver partitions the genome into chunks (by default, each chunk contains 256 SNPs),

then uses chunk-based scans (see **Supplementary Figure 1** for an illustration). On Scan 1, our solver first updates

$Q_j(\gamma_j)$ for SNPs in Chunk 1, continuing until LL has converged (the default tolerance is $n/10^6$). Our solver then updates

$Q_j(\gamma_j)$ for SNPs in Chunk 2, then for SNPs in Chunk 3, continuing until it reaches the final chunk in the genome. On

subsequent scans, our solver repeats the same process, except that it only considers chunks that had a sizeable impact on

LL (specifically, it only revisits a chunk if on the previous scan, the updates for that chunk caused LL to change by more

than $n/10^6$). Our solver typically requires no more than ten scans to converge (because at this point, no chunks remain that

have a sizeable impact on LL). We note that our solver has similarities to block coordinate descent methods, indicating that

theoretical results regarding the convergence properties of the latter may also be applicable to our solver.[38]

Our chunk-based solver has three main advantages over the genome-wide solver. Firstly, it prioritizes SNPs in regions that

have a larger influence on LL (which is more efficient than simply treating all SNPs the same). Secondly, it enables on-the-

fly reading of the genotypes (while this is, in theory, possible with the genome-wide solver, it would be necessary to read

the data 50-150 times). Thirdly, it is more cache-friendly. **Supplementary Figure 2** compares our chunk-based solver with

a genome-wide version when analyzing either 50k or 100k individuals. We see that both solvers have very similar accuracy

(in that both produce models with very similar LL). However, we find that the chunk-based solver is substantially faster,

reflecting that it performs fewer scans, and in turn fewer updates of $Q_j(\gamma_j)$. For example, when analyzing 100k

individuals, the genome-wide solver on average requires 56 scans (so updates each $Q_j(\gamma_j)$ 56 times). By contrast, our

chunk-based solver requires on average 4 scans, and on average updates each $Q_j(\gamma_j)$ 11 times. **Supplementary Figure**

37 shows that the default convergence criterion suffices, in the sense that results are almost unchanged if the tolerance is

made five times smaller.

Computing terms of the form V⁻¹A and KV⁻¹A.

Our variational Bayes solver can be used to construct ridge regression PGS by assuming the prior distribution

$\gamma_j \sim N(0, \hat{h}_j^2)$. In this application, each $Q_j(\gamma_j)$ has the form $N(\eta_j, \sigma_j^2)$, and is updated by setting

$$\eta_j = \frac{X_j^T(Y - P_j)}{X_j^T X_j + (1 - \hat{h}^2)/\hat{h}_j^2} \quad \text{and} \quad \sigma_j^2 = \frac{1 - \hat{h}^2}{X_j^T X_j}$$

However, for this choice of prior, the posterior mean has an explicit form (derived in **Supplementary Note 4**). In

particular, it can be shown that if P is a (genome-wide or LOCO) ridge regression PGS, then $P = \hat{h}^2 K V^{-1} Y$ and

$Y - P = (1 - \hat{h}^2) V^{-1} Y$ where V is a (genome-wide or LOCO) variance matrix. It follows that we can estimate terms of

the form V⁻¹Y and KV⁻¹Y by using our variational Bayes solver to construct ridge regression PGS for Y, then dividing the

estimated PGS by $\hat{h}^2$ or dividing the corresponding residuals by $(1 - \hat{h}^2)$. More generally, we can estimate terms of the

form V⁻¹A and KV⁻¹A, where A is an arbitrary length-n vector, by performing the same steps but replacing Y with A (i.e.,

instead of constructing a PGS for Y, we construct a PGS for A). Therefore, our novel variational Bayes solver can not only

be used to construct PGS, but also to compute the terms required when performing either Monte Carlo REML or using the

Grammar-Gamma formula.[11]

Overview of SPA.

Here we summarize the SPA; for a fuller description, we recommend reading the supplementary material of the REGENIE

paper.[13] If A is a random variable, then its cumulant-generating function (CGF) is $K_A(t) = \log(E[\exp(tA)])$. The first,

second and third derivatives of $K_A(t)$ are

$$K_A^1(t) = \frac{m_1(t)}{m_0(t)}, \quad K_A^2(t) = \frac{m_2(t)}{m_0(t)} - \frac{m_1(t)^2}{m_0(t)^2} \quad \text{and} \quad K_A^3(t) = \frac{m_3(t)}{m_0(t)} - \frac{3 m_1(t) m_2(t)}{m_0(t)^2} + \frac{2 m_1(t)^2}{m_0(t)^3}$$

where $m_k(t) = E[A^k \exp(tA)]$. The CGF is additive, such that if A and B are independent random variables, then

$K_{aA+bB}(t) = K_A(at) + K_B(bt)$. Similar relationships hold for the first, second and third derivatives:

$K_{aA+bB}^1(t) = a K_A^1(at) + b K_B^1(bt), \quad K_{aA+bB}^2(t) = a^2 K_A^2(at) + b^2 K_B^2(bt) \quad \text{and} \quad K_{aA+bB}^3(t) = a^3 K_A^3(at) + b^3 K_B^3(bt)$

Now suppose A arises as a test statistic from regressing a phenotype on X_j. The most common way to calculate a p-value is

to compute $U_j = (A - E[A])^2 / Var(A)$, where E[A] is the expectation of A under the null hypothesis, while Var(A) is

its estimated variance, then to compare U_j to a $\chi^2(1)$ distribution (or equivalently, compare its square root to a standard

normal distribution). However, this approach assumes the null distribution of A is approximately normal, which can be

inappropriate (e.g., if the phenotype is binary and very imbalanced, or when testing rare variants). The SPA method instead

computes

$$U'_j = \left(w + \log\left(\frac{v}{w}\right)/w\right)^2 \quad \text{with} \quad w = sign(t')\sqrt{2(t'A - K_A(t'))} \quad \text{and} \quad v = t'\sqrt{K_A^2(t')} \qquad (2)$$

where t' is the solution to K¹(t')=A, then obtains a p-value by comparing U'$_j$ to a $\chi^2(1)$ distribution.

Our Empirical SPA solver.

Suppose the test statistic from regressing a phenotype B on X_j takes the form $A = a_1B_1 + \ldots + a_nB_n$. Our solver starts by

calculating $K_B(at) = \log\left(\sum \exp(atB_i)/n\right)$ for 41 predetermined values of a (evenly spaced between -2 and 2), and for

256 predetermined values of t (ranging from t_{min} to t_{max}, as described below). Note that these calculations correspond to

assuming that the B_i are independent and identically distributed, and that their true distribution matches the observed

distribution (see below).[23] Our solver similarly computes 41 x 256 realizations for each of $K^1_B(at)$, $K^2_B(at)$ and $K^3_B(at)$. We

refer to the predetermined values of a and t as "bin centres" and "knots", respectively.

When LDAK-KVIK analyzes a quantitative phenotype, the (unscaled) Step 2 test statistic for SNP j is $A = X_j^T(Y - P_c)$,

so we set $a_i = X_{ij}$ and $B_i = Y_i - P_{ci}$ in the above equations; when LDAK-KVIK analyzes a binary phenotype, the test statistic is

$A = X_j^T D(Y - P_c)$, so we set $a_i = X_{ij}$ and $B_i = D_{ii}(Y_i - P_{ci})$. Note that when calculating the CDF of A and its derivatives, it is

necessary to calculate terms of the form $K_B(a_it)$, $K^1_B(a_it)$ and $K^2_B(a_it)$, and in general, a_i will not match one of the 41 bin

centres. Therefore, we approximate these terms using first, second and third order Taylor Series. Specifically, if a' denotes

the bin centre closest to a_i, then we use the three approximations

$K_B(a_it) \approx K_B(a't) + K^1_B(a't)(a_it - a't) + K^2_B(a't)(a_it - a't)^2/2 + K^3_B(a't)(a_it - a't)^3/6$

$K^1_B(a_it) \approx K^1_B(a't) + K^2_B(a't)(a_it - a't) + K^3_B(a't)(a_it - a')^2/2$

and $K^2_B(a_it) \approx K^2_B(a't) + K^3_B(a't)(a_it - a't)$

Our solver uses the second approximation to estimate $K^1_A(t) = a_1K^1_B(a_1t) + \ldots + a_nK^1_B(a_nt)$ for each of the 256 knots. It then

identifies t_L and t_R, the knots immediately left and right of the solution to $K^1_A(t) = A$, and uses the first and third

approximations to calculate $K_A(t_L)$, $K_A(t_R)$, $K^2_A(t_L)$ and $K^2_A(t_R)$. Lastly, our solver uses linear interpolation to estimate t',

$K_A(t')$ and $K^2_A(t')$. Specifically, it computes $\epsilon = (K^1_A(t_L) - A)/(K^1_A(t_L) - K^1_A(t_R))$, which estimates the location of the

solution, relative to the closest two knots (e.g., $\epsilon = 0.5$ indicates that t' is approximately halfway between t_L and t_R), then sets

$t' = (1-\epsilon)t_L + \epsilon t_R$, $K_A(t') = (1-\epsilon)K_A(t_L) + \epsilon K_A(t_R)$ and $K^2_A(t') = (1-\epsilon)K^2_A(t_L) + \epsilon K^2_A(t_R)$

We now have all terms required to compute U'_j, the $\chi^2(1)$ test statistic defined in Equation 2. If our solver performed the

above calculations naively, it would likely be no faster than existing SPA solvers, because computing each of the CGF and

its derivatives still requires n operations (e.g., to compute $K_A(t)$ for a particular knot, it is necessary compute $K_B(a_it)$ for

each individual). However, the number of operations can be reduced dramatically by first summarizing X_j with respect to

the bin centres. Specifically, if b_k denotes the kth bin centre, and the function I(i,k) indicates whether a_i is closest to b_k, then

our solver computes $C_1, \ldots, C_9$, nine length-41 count vectors whose elements are

$C_{1,k} = \sum I(i,k)$, $C_{2,k} = \sum I(i,k)a_i$, $C_{3,k} = \sum I(i,k)a_i^2$

$C_{4,k} = \sum I(i,k)(a_i - b_k)$, $C_{5,k} = \sum I(i,k)a_i(a_i - b_k)$, $C_{6,k} = \sum I(i,k)a_i^2(a_i - b_k)$

$C_{7,k} = \sum I(i,k)(a_i - b_k)^2$, $C_{8,k} = \sum I(i,k)a_i(a_i - b_k)^2$, $C_{9,k} = \sum I(i,k)(a_i - b_k)^3$

Given these nine vectors, we can rewrite the CDF of A and its derivatives as

$K_A(t) = \sum \left(C_{1,k}K_A(b_k) + tC_{4,k}K^1_A(b_k) + t^2C_{7,k}K^2_A(b_k) + t^3C_{9,k}K^3_A(b_k)\right)$

$K^1_A(t) = \sum \left(C_{2,k}K^1_A(b_k) + tC_{5,k}K^2_A(b_k) + t^2C_{8,k}K^3_A(b_k)\right)$

$K^2_A(t) = \sum \left(C_{3,k}K^2_A(b_k) + tC_{6,k}K^3_A(b_k)\right)$

which can be computed using 164, 123 and 82 operations, respectively (numbers that, for large datasets, are substantially

smaller than n).

When deciding the predetermined knot values, we initially use 256 quantiles from a Cauchy distribution,[23] scaled such that

$t_{min} = -2000\sqrt{n}$ and $t_{max} = 2000\sqrt{n}$. However, if our solver encounters a SNP for which this range is not sufficient (i.e.,

the corresponding test statistic is not bounded by $K^1_A(t_{min})$ and $K^1_A(t_{max})$), then our solver resets the knot values so that t_{min}

and t_{max} are five times larger than their original values (this was not necessary for any of the analyses in this paper).

As explained above, our SPA solver assumes the true distribution of B, the adjusted phenotype, matches its empirical

distribution. This has the advantage that our solver can be (validly) applied to any phenotype, whereas existing SPA solvers

generally assume the phenotype has a Bernouilli distribution, so can only be applied to binary phenotypes. Furthermore,

our solver makes no requirements on the form of X_j (although the predetermined bin centres assume that all elements of X_j

are between -2 and 2, when this is not the case, our solver simply rescales X_j). This means that our solver can automatically

be applied to dosage data produced by genotype imputation, or used with non-SNP data.

Supplementary Figure 38 shows that our empirical SPA solver is effective at controlling type 1 error when used either for

rare binary phenotypes or for datasets with rare variants, while **Supplementary Figure 39** shows that the default values for

the numbers of bin centres and knots suffice, in the sense that results are almost unchanged if we increase either of these

values (e.g., increase the number of bin centres from 41 to 100, or the number of knots from 256 to 512).

Comparison between our SPA solver and EmpSPA. Our SPA solver is inspired by EmpSPA,[39] which was developed in

order to compute p-values when performing Cox Regression (i.e., when analyzing survival data). In particular, we use the

same formulae for $K_B(at)$, $K^1_B(at)$ and $K^2_B(at)$, and also copy their use of a Cauchy distribution when deciding the pre-

determined knots. Saying this, a key difference is that our solver uses two-dimensional look-up tables (i.e., considers 41

values for a and 256 values for t), whereas EmpSPA uses one-dimensional look-up tables (in our notation, EmpSPA would

be equivalent to setting a=1, then considering 10,000 values for t). Although, these two approaches have a similar one-off

complexity (both involve evaluating the CGF and its derivatives for approximately 10,000 values), we find that using a

two-dimensional look-up table is substantially more efficient. This is because, having mapped each value of X_{ij} to the

nearest bin (i.e., obtained the count vectors $C_1, \ldots, C_9$), our solver requires only 3x41 operations to evaluate $K^1_A(t)$ for each

knot, and having found the two closest knots, a further 6x41 operations to evaluate the corresponding values for $K_B(at)$ and

$K^2_B(at)$. Additionally, because we use uniformly-spaced bins, the (base-0) indexes of the nearest bins can be obtained by

computing the integer part of $10(X_{ij}+2)$. By contrast, to evaluate $K^1_A(t)$ for a given value of t, EmpSPA must map each

value of a_iX_{ij} to the nearest pre-computed knot, then repeat this process for each t. As well as requiring more operations, the

mapping is made more challenging by the fact that the pre-computed knots are not uniformly spaced (so requires a divide-

and-conquer approach).

REFERENCES

1. Uffelmann, E. *et al.* Genome-wide association studies. *Nature Reviews Methods Primers* **1**, 59 (2021).

2. Visscher, P. M. *et al.* 10 Years of GWAS Discovery: Biology, Function, and Translation. *Am J Hum Genet* **101**, 5–22 (2017).

3. Chen, Z. *et al.* China Kadoorie Biobank of 0.5 million people: survey methods, baseline characteristics and long-term follow-up. *Int J Epidemiol* **40**, 1652–1666 (2011).

4. Keaton, J. M. *et al.* Genome-wide analysis in over 1 million individuals of European ancestry yields improved polygenic risk scores for blood pressure traits. *Nature Genetics* **56**, 778–791 (2024).

5. Haines, J. L. *et al.* Complement factor H variant increases the risk of age-related macular degeneration. *Science* **308**, 419–421 (2005).

6. Kurki, M. I. *et al.* FinnGen provides genetic insights from a well-phenotyped isolated population. *Nature* **613**, 508–518 (2023).

7. Leitsalu, L. *et al.* Cohort Profile: Estonian Biobank of the Estonian Genome Center, University of Tartu. *International Journal of Epidemiology* **44**, 1137–1147 (2014).

8. Lippert, C. *et al.* FaST linear mixed models for genome-wide association studies. *Nature Methods* **8**, 833–835 (2011).

9. Zhou, X. & Stephens, M. Efficient multivariate linear mixed model algorithms for genome-wide association studies. *Nature Methods* **11**, 407–409 (2014).

10. Yang, J., Zaitlen, N. A., Goddard, M. E., Visscher, P. M. & Price, A. L. Advantages and pitfalls in the application of mixed-model association methods. *Nature Genetics* **46**, 100–106 (2014).

11. Svishcheva, G. R., Axenovich, T. I., Belonogova, N. M., van Duijn, C. M. & Aulchenko, Y. S. Rapid variance components–based method for whole-genome association analysis. *Nature Genetics* **44**, 1166–1170 (2012).

12. Loh, P.-R. *et al.* Efficient Bayesian mixed-model analysis increases association power in large cohorts. *Nature Genetics* **47**, 284–290 (2015).

13. Mbatchou, J. *et al.* Computationally efficient whole-genome regression for quantitative and binary traits. *Nature Genetics* **53**, 1097–1103 (2021).

14. Zhou, W. *et al.* Efficiently controlling for case-control imbalance and sample relatedness in large-scale genetic association studies. *Nat Genet* **50**, 1335–1341 (2018).

15. Loh, P. Mixed-model association for biobank-scale datasets. **50**, 906–908 (2018).

16. Campos, A. I. *et al.* Boosting the power of genome-wide association studies within and across ancestries by using polygenic scores. *Nature Genetics* **55**, 1769–1776 (2023).

17. Bycroft, C. *et al.* The UK Biobank resource with deep phenotyping and genomic data. (2018) doi:10.1038/s41586-018-0579-z.

18. Sudlow, C. *et al.* The UK Biobank resource with deep phenotyping and genomic data. *PLoS Med.* **12**, e1001779 (2015).

19. Jiang, L. *et al.* A resource-efficient tool for mixed model association analysis of large-scale data. *Nature Genetics* **51**, 1749–1755 (2019).

20. Berrandou, T., Balding, D. & Speed, D. LDAK-GBAT: Fast and powerful gene-based association testing using summary statistics. *Am. J. Hum. Genet.* **110**, 23–29 (2023).

21. MacKay, D. J. *Information Theory, Inference and Learning Algorithms*. (Cambridge university press, 2003).

22. Dey, R., Schmidt, E. M., Abecasis, G. R. & Lee, S. A Fast and Accurate Algorithm to Test for Binary Phenotypes and Its Application to PheWAS. *Am J Hum Genet* **101**, 37–49 (2017).

23. Ma, Y., Bi, W. & Zhang, J.-F. Empirical Saddlepoint Approximation and Its Application to Genome-Wide Association Studies. in *2021 40th Chinese Control Conference (CCC)* 6380–6385 (2021). doi:10.23919/CCC52363.2021.9549628.

24. Bi, W., Fritsche, L. G., Mukherjee, B., Kim, S. & Lee, S. A Fast and Accurate Method for Genome-Wide Time-to-Event Data Analysis and Its Application to UK Biobank. *The American Journal of Human Genetics* **107**, 222–233 (2020).

25. Speed, D., Holmes, J. & Balding, D. Evaluating and improving heritability models using summary statistics. *Nat. Genet.* **52**, 458–462 (2020).

26. Zhang, Q., Privé, F., Vilhjálmsson, B. & Speed, D. Improved genetic prediction of complex traits from individual-level data or summary statistics. *Nature Communications* **12**, 1–9 (2021).

27. Speed, D. *et al.* Reevaluation of SNP heritability in complex human traits. *Nat. Genet.* **49**, 986–992 (2017).

28. Speed, D. & Balding, D. SumHer better estimates the SNP heritability of complex traits from summary statistics. *Nat. Genet.* **51**, 277–284 (2019).

29. Zou, H. & Hastie, T. Regularization and variable selection via the elastic net. *J. R. Statist. Soc. B* **67**, 301–320 (2005).

30. Organization, W. H. *The ICD-10 Classification of Mental and Behavioural Disorders: Clinical Descriptions and Diagnostic Guidelines*. vol. 1 (World Health Organization, 1992).

31. de Leeuw, C. A., Mooij, J. M., Heskes, T. & Posthuma, D. MAGMA: generalized gene-set analysis of GWAS data. *PLoS Comput Biol* **11**, e1004219 (2015).

32. Bakshi, A. *et al.* Fast set-based association analysis using summary data from GWAS identifies novel gene loci for human complex traits. *Scientific Reports* **6**, 32894 (2016).

33. Momin, Md. M. *et al.* A method for an unbiased estimate of cross-ancestry genetic correlation using individual-level data. *Nature Communications* **14**, 722 (2023).

34. Zeng, J. *et al.* Signatures of negative selection in the genetic architecture of human complex traits. *Nat. Genet.* **50**, 746–753 (2018).

35. Schoech, A. *et al.* Quantification of frequency-dependent genetic architectures and action of negative selection in 25 UK Biobank traits. (2017).

36. Pruitt, K. D., Tatusova, T. & Maglott, D. R. NCBI reference sequences (RefSeq): a curated non-redundant sequence database of genomes, transcripts and proteins. *Nucleic Acids Res* **35**, D61-65 (2007).

37. Pazokitoroudi, A. *et al.* Efficient variance components analysis across millions of genomes. *Nat Commun* **11**, 4020 (2020).

38. Tseng, P. Convergence of a Block Coordinate Descent Method for Nondifferentiable Minimization. *Journal of Optimization Theory and Applications* **109**, 475–494 (2001).

39. Ma, Y., Bi, W. & Zhang, J.-F. Empirical Saddlepoint Approximation and Its Application to Genome-Wide Association Studies. in *2021 40th Chinese Control Conference (CCC)* 6380–6385 (2021). doi:10.23919/CCC52363.2021.9549628.