Transformers in Skin Lesion Classification and Diagnosis: A Systematic Review

Abdulmateen Adebiyi MS [1], Nader Abdalnabi MSB, [2*] Eduardo J. Simoes MD [3], Mirna Becevic PhD [4], Emily Hoffman Smith MD [5], Praveen Rao PhD [1]*

* Indicates that the first and second authors have equal contributions

[1] *Department of Electrical Engineering and Computer Science,* University of Missouri, United States

[2] *MU Institute for Data Science and Informatics,* University of Missouri, United States

[3] *Department of Biomedical Informatics, Biostatistics and Medical Epidemiology,* University of Missouri, United States

[4] *Department of Dermatology,* University of Missouri, United States

[5] Department of Dermatology, Saint Louis University, United States

Corresponding Author: Praveen Rao, Ph.D., Department of Electrical Engineering and Computer Science, 411 S 6th St, Columbia, MO 65201

Abstract

Objectives: This systematic review aims to provide a comprehensive overview of the current state of research on the application of transformers in skin lesion classification.

Materials and Methods: Over the period 2017-2023, this systematic review investigated the application of transformer-based models in skin lesion classification, focusing on 57 articles retrieved from prominent databases which are PubMed, Scopus, and Medline. The inclusion criteria encompass studies centering on transformer-based models for skin lesion classification, utilization of diverse datasets (dermoscopic images, clinical images, or histopathological images), publication in peer-reviewed journals or conferences, and availability in English. Conversely, exclusion criteria filter out studies not directly related to skin lesion classification, research applying algorithms other than transformer-based models, non-academic articles lacking empirical data, papers without full-text access, and those not in English.

Results: Our findings underscore the adaptability of transformers to diverse skin lesion datasets, the utilization of pre-trained models, and the integration of various mechanisms to enhance feature extraction.

Conclusion: Our Systematic review showed the implementation and the application of the Transformer models for skin lesion classification. Our study showed the research areas and future research ideas for the use of transformers on skin lesion classification.

Keywords: Transformer, Vision Transformer, Skin Cancer, Primary Care Physicians

Introduction:

Skin cancer is the most common type of cancer in the United States[1]. Melanoma, a type of skin cancer, accounts for most skin cancer deaths[1]. About 100,640 new cases of melanoma will be diagnosed in 2024[1]. Around 59,170 of these cases are in men and 41,470 in women[1]. Specifically, the unregulated growth of abnormal skin cells is identified as skin cancer. DNA damage in skin cells from exposure to Ultraviolet (UV) radiation from the sun or tanning beds leads to mutations or genetic abnormalities. These mutations prompt the rapid reproduction of skin cells[2].

The initial stage in diagnosing a potentially malignant skin lesion involves a visual inspection by a trained clinician[3]. Achieving an accurate diagnosis is crucial due to the similarities among other lesion types, such as seborrheic keratosis, pigmented spindle cell nevus, among others.[2] Notably, the Computer-Aided System (CAD) demonstrates a diagnostic accuracy closely comparable to that of an experienced dermatologist[4]. In the absence of technological support, dermatologists with over 10 years of clinical experience can diagnose melanoma with an accuracy rate of around 65% to 80%[5,6]. In cases requiring additional verification, dermatoscopic images are captured using a high-resolution camera to supplement the visual examination[7]. This process involves controlled lighting and the use of a filter during image capture to diminish skin reflections[8].Integration of this technical assistance has yielded a significant improvement in skin lesion diagnosis. Ultimately, the synergy between visual examinations and dermatoscopy images have resulted in an improved accuracy ranging from 75% to 84% for melanoma detection[9].

The emergence of the transformer models has sparked a lot of interest in the vision community because of their great performance on natural language tasks[10,12]. Unlike previous methods like gated Neural Networks (NNs), Recurrent Neural Networks (RNNs), and Long-Short Term Memory (LSTM) networks, transformers enables global dependency modeling and parallelization. It has sparked interest in applying transformers to many domains such as audio, vision, and medical imaging tasks, notably in skin lesion classification[11,12].

Our objectives in this systematic review are:

- To analyze current research on the use of transformers in skin lesion classification.

- To compare the performance of the different transformer models with convolution neural network architecture in skin lesion classification.

- To discuss the research gaps, future research ideas, under-researched areas and opportunities regarding the use of transformers on skin lesion classification.

Methods:

Search process

We utilized three databases—PubMed, Scopus, and Medline—to retrieve pertinent research articles. The search was conducted in July 2024, and all obtained search results were considered. We examined the reference lists of the finalized articles to ensure any additional relevant studies are included. Our search string encompassed two major terms: "Skin Neoplasms" and "Transformers." Variations of the term "Skin Neoplasms" included "Cancer of Skin" and "Skin Cancer," while for "Transformers," we employed alternate phrasings such as "Vision Transformers" and "Image Transformers." The search strategy involved using diverse forms of each term and refining the search string based on both search outcomes and database

Figure 1: Study PRISMA flowchart

specifications. PRISMA guidelines are followed for this scoping review. Figure 1 shows the study flow based on the PRISMA guidelines.

Inclusion and exclusion criteria

Our inclusion criteria included articles that reported transformer-based approaches for skin lesion detection using dermascopy images, published in the English language, and in or after 2017. We included research studies that used transformers for lesion segmentation, lesion boundaries identification, lesion detection, and semantic information/features calculation from dermoscopy images. We excluded studies that used transformers for medical image data other than skin cancer applications. During the process of inclusion and exclusion, we considered only primary studies and published conference proceedings. We excluded preprints, short reviews, commentaries, editorials, and abstracts. Additionally, non-English studies were excluded from this review.

Study selection

In this study, we employed the PRISMA tool for the initial screening and selection of studies. Duplicates were removed, and the remaining studies were evaluated based on their titles and abstracts. The contents of the studies that met the inclusion and exclusion criteria were then assessed for eligibility.

Data extraction

A data extraction sheet was prepared to retrieve all relevant information from the final included articles. This information includes the first author's name, publication year, type of article, first author's institution and location (country), data modality, availability of data (public or private, with access link), and architecture of the transformer model.

Results

After applying the inclusion and exclusion criteria, we identified 20 papers focused on implementation of transformers architecture for skin lesion classification.

Transformers for Skin Lesion Classification

Transformer Architecture: Many of the papers we reviewed implemented models with transformer or transformer-like architecture[13,15,17].Transformer architecture proposed by Vaswani et al[25]. As shown in figure 2 as the encoder-decoder structure. The encoder maps an input sequence which is then fed to the decoder. The decoder then generates the output

sequence. They proposed a mechanism known as the Self Attention. Transformer has stacks of transformer blocks that maps sequences of input vectors (x1……xn) to sequences of output vectors (z1…. zn) of corresponding size. All these blocks are made by combining the simple linear layers, feedforward networks and self-attention layers.

Vision Transformer: More specifically, some of the papers we reviewed implemented the Vision Transformer model[13,15,17].This is an image classification deep learning model that employs a transformer-like architecture for the classification task. The model was proposed in the research work entitled "An image is worth 16*16 words: Transformers for image recognition at scale"[26]. Vision transformers has been applied in many real-life

Figure 3: Vision Transformer Architecture[28]

applications like object detection, image classification etc. It has also been recently applied in many skin lesion classification tasks. Figure 3 shows the architecture for vision transformers.

Many of the papers we reviewed implemented the Vision Transformer model. Nie et al 2022 proposed a hybrid model that combines Convolution Neural Network (CNN) feature extraction with Vision transformer on the ISIC 2018 datasets[13]. Their Vision Transformer contains the embedding layer, the transformer encoder and the MLP head. They used ResNet50 for the feature extraction. The main difference between their model and the conventional Transformer model is that they used the traditional convolution neural network feature extraction with Vision Transformer. They performed their experiment using different loss function namely: Cross-Entropy Loss (CE), Weighted Cross-Entropy Loss (WCE) and Focal Loss (FL). They also compared the result of their Hybrid model (CNN+VIT) to ResNet50(CNN) model. They performed 6 different experiments using the loss function. The different experiments are using the ResNet50 model with the three Loss Function which they name (CNNce, CNNwce and CNNfl) and using the Hybrid model (CNNViT) on the different loss functions which they name (CNNViTfc, CNNViTwce and CNNVITfl). Aladhadh et al proposed a Medical Vision Transformer (MVT) model for the Skin Cancer Classification[15]. The MVT architecture has the Embedding layer, Encoder Layer, and the Classification layer. Their model used an input data of the size 72 * 72. Their input image was converted into 9 patches. The MVT had 24 layers, hidden size D of 1024, MLP size of 4096 and a total parameter of 86 million. They compared the proposed MVT model to the state-of-the-art methods.

Xin et al applied multiscale vision transformer (ViT) in their work[16]. A multiscale ViT improves the image feature embedding module. The major difference between their multi-scale vision

transformer is that it mainly improves the image feature embedding module and applies the contrastive learning method to the skin cancer classification. The multi-scale sliding window generates the overlapping patch images. Their model has the multi-scale image sequentialization, the patch embedding and the contrastive learning.

Abbas et al proposed Assist Demo using a separable vision transformer to classify pigmented skin lesions[27]. Their model is based on the Squeezenet and depthwise separable convolution neural network models. They modified SqueezeNet design into Squeeze-light by using depthwise separable convolutions (SepConv). The SqueezeNet-Light architecture contains the SqueezeNet-Light base structure, fire module structure and SepConv Structure. They presented Assist-Dermo, a lightweight separable vision transformer model for classifying nine different classes of pigmented skin lesions (PSLs). The model achieved a high accuracy, sensitivity, and specificity, outperforming the state-of-the-art models.

Cirrincione et al implemented a vision transformer model to classify the ISIC 2017 dataset[18]. Their proposed model is based on Vision Transformer which can be used for encoding images that are able to model long-range spatial relationships in the skin lesions. Their model has a Multi-Head Attention. The input is associated with key, query, and the value. Their result was fed to a SoftMax function and multiplied by the value vector. Their architecture encompasses patching, flattening, embedding and positional encoding, concatenation of the input sequence, layer normalization, multi-Head attention, layer normalization, Multilayer perceptron, classification head and the classification output.

Yacob et al proposed a weakly supervised approach for detecting and classifying basal cell carcinoma (BCC) using a graph-transformer on whole slide images (WSIs)[19]. They used features

that were generated from self-supervised contrastive learning for their Graph Convolution Neural Network. They then fed the network to a Vision Transformer.

Wang et al used XBound-Former, a novel cross-scale boundary-aware transformer, for skin lesion segmentation from dermoscopy images[20]. X-Bound is a cross-scale attention mechanism for curbing the problems of ambiguous boundaries and size variation. The Cross-scale-aware transformer (XBound-Former) uses a pyramid vision transformer for extracting features of the skin lesions. The model addresses the variation and boundary problems of skin lesion segmentation by integrating boundary knowledge into a transformer-based network.

Vasu et al proposed an approach using Vision Transformers (ViT) to identify seborrheic keratosis skin disease, achieving 99% accuracy. The study compares ViT with VGG-19 and Inception-V3 CNN algorithms for classification[28].

Yang et. al implemented a novel Vision Transformer model[21]. Their method has four bocks: The data augmentation and cancer-class rebalancing block, the image restructuring block, the transformer encoder block, and the classification block. They conducted four different experiments. They are ResNet50 with Soft Attention (ResNet50+SA), Inception ResNet with Soft Attention (Irv2+SA) and the two Vit for Skin Cancer detection (VitfSCD) models. The VitFSCD-base has 12 layers while the VITfSCD-large has 24 layers.

Salvia et al. proposed a novel hyperspectral image classification architecture utilizing Vision Transformers[22]. Their ViT model received N-D data (Hyperspectral dataset) that were transformed into a 1-D arrays by dividing the original image into patches of the same dimension. The method is validated on a real hyperspectral dataset containing 76 skin cancer images. Results demonstrate that Vision Transforms are suitable for this task, outperforming the state-of-the-art methods in terms of false negative rates and processing times. Additionally, the attention mechanism is

evaluated for the first time on medical hyperspectral images. Their ViT model was trained for classifying the dataset on four classes which are the malignant melanocytic, benign melanocytic, malignant epithelial and benign epithelial.

Vachmanus et al. proposed DeepMetaForge, a deep-learning framework for skin cancer detection, which integrates metadata with visual features using a Vision Transformer backbone[23]. They used Bidirectional Encoder representation from Image Transformers (BEiT) backbone and the metadata forging mechanism. Their model contains the Image Encoder where they used the BEiT, the Metadata Encoder, which is based on a Convolution Neural Network, the Deep metadata fusion module that combines the image and metadata encoder and the classification layer.

Arshed at al proposed an approach using pre-trained Vision Transformers for multi-class skin cancer classification, addressing class imbalance within the dataset[29]. Their model preprocessed series of learned transformation of the input lesions. The input images were divided into 16*16 patches after resizing the images to 224 * 224 pixels.

Gulzar et al compares U-Net and attention-based methods for skin lesion image segmentation, aiming to assist in the diagnosis of skin lesions[24]. The hybrid TransUNet method is proposed and evaluated, achieving superior performance compared to benchmarking methods. The TransUNet architecture has been applied for medical image segmentation. TransUNet is a combination of the Transformer and U-Net architecture.

Lungu-Stan et al proposed a lightweight Vision Transformer for skin lesion classification, focusing on efficient inference and reduced memory usage. The model employs knowledge distillation and achieves competitive performance compared to larger models[30].

Khan et al proposed the SkinViT architecture[11]. They combined the idea of Yuan et al in VOLO[31] and the VIT architecture[26]. Their model has the Outlooker block, transformer block and SkinViT

Multilayer perceptron head block. The input images are transformed into an 8 by 8 patches which are then fed to the outlooker block. The tokens are then sampled using the patch embedding and then finally to the Multi-Layer Perceptron head.

Wang et al proposed Melanoma BatchFormer Vision Transformer Model (MBViT) [32]. The model combines the Vision Transformer model with the batchFormer module. They employed a dual-branch training strategy in their model training.

Reis al implemented a new deep learning model, a modified lightweight vision transformer (ViT) and a hybrid framework that combines an integrated deep learning model and an Ensemble learning model[33]. They named the model the multi head attention block depthwise separable convolution network (MABSCNET). The MABSCNET model was designed to combine the advantages of both the CNN and transformer model. The architecture includes the multi-head attention (MHA) and depthwise Separable Convolution (DSC).

Dai et al introduced an efficient and lite convolution transformer model. Their model hierarchically learns the local and global representations through the attention mechanisms. Branch attention helps their model to extract features from different layers[34].

Remya et al applied the Vision Transformer model for their skin lesion classification[35]. Their images were resized to 224 by 224 pixels and were set from 0 to 1 range. They applied EfficientNet-BO model as their feature extractor. A feedforward neural network was placed after many multi-head self-attention layers in their architecture.

Evaluation Metrics of the Transformer Models

We want to emphasize the performance of the different transformers models that were implemented in the papers we surveyed. The evaluation metrics is used to understand the

performance of the models and to compare different models or to compare a model with the baseline/state-of-the-art models. Table 1 below shows the evaluation metrics used in the papers with their corresponding computing formulas.

Table 1: Performance metrics used in the reviewed papers.

Metric	Formula
Precision (P)	$T_p/(T_p+F_p)$
Sensitivity/ Recall (R)	$T_p/(T_p+F_n)$
Specificity	$T_n/(T_n+F_p)$
Accuracy	$(T_p+T_n)/(T_p+T_n+F_p+F_n)$
F1-score	$2{\times}P{\times}R/(P+R)$
Intersection over Union (IoU)	$(T_p+T_n)/(T_p+F_p+F_n)$

In Table 2, T_p denotes True Positives, T_n denotes True Negatives, F_p denotes False Positives and F_n denotes False Negatives.

Nie et al used accuracy, precision, recall, f1-score, and Area Under Curve (AUC) in their work[13]. Aladhadh et al evaluated their models with precision, recall or sensitivity, F1-measure, and accuracy[15]. Desale et al. employed accuracy, precision, sensitivity, f-measure, specificity, recall, Jaccard coefficient and mathew's correlation coefficient(mcc)[17]. Xin et al used precision, recall, accuracy and f1-score in their work. Abbas et. al. also applied accuracy, precision, recall, fi-score and mcc in their work[16]. Cirrincione at al evaluated their model on accuracy, sensitivity, and specificity[18]. Yacob et al evaluated their model on accuracy, sensitivity, and specificity[19]. Wang J. employed dice coefficient, IoU score, Average symmetric surface distance (ASSD) and Hausdorff distance of boundaries. Guang et al used accuracy, precision, sensitivity, f1score and specificity for their evaluation[21]. Salvia et al evaluated their model by using the metric accuracy, specificity, and false negative rate per class[22]. Vachmanus et al evaluated their vison transformer models by using precision, recall, F1 score, accuracy, MCC, sensitivity, specificity, and negative predictive value(npv)[23]. Arshed et al. used accuracy, precision, recall and F1 score for their

evaluation. Yonis et al used Intersection over Union (IoU), precision, recall and accuracy for its evaluation[29]. Lungu stan et al evaluated their SkinDistilVit model with balanced multi-class accuracy (BMA), accuracy, precision, recall and f1-score. Overall, almost all the papers we reviewed used accuracy, specificity, sensitivity, and f1-score for the evaluation.

Table 2 below briefly shows the performance metrics and the corresponding values in each paper, the models used in the papers and finally, the dataset

Table 2: Summary of the best performance metric, models used and dataset for each reviewed paper

#.	Title	Performance Metric (value)	Best Models Used	Dataset
1	A Deep CNN Transformer Hybrid Model for Skin Lesion Classification of Dermoscopic Images Using Focal Loss.	Accuracy (89.61%) Precision (82.12%) Recall (89.48%) F1-Score (89.09%)	Hybrid Model (CNN + Vision Transformer+ Focal Loss)	ISIC 2018
2	An Effective Skin Cancer Classification Mechanism via Medical Vision Transformer.	Accuracy (96.14%) Precision (96.00%) Recall (96.50) F1-Measure (97.00)	Medical Vision Transformer	HAM10000

3	An efficient multi-class classification of skin cancer using optimized vision transformer	Accuracy (99.81%) Precision (96.65%) Sensitivity (98.21%) F-Measures (97.42%) Specificity (99.88%) Recall (98.21%) Jaccard Coefficient (98.54%)	Vision Transformer	ISIC 2019
4	An improved transformer network for skin cancer classification	Precision (94.20%) Accuracy (94.10%) F1-Score (94.10%)	Multi-scale Vision Transformer	HAM10000 Custom Data
5	Assist-Dermo: A Lightweight Separable Vision Transformer Model for Multiclass Skin Lesion Classification.	Accuracy (95.6%) Sensitivity (96.7%) Specificity (95%) AUROC (0.95)	Assist Demo (Light weight Vision Transformers)	Ph2 ISBI-2017 HAM10000

6	Transformer-Based Approach to Melanoma Detection	Accuracy (0.948) Sensitivity (0.928) Specificity (0.967) AUROC. (0.948)	VIT-based approach	ISIC 2017
7	Weakly supervised detection and classification of basal cell carcinoma using graph-transformer on whole slide images.	Accuracy (2 classes) (93.5%) Sensitivity-Healthy (96%) Sensitivity-Tumor (91.9%) Specificity-Healthy (91.9%) Specificity-Tumor (96%)	Graph-Transformer (Graph Neural Network and Vision Transformer)	Custom Dataset (Sahlgrenska University Hospital)
8	XBound-Former: Toward Cross-Scale Boundary Modeling in Transformers.	Dice Coefficient (93.08) IoU Score (87.69)	XBound-Former (Uses a pyramid vision transformer)	ISIC-2016 & PH2 ISIC-2018

		Average symmetric surface distance (8.21) Hausdorff distance of boundaries (21.83)		
9	A framework for seborrheic keratosis skin disease identification using Vision Transformer	Accuracy (99%)	Vision Transformer	386 Images on Kaggle
10	A Novel Vision Transformer Model for Skin Cancer Classification	Accuracy (94.1%) Precision Sensitivity F1 Score Specificity	Vision Transformer (ViTfSCD-B and ViTfSCD-L)	HAM10000 Dermofit dataset
11	Attention-based Skin Cancer Classification Through Hyperspectral Imaging	Accuracy Benign Epithelia (63%) Benign Melanocytic (84%)	Vision Transformer	Custom Dataset (Skin Cancer Hyperspectral Dataset)

		Malignant Epithelial (41%) Malignant Melanocytic (91%) Specificity Benign Epithelia (90%) Benign Melanocytic (100%) Malignant Epithelial (5%) Malignant Melanocytic (99%)		
12	DeepMetaForge: A Deep Vision-Transformer Metadata-Fusion Network for Automatic Skin Lesion Classification	Accuracy (0.916) Matthew's correlation coefficient (0.751) Sensitivity (0.867) Specificity (0.876)	Bidirectional Encoder representation from Image Transformers (BEiT)	ISIC 2020 PAD-UFES-20 SKINL2 PH2

		Negative predictive value (0.901)		
13	Multi-Class Skin Cancer Classification Using Vision Transformer Networks and Convolutional Neural Network-Based Pre-Trained Models	Accuracy (92.14%) Precision (92.61%) Recall (92.14%) F1 (92.17%)	Vision Transformers	HAM10000
14	Skin Lesion Segmentation Based on Vision Transformers and Convolutional Neural Networks—A Comparative Study	Intersection over Union (87.96) Precision (89.93) Recall (98.17) Accuracy (92.11)	TransUNet	ISIC 2018 Datastet
15	SkinDistilViT: Lightweight Vision Transformer for Skin Lesion Classification	Balanced multi-class accuracy (82.34%) Accuracy (88.51%) Precision (88.34%) Recall. (88.51%) F1-Score (88.37%)	SkinDistilViT	ISIC 2019 Dataset

16	SkinViT: A transformer-based method for Melanoma and Nonmelanoma classification	Accuracy (0.9019) Recall (0.9082) Precision (0.9235) F1-Score (0.9158)	EfficientNetV2 MaxViT MobileViTV2 ViT SkinViT	ISIC 2019 DermIS PH2 Dermnet-NZ
17	Fusion of transformer attention and CNN features for skin cancer detection	Accuracy (0.7821) Positive Predictive value (0.7344) Sensitivity (0.8468) F1-Score (0.7866) Cohen's Kappa (0.5662) Mean Square Error (0.2179)	ViT MABSCNET	ISIC 2019 ISIC 2020

18	A novel approach for melanoma detection utilizing GAN synthesis and vision transformer	Accuracy (98.27%) AUC (98.29%) Sensitivity (99.20%) F1-Score (96.25%)	MBViT	ISIC 2020
19	Deeply Supervised Skin Lesions Diagnosis with Stage and Branch Attention	Accuracy (96.70%)	HierAttn_xs HierAttn_s	ISIC 2019 PAD 2020
20	A Novel Transfer Learning Framework for Multimodal Skin Lesion Analysis	Accuracy (99%) Precision (0.98) Recall (0.97) F1 (0.98)	Vision Transformer	HAM10000

Discussion

This systematic review analyzed different transformer techniques implemented and applied in skin lesion classification and diagnosis. The skin cancer detection process in the reviewed manuscripts included the collection of the dataset, dataset pre-processing, the application of the transformer

models and then the evaluation of the different transformer models using different performance metrics.

Many of the available reviews on the detection of skin lesion for primary care settings are focused on Deep Learning Algorithms. With the recent introduction of the transformers model, researchers have started implementing transformer models for skin lesion detection. In this review, we surveyed different works that have been done in skin lesion classification using transformers from 2017 till date.

Most of the papers analyzed in this systematic literature review reported their best performance when Vision Transformer was applied on skin lesion dataset. They compared their performance with the state-of-the-art algorithms and other Convolution Neural Network as the benchmark. This shows that Transformer models specifically the Vision Transformer model generally outperforms the conventional convolution neural network models in the manuscripts we surveyed. We noted that the combination of images and the associated patient's data for lesion classification seems promising as one of the papers we reviewed by Xin et al implemented a transformer model to solve this. They achieved an accuracy of 94.10% in their work.

Nie et al Hybrid model outperformed the ResNet50 model with an accuracy of. 89.48%[13]. Specifically, they had the best performance when the Hybrid model (CNN+ViT) was combined with focal loss. Aladhadh et al Medical Vision Transformer (MVT) achieved an accuracy of 96.14%, precision of 96%, Recall/Sensitivity of 96.50% and F1-Measure of 97.00[15]. Xin et al proposed Multiscale VIT[16]. It achieved a precision of 0.942, an accuracy of 0.941 and an F1-score of 0.941 on their custom dataset and it achieved an AUC of 0.987, precision of 0.941 and an accuracy of 0.943 on the HAM10000 datasets. Abbas et al proposed the SqueezeNet-Light model[27]. It achieved a sensitivity of 94%, a specificity of 96%, an accuracy of 95.6%, a precision

of 94.12% and an F1-Score of 95.2[16]. It can support dermatologists in diagnosing a wide variety of PSLs through dermoscopy.

Cirrincione et al implemented a vision transformer model to classify the ISIC 2017 dataset[18]. Their model achieved an accuracy of 0.948, sensitivity of 0.928, specificity of 0.967 and AUROC of 0.948. Yacob et al proposed a weakly supervised approach for detecting and classifying basal cell carcinoma (BCC) using a graph-transformer on whole slide images (WSIs) [19]. The approach achieved a high accuracy in both tumor detection and grading of BCCs, offering potential for increasing workflow efficiency in pathology laboratories. They achieved their best accuracy of 93.5% on the 2-class problem. Experimental results demonstrate the effectiveness of the proposed Wang et al used XBound-Former model, especially on boundary-wise metrics. Vasu et al proposed an approach using Vision Transformers (ViT) to identify seborrheic keratosis skin disease, achieving 99% accuracy[28]. The proposed method achieved high accuracy through class rebalancing, image preprocessing, and a transformer-based classification block. Yang et al. proposed VitfSCD-Large[21]. It achieved an overall accuracy of 94.1% on the HAM10000 dataset and VitfSCD-Base achieved an accuracy of 80.5% on the Dermofit dataset. Salvia et al. proposed a novel hyperspectral image classification that achieved a best accuracy of 93% on the malignant melanocytic dataset. Vachmanus et al. proposed DeepMetaForge, a deep-learning framework for skin cancer detection[23]. The method achieved high accuracy and outperformed CNN-based transfer learning models. It achieved an accuracy of 92.14%.

Dataset imbalance may lead to some biases in the evaluation of the skin cancer classification. Abbas et al pointed out that weighted cross entropy improves the performance of their models by correcting the class imbalance. Aladhadh et al. also handled the class imbalance problems in their preprocessing phase of the HAM10000 dataset[15]. They applied Brightness adjustment, Contrast

Enhancement and Geometric Transformations in their Data Preprocessing phase[15] They increased the numbers of AKIEC, BCC, DF and VASC to 1099 samples after preprocessing. They didn't increase the numbers of the class BKL, NV and MEL. Nie et al 2022 handled the class imbalance problems in their dataset by using the loss functions: cross-entropy (CE), weighted-cross entropy (WCE), and Focal Loss function[13]. The Focal Loss strategy that Nie et al. implemented in their work was proposed by Lin et al[36] Xin et al. employed label shuffling to handle the class imbalance in their experiments.

Many of the studies we analyzed did not implement any explainability techniques like SHapley Additive exPlanations and Local Interpretable Model-agnostic Explanations. We recommend that future research in the classification of skin lesions using transformer models to employ and prioritize model interpretability. Understanding the rationale behind model predictions is crucial for Primary Care Physicians and Nurse Practitioners, enabling them to make informed clinical decisions.

Acknowledgments

This project was funded by the Translational Research Informing Useful and Meaningful Precision Health (TRIUMPH) grant at the University of Missouri-Columbia.

1. Information and Resources about Cancer: Breast, Colon, Lung, Prostate, Skin https://www.cancer.org

2. Kassem MA, Hosny KM, Damaševičius R, Eltoukhy MM. Machine Learning and Deep Learning Methods for Skin Lesion Classification and Diagnosis: A Systematic Review. Diagnostics. 2021 Aug;11(8):1390.

3. Artificial intelligence used to identify skin cancer https://news.stanford.edu/stories/2017/01/artificial-intelligence-used-identify-skin-cancer

4. Dick V, Sinz C, Mittlböck M, Kittler H, Tschandl P. Accuracy of Computer-Aided Diagnosis of Melanoma. JAMA Dermatol. 2019 Nov;155(11):1291–9.

5. Naik PP. Cutaneous Malignant Melanoma: A Review of Early Diagnosis and Management. World J Oncol. 2021 Feb;12(1):7–19.

6. Pampena R, Lai M, Lombardi M, Mirra M, Raucci M, Lallas A, et al. Clinical and Dermoscopic Features Associated With Difficult-to-Recognize Variants of Cutaneous Melanoma: A Systematic Review. JAMA Dermatol. 2020 Apr 1;156(4):430–9.

7. Mashoudy KD, Perez SM, Nouri K. From diagnosis to intervention: a review of telemedicine's role in skin cancer care. Arch Dermatol Res. 2024;316(5):139.

8. Sonthalia S, Yumeen S, Kaliyadan F. Dermoscopy Overview and Extradiagnostic Applications. In: StatPearls http://www.ncbi.nlm.nih.gov/books/NBK537131/

9. Alwakid G, Gouda W, Humayun M, Jhanjhi NZ. Diagnosing Melanomas in Dermoscopy Images Using Deep Learning. Diagnostics (Basel). 2023 May 22;13(10):1815.

10. Navigating the Landscape of Large Language Models: A Comprehensive Review and Analysis of Paradigms and Fine-Tuning Strategies https://arxiv.org/html/2404.09022v1

11. Khan S, Naseer M, Hayat M, Zamir SW, Khan FS, Shah M. Transformers in Vision: A Survey. ACM Comput Surv. 2022 Sep 13;54(10s):200:1-200:41.

12. Khan RF, Lee BD, Lee MS. Transformers in medical image segmentation: a narrative review. Quantitative Imaging in Medicine and Surgery. 2023 Dec 1;13(12):8747767–8767.

13. Nie Y, Sommella P, Carratù M, O'Nils M, Lundgren J. A Deep CNN Transformer Hybrid Model for Skin Lesion Classification of Dermoscopic Images Using Focal Loss. Diagnostics. 2023 Jan;13(1):72.

14. ISIC Challenge https://challenge.isic-archive.com/leaderboards/2018/

15. Aladhadh S, Alsanea M, Aloraini M, Khan T, Habib S, Islam M. An Effective Skin Cancer Classification Mechanism via Medical Vision Transformer. Sensors. 2022 Jan;22(11):4008.

16. Xin C, Liu Z, Zhao K, Miao L, Ma Y, Zhu X, et al. An improved transformer network for skin cancer classification. Computers in Biology and Medicine. 2022 Oct 1;149:105939.

17. Desale RP, Patil PS. An efficient multi-class classification of skin cancer using optimized vision transformer. Med Biol Eng Comput. 2024 Mar;62(3):773–89.

18. Cirrincione G, Cannata S, Cicceri G, Prinzi F, Currieri T, Lovino M, et al. Transformer-Based Approach to Melanoma Detection. Sensors. 2023 Jan;23(12):5677.

19. Yacob F, Siarov J, Villiamsson K, Suvilehto JT, Sjöblom L, Kjellberg M, et al. Weakly supervised detection and classification of basal cell carcinoma using graph-transformer on whole slide images. Sci Rep. 2023 May 9;13(1):7555.

20. Wang J, Chen F, Ma Y, Wang L, Fei Z, Shuai J, et al. XBound-Former: Toward Cross-scale Boundary Modeling in Transformers http://arxiv.org/abs/2206.00806

21. Yang G, Luo S, Greer P. A Novel Vision Transformer Model for Skin Cancer Classification. Neural Process Lett. 2023 Dec 1;55(7):9335–51.

22. Salvia ML, Torti E, Gazzoni M, Marenzi E, Leon R, Ortega S, et al. Attention-based Skin Cancer Classification Through Hyperspectral Imaging. In: 2022 25th Euromicro Conference on Digital System Design (DSD) [Internet]. Maspalomas, Spain: IEEE; 2022 p. 871–6.

23. Vachmanus S, Noraset T, Piyanonpong W, Rattananukrom T, Tuarob S. DeepMetaForge: A Deep Vision-Transformer Metadata-Fusion Network for Automatic Skin Lesion Classification. IEEE Access. 2023;11:145467–84.

24. Gulzar Y, Khan SA. Skin Lesion Segmentation Based on Vision Transformers and Convolutional Neural Networks—A Comparative Study. Applied Sciences (Switzerland). 2022;12(12).

25. Vaswani A, Shazeer N, Parmar N, Uszkoreit J, Jones L, Gomez AN, et al. Attention Is All You Need [Internet]. arXiv; 2023 [cited 2024 Jul 30]. Available from: http://arxiv.org/abs/1706.03762

26. Dosovitskiy A, Beyer L, Kolesnikov A, Weissenborn D, Zhai X, Unterthiner T, et al. An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale http://arxiv.org/abs/2010.11929

27. Abbas Q, Daadaa Y, Rashid U, Ibrahim MEA. Assist-Dermo: A Lightweight Separable Vision Transformer Model for Multiclass Skin Lesion Classification. Diagnostics. 2023 Jan;13(15):2531.

28. Roy VK, Thakur V, Baliyan N, Goyal N, Nijhawan R. A framework for seborrheic keratosis skin disease identification using Vision Transformer. In 2022. p. 117–28.

29. Arshed MA, Mumtaz S, Ibrahim M, Ahmed S, Tahir M, Shafi M. Multi-Class Skin Cancer Classification Using Vision Transformer Networks and Convolutional Neural Network-Based Pre-Trained Models. Information. 2023 Jul;14(7):415.

30. Lungu-Stan VC, Cercel DC, Pop F. SkinDistilViT: Lightweight Vision Transformer for Skin Lesion Classification: http://arxiv.org/abs/2308.08669

31. VOLO: Vision Outlooker for Visual Recognition | IEEE Journals & Magazine | IEEE Xplore https://ieeexplore.ieee.org/abstract/document/9888055

32. Wang R, Chen X, Wang X, Wang H, Qian C, Yao L, et al. A novel approach for melanoma detection utilizing GAN synthesis and vision transformer. Comput Biol Med. 2024 Jun;176:108572.

33. Reis HC, Turk V. Fusion of transformer attention and CNN features for skin cancer detection. Applied Soft Computing. 2024 Oct 1;164:112013.

34. Dai W, Liu R, Wu T, Wang M, Yin J, Liu J. Deeply Supervised Skin Lesions Diagnosis with Stage and Branch Attention. IEEE J Biomed Health Inform. 2023;1–12.

35. Remya S, Anjali T, Sugumaran V. A Novel Transfer Learning Framework for Multimodal Skin Lesion Analysis. IEEE Access. 2024;12:50738–54.

36. Lin TY, Goyal P, Girshick R, He K, Dollar P. Focal Loss for Dense Object Detection. In 2017 https://openaccess.thecvf.com/content_iccv_2017/html/Lin_Focal_Loss_for_ICCV_2017_paper.html