HypnoGPT: A Hypnogram Language Model for Sleep Staging Enhancement and Sleep Disorder Diagnosis

Tianyou Yu[1,3†], Zhenghui Gu[1,3†], Fei Wang[9,3], Rui Huang[1,3],
Man Li[1,3], Jingang Yu[1,3], Zhuliang Yu[1,3], Jun Zhang[10,3],
Yan Xu[11], Haiteng Jiang[4,5], Wenjuan Liu[4,6], Guifeng Deng[4,6],
Zhengrun Gao[7], Yiwen Wu[8], Jun Liu[8], Yu Zhang[12],
Shumin Duan[7], Yuanqing Li[1,3*], Jun Xiao[2,3*], Wei Wu[7*]

[1]School of Automation Science and Engineering, South China University of Technology, Guangzhou, 510641, China.
[2]School of Electric Power Engineering, South China University of Technology, Guangzhou, 510641, China.
[3]Pazhou Lab, Guangzhou, 510330, China.
[4]Affiliated Mental Health Center & Hangzhou Seventh People's Hospital and Liangzhu Laboratory, Zhejiang University School of Medicine, Hangzhou, 310058, China.
[5]School of Brain Science and Brain Medicine, MOE Frontier Science Center for Brain Science and Brain-machine Integration, State Key Laboratory of Brain-machine Intelligence, Zhejiang University, Hangzhou, 311121, China.
[6]College of Biomedical Engineering & Instrument Science, Zhejiang University, Hangzhou, 310058, China.
[7]Songjiang Hospital & Songjiang Research Institute, Shanghai Key Laboratory of Emotions and Affective Disorders, Shanghai Jiao Tong University School of Medicine, Shanghai, 201600, China.
[8]Department of Neurology & Institute of Neurology, Ruijin Hospital Affiliated to Shanghai Jiao Tong University School of Medicine, Shanghai, 200025, China.
[9]School of Artificial Intelligence, South China Normal University, Guangzhou, 510631, China.
[10]School of Information Engineering, Guangdong University of Technology, Guangzhou, 510320, China.

¹¹Sleep Medicine Center, Department of Psychiatry, Nanfang Hospital Affiliated to Southern Medical University, Guangzhou, 510515, China.
¹²Department of Neurology, Songjiang Hospital Affiliated to Shanghai Jiao Tong University School of Medicine, Shanghai, 201699, China.

*Corresponding author(s). E-mail(s): auyqli@scut.edu.cn; junxiao@scut.edu.cn; weiwuneuro@sjtu.edu.cn;
†These authors contributed equally to this work.

Abstract

Sleep hypnograms are essential for understanding sleep architecture and diagnosing prevalent sleep disorders. Recognizing the strong correlations between successive sleep stages and the inherent sequential structure of sleep hypnograms, this study introduces HypnoGPT, the first GPT-based hypnogram language model. By modeling the sequential nature of sleep and capturing transition patterns within hypnograms, HypnoGPT extracts salient sleep information to improve both sleep staging and disorder diagnosis. Following self-supervised pretraining on manually annotated whole-night sleep hypnograms, HypnoGPT yielded significant performance gains in sleep staging and disorder diagnosis across 4 publicly available datasets, with successful blinded replications on 3 independent datasets. Notably, experiments on established sleep staging benchmarks validate HypnoGPT as a robust add-on module that consistently enhances the performance of existing sleep staging methods. Moreover, a HypnoGPT-powered transformer model achieved high sensitivity and specificity in classifying abnormal sleep stage sequences and diagnosing Type-1 narcolepsy without requiring the costly multiple-sleep latency test. Additionally, the model identified a range of sleep disorder-associated patterns embedded within sleep stage sequences. HypnoGPT offers a powerful approach to modeling sleep architecture and developing artificial intelligence (AI) models for downstream applications, opening new avenues to advancing precision medicine for sleep disorders.

Keywords: Hypnogram language model, automatic sleep staging, sleep disorder diagnosis, hypnogram, generative pre-trained transformers

Introduction

Sleep accounts for one-quarter to one-third of the human lifespan. Sleep disorders, such as insomnia, sleep apnea, and narcolepsy, affect hundreds of millions of people worldwide and can lead to serious health problems, including hypertension, diabetes, depression, and heart disease [1, 2]. Sleep staging involves partitioning an entire night's sleep into distinct sleep stages, a pivotal phase in evaluating sleep quality and diagnosing sleep disorders. These stages typically encompass wakefulness (W), rapid eye movement (REM) sleep, and non-rapid eye movement (NREM) sleep, which

are further segmented into N1, N2, and N3 according to the American Academy of Sleep Medicine (AASM) standard [3], or into N1, N2, N3, and N4 according to the Rechtschaffen and Kales (R&K) standard [4]. Typically, this procedure employs nocturnal polysomnography (PSG), a composite recording featuring multiple digital signals encompassing electroencephalography (EEG), electrooculography (EOG), electromyography (EMG) of the chin and legs, and electrocardiography (ECG), as well as measures of breathing effort, oxygen saturation, and airflow. The manual labeling of sleep stages via PSG signals by sleep experts is a time-intensive, costly, subjective, and inconsistent endeavor, with reported inter-scorer reliability no more than 82.6% [5–7]. Consequently, there is a strong demand for automated sleep staging.

Machine learning (ML), especially deep learning (DL), has been extensively employed to automate the sleep staging process. Initially, conventional machine learning techniques were employed to classify sleep stages using handcrafted features [8, 9]. Capitalizing on the rapid advancements in deep learning and the increasing accessibility of large sleep datasets, deep neural networks, such as convolutional neural networks (CNNs)[10–13], recurrent neural networks (RNNs)[14–16], transformers[17, 18], and hybrid networks[19–22], have been proposed for the automated extraction of features from raw PSG signals, subsequently facilitating sleep stage classification. These deep neural networks can process either the raw multimodal time series (EEG, EOG, ECG, EMG, etc.) or time-frequency representations derived from the PSG signals [23, 24]. Moreover, sleep staging involves a classification of discrete time series, in which adjacent segments are highly correlated. Common intuition suggests that models that stage multiple consecutive epochs will generally have better performance than those that stage a single epoch. Hence, RNN models equipped with memory, such as long short-term memory (LSTM) and gated recurrent unit (GRU) are commonly employed to exploit contextual information from adjacent epochs [14, 15, 25, 26].

On the other hand, sleep patterns, including stages, duration, and regularity, are linked to the development of chronic conditions such as obesity, hyperlipidemia, hypertension, major depressive disorder, and generalized anxiety disorder. These patterns can inform evidence-based recommendations for healthy sleep habits [2]. Fast detection can improve the management and treatment of sleep disorders. Traditional diagnostic processes require highly trained sleep specialists to manually analyze and interpret results, leading to the problem of inter- and intra-operator variability and resource-intensive procedures. For instance, diagnosing narcolepsy typically involves a multiple sleep latency test (MSLT), a 10-hour test in which patients nap 4-5 times for 20 minutes every 2 hours during the day. Sleep latency and the presence of REM sleep are recorded. A mean sleep latency (MSL) of less than 8 minutes, indicative of sleepiness, and the presence of at least 2 sleep-onset REM periods (SOREMPs, REM latency $\leq$ 15 minutes following sleep onset in naps) during the MSLT, or 1 SOREMP plus a REM latency $\leq$ 15 minutes during nocturnal PSG, is diagnostic for narcolepsy [27, 28]. Automated methods for detecting sleep disorders have been suggested to increase cost-effectiveness and mitigate inter- and intra-operator variability [29]. Traditional machine learning and deep learning approaches have been employed for automated sleep disorder detection using PSG data. However, the inter-subject variability, the

high dimensionality of PSG data, and the shortage of labeled instances present challenges in training a machine learning model with robust generalization capabilities. Various features, such as time and frequency representations of single-lead or multi-channel EEG or ECG signals [30], disorder-specific events or waveforms [31], and sleep macrostructure statistics [27], have been used to train classifiers for sleep disorder diagnosis tasks with limited success. The lack of generalization capabilities and the need for extensive feature engineering have hindered the development of robust and accurate sleep disorder diagnostic models. To date, no study has employed raw sleep stage annotation sequences to diagnose sleep disorders in an end-to-end manner.

A whole-night sleep stage sequence, or hypnogram, obtained either by manual annotation or automatic sleep staging models, has pivotal significance in quantifying parameters of the sleep macrostructure, including sleep cycles, stage-specific time allocation, stage transitions, sleep latency, efficiency, etc. Typically, a sleep cycle starts with wakefulness, moves through light sleep to deep sleep, returns to light sleep, and ends with REM sleep. Once asleep, the brain cycles repeatedly through non-REM sleep and REM sleep. These stages repeat approximately 4 to 6 times each night, averaging 90 minutes for each cycle. These transitions and cycles, reflecting fundamental neurophysiological mechanisms, suggest strong correlations between consecutive sleep stages and reveal inherent sequential characteristics and transition patterns within sleep stages. These patterns offer the potential for improving the accuracy of both sleep staging and sleep disorder diagnosis [32, 33]. For instance, the characteristics of sleep stage transitions have been leveraged to facilitate automatic sleep staging through the construction of correction rules, either manually defined [34] or learned from data using Markov models [9, 32, 35]. Clinical diagnostic experience has shown that in obstructive sleep apnea (OSA), the balance between transitions from REM to NREM stages is disrupted [36]. Individuals afflicted with insomnia commonly exhibit reduced proportions of deep and REM sleep, along with an elevated incidence of light sleep. Narcolepsy, in contrast, is characterized by short-latency REM sleep, fast transitions from waking to REM sleep, and sleep/wake mixing or dissociation [27, 37]. These observations underscore the importance of capturing the sequential attributes and transition patterns embedded within sleep stage sequences for accurate sleep staging and sleep disorder diagnosis.

Although improvements have been observed by utilizing the sequential attributes of sleep stages, the feasibility of existing methods heavily depends on prior knowledge of the sleep study and the characteristics of the sleep dataset. Additionally, these methods may struggle to encode the long-term dependencies of sleep stages. We note that the contextual dependence observed in sleep stage sequences is very similar to the sequential attributes inherent in natural languages. Recent developments in various language models (LMs) for biological sequence data analysis are noteworthy. For instance, Yang et al. proposed scBERT, a large-scale pretrained deep language model for cell type annotation of single-cell RNA-seq data [38]. Born introduced a regression transformer enabling concurrent sequence regression and generation for molecular language modeling [39]. Protein language models have been proposed to predict structural viral evolution and escape patterns using sequence data alone [40], to predict atomic-level protein structures [41], and to capture biophysical features of protein sequences

for protein secondary structure prediction [42]. These language models are effective in capturing the sequential attributes of biological sequences.

Inspired by the fruitful utilization of language models in text classification, speech recognition, and biomedical sequence data analysis, we introduce a hypnogram language model named HypnoGPT, as depicted in Fig. 1. The primary objective is to encapsulate the sequential dynamics inherent to sleep stages. The model undergoes self-supervised training on an extensive dataset comprising millions of sleep stage annotations sourced from a large sleep cohort. The overarching aim is to predict the next sleep stage based on the preceding sleep stages, akin to the operation of the GPT language model [43, 44]. To our knowledge, this is the first study to harness a hypnogram language model to directly capture the inherent sequential attributes and transition patterns embedded within sleep stage sequences. The pretrained HypnoGPT model helps increase the efficacy of both sleep staging and sleep disorder diagnosis endeavors. Specifically, we treat the PSG-based sleep staging task as a speech recognition task, with speech audio replaced by PSG signals. HypnoGPT acts like a language model and is used to correct the sleep stage predictions of a sleep staging model. Similarly, we treat the task of sleep disorder diagnosis as a long text classification exercise. Here, the text sequences are substituted with sleep stage annotation sequences (hypnograms), and the classification of sleep disorders replaces the objective. Comprehensive experiments are performed to verify that the proposed HypnoGPT model can not only be used as an effective plug-and-play module, leading to stable improvements in sleep staging performance but is also effective for sleep disorder diagnosis, suggesting its potential for discovering new biomarkers for sleep disorders and other related central nervous system (CNS) diseases.

Fig. 1: **Overview of the proposed HypnoGPT model and applications to sleep staging enhancement and sleep disorder diagnosis**. (**a**) The HypnoGPT model is pretrained on a large sleep stage annotation dataset and is used to correct the sleep stage predictions of existing sleep staging models. Moreover, a hierarchical transformer network (HTN) is employed for sleep disorder diagnosis, with HypnoGPT acting as a local feature extractor. (**b**) Datasets for evaluating the proposed artificial intelligence (AI) models. For sleep staging, cross-validation of the AI models is performed on the SleepEDF and MASS datasets. The models trained from the MASS datasets are then externally validated on the Physio2018 dataset for generalizability assessment. For sleep disorder diagnosis, cross-validation of the AI models is performed on the CAP and MNC datasets. For generalizability assessment, models trained on the CAP dataset for distinguishing normal from abnormal sleep stage sequences are validated externally using the ISRUC, MNC, and HANG7 datasets, while those trained on the MNC dataset for distinguishing Type-1 narcolepsy from other hypersomnia and healthy controls are externally validated on the HANG7 dataset.

Results

Development of HypnoGPT

The HypnoGPT model, built on the GPT-2 architecture [44], is trained using the SHHS-1 dataset ($N = 5793$) with a next-stage prediction objective (Fig. **S1**). Specifically, each subject's sleep stage annotations from SHHS-1 are organized into sequences

ranging from 360 to 1199 stages in length, with an average of 1,012 stages. In total, the dataset comprises 5,863,207 sleep stage annotations.

The pretrained HypnoGPT model is then evaluated on the sleep staging task (Fig. **S2**) using the SleepEDF ($N = 153$) and MASS ($N = 200$) datasets. Concretely, several state-of-the-art sleep staging models are employed to predict sleep stages from PSG signals, and the predictions with and without HypnoGPT corrections are compared to demonstrate the enhancement enabled by HypnoGPT. Both intra-cohort cross-validation and inter-cohort validation are conducted on the SleepEDF and MASS datasets to assess the capability of the HypnoGPT model in enhancing the performance of existing sleep staging models. Additionally, the Physio2018 dataset ($N = 994$), along with the YASA toolbox containing pretrained sleep staging models, are included to blindly (i.e., after the models are finalized and locked) assess the out-of-sample prediction performance of the models.

The HypnoGPT model is further utilized as a local feature extractor within a hierarchical transformer network (HTN) for the diagnosis of sleep disorders (Fig. **S3**). The HTN model is cross-validated on the CAP ($N = 108$) dataset to distinguish normal from abnormal sleep stage sequences and blindly validated on the ISRUC dataset ($N = 86$), the MNC dataset ($N = 407$) and the HANG7 dataset ($N = 84$). To demonstrate its performance on a potentially more challenging task, the diagnosis of Type-1 narcolepsy (vs. other hypersomnia and healthy controls) is also performed on the MNC dataset ($N = 407$) via cross-validation and blindly validated on the HANG7 dataset ($N = 84$). Finally, a visualization of the learned global attention weights of HTN is provided to offer insights into the salient patterns captured by the model.

Enhancing sleep staging with HypnoGPT

The performance of the proposed HypnoGPT model is assessed in terms of accuracy, macro-averaging F1-score (MF1), and Cohen's kappa coefficient (κ) for the sleep staging task on the SleepEDF and MASS datasets. Among these performance metrics, accuracy indicates the proportion of correctly classified sleep stages, while MF1 ensures that performance is balanced across all classes, addressing the impact of class imbalance [45]. Cohen's Kappa (κ) adjusts for chance agreement, providing a more robust assessment of model performance, especially in multi-class classification [46]. Table 1 presents the results of the proposed methods alongside those of contemporary state-of-the-art methodologies, with the referenced methods directly sourced from the original publications. Despite its simple design (Fig. **S4**), TinySleepNet [13] attains competitive performance across both datasets. Moreover, by integrating information from preceding EEG epochs, TinySleepNet-seq outperforms the TinySleepNet-nonseq. This improvement stems from the ability of the LSTM layer to capture the sequential attributes of EEG data, a feature leveraged by most advanced sleep staging models. Improvement is also observed between the multi-view architecture-based XSleepNet models with and without the LSTM sequential module [24], highlighting the importance of capturing sleep stage sequences to enhance sleep staging performance. The integration of HypnoGPT improves the accuracy of TinySleepNet-nonseq by 2.1% and 1.5%, and that of XSleepNet-nonseq by 2.5% and 1.3%, on the SleepEDF and

MASS datasets, respectively. Notably, the performance of the non-sequential models on the SleepEDF dataset approaches that of their sequential counterparts, i.e., TinySleepNet-seq and XSleepNet-seq. This demonstrates the ability of the HypnoGPT model to capture the sequential characteristics of sleep stages, compensating for the limitations of the non-sequential models in encoding the contextual information of EEG signals. Importantly, the staging accuracy of TinySleepNet-seq with HypnoGPT exhibits improvements of 0.5% and 0.6% on the SleepEDF and MASS datasets, respectively. The results of the XSleepNet model from [24] are also presented for comparison. Our implementation of XSleepNet (XSleepNet-reimp) replicates the results reported in the original study. The incorporation of HypnoGPT further enhances the accuracy of XSleepNet, including the original model and our reimplementation, by 0.2% (0.4%) and 0.5% (0.4%) on the SleepEDF and MASS datasets, respectively. These results underscore the effectiveness of the HypnoGPT model in enhancing the performance of state-of-the-art sleep staging models, even those already equipped with sequential modules.

Table 1: Performance of state-of-the-art sleep staging methods and the proposed HypnoGPT-powered models on the SleepEDF and MASS datasets. The best results are highlighted in bold, while the results with the HypnoGPT-powered model are underlined. **Seq**: with or without a sequential module, **HypnoGPT**: with or without HypnoGPT, **ACC**: accuracy (%), **MF1**: macro-averaging F1-score (%), **kappa**: Cohen's kappa coefficient.

Method	Seq	HypnoGPT	SleepEDF			MASS		
			ACC	MF1	kappa	ACC	MF1	kappa
DeepSleepNet[10]	w	w/o	77.8	71.8	0.700	-	-	-
SleepEEGNet[12]	w	w/o	80.0	73.6	0.730	-	-	-
AttnSleepNet[21]	w	w/o	82.9	**78.1**	0.770	-	-	-
SeqSleepNet[15]	w	w/o	82.6	76.4	0.760	84.5	79.8	0.778
IITNet*[25]	w	w/o	-	-	-	86.3	80.5	0.790
TinySleepNet	w/o	w/o	80.5	73.7	0.728	81.7	75.2	0.737
TinySleepNet	w/o	w	82.6	76.5	0.762	83.2	75.9	0.755
TinySleepNet[13]	w	w/o	83.1	**78.1**	0.770	84.2	78.8	0.775
TinySleepNet	w	w	83.6	77.8	0.771	84.8	80.3	0.782
XSleepNet	w/o	w/o	80.3	73.5	0.731	82.1	75.3	0.746
XSleepNet	w/o	w	82.8	76.6	0.763	83.4	76.1	0.768
XSleepNet[24]	w	w/o	84.0	77.9	0.778	85.2	80.6	0.788
XSleepNet-reimp	w	w/o	83.8	77.7	0.776	85.3	80.5	0.789
XSleepNet	w	w	**84.2**	**78.1**	**0.783**	**85.7**	**80.7**	**0.799**

* the results are not directly comparable since they were evaluated on the SS3 subset with 62 healthy subjects in the MASS dataset.

Testing the generalization of the sleep staging models

To evaluate the out-of-sample generalizability of HypnoGPT for sleep staging, we applied the sleep staging models trained on the MASS dataset to the Physio2018 dataset, which contains 994 PSG recordings. Our aim was to assess whether

HypnoGPT could similarly enhance sleep staging performance in an independent dataset, as observed in the cross-validation experiments. The MASS dataset was chosen for training due to its identical EEG channel configurations (C3-A2/C4-A1) to those in the Physio2018 dataset, ensuring consistent input features in the PSG recordings. To confirm the performance improvements were bidirectional, after the generalization assessment of the MASS models is completed, we also reversed the process by applying the sleep staging models trained on the Physio2018 dataset to the MASS dataset. As an additional part of out-of-sample validation, YASA (Yet Another Spindle Algorithm)[47], an open-source sleep analysis toolbox with pretrained sleep staging models, was also applied to stage the sleep EEG data from the SleepEDF and MASS datasets, and HypnoGPT was assessed to determine whether it could improve the performance of this established sleep staging tool.

Fig. 2: Results of three state-of-the-art staging methods with and without HypnoGPT when performing cross-dataset sleep staging on the SleepEDF, MASS, and Physio2018 datasets. The x-axis labels **Source → Target** indicate that the staging model is trained from the **Source** dataset and evaluated on the **Target** dataset. **ACC**: accuracy, **MF1**: macro-averaging F1-score, **kappa**: Cohen's kappa coefficient.

The results, shown in Fig. 2, indicate that HypnoGPT consistently enhances the performance of YASA, TinySleepNet, and XSleepNet across all three datasets. Notably, it improves YASA's accuracy on the SleepEDF and MASS datasets by 3.8% and 1.6%, respectively. Furthermore, integrating HypnoGPT enhances the accuracy of TinySleepNet by 2.9% and 1.6%, and that of XSleepNet by 2.3% and 1.8%, during cross-dataset validation between the Physio2018 and MASS datasets. Consistent

improvements in MF1 and κ are also observed. These findings validate the generalizability and robustness of HypnoGPT, as it reliably improves the out-of-sample prediction performance of existing sleep staging models across diverse datasets.

Visualization of the sleep staging enhancement via HypnoGPT

Fig. 3: Example sleep staging results from the SleepEDF and MASS datasets using both the proposed and baseline methods. The vertical sequence shows hypnograms depicting sleep staging outcomes as determined by sleep specialists (Truth), the non-sequential model (Nonseq), the non-sequential model with HypnoGPT correction (Nonseq + HypnoGPT), the sequential model (Seq), and the sequential model with HypnoGPT correction (Seq + HypnoGPT). The color-shaded areas indicate the erroneous sleep stage predictions (pink-shaded) of the baseline staging models, rectified by the HypnoGPT model (blue-shaded).

To provide insight into the effectiveness of HypnoGPT in enhancing sleep staging, we examined two selected sessions from the SleepEDF and MASS datasets. The sleep stage classification results of these two sessions, as produced by the TinySleepNet and XSleepNet models, both with and without HypnoGPT correction, are presented in Fig. 3. As non-sequential models do not consider contextual information, TinySleepNet-nonseq and XSleepNet-nonseq misclassify REM and WAKE as other stages and exhibit erroneous transitions between REM sleep and WAKE stages, particularly during prolonged REM sleep periods. Incorporating HypnoGPT effectively corrects these misclassifications, resulting in more accurate sleep stage predictions. The sequential models, TinySleepNet-seq and XSleepNet-seq, perform better than their non-sequential counterparts. However, they still struggle with certain sleep stages, such as light sleep, often misclassified as WAKE or REM. HypnoGPT further refines these predictions, correcting the misclassifications and increasing the overall accuracy of sleep stage predictions, as indicated by the color-shaded areas in Fig. 3. The context-aware nature of HypnoGPT corrects the predicted sleep stages produced by sleep staging models, particularly for non-sequential models, resulting in a hypnogram more consistent with the ground truth.

Fig. 4: Example sleep staging results from the SleepEDF and MASS datasets using the YASA toolbox [47]. The vertical sequence shows hypnograms depicting sleep staging outcomes as determined by sleep specialists (Truth), the YASA toolbox (YASA), and the YASA toolbox with HypnoGPT correction (YASA + HypnoGPT). The color-shaded areas indicate the erroneous sleep stage predictions (pink-shaded) of the original staging models, rectified by the HypnoGPT model (blue-shaded).

The results of using the YASA toolbox to stage the sleep EEG data from the SleepEDF and MASS datasets, with and without HypnoGPT correction, are presented in Fig. 4. HypnoGPT similarly corrects the misclassifications of the YASA toolbox, resulting in more accurate sleep stage predictions.

Sleep disorder diagnosis with HypnoGPT

We evaluated the performance of sleep disorder diagnosis models using balanced classification accuracy (BACC), sensitivity, and specificity across the modified CAP and MNC datasets. Table 2 presents the results for two empirical feature-based XGBoost classifiers—Hypnogram [47] and Hypnodensity [27]—as well as a baseline neural network (BaseNet; Fig. **S5**), the proposed hierarchical transformer network (HTN) trained from scratch, and the HTN model incorporating pretrained HypnoGPT parameters. The receiver operating characteristic (ROC) curves of each method across the CAP and MNC datasets are also shown in Fig. 5 to provide a detailed breakdown of the results (Also see Fig. **S6** for the confusion matrix of each method).

On the CAP dataset, in which the task was to distinguish between normal sleep and abnormal sleep (including sleep disorders such as insomnia, disordered breathing, narcolepsy, etc.), the XGBoost classifier trained with hypnogram features achieved a balanced accuracy of 90.91%, with a sensitivity of 95.65% and a specificity of 86.17%. Hypnodensity-based XGBoost results were unavailable due to the absence of hypnodensity data for the CAP dataset. While end-to-end models like BaseNet can learn useful features from hypnograms, they may struggle to capture the sequential attributes of sleep stages if the model architecture is not carefully designed, as evidenced by a balanced accuracy of 84.97%, with a sensitivity of 86.96% and a specificity of 82.98%. The HypnoGPT-based HTN model, however, significantly improved performance in an end-to-end fashion. This highlights the HTN's capacity to grasp both localized sequential sleep transitions and broader contextual patterns in sleep hypnograms, enhancing diagnostic performance. Notably, initializing the HTN with pretrained HypnoGPT parameters yielded the highest performance, achieving a balanced accuracy of 96.27%, with a sensitivity of 98.91% and a specificity of 93.62%. This pretrained HTN demonstrated a remarkable improvement in sensitivity over its non-pretrained counterpart, with an increase of over 10% on the CAP dataset.

Similar trends were observed in the MNC dataset, which involved distinguishing Type-1 narcolepsy (T1N) patients from non-T1N individuals (including other hypersomnia patients and healthy controls), an arguably more challenging task than distinguishing general sleep-disorder patients from health controls. The XGBoost classifier trained on hypnogram and hypnodensity features achieved balanced accuracies of 84.39% and 85.16%, respectively. Although the BaseNet model performed reasonably well in diagnosing T1N patients, achieving a balanced accuracy of 79.69%, it struggled with sensitivity, identifying only 67.07% of T1N subjects. The HTN model trained from scratch produced a balanced accuracy of 85.49%, a sensitivity of 78.05%, and a specificity of 92.92%, matching the performance of the XGBoost classifier trained on hypnodensity features. When fine-tuned with pretrained HypnoGPT parameters, the HTN model further boosted performance, achieving a balanced accuracy of 92.81%, a sensitivity of 91.46%, and a specificity of 94.15%. This improvement underscores

the benefits of the HypnoGPT model's self-supervised pretraining on large-scale sleep stage datasets, such as the SHHS database, which includes 5,793 subjects. Importantly, the pretrained HypnoGPT model demonstrated the potential for fine-tuning on smaller datasets, which is crucial in sleep medicine, where data scarcity often presents a challenge.

Table 2: Performance of the proposed HypnoGPT model on the sleep disorder diagnosis task. All results are reported in terms of balanced accuracy (**BACC**) (%), sensitivity (**SENS**) (%), and specificity (**SPEC**) (%).

Method	CAP			MNC		
	BACC	SENS	SPEC	BACC	SENS	SPEC
Hypnogram [47]	90.91	95.65	86.17	84.39	82.93	85.85
Hypnodensity [27]	-	-	-	85.16	81.71	88.62
BaseNet	84.97	86.96	82.98	79.69	67.07	92.31
No pretraining	89.77	88.04	91.49	85.49	78.05	92.92
Finetuning	**96.27**	**98.91**	**93.62**	**92.81**	**91.46**	**94.15**

Fig. 5: Receiver operating characteristic (ROC) curves of the proposed HypnoGPT-powered models as well as the baseline methods for sleep disorder diagnosis on the CAP, ISRUC, and MNC datasets. The area under the ROC curve (AUC) of each method is reported in the legend.

Testing the generalization of the sleep disorder diagnosis models

We next assess the out-of-sample generalizability of HypnoGPT in diagnosing abnormal sleep by evaluating the prediction performance of the models trained from the CAP dataset on the ISRUC [48], MNC [27], and HANG7 dataset [49]. The ISRUC sleep dataset contains whole-night PSG recordings of obstructive sleep apnea (OSA) patients ($N = 76$) and healthy controls ($N = 10$). As shown in Table 3, on this unseen dataset, the pretrained HTN model achieved a balanced accuracy of 90.00%, with a sensitivity of 100% and a specificity of 80.00% when distinguishing OSA patients from healthy controls. The model also demonstrated strong performance on the MNC dataset, achieving a balanced accuracy of 83.72%, with a sensitivity of 88.00% and a specificity of 79.43% in discriminating healthy controls ($N = 282$) from patients with T1N or other hypersomnia ($N = 125$). On the HANG7 dataset, which contains 51 patients with narcolepsy and 33 healthy controls, the HTN model achieved a balanced accuracy of 84.05%, with a sensitivity of 86.27% and a specificity of 81.82%.

External validation of the HTN model trained on the MNC dataset and tested on the HANG7 dataset, which involves distinguishing T1N patients from other hypersomnia patients and healthy controls, is also presented in Table 4. The HTN model fine-tuned with HypnoGPT parameters achieved a balanced accuracy of 84.18%, with a sensitivity of 92.31% and a specificity of 76.06%, outperforming the compared methods.

The ROC curves of each method across the generalization datasets are shown in Fig. 5. These results significantly outperform the compared methods, demonstrating the robustness and generalizability of the HypnoGPT model in diagnosing sleep disorders.

Table 3: Generalization performance on the ISRUC [48], MNC [27], and HANG7 dataset [49] with model trained from the CAP [50] dataset when classifying abnormal vs normal sleep. All results are reported in terms of balanced accuracy (**BACC**) (%), sensitivity (**SENSI**) (%), and specificity (**SPECI**) (%).

Method	CAP → ISRUC			CAP → MNC			CAP → HANG7		
	BACC	SENSI	SPECI	BACC	SENSI	SPECI	BACC	SENSI	SPECI
Hypnogram [47]	80.39	90.79	70.00	77.72	82.40	73.05	79.59	80.39	78.79
BaseNet	67.11	84.21	50.00	74.92	67.07	**82.77**	72.99	82.35	63.64
No pretraining	76.71	93.42	60.00	79.94	84.00	75.89	76.65	74.51	78.79
Finetuning	**90.00**	**100.00**	**80.00**	**83.72**	**88.00**	79.43	**84.05**	**86.27**	**81.82**

Visualization of the HypnoGPT-powered sleep disorder diagnosis model

To provide insights into the global feature extractor of the HTN model, a visualization of the attention weights from the global feature extractor on the CAP dataset is presented in Fig. 6. Specifically, we select one healthy subject and five subjects

Table 4: Generalization performance on the HANG7 dataset [49] with model trained from the MNC [27] dataset when classifying Type-1 narcolepsy (T1N) vs others. All results are reported in terms of balanced accuracy (**BACC**) (%), sensitivity (**SENSI**) (%), and specificity (**SPECI**) (%).

Method	MNC → HANG7		
	BACC	SENSI	SPECI
Hypnogram [47]	72.32	61.54	**83.10**
Hypnodensity [27]	75.46	69.23	81.69
BaseNet	69.12	69.23	69.01
No pretraining	75.08	76.92	73.24
Finetuning	**84.18**	**92.31**	76.06

with distinct sleep disorders—insomnia, narcolepsy, nocturnal frontal lobe epilepsy (NFLE), periodic leg movements (PLMs), and REM behavior disorder (RBD). By focusing on the attention weights assigned to the CLS token (a special token that outputs a global representation of the entire sequence, detailed in the Methods section) within the final transformer layer, we can observe how each model identifies and prioritizes salient features in the data. The results clearly demonstrate the effectiveness of the global feature extractor in capturing atypical sleep patterns associated with sleep disorders. For instance, in the case of the insomnia subject, characterized by small N3 and REM sleep ratios and direct transitions from REM sleep to wakefulness, the global feature extractor allocates more attention to the segments marked by these transitions (Fig. 6b). Likewise, the global transformer encoder of HTN highlights segments with short wake-to-REM sleep latency or abrupt transitions from wakefulness to REM sleep for the narcolepsy subject (Fig. 6c). Furthermore, the self-attention module identifies segments featuring abnormal stage transitions, short N3 and REM sleep durations, direct shifts from REM sleep to wakefulness, and frequent toggling between deep sleep (N3 and REM sleep) and wakefulness (Figs. 6d-f). Conversely, for subjects without pathologies, the attention weights are more evenly dispersed across the hypnogram segments (Fig. 6a). The above abnormal patterns in sleep stage sequences are indicative of sleep disorders and may serve as potential biomarkers for sleep disorder diagnosis.

We also show the attention weights obtained by the global feature extractor of the HTN model on the MNC dataset in Fig. 7. The subjects selected included a healthy control, a hypersomnia patient, and a T1N patient. The attention weights are more evenly distributed across the hypnogram segments for the healthy control, while for the narcolepsy patient, there is heightened attention to segments featuring short wake-to-REM latency or direct transitions from wakefulness to REM sleep. Since we are classifying T1N patients from other hypersomnia patients and healthy controls, the attention weights are more focused on segments similar to those of the narcolepsy patient. These segments include short wake-to-REM latency, direct transitions from wakefulness to REM sleep, and long REM sleep duration. The self-attention module

Fig. 6: Visualization of the learned attention weights of the global transformer encoder on the CAP dataset for sleep disorder diagnosis (abnormal vs. normal). (a) The attention weights are more evenly distributed among the segments of the sleep hypnogram for a healthy subject. (b) There is a small N3 and REM sleep ratio and direct transitions from REM sleep to wakefulness for the insomnia subject. (c) Segments with short REM sleep latency or direct transitions into REM sleep from wakefulness are highlighted by the global transformer encoder of the HTN for the narcolepsy subject. (d-f) Segments with abnormal stage transitions, such as short N3 and REM sleep duration, a direct transition from REM sleep to wakefulness, and frequent switches between deep sleep, i.e., N3 and REM sleep, and wakefulness, are identified by the self-attention module for the subjects with NFLE, PLMs, and RBD, respectively. The color-shaded areas highlight the segments with abnormal sleep patterns.

of the HTN model effectively identifies the most discriminative sleep patterns, thereby enhancing the classification performance for T1N.

Discussion

This study introduces HypnoGPT, a novel hypnogram language model adapted from the GPT architecture and trained in a self-supervised manner on a comprehensive sleep stage dataset. This model offers several key advantages. First, it consistently improves the performance of existing sleep staging systems, acting as a powerful enhancement layer analogous to a language model in speech recognition. Second, HypnoGPT effectively captures sleep stage transition dynamics, extracting both sequential and statistical features from sleep stage sequences. This capability allows for its integration as a local feature extractor within a hierarchical transformer network, where it can be fine-tuned to enhance end-to-end sleep disorder diagnosis significantly. Finally, HypnoGPT contributes to the identification of potential biomarkers within sleep stage sequences, which may provide mechanistic insight into sleep disorders. These findings underscore the potential of HypnoGPT to advance both sleep staging and sleep disorder diagnosis.

Fig. 7: Visualization of the learned attention weights of the global transformer encoder on the MNC dataset for sleep disorder diagnosis (Type-1 narcolepsy vs. (other hypersomnia + healthy control)). (a) The attention weights are more evenly distributed among the segments of the sleep hypnogram for a healthy subject. (b) The attention weights for a hypersomnia subject, are similar to those for a healthy subject. (c) Segments with abnormal stage transitions, such as short REM sleep latency, and long REM sleep duration, are identified by the self-attention module for the narcolepsy subject. The color-shaded areas highlight the segments with the most discriminative sleep patterns.

The integration of HypnoGPT consistently enhances sleep staging performance, although the degree of improvement varies across models and datasets. Notably, models lacking memory mechanisms, which fail to utilize contextual information from physiological signals and sleep stages, exhibit more substantial improvement. Conversely, models with sequential components like LSTMs show more moderate gains, likely due to their inherent ability to capture temporal dependencies in sleep-related data. The benefits of HypnoGPT are particularly pronounced in blinded evaluations on independent datasets, where data heterogeneity often hinders the generalizability of sleep staging models. By effectively capturing the intrinsic sequential patterns of sleep stages, HypnoGPT enhances model generalizability across diverse datasets. Furthermore, we anticipate even greater performance improvements as the volume of training data for HypnoGPT increases.

In contrast to traditional sleep disorder diagnosis approaches that rely on hand-crafted features derived from hypnogram analysis (e.g., stage latencies, durations, and transitions), our proposed hierarchical transformer network (HTN) directly models and categorizes sleep stage sequences in an end-to-end fashion. This hierarchical architecture allows the model to capture both local and global contextual information within sleep hypnograms, enabling more accurate classification of sleep stage sequences, especially those with varying lengths, compared to the baseline model. By

initializing the HTN's local feature extractor with pretrained HypnoGPT parameters and subsequently fine-tuning it, we can extract highly informative features for sleep disorder diagnosis. Notably, the HTN effectively addresses the challenge of subject-level sleep disorder diagnosis in weakly supervised learning scenarios, where only session-level labels are available and sleep disorder symptoms may not be consistently present throughout the entire sleep session [37]. Leveraging the self-attention mechanism in its global transformer module, the HTN achieves accurate subject-level classification and identifies potential biomarkers indicative of specific sleep disorders. These include, but are not limited to: (1) reduced REM sleep ratio and frequent REM sleep-to-wake transitions, suggesting insomnia; (2) shortened REM sleep latency and direct transitions from wakefulness to REM sleep, characteristic of narcolepsy; and (3) brief REM sleep duration and frequent shifts between deep sleep (N3 and REM) and wakefulness, signaling other sleep abnormalities. These insights hold promise for developing novel diagnostic methodologies. Moreover, the HTN's adaptability allows for its potential application to other sleep-related brain disorders, such as depression, anxiety, dementia, and Parkinson's disease [1, 2], e.g., by replacing sleep disorder labels with corresponding condition labels. This flexibility is particularly valuable given the frequent comorbidity of sleep disorders with other neurological or psychiatric conditions. Additionally, information in sleep stage sequences or hypnograms is much simpler than that in PSG data, which is often noisy and complex. Diagnosis from sleep stage sequences has the advantage of alleviating inter-subject or inter-cohort heterogeneity. However, PSG data may also be fused with the sequential features of sleep stages to further improve the performance of sleep disorder diagnosis.

On the CAP dataset, the pretrained HTN model effectively identifies nearly all abnormal subjects, with only 1.09% of abnormal subjects being erroneously classified as normal. This high sensitivity is particularly crucial in sleep disorder diagnosis, where false positives (misclassifying normal as abnormal) are generally preferable to false negatives, as they lead to further medical investigation, while undetected abnormalities could have serious consequences. Moreover, previous literature indicates that sensitivity and specificity for T1N are 75-90% and 90-98%, respectively [27, 51–53]. The performance achieved by the pretrained HTN model on the MNC dataset is comparable to or exceeds these reported values. These results suggest that analyzing a single-night PSG can be as effective as the PSG-MSLT gold standard, which involves a 24-hour procedure. Furthermore, in their study, Stephansen et al. [27] reported a sensitivity of 91% and specificity of 96% on the test data from the MNC dataset. On the replication set, the sensitivity and specificity were 93% and 91%, respectively. However, Stephansen et al.'s study utilized the complete MNC dataset from nine cohorts, whereas this study evaluated only a subset of the MNC dataset (SSC, DHC, and CNC) due to missing sleep staging labels for the other six cohorts.

The implementation of HypnoGPT in wearable devices can open exciting possibilities for at-home, real-time sleep monitoring. Wearable devices powered by HypnoGPT could provide immediate feedback on sleep quality, identify potential sleep disturbances as they occur, and offer personalized advice for improving sleep. Such real-time monitoring could be invaluable for individuals with chronic sleep disorders, allowing

for timely interventions and adjustments to treatment plans. Furthermore, continuous sleep monitoring could facilitate early detection of sleep problems, potentially preventing them from escalating into more serious health issues.

While our experiments demonstrate the effectiveness of HypnoGPT, it is important to acknowledge certain limitations. Computational constraints restricted extensive exploration of model configurations and hyperparameters for both HypnoGPT and the HTN. Further investigation of diverse model architectures and parameter optimization strategies may yield additional performance gains. Additionally, the SHHS dataset used for pretraining HypnoGPT is relatively small compared to the massive text corpora used to train traditional GPT models. Expanding the pretraining dataset could further enhance model performance. Future research should also explore fine-grained sleep disorder classification by leveraging larger and more diverse datasets to gain deeper insights into specific sleep stage patterns and transitions associated with particular disorders. Furthermore, while hypnograms provide valuable information on sleep macrostructure, they have limited ability to capture microstructural events like sleep spindles and K-complexes [54]. Integrating additional data modalities, such as high-resolution EEG or other physiological signals, may enhance the accuracy and granularity of sleep disorder diagnosis. Finally, further validation of HypnoGPT across a broader range of sleep datasets is essential to establish its generalizability and robustness before it could be translated for use in clinical practice.

In summary, this study introduced HypnoGPT, a novel hypnogram language model based on the GPT architecture, designed to capture the sequential dependencies inherent in sleep stage transitions. By pretraining HypnoGPT on a large sleep dataset with stage annotations, we adopted a strategy analogous to the successful pipeline in speech recognition, demonstrating its ability to enhance automatic sleep staging performance. Furthermore, we developed a hierarchical transformer network (HTN) that incorporates HypnoGPT as a local feature extractor, enabling end-to-end sleep disorder diagnosis directly from sleep hypnograms. Extensive evaluation across multiple publicly available sleep datasets as well as fully blinded replications on independent datasets demonstrated that HypnoGPT significantly improves sleep staging accuracy and exhibits promising efficacy in classifying abnormal sleep patterns. This novel approach for modeling sleep architecture opens new avenues for sleep data analysis, and significantly advancing automated diagnosis and personalized treatment of sleep disorders.

Methods

Datasets

This study utilizes three distinct types of datasets: sleep datasets for HypnoGPT pre-training, sleep staging, and sleep disorder diagnosis. A total of six publicly accessible sleep datasets are employed in the experiments. Table 5 provides a comprehensive summary of these datasets, and further details are provided below.

Table 5: Overview of the involved sleep datasets. **BMI** = body mass index, **AHI** = apnea-hypopnea index.

Dataset	Subjects / Sessions	Recording Duration	Age (AVG±STD)	Sex (% Male)	BMI (AVG±STD)	AHI (AVG±STD)	Health Conditions
SHHS [55, 56]	5793 / 5793	Overnight	63.1 ± 11.2	47.6	28.2 ± 5.1	17.9 ± 16.1	Sleep-disordered breathing, heart diseases, and others
SleepEDF [57, 58]	78 / 153	Around 9h	59 ± 22.1	46.4	-	-	Healthy subjects
MASS [59]	200 / 200	Overnight	40.6 ± 19.4	48.5	-	≤ 20	Healthy subjects
Physio2018 [58, 60]	994 / 994	7.7h	55 ± 14.3	67.0	33 ± 7.8	19 ± 14.6	Sleep disorders, healthy subjects
CAP [50, 58]	108 / 108	8–10h	45.2 ± 19.7	61.1	-	-	Sleep disorders (n=92), healthy subjects (n=16)
ISRUC [48]	86 / 86	Overnight	49.7 ± 15.7	59.4	-	-	Sleep apnea (n=76), healthy subjects (n=10)
MNC-CNC [27, 56]	77 / 77	Overnight	28.5 ± 16.9	51.3	23.2 ± 11.5	5.34 ± 1.51	Type-1 narcolepsy (n=54), healthy subjects (n=23)
MNC-DHC [27, 56]	79 / 79	Overnight	33.4 ± 14.8	50.0	24.8 ± 4.9	-	Type-1 narcolepsy (n=21), hypersomnia (n=38), healthy subjects (n=20)
MNC-SSC [27, 56]	251 / 251	Overnight	45.4 ± 13.8	59.4	23.9 ± 6.5	13.7 ± 0.7	Type-1 narcolepsy (n=7), hypersomnia (n=5), healthy subjects (n=239)
HANG7 [49]	84 / 84	8h	24.5 ± 9.6	47.6	-	-	Type-1 narcolepsy (n=13), other narcolepsy (n=38), healthy subjects (n=33)

Datasets for HypnoGPT Pretraining

Training a transformer-based language model typically requires an extensive text corpus, often encompassing millions or even billions of web pages or documents. However, a sleep dataset of comparable scale, complete with sleep stage annotations, is not available. Fortunately, the increasing advancements in sleep medicine research, coupled with the research community's open data policy, have produced several publicly accessible sleep datasets with sleep stage annotations. The Sleep Heart Health Study (SHHS) database, a multi-center cohort study examining the cardiovascular and other consequences of sleep-disordered breathing [55, 56], is a noteworthy example. This database comprises two rounds of PSG records: Visit 1 (SHHS-1) and Visit 2 (SHHS-2). In this work, we use the SHHS-1 cohort, which encompasses 5,793 subjects aged

between 39 and 90 years, to train the HypnoGPT model. Notably, to ensure alignment with the AASM scoring standard [3], we merge the N3 and N4 stages into the N3 stage while discarding the MOVEMENT and UNKNOWN epochs, as the SHHS-1 database was manually scored following the R&K guidelines [4].

Datasets for Sleep Staging

The proposed HypnoGPT model's performance on sleep staging tasks is evaluated with two widely used sleep datasets, namely, the Sleep-EDF and the Montreal Archive of Sleep Studies (MASS). The Physio2018 dataset serves as a benchmark to evaluate the generalization performance of HypnoGPT in enhancing sleep staging. Table 6 provides a detailed summary of these datasets.

Table 6: Number of subjects, EEG channels, and sleep stage distribution of the sleep staging datasets

Datasets	Subjects	EEG channel	W	N1	N2	N3	REM	Total
SleepEDF	78	Fpz-Cz	69824	21522	69132	13039	25835	199352
MASS	200	C4-A1/C3-A2	31184	19359	107930	30383	40184	229040
Physio2018	994	C3-A2	157945	136978	377870	102592	116877	892262

SleepEDF Dataset: We utilize the 2018 version of the SleepEDF Expanded dataset [57, 58]. This collection comprises data from 78 healthy Caucasian subjects aged 25 to 101 years. Each subject contributed two consecutive day-night PSG recordings, except for subjects 13, 36, and 52, where one recording was lost due to device failure. Consequently, the dataset contains 153 overnight recordings. Sleep experts manually scored the epochs based on the R&K standard [4], assigning each 30-second PSG epoch to one of eight categories: {W, N1, N2, N3, N4, REM, MOVEMENT, UNKNOWN}. To align with convention, the N3 and N4 stages were merged into the N3 stage, while the MOVEMENT and UNKNOWN epochs were excluded. Notably, the SleepEDF-20 dataset was not assessed because it is a subset of this particular version of SleepEDF.

MASS Dataset: Derived from different hospital-based sleep laboratories, the MASS database comprises whole-night recordings from 200 subjects (97 males and 103 females) aged 18 to 76 years [59]. The annotation process involved sleep experts adhering to either the AASM standard [3] (for the SS1 and SS3 subsets) or the R&K standard [4] (for the SS2, SS4, and SS5 subsets). In alignment with the previously mentioned datasets, we harmonized the R&K annotations with the five sleep stages {W, N1, N2, N3, REM} according to the AASM standard. Epochs initially spanning 20 seconds were extended to 30 seconds by incorporating the 5-second segments before and after them.

Physio2018: The PhysioNet 2018 Challenge dataset, also known as the Physio2018 dataset, comprises 1,985 polysomnographic recordings provided by the Computational Clinical Neurophysiology Laboratory (CCNL) and the Clinical Data

Animation Center (CDAC) at Massachusetts General Hospital (MGH). This dataset was used in the 2018 PhysioNet Challenge [58, 60] to detect sleep arousals. We used the training set for our experiments, which includes 944 subjects aged 18 to 90. Sleep experts manually scored the recordings according to the American Academy of Sleep Medicine (AASM) guidelines [3], annotating five sleep stages: W, N1, N2, N3, and REM. This dataset is employed to blindly validate the sleep staging model derived from the MASS dataset.

Datasets for Sleep Disorder Diagnosis

Two sleep-disorder-related datasets were identified for the sleep disorder diagnosis analysis, including the CAP Sleep Database and the Mignot Nature Communications (MNC) dataset, which offer both sleep stage annotations and sleep disorder labels.

CAP Dataset: The CAP Sleep Database is a collection of 108 polysomnographic recordings contributed by the Sleep Disorders Center of the Ospedale Maggiore of Parma, Italy [50, 58]. It contains data from seven groups of patients with distinct sleep disorders, as well as a healthy control group without any medical, neurological, or psychiatric conditions. The details of these groups are summarized in Table 7. Well-trained neurologists who are sleep experts manually scored the sleep recordings based on the R&K rules, categorizing the epochs into sleep stages 1-4, wake, REM sleep, and movement artifacts. To adhere to the AASM standard, we harmonized the R&K annotations, obtaining five sleep stages: {W, N1, N2, N3, REM}. Notably, the CAP Sleep Database has been widely used in numerous studies focusing on sleep disorder diagnosis.

Table 7: Sleep disorder groups in the CAP Sleep Database.

Sleep disorder	No. of subjects
Bruxism (BRUX)	2
Sleep-disordered breathing (SBD)	4
Insomnia (INS)	9
Narcolepsy (NARCO)	5
Nocturnal frontal lobe epilepsy (NFLE)	40
Periodic leg movements (PLMs)	10
REM behavior disorder (RBD)	22
No pathology (N)	16

Note that the CAP Sleep Database is inherently imbalanced. Several groups contain an extremely limited number of subjects. For instance, the BRUX and SBD groups consisted of only 2 and 3 subjects, respectively. To facilitate subject-level diagnoses, we conducted binary classification experiments on the CAP Sleep Database, specifically distinguishing abnormal from normal cases. Furthermore, after incorporating the first-session data of 78 subjects (excluding subjects 36 and 52, who had only one session available) from the SleepEDF Expanded database into the normal group, the comprehensive dataset included 186 subjects, 94 of whom were labeled as normal and 92 of whom were labeled as abnormal.

ISRUC Dataset: The ISRUC-Sleep dataset [48] contains full-night PSG recordings, each approximately eight hours in duration, collected at the Sleep Medicine Centre of Coimbra University Hospital (CHUC) between 2009 and 2013. Data were acquired non-invasively using a SomnoStar Pro multi-channel system, with sensors placed according to the international 10–20 standard. The dataset includes recordings from both healthy adults and subjects with sleep disorders under medication, divided into three groups: 1) 100 subjects with one session each; 2) 8 subjects with two sessions for longitudinal studies; 3) 10 healthy subjects with one session, used for comparison with sleep disorder patients. Among the dataset, 76 obstructive sleep apnea (OSA) patients and 10 healthy controls are included to blindly validate the sleep disorder diagnosis model derived from the CAP dataset.

MNC Dataset: The Mignot Nature Communications (MNC) dataset comprises raw polysomnography data collected from an automated sleep staging project utilizing neural networks [27, 56]. It encompasses data from ten distinct cohorts recorded at twelve sleep centers across three continents: the patient-based Stanford Sleep Cohort (SSC), the population-based Wisconsin Sleep Cohort (WSC), the patient-based Inter-scorer Reliability Cohort (IS-RC), the Jazz Clinical Trial Sample (JCTS), the patient-based Korean Hypersomnia Cohort (KHC), the patient-based Austrian Hypersomnia Cohort (AHC), the patient-based Italian Hypersomnia Cohort (IHC), the patient-based Danish Hypersomnia Cohort (DHC), the patient-based French Hypersomnia Cohort (FHC), and the patient-based Chinese Narcolepsy Cohort (CNC). The study received approval from institutional review boards, and informed consent was obtained from all participants. Trained sleep-scoring technicians manually annotated all sleep studies according to the AASM Scoring Manual [3]. Additionally, the subjects were divided into the Type-1 narcolepsy (T1N), other hypersomnia (OHS), or non-narcolepsy control (NNC) group based on multiple sleep latency test (MSLT) results, cataplexy symptoms, and human leukocyte antigen (HLA) results (if available). Further information about the MNC dataset can be found in [27].

However, as diagnostic results were only available for the SSC, DHC, and CNC cohorts, we exclusively utilized these three cohorts for the sleep disorder diagnosis task. The dataset compiled from these cohorts encompassed 407 subjects, among whom 82 were in the T1N group, 43 were in the OHS group, and 282 were in the NNC group (see Table 8). To facilitate comparison with previous research, we adhered to the methodology outlined in [27] and conducted binary classification experiments on the MNC dataset to discriminate T1N subjects from all other subjects, i.e., OHS and NNC subjects. This dataset is also employed to blindly assess the generalizability of the sleep disorder diagnosis model derived from the CAP dataset.

HANG7 Dataset: In the HANG7 dataset [49], 84 participants aged 11 to 57 years (mean age: 24.5 ± 9.6), including 44 females and 40 males, were recruited to collect polysomnography recordings at the Affiliated Mental Health Center & Hangzhou Seventh People's Hospital, Zhejiang University School of Medicine. The study was conducted at Zhejiang University with Institutional Review Board approval, and written consent was obtained from all participants or their caregivers. PSG recordings were collected following the AASM sleep standards [3] and manually scored by experienced sleep technicians. Each participant's PSG recording covered one full night, from

Table 8: Sleep disorder groups in the MNC dataset.

Sleep disorder	No. of subjects			
	CNC	DHC	SSC	Total
Type-1 narcolepsy (T1N)	54	21	7	82
Other hypersomnia (OHS)	0	38	5	43
Non-narcolepsy control (NNC)	23	20	239	282
Total	77	79	251	407

approximately 21:00 to 5:00 the next morning, totaling about 8 hours. Of the 84 participants, 13 were diagnosed with Type-1 narcolepsy (T1N), 38 were other narcolepsy, and 33 were healthy controls. The dataset was used to blindly validate the generalizability of the sleep disorder diagnosis models derived from the CAP (abnormal vs. normal) and MNC (T1N vs. others) datasets.

Problem Formulation

Sleep Staging as Speech Recognition

A general speech recognition system consists of an acoustic model and a language model. The acoustic model $\mathcal{M}_1$ predicts the most likely word sequence given speech audio features X via

$$P(Y; \mathcal{M}_1) = P(Y|X; \mathcal{M}_1), \tag{1}$$

while the language model $\mathcal{M}_2$ is built based on a large-scale text corpus to capture the sequential characteristics of the word sequence via

$$P(Y; \mathcal{M}_2) = P(y_1, y_2, \cdots, y_T) = \prod_{t=1}^{T} P(y_t|y_1, y_2, \cdots, y_{t-1}). \tag{2}$$

The trained language model is then used to rectify the word sequence predicted by the acoustic model to improve the speech recognition performance as follows [61–63]:

$$\begin{aligned} Y^{\star} &= \arg\max_{Y} P(Y; \mathcal{M}_1, \mathcal{M}_2) \\ &= \arg\max_{Y} P(Y|X; \mathcal{M}_1)P(Y; \mathcal{M}_2). \end{aligned} \tag{3}$$

In the automated sleep staging process, features are extracted from a sleep data epoch, and a sleep staging model is then applied to predict the most likely sleep stage for that epoch. The model, whether it is a traditional machine learning or deep learning model, is similar to the acoustic model in a speech recognition system. It is designed and trained on a large-scale sleep dataset to achieve satisfactory prediction accuracy on unseen sleep epochs. However, due to various factors such as architectural limitations, training inadequacies, and data scarcity, imperfections in the PSG-based sleep staging model may occur, leading to inaccurate predictions of sleep stages. The sleep staging accuracy of human experts is approximately 82%, which closely aligns with that achieved by machine learning-based automatic staging systems [27]. Given

the analogous nature of text and sleep stage sequences, emulating the speech recognition system paradigm may improve sleep staging performance. This involves training a hypnogram language model that can capture the inherent sequential characteristics of sleep stages to assume a role akin to that of a natural language model (see Fig. **S1**).

Sleep Disorder Diagnosis as Text Classification

It is believed that sleep architecture, i.e., the distribution of sleep stages, is strongly related to the quality of sleep. Certain sleep disorders exhibit disrupted sleep architecture and atypical sleep stage transitions. Examples include shortened deep sleep stages in cases of insomnia, and short REM sleep latency or immediate transitions from wakefulness to REM sleep in narcolepsy. An overnight sleep stage sequence has the form $\{W, \cdots, N1, \cdots, N2, \cdots, N3, \cdots, REM, \cdots\}$. Such sequences are plotted as hypnograms in Fig. 1 (top-left). They are akin to concise news pieces or textual documents with a vocabulary of only five words. In turn, the sleep stage sequence encodes the sequential attributes and transitional patterns characterizing the progression between sleep stages. The integration of a sequential model enables these characteristics to be identified and described.

Hence, a viable approach is to treat sleep disorder diagnosis as a long text classification task. Here, the trained hypnogram language model is harnessed to extract features from the sleep stage sequences (hypnograms), enabling the subsequent classification of these sequences as associated with a sleep disorder or not. This is an innovative method for sleep disorder diagnosis using only the sleep stages obtained from either human experts or automatic sleep staging models.

The HypnoGPT model

Recently, the success of transformer-based language models (LMs), including bidirectional encoder representations from transformers (BERT) and generative pretrained transformers (GPT), has been noted across various natural language processing (NLP) tasks, such as machine translation, question-answering, and text generation [43, 44, 64]. BERT, which functions as a bidirectional LM, is trained to predict masked words based on neighboring words and to perform next-sentence prediction. Conversely, GPT operates as a decoder-only transformer LM, autoregressively predicting the next character or word based on preceding ones. Both models undergo self-supervised training on extensive text corpora. The success of ChatGPT has illustrated its proficient ability to capture the inherent sequential attributes of natural language. This ability has been extensively utilized to improve performance in speech recognition and diverse NLP tasks, such as text classification.

Transformers consist of multiple transformer blocks, typically including a multi-head self-attention layer, a feed-forward layer, and residual and normalization layers [65]. GPT employs causal attention in its self-attention layer to ensure exclusive attention to preceding words. This concept has been applied in sequential sleep staging models that rely on prior sleep epochs for current sleep stage predictions. It has proven to be especially significant in online sleep staging systems, where only preceding epochs are accessible during the current prediction task. Hence, GPT is selected to

capture the sequential traits of sleep stages. The HypnoGPT model adopts the architecture of the GPT-2 language model developed by OpenAI [43, 44]. As illustrated in Fig. **S2**, the main part of the model is composed of a series of n transformer decoder blocks, marked by the masked multi-head self-attention layers. Token embedding and position embedding layers are employed to map the sleep stage tokens into a vector space and to infuse positional information into each token's sequence placement, respectively. The final transformer block's output is input to a linear layer to obtain the probability distribution of the next sleep stage.

The model undergoes self-supervised training through the autoregressive forecast of the most likely sleep stage based on preceding sleep stages. For each subject or sleep session, the overnight sleep stage annotations are structured as a long sequence $\mathcal{U} = \{u_1, ..., u_N\}$, where $u_i \in \{0, 1, 2, 3, 4\}$ represents the five sleep stages $\{\mathrm{W}, \mathrm{N1}, \mathrm{N2}, \mathrm{N3}, \mathrm{REM}\}$ as integers ranging from 0 to 4. Training samples are derived from the sequence using a sliding window of dimensions K, passing over the sequence with a stride of 1, where K signifies the sample sequence length. Consequently, the overnight stage sequence yields $N - K + 1$ overlapping instances. The $(i-1)$th instance of the K sleep stages, denoted as $\mathbf{U}_{i-1} = \{u_{i-K}, ..., u_{i-1}\}$, constitutes the input and is fed into the model for predicting the target; the target is the ith instance $\mathbf{U}_i = \{u_{i-K+1}, ..., u_i\}$:

$$h_0 = \mathbf{U}_{i-1}\mathbf{W}_e + \mathbf{W}_p \tag{4}$$

$$h_l = \text{transformer\_block}(h_{l-1}), \ \forall l \in [1, L] \tag{5}$$

$$P(\mathbf{U}_i) = \text{softmax}(h_n \mathbf{W}_s^T) \tag{6}$$

where L is the number of transformer layers, $\mathbf{W}_e$ is the token embedding matrix, $\mathbf{W}_p$ is the position embedding matrix, and $\mathbf{W}_s$ is the weight of the classification head. The model is trained with the objective of minimizing the cross-entropy loss, thereby reducing the disparity between the predicted sleep stage and the actual ground truth:

$$\mathcal{L}(\mathcal{U}) = -\sum_{i=1} \log P(\mathbf{U}_i | \mathbf{U}_{i-1}; \Theta), \tag{7}$$

where Θ is the parameter of the GPT sequential model.

Sleep Staging with HypnoGPT

Automatic sleep staging is an active research topic within the realm of sleep medicine; it aims to automate the prediction of sleep stages for individual sleep PSG data epochs, typically spanning 30 seconds. Several excellent deep learning models have been proposed for this purpose. Most of them share a common architecture, comprising a CNN to extract intra-epoch features and an RNN to incorporate the contextual information in adjacent PSG data epochs[10, 12–15, 24]. Among cutting-edge sleep staging models, XSleepNet[24] employs two network streams to learn from multi-view inputs (e.g., both raw signals and time-frequency images) for sleep staging. By adapting the contributions of the two views on time to perform joint feature learning during training, XSleepNet outperforms the single-view baselines and multi-view baselines with a

simple fusion strategy. However, while contextual information within PSG signals is incorporated into the above deep learning models, they neglect the inherent sequential traits and transition patterns within sleep stages.

To use the trained HypnoGPT model to improve sleep staging performance, we treat the sleep staging task as a speech recognition task and follow the pipeline in Fig. **S1**. The sleep staging model (SSM) is used to predict the most likely sleep stage given a PSG data epoch or preceding epochs, while the HypnoGPT model is used to rectify the predicted sleep stage given past stages. That is, the output logits of the SSM $P_{\text{SSM}}(y)$ and those of the hypnogram language model (HLM) $P_{\text{HLM}}(y)$ are weighted by a factor α to obtain the final sleep stage prediction:

$$P(y) = \alpha P_{\text{SSM}}(y|\mathbf{x}) + (1 - \alpha)P_{\text{HLM}}(y|\mathbf{y}_-), \tag{8}$$

where $\mathbf{x}$ is the set of input data epochs, including the current and preceding epochs depending on whether a memory staging model is used, and $\mathbf{y}_-$ is the set of preceding sleep stages (context). Notably, the hyperparameter α governs the relative influences of these two models, ultimately steering the sleep stage prediction toward the highest probability outcome.

Sleep Disorder Diagnosis with HypnoGPT

Sleep disorder diagnosis involves discerning the presence and specific type of sleep disorder in an individual. This task is typically conducted either by sleep specialists or by ML models that leverage PSG data for automated assessment. ML-based approaches often include PSG data feature extraction, followed by the classification of sleep disorders. However, the high dimensionality of PSG data, coupled with a lack of labeled instances, makes it challenging to train an ML model with robust generalizability. The situation is even worse in the case of deep learning models, which commonly demand an extensive volume of labeled data to achieve optimal model performance.

Pretrained language models, such as GPTs trained on expansive text corpora, can capture the intrinsic sequential characteristics of natural language. These pretrained language models can function as feature extractors, processing text sequences to subsequently enable classification. Notably, these pretrained models can be further fine-tuned using limited-scale datasets, significantly enhancing the classification performance. This strategy, referred to as transfer learning, effectively addresses the challenge of limited sample size, and it has a proven track record of success across numerous NLP applications.

Drawing inspiration from this pretraining and fine-tuning paradigm, we leverage the pretrained HypnoGPT model as a feature extractor. We replace the subsequent stage prediction layer with a classifier and perform comprehensive fine-tuning to facilitate sleep disorder classification. Nevertheless, a challenge arises for the HypnoGPT model in handling long sequences: the sequence length limitation. A whole-night (8-hour) sleep stage sequence comprises 960 time steps, significantly exceeding the sequence length restriction of the HypnoGPT model. We address this by segmenting the overnight sequence into shorter sections. Initially, the HypnoGPT model is employed to extract local context features from these short sleep stage segments.

Subsequently, another sequential model (a transformer encoder) is used to capture the global contextual features from the HypnoGPT output [65]. Finally, the resulting global context features are fed into a classification head to predict sleep disorder labels. The configuration of the hierarchical transformer network (HTN) is depicted in Fig. **S3**. This architecture, which is tailored for lengthy sequence classification, is borrowed from the hierarchical attention network (HAN) and hierarchical transformers utilized for long text classification [66, 67].

Additionally, to facilitate mini-batch training, we pad the short sleep stage sequences within a batch to achieve a uniform length. Subsequently, a mask matrix is employed to exclude the padded values during the computation of attention weights and the loss calculation. The loss function involves cross-entropy loss, which compares the predicted sleep disorder labels with the ground truth:

$$\mathcal{U} = \{\mathbf{U}_i\}, \ \forall i \in [1, N] \tag{9}$$

$$\mathbf{z}_i = \text{HypnoGPT}(\mathbf{U}_i) \tag{10}$$

$$\mathbf{V} = \text{transformer\_encoder}(\mathbf{Z}) \tag{11}$$

$$P(\mathcal{U}) = \text{softmax}(\mathbf{W}_c \mathbf{v}_0 + b_c) \tag{12}$$

$$\mathcal{L}(\mathcal{U}) = -\sum_{i=1} \log P(\mathcal{U}; \Phi), \tag{13}$$

where $\mathbf{U}_i$ is the ith segment, and N represents the number of segments within a sleep stage sequence. $\mathbf{z}_i$ denotes the ith local feature vector generated by HypnoGPT. Notably, $\mathbf{Z} = \{\mathbf{z}_0, \cdots, \mathbf{z}_N\}$ and $\mathbf{V} = \{\mathbf{v}_0, \cdots, \mathbf{v}_N\}$ denote the input and output sequences of the transformer encoder, respectively. Here, $\mathbf{z}_0$ corresponds to the CLS token, while $\mathbf{v}_0$ represents the global feature vector at the CLS token's output position. The CLS token in transformers is a special token added at the beginning of the input sequence, and its final output serves as a global representation of the entire sequence for tasks like classification [64, 68]. The parameters of the classification head are denoted as $\mathbf{W}_c$ and b_c, and Φ includes the trainable parameters of the entire model.

Baseline Models

To evaluate the efficacy of the HypnoGPT model, we utilized two baseline models for sleep staging tasks: TinySleepNet [13] and XSleepNet [24]. TinySleepNet is a lightweight architecture integrating a convolutional neural network (CNN) and long short-term memory (LSTM) components. It extracts local EEG signal features via the CNN, while the LSTM captures sequential dependencies between sleep epochs (refer to Fig. **S4**). Despite its simplicity, TinySleepNet exhibits competitive performance across various publicly available sleep datasets. XSleepNet, on the other hand, is a state-of-the-art sleep staging model that harnesses multi-view inputs, including raw signals and time-frequency images, to increase sleep staging accuracy. The model comprises two network streams, each learning from a distinct view, with a fusion strategy to integrate the contributions of the two views. Additionally, a bidirectional LSTM is employed to capture temporal dependencies within sleep stage sequences. XSleepNet has demonstrated superior performance over single-view and multi-view

baselines by employing a simple fusion strategy. Further details regarding the XSleep-Net model can be found in [24]. However, to eliminate the impact of numerical precision and device-specific factors, we reimplemented the XSleepNet models using the PyTorch framework. Experiments were conducted with the reimplemented version of XSleepNet, referred to as XSleepNet-reimp.

In the context of sleep disorder diagnosis based on stage sequences, two types of models were employed: empirical feature-based XGBoost classifiers and end-to-end deep neural networks. One XGBoost classifier was trained on statistical features extracted from the sleep stage sequences, including the percentage of each sleep stage, stage latency, stage duration, sleep efficiency, and transition probabilities between stages (as detailed in [47]). Another XGBoost classifier was trained on hypnodensity features, which represent the classification probabilities for each sleep stage, introduced by [27]. On the other hand, deep neural network models were trained directly on the raw sleep stage sequences. As a baseline end-to-end model (BaseNet), we employed the widely recognized fastText model for feasibility validation [69]. The fastText model consists of an embedding layer followed by averaging operations and a hidden layer (Fig. **S5**). While extremely simple, it often matches the accuracy of deep learning classifiers and is significantly faster in both training and evaluation.

Experimental Setup

Settings for HypnoGPT pretraining

Importantly, the sleep stage vocabulary consists of only five "words", namely {W, N1, N2, N3, REM}, so it is significantly smaller than the vocabulary of a typical language model. Consequently, the size of HypnoGPT is much smaller than the original GPT model. Specifically, the HypnoGPT model architecture comprises 3 stacked transformer blocks, each having 6 attention heads and 48 hidden units. Both the token and position embeddings have a size of 48. Training is performed on the SHHS dataset for 50 epochs, utilizing a batch size of 256. The learning rate is set at 5e-4, and the Adam optimizer is employed, utilizing a cosine learning rate decay schedule. The training is implemented is done via the PyTorch framework and the HuggingFace Transformers library.

Settings for sleep staging

We adapted the original TinySleepNet and XSleepNet by eliminating the temporal LSTM layer, allowing them to make predictions based solely on the current EEG epoch. This exclusion of memory resulted in versions named TinySleepNet-nonseq and XSleepNet-nonseq. We deployed both TinySleepNet-nonseq and XSleepNet-nonseq and their original implementations, TinySleepNet-seq and XSleepNet-seq, for a thorough evaluation of the proposed HypnoGPT model. The temporal sequential model has a sequence length of 15, utilizing the current and preceding 14 epochs to forecast the current sleep stage. All sleep staging models underwent 200 training epochs, utilizing a batch size of 256. A learning rate of 5e-4 was employed along with the Adam optimizer, implementing a cosine learning rate decay schedule. To determine a reasonable value for the weight α in Eq. 8, which influences the balance between

the sleep staging model and the HypnoGPT model, a grid search was conducted on an independent validation set. The evaluation of model performance involved ten-fold cross-validation, conducted at either the subject or session level, aligning with the evaluation protocols commonly adopted in related research. Independent validation experiments were also conducted to assess the generalization performance of the models across different sleep datasets.

Settings for sleep disorder diagnosis

Given that a sleep cycle typically spans approximately 90 minutes, multiple HypnoGPT models were trained, each with distinct context sizes: 30, 60, 120, and 180 epochs (equal to 15, 30, 60, and 90 minutes, respectively). The context size directly influences the segment lengths of the sleep stage sequences used in our sleep disorder diagnosis HTN model. Despite the use of larger local context sizes, noteworthy performance gains were not observed. Instead, these larger sizes led to increased training time and memory utilization. Consequently, a context size of 60 epochs (30 minutes) was selected for both the HypnoGPT model and the HTN model. In the HTN architecture, the local feature extraction HypnoGPT module adopts a configuration identical to that of the pretraining phase, facilitating the direct application of the pretrained model. For global feature extraction through the transformer encoder, one transformer block consisting of 6 attention heads and 48 hidden units is sufficient. Moreover, to validate the efficacy of pretraining, we trained the hierarchical sleep disorder diagnosis model entirely from scratch. Additionally, we evaluated the previously mentioned fastText model as a baseline in the context of the sleep disorder diagnosis task, facilitating direct comparison. Training was conducted for 100 epochs on both the CAP and MNC datasets, employing a batch size of 16. The learning rate was set at 5e-5, with optimization performed by the Adam optimizer with a cosine learning rate decay schedule. Furthermore, following previous protocols, both ten-fold cross-validation and independent-sample test were utilized to evaluate model performance.

Reporting Summary. Further information on research design is available in the Nature Research Reporting Summary linked to this article.

Data availability

The SHHS [55] and MNC [27] datasets are provided by the National Sleep Research Resource with appropriate deidentification. Permission and access for these datasets can be obtained via the online portal: https://www.sleepdata.org. The SleepEDF [57], Physio2018 [60], and CAP [50] datasets are available from PhysioNet at https://physionet.org/content/sleep-edfx/1.0.0/, https://physionet.org/content/challenge-2018/1.0.0/, and https://physionet.org/content/capslpdb/1.0.0/, respectively. The MASS [59] dataset is available from http://ceams-carsm.ca/mass/. The ISRUC [48] dataset can be accessed from https://sleeptight.isr.uc.pt/. Access to the HANG7 dataset is governed by data-use agreements, and it is therefore not publicly available.

Code availability

The models and source codes for reproducing the results reported in this paper can be accessed at https://github.com/yuty2009/hypnogpt.

Acknowledgements

This work was supported in part by STI2030-Major Projects under Grant 2022ZD0211700, the National Natural Science Foundation of China under Grant 62376098, 62276102, and U22A20293, and GuangDong Basic and Applied Basic Research Foundation 2024A1515011983.

Author contributions

T.Y. contributed to the development of methods, the analysis and interpretation of the data, and the drafting of the manuscript. Z.G. contributed to the development of methods, the analysis and interpretation of the data, and the drafting of the manuscript. F.W., R.H., M.L., J.Y., Z.Y., J.Z., Y.X., H.J., W.L., G.D., Z.G., Y.W, J.L., Y.Z., and S.D. contributed to the analysis and interpretation of the data. Y.L. contributed to the analysis and interpretation of the data, and the drafting of the manuscript. J.X. contributed to the development of methods and the analysis and interpretation of the data. W.W. contributed to the development of methods, the analysis and interpretation of the data, and the drafting of the manuscript. All authors reviewed the manuscript.

Competing interests

W.W. reports equity from Alto Neuroscience. None of the other authors has financial disclosures to report.

Additional information

Additional study and data information is contained in the supplementary material.

References

[1] Mahowald, M.W., Schenck, C.H.: Insights from studying human sleep disorders. Nature **437**(7063), 1279–85 (2005) https://doi.org/10.1038/nature04287

[2] Zheng, N.S., Annis, J., Master, H., Han, L., Gleichauf, K., Ching, J.H., Nasser, M., Coleman, P., Desine, S., Ruderfer, D.M., Hernandez, J., Schneider, L.D., Brittain, E.L.: Sleep patterns and risk of chronic disease as measured by long-term monitoring with commercial wearable devices in the all of us research program. Nature Medicine **30**(9), 2648–2656 (2024) https://doi.org/10.1038/s41591-024-03155-8

[3] Iber, C., Ancoli-Israel, S., Chesson, A.L., Quan, S.: The AASM manual for the scoring of sleep and associated events: Rules, terminology and technical specifications. American Academy of Sleep Medicine (2007)

[4] Wolpert, E.A.: A Manual of Standardized Terminology, Techniques and Scoring System for Sleep Stages of Human Subjects. Archives of General Psychiatry **20**(2), 246–247 (1969) https://doi.org/10.1001/archpsyc.1969.01740140118016

[5] MacLean, A.W., Lue, F., Moldofksy, H.: The reliability of visual scoring of alpha eeg activity during sleep. Sleep **18**(7), 565–9 (1995)

[6] Danker-Hopfe, H., Anderer, P., Zeitlhofer, J., Boeck, M., Dorn, H., Gruber, G., Heller, E., Loretz, E., Moser, D., Parapatics, S., Saletu, B., Schmidt, A., Dorffner, G.: Interrater reliability for sleep scoring according to the rechtschaffen & kales and the new aasm standard. J. Sleep Res. **18**(1), 74–84 (2009) https://doi.org/10.1111/j.1365-2869.2008.00700.x

[7] Rosenberg, R.S., Van Hout, S.: The american academy of sleep medicine inter-scorer reliability program: sleep stage scoring. J. Clin. Sleep Med. **9**(1), 81–7 (2013) https://doi.org/10.5664/jcsm.2350

[8] Alickovic, E., Subasi, A.: Ensemble svm method for automatic sleep stage classification. IEEE Transactions on Instrumentation and Measurement **67**(6), 1258–1265 (2018) https://doi.org/10.1109/TIM.2018.2799059

[9] Li, X., Cui, L., Tao, S., Chen, J., Zhang, X., Zhang, G.-Q.: HyCLASSS: A hybrid classifier for automatic sleep stage scoring. IEEE Journal of Biomedical and Health Informatics **22**(2), 375–385 (2018) https://doi.org/10.1109/JBHI.2017.2668993

[10] Supratak, A., Dong, H., Wu, C., Guo, Y.: DeepSleepNet: A model for automatic sleep stage scoring based on raw single-channel eeg. IEEE Trans. Neural Syst. Rehabil. Eng. **25**(11), 1998–2008 (2017) https://doi.org/10.1109/TNSRE.2017.2721116

[11] Memar, P., Faradji, F.: A novel multi-class eeg-based sleep stage classification system. IEEE Trans. Neural Syst. Rehabil. Eng. **26**(1), 84–95 (2018) https://doi.org/10.1109/TNSRE.2017.2776149

[12] Mousavi, S., Afghah, F., Acharya, U.R.: SleepEEGNet: Automated sleep stage scoring with sequence to sequence deep learning approach. PLoS One **14**(5), 0216456 (2019) https://doi.org/10.1371/journal.pone.0216456

[13] Supratak, A., Guo, Y.: TinySleepNet: An efficient deep learning model for sleep stage scoring based on raw single-channel eeg. In: The 42nd Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC), pp. 641–644 (2020). https://doi.org/10.1109/EMBC44109.2020.9176741

[14] Phan, H., Andreotti, F., Cooray, N., Chen, O.Y., De Vos, M.: Joint classification and prediction CNN framework for automatic sleep stage classification. IEEE Trans. Biomed. Eng. **66**(5), 1285–1296 (2019) https://doi.org/10.1109/TBME.2018.2872652

[15] Phan, H., Andreotti, F., Cooray, N., Chen, O.Y., De Vos, M.: SeqSleepNet: End-to-end hierarchical recurrent neural network for sequence-to-sequence automatic sleep staging. IEEE Trans. Neural Syst. Rehabil. Eng. **27**(3), 400–410 (2019) https://doi.org/10.1109/TNSRE.2019.2896659

[16] Phan, H., Lorenzen, K.P., Heremans, E., Chén, O.Y., Tran, M.C., Koch, P., Mertins, A., Baumert, M., Mikkelsen, K.B., De Vos, M.: L-SeqSleepNet: Whole-cycle long sequence modeling for automatic sleep staging. IEEE Journal of Biomedical and Health Informatics **27**(10), 4748–4757 (2023) https://doi.org/10.1109/JBHI.2023.3303197

[17] Phan, H., Mikkelsen, K., Chén, O.Y., Koch, P., Mertins, A., De Vos, M.: SleepTransformer: Automatic sleep staging with interpretability and uncertainty quantification. IEEE Transactions on Biomedical Engineering **69**(8), 2456–2467 (2022) https://doi.org/10.1109/TBME.2022.3147187

[18] Dai, Y., Li, X., Liang, S., Wang, L., Duan, Q., Yang, H., Zhang, C., Chen, X., Li, L., Li, X., Liao, X.: MultiChannelSleepNet: A transformer-based model for automatic sleep stage classification with psg. IEEE Journal of Biomedical and Health Informatics **27**(9), 4204–4215 (2023) https://doi.org/10.1109/JBHI.2023.3284160

[19] Dong, H., Supratak, A., Pan, W., Wu, C., Matthews, P.M., Guo, Y.: Mixed neural network approach for temporal sleep stage classification. IEEE Trans. Neural Syst. Rehabil. Eng. **26**(2), 324–333 (2018) https://doi.org/10.1109/TNSRE.2017.2733220

[20] Perslev, M., Jensen, M.H., Darkner, S., Jennum, P.J., Igel, C.: U-Time: A Fully Convolutional Network for Time Series Segmentation Applied to Sleep Staging. Curran Associates Inc., Red Hook, NY, USA (2019)

[21] Eldele, E., Chen, Z., Liu, C., Wu, M., Kwoh, C.K., Li, X., Guan, C.: An attention-based deep learning approach for sleep stage classification with single-channel eeg. IEEE Trans. Neural Syst. Rehabil. Eng. **29**, 809–818 (2021) https://doi.org/10.1109/TNSRE.2021.3076234

[22] Perslev, M., Darkner, S., Kempfner, L., Nikolic, M., Jennum, P.J., Igel, C.: U-Sleep: resilient high-frequency sleep staging. npj Digital Medicine **4**(1), 72 (2021) https://doi.org/10.1038/s41746-021-00440-5

[23] Jia, Z., Lin, Y., Wang, J., Ning, X., He, Y., Zhou, R., Zhou, Y., Lehman, L.-w.H.: Multi-view spatial-temporal graph convolutional networks with domain

generalization for sleep stage classification. IEEE Transactions on Neural Systems and Rehabilitation Engineering **29**, 1977–1986 (2021) https://doi.org/10.1109/TNSRE.2021.3110665

[24] Phan, H., Chen, O.Y., Tran, M.C., Koch, P., Mertins, A., De Vos, M.: XSleepNet: Multi-view sequential model for automatic sleep staging. IEEE Trans. Pattern Anal. Mach. Intell. **44**(9), 5903–5915 (2022) https://doi.org/10.1109/TPAMI.2021.3070057

[25] Seo, H., Back, S., Lee, S., Park, D., Kim, T., Lee, K.: Intra- and inter-epoch temporal context network (IITNet) using sub-epoch features for automatic sleep scoring on raw single-channel eeg. Biomedical Signal Processing and Control **61**, 102037 (2020) https://doi.org/10.1016/j.bspc.2020.102037

[26] Zhou, W., Zhu, H., Shen, N., Chen, H., Fu, C., Yu, H., Shu, F., Chen, C., Chen, W.: A lightweight segmented attention network for sleep staging by fusing local characteristics and adjacent information. IEEE Transactions on Neural Systems and Rehabilitation Engineering **31**, 238–247 (2023) https://doi.org/10.1109/TNSRE.2022.3220372

[27] Stephansen, J.B., Olesen, A.N., Olsen, M., Ambati, A., Leary, E.B., Moore, H.E., Carrillo, O., Lin, L., Han, F., Yan, H., Sun, Y.L., Dauvilliers, Y., Scholz, S., Barateau, L., Hogl, B., Stefani, A., Hong, S.C., Kim, T.W., Pizza, F., Plazzi, G., Vandi, S., Antelmi, E., Perrin, D., Kuna, S.T., Schweitzer, P.K., Kushida, C., Peppard, P.E., Sorensen, H.B.D., Jennum, P., Mignot, E.: Neural network analysis of sleep stages enables efficient diagnosis of narcolepsy. Nat. Commun. **9**(1), 5229 (2018) https://doi.org/10.1038/s41467-018-07229-3

[28] Association, A.P.: Diagnostic and Statistical Manual of Mental Disorders, Fifth Edition, Text Revision (DSM-5-TR). American Psychiatric Publishing, Washington, DC, USA (2022)

[29] Thachayani, M., Loganayagi, M.: Artificial intelligence based classifier for sleep disorder detec-tion using eeg-bci data. Int. J. Comp. Sci. Trends. Technol. **9** (2021)

[30] Sharma, M., Dhiman, H.S., Acharya, U.R.: Automatic identification of insomnia using optimal antisymmetric biorthogonal wavelet filter bank with ecg signals. Comput Biol Med **131**, 104246 (2021) https://doi.org/10.1016/j.compbiomed.2021.104246

[31] Dimitriadis, S.I., Salis, C.I., Liparas, D.: An automatic sleep disorder detection based on eeg cross-frequency coupling and random forest model. J. Neural Eng. **18**(4) (2021) https://doi.org/10.1088/1741-2552/abf773

[32] Phyo, J., Ko, W., Jeon, E., Suk, H.-I.: TransSleep: Transitioning-aware attention-based deep neural network for sleep staging. IEEE Transactions on Cybernetics

        53(7), 4500–4510 (2023) https://doi.org/10.1109/TCYB.2022.3198997

[33] Phan, H., Mikkelsen, K.: Automatic sleep staging of eeg signals: recent development, challenges, and future directions. Physiol. Meas. **43**(4) (2022) https://doi.org/10.1088/1361-6579/ac6049

[34] Liang, S.-F., Kuo, C.-E., Hu, Y.-H., Cheng, Y.-S.: A rule-based automatic sleep staging method. Journal of Neuroscience Methods **205**(1), 169–176 (2012) https://doi.org/10.1016/j.jneumeth.2011.12.022

[35] Malafeev, A., Laptev, D., Bauer, S., Omlin, X., Wierzbicka, A., Wichniak, A., Jernajczyk, W., Riener, R., Buhmann, J., Achermann, P.: Automatic human sleep stage scoring using deep neural networks. Frontiers in Neuroscience **12** (2018)

[36] Bianchi, M.T., Cash, S.S., Mietus, J., Peng, C.-K., Thomas, R.: Obstructive sleep apnea alters sleep stage transition dynamics. PLOS ONE **5**(6), 1–12 (2010) https://doi.org/10.1371/journal.pone.0011356

[37] Xu, S., Faust, O., Seoni, S., Chakraborty, S., Barua, P.D., Loh, H.W., Elphick, H., Molinari, F., Acharya, U.R.: A review of automated sleep disorder detection. Comput. Biol. Med. **150**, 106100 (2022) https://doi.org/10.1016/j.compbiomed.2022.106100

[38] Yang, F., Wang, W., Wang, F., Fang, Y., Tang, D., Huang, J., Lu, H., Yao, J.: scBERT as a large-scale pretrained deep language model for cell type annotation of single-cell rna-seq data. Nature Machine Intelligence **4**(10), 852–866 (2022) https://doi.org/10.1038/s42256-022-00534-z

[39] Born, J., Manica, M.: Regression transformer enables concurrent sequence regression and generation for molecular language modelling. Nature Machine Intelligence **5**(4), 432–444 (2023) https://doi.org/10.1038/s42256-023-00639-z

[40] Hie, B., Zhong, E.D., Berger, B., Bryson, B.: Learning the language of viral evolution and escape. Science **371**(6526), 284–288 (2021) https://doi.org/10.1126/science.abd7331

[41] Lin, Z., Akin, H., Rao, R., Hie, B., Zhu, Z., Lu, W., Smetanin, N., Verkuil, R., Kabeli, O., Shmueli, Y., Santos Costa, A., Fazel-Zarandi, M., Sercu, T., Candido, S., Rives, A.: Evolutionary-scale prediction of atomic-level protein structure with a language model. Science **379**(6637), 1123–1130 (2023) https://doi.org/10.1126/science.ade2574

[42] Elnaggar, A., Heinzinger, M., Dallago, C., Rehawi, G., Wang, Y., Jones, L., Gibbs, T., Feher, T., Angerer, C., Steinegger, M., Bhowmik, D., Rost, B.: ProtTrans: Toward understanding the language of life through self-supervised learning. IEEE Transactions on Pattern Analysis and Machine Intelligence **44**(10), 7112–7127 (2022) https://doi.org/10.1109/TPAMI.2021.3095381

[43] Radford, A., Narasimhan, K., Salimans, T., Sutskever, I.: Improving language understanding with unsupervised learning (2018)

[44] Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., Sutskever, I., *et al.*: Language models are unsupervised multitask learners. OpenAI blog **1**(8), 9 (2019)

[45] Sokolova, M., Lapalme, G.: A systematic analysis of performance measures for classification tasks. Information Processing & Management **45**(4), 427–437 (2009) https://doi.org/10.1016/j.ipm.2009.03.002

[46] Cohen, J.: A coefficient of agreement for nominal scales. Educational and Psychological Measurement **20**, 37–46 (1960) https://doi.org/10.1177/001316446002000104

[47] Vallat, R., Walker, M.P.: An open-source, high-performance tool for automated sleep staging. eLife **10**, 70092 (2021) https://doi.org/10.7554/eLife.70092

[48] Khalighi, S., Sousa, T., Santos, J.M., Nunes, U.: Isruc-sleep: A comprehensive public dataset for sleep researchers. Computer Methods and Programs in Biomedicine **124**, 180–192 (2016) https://doi.org/10.1016/j.cmpb.2015.10.013

[49] Wang, J., Zhao, S., Zhou, Y., Jiang, H., Yu, Z., Li, T., Li, S., Pan, G.: Narcolepsy diagnosis with sleep stage features using psg recordings. IEEE Transactions on Neural Systems and Rehabilitation Engineering **31**, 3619–3629 (2023) https://doi.org/10.1109/TNSRE.2023.3312396

[50] Terzano, M.G., Parrino, L., Sherieri, A., Chervin, R., Chokroverty, S., Guilleminault, C., Hirshkowitz, M., Mahowald, M., Moldofsky, H., Rosa, A., Thomas, R., Walters, A.: Atlas, rules, and recording techniques for the scoring of cyclic alternating pattern (CAP) in human sleep. Sleep Medicine **2**(6), 537–553 (2001) https://doi.org/10.1016/S1389-9457(01)00149-6

[51] Mignot, E., Lammers, G.J., Ripley, B., Okun, M., Nevsimalova, S., Overeem, S., Vankova, J., Black, J., Harsh, J., Bassetti, C., Schrader, H., Nishino, S.: The Role of Cerebrospinal Fluid Hypocretin Measurement in the Diagnosis of Narcolepsy and Other Hypersomnias. Archives of Neurology **59**(10), 1553–1562 (2002) https://doi.org/10.1001/archneur.59.10.1553

[52] Andlauer, O., Moore, I. Hyatt, Hong, S.-C., Dauvilliers, Y., Kanbayashi, T., Nishino, S., Han, F., Silber, M.H., Rico, T., Einen, M., Kornum, B.R., Jennum, P., Knudsen, S., Nevsimalova, S., Poli, F., Plazzi, G., Mignot, E.: Predictors of Hypocretin (Orexin) Deficiency in Narcolepsy Without Cataplexy. Sleep **35**(9), 1247–1255 (2012) https://doi.org/10.5665/sleep.2080

[53] Andlauer, O., Moore, I. Hyatt, Jouhier, L., Drake, C., Peppard, P.E., Han, F., Hong, S.-C., Poli, F., Plazzi, G., O'Hara, R., Haffen, E., Roth, T., Young,

T., Mignot, E.: Nocturnal Rapid Eye Movement Sleep Latency for Identifying Patients With Narcolepsy/Hypocretin Deficiency. JAMA Neurology **70**(7), 891–902 (2013) https://doi.org/10.1001/jamaneurol.2013.1589

[54] Wikipedia: Hypnogram. https://en.wikipedia.org/wiki/Hypnogram (2023)

[55] Quan, S.F., Howard, B.V., Iber, C., Kiley, J.P., Nieto, F.J., O'Connor, G.T., Rapoport, D.M., Redline, S., Robbins, J., Samet, J.M., Wahl, P.W.: The Sleep Heart Health Study: Design, Rationale, and Methods. Sleep **20**(12), 1077–1085 (1997) https://doi.org/10.1093/sleep/20.12.1077

[56] Zhang, G.-Q., Cui, L., Mueller, R., Tao, S., Kim, M., Rueschman, M., Mariani, S., Mobley, D., Redline, S.: The National Sleep Research Resource: towards a sleep data commons. Journal of the American Medical Informatics Association **25**(10), 1351–1358 (2018) https://doi.org/10.1093/jamia/ocy064

[57] Kemp, B., Zwinderman, A.H., Tuk, B., Kamphuisen, H.A.C., Oberye, J.J.L.: Analysis of a sleep-dependent neuronal feedback loop: the slow-wave microcontinuity of the eeg. IEEE Transactions on Biomedical Engineering **47**(9), 1185–1194 (2000) https://doi.org/10.1109/10.867928

[58] Goldberger, A.L., Amaral, L.A.N., Glass, L., Hausdorff, J.M., Ivanov, P.C., Mark, R.G., Mietus, J.E., Moody, G.B., Peng, C.-K., Stanley, H.E.: Physiobank, physiotoolkit, and physionet. Circulation **101**(23), 215–220 (2000) https://doi.org/10.1161/01.CIR.101.23.e215

[59] O'Reilly, C., Gosselin, N., Carrier, J., Nielsen, T.: Montreal archive of sleep studies: an open-access resource for instrument benchmarking and exploratory research. Journal of Sleep Research **23**(6), 628–635 (2014) https://doi.org/10.1111/jsr.12169

[60] Ghassemi, M.M., Moody, B.E., Lehman, L.H., Song, C., Li, Q., Sun, H., Mark, R.G., Westover, M.B., Clifford, G.D.: You snooze, you win: the physionet/computing in cardiology challenge 2018. Comput Cardiol (2010) **45** (2018) https://doi.org/10.22489/cinc.2018.049

[61] Chan, W., Jaitly, N., Le, Q., Vinyals, O.: Listen, attend and spell: A neural network for large vocabulary conversational speech recognition. In: 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 4960–4964 (2016). https://doi.org/10.1109/ICASSP.2016.7472621

[62] Rao, K., Sak, H., Prabhavalkar, R.: Exploring architectures, data and units for streaming end-to-end speech recognition with RNN-transducer. In: 2017 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), pp. 193–199 (2017). https://doi.org/10.1109/ASRU.2017.8268935

[63] Karita, S., Soplin, N., Watanabe, S., Delcroix, M., Ogawa, A., Nakatani, T.:

Improving transformer-based end-to-end speech recognition with connectionist temporal classification and language model integration. Proceedings of the Annual Conference of the International Speech Communication Association, INTERSPEECH **2019-September**, 1408–1412 (2019) https://doi.org/10.21437/Interspeech.2019-1938 . Publisher Copyright: Copyright © 2019 ISCA; 20th Annual Conference of the International Speech Communication Association: Crossroads of Speech and Language, INTERSPEECH 2019 ; Conference date: 15-09-2019 Through 19-09-2019

[64] Kenton, J.D.M.-W.C., Toutanova, L.K.: BERT: Pre-training of deep bidirectional transformers for language understanding. In: Proceedings of NAACL-HLT, pp. 4171–4186 (2019)

[65] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, L., Polosukhin, I.: Attention is all you need. In: Advances in Neural Information Processing Systems, vol. 30 (2017)

[66] Yang, Z., Yang, D., Dyer, C., He, X., Smola, A., Hovy, E.: Hierarchical attention networks for document classification. In: Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pp. 1480–1489. Association for Computational Linguistics, San Diego, California (2016). https://doi.org/10.18653/v1/N16-1174 . https://aclanthology.org/N16-1174

[67] Pappagari, R., Zelasko, P., Villalba, J., Carmiel, Y., Dehak, N.: Hierarchical transformers for long document classification. In: 2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), pp. 838–844 (2019). https://doi.org/10.1109/ASRU46091.2019.9003958

[68] Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., Houlsby, N.: An image is worth 16x16 words: Transformers for image recognition at scale. In: International Conference on Learning Representations (2021). https://openreview.net/forum?id=YicbFdNTTy

[69] Joulin, A., Grave, E., Bojanowski, P., Mikolov, T.: Bag of tricks for efficient text classification. In: Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers, pp. 427–431. Association for Computational Linguistics, Valencia, Spain (2017). https://aclanthology.org/E17-2068