TITLE

Fine-tuned large language models for answering questions about full-text biomedical research studies

SHORT TITLE

Fine-tuned LLM for answering questions about biomedical research studies

AUTHORS

Kaiming Tao[1], Jinru Zhou[1], Zachary A. Osman[1], Vineet Ahluwalia[1], Chiara Sabati[2], Robert W. Shafer[1*]

AFFILIATIONS

[1]Division of Infectious Diseases, Dept. of Medicine, Stanford University, Stanford, CA, USA 94305; [2]Dept.

of Biomedical Data Sciences, Stanford University, Stanford, CA, USA 94305.

[*]Corresponding author (rshafer@stanford.edu).

15   **ABSTRACT**

Background: Few studies have explored the degree to which fine-tuning a large-language model (LLM)

can improve its ability to answer a specific set of questions about a research study. **Methods**: We created

an instruction set comprising 250 marked-down studies of HIV drug resistance, 16 questions per study,

answers to each question, and explanations for each answer. The questions were broadly relevant to

studies of pathogenic human viruses including whether a study reported viral genetic sequences and the

demographics and antiviral treatments of the persons from whom sequences were obtained. We fine-

tuned GPT-4o-mini (GPT-4o), Llama3.1-8B-Instruct (Llama3.1-8B), and Llama3.1-70B-Instruct (Llama3.1-

70B) using a quantized low rank adapter (QLoRA). We assessed the accuracy, precision, and recall of each

base and fine-tuned model in answering the same questions on a test set comprising 120 different studies.

Paired t-tests and Wilcoxon signed-rank tests were used to compare base models to one another, fine-

tuned models to their respective base model, and the fine-tuned models to one another. **Results**: Prior to

fine-tuning, GPT-4o displayed significantly greater performance than both Llama3.1-70B and Llama3.1-8B

due to its greater precision compared with Llama3.1-70B and greater precision and recall compared with

Llama3.1-8B; there was no difference in performance between Llama3.1-70B and Llama3.1-8B. After fine-

tuning, both GPT-4o and Llama3.1-70B, but not Llama3.1-8B, displayed significantly improved

performance compared with their base models. The improved performance of GPT-4o resulted from a

mean 6% increased precision and 9% increased recall; the improved performance of Llama3.1-70B

resulted from a 15% increased precision. After fine-tuning, Llama3.1-70B significantly outperformed

Llama3.1-8B but did not perform as well as the fine-tuned GPT-4o model which displayed superior recall.

Conclusion: Fine-tuning GPT-4o and Llama3.1-70B, but not the smaller Llama3.1-8B, led to marked

improvement in answering specific questions about research papers. The process we describe will be

useful to researchers studying other medical domains.

<u>AUTHOR SUMMARY</u>

Addressing key biomedical questions often requires systematically reviewing data from numerous

studies—a process that demands time and expertise. Large language models (LLMs) have shown potential

in screening papers and summarizing their content. However, few research groups have fine-tuned these

models to enhance their performance in specialized biomedical domains. In this study, we fine-tuned

three LLMs to answer questions about studies on the subject of HIV drug resistance including one

proprietary LLM (GPT-4o-mini) and two open-source LLMs (Llama3.1-Instruct-70B and Llama 3.1-Instruct-

8B). To fine-tune the models, we used an instruction set comprising 250 studies of HIV drug resistance

and selected 16 questions covering whether studies included viral genetic sequences, patient

demographics, and antiviral treatments. We then tested the models on 120 independent research studies.

Our results showed that fine-tuning GPT-4o-mini and Llama3.1-Instruct-70B significantly improved their

ability to answer domain-specific questions, while the smaller Llama3.1-Instruct-8B model was not

improved. The process we described offers a roadmap for researchers in other fields and represents a

step in our attempt towards developing an LLM capable of answering questions about research studies

across a range of pathogenic human viruses.

INTRODUCTION

The systematic review of data from multiple research studies is often required to answer many

biomedical questions. The use of automated software tools to assist in reviewing research papers is a

topic of increasing interest (1–7). Several research studies have described the use of LLMs, primarily the

GPT-4.0 API or ChatGPT, to screen papers for specific criteria and for summarizing their content (8–14).

We previously assessed the use of GPT-4 to answer questions about studies on HIV drug resistance

(HIVDR) (15). In that study, we found that GPT-4 reproducibly answered a set of 60 questions with a

precision of 87% and a recall of 73% without human feedback. However, its performance was not

improved with a 2000-word instruction sheet. The lack of improvement with this form of prompt

engineering, led us to assess the degree to which fine-tuning could improve the performance of an LLM

to specific answer questions about published HIVDR research studies.

We selected questions designed to determine whether a study reported HIV sequences and

whether the sequences and their associated data were made publicly available. A fine-tuned model

capable of answering questions about viral sequences, their public availability, and the demographics and

antiviral treatments of the persons from whom the sequenced viruses were obtained would be invaluable

to virology researchers, journal editors, and funding agencies.

MATERIALS AND METHODS

Fine-tuning

Figure 1 outlines the approach to fine-tuning, testing, and analysis used in this study. We worked

with three LLMs: (1) GPT-4o mini-2024-07-18 (GPT-4o); (2) Meta-Llama 3.1-70B-Instruct (Llama3.1-70B);

and (3) Meta-Llama 3.1-8B-Instruct (Llama3.1-8B). Llama3.1-70B and Llama3.1-8B have 70 billion and 8

billion parameters, respectively. The exact parameter count for GPT-4o has not been reported.

Research papers: We selected 250 curated research papers about HIV drug resistance from the

Stanford HIV Drug Resistance Database (HIVDB) encompassing studies of (1) HIV sequences from infected

persons who were either antiretroviral treatment (ART)-experienced or ART-naïve; (2) HIV isolates with

known mutations undergoing *in vitro* susceptibility testing; (3) wildtype HIV isolates cultured in the

presence of increasing concentrations of an antiretroviral drug (i.e., *in vitro* selection experiments); and

(4) different approaches to HIV sequencing and cloning. The complete list of papers are in Supplementary

Table 1.

Research questions: We designed 16 questions addressing key aspects of HIVDR including (1)

Whether sequencing was performed on HIV isolates obtained from patients and whether the sequences

were made publicly available (5 questions); (2) The demographics of patients whose viruses were

sequenced (2 questions); (3) The treatment characteristics of patients whose viruses were sequenced (5

questions); and (4) The technical aspects of sequencing (4 questions). For eight questions, the answer was

a list of items; for seven questions the answer was yes or no; and for one question, the answer was a

number. For studies in which sequencing was not performed, the answers to patient demographics,

treatments, and technical aspects of sequencing were considered to be "not reported". Table 2 presents

the complete list of questions along with their frequencies of being classified as true (for Boolean

questions), non-empty (for list questions), or non-zero (for the single numeric question) in both the 250

study instruction set and the 120 study test set.

Instruction set: The instruction set contained 250 training samples. Each sample contained (1) a

markdown version of one of the 250 papers containing its abstract, methods, results, discussion, and data

sharing statement; (2) the 16 research questions; (3) the answers to the research questions; and (4) the

explanation for each of the answers, including the text relevant to each answer. For questions not

addressed by a study, the explanation indicated that the study did not address the question. The complete

training set is in Supplementary Table 2.

103   Training hyperparameters: We used Hugging Face's parameter efficient fine-tuning (16) using

104 Quantized Low-Rank Adaptation (QLoRA) (17,18). Because our dataset was complex, we used a rank of

105 25, which is in the upper range of the recommended values of 4 to 32.  We set our batch size to one

106 because our sample sizes were large with the median number of tokens per sample being 9343 (range:

107 4261-22085).

108   Implementation: Table 1 shows the GPU, VRAM, and time requirements associated with fine-

109 tuning and testing each model used in this study. For GPT-4o, the GPU and VRAM requirements were not

110 known because fine-tuning and testing were done using the OpenAI API (19).

112 **Testing and analysis**

113   We created a test set comprising 120 journal articles. One hundred studies were identified by

114 querying PubMed for journal articles about HIV drug resistance published in 2023. Twenty additional

115 studies were selected from HIVDB because they reported data on uncommon topics that were unlikely to

116 be reported in the first 100 studies. Like the training set, these papers included studies of viral sequences

117 from HIV-infected persons, *in vitro* susceptibility testing, *in vitro* selection experiments, and technical

118 aspects of HIV sequencing. Supplementary Table 3 lists the 120 papers used for testing.

119   For each question, we evaluated the answers of the original and fine-tuned models. Model-

120 generated answers were compared to the human-curated answers, which were considered to be the

121 ground truth. For the seven Boolean questions, we calculated the number of true positives, true negatives,

122 false positives, and false negatives, as well as the model's precision, recall, accuracy, and F1-score. For the

123 eight list-based questions, we defined true positive when the model outputted a non-empty list exactly

124 matching the human answer; true negative when both the human answer and the model output were

125 empty lists; false positive when the human answer was an empty list while the model outputted a non-

126 empty list; and false negative when the human answer was a non-empty list, but the model output was

either an empty list or a list that did not match the human list. A similar approach was applied to the sole

numeric question in that a result of 0 was considered analogous to an empty list. Supplementary Table 4

lists the correct answers and the answers for the three base and fine-tuned models for 1920 questions

(120 papers x 16 questions).

We used Fisher Exact Tests to compare the accuracy, recall, and precision of the base model and

fine-tuned model on the individual questions. For these tests, a Benjamini-Hochberg adjustment was

calculated for the 16 questions evaluated. We used parametric (paired T-tests) and nonparametric

(Wilcoxon-Rank Sign Test) tests to compare the average accuracy, recall, precision, and F1-score across

questions of (1) the base models to one another; (2) the fine-tuned models to one another; and (3) each

fine-tuned model to its base model. For these nine comparison, a Benjamini-Hochberg adjustment was

calculated. A summary of the statistical analysis is in Supplementary File 5.

139   **RESULTS**

Figure 2 displays the accuracy, precision, recall, and F1-score of the base and fine-tuned models

for each of the 16 questions, individually. Points to the upper left of the diagonal line indicate questions

for which there was any improvement for the fine-tuned model compared with the base model. Table 3

displays the accuracy, precision, recall, and F1-scores for the base and fine-tuned GPT-4o and Llama3.1-

70B models for those questions for which there was a significant increase in either precision or recall for

the fine-tuned model by Fisher Exact testing. For GPT-4o, the questions with improvements were Q2, Q6,

Q9, Q11, Q14, Q15, and Q16. For Llama-70B, the questions with improvements were Q14, Q15, and Q16.

The fine-tuning of Llama3.1-8B did not result in a significant increase in precision or recall for any question.

Figure 3 compares the overall mean accuracy, precision, recall, and F1-score for the 16 questions

pooled over the 120 test set studies. Prior to fine-tuning, GPT-4o displayed significantly greater precision

and recall compared with Llama3.1-8B and significantly greater precision compared with Llama3.1-70B

using both paired t-tests and Wilcoxon-ranked sign tests (Figure 2A). There were no statistically significant

differences between Llama3.1-70B and Llama3.1-8B base models.

After fine-tuning, GPT-4o displayed 6% increased accuracy, 6% increased precision, 9% increased

recall, and 8% increased F1-score (Figure 2B). Llama3.1-70B displayed 8% increased accuracy, 15%

increased precision, 1% increased recall, and 8% increased F1-score. Llama3.1-8B did not display

significantly improved performance after fine-tuning. The increased recall, accuracy, and F1- score for the

fine-tuned GPT-4o model and the increased precision, accuracy, and F1-score for the Llama3.1-70B model

were statistically significant using both paired t-tests and Wilcoxon-ranked sign tests.

Figure 2C shows that the fine-tuned GPT-4o model displayed significantly greater accuracy, recall,

and F1-score compared with both the fine-tuned Llama3.1-8B and Llama3.1-70B models using both paired

t-tests and Wilcoxon-ranked sign tests. Llama3.1-70B displayed significantly greater accuracy, recall, and

F1-score compared with Llama3.1-8B using both paired t-tests and Wilcoxon-ranked sign tests.

164   **DISCUSSION**

Fine-tuning a foundation model provides significant advantages for handling domain-specific

tasks. By training a model on targeted data, it becomes more reliable and effective in delivering accurate

results without requiring complex prompts. Using a pre-trained model for fine-tuning lowers

computational costs making it a highly efficient approach for specialized use cases. This study

demonstrates that fine-tuning GPT-4o and Llama3.1-70B significantly improved their ability to answer

questions about research studies in a specialized medical field, specifically those questions included in

their training.

Our findings can be distilled into four main observations: (1) Prior to fine-tuning, GPT-4o displayed

significantly greater performance than both Llama3.1-70B and Llama3.1-8B as a result of increased

precision compared with Llama3.1-70B and increased precision and recall compared with Llama3.1-8B,

while no difference in performance between Llama3.1-70B and Llama3.1-8B was observed; (2) After fine-

tuning both GPT-4o and Llama3.1-70B, but not Llama3.1-8B, displayed significantly improved

performance compared with their base models; (3) The improved performance of GPT-4o was a result of

its 6% increased precision and 9% increased recall while the improved performance of Llama3.1-70B

resulted from its 15% increased precision; (4) After fine-tuning, Llama3.1-70B outperformed Llama3.1-8B

primarily as a result of its improved precision, but still did not perform as well as the fine-tuned GPT-4o

model which displayed superior recall.

Most studies evaluating the potential use of LLMs for answering questions about research studies

have evaluated the use of foundational models to determine whether the titles and abstracts of a study

were likely to meet the inclusion criteria for a systematic review (8–14,20). Few have evaluated fine-tuned

foundational models for their ability to answer questions about full-text research papers (21,22).

We examined the effects of fine-tuning on three models: GPT-4o, selected for its top-tier

performance and ease of fine-tuning with just an API and Python script (23); Llama3.1-70B, chosen for its

long context length and high ranking among open-source models (24); and Llama3.1-8B, to assess fine-

tuning's impact on a smaller model. We intended to fine-tune the even larger Llama3.1-405B model, but

the most widely available GPUs lacked the memory capacity to train this model, despite several

optimization attempts. Testing this larger model would have required even more memory, and renting

the necessary GPUs was cost-prohibitive at significantly more than $10,000 for both fine-tuning and

testing.

LoRA and QLoRA are widely used approaches for fine-tuning foundational models, as they adjust

a small subset of parameters, reducing both memory usage and computational costs compared to full

fine-tuning (17). LoRA adapters can be reused to fine-tune multiple foundational models and enable low-

cost re-tuning when these models are updated. Moreover, LoRA adapters can be easily swapped or

combined, facilitating modular specialization (17). QLoRA further introduces innovations that optimize

memory usage while maintaining performance (18).

We selected a narrow topic to determine whether a foundation model could be fine-tuned to

answer questions about full-text research studies. Given the specificity of our topic, we chose not to

expand our training set or further optimize our model. However, the questions able to be answered by

the fine-tuned models target key data types broadly relevant to studies of pathogenic human viruses,

including those with available antiviral treatments, as well as those with pandemic potential. Therefore,

the success that we have described is a step towards accomplishing the more ambitious goal of developing

a fine-tuned model capable of answering questions broadly applicable to all pathogenic human viruses.

Financial disclosure statement

This work was funded by a grant from the National Institutes of Health: 2R24AI13661806. The

funder played no role in this review.

Competing interests

Data availability statement

All data generated or analyzed during this study are included in this published article and its

supplementary information files. The Llama3.1-70B and Llama3.1-8B LoRA adapters developed

for this study was shared on the Hugging Face platform (https://huggingface.co/kmtao/llama3.1-

8B-HIVDB-adapter, https://huggingface.co/kmtao/llama3.1-70B-HIVDB-adapter).

Author contributions

Conceptualization: K.T., V.A., and R.W.S; Data Curation: K.T, J.Z and Z.A.O; Formal analysis:

K.T, J.Z, C.S and R.W.S; Methodology: K.T, J.Z, J.A and R.W.S; Writing – Original Draft

Preparation: K.T, J.Z and R.W.S; Writing – Review & Editing: K.T, J.Z, V.A, C.S., and R.W.S

REFERENCES

1. van de Schoot R, de Bruin J, Schram R, Zahedi P, de Boer J, Weijdema F, et al. An open source
machine learning framework for efficient and transparent systematic reviews. Nat Mach Intell. 2021
Feb;3(2):125–33.

2. Cierco Jimenez R, Lee T, Rosillo N, Cordova R, Cree IA, Gonzalez A, et al. Machine learning
computational tools to assist the performance of systematic reviews: A mapping review. BMC
Medical Research Methodology. 2022 Dec 16;22(1):322.

3. Blaizot A, Veettil SK, Saidoung P, Moreno-Garcia CF, Wiratunga N, Aceves-Martins M, et al. Using
artificial intelligence methods for systematic review in health sciences: A systematic review.
Research Synthesis Methods. 2022;13(3):353–62.

4. Dijk SHB van, Brusse-Keizer MGJ, Bucsán CC, Palen J van der, Doggen CJM, Lenferink A. Artificial
intelligence in systematic reviews: promising when appropriately used. BMJ Open. 2023 Jul
1;13(7):e072254.

5. Jin Q, Kim W, Chen Q, Comeau DC, Yeganova L, Wilbur WJ, et al. MedCPT: Contrastive Pre-trained
Transformers with large-scale PubMed search logs for zero-shot biomedical information retrieval.
Bioinformatics. 2023 Nov 1;39(11):btad651.

6. Santos ÁO dos, da Silva ES, Couto LM, Reis GVL, Belo VS. The use of artificial intelligence for
automating or semi-automating biomedical literature analyses: A scoping review. Journal of
Biomedical Informatics. 2023 Jun 1;142:104389.

7. Kebede MM, Le Cornet C, Fortner RT. In-depth evaluation of machine learning methods for semi-
automating article screening in a systematic review of mechanistic literature. Research Synthesis
Methods. 2023;14(2):156–72.

8. Alshami A, Elsayed M, Ali E, Eltoukhy AEE, Zayed T. Harnessing the Power of ChatGPT for
Automating Systematic Review Process: Methodology, Case Study, Limitations, and Future
Directions. Systems. 2023 Jul;11(7):351.

9. Schopow N, Osterhoff G, Baur D. Applications of the Natural Language Processing Tool ChatGPT in
Clinical Practice: Comparative Study and Augmented Systematic Review. JMIR Medical Informatics.
2023 Nov 28;11(1):e48933.

10. Syriani E, David I, Kumar G. Assessing the Ability of ChatGPT to Screen Articles for Systematic
Reviews [Internet]. arXiv; 2023 [cited 2023 Nov 14]. Available from:
https://arxiv.org/abs/2307.06464

11. Khraisha Q, Put S, Kappenberg J, Warraitch A, Hadfield K. Can large language models replace
humans in systematic reviews? Evaluating GPT-4's efficacy in screening and extracting data from
peer-reviewed and grey literature in multiple languages. Research Synthesis Methods [Internet].
2024 [cited 2024 Mar 17];n/a(n/a). Available from:
https://onlinelibrary.wiley.com/doi/abs/10.1002/jrsm.1715

12. Guo E, Gupta M, Deng J, Park YJ, Paget M, Naugler C. Automated Paper Screening for Clinical
Reviews Using Large Language Models: Data Analysis Study. Journal of Medical Internet Research.
2024 Jan 12;26(1):e48996.

13. Polak MP, Morgan D. Extracting accurate materials data from research papers with conversational
language models and prompt engineering. Nat Commun. 2024 Feb 21;15(1):1569.

14. Dennstädt F, Zink J, Putora PM, Hastings J, Cihoric N. Title and abstract screening for literature
reviews using large language models: an exploratory study in the biomedical domain. Syst Rev. 2024
Jun 15;13(1):158.

15. Tao K, Osman ZA, Tzou PL, Rhee SY, Ahluwalia V, Shafer RW. GPT-4 performance on querying
scientific publications: reproducibility, accuracy, and impact of an instruction sheet. BMC Medical
Research Methodology. 2024 Jun 25;24(1):139.

16. Huggingface. PEFT (PEFT) [Internet]. 2023 [cited 2024 Oct 2]. Available from:
https://huggingface.co/PEFT

17. Hu EJ, Shen Y, Wallis P, Allen-Zhu Z, Li Y, Wang S, et al. LoRA: Low-Rank Adaptation of Large
Language Models [Internet]. arXiv; 2021 [cited 2024 Jul 5]. Available from:
http://arxiv.org/abs/2106.09685

18. Dettmers T, Pagnoni A, Holtzman A, Zettlemoyer L. QLoRA: Efficient Finetuning of Quantized LLMs
[Internet]. arXiv; 2023 [cited 2024 Aug 30]. Available from: http://arxiv.org/abs/2305.14314

19. OpenAI Platform [Internet]. [cited 2024 Aug 30]. Available from: https://platform.openai.com

20. Zhang G, Jin Q, Zhou Y, Wang S, Idnay BR, Luo Y, et al. Closing the gap between open-source and
commercial large language models for medical evidence summarization [Internet]. arXiv; 2024
[cited 2024 Sep 12]. Available from: http://arxiv.org/abs/2408.00588

21. Shah A, Mehendale S, Kanthi S. Efficacy of Large Language Models in Systematic Reviews [Internet].
arXiv; 2024 [cited 2024 Sep 12]. Available from: http://arxiv.org/abs/2408.04646

22. Susnjak T, Hwang P, Reyes NH, Barczak ALC, McIntosh TR, Ranathunga S. Automating Research
Synthesis with Domain-Specific Large Language Model Fine-Tuning [Internet]. arXiv; 2024 [cited
2024 Oct 11]. Available from: http://arxiv.org/abs/2404.08680

23. API Reference - OpenAI API [Internet]. [cited 2024 Sep 13]. Available from:
https://platform.openai.com/docs/api-reference/fine-tuning

24. LYSYS.org. Chatbot Arena Leaderboard - a Hugging Face Space by lmsys [Internet]. [cited 2024 Sep
13]. Available from: https://huggingface.co/spaces/lmsys/chatbot-arena-leaderboard

<u>SUPPORT INFORMATION CAPTIONS</u>

<u>Supplementary Table 1 (S1Table.xlsx)</u>: The list of research studies used for the instruction set.

<u>Supplementary Table 2 (S2Table.xlsx)</u>: The list of training examples included in the instruction set.

<u>Supplementary Table 3 (S3Table.xlsx)</u>: The list of research studies used for testing.

<u>Supplementary Table 4 (S4Table.xlsx)</u>: The correct answers and the answers of each of the six models

(base and fine-tuned for GPT-4o, Llama3.1-70B, and Llama3.1-8B) for 1920 questions (120 test studies x

16 questions).

<u>Supplementary File 5 (S5Appendix.xlsx)</u>: Tab 1 contains the raw data and results of Fisher Exact Tests for

each of the 16 questions for each of the six models (base and fine-tuned for GPT-4o, Llama3.1-70B, and

Llama3.1-8B). Tab 2 contains the raw data and nine comparisons between the models. Specifically, paired

t-tests and Wilcoxon signed-rank tests were used to compare the base models to one another, the fine-

tuned models to their respective base model, and the fine-tuned models to one another. Tab 3 illustrates

how the Benjamini-Hochberg adjustment for the nine model comparisons was performed.

FIGURE LEGENDS

Figure 1

Approach to fine-tuning (A), testing (B), and analyses (C) performed in this study. Fine-tuning was

performed using an instruction set comprising 250 marked-down research studies, 16 questions about

each study, answers to each question, and explanations for each answer. GPT-4o was fine-tuned using the

OpenAI API; Llama3.1-70B and Llama3.1-8B were fine-tuned using QLoRA (A). The accuracy, precision,

recall, and F1-score of each base and fine-tuned model was assessed using a test set comprising 16

questions applied to 120 different published research studies on HIV drug resistance (B). Parametric

(paired t-tests) and nonparametric (Wilcoxon signed-rank tests) methods were used to compare the

performance of the base models to one another, the fine-tuned models to their respective base model,

and the fine-tuned models to one another (C).

Figure 2

Comparison of base and fine-tuned models for each of the 16 questions applied to 120 published test

studies. The accuracy (A), precision (B), recall (C), and F1-score (D) of the GPT4o, Llama3.1-70B, and

Llama3.1-8B models are shown with the metrics for the base model indicated on the X-axis and for the

fine-tuned model indicated on the Y-axis. Points to the left of the diagonal line indicate those questions

for which there was an improvement for the fine-tuned model compared with the base model.

Figure 3

Comparisons of the performance of the base models to one another (A), the fine-tuned models to their

respective base model (B), and the fine-tuned models to one another (C). The histograms in figures 3A

and 3C represent the performance of the base and fine-tuned models, respectively. The histograms in

figure 3B represent the difference in performance between the fine-tuned and base model. The error bars

in figure 3B represent the standard error of the mean of the paired differences between the fine-tuned

and base models. The mean differences in accuracy, precision, recall, and F1-score between models are

indicated above the relevant histograms when statistically significant using both parametric (paired t-test)

and nonparametric (Wilcoxon signed-rank test) methods. The p values shown are for the paired t-test

performed on the aggregate data for each of the 16 questions. After adjustment for nine comparisons,

the Benjamini-Hochberg false discovery rate was ≤0.05 for each of the p values shown.

Table 1. GPU, VRAM, and Time Requirements Associated with Fine-Tuning and Testing

Model	Fine-Tuning			Testing the Base Model			Testing the Fine-Tuned Model		
	GPU	**VRAM**	**Time**	**GPU**	**VRAM**	**Time**	**GPU**	**VRAM**	**Time**
GPT-4o-mini	NA	NA	2h	NA	NA	1h	NA	NA	1h
Llama3.1 8B	1 A100	80G	1h	1 A100	80G	2h	2 A100	160G	13h
Llama3.1 70B	3 A100	240G	7h	3 A100	240G	5h	4 A100	320G	21h

Footnote: GPU (graphical processing unit); VRAM (video random access memory); A100 (Nvidia A100 tensor core GPU); VRAM is indicated as gigabytes.

Table 2. Complete List of Questions with their Frequencies of True, Non-Empty or Non-Zero in Both Instruction Set and Test Set

	Question	Subject	Type	Instruction set (%)	Test set (%)
Q1	Does the paper report HIV sequences from patient samples?	Data availability	Boolean	85.6	66.7
Q2	Does the paper report in vitro drug susceptibility data?	Data availability	Boolean	20	20.8
Q3	Were sequences from the paper made publicly available?	Data availability	Boolean	56.4	17.5
Q4	What were the GenBank accession numbers for sequenced HIV isolates?	Data availability	List	54.4	12.5
Q5	How many individuals had samples obtained for HIV sequencing?	Data availability	Number	82.8	64.2
Q6	From which countries were the sequenced samples obtained?	Demographics	List	76.8	56.7
Q7	From what years were the sequenced samples obtained?	Demographics	List	64	51.7
Q8	Were samples cloned prior to sequencing?	Technical	Boolean	2.8	2.5
Q9	Which HIV genes were reported to have been sequenced?	Technical	List	91.2	75.0
Q10	What method was used for sequencing?	Technical	List	64.8	45.8
Q11	What type of samples were sequenced?	Technical	List	79.2	52.5
Q12	Were any sequences obtained from individuals with virological failure on a treatment regimen?	Treatment	Boolean	36.4	30.8
Q13	Were the patients in the study in a clinical trial?	Treatment	Boolean	14.4	15.8
Q14	Does the paper report HIV sequences from individuals who had previously received ARV drugs?	Treatment	Boolean	46.4	46.7
Q15	Which drug classes were received by individuals in the study before sample sequencing?	Treatment	List	36.8	38.3
Q16	Which drugs were received by individuals in the study before sample sequencing?	Treatment	List	34.4	32.5

Table 3. Accuracy, Precision, Recall and F1 Score for the Research Questions for which an Improvement was Observed After Fine-Tuning (FT) of Either GPT-4o or Llama3.1-70B

	Accuracy		Precision		Recall		F1-Score	
	B	FT	B	FT	B	FT	B	FT
GPT-4o								
Q2. Does the paper report in vitro drug susceptibility data?	85.0	95.8**(†)	58.1	91.7**(†)	100.0	88.0	73.5	89.8
Q6. From which countries were the sequenced samples obtained?	80.0	89.2	100.0	93.7	64.7	86.8**	78.6	90.1
Q9. Which HIV genes were reported to have been sequenced?	61.7	73.3	97.8	91.4	50.0	71.1**	66.2	80.0
Q11. What type of samples were sequenced?	80.0	86.7	95.4	88.5	65.1	85.7*	77.4	87.1
Q14. Does the paper report HIV sequences from individuals who had previously received ARV drugs?	84.2	91.7	100.0	91.1	66.1	91.1**	79.6	91.1
Q15. Which drug classes were received by individuals in the study before sample sequencing?	57.5	77.5**	44.9	77.1**(†)	47.8	58.7	46.3	66.7
Q16. Which drugs were received by individuals in the study before sample sequencing?	57.5	74.2**(†)	33.3	66.7*(§)	30.8	41.0	32.0	50.8
Llama3.1-70B								
Q14. Does the paper report HIV sequences from individuals who had previously received ARV drugs?	74.2	84.2	73.6	100.0***	69.6	66.1	71.6	79.6
Q15. Which drug classes were received by individuals in the study before sample sequencing?	34.2	70.8***	29.6	76.2***	52.2	34.8	37.8	47.8
Q16. Which drugs were received by individuals in the study before sample sequencing?	27.5	71.7***	17.6	69.2***	33.3	23.1	23.0	34.6

Footnote: OR: Odds ratio of Fisher's Exact Test. ***: unadjusted p < 0.001; **: unadjusted p < 0.01; *: unadjusted p < 0.05. After adjustment for 16 comparisons, the Benjamini-Hochberg false discovery rate was ≤0.05 for each significant comparison except for those indicated by (†) for which it was 0.06 and (§) for which it was 0.09.

Figure 1

A

B

C

Figure 2

Figure 3

A. Comparison of the Base Models

B. Comparison of the Base and Fine-Tuned Models

C. Comparison of the Fine-Tuned Models