Leveraging hierarchical structures for genetic block interaction studies using the hierarchical transformer

Shiying Li[1], Shivam Arora[2], Redha Attaoua[1], Pavel Hamet[1], Johanne Tremblay[1], Alexander Bihlo[2], Bang Liu[3] and Guy Rutter[1,4,5*]

[1]Centre de Recherche du CHUM, and Faculty of Medicine, University of Montreal, QC, Canada

[2]Department of Mathematics and Statistics, Memorial University of Newfoundland, NL, Canada

[3]Département d'informatique et de recherche opérationnelle, Université de Montréal, QC, Canada

[4]Section of Cell Biology and Functional Genomics, Department of Metabolism, Diabetes and Reproduction, Imperial College of London, du Cane Road, London W120NN, United Kingdom

[5]Lee Kong Chian School of Medicine, Nan Yang Technological University, Singapore.

Address correspondence to:

Guy A. Rutter guy.rutter@umontreal.ca, 514 890-8000, ext. 27081

Word count: 5558   Number of Figures: 5   Number of Tables: 3

1. Abstract

Initially introduced in 1909 by William Bateson, classic epistasis (genetic variant

interaction) refers to the phenomenon that one variant prevents another variant from a

different locus from manifesting its effects. The potential effects of genetic variant

interactions on complex diseases have been recognized for the past decades.

Moreover, It has been studied and demonstrated that leveraging the combined SNP

effects within the genetic block can significantly increase calculation power, reducing

background noise, ultimately leading to novel epistasis discovery that the single SNP

statistical epistasis study might overlook. However, it is still an open question how we

can best combine gene structure representation modelling and interaction learning into

an end-to-end model for gene interaction searching. Here, in the current study, we

developed a neural genetic block interaction searching model that can effectively

process large SNP chip inputs and output the potential genetic block interaction

heatmap. Our model augments a previously published hierarchical transformer

architecture (Liu and Lapata, 2019) with the ability to model genetic blocks. The

cross-block relationship mapping was achieved via a hierarchical attention mechanism

which allows the sharing of information regarding specific phenotypes, as opposed to

simple unsupervised dimensionality reduction methods e.g. PCA. Results on both

simulation and UK Biobank studies show our model brings substantial improvements

compared to traditional exhaustive searching and neural network methods.

2. Introduction

In the past decades, the genetic factors that contribute to the pathogenesis of complex diseases have been extensively studied, and genome-wide association study (GWAS) has played a fundamental role in unveiling novel risk alleles. The approach of the GWAS framework assumes each SNP has an independent effect on phenotype and the disease's statistical relevance was tested individually (Niel et al., 2015). However, most complex disease variants identified so far confer relatively small increments in risk, leading to many questions about how the remaining "missing heritability" can be explained (Maher, 2008). For example, GWAS correlation identified >80 common variants for type 2 diabetes with most of those associated with insulin secretion, together, they only contribute ~ 10% of type 2 diabetes (T2D) heritability. T2D Low-frequency and rare variants have also been identified, but their contribution towards "missing heritability" is also limited (Stančáková and Laakso, 2016). Indeed, with a larger sample size and the advancement of sequencing techniques, GWAS will likely continue to expand the number of novel complex disease genetic markers. However, the current consensus underscores the growing recognition that the missing heritability of complex diseases extends beyond the scope of singular genetic factors. Interactions among two or more SNPs, a combinatorial effect known as epistasis, have been proven (Turton et al., 2011) can at least partly explain the "missing heritability".

Finding the optimal interacting SNP combination for certain phenotypes, which implies an exhaustive search of all possible cases, can be a challenging task. For instance, in a dataset containing 500,000 SNPs, there are approximately 250 billion possible pairwise SNP combinations. This immense number presents significant

challenges, not only in terms of computational hardware requirements but also in the

risk of losing true signals due to overcorrection for multiple comparisons resulting in a

reduction in statistical power. A problem we often refer to as the "curse of

dimensionality". To address this issue, several scalable statistical approaches have

been proposed in recent years; however, each comes with its own set of limitations.

Some methods (Cordell, 2002) only select "top SNPs" (the SNPs most correlated with

phenotypes) for epistasis searching, while ignoring the potential effects of

neighbouring SNPs. Indeed, over the past few decades, extensive research (Morris and

Kaplan, 2002; Zaykin et al., 2002; Chen et al., 2020) has highlighted the necessity and

efficiency of leveraging the combined effects of multiple SNPs within certain genetic

regions e.g. haplotype blocks, rather than focusing on individual SNPs in association

studies. Some have proposed to summarise multi-dimensional SNPs into one-

dimensional representations using unsupervised methods such as PCA (Li et al.,

2009). However, these methods overlook important phenotype information and

compress highly dependent SNPs into a single dimension, making it difficult to detect

signals within these units. In short, it is still an open question how we can best

combine genetic block representation learning and interaction modelling to an end-to-

end model to increase calculation power.

The rapid development of deep learning and artificial intelligence seems to hold

another promise for epistasis studies. Several studies (Pérez-Enciso and Zingaretti

2019; Cui et al., 2022) have suggested Deep Neural Networks (DNNs) can map the

flexible, both linear and non-linear relationships between SNPs and observed

phenotypes. However, DNNs, which are primarily designed for classification, with a

black-box nature that makes it challenging to interpret results, particularly in

identifying which SNPs are interacting. Many studies aim to bridge this gap between

interpretability and DNN structures using such as layerwise relevance (Mieth et al.,

2021), permutation testing (Cui et al., 2022), and more recently, transformer with

attention scores (Graça et al., 2024). While the potential application of transformer in

genome sequencing analysis has enjoyed renewed interest. Scanning through most of

the genetic transformer studies in recent years (Jubair et al., 2021; Reyes et al., 2022;

Zhou et al., 2022), the basic unit, as the "word" in natural language, is still single SNP

with little existing genetic structure e.g. haplotype block, the main focus of current

study, introduced within the attention block. The size of haplotype blocks can vary

and is often larger than the typical units analysed in natural language processing. This

variability poses a substantial challenge in encoding these differently-sized haplotype

blocks into the transformer encoder while preserving their biological significance

during this process, to ensure that the outputs of the attention scores are interpretable

and relevant.

In the current study, taking inspiration from the hierarchical transformer model (Liu

and Lapata, 2019), we proposed a novel haplotype block-haplotype block association

study workflow, Haplotype Block LSTM hierarchical Transformer (HB-LT). HB-LT

is constructed in a hierarchical manner which allows it to efficiently capture both

within and cross-haplotype relationships relevant to specific phenotypes. We

demonstrate with simulations that grouping SNPs into dimensionality-reduced

haplotype block structures significantly increases detection power for epistasis studies

compared to existing methods. Furthermore, by evaluating our model on the UK

Biobank dataset, we demonstrated its potential for real-world applications.

119
3. Methods

3.1 Model description.

The model in the current study is mainly inspired by Liu and Lapata (2019) and

several previous machine learning works (Chang et al., 2020; Cui et al., 2022 and

Graça et al., 2023) dedicated to epistasis studies. Our haplotype epistasis study system

is illustrated in Figure 1. The inputs of the model are the pre-organised haplotype

datasets and the associated phenotype of each individual, while the outputs are the

attention weights (epistasis) among potential candidates.

128
3.1.1 Long short-term memory (LSTM) pre-selection. For large dataset analysis,

applying pre-selection methods effectively reduces computational burdens and

enhances calculation efficiency. However, one of the key challenges in the current

study is the variation in haplotype block lengths, which can range from as few as 2 to

more than 100 SNPs. Here, we adopted a learning-based approach. A linear regression

model is applied to each haplotype individually, and its average root of mean square

error on the testing dataset is used as a score indicating whether it should be selected

as a phenotype-associated candidate. Haplotype blocks of the SNP dataset were first

constructed using the confidence interval method (Gabriel et al., 2002), we then use

recurrent neural network LSTM to represent each haplotype block. Let

139
$$\{u_{h1}, \cdots, u_{hi}\} = \mathrm{lstm}(\{w_{h1}, \cdots, w_{hi}\})$$

140 $w_h i$ are word embedding for tokens in each haplotype block, where $u_h i$ are updated

141 vectors for the token after LSTM.

142 An average-pooling is then used to obtain a fixed length representation and a linear

143 transformation yields the final representation of the haplotype block s_i.

144
$$s_i = \text{linear}\left(W \cdot \text{avgpool}\left(u_{h1}, \ldots, u_{hi}\right)\right)$$

All input haplotype blocks were pre-split into training and testing datasets. The model

is trained by minimising the root of mean square error of s_i and the phenotype y. In

testing, the phenotype-associated haplotype block candidates were selected based on

the mean prediction score.

3.1.2 Hierarchical transformer encoder.

3.1.2.1 Embedding. Input SNPs are first represented by word embeddings. Let

$e_i \in \mathbb{R}^{d_e}$ represent the embedded dimensional vectors of the SNP i. Let H denote the

haplotype where $H = \{\mathbf{e}_i\}_{i=1}^{n}$. n is the total number of SNPs in each haplotype block.

In our hierarchical haplotype transformer, each token (SNP) has two positions that

need to be considered, namely i, the position of the token (SNP) within the haplotype,

and j, the position of the haplotype block within the input sequence. We follow

(Vaswani et al., 2017) and use sine and cosine functions for calculating positional

embedding. These two positional embedding vectors were then concatenated and the

final input vector of each token (SNP) for the hierarchical haplotype transformer

model is: $x_i = e_i + e_p$.

3.1.2.2 Local haplotype attention block. The main aim of the local haplotype

attention block is to map the dynamic attention scores among SNPs within each

haplotype block. It contains several components, including multi-head attention, layer

normalisation and feed-forward. The number of these local attention blocks to be used

in the model will be decided by the researchers themselves. Let

$F = \{f_i\}_{i=1}^n, \quad f_i \in \mathbb{R}^{d_{\text{model}}}$ denote the features of SNPs within each haplotype input to

the local haplotype attention block. For the i attention head, the query $Q^j = \{q_i^j\}_{i=1}^n$,

key $K^j = \{k_i^j\}_{i=1}^n$ and value $V^j = \{v_i^j\}_{i=1}^n$ of each SNP are calculated based on

$q_i^j = W_Q^j f_i, k_i^j = W_K^j f_i$ and $v_i^j = W_V^j f_i$ respectively. The linear projection learnable

parameters weight W are matrices $W_i^Q \in \mathbb{R}^{d_{\text{model}} \times d_k}, W_i^K \in \mathbb{R}^{d_{\text{model}} \times d_k}, W_i^V \in \mathbb{R}^{d_{\text{model}} \times d_v}$.

$d_k = d_v = d_{\text{model}}/h$. The output of j attention head will be: $\text{softmax}\left(\dfrac{QK^T}{\sqrt{d_k}}\right)V$. The

multi-head results were then concatenated and linear transferred with learnable weight

$W^O \in \mathbb{R}^{hd_v \times d_{\text{model}}}$ to get the final results. The feed-forward layer is composed of two

fully connected (FC) layers in inverse order with an activation function *Tahn* in

between.

3.1.2.3 Inter-haplotype attention block. To exchange information across different

haplotypes, an inter-haplotype attention block was used. To obtain a fixed-length

haplotype representation, a weighted, multi-head pooling was first used to represent

each haplotype. In each head, weight distributions over tokens (SNPs) are calculated

and different heads will encode haplotypes with different attention weights. Let

$x_i^{l-1} \in \mathbb{R}^d$ denote the output vector from the last layer of the local haplotype attention

block, which will be the input of the multi-head pooling layer. For haplotype H_j, for

head z, a linear transformation was first applied to convert the input vector into an

attention score a_i^z and a value vector b_i^z with the weight $W_a^z \in \mathbb{R}^{1 \times d}$ and $W_b^z \in \mathbb{R}^{d_{\text{head}} \times d}$.

The final output $d_{\text{head}} \times 1$ is a weighted sum representing haplotype j in head z where

$W_c^z \in \mathbb{R}^{d_{\text{head}} \times d_{\text{head}}}$.

$$\text{head}_j^z = \text{LayerNorm}\left(W_c^z \sum_{i=1}^{n} a_i^z b_i^z\right)$$

190   Similar to local haplotype attention blocks, inter-haplotype allows one haplotype to

191   attend to another to model the haplotype-haplotype dependencies.

$$q_j^z \& = W_q^z \text{head}_j^z$$

$$k_j^z = W_k^z \text{head}_j^z$$

$$v_j^z = W_v^z \text{head}_j^z$$

$$context_j^z = \sum_{j=1}^{m} \frac{\exp\left(q_j^{z\,T} k_{j'}^z\right)}{\sum_{o=1}^{m} \exp\left(q_j^{z\,T} k_o^z\right)} v_{j'}^z$$

Where $q_i^z, k_i^z \in \mathbb{R}^{d_{\text{head}} \times d_{\text{head}}}$ and $v_j^z \in \mathbb{R}^{d_{\text{head}} \times 1}$, the output $context_j^z$ was then flatted to

generate a vector with dimension $\mathbb{R}^{d_{\text{head}}}$. Finally, the different heads for each haplotype

were then concatenated and linear transformed $c_j = W_c[\text{context}_j^1; \ldots; \text{context}_j^{n_{\text{head}}}]$

where $W_c \in \mathbb{R}^{d \times d}$ and $c_j \in \mathbb{R}^d$ will be added to the original token i vector to update the

token. Figure 2 provides a schematic view of inter-haplotype block attention.

3.2 Simulation dataset.

The simulation datasets were achieved by re-sampling approaches with existing

genotype data as reference panels, thereby retaining allele frequency and LD patterns

(Wright et al., 2007). In the current study, the re-sampling based method Hapgen2 (Su

et al., 2011) was applied with 1000Genomes (Auton & Salcedo, 2015) as a reference

panel. In total, chromosome 20 of 1000 individuals was resampled and subjected to

the following analysis. The haplotype block was parsed based on the confidence

interval method (Gabriel et al., 2002) by *PLINK* (Purcell et al., 2007).

In our current study, we first simulate the expression of h_i of each haplotype block i

according to a linear combination of all SNPs in the haplotype block.

$$h_i = \sum_{j=1}^{d_i} \alpha_{ij} x_{ij}$$

The phenotype was then simulated based on three epistasis models, which were

originally proposed by Burton et al (2007). More specifically, model 1 reflects an

epistasis model where the odds of disease increase multiplicatively within and

between 2-way disease markers. Using h_i and h_j to denote the expression of haplotype

i and j, α and θ to denote the baseline and the factor of odd disease increase. Model1:

$$\text{odds}[h_i, h_j] = \alpha \times (1 + \theta_1)^{h_i} \times (1 + \theta_2)^{h_j} + \epsilon$$

In contrast, model 2 represents a disease model where the odds of disease only

increase unless both loci have at least one disease-associated allele,

$$\text{odds}[h_i, h_j] = \alpha \times (1 + \theta)^{(h_i) \times (h_j)} + \epsilon$$

Model 3 is similar to model 2, but renders a simpler threshold model as

$$\text{odds}[h_i, h_j] = \alpha \times (1 + \theta) + \epsilon$$

To simulate the simple epistasis model, two haplotype blocks will be randomly

selected each time and the phenotype model 1, model 2 or model 3 will be simulated

accordingly. To simulate the complex epistasis model, one dataset will contain

multiple epistasis from different SNP pairs. Here, we use the 'Combined Model

1+2+3' as a complex epistasis model which contains three epistasis from the previous

three basic models.

3.3 Baseline models.

To benchmark our model, we selected two state-of-the-art approaches for comparison

with the current proposed framework, matrixEpistasis (Zhu and Fang, 2017) and

GWAS_NN (Cui et al., 2022). MatrixEpistasis represents a state-of-the-art method

for exhaustive epistasis searching. In contrast, GWAS_NN is one of the few methods

in the current field that tackles epistasis detection using neural networks, while also

providing an interpretation for the observed results. The GWAS_NN model first

learns the genetic block representations from all SNPs of a genetic block in a shallow

layer and then learns the complex relationships between genetic blocks in a deep

layer. These two baseline models exemplify the two main categories for epistasis

detection: exhaustive searching and machine learning. Both baseline models were

operated with the default settings unless indicated otherwise.

3.4 Cohort description and statistical analysis.

3.4.1 Cohort description. This research has been conducted using the UK Biobank

Resource. A material transfer agreement was signed with UK Biobank that covers

Research Tissue Bank (RTB) under projects 49731 and 59642. The UK Biobank study

began in 2006 and, by 2010, had recruited over 500,000 participants from the general

UK population, aged 40 to 69 at the time of enrollment. The UK Biobank genetic data

contains genotypes for 488,377 participants. These were assayed using two different

yet similar assays, Applied Biosystems UK BiLEVE Axiom Array by Affymetrix

(Thermo Fisher Scientific) and Applied Biosystems UK Biobank Axiom Array. More

detail on the assay and quality control can be found in the UK Biobank Genotyping

and Quality Control

(https://biobank.ctsu.ox.ac.uk/crystal/crystal/docs/genotyping_qc.pdf.). Individuals

included in the current study from UK Biobank have T2D and are of European

descent. The UK The REC reference for UK Biobank is 16/NW/0274.

3.4.2 Candidate genes selection. To test the potential application of HB-LT in a real-

world scenario, we applied HB-LT to pre-selected glycated haemoglobin associated

genes. The candidate genes were first extracted from the DisGeNET database (Piñero,

et al., 2015). In total, fourteen genes were extracted and their coordinates

(chromosome, gene start position, and gene end position) were obtained using the

BioMart Project martview tool (Supplemental material). Next, SNPs located in each

gene $\pm$ 10 kbps were extracted in *PLINK* (Purcell et al., 2007). The thresholds set for

quality control including, imputation quality, Hardy-Weinberg equilibrium,

genotyping missing data across individuals, and genotyping missing rate were 0.8, 10-

10, 0.05, and 0.05 respectively.

3.4.3 Covariants pre-filtering. The datasets were subjected to a PCA-based covariant

pre-filtering stage to reduce the confounding effects before they feed into the HB-LT

for potential epistasis signal mining. Four covariants, including sex, age of diabetes

diagnosis, diabetes duration and population genetic structure were standardised

(*Scikit-learn* package) and subjected to PCA (*Scikit-learn* package) to reduce into a 2-

dimensional space. A 1×1 square was then applied to locate the most densely

populated area and individuals within this area were selected and subjected to the

following analysis.

280
3.5 Software support.

We conducted model-building and statistical analysis mainly using Python 3.9

(https://www.python.org/) and additional packages including *Pandas* (2.2.2), *Numpy*

(1.26.4), *PyTorch* (2.3.1), and *Tensorflow* (2.16.1). Other software includes R 4.2.2

(https://www.r-project.org/), Hapgen2

(https://mathgen.stats.ox.ac.uk/genetics_software/hapgen/), PLINK 1.9

(https://www.cog-genomics.org/plink/) and BioMart Project martview

(https://mart.ensembl.org/). The figures in the current study were drawn by *Matplotlib*

(3.8.2) and *Plotly* (5.22.0).

3.6 Data availability statement.

UK Biobank data are available to registered investigators under approved applications

(http://www.ukbiobank.ac.uk). Other relevant data are available from the

corresponding author upon request. The source code is available at

https://github.com/LI-SHIYING118/HB-LT.

4. Results

Long short-term memory (LSTM) selects potential phenotype-associated signals

as stage 1 of the current model.

To pre-select potential phenotype-associated candidates from pools of haplotype

blocks in the human genome while maintaining a feasible computational burden, it is

essential to implement efficient filtering techniques. These techniques should be

capable of learning the representations of haplotype blocks by considering all the

SNPs within each block to the phenotype. Long short-term memory (LSTM) is a

recurrent neural network that is capable of learning long-range dependency and can

process sequences with variable lengths. It was widely used in datasets that process

"sequential" properties, such as natural language translation, before the introduction of

the Transformer model (Vaswani et al., 2017). Nevertheless, LSTMs still demonstrate

several advantages, especially for small datasets such as haplotype blocks, making

them a potentially effective technique for the filtering stage.

In the current study, we evaluated three epistasis models (model 1, model 2, and

model 3) as described by Burton et al. (2007), using chromosome 20 data from 1,000

individuals. Single nucleotide polymorphisms (SNPs) were pre-organized into

haplotype blocks using *PLINK*. Detailed descriptions of the dataset simulation and

haplotype block parsing methods can be found in the Methods section. Each haplotype

was tested individually by LSTM (n=10) and the root of mean square error was

recorded each time. Figure 3 shows the LSTM performance of chromosome 20 with 2

random haplotype blocks selected as epistasis signals of model 1, model 2 and model

3 (from top to bottom) at one record. Multiple valleys can be observed in all three

plots, indicating the presence of real epistasis signals. To quantify the performance of

the model across multiple runs with different haplotype block sizes, we repeated this

process 10 times and recorded the ROC AUC each time. As shown in the figure, the

LSTM can distinguish the epistasis signals from the background noise, achieving an

area under the curve (AUC) close to 1 in all three simple epistasis models.

Additionally, we conducted tests using the complex epistasis model to evaluate the

LSTM's capability in distinguishing signals. This complex epistasis model

encapsulates the combined effects of model 1, model 2, and model 3, which feature

multiple epistatic interactions from different haplotype block pairs. Employing

assessment criteria similar to those used for the simple epistasis model, Figure 3

shows that the LSTM demonstrates robust performance in accurately identifying all

haplotype blocks which contain complex epistasis signals. In short, in both simple and

complex epistasis models, the LSTM is an effective tool for selecting potential

candidates from large haplotype pools, significantly reducing the computational

burden and increasing the calculation power for subsequent hierarchical transformer

analysis.

The hierarchical transformer encoder maps the haplotype block interactions

with the complex epistasis model as stage 2 of the current study.

After selecting the potential phenotype-associated haplotype block candidates, we

applied a hierarchical transformer encoder and continued with the simulation datasets

to assess its ability for epistasis signal detections. The hierarchical transformer

encoder is a modified version of the hierarchical transformer that was originally

proposed by Liu and Lapata (2019). The potential epistasis signals were quantified

and visualised using the attention weights, which served as the main output of the

current hierarchical transformer encoder. "Attention," first introduced by Vaswani et

al. (2017), is a mechanism in the transformer neural network that enables the model to

dynamically weigh the importance of each element in an input sequence relative to the

others. The attention weights, the main output of our current model, are computed

using a scaled dot-product that quantifies this "relatedness" between pairs of haplotype

blocks and SNPs (within haplotype block). Several studies (Ahmed, Aly and Liu,

2024; Graça et al., 2024) have demonstrated these attention weights that learned by

the model, at least partially, can be interpreted as the epistasis interactive scores

between genetic regions.

In the hierarchical transformer encoder, attention weights are initially mapped

between each SNP within each haplotype block. Subsequently, a fixed-length

representation of each haplotype is generated using multi-head pooling. Multi-head

attention weights are then calculated between haplotypes. This updated information is

incorporated into the original SNP embedding and processed through the feed-forward

layer. For further details, please refer to the Methods section. Figure 4a illustrates the

Root Mean Square Error (RMSE) and loss for both training and testing datasets, split

in a ratio of 0.8:0.2, for a single record. The plots demonstrate a smooth training

trajectory with no significant discrepancies between the training and testing datasets,

indicating stable model performance and effective training without overfitting.

Additionally, this process was repeated 10 times, each iteration using different pre-

selected simulated signals (Figure 4b). The model consistently demonstrated a robust

performance in phenotype predictions with mean RMSE lower than 0.012 for both

training and testing datasets.

More importantly, to evaluate whether the simulated complex epistasis signals

(model1+2+3) can be at least partially captured by the cross-haplotype attention

weights, which are the primary output of our current HB-LT model, we compared

these weights with the ground truth matrix. We then plotted the ROC AUC curve

(n=10), as shown in Figure 4c. The model achieved an average AUC of 0.83. In short,

after the LSTM pre-selected the potential phenotype-associated haplotype blocks, the

hierarchical transformer encoder demonstrated reasonable performance in

distinguishing potential interaction/epistasis signals between haplotype blocks.

HB-LT outperforms baseline models for both simple and complex epistasis

models.

Traditional exhaustive epistasis searching methods are often facing a challenge

referred to as the "curse of dimensionality". The SNPs that are involved in the

epistatic interactions might have low minor allele frequencies, however, the variants

to be tested can be huge. As a result, detecting these interactions becomes challenging

due to the reduced statistical power and the increased likelihood of both type 1 and

type 2 errors. In the current study, we selected matrixEpistasis (Zhu and Fang, 2017)

as one of the representatives for an exhaustive epistasis searching method against our

current HB-LT model.

In contrast, we also tested two deep learning neural network baseline models,

GWAS_NN (Cui et al., 2022) and LSTM with the vanilla transformer encoder, against

our current HB-LT model. In GWAS_NN, the long sequence of SNPs was initially

divided into different genetic blocks (SNPs layer). Fully connected multilayer

perceptrons (MLPs) were then used to learn a fixed representation for each genetic

block$(g_1, ..., g_m)$. Another set of MLPs was subsequently trained to learn the epistasis

between these genetic blocks. Additionally, we also tested the LSTM with the vanilla

transformer encoder against our HB-LT model to assess the potential advantages of

the hierarchical transformer structure compared to the vanilla single SNP transformer

structure for epistasis studies.

A total of 6,156 haplotype blocks (60,501 SNPs) from chromosome 20 in the

simulation datasets were analysed using three baseline models and the HB-LT model.

These models were evaluated under both simple and complex epistasis conditions

with recorded ROC AUC (n=10). Overall, all four models showed robust performance

in identifying epistasis signals. MatrixEpistasis demonstrated a stable yet

comparatively low performance, with an average of around 0.73 across both simple

and complex epistasis models. This outcome likely reflects the reduced statistical

power of exhaustive searching methods when handling large SNP datasets. In

contrast, HB-LT exhibited the highest performance across both simple and complex

models, although this advantage was less pronounced when dealing with complex

models. The reason HB-LT has a larger ROC AUC than baseline models could mainly

be because HB-LT employs multi-head pooling to utilise all SNPs for representing

haplotype blocks in a supervised manner. This approach not only reduces

dimensionality compared to considering each SNP individually but also provides more

informative representations than selecting a single SNP or using unsupervised

methods such as PCA.

417
418
Interaction discovery in a diabetes glycated haemoglobin study.

To inspect how trustworthy our proposed framework is in a real-world scenario,

experiments on real-world cohort, UK BioBank for glycated haemoglobin (HbA1c)

are performed. Glycated haemoglobin (HbA1c) is the most common biomarker used

to monitor glucose control in diabetes patients (WHO, 2011), which reflects the

glycemic load ~ 3 months and traits such as hemoglobinopathies and alteration in

intracellular glucose metabolism (Nathan, Turgeon and Regan, 2007). HbA1c levels

are influenced by both environmental and genetic factors. Research studies (Snieder et

al., 2001; Meigs et al., 2002) estimating the heritability of HbA1c in non-diabetic

individuals report a range from 27% to 62%, providing strong evidence of a

significant genetic component in HbA1c variability. Previous genome-wide

association studies (GWAS) (Wheeler et al., 2017) have identified more than 100

genetic variants to be associated with HbA1c. In this study, we re-examined the

HbA1c-associated loci in the UK Biobank cohort to explore potential novel epistasis

signals, both within and across haplotype blocks. To limit the potential confounding

factors in our current study, patients were pre-filtered based on 4 covariants (age of

diabetes diagnosis; diabetes duration; sex and population genetic structure) in UK

Biobank to select individuals with similar characteristics and eliminate the potential

outliers. The clinical features of individuals from the UK Biobank used in the current

study are shown in Table 1. The chosen datasets have 1277 individuals, with in total

of 14 genes with 10kbp flanking regions added to both ends, 74 haplotype blocks and

1821 SNPs. The haplotype blocks were parsed based on the confidence interval

method (Gabriel et al., 2002). More details regarding individual covariants pre-

selection and haplotype block parsing can be referred to the Methods section.

Cross-haplotype block epistasis

Unlike the simulated datasets, the interacting haplotype blocks are not known in the

real datasets. One of the common approaches to validate the proposed framework's

prediction and interpretation is to find previous works that report genes and epistatic

relationships on the related disease. Afterwards, the objective is to map the framework

haplotype block outputs to the target genes. In the UK Biobank, using HB-LT, we

observed 7 pairwise interaction candidates. All interaction candidates of the HbA1c

phenotype and their corresponding attention scores were listed in the first two

columns of Table 2. The threshold is set as attention scores higher than 0.1. There are

no standard ways to choose the attention threshold. For the future studies, researchers

can set the threshold wherever they think that fits their hypothesis.

We then investigate whether the interaction candidates discovered by HB-LT can be

detected by other methods. Similarly to the simulation dataset section, we trained

GWAS_NN and recorded the interaction scores for each interaction candidate in the

third column in Table 2. Not all signals detected by HB-LT can also be mapped out by

GWAS_NN as significant. This could potentially highlight that HB-LT can detect

novel signals which can be overlooked by other methods. Finally, We then check if

any of the gene interactions have already been recorded in the previous studies, shown

in the last column of Table 2.

Within-haplotype SNP epistasis

One of the key advantages of HB-LT compared to other multi-dimensional reduction

methods is that it trains each SNP individually before pooling them into a fixed

haplotype representation. This approach preserves the haplotype structure during the

training process, allowing us to monitor not only potential cross-haplotype

interactions but also SNP interactions within each haplotype block. Indeed, it is

believed that SNPs within a functional region have a higher chance to interact with

each other and influence the phenotype (Ma, Clark and Keinan, 2013). We listed all

the within-haplotype SNP interaction candidates, gene names and attention scores in

the first three columns of Table 3. By setting the threshold > 0.05, there are 16 within

haplotype block pairwise SNP interactions observed. Similarly, we compared the

within-haplotype pairwise SNP interaction results obtained from HB-LT with those

identified using the previously published exhaustive search method, MatrixEpistasis

and recorded the *p-value* in the last column of Table 3.

In summary, leveraging pre-selected HbA1c-associated genes from the UK Biobank,

we explore the potential real-world application of HB-LT. Future studies are essential

to statistically and biologically validate our current findings. Additionally, further

investigation is warranted to assess the feasibility of HB-LT in hypothesis-free, large-

scale genetic datasets.

5. Discussion

The current existing approaches for detecting interactions in genetic study face several

challenges including: (i) to reduce the "curse of dimensionality", genes are typically

represented as the most important SNPs while ignoring the potential effects of

neighbouring SNPs. (ii) only restrictive forms of interactions are considered. (iii)

while scalable methods like PCA have been proposed to reduce the multidimensional

SNP data into a one-dimensional representation, these techniques often neglect

important phenotype-related information. Additionally, such methods make it difficult

to analyse the internal structure of each condensed multi-SNP unit in relation to the

phenotype. Indeed, there is a need for a framework that integrates genetic block

representation learning with the modelling of both intra- and inter-block interactions

within an end-to-end model. Here, we proposed a deep learning genetic block

detection method, Haplotype Block LSTM hierarchical Transformer (HB-LT). HB-LT

can hierarchically encode genetic SNP sequences. In HB-LT, each SNPs in

relationship to its surrounding SNPs within each genetic block were learned by a

multi-attention head. Next, a pooling method is applied to get a fixed representation of

each genetic block, cross genetic block relationships via an attention method were

then mapped as opposed to concatenating dimensional condensed genetic units into

flat sequences and then fed into the model. This approach enables the model to

dynamically learn richer structural dependencies among SNPs within each genetic

block and effectively incorporate these insights into the inter-genetic block layer. In

the experimental work, the results obtained from HB-LT were compared with both

exhaustive searching (MatrixEpistasis) and deep learning methods (GWAS_NN). The

current study shows that HB-LT exhibits a better performance for epistasis detections

in both simple and complex epistasis models. Moreover, HB-LT was also tested on

HbA1c in the UK Biobank to assess its application in a real-world scenario.

The current proposed deep learning framework may have many attractive features, but

it also has several shortcomings. First, it should be noted, that although the potential

applications of attention weights in transformer as an indicator of epistasis have been

studied and demonstrated in recent years (Reyes et al., 2022; Graça et al., 2024), these

weights cannot be directly interpreted as measurements of epistasis levels in genetics.

While these weights can highlight regions of interest in relation to the phenotype, the

focus of attention mechanisms is on capturing token dependencies and relevant

patterns in the dataset to improve outcome predictions, not necessarily to isolate or

quantify specific genetic interactions. Moreover, the intricate relationship between

statistical and biological epistasis adds an additional layer of complexity (Moore and

Williams, 2005; Ebbert, Ridge, and Kauwe, 2015). The disparity between these two

models of epistasis often obscures the biological relevance and implications of

statistical findings, making it challenging to draw clear, meaningful conclusions about

the underlying genetic mechanisms. Indeed, we view our proposed HB-LT framework

as a tool for mining and filtering large datasets. Regions of interest identified by HB-

LT should be further investigated and validated through more targeted statistical

methods and potential complementary biological experiments. Second, the potential

covariants, such as age and population genetic structure are not directly incorporated

in the current model, instead, a PCA-based pre-filtering stage was applied to minimise

the confounding effects. By implementing this approach, we minimised the risk of

extraneous factors contaminating the HB-LT model outputs, making the results more

straightforward to interpret. However, this adjustment means that the HB-LT model

will not be applied to the full dataset size, potentially leading to a loss of information.

Additionally, this change may introduce new complexities for future users. The

challenge of how to incorporate potential covariates into the model remains an open

question that needs to be addressed. Finally, the potential of whole-genome

hypothesis-free epistasis studies to significantly enhance outcome prediction has been

a topic of debate and scepticism for decades. Several studies (González-Camacho et

al., 2012; Mäki-Tanila and Hill, 2014 and Wei et al., 2014) have demonstrated that

despite the possible biological ubiquity of epistasis, the total genetic variance of

polygenic traits is likely largely to be explained by the "additive top SNPs model".

However, other studies (Dudley and Johnson, 2009; Hu et al., 2011; Álvarez-Castro et

al., 2012; Wang et al., 2012) conducted showed that the inclusion of epistatic effect

networks for prediction improved prediction over the use of additive effects only.

Indeed, we do not intend to propose HB-LT as a replacement for the "top SNPs

approach". This study is not aimed at comparing epistasis and non-epistasis models

for outcome prediction. Instead, HB-LT serves as a complementary tool designed to

uncover interactions that might otherwise be overlooked, potentially revealing novel

genetic structures underlying complex disease development and leading to the

discovery of new markers.

6. Conclusion

For the past decades, Genome-wide Association Studies (GWAS) have successfully

identified thousands of risk alleles for complex diseases. Despite this, it usually failed

to capture the statistical epistasis i.e. interaction between SNPs, which is

acknowledged as a fundamental factor for understanding complex disease genetic

pathways. Traditional epistasis searching tools often suffer from computational burden

and lack of calculation power. Moreover, it has become increasingly recognized that

leveraging the combined effects of SNP groups within specific genetic blocks for

epistasis searching can yield greater phenotypic variance than focusing on individual

SNPs alone. However, to our best knowledge, there is yet a framework that has been

proposed that can incorporate this hierarchical genetic structure to form an end-to-end

model for epistasis searching. Here, we proposed HB-LT, which takes advantage of

the haplotype block structure existing in the genome to reduce the dimensionality of

SNP features and increase statistical power. Haplotype block is not the only way to

measure SNP dependencies and grouping, the impact of different methods for

epistasis study should be investigated in the future.

7. Acknowledgement

Funding: G.A.R. was supported by a Wellcome Trust Investigator Award

(WT212625/Z/18/Z), MRC Programme grant (MR/R022259/1), Diabetes UK (BDA

16/0005485) and NIH-NIDDK (R01DK135268) project grants, a CIHR-JDRF Team

grant (CIHR-IRSC TDP-186358 and JDRF 4-SRA-2023-1182-S-N), CRCHUM start-

up funds, and an Innovation Canada John R. Evans Leader Award (CFI 42649). A.B.

was supported by the Canada Research Chairs program.

Duality of Interest: G.A.R. has received grant funding from, and is a consultant for,

Sun Pharmaceuticals Inc. All other authors declare that there are no relationships or

activities that might bias, or be perceived to bias, their work.

Contribution Statement: The current project was designed by S.L. and S.A. under

the supervision of G.A.R. and with professional support from P.H., J.T., A.B. and B.L.

The current model (HB-LT) was designed by S.L. and S.A. The source code was

written by S.A. and S.L. The model training and testing were performed by S.L. and

S.A. The real-world cohort genetic datasets were organized, maintained and queried

by R.A. The manuscript was written by S.L.

8. References

Ahmed, F. S., Aly, S. and Liu, X. (2024). EPI-Trans: an effective transformer-based

deep learning model for enhancer promoter interaction prediction. BMC

Bioinformatics, 25 (1), p.216.

Álvarez-Castro, J. M. et al. (2012). Modelling of genetic interactions improves

prediction of hybrid patterns--a case study in domestic fowl. Genetics Research, 94

(5), pp.255–266.

Auton, A. and Salcedo, T. (2015). The 1000 Genomes Project. Assessing Rare

Variation in Complex Traits, pp. 71–85. doi:10.1007/978-1-4939-2824-8_6.

Bayat, A. et al. (2021). Fast and accurate exhaustive higher-order epistasis search with

BitEpi. Scientific Reports, 11 (1), p.15923.

Burton, P.R. et al. (2007). Genome-wide association study of 14,000 cases of seven

common diseases and 3,000 shared controls. Nature, 447(7145), pp.661–678.

doi:10.1038/nature05911.

Chen, H. et al. (2020). A fast-linear mixed model for genome-wide haplotype

association analysis: application to agronomic traits in maize. BMC Genomics, 21 (1),

p.151.

Chen, Y. et al. (2023). Molecular language models: RNNs or transformer? Briefings

in Functional Genomics, 22 (4), pp.392–400.

Cordell, H. J. (2002). Epistasis: what it means, what it doesn't mean, and statistical

methods to detect it in humans. Human Molecular Genetics, 11 (20), pp.2463–2468.

Cui, T. et al. (2022). Gene-gene interaction detection with deep learning.

Communications Biology, 5 (1), p.1238.

Cui, T. et al. (2022). Gene–gene interaction detection with deep learning.

Communications Biology, 5(1). doi:10.1038/s42003-022-04186-y.

De Franco, E. et al. (2020). Update of variants identified in the pancreatic β-cell

KATP channel genes KCNJ11 and ABCC8 in individuals with congenital

hyperinsulinism and diabetes. Human Mutation, 41 (5), pp.884–905.

Dudley, J. W. and Johnson, G. R. (2009). Epistatic models improve prediction of

performance in corn. Crop Science, 49 (4), pp.1533–1533.

Ebbert, M. T. W., Ridge, P. G. and Kauwe, J. S. K. (2015). Bridging the gap between

statistical and biological epistasis in Alzheimer's disease. BioMed Research

International, 2015, p.870123.

Gabriel, S.B. et al. (2002). The structure of haplotype blocks in the human genome.

Science, 296(5576), pp.2225–2229. doi:10.1126/science.1069424.

González-Camacho, J. M. et al. (2012). Genome-enabled prediction of genetic values

using radial basis function neural networks. TAG. Theoretical and Applied Genetics,

125 (4), pp.759–771.

Graça, M. et al. (2023). Interpreting High Order Epistasis Using Sparse Transformers.

[Online]. Available at: https://ieeexplore.ieee.org/document/10183767.

Graça, M. et al. (2024). Distributed transformer for high order epistasis detection in

large-scale datasets. Scientific Reports, 14 (1), p.14579.

Hill, W.G. and Robertson, A. (1968). Linkage disequilibrium in finite populations.

Theoretical and Applied Genetics, 38(6), pp.226–231. doi:10.1007/bf01245622.

Hu, Z. et al. (2011). Genomic value prediction for quantitative traits under the

epistatic model. BMC Genetics, 12, p.15.

Jubair, S. et al. (2021). GPTransformer: A Transformer-Based Deep Learning Method

for Predicting Fusarium Related Traits in Barley. Frontiers in Plant Science, 12,

p.761402.

Li, J. et al. (2009). Identification of gene-gene interaction using principal components.

BMC Proceedings, 3 Suppl 7 (Suppl 7), p.S78.

Liu, Y. and Lapata, M. (2019). Hierarchical Transformers for Multi-Document

Summarization. arXiv [cs.CL]. arXiv [Online]. Available at:

http://arxiv.org/abs/1905.13164.

Ma, L., Clark, A. G. and Keinan, A. (2013). Gene-based testing of interactions in

association studies of quantitative traits. PLoS Genetics, 9 (2), p.e1003321.

Maher, B. (2008). Personal genomes: The case of the missing heritability. Nature, 456

(7218), pp.18–21.

Mäki-Tanila, A. and Hill, W. G. (2014). Influence of gene interaction on complex trait

variation with multilocus models. Genetics, 198 (1), pp.355–367.

Meigs, J. B. et al. (2002). A genome-wide scan for loci linked to plasma levels of

glucose and HbA(1c) in a community-based sample of Caucasian pedigrees: The

Framingham Offspring Study. Diabetes, 51 (3), pp.833–840.

Mieth, B. et al. (2021). DeepCOMBI: explainable artificial intelligence for the

analysis and discovery in genome-wide association studies. NAR Genomics and

Bioinformatics, 3 (3), p.lqab065.

Moore, J. H. and Williams, S. M. (2005). Traversing the conceptual divide between

biological and statistical epistasis: systems biology and a more modern synthesis.

BioEssays, 27 (6), pp.637–646.

Morris, R. W. and Kaplan, N. L. (2002). On the advantage of haplotype analysis in the

presence of multiple disease susceptibility alleles. Genetic Epidemiology, 23 (3),

pp.221–233.

Nathan, D. M., Turgeon, H. and Regan, S. (2007). Relationship between glycated

haemoglobin levels and mean glucose levels over time. Diabetologia, 50 (11),

pp.2239–2244.

Niel, C. et al. (2015). A survey about methods dedicated to epistasis detection.

Frontiers in Genetics, 6, p.285.

Oishi, Y. and Manabe, I. (2018). Krüppel-Like Factors in Metabolic Homeostasis and

Cardiometabolic Disease. Frontiers in Cardiovascular Medicine, 5, p.69.

Pérez-Enciso, M. and Zingaretti, L. M. (2019). A Guide for Using Deep Learning for

Complex Trait Genomic Prediction. Genes, 10 (7). [Online]. Available at:

doi:10.3390/genes10070553.

Piñero, J. et al. (2015). DisGeNET: a discovery platform for the dynamical

exploration of human diseases and their genes. Database: the journal of biological

databases and curation, 2015 (0), p.bav028.

Purcell, S. et al. (2007). PLINK: a tool set for whole-genome association and

population-based linkage analyses. The American Journal of Human Genetics, 81 (3),

pp.559–575.

Reyes, D. M. et al. (2022). Genomics transformer for diagnosing Parkinson's disease.

IEEE-EMBS International Conference on Biomedical and Health Informatics. IEEE-

EMBS International Conference on Biomedical and Health Informatics, 2022.

[Online]. Available at: doi:10.1109/bhi56158.2022.9926815.

Snieder, H. et al. (2001). HbA(1c) levels are genetically determined even in type 1

diabetes: evidence from healthy and diabetic twins. Diabetes, 50 (12), pp.2858–2863.

Stančáková, A. and Laakso, M. (2016). Genetics of Type 2 Diabetes. Endocrine

Development, 31, pp.203–220.

Su, Z., Marchini, J. and Donnelly, P. (2011). Hapgen2: Simulation of multiple disease

snps. Bioinformatics, 27(16), pp.2304–2305. doi:10.1093/bioinformatics/btr341.

Turton, J. C. et al. (2011). Investigating statistical epistasis in complex disorders.

Journal of Alzheimer's Disease, 25 (4), pp.635–644.

Vaswani, A. et al. (2017). Attention Is All You Need. arXiv [cs.CL]. arXiv [Online].

Available at: http://arxiv.org/abs/1706.03762.

Wang, D. et al. (2012). Prediction of genetic values of quantitative traits with epistatic

effects in plant breeding populations. Heredity, 109 (5), pp.313–319.

Wei, W.-H., Hemani, G. and Haley, C. S. (2014). Detecting epistasis in human

complex traits. Nature Reviews Genetics, 15 (11), pp.722–733.

Wheeler, E. et al. (2017). Impact of common genetic determinants of Hemoglobin

A1c on type 2 diabetes risk and diagnosis in ancestrally diverse populations: A

transethnic genome-wide meta-analysis. PLoS Medicine, 14 (9), p.e1002383.

World Health Organization. (2011). Glycated haemoglobin (HbA1c) for the diagnosis

of diabetes.

Wright, F.A. et al. (2007). Simulating Association Studies: A data-based resampling

method for candidate regions or whole genome scans. Bioinformatics, 23(19),

pp.2581–2588. doi:10.1093/bioinformatics/btm386.

Zaykin, D. V. et al. (2002). Testing association of statistically inferred haplotypes

with discrete and continuous traits in samples of unrelated individuals. Human

Heredity, 53 (2), pp.79–91.

Zhou, J. et al. (2022). Deep learning predicts DNA methylation regulatory variants in

the human brain and elucidates the genetics of psychiatric disorders. Proceedings of

the National Academy of Sciences of the United States of America, 119 (34),

p.e2206069119.

Zhu, S. and Fang, G. (2018). Matrixepistasis: Ultrafast, exhaustive epistasis scan for

quantitative traits with covariate adjustment. Bioinformatics, 34(14), pp.2341–2348.

doi:10.1093/bioinformatics/bty094.

Figure Legend

Figure 1. Pipeline of our within and cross haplotype block epistasis detection

method (HB-LT). The haplotype dataset was first selected by Long short-term

memory (LSTM) to obtain the potential phenotype-associated haplotype blocks

(HBs). These candidates are then fed into the Hierarchical transformer encoder to

obtain the within and cross-haplotype block attention weights, which could be

subjected to the following analysis for potential epistasis signal discoveries.

Figure 2. The overall pipeline of the hierarchical haplotype transformer

encoder.

Figure 3. Long short-term memory (LSTM) selects potential phenotype-

associated haplotype block candidates on both simple and complex epistasis

models using simulated datasets. Each haplotype block was independently trained

and tested by the LSTM model. The root mean square error (RMSE) of the testing

datasets was plotted along with the mean and standard deviation (SD). To evaluate the

model's performance with different haplotype block lengths, the process was repeated

(n=10). For each iteration, the area under the curve (AUC) of the model's predictions

was plotted against the ground truth.

Figure 4. The hierarchical transformer encoder distinguishes epistasis signals in

a complex epistasis model using simulated datasets. Pre-selected haplotype block

candidates identified by the long short-term memory (LSTM) model were

subsequently processed by the hierarchical transformer encoder. (a) Training and

testing loss, and root mean square error (RMSE) for a single record. (b) Box plot

showing the RMSE for training and testing datasets (n=10). (c) The area under the

curve (AUC) for the complex epistasis signals predicted by the hierarchical

transformer encoder, compared to the ground truth.

Figure 5. The comparison of HB-LT with state-of-art Epistasis searching

methods, MatrixEpistasis (Zhu and Fang, 2017) and GWAS_NN (Cui et al.,

2022) in both simple and complex epistasis models with n=10.

Table 1. Characteristics of the included individuals of the cohorts.

Clinical Features	UK Biobank (n=1277) (Mean+-SD)
Age of diabetes diagnosis	56.3+-3.0
Duration (year)	4.0+-2.4
Diastolic blood pressure	83.0+-5.1
Systolic blood pressure	142.0+-8.8
Sex (Male: Female)	482:795

797 Table 2. Cross-haplotype blocks attention in UK Biobank by two independent

798 methods.

Phenotype	Genes	Haplo Block*	HB-LT Attention Scores (UK	GWAS_N N Interactio n Scores	References

			Biobank)	(UK Biobank)	
HbA1c	LOC112268412, KLF11, CYS1; GCK, LOC10537 5257, YKT6	H2, H11	0.23	0.0012	Oishi and Manabe, 2018
	LOC112268412, KLF11, CYS1; BLK	H2, H15	0.22	0.17	NA
	BLK, LOC10537 9241; NSMCE2	H23, H30	0.13	0.09	NA
	NSMCE2	H30, H31	0.30	0.23	
	CEL;	H34, H41	0.13	0.19	NA

	KCNJ11				
	CEL; NCR3LG 1, KCNJ11	H34, H40	0.12	0.19	NA
	ABCC8; KCNJ11	H40, H42	0.12	0.008	De Franco et al., 2020

799   * Full length of each Haplotype block seen in Supplemental material.

801   Table 3. Within haplotype block SNP attention in UK Biobank by both HB-LT and

802   MatrixEpistasis.

Phenotype	Genes	Pairwise SNPs	Attention Scores (UK BioBank) HB-LT	P-value (UK BioBank) MatrixEpistasis
HbA1c	NA	rs6756950, rs7420169	0.11	0.00037
	HNF4A	rs736820, rs736824	0.11	0.00046

	GCK	rs2908285, rs118180640	0.09	0.00023
	YKT6, GCK	rs1814253, rs118180640	0.07	0.00163
	GCK, NA	rs118180640, rs758983	0.07	0.00091
	NEUROD1, NA	rs12053195, rs6756950	0.06	0.052
	NA, NEUROD1	rs6756950, rs12052558	0.05	0.002
	NA, NEUROD1	rs6756950, rs16867467	0.05	0.0002

HB-LT

Hierarchical haplotype transformer encoder

Epistasis model 1

Epistasis model 2

Epistasis model 3

Complex Epistasis model (model1+2+3)

a.

b.

c.

ROC AUC of HB-LT and baseline models