Cross-dataset Evaluation of Dementia
Longitudinal Progression Prediction Models

Chen Zhang[1,2,4], Lijun An[1,2,4], Naren Wulan[1,2,4], Kim-Ngan Nguyen[1], Csaba Orban[1,2,4], Pansheng Chen[1,2,4], Christopher Chen[6], Juan Helen Zhou[1,2,3,5], Keli Liu[7], B.T. Thomas Yeo[1,2,3,4,5,8]

for the Alzheimer's Disease Neuroimaging Initiative* and the Australian Imaging Biomarkers and Lifestyle Study of Aging*

[1] Centre for Sleep and Cognition (CSC) & Centre for Translational Magnetic Resonance Research (TMR), Yong Loo Lin School of Medicine, National University of Singapore, Singapore [2] Department of Electrical and Computer Engineering, National University of Singapore, Singapore [3] Department of Medicine, Healthy Longevity Translational Research Programme, Human Potential Translational Research Programme & Institute for Digital Medicine (WisDM), Yong Loo Lin School of Medicine, National University of Singapore, Singapore [4] N.1 Institute for Health, National University of Singapore, Singapore [5] Integrative Sciences and Engineering Programme (ISEP), National University of Singapore [6] Memory Aging and Cognition Centre, Department of Pharmacology, Yong Loo Lin School of Medicine, National University of Singapore, Singapore [7] Company A, Berkeley, CA, USA [8] Martinos Center for Biomedical Imaging, Massachusetts General Hospital, Charlestown, MA, USA

Address correspondence to:

B.T. Thomas Yeo

CSC, TMR, ECE, N.1 & WISDM

National University of Singapore

Email: thomas.yeo@nus.edu.sg

*Data used in preparation of this article were obtained from the Alzheimer's Disease Neuroimaging Initiative (ADNI) database (adni.loni.usc.edu) and the Australian Imaging Biomarkers and Lifestyle Study of Aging (AIBL) database (https://aibl.org.au/). As such, the investigators within the ADNI and AIBL contributed to the design and implementation of ADNI and AIBL and/or provided data but did not participate in analysis or writing of this report. A complete listing of ADNI and AIBL investigators can be found at https://adni.loni.usc.edu/wp-content/uploads/how_to_apply/ADNI_Acknowledgement_List.pdf and https://aibl.org.au/

Abstract

Introduction: Accurately predicting Alzheimer's Disease (AD) progression is useful for clinical

care. The 2019 TADPOLE (The Alzheimer's Disease Prediction Of Longitudinal Evolution)

challenge evaluated 92 algorithms from 33 teams worldwide. Unlike typical clinical prediction

studies, TADPOLE accommodates (1) variable number of observed timepoints across patients, (2)

missing data across modalities and visits, and (3) prediction over an open-ended time horizon,

which better reflects real-world data. However, TADPOLE only used the Alzheimer's Disease

Neuroimaging Initiative (ADNI) dataset, so how well top algorithms generalize to other cohorts

remains unclear.

Methods: We tested five algorithms in three external datasets covering 2,312 participants and

13,200 timepoints. The algorithms included FROG, the overall TADPOLE winner, which utilized

a unique Longitudinal-to-Cross-sectional (L2C) transformation to convert variable-length

longitudinal histories into feature vectors of the same length across participants (i.e., same-length

feature vectors). We also considered two FROG variants. One variant unified all XGBoost models

from the original FROG with a single feedforward neural network (FNN), which we referred to as

L2C-FNN. We also included minimal recurrent neural networks (MinimalRNN), which was

ranked second at publication time, as well as AD Course Map (AD-Map), which outperformed

MinimalRNN at publication time. All five models – three FROG variants, MinimalRNN and AD-

Map – were trained on ADNI and tested on the external datasets.

Results: L2C-FNN performed the best overall. In the case of predicting cognition and ventricle

volume, L2C-FNN and AD-Map were the best. For clinical diagnosis prediction, L2C-FNN was

the best, while AD-Map was the worst. L2C-FNN also maintained its edge over other models,

regardless of the number of observed timepoints, and regardless of the prediction horizon from 0

to 6 years into the future.

Conclusions: L2C-FNN shows strong potential for both short-term and long-term dementia

progression   prediction.   Pretrained   ADNI   models   are   available:

https://github.com/ThomasYeoLab/CBIG/tree/master/stable_projects/predict_phenotypes/Zhang20

25_L2CFNN.

Keywords: Alzheimer's disease, longitudinal progression modelling, domain generalization,

recurrent neural networks, XGBoost, feature engineering

1   Introduction

Alzheimer's disease (AD) is a devastating neurodegenerative disorder (Jack et al., 2018;

Hampel et al., 2021), which progresses over many years from a preclinical phase to a fully

manifested clinical syndrome (Villemagne et al., 2013). There is no cure for AD, although

medications exist to slow down cognitive decline in early AD (Van Dyck et al., 2023). The

growing consensus is that early intervention is critical for slowing or stopping disease progression

(Dubois et al., 2016; Scheltens et al., 2016; Aisen et al., 2022), and for enabling earlier caregiver

planning (de Vugt & Verhey, 2013; Rasmussen & Langerman, 2019; Porsteinsson et al., 2021) as

well as more efficient clinical trial enrollment (Burns et al., 2021; Oxtoby et al., 2022). Therefore,

predicting AD progression is an important task (Zhang et al., 2017; Venkatraghavan et al., 2019).

The Alzheimer's Disease Prediction Of Longitudinal Evolution (TADPOLE) challenge [1]

(Marinescu et al., 2019, 2021) evaluated 92 algorithms from 33 teams worldwide for predicting

AD progression. Given multimodal biomarkers at one or more timepoints, the goal was to predict

cognition, ventricular volume and clinical diagnosis of an individual every month into the future.

The TADPOLE challenge was run only on the Alzheimer's Disease Neuroimaging Initiative

(ADNI) dataset, so the current study seeks to evaluate the cross-dataset performance of several

strong algorithms.

There are three key differences between the TADPOLE setup and most existing AD

prediction studies. First, many studies use data from only a fixed number of timepoints (often just

one) to predict future outcomes (Hebling Vieira et al., 2022; Hett et al., 2021; Wang et al., 2022).

In practice, patients have varying numbers of visits, e.g., Patient A has three visits, while Patient B

has only one. Limiting analyses to a single timepoint to accommodate Patient B wastes valuable

information from Patient A. In contrast, TADPOLE encourages algorithms to leverage the full

visit histories, which vary in length across participants. Second, many studies restrict their

analyses to participants with complete multimodal data at all timepoints (Golovanevsky et al.,

2022; Wang et al., 2022; Reas et al., 2023). But in clinical settings, not every patient undergoes

every assessment (e.g., imaging, cognitive testing) at every visit. Discarding timepoints with

incomplete data overlooks useful information. TADPOLE instead promotes using all available

time points, even when some modalities are missing. Third, most studies predict a single outcome

within a predefined window. For example, a typical mild cognitive impairment (MCI) progression

task is to predict whether an MCI patient will develop dementia within three years (Basaia et al.,

[1] The TADPOLE challenge website: https://tadpole.grand-challenge.org/. Note that the website may not be actively updated. In addition, even though the goal is to predict indefinitely into the future, evaluation can only be performed on the finite number of timepoints available in a dataset.

2019; El-Sappagh et al., 2021; Ocasio & Duong, 2021). The TADPOLE challenge, by contrast, requires forecasting monthly outcomes indefinitely into the future, which could then be flexibly used to answer specific clinical questions, such as the MCI progression task. Overall, unlike most existing studies, TADPOLE accommodates (1) a variable number of observed timepoints per patient, (2) missing data across modalities and visits, and (3) prediction over an open-ended time horizon. These features make it better aligned with the complexities of real-world clinical prediction.

There are two classes of existing algorithms naturally suited for the TADPOLE setup. The first class of models is dynamical state models, such as recurrent neural networks (RNNs; Ghazi et al., 2019; Nguyen et al., 2020; Jung et al., 2021; Liang et al., 2021; Xu et al., 2022; Cheng et al., 2024), where an individual's latent state is represented by a vector, thus providing a rich encoding of an individual's "disease state" beyond a single integer (such as in discrete state hidden Markov models). At each timepoint, observations are used to update the latent state of the individual at that timepoint. The latent state is in turn used to predict observations at the next time point. If some (or even all) observations are missing at the next time point, the model predictions can be used to fill in the missing data. Therefore, predicting missing data and future disease progression are unified into a single prediction task. This "model-filling" strategy was introduced by the MinimalRNN (Nguyen et al., 2020) and adopted by several subsequent studies (Jung et al., 2021; Liang et al., 2021; Xu et al., 2022; Cheng et al., 2024). MinimalRNN was evaluated by the TADPOLE organizers on their non-public ADNI test set, and was found to rank second at publication time (Nguyen et al., 2020). As such, the current benchmarking study included MinimalRNN because it is an influential algorithm whose performance has been evaluated in truly unseen data.

The second class of models is inspired by theoretical models of sigmoidal evolution of AD biomarkers (Jack et al., 2010; Villemagne et al., 2013; Selkoe & Hardy, 2016). These approaches fit parametric sigmoid-like functions to longitudinal biomarkers. Mixed-effects models capture group-level trends as fixed effects and individual variations as random effects (Iddi et al., 2019; Li, Iddi, et al., 2019; Oxtoby, 2023). Jedynak and colleagues used dynamic time-warping to align individual biomarker data to a group template represented by sigmoid curves (Jedynak et al., 2012). A Bayesian extension incorporated individual-specific latent time shifts (Bilgel et al., 2019). This line of research was extended to fit a constrained generalized sigmoidal function (Ghazi et al., 2021). A disease course mapping framework integrating Riemannian geometry and mixed-effects modeling with time reparameterization, known as AD course map (AD-Map; Koval et al., 2021) was shown to outperform 56 TADPOLE algorithms, including MinimalRNN, for predicting cognition (Maheux et al., 2023). Given the promise of the AD-Map algorithm, we also included AD-Map in the current benchmarking study.

In contrast to previous algorithms, the TADPOLE winner FROG utilized a longitudinal-to-
cross-sectional (L2C) transformation (Nanopoulos et al., 2001; Deng et al., 2013; Barandas et al.,
2020) to convert the longitudinal data into a cross-sectional format. Although the number of input
features was initially different across participants (because of varying number of visits), the
number of features was the same for all participants after L2C transformation (i.e., same-length
input features). An important benefit of L2C transformation is that many powerful algorithms (e.g.,
random forest, support vector machines, etc) cannot be applied to variable-length input features,
but could now be applied to the same-length L2C features. In the case of FROG, XGBoost
(eXtreme Gradient Boost; Chen & Guestrin, 2016) was used to predict disease progression with
the L2C features. The L2C transformation is relatively unique in the medical imaging community.
There have been studies that converted longitudinal MRI histories into brain atrophy rates (Jack et
al., 2004; Chincarini et al., 2016), but FROG's L2C transformation captured a richer set of
temporal statistics, such as past maximum and past minimum, in addition to rate of change (see
Section 2.6). A final benefit of the L2C transformation was the amount of missing data was greatly
reduced (see Section 2.6). In the TADPOLE challenge, FROG was the best for predicting clinical
diagnosis and the overall winner. However, FROG has only been tested in the ADNI dataset, so it
remains unclear how well it generalizes to new datasets.

In the current study, we trained the FROG algorithm on the ADNI dataset and evaluated its
performance in three external datasets comprising 2312 participants with 13200 timepoints from
the United States, Australia and Singapore. In the original FROG algorithm, separate XGBoost
models were trained for different forecast windows and target variables. Here we considered a
FROG variant that unified all XGBoost models with a single XGBoost model. Another FROG
variant unified all XGBoost models with a single feedforward neural network (FNN) model, which
we refer to as L2C-FNN. We also compared the FROG variants with a strong parametric modeling
algorithm AD-Map, and a strong dynamic state algorithm MinimalRNN.

2   Methods

2.1   Problem overview

The problem setup followed the TADPOLE challenge (Marinescu et al., 2019, 2021).
Given multimodal biomarkers and diagnostic history (Table 1) at one or more timepoints of an
individual, we aimed to predict the cognitive state, ventricle volume normalized by intracranial
volume (ICV), and clinical diagnosis of the individual for every subsequent month beyond the last
observed timepoint up to 120 months into the future. Cognitive state was measured with the
Alzheimer's Disease Assessment Scale Cognitive Subdomain (ADAS-Cog13) in the original
TADPOLE challenge. However, not all the external datasets had ADAS-Cog13, so we switched to
predicting mini mental state examination (MMSE) in this study.

We used four datasets: the Alzheimer's Disease Neuroimaging Initiative (ADNI) dataset,
the Australian Imaging Biomarkers and Lifestyle Study of Ageing (AIBL) dataset, the Memory,
Ageing and Cognition Centre (MACC) Harmonization Cohort, and the Open Access Series of
Imaging Studies (OASIS) dataset. These datasets consisted of longitudinal multimodal data, such
as T1-weighted structural MRI data, cognitive measurements and clinical diagnosis, as well as
baseline demographics. The diagnostic categories corresponded to cognitively normal (CN), mild
cognitive impairment (MCI), as well as dementia with various etiologies (DEM). Data collection
was approved by the Institutional Review Board (IRB) at each corresponding institution. The
analysis in the current study is approved by the National University of Singapore IRB.

Baseline features	Sex (male, female), Genetics (number of APOE-ε4 allele), Marital status (married, not married), Education level (number of years of education)	
Recurring features	MRI features	Hippocampus, Fusiform, Middle Temporal, Ventricle, Whole Brain, ICV
	Cognitive features	MMSE (0-30), CDR GLOBAL (0, 0.5, 1, 2, 3)
	Diagnostic features	Clinical diagnosis (CN, MCI, DEM)
	Demographics	Age

Table 1. Features used in the current study. ICV: intracranial volume. MMSE: mini mental state examination. CDR: Clinical Dementia Rating scale. CN: cognitively normal. MCI: mild cognitive impairment. DEM: Dementia with various etiologies. Note that FROG variants use all features. AD-Map was not developed to handle categorical variables or covariates, so do not utilize any of the baseline features or clinical diagnosis (see Section 2.5 for more details). MinimalRNN was not

developed to handle covariates, so do not utilize any baseline features and age (see Section 2.4 for more details).

2.2 Datasets, preprocessing and participant selection

2.2.1 Datasets

The ADNI dataset (Jack et al., 2008; Petersen et al., 2010) is a comprehensive multicenter
research initiative in the United States with three phases: ADNI1 (2004-2009), ADNI-GO/2
(2010-2016), and ADNI3 (2017-2023), with a primary focus on advancing the understanding of
Alzheimer's disease dementia. Each phase incorporates newly enrolled participants and individuals
transitioning from earlier phases. Notably, there are variations in MRI scanner models and
protocols across the phases, with ADNI1 primarily employing 1.5T scanners and subsequent
phases adopting 3T scanners (see Table S1 for details). T1 images were downloaded from the USC
Laboratory of Neuro Imaging's Image and Data Archive (IDA). The ADNIMERGE spreadsheet
(the ADNI team, 2023) containing various phenotypic data (e.g., demographics, clinical diagnoses,
cognitive measurements) was also downloaded.

The AIBL study (Fowler et al., 2021) is an Australian flagship initiative that shares a
similar goal and technical infrastructure with ADNI. MRI scans were acquired using both 1.5T and
3T (Avanto, Tim Trio and Verio) scanners (see Table S2 for details). MRI scans and phenotypic
data were obtained from the USC Laboratory of Neuro Imaging's Image and Data Archive (IDA).

The MACC Harmonization dataset (Hilal et al., 2020) focuses on a memory clinic
population in Singapore. T1 images in this dataset were acquired exclusively using 3T (Tim Trio
and Prisma) scanners (see Table S3 for details). Note that this dataset contained participants with
vascular dementia and/or Alzheimer's Disease dementia, which we have grouped together as
Vascular/Alzheimer's disease dementia (DEM). The mixed pathology allowed us to evaluate the
generalizability of these models beyond AD dementia. However, for completeness, we will also
report results for only AD dementia.

The OASIS dataset (LaMontagne et al., 2019) serves as a multimodal resource for studying
normal aging and cognitive decline. It consists of four releases: OASIS-1 (cross-sectional) and
OASIS-2 (longitudinal) as smaller-scale studies, OASIS-3 as the primary large dataset that
includes OASIS-1 and OASIS-2 subjects, and OASIS-4, which encompasses a separate clinical
cohort. For this study, we utilized OASIS-3 data. Note that this dataset included both AD and non-
AD dementia, which we have grouped together as DEM (similar to MACC). However, for
completeness, we will also report results for only AD dementia. The imaging data in OASIS were
acquired using both 1.5T and 3T scanners (see Table S4 for details). MRI scans and phenotypic
data were downloaded from the XNAT Central (Herrick et al., 2016).

2.2.2 Preprocessing

All T1 images were de-obliqued and reoriented to the RPI orientation. Subsequently, we
used the FreeSurfer 6.0 recon-all pipeline (Fischl et al., 2002; Desikan et al., 2006) to derive the
volumes of various regions of interest (ROIs). Following the FROG algorithm, we derived five
brain ROI volumetric features associated with AD-dementia, namely Hippocampal volume,
Fusiform volume, Middle Temporal (MidTemp) volume, Ventricle volume, and Whole Brain
volume (see Table S5 for details). We also incorporated ICV as an additional feature and
standardized the five brain ROI features with respect to ICV (Table 1).

The generated brain ROI features were then merged with downloaded phenotypic data (e.g.,
demographics, clinical diagnoses, cognitive measurements). Notably, non-MRI phenotypes (e.g.,
clinical diagnoses and cognitive measurements) and MRI scans might not have been performed on
the same day. Following the ADNIMERGE convention, if the non-MRI and MRI dates were
within 6 months of each other, then the non-MRI and MRI phenotypes were merged into one
timepoint corresponding to the non-MRI date.

We systematically eliminated empty or duplicate entries, along with those displaying
outliers or errors. Certain datasets used inconsistent coding for missing values, such as NaN or
special integers (e.g., -1, -4, 999). To ensure consistency, we replaced all special integers with
NaN. Consequently, we obtained a clean longitudinal data table where each row represents one
timepoint of a participant, containing MRI features and/or cognitive features and/or diagnostic
features (Table 1).

2.2.3 Participant selection and characteristics

Our objective was to predict the longitudinal progression of dementia, so across all four
datasets, we only included participants with recurring features (Table 1) at two or more timepoints.
We note that under this criterion, the recurring features did not need to all occur in the same
timepoints. For example, a participant with only MRI features in timepoint 1 and only cognitive
features in timepoint 2 was considered acceptable.

With the above selection criterion, the final ADNI dataset comprised 2111 participants
with a total of 15791 timepoints, including 9668 timepoints with MRI features. In the case of
AIBL, the final dataset comprised 402 participants with a total of 1220 timepoints, including 940
timepoints with MRI features. In the case of MACC, the final dataset comprised 650 participants
with a total of 3067 timepoints, including 1453 timepoints with MRI features. In the case of
OASIS, the final dataset comprised 1260 participants with a total of 8913 timepoints, including
2519 timepoints with MRI scans.

The demographics, disease severity and number of timepoints vary significantly between ADNI and the three external datasets (Table 2). Actual distributions are plotted in Figures S1 and S2. Compared with ADNI, the AIBL participants were younger and had higher MMSE scores. There were also proportionally more female and CN participants in the AIBL dataset than the ADNI dataset. Compared with ADNI, the MACC participants had lower MMSE scores. Furthermore, there were proportionally more female and participants with DEM diagnosis in MACC than ADNI. Finally, compared with ADNI, the OASIS participants were younger and had higher MMSE scores. There were also proportionally more female and CN participants in the OASIS dataset than the ADNI dataset.

Furthermore, both the AIBL and MACC datasets typically have fewer than 7 timepoints collected within a span of 7 years. In contrast, some participants in the ADNI and OASIS datasets have up to 20 to 30 timepoints, covering a tracking period of over 15 years. The percentage of timepoints with missing data was also highly different across the datasets (Table 2).

	ADNI (N = 2111)	AIBL (N = 402)		MACC (N = 650)		OASIS (N = 1260)	
	mean ± std	mean ± std	p	mean ± std	p	mean ± std	p
Baseline age (y)	73.3 ± 7.2	72.4 ± 6.7	**2.9e-2**	72.7 ± 7.9	7.8e-2	69.0 ± 9.0	**1.0e-4**
Baseline MMSE	27.4 ± 2.6	28.0 ± 2.8	**1.0e-4**	21.6 ± 6.0	**1.0e-4**	28.3 ± 2.5	**1.0e-4**
Sex (M/F)	1135 / 976 (54% / 46%)	157 / 176 (39% / 44%)	**2.9e-2**	286 / 364 (44% / 56%)	**1.6e-5**	560 / 700 (44% / 56%)	**2.0e-7**
Baseline diagnosis (CN/MCI/DEM)	745 / 995 / 371 (35%/47%/18%)	319 / 48 / 35 (79%/12%/9%)	**8.4e-60**	131 / 272 / 247 (20%/42%/38%)	**2.7e-29**	741 / 27 / 187 (59%/2%/15%)	**7.6e-138**
Baseline DEM (AD/Other dementias)	-	-	-	194 / 53 (79% / 21%)	-	53 / 134 (28% / 72%)	-
Cognitively Normal (CN)							
Baseline Age (y)	73.0 ± 6.2	72.1 ± 6.4	**2.5e-2**	68.4 ± 7.5	**1.0e-4**	68.3 ± 8.4	**1.0e-4**
Sex (M/F)	333 / 412 (45% / 55%)	125 / 148 (39% / 46%)	8.1e-1	58 / 73 (44% / 56%)	1.0	319 / 422 (43% / 57%)	5.6e-1
Mild Cognitive Impairment (MCI)							
Baseline age (y)	73.0 ± 7.5	75.2 ± 6.5	4.2e-2	72.9 ± 7.6	9.2e-1	71.8 ± 6.2	4.3e-1
Sex (M/F)	592 / 403 (59% / 41%)	22 / 14 (46% / 29%)	9.8e-1	130 / 142 (48% / 52%)	**7.1e-4**	15 / 12 (56% / 44%)	8.3e-1
Dementia (DEM)							
Baseline age (y)	74.6 ± 7.8	71.8 ± 8.8	5.2e-2	74.7 ± 7.7	8.4e-1	74.2 ± 7.3	6.1e-1
Sex (M/F)	210 / 161 (57% / 43%)	10 / 14 (29% / 40%)	2.2e-1	98 / 149 (40% / 60%)	**5.3e-5**	96 / 91 (51% / 49%)	2.8e-1
Number of visits	7.5 ± 4.5	3.0 ± 1.3	**1.0e-4**	4.7 ± 1.4	**1.0e-4**	7.1 ± 4.7	**1.7e-2**

Follow-up duration (y)	4.5 ± 3.4	3.3 ± 2.0	**1.0e-4**	3.9 ± 1.5	**1.0e-4**	7.8 ± 5.6	**1.0e-4**
Percentage of timepoints with missing data for recurring features							
CDR Global	28.6%	0.5%	**2.7e-101**	1.6%	**5.8e-224**	5.1%	**0.0**
MMSE	30.1%	0.4%	**1.4e-109**	1.7%	**7.6e-240**	16.6%	**2.3e-122**
MRI features	38.8%	23.0%	**5.9e-28**	52.6%	**4.6e-46**	71.8%	**0.0**
Diagnosis	30.2%	0.4%	**5.8e-110**	1.2%	**1.7e-249**	19.2%	**5.3e-80**

Table 2. Participant characteristics in the four datasets. Statistical tests were performed to compare ADNI and each external dataset. For continuous variables (e.g., age and MMSE), a permutation test was used. For discrete variables (e.g., sex and diagnosis), the chi square test was used. Bolded p values indicate statistical significance after correcting for multiple comparisons with false discovery rate (FDR) q < 0.05. Note that not all OASIS participants have clinical diagnosis at baseline, so the percentages of participants with baseline diagnosis do not add up to 100%.

2.3 Training, validation and test procedure

We compared five different models: MinimalRNN, AD-Map, original FROG (L2C-
XGBw), FROG variant 1 (L2C-XGBnw) and FROG variant 2 (L2C-FNN). We trained different
models using ADNI and evaluated their performance within the ADNI dataset (within-dataset
evaluation) and in AIBL, MACC and OASIS datasets (cross-dataset evaluation). More specifically,
we randomly divided the ADNI participants into 20 partitions. Since each participant contributed
data from multiple timepoints, care was taken to assign all timepoints from the same participant to
a single partition to prevent test set leakage. In other words, no participant's data was split across
multiple partitions.

To train a given model, 18 partitions were used for training, while 1 partition was used as a
validation set to tune the hyperparameters. The remaining partition was used as test set to evaluate
the within-cohort performance of the model. To ensure stability of results (Kong et al., 2019; Li,
Kong, et al., 2019; Varoquaux, 2018), this procedure was repeated 20 times with a different
partition being the test set (e.g., partition 5) and the partition next to it being the validation set (e.g.,
partition 6). Therefore, we ended up with 20 sets of trained models together with 20 sets of within-
cohort evaluation results. The 20 sets of trained models were applied to all participants in AIBL,
MACC, and OASIS for cross-cohort evaluation (Figure 1).

Following TADPOLE convention, for participants in the ADNI validation and test sets, as
well as all participants in AIBL, MACC, and OASIS, the first half of each participant's timepoints
were used to predict the second half of the same participant's timepoints. For example, if a
participant had 10 timepoints, then the first 5 timepoints were used as input (observed) timepoints,
and we sought to predict the second 5 timepoints (unobserved). On the other hand, the entire

longitudinal time series of training participants were used during training to increase data
efficiency.

The Optuna library (Akiba et al., 2019) was utilized to find the best hyperparameters by
maximizing model performance on the validation set. We note that this optimization was
performed independently for each training/validation/test split of the dataset. The hyperparameter
search spaces for each algorithm are described in their respective method sections.

Figure 1. Training and testing procedure. All models were trained on the ADNI dataset and subsequently applied to three unseen test datasets to assess generalizability. ADNI participants were randomly divided into training, validation, and test sets (ratio of 18:1:1) for hyperparameter tuning and within-cohort evaluation. This procedure was repeated 20 times to ensure result stability. Care was taken to ensure non-overlapping test sets, covering the entirety of the ADNI dataset across the 20 data splits. Trained models were then evaluated on participants from the three unseen test datasets (AIBL, MACC, and OASIS) for cross-cohort evaluation.

2.4   MinimalRNN

MinimalRNN is a recurrent neural network (RNN) with less parameters than LSTM (Long
short-term memory) to mitigate overfitting. In our previous study (Nguyen et al., 2020), we found
that MinimalRNN performed better than the more complex LSTM, as well as a simpler linear state
space model in the TADPOLE challenge. As such, the MinimalRNN struck the perfect complexity
balance, yielding the best prediction performance among the RNN models we tested.

In RNNs, the same computational unit is repeated at each time step, where the output at the
current step becomes the input at the next step. Therefore, the longitudinal data of a participant is
analyzed sequentially, where the input features at a particular timepoint is used to update the
internal "disease" state of the participant. This internal state is then used to predict the input
features at the next time point.

For our experiments, we utilized the publicly available code from
https://github.com/ThomasYeoLab/CBIG/tree/master/stable_projects/predict_phenotypes/Nguyen
2020_RNNAD. However, we replaced the HORD hyperparameter search algorithm (Eriksson et
al., 2019; Ilievski et al., 2017) employed in our previous study (Nguyen et al., 2020) with Optuna
(Akiba et al., 2019) because of its ease of use.

Table 3 summarizes the hyperparameters optimized by Optuna and their corresponding
search range. Consistent with the original study (Nguyen et al., 2020), MinimalRNN only utilized
the recurring MRI features, cognitive features and clinical diagnosis (Table 1), but not any
baseline features (sex, education, marital status and number of APOE-ε4) and age. Our previous
experiments (not shown) found that these additional information did not improve prediction
performance.

Hyper-parameter	Range
Input dropout rate	0-0.5
Recurrent dropout rate	0-0.5
L2 weight regularization	10^{-7}-10^{-5}
Learning rate	10^{-5}-10^{-2}
# hidden layers	1-3
Size of hidden state	128-512

Table 3. Hyper-parameters and corresponding search ranges for MinimalRNN estimated from the validation sets using Optuna.

2.5   AD Course Map (AD-Map)

AD-Map is a parametric Bayesian non-linear mixed-effects model designed to predict
cognition and brain atrophy. It was shown to outperform MinimalRNN (Maheux et al., 2023). AD-
Map assumes that each biomarker follows a logistic curve, with different biomarkers exhibiting
distinct progression rates and ages at inflexion point. The model adjusts these curves for each
individual by learning individual-specific shifts in disease onset, progression rates, and the
timing/ordering of biomarker progression. As a result, the model predicts an individual-specific set
of logistic curves, which show the value of each biomarker at any age of the participant.

For our experiments, we used the Leaspy software (https://gitlab.com/icm-
institute/aramislab/leaspy) and optimized hyperparameters (Table 4) via Optuna (Akiba et al.,
2019). We note that ICV was not included as a feature since AD-Map requires time-dependent
features, and ICV shows minimal change with time (Courchesne et al., 2000; Jenkins et al., 2000).
However, we remind the reader that the other MRI volumetric features were normalized with
respect to ICV, consistent with other algorithms.

Hyper-parameter	Range
Source dimension	1-5
# iterations	(1-10) * 500

Table 4. Hyper-parameters and corresponding search ranges for AD-Map estimated from the validation sets using Optuna.

Because AD-Map assumes that each biomarker follows a sigmoidal-like curve,
categorical variables (e.g., clinical diagnosis) cannot be used as an input or be predicted with AD-
Map (Maheux et al., 2023). To compare with models that predict clinical diagnosis, we converted
AD-Map's predicted CDR score into probabilities for CN, MCI, and DEM using standard cut-off
points (O'Bryant et al., 2010; Tariot et al., 2024): CDR 0 was mapped to CN, CDR 0.5 was
mapped to MCI, and CDR 1, 2, and 3 were mapped to DEM. For predicted CDR scores between 0
and 0.5, we used linear interpolation, so for instance, a CDR score of 0.1 resulted in 80%
probability for CN, 20% probability for MCI, and 0% probability for DEM. For scores between
0.5 and 1, we again used linear interpolation, so for instance, a CDR score of 0.6 resulted in 0%
probability for CN, and 80% probability for MCI, and 20% probability for DEM. CDR scores of 1
or higher are fully assigned to DEM.

We also explored the possibility of treating clinical diagnosis as a continuous variable by
setting CN to be 0, MCI to be 1 and DEM to be 2. This allowed clinical diagnosis to be included
as an input to AD-Map and also allowed diagnosis to be directly predicted. We found that this
approach improved clinical diagnosis prediction but led to very poor MMSE and ventricular
volume prediction. Therefore, consistent with the original study (Maheux et al., 2023), we did not
include clinical diagnosis in the AD-Map algorithm. Instead, we used the posthoc CDR-to-
Diagnosis conversion approach described above, which maintained AD-Map's original focus on
continuous biomarkers while allowing for comparisons of clinical diagnosis prediction.

Furthermore, the AD-Map package does not take in any baseline features (sex, education,
marital status and number of APOE-ε4), so in summary, the AD-Map only used recurring MRI
features (excluding ICV), cognitive features and age.

2.6   Original FROG: Longitudinal-to-Cross-sectional XGBoost with Windows (L2C-XGBw)

2.6.1   Longitudinal-to-Cross-sectional (L2C) transformation

The TADPOLE problem set up is challenging for standard machine learning algorithms
(e.g., support vector machine) because of the variable length of observed timepoints. The winner
of the TADPOLE challenge FROG used a feature engineering technique (Nanopoulos et al., 2001;

Deng et al., 2013; Barandas et al., 2020) that transformed the longitudinal visit history of
participants into a cross-sectional format, which we will refer to L2C (Longitudinal-to-Cross-
sectional) transformation.

More specifically, suppose for a given participant, we observed data at m timepoints t_1, t_2,
t_3, t_4, ..., t_m, and we would like to predict clinical diagnosis (or MMSE or ventricular volume) at a
future timepoint t_f. Note that these timepoints might not be equally spaced in time. To convert the
variable length input features, FROG proposed the following L2C transformation, in which each
continuous input modality (i.e., MMSE, CDR_GLOBAL, six anatomical ROI volumes) is
converted into seven features (Table 5) and clinical diagnosis is converted into eight features
(Table 6), resulting in 8 x 7 + 8 = 64 features.

The 64 L2C features were additionally augmented by age at future timepoint t_f, baseline
sex, baseline education level, baseline marital status, APOE status and number of months between
future timepoint t_f and the first (baseline) visit. In total, there were 64 + 6 = 70 features. Please
refer to Supplementary Table S6 for the complete set of L2C features used by FROG.

L2C feature names	Meaning
mr_fname	most recent measurement for feature
time_since_mr_fname	time since the most recent measurement
mr_change_fname	most recent change rate
low_fname	lowest historical measurement
time_since_low_fname	time since lowest historical measurement
high_fname	highest historical measurement
time_since_high_fname	time since highest historical measurement

Table 5. L2C feature names and their corresponding meaning for continuous input modalities.

L2C feature names	Meaning
mr_dx	most recent non-missing diagnosis
time_since_mr_dx	time since the most recent non-missing diagnosis
best_dx	best historical diagnosis
time_since_best_dx	time since best historical diagnosis
worst_dx	worst historical diagnosis
time_since_worst_dx	time since worst historical diagnosis
milder	1 if a milder diagnosis occurred in history
time_since_milder	time since the milder diagnosis and 999 if no milder diagnosis

Table 6. L2C feature names and their corresponding meaning for clinical diagnosis.

2.6.2 Theoretical benefits of the L2C transformation

We note that it is not the case that the L2C transformation necessarily reduced the number

of features. For a participant with the full set of multimodal data on two visits, the L2C

transformation would generate 70 features, while MinimalRNN and AD-Map would only have $9 \times$

$2 = 18$ and $8 \times 2 = 16$ features, respectively. For a participant with three complete visits, the L2C

transformation would again generate 70 features, while MinimalRNN and AD-Map would only

have $9 \times 3 = 27$ and $8 \times 3 = 24$ features, respectively.

In the above example, MinimalRNN had to deal with 18 features for a participant with two

complete visits and 27 features for a participant with three complete visits. On the other hand, the

L2C transformation always generates 70 features, regardless of whether a participant has one past

visit or ten past visits. This is a key benefit of L2C transformation because a wide range of

powerful machine learning models (e.g., random forests, support vector machines, etc) require the

same number of features for each participant. In the case of FROG, the powerful XGBoost model

was used (Section 2.6.4), while L2C-FNN utilized a fully connected feedforward network (Section

2.8). In other words, the L2C transformation gives the user great flexibility in choosing the

algorithm to be applied to the L2C features.

The L2C features also captured key aspects of a time series, including temporal trends (i.e.,

most recent change rate) and extreme values (lowest and highest historical measurements), which

are well-established summaries in time series feature extraction (Nanopoulos et al., 2001; Deng et

al., 2013; Barandas et al., 2020). For example, a rapid decline in hippocampal volume or extremely

low hippocampal volume might be predictive of progression to dementia. The inclusion of time-

varying covariates (e.g., "time since the most recent measurement" or "time since lowest historical

measurement") are necessary to compensate for the loss of temporal information when collapsing

the longitudinal history into cross-sectional features. For example, the lowest measured

hippocampal volume would be more useful if we also knew how far in the past the measurement

occurred.

While a broader set of transformations (e.g., standard deviation) could be considered, these

were not explored in the TADPOLE challenge, when FROG was first developed. To maintain

consistency with the original FROG algorithm and given the strong performance we already

observed, we did not introduce additional transformations in the current study. However, we

suspect that any sufficiently rich set of the time series summaries might be equally effective.

Another advantage of the L2C transformation is the reduction in missing data. For example,

the average ADNI participant has 7.5 visits. Let us consider a participant with eight visits, and the

first four visits were used to predict MMSE, ventricular volume and clinical diagnosis in the last

four visits. Suppose MMSE was only measured in two of the four input timepoints. In the case of

MinimalRNN, the missing MMSE values needed to be filled in by the MinimalRNN model (i.e., model filling). However, in the case of L2C transformation, all seven features associated with MMSE (Table 5) could be computed with just two MMSE measurements in the visit history. Even if there was only one MMSE measurement, there would only be one missing value out of the seven features associated with MMSE ("most recent change rate" in Table 5).

2.6.3 Data augmentation

In addition to the L2C transformation, FROG proposed the following data augmentation strategy during training. Suppose we observed data at m timepoints t_1, t_2, t_3, t_4, ..., t_m for a particular training participant. FROG then generated $m - 1$ training samples by using t_1 to predict t_2, or t_3 or t_4 or t_5 etc. FROG also generated another $m - 2$ training samples by using t_1 and t_2 to predict t_3 or t_4 or t_5 etc. In total, given m timepoints, FROG generated $m * (m - 1)/2$ training samples.

2.6.4 L2C eXtreme Gradient Boost with separate windows (L2C-XGBw)

The L2C transformation converted variable length input features into same-length input features for each participant (Section 2.6.1), while the data augmentation procedure generated more training samples (Section 2.6.3). The original FROG team used eXtreme Gradient Boost (XGBoost; Chen & Guestrin, 2016) to predict the target variables from the L2C features. Gradient boosting is a model ensemble of individual decision trees that are trained sequentially such that a new tree improves the error of the previous tree ensemble. XGBoost is an optimized distributed gradient boosting library. The original FROG submission used the XGBoost R library, while we reimplemented the FROG algorithm in python. We performed 5 repetitions of train/validation/test split in the ADNI dataset to ensure our python implementation yields numerically the same results as the R code.

Furthermore, consistent with the original FROG submission to the TADPOLE challenge, we trained separate XGBoost models for each target variable (clinical diagnosis, MMSE, ventricle volume). Following the original FROG submission, we also trained separate models based on specific forecast interval ranges, with the assumption that certain models may excel in short-term predictions while others in long-term forecasts. The forecast interval ranges (i.e., forecast windows) for each target variable (measured in months) adhere to the FROG team's settings (Table 7). Hence, we referred to this algorithm as L2C eXtreme Gradient Boost with separate windows (L2C-XGBw).

Target variables	Forecast Windows (months)
MMSE	0-9, 9-15, 15-27, 27-39, >54
Clinical diagnosis	0-8, 8-15, 15-27, 27-39, 39-60, >60
Ventricle volume	0-9, 9-15, 15-30, >30

Table 7. L2C-XGBw (FROG) trained a separate XGBoost model for each forecast window and each target variable.

374   Three important hyperparameters were tuned in the ADNI validation sets using Optuna
375 (Akiba et al., 2019). The three hyperparameters and search ranges are detailed in Table 8. We note
376 that there is no extra feature normalization or missing data imputation since the XGBoost package
377 handles such issues internally.

Hyper-parameter	Range
Max depth	3-8
Subsample rate	0.4-1
Learning rate (η)	0.01-0.2

Table 8. Hyper-parameters and corresponding search ranges for L2C-XGBw estimated from the validation sets using Optuna.

2.7   FROG variant 1: L2C eXtreme Gradient Boost with no window (L2C-XGBnw)

L2C-XGBw (FROG) involved training a separate XGBoost model for each forecast
window. This is not ideal because the forecast windows are themselves hyperparameters, which
might be hard to pick for new target variables. We hypothesized that the multiple forecast
windows might not be necessary because L2C features like "time since baseline" and "time since
most recent measurement" already encode the necessary temporal information for the model.
Therefore, we considered a variant of FROG, where a single XGBoost model was trained for all
future timepoints, as opposed to a separate model for each time window. We refer to this baseline
as L2C eXtreme Gradient Boost with no window (L2C-XGBnw). All other implementation details
remain consistent with those of L2C-XGBw.

2.8   FROG variant 2: L2C Fully-Connected Feedward Neural Network (L2C-FNN)

L2C-XGBnw trained a separate XGBoost model for each target variable. Previous studies
have suggested that predicting multiple target variables can potentially improve prediction
performance. By learning shared representations to capture common patterns among related tasks,

these shared representations might enhance data efficiency, accelerate learning, and mitigate

overfitting issues (Rahim et al., 2017; Crawshaw, 2020).

A natural choice to incorporate multi-task learning is to replace XGBoost with a fully

connected feedforward neural network (FNN) model, with the output layer predicting all target

variables jointly. Adding new target variables only increases the dimension of the output layer,

which eliminates the need for separate models and simplifies the coding and hyperparameter

tuning. Similar to L2C-XGBnw, we will train a single FNN model to predict all future timepoints,

instead of the original FROG implementation which trained a separate XGBoost model for each

forecast window. We will refer to this model as the L2C Fully-Connected Feedward Neural

Network (L2C-FNN).

Figure 2. Architecture of the L2C Fully Connected Feedforward Neural Network (L2C-FNN). FNN incorporates leaky rectified linear units (LeakyReLU) between layers. The input layer comprises multimodal L2C features, among which "time since baseline" denotes the duration from the baseline visit to the timepoint we want to predict, aiding in longitudinal prediction. The final layer simultaneously outputs clinical diagnosis probabilities (calculated with a soft-max function), MMSE score, and ventricle volume for multi-task learning.

Figure 2 illustrates the L2C-FNN architecture. LeakyReLU (Maas, 2013) was chosen as

the activation function, and dropout (Srivastava et al., 2014) was applied after each activation

function to enhance model generalizability. The FNN output is a 5-dimensional vector: the first

three elements represent the individual's probabilities of being diagnosed as CN, MCI, or DEM at

a future timepoint, computed using a SoftMax function, while the fourth and fifth elements

correspond to MMSE and ventricle volume predictions.

Input features are similar to L2C-XGBw (FROG), with additional preprocessing steps. Due
to FNN sensitivity to input scale and missing data compared to tree-based models such as
XGBoost, we performed Gauss Rank normalization, a special form of quantile normalization
(Zhao et al., 2020), with a Gaussian reference distribution. The transformation was performed
using the Scikit-learn quantile transform function (Pedregosa et al., 2011). Discrete features, such
as APOE, sex, and most recent diagnosis (mr_dx) were encoded using one-hot encoding. To
handle missing data, an "unknown" class was introduced for all discrete features, and missing
values were assigned to this class. Numeric feature imputation involved replacing missing values
with the median of the training set before Gauss Rank transformation. During inference, the
learned Gauss Rank transformations and statistics from the training set were used to impute and
transform validation and test data. Notably, the "time since milder clinical diagnosis" feature was
removed due to its high proportion of NaN values (91.57%) which primarily stems from two
causes: either because there is no milder clinical diagnosis in the patient's history or the clinical
diagnosis data is missing. Overall, this yields a 101-dimensional input vector for L2C-FNN (see
Supplementary Table S7 for details).

The loss function is computed by comparing the predictions with the ground truth. Similar
to MinimalRNN, cross-entropy loss was used for clinical diagnosis prediction, while mean
absolute error (MAE) loss was employed for MMSE and ventricle volume prediction (based on the
Gauss Rank values). Because MAE was based on Gauss Rank values, the three losses were of
similar magnitude, and so the three losses were added together with equal weighting. Changing the
relative weights of the three terms could potentially influence the model performance. However,
this would increase the number of hyperparameters, so we did not experiment with different
weights in this study.

Finally, stochastic gradient descent (SGD) with momentum (Qian, 1999; Sutskever et al.,
2013) was chosen as the optimizer, with Optuna utilized to search for optimal hyperparameters.
Table 9 shows all the hyperparameters considered and their corresponding search range. The
ExponentialLR scheduler was employed to regulate learning rate behavior.

Hyper-parameter	Range
Dropout rate	0-0.5
LeakyReLU slope	0.01-0.1
L2 weight regularization	10^{-7}-10^{-4}
SGD momentum	0-0.9
Learning rate	10^{-5}-10^{-1}

ExponentialLR gamma	0.1-0.9
Num of hidden layers	2-5
Size of hidden state	128-512

Table 9. Hyper-parameters and corresponding search ranges for L2C-FNN estimated from the validation sets using Optuna.

2.9 Further analyses

433   We performed five additional analyses to study the effectiveness of all five models
434   (MinimalRNN, AD-Map and the three FROG variants).

2.9.1 Impact of the number of observed timepoints on cross-cohort prediction accuracy

For a disease progression model to be effective in early detection of AD-dementia risk, it
should ideally perform well with a small number of input timepoints. We evaluated the
performance of all four models on external test datasets using only 1, 2, 3, or 4 input timepoints.
This contrasts with the main benchmarking analysis (Section 3.2), where half the total number of
timepoints (for each participant) were used to predict the remaining timepoints.

For the OASIS dataset, test subjects with fewer than 4 input timepoints were discarded so
that the same test subjects were evaluated across the four conditions (i.e., 1, 2, 3, or 4 input
timepoints). In contrast, the maximum number of input timepoints for each subject is less than 4 in
the AIBL and MACC datasets (2 for AIBL and 3 for MACC). Consequently, we discarded test
subjects with fewer than 2 input timepoints for AIBL and fewer than 3 input timepoints for MACC.
Because we excluded some test subjects, the results of this analysis are not directly comparable to
those of the main benchmarking analysis (Section 3.2).

2.9.2 Breakdown of cross-cohort prediction in yearly intervals

We extended our investigation of cross-cohort prediction performance by breaking down
the prediction results into yearly intervals up to 6 years into the future. Each participant's future
timepoints were categorized into yearly intervals based on the duration between the last input
timepoint and the target future timepoint for prediction. For instance, considering a participant
with 10 timepoints, if the last input timepoint (5th timepoint) was at month 60 and the 6th
timepoint was at month 70, the prediction at the 6th timepoint would be classified as 1 year into
the future due to the 10-month duration.

We anticipated that all tested algorithms would experience a decline in performance as the
prediction horizon extended further into the future. Nevertheless, a robust algorithm was expected
to maintain relatively high performance in both early and later years in the prediction horizon.

2.9.3 Subgroup analysis of cross-cohort prediction performance

We conducted an analysis on the external test datasets to evaluate model performance
across different diagnostic groups. Participants in each test set were divided into three subgroups
(CN, MCI and DEM) based on their last observed clinical diagnosis from the input timepoints. We
emphasize that clinical diagnoses from the output (test) timepoints were not used to divide
participants into subgroups. Trained models from ADNI were applied and evaluated for each
subgroup. A robust algorithm was expected to maintain relatively high performance across various
diagnostic groups, ensuring effectiveness in different stages of disease progression.

2.9.4 Effects of missing modalities on cross-cohort prediction accuracy

We also evaluated model performance under real-world conditions where certain
biomarker modalities may be unavailable. For each external test dataset, we selected a subset of
participants who had at least one observed value for every feature across all input timepoints,
which we refer to as the "full feature set". Participants missing an entire modality across all input
timepoints were excluded from this analysis. Because we excluded some test participants, the
results of this analysis are not directly comparable to the main benchmarking results (Section 3.2).
We generated three modified versions of the full feature set by ablating one modality at a
time: MRI features, cognitive features, or diagnostic features (Table 1). In each version, all
features belonging to the ablated modality were set to missing (NaN), while the remaining features
were left unaltered. Trained models from ADNI were then applied and evaluated under each
scenario. While all algorithms were expected to experience performance decline, a robust
algorithm would maintain reasonable performance even under the missing-modality scenarios.

2.9.5 Feature importance analysis for L2C-FNN

476   Given that L2C-FNN performed the best, we analyzed the L2C-FNN results from the
477 previous ablation analysis (Section 2.9.4). More specifically, we examined the performance
478 decline of L2C-FNN under each modality ablation scenario, by comparing with its performance on
479 the full feature set. A substantial drop in performance following the removal of a modality
480 indicated greater reliance on that modality, highlighting its importance to the model.

2.10 Deep neural network implementation

481   MinimalRNN and L2C-FNN were implemented using PyTorch (Paszke et al., 2019) and
482 computed on NVIDIA RTX 3090 GPUs with CUDA 11.0.

2.11 Performance evaluation and statistical tests

In the preceding sections, we utilized a 20-fold cross-validation procedure to train models
(MinimalRNN. AD-Map and three FROG variants) in ADNI, and then applied the models to
predict clinical diagnosis, MMSE score, and ventricle volume in ADNI test sets (within-dataset
evaluation), as well as in the three external datasets (cross-dataset evaluation). This section
provides a detailed description of evaluation metrics and statistical tests.

Diagnosis classification accuracy was evaluated using the multiclass area under the
operating curve (mAUC; Hand & Till, 2001) following the TADPOLE challenge. The mAUC was
computed as the average of three two-class AUC (DEM vs not DEM, MCI vs. not MCI, and CN
vs not CN). For mAUC, higher values indicate better performance. The mAUC is a group-level
metric whereby the predictions were first pooled over all test participants across their entire
forecast horizon into a vector of length # total future timepoints, before calculating the mAUC,
resulting one value per test set.

MMSE and ventricles prediction accuracy was evaluated using mean absolute error (MAE),
following the TADPOLE challenge (Marinescu et al., 2021), as well as MinimalRNN (Nguyen et
al., 2020), and AD-Map (Maheux et al., 2023) studies. Lower MAE indicates better performance.
The MAEs were averaged across all forecast timepoints within each participant, resulting in a
vector of length #test_participant values per test set. For the main within-ADNI (Section 3.1) and
cross-dataset (Section 3.2) analyses, root mean square error (RMSE) was also reported in the
supplementary results, confirming that both MAE and RMSE exhibit similar trends.

For within-cohort evaluation, because of the 20-fold cross-validation, there were 20 mAUC
values, 20 MAE values for MMSE and 20 MAE values for ventricle volumes. Although the test
sets do not overlap, the participants used for training do overlap across the test sets. Therefore, the
prediction metrics were not independent across the 20 test sets. To account for the non-
independence, we utilized the corrected resampled t-test (Nadeau & Bengio, 2003) to assess
performance differences between algorithms. Separate tests were performed for mAUC, MMSE
and ventricle volume.

For cross-cohort evaluation, the final performance was computed by averaging the
performance metrics across 20 trained models of each algorithm. To assess performance
differences between algorithms, since each participant in the external datasets were independent,
we performed paired sample t-test (Cohen, 1988) for MMSE MAE and ventricle volume MAE, as
well as a permutation test (Good, 2000) for group-level metrics (mAUC). Supplementary Figures
S3 and S4 illustrate the t-test and permutation test respectively.

 Multiple comparisons were corrected with a false discovery rate (FDR) of q < 0.05

516 (Benjamini & Hochberg, 1995) for both within and cross-cohort evaluations.

3   Results

3.1   FROG variants perform the best for within-cohort clinical diagnosis prediction

Figure 3 and Table 10 compare the prediction performance of MinimalRNN, AD-Map and

three FROG variants (L2C-XGBw, L2C-XGBnw and L2C-FNN) for within-cohort (ADNI)

clinical diagnosis, MMSE and ventricle volume prediction. All models exhibited similar

performance for predicting MMSE and ventricle volume. However, for predicting future clinical

diagnosis, the three FROG variants were better than MinimalRNN, which was in turn better than

AD-Map.

	Diagnosis					MMSE					Ventricle				
	MinimalRNN	AD-Map	L2C-XGBw	L2C-XGBnw	L2C-FNN	MinimalRNN	AD-Map	L2C-XGBw	L2C-XGBnw	L2C-FNN	MinimalRNN	AD-Map	L2C-XGBw	L2C-XGBnw	L2C-FNN
MinimalRNN		***	**	***	***		ns	ns	ns	ns		ns	ns	ns	ns
AD-Map	***		***	***	***	ns		ns	ns	ns	ns		ns	*	ns
L2C-XGBw	**	***		ns	ns	ns	ns		ns	ns	ns	ns		ns	ns
L2C-XGBnw	***	***	ns		ns	ns	ns	ns		ns	ns	*	ns		ns
L2C-FNN	***	***	ns	ns		ns	ns	ns	ns		ns	ns	ns	ns	

Figure 3. **Within-cohort (ADNI) prediction performance** (a) Boxplots represent variability in prediction performance across 20 test folds for (left) clinical diagnosis prediction measured, (middle) MMSE prediction and (right) ventricular volume prediction. (b) Statistical difference between all models. "***" indicates p < 0.00001 and statistical significance after multiple comparison correction (FDR q < 0.05). "**" indicates p < 0.001 and statistical significance after multiple comparison correction (FDR q < 0.05). "ns" indicates no statistical significance (p ≥ 0.05) or did not survive FDR correction.

	Diagnostic mAUC ↑	MMSE MAE ↓	Ventricle MAE (1e-3) ↓
MinimalRNN	0.916 ± 0.027	1.899 ± 0.212	1.928 ± 0.279
AD-Map	0.847 ± 0.027	1.976 ± 0.171	1.993 ± 0.278
L2C-XGBw	0.942 ± 0.018	1.896 ± 0.185	1.796 ± 0.279
L2C-XGBnw	0.945 ± 0.019	1.875 ± 0.192	**1.768 ± 0.247**
L2C-FNN	**0.946 ± 0.018**	**1.824 ± 0.201**	1.884 ± 0.193

Table 10. Within-cohort (ADNI) prediction performance averaged across 20 folds. For clinical diagnosis, ↑ implies that higher mAUC indicates better performance. For MMSE and ventricular volume, ↓ indicates that lower MAE indicates better performance. The best result for each performance metric was bolded. Similar conclusions were obtained with root mean square error (RMSE) instead of MAE (Supplementary Table S8).

3.2 L2C-FNN performed the best for cross-cohort prediction

Figures 4 and 5 compare the prediction performance of MinimalRNN, AD-Map and three

FROG variants (L2C-XGBw, L2C-XGBnw and L2C-FNN) for cross-cohort MMSE, ventricle

volume and clinical diagnosis prediction in three external datasets (AIBL, MACC, and OASIS).

Numerical values are reported in Table 11.

To simplify the reported statistical tests (Figure 5) into an easier-to-understand format,

Table 12 shows the ranking of all models for the three prediction tasks (MMSE, ventricle,

diagnosis) across the three external datasets (AIBL, MACC, OASIS). For example, in the case of

MMSE prediction in the MACC dataset, L2C-FNN was statistically better than three algorithms

and was statistically worse than one algorithm (Figure 5a), so we assigned L2C-FNN a score of 3

– 1 = 2. On the other hand, AD-Map was statistically better than four algorithms and statistically

worse than no algorithm for MMSE prediction in the MACC dataset (Figure 5a), so we assigned

AD-Map a score of 4 – 0 = 4. By comparing the scores of different algorithms, we concluded that

for MMSE prediction in the MACC dataset, AD-Map was ranked first, L2C-FNN was ranked

second, while MinimalRNN, L2C-XGBw and L2C-XGBnw were tied for third with a score of -2

(Table 12).

Based on Table 12 (and Figures 4 and 5), in the case of MMSE prediction in the AIBL

dataset, L2C-FNN was the best, followed by AD-Map and MinimalRNN. In the MACC dataset,

AD-Map was the best followed by L2C-FNN. In the OASIS dataset, L2C-FNN and AD-Map were

the best. Overall, for MMSE prediction, L2C-FNN and AD-Map were the best (Table 12). Similar conclusions were obtained if we only considered AD dementia, with non-AD dementia set to NaN (Figure S5).

In the case of ventricle volume prediction in the AIBL dataset, all approaches had similar performance, although L2C-XGBnw was the best, followed closely by L2C-FNN (Table 12). In the MACC dataset, L2C-FNN was the best, followed by AD-Map. In the OASIS dataset, AD-Map performed the best, followed by L2C-XGBnw. Overall, for ventricle volume prediction, L2C-FNN had the best ranking (Table 12). The original FROG algorithm (L2C-XGBw) and MinimalRNN performed the worst. Similar conclusions were obtained if we only considered AD dementia, with non-AD dementia set to NaN (Figure S5).

In the case of clinical diagnosis prediction in the AIBL dataset, L2C-FNN was numerically the best, but there was no statistical difference among the FROG variants and MinimalRNN. However, AD-Map was statistically worse than the three FROG variants. In the MACC dataset, the three FROG variants performed similarly well and were all statistically better than MinimalRNN, which was in turn better than AD-Map. Finally, in the OASIS dataset, L2C-FNN was the best, while the original FROG algorithm (L2C-XGBw) was the worst. Overall, for clinical diagnosis prediction, L2C-FNN performed the best. Similar conclusions were obtained if we only considered AD dementia, with non-AD dementia set to NaN (Figure S5).

The "overall" column in Table 12 shows the overall ranking by adding the rankings across all three prediction tasks (MMSE, ventricle, diagnosis) in the three external datasets. The best possible overall ranking was nine, which could be achieved by being the top ranked algorithm for every prediction task in every dataset. With an overall ranking of 11, L2C-FNN performed the best, followed by L2C-XGBnw (19) and AD-Map (20).

Figure 4. Cross-cohort prediction performance on three external test datasets. (a) Boxplots illustrate the variability across 20 trained models (from ADNI) for MMSE prediction assessed using MAE. Lower MAE indicates better performance. The x-axis denotes the test dataset used for evaluation. (b) Same as (a) but for ventricular volume prediction error assessed using MAE. Lower

MAE indicates better performance. (c) Same as (a) but for diagnosis accuracy (mAUC). Higher mAUC indicates better performance.

(a)

MMSE	MinimalRNN			AD-Map			L2C-XGBw			L2C-XGBnw			L2C-FNN		
	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS
Minimal RNN				ns	***	**	**	ns	*	***	ns	ns	*	**	***
AD-Map	ns	***	**				ns	***	***	**	***	**	ns	**	ns
L2C-XGBw	**	ns	*	ns	***	***				**	ns	*	***	**	***
L2C-XGBnw	***	ns	ns	**	***	**	**	ns	*				***	***	***
L2C-FNN	*	**	***	ns	**	ns	***	**	***	***	***	***			

(b)

Ventricle	MinimalRNN			AD-Map			L2C-XGBw			L2C-XGBnw			L2C-FNN		
	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS
Minimal RNN				ns	**	***	ns	***	*	*	*	***	*	***	***
AD-Map	ns	**	***				ns	***	***	ns	ns	ns	ns	ns	ns
L2C-XGBw	ns	***	*	ns	***	***				*	***	***	ns	***	***
L2C-XGBnw	*	*	***	ns	ns	ns	*	***	***				ns	***	ns
L2C-FNN	*	***	***	ns	ns	ns	ns	***	***	ns	***	ns			

(c)

Diagnosis	MinimalRNN			AD-Map			L2C-XGBw			L2C-XGBnw			L2C-FNN		
	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS
Minimal RNN				ns	**	ns	ns	*	**	ns	*	ns	ns	*	ns
AD-Map	ns	**	ns				*	**	ns	*	**	ns	**	**	*
L2C-XGBw	ns	*	**	*	**	ns				ns	ns	**	ns	ns	**
L2C-XGBnw	ns	*	ns	*	**	ns	ns	ns	**				ns	ns	**
L2C-FNN	ns	*	ns	**	**	*	ns	ns	**	ns	ns	**			

Figure 5. Statistical significance in the prediction performance between all models across the three external datasets. (a) Statistical significance between algorithms for MMSE prediction. Each row shows the statistical difference between a model and all other models across the three test datasets. The columns are grouped into five major columns corresponding to the five approaches. Within each major column, the three sub-columns represent results on AIBL, MACC,

and OASIS datasets, respectively. For example, the first row corresponds to the statistical difference between MinimalRNN and the other models – green indicates that MinimalRNN performs better, while red indicates that MinimalRNN performs worse. "*" indicates p < 0.05 and statistical significance after multiple comparisons correction (FDR q < 0.05). "**" indicates p < 0.001 and statistical significance after multiple comparisons correction (FDR q < 0.05). "***" indicates p < 0.00001 and statistical significance after multiple comparisons correction (FDR q < 0.05). "ns" indicates no statistical significance (p ≥ 0.05) or did not survive FDR correction. (b) Same as (a) but for ventricular volume prediction. (c) Same as (a) but for clinical diagnosis prediction.

	MMSE MAE ↓			Ventricle MAE (1e-3) ↓			Diagnostic mAUC ↑		
	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS
MinimalRNN	1.406 ± 0.040	2.965 ± 0.298	1.688 ± 0.095	2.311 ± 0.284	3.260 ± 0.709	5.625 ± 0.431	0.880 ± 0.016	0.906 ± 0.029	0.739 ± 0.024
AD-Map	1.379 ± 0.008	**2.489 ± 0.022**	1.569 ± 0.017	2.144 ± 0.044	2.749 ± 0.062	**3.887 ± 0.045**	0.839 ± 0.004	0.835 ± 0.006	0.743 ± 0.004
L2C-XGBw	1.595 ± 0.119	2.891 ± 0.075	1.787 ± 0.030	2.310 ± 0.412	3.858 ± 0.636	4.652 ± 0.118	0.889 ± 0.015	**0.960 ± 0.005**	0.702 ± 0.013
L2C-XGBnw	1.752 ± 0.415	2.979 ± 0.116	1.718 ± 0.057	**2.057 ± 0.060**	3.029 ± 0.350	4.044 ± 0.150	0.900 ± 0.008	**0.960 ± 0.004**	0.746 ± 0.015
L2C-FNN	**1.314 ± 0.033**	2.696 ± 0.142	**1.526 ± 0.013**	2.124 ± 0.090	**2.541 ± 0.223**	4.133 ± 0.039	**0.911 ± 0.004**	0.958 ± 0.003	**0.794 ± 0.004**

Table 11. Cross-cohort prediction performance averaged across 20 trained models (from ADNI). For clinical diagnosis, higher mAUC indicates better performance. For MMSE and ventricles, lower MAE indicates better performance. The best result for each performance metric on each test dataset was bolded. Similar conclusions were obtained with root mean square error (RMSE) instead of MAE (Supplementary Tables S9 and S10).

	MMSE MAE			Ventricle MAE			Diagnostic mAUC			Overall
	AIBL	MACC	OASIS	AIBL	MACC	OASIS	AIBL	MACC	OASIS	
MinimalRNN	2	3	2	5	4	3	2	2	2	25
AD-Map	2	1	1	3	2	1	3	3	4	20
L2C-XGBw	3	3	3	4	5	2	1	1	5	27
L2C-XGBnw	4	3	2	1	3	1	1	1	3	19
L2C-FNN	1	2	1	2	1	1	1	1	1	11

Table 12. Cross-cohort prediction performance rankings of all models. Each row shows the rank of a model for three evaluation metrics: MMSE MAE, ventricle MAE, and diagnostic mAUC across AIBL, MACC, and OASIS datasets (1 = best, 5 = worst; ties allowed). Rankings were derived by summing wins (+1) and losses (–1) for each model, as indicated by green (win) and red (loss) in the statistical significance tables (Figure 5). The model with the highest total score receives rank 1 for that metric on each dataset. More details can be found in Section 3.2. The "overall" column adds up all the rankings, so a smaller overall ranking was better. The best possible overall ranking was nine, which could be achieved by being the top ranked algorithm for every prediction task in every dataset. With an overall ranking of 11, L2C-FNN performed the best.

3.3 Further analysis 1: cross-dataset prediction with varying input timepoints

Figures S6 to S8 show the cross-dataset prediction performance of MinimalRNN, AD-Map

and three FROG variants (L2C-XGBw, L2C-XGBnw and L2C-FNN) with varying number of

input time points. Actual numerical values are reported in Tables S11 to S13. Due to the

constraints of the datasets, the maximum number of input timepoints for each participant is only 2

for AIBL and 3 for MACC. Therefore, results for AIBL with 3 and 4 timepoints and for MACC

with 4 timepoints are marked as "N.A." Figure 6 shows the results of statistical tests comparing

L2C-FNN and other approaches.

As anticipated, prediction performance generally improved with more input timepoints

(Figures S6 to S8). Overall, L2C-FNN consistently matched or outperformed other approaches

across all datasets and different number of observed timepoints, with only two exceptions (Figure

6). The first exception was that AD-Map was statistically better than L2C-FNN when predicting

ventricle volume with 1 input timepoint in the MACC dataset (Figure 6). The second exception

was that L2C-XGBnw was statistically better than L2C-FNN when predicting ventricle volume

with 1 input timepoint in the OASIS dataset (Figure 6).

	AIBL		MACC			OASIS			
MMSE	1	2	1	2	3	1	2	3	4
L2C-FNN vs MinimalRNN	ns	ns	***	***	**	***	***	***	***
L2C-FNN vs AD-Map	ns	ns	ns	ns	ns	ns	*	*	**
L2C-FNN vs L2C-XGBw	***	**	**	*	*	***	***	***	***
L2C-FNN vs L2C-XGBnw	***	**	**	**	**	***	***	***	***
Ventricle	1	2	1	2	3	1	2	3	4
L2C-FNN vs MinimalRNN	**	**	***	***	***	***	***	***	***
L2C-FNN vs AD-Map	ns	ns	*	ns	ns	ns	ns	ns	ns
L2C-FNN vs L2C-XGBw	ns	*	***	***	***	ns	ns	**	**
L2C-FNN vs L2C-XGBnw	ns	ns	***	***	***	*	ns	ns	ns
Diagnosis	1	2	1	2	3	1	2	3	4
L2C-FNN vs MinimalRNN	ns	ns	**	**	**	ns	ns	ns	ns
L2C-FNN vs AD-Map	*	*	**	**	**	ns	ns	ns	ns
L2C-FNN vs L2C-XGBw	**	ns	**	**	ns	**	**	**	**
L2C-FNN vs L2C-XGBnw	ns	ns	ns	*	ns	*	**	**	**

Figure 6. Statistical significance between L2C-FNN and other models for cross-cohort MMSE, ventricle volume, and clinical diagnosis prediction performance, using different numbers of input timepoints (after training with all timepoints in ADNI). "*" indicates $p < 0.05$ and significance after multiple comparisons correction (FDR $q < 0.05$). "**" indicates $p < 0.001$ and significance after multiple comparisons correction (FDR $q < 0.05$). "***" indicates $p < 0.00001$ and significance after multiple comparisons correction (FDR $q < 0.05$). "ns" indicates no significance ($p \geq 0.05$) or did not survive FDR correction. Green indicates that L2C-FNN was statistically better than other approaches compared, while red indicates that it was statistically worse.

3.4 Further analysis 2: cross-dataset prediction across varying forecast windows

Supplementary Figures S9 to S11 show the yearly breakdown in prediction performance up to 6 years into the future (from Figure 4). As anticipated, the prediction performance for all algorithms declines as the prediction horizon increases. Numerical values are reported in Supplementary Tables S14 to S16. Figure 7 shows the results of statistical tests comparing L2C-FNN with other approaches. L2C-FNN consistently matched or outperformed other methods from year 1 to year 6 across all datasets with two exceptions (Figure 7). The exceptions were that AD-

Map was statistically better than L2C-FNN when predicting MMSE in year 0-1 and year 1-2 in the MACC dataset.

	AIBL						MACC						OASIS					
MMSE	0-1	1-2	2-3	3-4	4-5	5-6	0-1	1-2	2-3	3-4	4-5	5-6	0-1	1-2	2-3	3-4	4-5	5-6
L2C-FNN vs MinimalRNN	ns	ns	ns	ns	ns	ns	ns	**	***	**	ns	ns	**	*	**	**	**	***
L2C-FNN vs AD-Map	ns	ns	ns	ns	*	ns	***	**	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns
L2C-FNN vs L2C-XGBw	*	***	ns	ns	*	ns	ns	ns	ns	**	ns	ns	***	***	**	***	***	***
L2C-FNN vs L2C-XGBnw	ns	***	*	ns	**	ns	*	***	*	**	ns	ns	***	**	**	*	**	***
Ventricle	0-1	1-2	2-3	3-4	4-5	5-6	0-1	1-2	2-3	3-4	4-5	5-6	0-1	1-2	2-3	3-4	4-5	5-6
L2C-FNN vs MinimalRNN	ns	ns	*	ns	***	ns	**	**	**	**	*	ns	*	ns	ns	*	ns	**
L2C-FNN vs AD-Map	ns	ns	ns	ns	*	ns	ns	ns	ns	*	ns	ns	ns	ns	ns	ns	ns	ns
L2C-FNN vs L2C-XGBw	ns	**	ns	ns	ns	ns	***	***	***	***	*	ns	ns	ns	*	ns	ns	**
L2C-FNN vs L2C-XGBnw	*	ns	ns	ns	ns	ns	ns	***	**	***	*	ns	ns	ns	ns	ns	ns	ns
Diagnosis	0-1	1-2	2-3	3-4	4-5	5-6	0-1	1-2	2-3	3-4	4-5	5-6	0-1	1-2	2-3	3-4	4-5	5-6
L2C-FNN vs MinimalRNN	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns
L2C-FNN vs AD-Map	ns	**	ns	ns	ns	ns	**	**	**	**	ns	ns	ns	ns	**	ns	ns	ns
L2C-FNN vs L2C-XGBw	ns	ns	**	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	ns	*	**	ns	**
L2C-FNN vs L2C-XGBnw	ns	ns	*	ns	ns	ns	ns	ns	ns	ns	ns	ns	**	ns	ns	ns	ns	*

Figure 7. Statistical significance between L2C-FNN and other models for cross-cohort MMSE, ventricle volume, and clinical diagnosis prediction performance (from Figure 4) broken down into yearly intervals up to 6 years into the future. "*" indicates $p < 0.05$ and significance after multiple comparisons correction (FDR $q < 0.05$). "**" indicates $p < 0.001$ and significance after multiple comparisons correction (FDR $q < 0.05$). "***" indicates $p < 0.00001$ and significance after multiple comparisons correction (FDR $q < 0.05$). "ns" indicates no significance ($p \geq 0.05$) or did not survive FDR correction. Green indicates L2C-FNN was statistically better than other approaches compared, while red indicated that it was statistically worse.

3.5 Further analysis 3: Initial diagnostic group

Tables S17 to S19 report the prediction performance (from Figure 4) broken down by last observed diagnostic group (CN, MCI or DEM). Figure 8 shows the results of statistical tests comparing L2C-FNN with other approaches. Overall, L2C-FNN demonstrated robust performance across clinical groups, showing comparable or better performance than other models (Figure 8). The one exception was that AD-Map was statistically better than L2C-FNN in predicting MMSE within the dementia group in the MACC dataset.

	AIBL			MACC			OASIS		
MMSE MAE	CN	MCI	DEM	CN	MCI	DEM	CN	MCI	DEM
L2C-FNN vs MinimalRNN	**	ns	ns	ns	ns	**	***	ns	*
L2C-FNN vs AD-Map	**	ns	ns	*	ns	***	**	ns	ns
L2C-FNN vs L2C-XGBw	***	ns	ns	ns	ns	*	***	ns	*
L2C-FNN vs L2C-XGBnw	***	ns	ns	ns	ns	***	***	ns	ns
Ventricle MAE	CN	MCI	DEM	CN	MCI	DEM	CN	MCI	DEM
L2C-FNN vs MinimalRNN	**	ns	ns	ns	*	***	***	ns	*
L2C-FNN vs AD-Map	ns	ns	ns	**	ns	ns	ns	ns	ns
L2C-FNN vs L2C-XGBw	ns	ns	ns	***	***	***	**	ns	*
L2C-FNN vs L2C-XGBnw	ns	ns	ns	*	***	***	ns	ns	ns
Diagnosis	CN	MCI	DEM	CN	MCI	DEM	CN	MCI	DEM
L2C-FNN vs MinimalRNN	ns	ns	na	ns	*	na	ns	ns	ns
L2C-FNN vs AD-Map	ns	ns	na	ns	ns	na	ns	ns	ns
L2C-FNN vs L2C-XGBw	ns	ns	na	ns	ns	na	*	ns	ns
L2C-FNN vs L2C-XGBnw	ns	ns	na	*	ns	na	*	ns	ns

Figure 8. Statistical significance between L2C-FNN and other models for cross-cohort MMSE, ventricle volume, and clinical diagnosis prediction performance (from Figure 4) broken down by last observed diagnostic group (CN, MCI or DEM). "*" indicates p < 0.05 and significance after multiple comparisons correction (FDR q < 0.05). "**" indicates p < 0.001 and significance after multiple comparisons correction (FDR q < 0.05). "***" indicates p < 0.00001 and significance after multiple comparisons correction (FDR q < 0.05). "ns" indicates no significance (p ≥ 0.05) or did not survive FDR correction. Green indicates L2C-FNN was statistically better than other approaches compared, while red indicated that it was statistically worse. "na" indicates not applicable.

3.6   Further analysis 4: cross-dataset prediction with missing modalities

Supplementary Tables S20 to S22 report the prediction performance for different missing-modality scenarios. As expected, prediction accuracy declined for all algorithms when an entire data modality is missing in a participant. Figure 9 reports the statistical comparisons between L2C-FNN and other approaches. L2C-FNN consistently outperformed MinimalRNN and L2C-XGBw with the exception of statistically worse performance than MinimalRNN when predicting MMSE when cognitive features were ablated in the MACC dataset. Compared to AD-Map, L2C-FNN

exhibited better performance in diagnosis and ventricular volume prediction. However, in the case of MMSE prediction, L2C-FNN was statistically better in two scenarios, and statistically worse in three scenarios, compared with AD-Map. Compared to L2C-XGBnw, L2C-FNN exhibited better performance in diagnosis and MMSE prediction. However, in the case of ventricular volume prediction, L2C-FNN was statistically better in five scenarios, and statistically worse in four scenarios (Figure 9). Therefore, overall, L2C-FNN compared favorably with other models.

	AIBL				MACC				OASIS			
MMSE MAE	NO	DX	COG	MRI	NO	DX	COG	MRI	NO	DX	COG	MRI
L2C-FNN vs MinimalRNN	ns	ns	***	ns	**	*	***	*	***	***	***	***
L2C-FNN vs AD-Map	ns	na	ns	ns	**	na	**	***	*	na	***	ns
L2C-FNN vs L2C-XGBw	**	***	ns	***	*	ns	na	***	***	***	na	***
L2C-FNN vs L2C-XGBnw	***	***	***	***	***	ns	*	ns	***	***	***	***
Ventricle MAE	NO	DX	COG	MRI	NO	DX	COG	MRI	NO	DX	COG	MRI
L2C-FNN vs MinimalRNN	*	ns	**	***	***	*	ns	***	***	***	***	***
L2C-FNN vs AD-Map	ns	na	ns	ns	*	na	*	ns	**	na	*	***
L2C-FNN vs L2C-XGBw	*	ns	***	na	***	***	***	na	***	***	***	ns
L2C-FNN vs L2C-XGBnw	ns	***	***	***	***	ns	***	**	**	ns	***	***
Diagnosis	NO	DX	COG	MRI	NO	DX	COG	MRI	NO	DX	COG	MRI
L2C-FNN vs MinimalRNN	ns	*	*	ns	**	ns	**	**	ns	*	*	ns
L2C-FNN vs AD-Map	**	na	**	**	**	na	**	**	*	na	**	*
L2C-FNN vs L2C-XGBw	ns	na	ns	**	ns	na	ns	**	ns	na	*	**
L2C-FNN vs L2C-XGBnw	ns	*	*	*	ns	ns	*	ns	ns	ns	ns	ns

Figure 9. Statistical significance between L2C-FNN and other models for cross-cohort MMSE, ventricle volume, and clinical diagnosis prediction performance under different modality ablation scenarios ("NO": no ablation; "DX": ablate diagnosis; "COG": ablate cognition; "MRI": ablate MRI). "*" indicates $p < 0.05$ and significance after multiple comparisons correction (FDR q < 0.05). "**" indicates $p < 0.001$ and significance after multiple comparisons correction (FDR q < 0.05). "***" indicates $p < 0.00001$ and significance after multiple comparisons correction (FDR q < 0.05). "ns" indicates no significance ($p \geq 0.05$) or did not survive FDR correction. Green indicates L2C-FNN was statistically better than other approaches compared, while red indicated that it was statistically worse. Due to model design, AD-Map did not utilize clinical diagnosis as input features (Section 2.5) and thus did not have results under the "DX" condition. These cases are marked as "na" (not applicable). On the other hand, L2C-XGBw relies on "time since most recent measurement" (MMSE, ventricle volume, or diagnosis) to select the appropriate XGBoost

model (Section 2.6.4), so no prediction could be made for a modality if it is completely missing from a participant. Therefore, these cases are also marked as "na" (not applicable).

3.7   Further analysis 5: feature importance for L2C-FNN

Figure 10 quantifies feature importance for the L2C-FNN model by comparing prediction

performance without ablation (dark color) and prediction performance with ablation (light color).

Actual numerical results are reported in Supplementary Table S23.

When predicting MMSE, ablating MMSE from visit histories led to a massive increase in

MMSE prediction error (Table S23; Figure 10a). This was especially pronounced in the MACC

dataset, where MAE increased by 250% from 2.672 to 6.809 (Table S23). The second most

important features were clinical diagnoses, followed by MRI, which impacted MMSE prediction

accuracy only by 2% to 6% (Table S23).

When predicting ventricular volume, ablating MRI from visit histories led to an even larger

increase in prediction error of around 400% to 600% (Table S23; Figure 10b). For example, MAE

increased from 1.985 to 10.288 in the OASIS dataset (Table S23). The second most important

features were clinical diagnoses, followed by cognitive features (Table S23).

Finally, excluding clinical diagnosis led to the largest drop in diagnosis prediction accuracy.

However, accuracy degradation was quite modest (unlike MMSE and ventricle volume prediction),

ranging from 3% to 10% (Table S23). Ablating cognitive features led to only 1% to 3% drop in

prediction accuracy (Table S23). In the OASIS, ablating cognitive features led to a larger drop in

accuracy than ablating clinical diagnoses. Finally, ablating MRI has little or no effect on clinical

diagnosis prediction.

Overall, not surprisingly, cognitive features, MRI and clinical diagnoses were the most

important for predicting MMSE, ventricle volume and clinical diagnoses respectively. What is

interesting is that ablating the most important feature for clinical diagnosis prediction led to only a

small drop in prediction performance unlike predicting MMSE or ventricular volume.

Furthermore, given the cost of MRI, if the goal is to predict future cognition or clinical

diagnoses, our analyses suggested limited additional value of MRI beyond neuropsychological

assessments. However, we note that we have only utilized T1 MRI in the current study. It is

possible that other MRI modality might be more predictive of future cognitive decline or clinical

diagnoses.

Figure 10. Cross-cohort feature importance analysis for L2C-FNN (a) Bar charts show the average MMSE prediction error (MAE) across 20 trained models (from ADNI), with error bars indicating standard deviation. The x-axis denotes the ablated modality. For each ablated modality, six bars are shown: three datasets (AIBL, MACC, OASIS) each represented in two shades—dark for the full feature set (i.e., no ablation) and light for the ablated modality. Dotted lines connect each pair of bars within a dataset, highlighting the performance decline caused by modality ablation. (b) Same as (a) but for ventricle prediction error (MAE). (c) Same as (a) but for clinical diagnosis accuracy (mAUC).

4 Discussion

In this study, we evaluated the winning algorithm of the TADPOLE challenge FROG, two

FROG variants, MinimalRNN and AD-Map in the ADNI dataset, as well as three external datasets.

In the ADNI dataset, all three FROG variants performed similarly well and outperformed

MinimalRNN and AD-Map for clinical diagnosis. The excellent performance of FROG in clinical

diagnosis was consistent with the outcome of the TADPOLE challenge, where FROG was ranked

1st in clinical diagnosis prediction (Marinescu et al., 2021).

In the three external datasets, the FROG variant L2C-FNN outperformed the other two

FROG variants, MinimalRNN and AD-map, achieving top rank in seven of nine scenarios and

second in the remaining two scenarios (Table 12). Furthermore, L2C-FNN mostly outperformed

other models, regardless of the number of observed input timepoints (many more green entries

than red entries in Figure 6), and regardless of the prediction horizon from 0 to 6 years into the

future (many more green entries than red entries in Figure 7). L2C-FNN also mostly outperformed

other models regardless of the last observed diagnoses (many more green entries than red entries in

Figure 8), and regardless of missing input modality (many more green entries than red entries in

Figure 9).

4.1 Algorithmic considerations

An inherent challenge in the TADPOLE problem set up is the pervasive missing data in

each participant. Missing data occurs when participants fail to show up or fail to complete certain

tests or scans during visits. In most longitudinal datasets, not all data is collected at all timepoints

by design. For example, one visit might only involve MRI scans, while another visit might only

involve detailed neuropsychological exams. Therefore, the implication is that in every participant,

there is missing data at almost every observed time point.

State-based models, such as MinimalRNN, require specialized techniques to handle the

missing data. By contrast, the L2C feature transformation significantly reduces the ratio of missing

data. As a result, the input to models, comprising L2C features, contains substantially fewer

missing data. Beyond mitigating missing data issues, this transformation also offers greater

flexibility in model selection. By converting longitudinal data into a cross-sectional format, L2C

removes the constraint of using time series models, allowing for a broader range of predictive

algorithms. This flexibility enables the use of established machine learning models that may not

naturally handle sequential inputs, potentially improving predictive performance and

interpretability. These properties of L2C transformation might explain the advantage of FROG

variants over MinimalRNN.

Another potential drawback of MinimalRNN is that each future prediction is based on
previous predictions, which might lead to error accumulation (Fan et al., 2019). This error
accumulation becomes particularly pronounced in longer-term predictions (Figures S9 to S11).
Indeed, we observed that L2C-FNN's improvements over MinimalRNN progressively improved
further into the future (Figure S12a). This trend was not obvious when comparing L2C-FNN and
other approaches (Figures S12b to S12d).

The original FROG algorithm (L2C-XGBw) constructs separate XGBoost models for each
target variable and different forecast windows, resulting in a total of 15 models. However, the
optimal window ranges might vary significantly between datasets. Furthermore, dividing training
samples into different bins based on the forecast interval range reduces the available training
samples in each bin. We hypothesized that eliminating forecast window stratification and enabling
the model to implicitly leverage temporal information within L2C features (e.g., time since
baseline, time since most recent measurements) could enhance model generalizability. To test this
hypothesis, we trained a single FNN for all training samples with varying forecast intervals.
Experimentally, L2C-FNN outperformed L2C-XGBw in every prediction task (i.e., clinical
diagnosis, MMSE, ventricle volume) across all external datasets (Table 12).

Another feature of L2C-FNN is the use of multi-task learning, such that a single FNN is
used to predict all three target variables (ventricle volume, cognition, clinical diagnosis)
simultaneously. Multi-task learning leverages shared representations to capture common patterns
among related tasks, which might enhance data efficiency, accelerate learning, and mitigate
overfitting (Crawshaw, 2020). The FROG variant (L2C-XGBnw) helped to dissociate the effects
of multi-task learning and the elimination of forecast window stratification by training a separate
XGBoost model for each target variable. L2C-FNN again outperformed L2C-XGBnw in nearly
every prediction task (i.e., clinical diagnosis, MMSE, ventricle volume) across all external datasets
(Table 12). Therefore, these results suggest the potential advantage of multi-task learning.

In our evaluation, AD-Map was highly competitive in terms of predicting MMSE and
ventricle volume but performed poorly for clinical diagnosis. Because AD-Map utilized a sigmoid-
like parameterization, it might predict continuous variables (e.g., MMSE and ventricle volume)
better than categorical variables (e.g., clinical diagnosis). Consistent with the original study
(Maheux et al., 2023), we did not directly model clinical diagnosis in the AD-Map algorithm. We
have also experimented with including clinical diagnosis in the AD-Map model, which improved
clinical diagnosis prediction, but resulted in much worse MMSE and ventricle prediction (not
shown).

4.2 Dataset variability and limitations

We observed significant variability in prediction performance across datasets (Figure 4)
that was consistent across algorithms. For example, MMSE prediction error was the highest in the
MACC dataset (compared with the AIBL or OASIS dataset) for all algorithms (Figure 4). The
reason might be because the MMSE scores were significantly lower in the MACC dataset
compared with the ADNI dataset, which was used to train the models. More specifically, the
average baseline MMSE scores were 27.4, 28.0, 28.3 and 21.6 in ADNI, AIBL, OASIS and
MACC datasets respectively (Table 2). The large shift in MMSE distributions between the ADNI
and MACC datasets might have contributed to the relatively poor MMSE prediction in the MACC
dataset.

On the other hand, ventricle volume and clinical diagnosis predictions were the worst in
the OASIS dataset (compared with the MACC and AIBL datasets) for all algorithms (Figure 4).
The reason for the poor ventricle volume prediction might be because MRI was missing in most
OASIS timepoints. More specifically, 39%, 23%, 53% and 72% of timepoints did not have any
MRI features in the ADNI, AIBL, MACC and OASIS datasets respectively (Table 2). The sparse
MRI availability in OASIS required models to make predictions with few or even no imaging
input features.

Furthermore, the average follow-up durations were 4.5, 3.3, 3.9 and 7.8 years in the ADNI,
AIBL, MACC and OASIS datasets respectively (Table 2). The longer follow-up durations in
OASIS required stronger long-term prediction capabilities, which may also explain the overall
lower ventricle volume and diagnosis prediction performance in the OASIS dataset.

A limitation of the current study is that the models are trained from a single dataset (ADNI).
We expect that models trained from multiple datasets might lead to better generalization to new
populations and scanners (Dou et al., 2019; Liu et al., 2020; Chen et al., 2024). Therefore, a
potential future work is to collate multiple datasets and train a single L2C-FNN model for future
usage. Another limitation is that the current study only considered biomarkers that existed in all
four datasets, so blood and PET biomarkers were excluded. Blood and PET biomarkers have been
shown to be important markers of AD dementia (Nordberg et al., 2010; Mattsson et al., 2017;
Chételat et al., 2020; Chong et al., 2021), therefore future studies could likely benefit from the
incorporation of these additional biomarkers.

Another limitation of the current study is that there are in general more early follow-up
data than late follow-up data. For example, a participant with a 5-year follow-up will almost
certainly have an earlier follow-up (e.g., 1-year or 2-year follow-up) before the 5-year follow-up.
On the other hand, participants with 1-year follow-up might never return for future follow-up. As a
result, the main cross-cohort results (Figure 4) are naturally weighted towards earlier prediction

horizons. We ameliorated this limitation by examining yearly breakdown in prediction
performance up to 6 years into the future (Figure 7), but could not extend further into the future
due to insufficient data.

We note that both short-term and long-term predictions can be clinically useful. On the one
hand, there is growing consensus that interventions should be as early as possible before neuronal
damage becomes irreversible (Dubois et al., 2016; Scheltens et al., 2016; Porsteinsson et al., 2021;
Aisen et al., 2022). Therefore, the ability to forecast disease progression many years in advance
can be highly beneficial. On the other hand, short-term predictions may be more actionable in
certain cases, particularly when considering a patient's age and comorbidities. For example,
predicting that a 90-year-old patient is at high risk of developing dementia in ten years may have
limited clinical utility, given the average life expectancy at that age is approximately another 3 to 5
years in the United States (U.S. Social Security Administration, 2020).

Moreover, prognosis can guide treatment preferences. A patient facing a poor short-term
outlook might be more willing to accept an intensive or burdensome treatment, such as frequent
infusions with serious side effects, for the chance of near-term benefit. Conversely, a patient with a
favorable short-term prognosis but poor long-term outlook might prefer a simpler regimen with
fewer side effects, prioritizing quality of life over aggressive intervention.

5   Conclusion

In this study, we evaluated three FROG variants, MinimalRNN and AD-Map in predicting
future dementia progression in the ADNI dataset and three external datasets. We found that a
FROG variant (L2C-FNN) performed the best in the three external datasets. L2C-FNN maintained
better prediction performance regardless of the number of observed timepoints in a participant.
L2C-FNN also consistently matched or outperformed other approaches from year 1 to year 6
across all external datasets, underscoring its potential for reliable long-term prediction in dementia
progression.

6 Acknowledgment

We would like to thank Christina Rabe, and Paul Manser from Team FROG for sharing
their code with us, which significantly facilitated the current study. This research is supported by
the NUS Yong Loo Lin School of Medicine (NUHSRO/2020/124/TMR/LOA), the Singapore
National Medical Research Council (NMRC) LCG (OFLCG19May-0035), NMRC CTG-IIT
(CTGIIT23jan-0001), NMRC STaR (STaR20nov-0003), NMRC OF-IRG (OFIRG24jan-0006;
OFIRG24jul-0049), Singapore Ministry of Health (MOH) Centre Grant (CG21APR1009), the
Temasek Foundation (TF2223-IMH-01), and the United States National Institutes of Health
(R01MH120080 & R01MH133334). Any opinions, findings and conclusions or recommendations
expressed in this material are those of the authors and do not reflect the views of the funders.

Data collection and sharing for this project was funded by the Alzheimer's Disease
Neuroimaging Initiative (ADNI) (National Institutes of Health Grant U01 AG024904) and DOD
ADNI (Department of Defense award number W81XWH-12-2-0012). ADNI is funded by the
National Institute on Aging, the National Institute of Biomedical Imaging and Bioengineering, and
through generous contributions from the following: AbbVie, Alzheimer's Association; Alzheimer's
Drug Discovery Foundation; Araclon Biotech; BioClinica, Inc.; Biogen; Bristol-Myers Squibb
Company; CereSpir, Inc.; Cogstate; Eisai Inc.; Elan Pharmaceuticals, Inc.; Eli Lilly and Company;
EuroImmun; F. Hoffmann-La Roche Ltd and its affiliated company Genentech, Inc.; Fujirebio; GE
Healthcare; IXICO Ltd.;Janssen Alzheimer Immunotherapy Research & Development, LLC.;
Johnson & Johnson Pharmaceutical Research & Development LLC.; Lumosity; Lundbeck; Merck
& Co., Inc.;Meso Scale Diagnostics, LLC.; NeuroRx Research; Neurotrack Technologies;
Novartis Pharmaceuticals Corporation; Pfizer Inc.; Piramal Imaging; Servier; Takeda
Pharmaceutical Company; and Transition Therapeutics. The Canadian Institutes of Health
Research is providing funds to support ADNI clinical sites in Canada. Private sector contributions
are facilitated by the Foundation for the National Institutes of Health (www.fnih.org). The grantee
organization is the Northern California Institute for Research and Education, and the study is
coordinated by the Alzheimer's Therapeutic Research Institute at the University of Southern
California. ADNI data are disseminated by the Laboratory for Neuro Imaging at the University of
Southern California.

Data were provided in part by OASIS-3: Longitudinal Multimodal Neuroimaging:
Principal Investigators: T. Benzinger, D. Marcus, J. Morris; NIH P30 AG066444, P50 AG00561,
P30 NS09857781, P01 AG026276, P01 AG003991, R01 AG043434, UL1 TR000448, R01
EB009352. AV-45 doses were provided by Avid Radiopharmaceuticals, a wholly owned
subsidiary of Eli Lilly.

7   Data availability statement

787 The ADNI and the AIBL datasets can be accessed via the Image & Data Archive
788 (https://ida.loni.usc.edu/). The MACC dataset can be obtained via a data-transfer agreement with
789 the MACC (http://www.macc.sg/). The OASIS dataset can be requested from (https://www.oasis-
790 brains.org/).

8   Code availability statement

791 Code   for   all   five   models   can   be   found   here
792 (https://github.com/ThomasYeoLab/CBIG/tree/master/stable_projects/predict_phenotypes/Zhang2
793 025_L2CFNN). Two co-authors (L.A. and N.W.) reviewed the code before merging it into the
794 GitHub repository to reduce the chance of coding errors.

9   Author contribution statement

C.Z.: Conceptualization; Data curation; Formal analysis; Investigation; Methodology;
Project administration; Software; Visualization; Writing – original draft; Writing – review &
editing. **L.A.**: Software; Validation; Visualization; Writing – review & editing. **N.W.**: Software;
Validation; Visualization; Writing – review & editing. **K.N.**: Investigation; Software; Data
curation; Visualization; Writing – review and editing. **C.O.**: Visualization; Writing – review and
editing. **P.C.**: Visualization; Writing – review & editing. **C.C.**: Resource; Writing – review &
editing. **J.H.Z.**: Resource; Writing – review & editing. **K.L.**: Methodology; Software; Writing –
review & editing. **B.T.T.Y.**: Conceptualization; Formal analysis; Funding acquisition;
Investigation; Methodology; Resource; Supervision; Visualization; Writing – original draft;
Writing – review & editing.

10 Conflict of interest statement

805 Associate Editor is co-author - Dr. Juan Helen Zhou is a handling editor of *Human Brain*
806 *Mapping* and a co-author of this article. To minimize bias, they were excluded from all editorial
807 decision-making related to the acceptance of this article for publication.

11 References

Aisen, P. S., Jimenez-Maggiora, G. A., Rafii, M. S., Walter, S., & Raman, R. (2022). Early-stage
Alzheimer disease: Getting trial-ready. *Nature Reviews Neurology*, *18*(7), 389–399.
https://doi.org/10.1038/s41582-022-00645-6Akiba, T., Sano, S., Yanase, T., Ohta, T., &
Koyama, M. (2019). Optuna: A Next-generation Hyperparameter Optimization Framework.
Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery
& Data Mining, 2623–2631. https://doi.org/10.1145/3292500.3330701
Barandas, M., Folgado, D., Fernandes, L., Santos, S., Abreu, M., Bota, P., Liu, H., Schultz, T., &
Gamboa, H. (2020). TSFEL: Time Series Feature Extraction Library. *SoftwareX*, *11*,
100456. https://doi.org/10.1016/j.softx.2020.100456
Basaia, S., Agosta, F., Wagner, L., Canu, E., Magnani, G., Santangelo, R., & Filippi, M. (2019).
Automated classification of Alzheimer's disease and mild cognitive impairment using a
single MRI and deep neural networks. *NeuroImage: Clinical*, *21*, 101645.
https://doi.org/10.1016/j.nicl.2018.101645
Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical and
Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society: Series B*
(Methodological), *57*(1), 289–300. https://doi.org/10.1111/j.2517-6161.1995.tb02031.x
Bilgel, M., Jedynak, B. M., & Initiative, A. D. N. (2019). Predicting time to dementia using a
quantitative template of disease progression. *Alzheimer's & Dementia: Diagnosis,*
Assessment & Disease Monitoring, *11*(1), 205–215.
https://doi.org/10.1016/j.dadm.2019.01.005
Burns, D. K., Alexander, R. C., Welsh-Bohmer, K. A., Culp, M., Chiang, C., O'Neil, J., Evans, R.
M., Harrigan, P., Plassman, B. L., Burke, J. R., Wu, J., Lutz, M. W., Haneline, S., Schwarz,
A. J., Schneider, L. S., Yaffe, K., Saunders, A. M., Ratti, E., Aarsland, D., … Zimmerman,
C. (2021). Safety and efficacy of pioglitazone for the delay of cognitive impairment in
people at risk of Alzheimer's disease (TOMMORROW): A prognostic biomarker study
and a phase 3, randomised, double-blind, placebo-controlled trial. *The Lancet Neurology*,
20(7), 537–547. https://doi.org/10.1016/S1474-4422(21)00043-0
Chen, P., An, L., Wulan, N., Zhang, C., Zhang, S., Ooi, L. Q. R., Kong, R., Chen, J., Wu, J.,
Chopra, S., Bzdok, D., Eickhoff, S. B., Holmes, A. J., & Yeo, B. T. T. (2024). Multilayer
meta-matching: Translating phenotypic prediction models from multiple datasets to small
data. *Imaging Neuroscience*, *2*, 1–22. https://doi.org/10.1162/imag_a_00233
Chen, T., & Guestrin, C. (2016). XGBoost: A Scalable Tree Boosting System. *Proceedings of the*
22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining,
785–794. https://doi.org/10.1145/2939672.2939785
Cheng, H., Yuan, S., Li, W., Yu, X., Liu, F., Liu, X., & Bezabih, T. T. (2024). De-accumulated
error collaborative learning framework for predicting Alzheimer's disease progression.
Biomedical Signal Processing and Control, *89*, 105767.
https://doi.org/10.1016/j.bspc.2023.105767
Chételat, G., Arbizu, J., Barthel, H., Garibotto, V., Law, I., Morbelli, S., Giessen, E. van de,
Agosta, F., Barkhof, F., Brooks, D. J., Carrillo, M. C., Dubois, B., Fjell, A. M., Frisoni, G.
B., Hansson, O., Herholz, K., Hutton, B. F., Jack, C. R., Lammertsma, A. A., … Drzezga,
A. (2020). Amyloid-PET and 18F-FDG-PET in the diagnostic investigation of Alzheimer's
disease and other dementias. *The Lancet Neurology*, *19*(11), 951–962.
https://doi.org/10.1016/S1474-4422(20)30314-8
Chincarini, A., Sensi, F., Rei, L., Gemme, G., Squarcia, S., Longo, R., Brun, F., Tangaro, S.,
Bellotti, R., Amoroso, N., Bocchetta, M., Redolfi, A., Bosco, P., Boccardi, M., Frisoni, G.
B., Nobili, F., & Alzheimer's Disease Neuroimaging Initiative. (2016). Integrating
longitudinal information in hippocampal volume measurements for the early detection of
Alzheimer's disease. *NeuroImage*, *125*, 834–847.
https://doi.org/10.1016/j.neuroimage.2015.10.065

Chong, J. R., Ashton, N. J., Karikari, T. K., Tanaka, T., Saridin, F. N., Reilhac, A., Robins, E. G., Nai, Y.-H., Vrooman, H., Hilal, S., Zetterberg, H., Blennow, K., Lai, M. K. P., & Chen, C. P. (2021). Plasma P-tau181 to Aβ42 ratio is associated with brain amyloid burden and hippocampal atrophy in an Asian cohort of Alzheimer's disease patients with concomitant cerebrovascular disease. *Alzheimer's & Dementia*, *17*(10), 1649–1662. https://doi.org/10.1002/alz.12332

Cohen, J. (1988). *Statistical Power Analysis for the Behavioral Sciences* (2nd ed.). Routledge. https://doi.org/10.4324/9780203771587

Courchesne, E., Chisum, H. J., Townsend, J., Cowles, A., Covington, J., Egaas, B., Harwood, M., Hinds, S., & Press, G. A. (2000). Normal Brain Development and Aging: Quantitative Analysis at in Vivo MR Imaging in Healthy Volunteers. *Radiology*, *216*(3), 672–682. https://doi.org/10.1148/radiology.216.3.r00au37672

Crawshaw, M. (2020). Multi-Task Learning with Deep Neural Networks: A Survey. *ArXiv*. https://www.semanticscholar.org/paper/Multi-Task-Learning-with-Deep-Neural-Networks%3A-A-Crawshaw/74f23063ca77f5b1caa3770a5957ae5fc565843e

de Vugt, M. E., & Verhey, F. R. J. (2013). The impact of early dementia diagnosis and intervention on informal caregivers. *Progress in Neurobiology*, *110*, 54–62. https://doi.org/10.1016/j.pneurobio.2013.04.005

Deng, H., Runger, G., Tuv, E., & Vladimir, M. (2013). A time series forest for classification and feature extraction. *Information Sciences*, *239*, 142–153. https://doi.org/10.1016/j.ins.2013.02.030

Desikan, R. S., Ségonne, F., Fischl, B., Quinn, B. T., Dickerson, B. C., Blacker, D., Buckner, R. L., Dale, A. M., Maguire, R. P., Hyman, B. T., Albert, M. S., & Killiany, R. J. (2006). An automated labeling system for subdividing the human cerebral cortex on MRI scans into gyral based regions of interest. *NeuroImage*, *31*(3), 968–980. https://doi.org/10.1016/j.neuroimage.2006.01.021

Dou, Q., Castro, D. C., Kamnitsas, K., & Glocker, B. (2019). Domain generalization via model-agnostic learning of semantic features. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems* (pp. 6450–6461). Curran Associates Inc.

Dubois, B., Hampel, H., Feldman, H. H., Scheltens, P., Aisen, P., Andrieu, S., Bakardjian, H., Benali, H., Bertram, L., Blennow, K., Broich, K., Cavedo, E., Crutch, S., Dartigues, J.-F., Duyckaerts, C., Epelbaum, S., Frisoni, G. B., Gauthier, S., Genthon, R., … Jack, C. R. (2016). Preclinical Alzheimer's disease: Definition, natural history, and diagnostic criteria. *Alzheimer's & Dementia: The Journal of the Alzheimer's Association*, *12*(3), 292–323. https://doi.org/10.1016/j.jalz.2016.02.002

El-Sappagh, S., Alonso, J. M., Islam, S. M. R., Sultan, A. M., & Kwak, K. S. (2021). A multilayer multimodal detection and prediction model based on explainable artificial intelligence for Alzheimer's disease. *Scientific Reports*, *11*(1), 2660. https://doi.org/10.1038/s41598-021-82098-3

Eriksson, D., Bindel, D., & Shoemaker, C. A. (2019). *pySOT and POAP: An event-driven asynchronous framework for surrogate optimization* (arXiv:1908.00420). arXiv. https://doi.org/10.48550/arXiv.1908.00420

Fan, C., Wang, J., Gang, W., & Li, S. (2019). Assessment of deep recurrent neural network-based strategies for short-term building energy predictions. *Applied Energy*, *236*, 700–710. https://doi.org/10.1016/j.apenergy.2018.12.004

Fischl, B., Salat, D. H., Busa, E., Albert, M., Dieterich, M., Haselgrove, C., van der Kouwe, A., Killiany, R., Kennedy, D., Klaveness, S., Montillo, A., Makris, N., Rosen, B., & Dale, A. M. (2002). Whole brain segmentation: Automated labeling of neuroanatomical structures in the human brain. *Neuron*, *33*(3), 341–355. https://doi.org/10.1016/s0896-6273(02)00569-x

Fowler, C., Rainey-Smith, S. R., Bird, S., Bomke, J., Bourgeat, P., Brown, B. M., Burnham, S. C., Bush, A. I., Chadunow, C., Collins, S., Doecke, J., Doré, V., Ellis, K. A., Evered, L., Fazlollahi, A., Fripp, J., Gardener, S. L., Gibson, S., Grenfell, R., … the AIBL investigators. (2021). Fifteen Years of the Australian Imaging, Biomarkers and Lifestyle (AIBL) Study: Progress and Observations from 2,359 Older Adults Spanning the Spectrum from Cognitive Normality to Alzheimer's Disease. *Journal of Alzheimer's Disease Reports*, *5*(1), 443–468. https://doi.org/10.3233/ADR-210005

Ghazi, M., Nielsen, M., Pai, A., Cardoso, M. J., Modat, M., Ourselin, S., & Sørensen, L. (2019). Training recurrent neural networks robust to incomplete data: Application to Alzheimer's disease progression modeling. *Medical Image Analysis*, *53*, 39–46. https://doi.org/10.1016/j.media.2019.01.004

Ghazi, M., Nielsen, M., Pai, A., Modat, M., Jorge Cardoso, M., Ourselin, S., & Sørensen, L. (2021). Robust parametric modeling of Alzheimer's disease progression. *NeuroImage*, *225*, 117460. https://doi.org/10.1016/j.neuroimage.2020.117460

Golovanevsky, M., Eickhoff, C., & Singh, R. (2022). Multimodal attention-based deep learning for Alzheimer's disease diagnosis. *Journal of the American Medical Informatics Association: JAMIA*, *29*(12), 2014–2022. https://doi.org/10.1093/jamia/ocac168

Good, P. (2000). Testing Hypotheses. In P. Good (Ed.), *Permutation Tests: A Practical Guide to Resampling Methods for Testing Hypotheses* (pp. 31–53). Springer. https://doi.org/10.1007/978-1-4757-3235-1_3

Hampel, H., Hardy, J., Blennow, K., Chen, C., Perry, G., Kim, S. H., Villemagne, V. L., Aisen, P., Vendruscolo, M., Iwatsubo, T., Masters, C. L., Cho, M., Lannfelt, L., Cummings, J. L., & Vergallo, A. (2021). The Amyloid-β Pathway in Alzheimer's Disease. *Molecular Psychiatry*, *26*(10), 5481–5503. https://doi.org/10.1038/s41380-021-01249-0

Hand, D. J., & Till, R. J. (2001). A Simple Generalisation of the Area Under the ROC Curve for Multiple Class Classification Problems. *Machine Learning*, *45*(2), 171–186. https://doi.org/10.1023/A:1010920819831

Hebling Vieira, B., Liem, F., Dadi, K., Engemann, D. A., Gramfort, A., Bellec, P., Craddock, R. C., Damoiseaux, J. S., Steele, C. J., Yarkoni, T., Langer, N., Margulies, D. S., & Varoquaux, G. (2022). Predicting future cognitive decline from non-brain and multimodal brain imaging data in healthy and pathological aging. *Neurobiology of Aging*, *118*, 55–65. https://doi.org/10.1016/j.neurobiolaging.2022.06.008

Hett, K., Ta, V.-T., Oguz, I., Manjón, J. V., Coupé, P., & Alzheimer's Disease Neuroimaging Initiative. (2021). Multi-scale graph-based grading for Alzheimer's disease prediction. *Medical Image Analysis*, *67*, 101850. https://doi.org/10.1016/j.media.2020.101850

Herrick, R., Horton, W., Olsen, T., McKay, M., Archie, K. A., & Marcus, D. S. (2016). XNAT Central: Open Sourcing Imaging Research Data. *NeuroImage*, *124*(Pt B), 1093–1096. https://doi.org/10.1016/j.neuroimage.2015.06.076

Hilal, S., Tan, C. S., van Veluw, S. J., Xu, X., Vrooman, H., Tan, B. Y., Venketasubramanian, N., Biessels, G. J., & Chen, C. (2020). Cortical cerebral microinfarcts predict cognitive decline in memory clinic patients. *Journal of Cerebral Blood Flow and Metabolism: Official Journal of the International Society of Cerebral Blood Flow and Metabolism*, *40*(1), 44–53. https://doi.org/10.1177/0271678X19835565

Iddi, S., Li, D., Aisen, P. S., Rafii, M. S., Thompson, W. K., Donohue, M. C., & for the Alzheimer's Disease Neuroimaging Initiative. (2019). Predicting the course of Alzheimer's progression. *Brain Informatics*, *6*(1), 6. https://doi.org/10.1186/s40708-019-0099-0

Ilievski, I., Akhtar, T., Feng, J., & Shoemaker, C. (2017). Efficient Hyperparameter Optimization for Deep Learning Algorithms Using Deterministic RBF Surrogates. *Proceedings of the AAAI Conference on Artificial Intelligence*, *31*(1), Article 1. https://doi.org/10.1609/aaai.v31i1.10647

Jack, C. R., Bennett, D. A., Blennow, K., Carrillo, M. C., Dunn, B., Haeberlein, S. B., Holtzman, D. M., Jagust, W., Jessen, F., Karlawish, J., Liu, E., Molinuevo, J. L., Montine, T., Phelps,

C., Rankin, K. P., Rowe, C. C., Scheltens, P., Siemers, E., Snyder, H. M., … Contributors. (2018). NIA-AA Research Framework: Toward a biological definition of Alzheimer's disease. *Alzheimer's & Dementia: The Journal of the Alzheimer's Association*, *14*(4), 535–562. https://doi.org/10.1016/j.jalz.2018.02.018

Jack, C. R., Bernstein, M. A., Fox, N. C., Thompson, P., Alexander, G., Harvey, D., Borowski, B., Britson, P. J., L Whitwell, J., Ward, C., Dale, A. M., Felmlee, J. P., Gunter, J. L., Hill, D. L. G., Killiany, R., Schuff, N., Fox-Bosetti, S., Lin, C., Studholme, C., … Weiner, M. W. (2008). The Alzheimer's Disease Neuroimaging Initiative (ADNI): MRI methods. *Journal of Magnetic Resonance Imaging: JMRI*, *27*(4), 685–691. https://doi.org/10.1002/jmri.21049

Jack, C. R., Knopman, D. S., Jagust, W. J., Shaw, L. M., Aisen, P. S., Weiner, M. W., Petersen, R. C., & Trojanowski, J. Q. (2010). Hypothetical model of dynamic biomarkers of the Alzheimer's pathological cascade. *The Lancet Neurology*, *9*(1), 119–128. https://doi.org/10.1016/S1474-4422(09)70299-6

Jack, C. R., Shiung, M. M., Gunter, J. L., O'Brien, P. C., Weigand, S. D., Knopman, D. S., Boeve, B. F., Ivnik, R. J., Smith, G. E., Cha, R. H., Tangalos, E. G., & Petersen, R. C. (2004). Comparison of different MRI brain atrophy rate measures with clinical disease progression in AD. *Neurology*, *62*(4), 591–600. https://doi.org/10.1212/01.wnl.0000110315.26026.ef

Jedynak, B. M., Lang, A., Liu, B., Katz, E., Zhang, Y., Wyman, B. T., Raunig, D., Jedynak, C. P., Caffo, B., & Prince, J. L. (2012). A computational neurodegenerative disease progression score: Method and results with the Alzheimer's disease neuroimaging initiative cohort. *NeuroImage*, *63*(3), 1478–1486. https://doi.org/10.1016/j.neuroimage.2012.07.059

Jenkins, R., Fox, N. C., Rossor, A. M., Harvey, R. J., & Rossor, M. N. (2000). Intracranial volume and Alzheimer disease: Evidence against the cerebral reserve hypothesis. *Archives of Neurology*, *57*(2), 220–224. https://doi.org/10.1001/archneur.57.2.220

Jung, W., Jun, E., & Suk, H.-I. (2021). Deep recurrent model for individualized prediction of Alzheimer's disease progression. *NeuroImage*, *237*, 118143. https://doi.org/10.1016/j.neuroimage.2021.118143

Kong, R., Li, J., Orban, C., Sabuncu, M. R., Liu, H., Schaefer, A., Sun, N., Zuo, X.-N., Holmes, A. J., Eickhoff, S. B., & Yeo, B. T. T. (2019). Spatial Topography of Individual-Specific Cortical Networks Predicts Human Cognition, Personality, and Emotion. *Cerebral Cortex (New York, N.Y.: 1991)*, *29*(6), 2533–2551. https://doi.org/10.1093/cercor/bhy123

Koval, I., Bône, A., Louis, M., Lartigue, T., Bottani, S., Marcoux, A., Samper-González, J., Burgos, N., Charlier, B., Bertrand, A., Epelbaum, S., Colliot, O., Allassonnière, S., & Durrleman, S. (2021). AD Course Map charts Alzheimer's disease progression. *Scientific Reports*, *11*(1), Article 1. https://doi.org/10.1038/s41598-021-87434-1

LaMontagne, Tammie LS. Benzinger, John C. Morris, Sarah Keefe, Russ Hornbeck, Chengjie Xiong, Elizabeth Grant, Jason Hassenstab, Krista Moulder, Andrei G. Vlassenko, Marcus E. Raichle, Carlos Cruchaga, & Daniel Marcus. (2019). OASIS-3: Longitudinal Neuroimaging, Clinical, and Cognitive Dataset for Normal Aging and Alzheimer Disease. *medRxiv*, 2019.12.13.19014902. https://doi.org/10.1101/2019.12.13.19014902

Li, D., Iddi, S., Thompson, W. K., Donohue, M. C., & Alzheimer's Disease Neuroimaging Initiative. (2019). Bayesian latent time joint mixed effect models for multicohort longitudinal data. *Statistical Methods in Medical Research*, *28*(3), 835–845. https://doi.org/10.1177/0962280217737566

Li, J., Kong, R., Liégeois, R., Orban, C., Tan, Y., Sun, N., Holmes, A. J., Sabuncu, M. R., Ge, T., & Yeo, B. T. T. (2019). Global signal regression strengthens association between resting-state functional connectivity and behavior. *NeuroImage*, *196*, 126–141. https://doi.org/10.1016/j.neuroimage.2019.04.016

Liang, W., Zhang, K., Cao, P., Liu, X., Yang, J., & Zaiane, O. (2021). Rethinking modeling Alzheimer's disease progression from a multi-task learning perspective with deep recurrent

neural network. *Computers in Biology and Medicine*, *138*, 104935. https://doi.org/10.1016/j.compbiomed.2021.104935

Liu, Q., Dou, Q., Yu, L., & Heng, P. A. (2020). MS-Net: Multi-Site Network for Improving Prostate Segmentation With Heterogeneous MRI Data. *IEEE Transactions on Medical Imaging*, *39*(9), 2713–2724. https://doi.org/10.1109/TMI.2020.2974574

Maas, A. L. (2013). *Rectifier Nonlinearities Improve Neural Network Acoustic Models*. https://www.semanticscholar.org/paper/Rectifier-Nonlinearities-Improve-Neural-Network-Maas/367f2c63a6f6a10b3b64b8729d601e69337ee3cc

Maheux, E., Koval, I., Ortholand, J., Birkenbihl, C., Archetti, D., Bouteloup, V., Epelbaum, S., Dufouil, C., Hofmann-Apitius, M., & Durrleman, S. (2023). Forecasting individual progression trajectories in Alzheimer's disease. *Nature Communications*, *14*(1), 761. https://doi.org/10.1038/s41467-022-35712-5

Marinescu, R. V., Oxtoby, N. P., Young, A. L., Bron, E. E., Toga, A. W., Weiner, M. W., Barkhof, F., Fox, N. C., Eshaghi, A., Toni, T., Salaterski, M., Lunina, V., Ansart, M., Durrleman, S., Lu, P., Iddi, S., Li, D., Thompson, W. K., Donohue, M. C., … The Alzheimer's Disease Neuroimaging Initiative. (2021). The Alzheimer's Disease Prediction Of Longitudinal Evolution (TADPOLE) Challenge: Results after 1 Year Follow-up. *Machine Learning for Biomedical Imaging*, *1*(December 2021 issue), 1–60. https://doi.org/10.59275/j.melba.2021-2dcc

Marinescu, R. V., Oxtoby, N. P., Young, A. L., Bron, E. E., Toga, A. W., Weiner, M. W., Barkhof, F., Fox, N. C., Golland, P., Klein, S., & Alexander, D. C. (2019). TADPOLE Challenge: Accurate Alzheimer's disease prediction through crowdsourced forecasting of future data. *PRedictive Intelligence in MEdicine. PRIME (Workshop)*, *11843*, 1–10. https://doi.org/10.1007/978-3-030-32281-6_1

Mattsson, N., Andreasson, U., Zetterberg, H., Blennow, K., & for the Alzheimer's Disease Neuroimaging Initiative. (2017). Association of Plasma Neurofilament Light With Neurodegeneration in Patients With Alzheimer Disease. *JAMA Neurology*, *74*(5), 557–566. https://doi.org/10.1001/jamaneurol.2016.6117

Nadeau, C., & Bengio, Y. (2003). Inference for the Generalization Error. *Machine Learning*, *52*(3), 239–281. https://doi.org/10.1023/A:1024068626366

Nanopoulos, A., Alcock, R., & Manolopoulos, Y. (2001). Feature-based classification of time-series data. In *Information processing and technology* (pp. 49–61). Nova Science Publishers, Inc.

Nguyen, M., He, T., An, L., Alexander, D. C., Feng, J., & Yeo, B. T. T. (2020). Predicting Alzheimer's disease progression using deep recurrent neural networks. *NeuroImage*, *222*, 117203. https://doi.org/10.1016/j.neuroimage.2020.117203

Nordberg, A., Rinne, J. O., Kadir, A., & Långström, B. (2010). The use of PET in Alzheimer disease. *Nature Reviews Neurology*, *6*(2), 78–87. https://doi.org/10.1038/nrneurol.2009.217

O'Bryant, S. E., Lacritz, L. H., Hall, J., Waring, S. C., Chan, W., Khodr, Z. G., Massman, P. J., Hobson, V., & Cullum, C. M. (2010). Validation of the New Interpretive Guidelines for the Clinical Dementia Rating Scale Sum of Boxes Score in the National Alzheimer's Coordinating Center Database. *Archives of Neurology*, *67*(6), 746–749. https://doi.org/10.1001/archneurol.2010.115

Ocasio, E., & Duong, T. Q. (2021). Deep learning prediction of mild cognitive impairment conversion to Alzheimer's disease at 3 years after diagnosis using longitudinal and whole-brain 3D MRI. *PeerJ Computer Science*, *7*, e560. https://doi.org/10.7717/peerj-cs.560

Oxtoby, N. P. (2023). Data-Driven Disease Progression Modeling. In O. Colliot (Ed.), *Machine Learning for Brain Disorders*. Humana. http://www.ncbi.nlm.nih.gov/books/NBK597485/

Oxtoby, N. P., Shand, C., Cash, D. M., Alexander, D. C., & Barkhof, F. (2022). Targeted Screening for Alzheimer's Disease Clinical Trials Using Data-Driven Disease Progression Models. *Frontiers in Artificial Intelligence*, *5*, 660581. https://doi.org/10.3389/frai.2022.660581

Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin, Z., Gimelshein, N., Antiga, L., Desmaison, A., Kopf, A., Yang, E., DeVito, Z., Raison, M., Tejani, A., Chilamkurthy, S., Steiner, B., Fang, L., … Chintala, S. (2019). PyTorch: An Imperative Style, High-Performance Deep Learning Library. *Advances in Neural Information Processing Systems*, *32*. https://papers.nips.cc/paper_files/paper/2019/hash/bdbca288fee7f92f2bfa9f7012727740-Abstract.html

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., & Duchesnay, É. (2011). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research*, *12*(85), 2825–2830.

Petersen, R. C., Aisen, P. S., Beckett, L. A., Donohue, M. C., Gamst, A. C., Harvey, D. J., Jack, C. R., Jagust, W. J., Shaw, L. M., Toga, A. W., Trojanowski, J. Q., & Weiner, M. W. (2010). Alzheimer's Disease Neuroimaging Initiative (ADNI): Clinical characterization. *Neurology*, *74*(3), 201–209. https://doi.org/10.1212/WNL.0b013e3181cb3e25

Porsteinsson, A. P., Isaacson, R. S., Knox, S., Sabbagh, M. N., & Rubino, I. (2021). Diagnosis of Early Alzheimer's Disease: Clinical Practice in 2021. *The Journal of Prevention of Alzheimer's Disease*, *8*(3), 371–386. https://doi.org/10.14283/jpad.2021.23

Qian, N. (1999). On the momentum term in gradient descent learning algorithms. *Neural Networks*, *12*(1), 145–151. https://doi.org/10.1016/S0893-6080(98)00116-6

Rahim, M., Thirion, B., Bzdok, D., Buvat, I., & Varoquaux, G. (2017). Joint prediction of multiple scores captures better individual traits from brain images. *NeuroImage*, *158*, 145–154. https://doi.org/10.1016/j.neuroimage.2017.06.072

Rasmussen, J., & Langerman, H. (2019). Alzheimer's Disease—Why We Need Early Diagnosis. *Degenerative Neurological and Neuromuscular Disease*, *9*, 123–130. https://doi.org/10.2147/DNND.S228939

Reas, E. T., Shadrin, A., Frei, O., Motazedi, E., McEvoy, L., Bahrami, S., van der Meer, D., Makowski, C., Loughnan, R., Wang, X., Broce, I., Banks, S. J., Fominykh, V., Cheng, W., Holland, D., Smeland, O. B., Seibert, T., Selbæk, G., Brewer, J. B., … Dale, A. M. (2023). Improved multimodal prediction of progression from MCI to Alzheimer's disease combining genetics with quantitative brain MRI and cognitive measures. *Alzheimer's & Dementia: The Journal of the Alzheimer's Association*, *19*(11), 5151–5158. https://doi.org/10.1002/alz.13112

Scheltens, P., Blennow, K., Breteler, M. M. B., Strooper, B. de, Frisoni, G. B., Salloway, S., & Flier, W. M. V. der. (2016). Alzheimer's disease. *The Lancet*, *388*(10043), 505–517. https://doi.org/10.1016/S0140-6736(15)01124-1

Selkoe, D. J., & Hardy, J. (2016). The amyloid hypothesis of Alzheimer's disease at 25 years. *EMBO Molecular Medicine*, *8*(6), 595–608. https://doi.org/10.15252/emmm.201606210

Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., & Salakhutdinov, R. (2014). Dropout: A Simple Way to Prevent Neural Networks from Overfitting. *Journal of Machine Learning Research*, *15*(56), 1929–1958.

Sutskever, I., Martens, J., Dahl, G., & Hinton, G. (2013). On the importance of initialization and momentum in deep learning. *Proceedings of the 30th International Conference on Machine Learning*, 1139–1147. https://proceedings.mlr.press/v28/sutskever13.html

Tariot, P. N., Boada, M., Lanctôt, K. L., Hahn-Pedersen, J., Dabbous, F., Udayachalerm, S., Raket, L. L., Halchenko, Y., Michalak, W., Weidner, W., & Cummings, J. (2024). Relationships of change in Clinical Dementia Rating (CDR) on patient outcomes and probability of progression: Observational analysis. *Alzheimer's Research & Therapy*, *16*(1), 36. https://doi.org/10.1186/s13195-024-01399-7

the ADNI team. (2023). *ADNIMERGE: Alzheimer's Disease Neuroimaging Initiative* (0.0.1) [R package]. https://adni.bitbucket.io/index.html

U.S. Social Security Administration. (2020). *Actuarial life table*. Social Security. https://www.ssa.gov/oact/STATS/table4c6.html

Van Dyck, C. H., Swanson, C. J., Aisen, P., Bateman, R. J., Chen, C., Gee, M., Kanekiyo, M., Li, D., Reyderman, L., Cohen, S., Froelich, L., Katayama, S., Sabbagh, M., Vellas, B., Watson, D., Dhadda, S., Irizarry, M., Kramer, L. D., & Iwatsubo, T. (2023). Lecanemab in Early Alzheimer's Disease. *The New England Journal of Medicine*, *388*(1), 9–21. https://doi.org/10.1056/NEJMoa2212948

Varoquaux, G. (2018). Cross-validation failure: Small sample sizes lead to large error bars. *NeuroImage*, *180*, 68–77. https://doi.org/10.1016/j.neuroimage.2017.06.061

Venkatraghavan, V., Bron, E. E., Niessen, W. J., & Klein, S. (2019). Disease progression timeline estimation for Alzheimer's disease using discriminative event based modeling. *NeuroImage*, *186*, 518–532. https://doi.org/10.1016/j.neuroimage.2018.11.024

Villemagne, V. L., Burnham, S., Bourgeat, P., Brown, B., Ellis, K. A., Salvado, O., Szoeke, C., Macaulay, S. L., Martins, R., Maruff, P., Ames, D., Rowe, C. C., Masters, C. L., & Australian Imaging Biomarkers and Lifestyle (AIBL) Research Group. (2013). Amyloid β deposition, neurodegeneration, and cognitive decline in sporadic Alzheimer's disease: A prospective cohort study. *The Lancet. Neurology*, *12*(4), 357–367. https://doi.org/10.1016/S1474-4422(13)70044-9

Wang, C., Li, Y., Tsuboshita, Y., Sakurai, T., Goto, T., Yamaguchi, H., Yamashita, Y., Sekiguchi, A., & Tachimori, H. (2022). A high-generalizability machine learning framework for predicting the progression of Alzheimer's disease using limited data. *Npj Digital Medicine*, *5*(1), Article 1. https://doi.org/10.1038/s41746-022-00577-x

Xu, L., Wu, H., He, C., Wang, J., Zhang, C., Nie, F., & Chen, L. (2022). Multi-modal sequence learning for Alzheimer's disease progression prediction with incomplete variable-length longitudinal data. *Medical Image Analysis*, *82*, 102643. https://doi.org/10.1016/j.media.2022.102643

Zhang, R., Simon, G., & Yu, F. (2017). Advancing Alzheimer's Research: A Review of Big Data Promises. *International Journal of Medical Informatics*, *106*, 48–56. https://doi.org/10.1016/j.ijmedinf.2017.07.002

Zhao, Y., Wong, L., & Goh, W. W. B. (2020). How to do quantile normalization correctly for gene expression data analyses. *Scientific Reports*, *10*(1), Article 1. https://doi.org/10.1038/s41598-020-72664-6