ClinVec: Unified Embeddings of Clinical Codes Enable Knowledge-Grounded AI in Medicine

Ruth Johnson[1,2], Uri Gottlieb[3], Galit Shaham[3], Lihi Eisen[3], Jacob Waxman[3], Stav Devons-Sberro[3], Curtis R. Ginder[4], Peter Hong[5,6,7], Raheel Sayeed[2], Xiaorui Su[2], Ben Y. Reis[1,2,8,11], Ran D. Balicer[1,3,9], Noa Dagan[1,2,3,10,*], and Marinka Zitnik[1,2,11,12,13,*]

[1] The Ivan and Francesca Berkowitz Family Living Laboratory Collaboration at Harvard Medical School and Clalit Research Institute, Boston, MA, USA
[2] Department of Biomedical Informatics, Harvard Medical School, Boston, MA, USA
[3] Clalit Research Institute, Innovation Division, Clalit Health Services, Ramat-Gan, Israel
[4] Cardiovascular Division, Department of Medicine, Brigham and Women's Hospital, Harvard Medical School, Boston, MA, USA
[5] Division of General Pediatrics, Department of Pediatrics, Boston Children's Hospital, Boston, MA, USA
[6] Information Technology, Enterprise Data Analytics and Reporting, Boston Children's Hospital, Boston, MA, USA
[7] Department of Pediatrics, Harvard Medical School, Boston, MA, USA
[8] Predictive Medicine Group, Computational Health Informatics Program, Boston Children's Hospital, Boston, MA, USA
[9] Faculty of Health Sciences, School of Public Health, Ben Gurion University of the Negev, Be'er Sheva, Israel
[10] Software and Information Systems Engineering, Ben Gurion University, Be'er Sheva, Israel
[11] Harvard Data Science Initiative, Cambridge, MA, USA
[12] Broad Institute of MIT and Harvard, Cambridge, MA, USA
[13] Kempner Institute for the Study of Natural and Artificial Intelligence, Harvard University, Allston, MA, USA
* Joint correspondence: noada@clalit.org.il and marinka@hms.harvard.edu

Integrating structured clinical knowledge into artificial intelligence (AI) models remains a major challenge. Medical codes primarily reflect administrative workflows rather than clinical reasoning, limiting AI models' ability to capture true clinical relationships and undermining their generalizability. To address this, we introduce *ClinGraph*, a clinical knowledge graph that integrates eight EHR-based vocabularies, and *ClinVec*, a set of 153,166 clinical code embeddings derived from *ClinGraph* using a graph transformer neural network. *ClinVec* provides a machine-readable representation of clinical knowledge that captures semantic relationships among diagnoses, medications, laboratory tests, and procedures. Panels of clinicians from multiple institutions evaluated the embeddings across 96 diseases and more than 3,000 clinical codes, confirming their alignment with expert knowledge. In a retrospective analysis of 4.57 million patients from Clalit Health Services, we show that *ClinVec* supports phenotype risk scoring and stratifies individuals by survival outcomes. We further demonstrate that injecting *ClinVec* into large language models improves performance on medical question answering, including for region-specific clinical scenarios. *ClinVec* enables structured clinical knowledge to be injected into predictive and generative AI models, bridging the gap between EHR codes and clinical reasoning.

Introduction

Medicine builds on centuries of accumulated knowledge and the goal of individualized patient care through clinical reasoning and evidence-based practice[1]. Over time, medical vocabularies and ontologies have been developed to represent clinical information, fostering interoperability and data exchange across healthcare systems[2–4]. However, these standardized coding systems remain fragmented, with each vocabulary designed for specific use cases. This fragmentation limits their integration into artificial intelligence (AI) models and introduces a gap between clinical knowledge and its computational representation in precision medicine.

The widespread adoption of electronic health records (EHRs) and data standardization initiatives has accelerated the use of structured clinical data in AI models[5,6], with more than half of healthcare foundation AI models relying on structured clinical codes, such as billing data and medication records[7]. These models implicitly assume that EHRs contain information sufficient to capture the clinical concepts relevant to patient care. In practice, this assumption often fails. Models trained on EHR data frequently learn patterns specific to a single healthcare system rather than generalizable medical relationships[8–11]. The variability of clinical codes across institutions further limits the transferability of prediction models[12–15]. Many codes are selected or recorded for operational rather than clinical reasons[16], influenced by geographic factors[17–19], national policies[20–23], insurance requirements[24–26], physician practices[27–29], and other features of local healthcare delivery[30–34]. EHR-based models, as a result, often fail to reflect consistent clinical definitions or relationships among codes[35–39].

The lack of alignment between EHR-based prediction models and clinical knowledge also introduces concerns about model bias and transparency[40]. Although large language models (LLMs) offer implicit access to clinical knowledge embedded within their training data, unvetted datasets from biological data repositories and scientific articles used to train LLMs can increase the risk of bias and mistakes in generated outputs[41–43]. LLMs can struggle to represent clinical codes[44–46], especially rare or highly specific codes, resulting in inaccuracies, over-generalizations, or hallucinations during inference[47]. This can be concerning given that a large portion of medical codes may not be used in everyday clinical practice where, for example, fewer than 5% of SNOMED CT codes account for 95% of usage in healthcare institutions[48], creating a mismatch between what is modeled and what is clinically relevant.

Most AI models lack mechanisms to integrate clinical knowledge, limiting their ability to align

with medical best practices[49,50]. Clinical researchers have published over 3,700 evidence-based

guidelines across 39 countries[51–54], yet this structured knowledge remains largely unused in

model development. Most AI models rely on statistical patterns in patient data or text corpora,

but these approaches do not capture the clinical knowledge embedded in structured EHR codes.

Bridging this gap requires consistent, machine-readable representations that reflect how clinical

codes relate to real-world medical practice. While embeddings exist for text and images[55–60], no

comparable resource captures structured clinical knowledge for use in AI models.

To address the gap between clinical knowledge and structured EHR data, we developed a

ClinGraph, a clinical knowledge graph spanning eight standardized medical vocabularies, and

ClinVec, a set of 153,166 clinical code embeddings derived from *ClinGraph*. *ClinVec* defines a

unified, machine-readable latent space that captures relationships among diagnoses, medications,

laboratory tests, and procedures. This approach generates clinically meaningful representations

of medical codes in a hypothesis-free manner and provides a resource for integrating structured

clinical knowledge into predictive models for precision medicine. The learned embeddings re-

veal patterns aligned with human anatomy and disease phenotypes and were validated by panels

of clinical experts across 96 diseases and more than 3,000 clinical codes. We further demonstrate

the predictive utility of *ClinVec* through phenotype risk score analyses for chronic kidney dis-

ease, chronic obstructive pulmonary disease, and heart failure, using EHR data from 4.57 million

patients in Clalit Health Services. Finally, we show that integrating *ClinVec* into large language

models improves medical question answering across a range of clinical scenarios. *ClinGraph* and

ClinVec provide a foundation for embedding structured clinical knowledge into AI models, sup-

porting interpretability, cross-institutional transferability, and alignment with clinical practice.

Results

ClinGraph **and** *ClinVec***: Representing structured medical knowledge for AI**

Many efforts have focused on structuring clinical knowledge for enhanced interoperability and

data harmonization. Clinical knowledge has been traditionally structured using Common Data

Models (CDMs), which standardize data by mapping diverse coding systems into a unified

schema[61]. Alternatively, biomedical ontologies organize information in a hierarchical structure to

facilitate semantic interoperability and reasoning across coding systems. However, both rely on

fixed schemas and expert-defined relationships that limit their contextual richness and

adaptability to real-world data. KGs offer a more flexible approach by integrating diverse

knowledge sources without rigid schema constraints. However, most knowledge graphs do not

explicitly incorporate standard clinical vocabularies and instead focus on biological processes[62–

64], therapeutics[55,65,66], genetic phenotypes[67–70], or a combination thereof[71–73]. KGs that incorpo-

rate clinical vocabularies are often restricted to ICD codes (diagnosis codes) or rely on medical

terminologies like HPO[74] and MONDO[75], which are not standard in most EHRs[76–78]. Several ap-

proaches construct KGs directly from patient data[79–81], but this process is highly sensitive to the

source patient population, potentially limiting generalizability.

We develop a resource consisting of *ClinGraph*, a knowledge graph consisting of 153,166 nodes

and 2,873,025 edges spanning eight clinical vocabularies (Figure 1A, 1B), and *ClinVec*, a set of

high-dimensional, vector representations (embeddings) of clinical knowledge that can be inte-

grated into AI models (Figure 1C, 1D). *ClinGraph* incorporates diagnosis codes (ICD9CM,

ICD10CM, phecodes), laboratory tests (LOINC), medications (RxNorm, ATC), procedures

(CPT), and other controlled clinical vocabularies (SNOMED CT, UMLS), and represents each

concept in the KG as a medical code (Supplementary Table S1). Relational information is de-

rived from multiple databases, including ontologies such as Unified Medical Language System[82]

(UMLS) and empirically constructed knowledge bases such as PheMap[83], which derives relation-

ships from the large-scale mining of biomedical literature (Supplementary Table S2).

Figure 1: Overview of approach. (A) Meta-graph showing the structure of *ClinGraph* and the edge relationships between clinical vocabularies shown as node types. **(B)** An example local neighborhood of *ClinGraph*. Each clinical code is represented as a node, and the color denotes the clinical vocabulary. **(C)** Workflow for generating clinical knowledge embeddings: building the clinical knowledge graph, constructing a graph transformer model, and generating embeddings through self-supervised learning. **(D)** Clinical AI applications of *ClinGraph* and *ClinVec*.

A key feature of *ClinGraph* is that it represents clinical concepts using their original coding systems, rather than aggregating them into a common vocabulary. This design preserves coding-specific structures such as hierarchical relationships and clinically meaningful groupings and avoids the information loss that can occur when mapping between vocabularies. To evaluate the coverage of EHR coding systems, we compared *ClinGraph* to six existing KGs. For each KG, we mapped its node identifiers to EHR codes and calculated the proportion of coverage for common coding systems (Supplementary Table S3). *ClinGraph* is the only resource that integrates diagnoses, medications, laboratory tests, and procedures in a unified framework based on structured EHR data. Other KGs do not include nodes for procedures or laboratory tests. While *ClinGraph*, PrimeKG[76], and PharMeBINet[84] capture similar proportions of ICD10CM codes, *ClinGraph* spans a broader range of diagnoses. By evaluating the number of distinct ICD10CM root codes (for example, J45), we found that *ClinGraph* includes 35% more disease areas than other graphs. This likely reflects the clinical orientation of *ClinGraph*, in contrast to other resources that emphasize biological and genetic phenotypes.

While KGs represent information as discrete nodes and edges, embedding-based representations
create a machine-readable form of information that encodes clinical concepts and their contex-
tual information into continuous vectors. Transforming discrete KGs into continuous embed-
dings enables complex inference tasks, such as grounding AI models in clinical knowledge[85],
that are not possible using only node-and-edge graph representations. Using a heterogenous
graph transformer (HGT)[86], we learn a function that maps each node (medical code) in the KG to
low-dimensional representations (embeddings). The KG determines how information is shared
between nodes throughout the KG, while a multi-head attention mechanism enhances the
model's ability to up-weight and down-weight different parts of the topological space[87]. We
model four distinct node types—diagnosis codes, medications, laboratory tests/procedures, and
clinical concepts/vocabularies—where grouping similar vocabularies (e.g., RxNorm and ATC)
enables information sharing across related nodes while preserving enough type-specific infor-
mation to support effective parameter learning (Methods). We train the model for edge predic-
tion through self-supervised learning via contrastive edge masking[88]. This approach generates
embeddings for each clinical code such that codes located near one another in the knowledge
graph are also positioned closely in the latent space, reflecting their semantic similarity.

To support the integration of *ClinVec* into AI models, the learned embeddings must be consistent
with current clinical knowledge and reflect information used in routine healthcare. Existing ref-
erence datasets for evaluating the semantic relatedness of clinical terms are limited in size (fewer
than 1,500 data points) and based on outdated coding systems that include obsolete codes. We
constructed a new validation dataset consisting of 96 diseases across 10 major disease categories,
such as circulatory and respiratory disorders, and over 3,000 SNOMED CT codes. A panel of ex-
pert clinicians from Israel and the United States annotated the dataset. Based on clinician input,
we selected 96 phecodes representing conditions that are clinically relevant to general adult pa-
tient populations. For each phecode, we identified the 20 SNOMED CT codes with the highest
cosine similarity to the phecode embedding and randomly sampled an additional 20 SNOMED
CT codes as controls (Figure 2A).

Codes already forming an edge with the disease node within the knowledge graph were excluded
from the analysis. The final evaluation dataset comprises 96 disease lists, each with 40
SNOMED CT codes for a total of 3,680 data points, almost 3 times the size of existing bench-
marks combined.

Figure 2: Concordance between *ClinVec* embedding similarity and clinical expert scores. (A) Overview of clinical expert review process. **(B)** We report the mean cosine similarity across all disease-term pairs stratified by clinical expert scores 1-5. **(C)** We stratify cosine similarity scores across four disease categories and show examples of SNOMED CT codes that were assigned a clinical expert score of 5.

To assess the relevance of each clinical code to a given disease, clinicians graded SNOMED CT codes on a scale from 1 (unrelated) to 5 (very relevant), evaluating both accuracy and applicability to clinical practice (Figure 2B). Clinicians graded each SNOMED CT code on a scale from 1 to 5, where 1 indicated the code was unrelated to the target disease and 5 indicated it was highly relevant and frequently observed in clinical practice. We compared these expert ratings to the cosine similarity between the corresponding *ClinVec* embeddings. Grouping similarity scores by clinician rating revealed a positive correlation, with mean cosine similarity increasing across scores 1 to 5 (0.30, 0.53, 0.58, 0.63, 0.61). When stratifying by disease category, we observed lower alignment for neoplasms compared to other categories. In this case, high embedding similarity was often assigned a low clinical relevance score by reviewers. This misalignment likely reflects the heterogeneity of neoplasms, which vary by organ system, stage, and metastatic

behavior. Among disease-code pairs with low clinician scores (≤2) and high cosine similarity

(>0.8), many mismatches involved anatomical proximity rather than clinical relevance. For ex-

ample, top-scoring terms for "cancer of salivary glands" included thyroid conditions. Although

these organs are anatomically adjacent and involved in autoimmune diseases such as Sjögren's

syndrome or Hashimoto's thyroiditis, they are not directly related in the context of salivary gland

cancer. These findings suggest that embeddings for highly specific diseases could benefit from

fine-tuning on subgraphs of the KG to improve granularity and clinical alignment.

Anatomical and medical subspecialty structure emerge in the embedding space

Clinical knowledge embeddings must capture patterns that align with human biology, disease

presentation, and clinical workflows. Although *ClinGraph* shares some content with other bio-

medical KGs, its integration of clinical vocabularies and relationship types produces embeddings

that more effectively represent clinically meaningful structure in the latent space. To evaluate

this, we trained heterogeneous graph transformers on PrimeKG and a SNOMED CT-based KG

using the same model architecture and training setup as for *ClinGraph*, and compared the result-

ing embedding spaces (Methods).

We characterize the breadth and granularity of the clinical knowledge represented in the learned

embeddings. Visualizing the latent space of disease (Figure 3A, Supplementary Figure S1A-C)

and drug embeddings (Figure 3B, Supplementary Figure S1D-F) generated by each KG, the em-

beddings derived from *ClinGraph* broadly maintain groupings of diseases by organ system, mir-

roring the organization of clinical care. However, embeddings produced by PrimeKG and

SNOMED-CT KG do not exhibit this distinct clustering pattern. This observation is supported

when comparing silhouette scores and adjusted mutual information (AMI) where embedding

clusters from *ClinGraph* (silhouette: 0.54, AMI: 0.31) produce metrics at the same value or

greater than clusters produced from other KGs (PrimeKG - silhouette: 0.54, AMI: 0.02;

SNOMED-CT KG - silhouette: 0.15, AMI: -1e-4). Further examining the clusters of phecode

embeddings from *ClinGraph*, although some phenotypes deviate from these main clusters, many

deviations reflect known distinctions within clinical care. For example, most endocrine condi-

tions cluster together (Figure 3A: orange cluster), but some phenotypes cluster more closely with

sense organ conditions (Figure 3A: green cluster). However, this small set of endocrine pheno-

types includes mainly eye-related conditions resulting from complications from endocrine disor-

ders, such as diabetic retinopathy and exophthalmos.

218
Figure 3. Latent *ClinVec* space captures biomedical knowledge consistent with organ system biology and
anatomy. (A) Scatter plots showing a reduced dimension of the embedding space of clinical codes. On the left, the
latent space of phecodes is shown, where each phecode is shaded by its corresponding organ system categorization.
On the right, the latent space of ATC medication codes is shown, where each ATC code is shaded according to the
corresponding ATC level 1. **(B)** Visualization of the embedding region of digestive system ICD10CM codes. We

highlight the following phenotype subcategories: functional digestive disorders – phecodes, teeth and mouth disor-

ders (center), and biliary system (right). **(C)** Visualization of embedding space overlaid with ICD10CM, ATC,

SNOMEDCT, and CPT codes. Codes are shaded based on cosine similarity with type 1 diabetes (left) and system-

atic lupus erythematosus (right), and the target disease embedding is denoted with a black diamond. The black stars

indicate a subset of codes related to each disease. These are presented along with other codes in their proximity but

are not directly related to the disease of interest.

Extending this clustering analysis to drug categories based on the ATC-1 level, embeddings gen-

erated by both *ClinGraph* and PrimeKG show clustering by drug category although *ClinGraph*

has a higher silhouette score (0.71 vs. 0.64). In contrast, embeddings from the SNOMED-CT

knowledge graph do not produce distinct clusters and have an AMI score close to zero. This is

likely attributable to the more extensive drug coverage in *ClinGraph* compared to SNOMED-CT

KG. Again, we also find that deviations in the expected cluster labeling according to the ATC-1

classification in *ClinGraph* reflect known artifacts of the ATC coding system. For example, the

embeddings for ATC-4 codes G01AA (antibiotics) and D06AX (antibiotics for topical use) are

located nearby in the embedding space despite being in different ATC-1 categories. These anal-

yses demonstrate that the effectiveness of clinical embeddings depends on the design of the un-

derlying KG. *ClinGraph*'s integration of clinically grounded vocabularies and relationship types

results in more accurate representations, outperforming existing KGs across multiple evaluation

metrics.

A unified clinical vocabulary latent space must capture patterns at broad anatomical levels while

also identifying discernible relationships at clinical subspecialty levels. To illustrate the granular-

ity of *ClinVec* clinical vocabulary embeddings, we perform a separate dimensionality reduction

analysis using only phecodes of the digestive system (Figure 3B). We find that conditions within

the same subspecialty are significantly closer together compared with all other conditions of the

digestive system, where codes describing functional digestive disorders (*p-value*=3.65×10^{-45};

two-sided Mann-Whitney U test), biliary system (*p-value*=6.38×10^{-44}), and conditions of mouth

and teeth (*p-value*=1.05×10^{-74}) are separated within the latent space. Although these codes all

fall under the practice of gastroenterology, the embeddings exhibit distinct clustering patterns

that reflect their unique clinical presentations and organ systems. This finding show that *ClinVec*

embeddings to capture fine-grained distinctions within broader medical categories.

A key advantage of *ClinVec* embedding space is that it allows direct comparison of clinical

codes across different vocabularies, bridging gaps between otherwise disconnected coding

systems. We compare *ClinVec* to two state-of-the-art open-source clinical embeddings,

snomed2vec[89] and cui2vec[90], in a set of zero-shot retrieval tasks. For a given disease, we select

the top k closest codes within the embedding space and compare with these with the diseases'

symptom list as listed in the Mayo Clinic disease description. We report each model's perfor-

mance using 'hits @ k' which measures the proportion of diseases where a relevant symptom is

ranked among the top k items within the embedding space. We find that the *ClinVec* embeddings

outperform other approaches across a variety of values of *k* (Supplementary Table S4A). While

hierarchical structures explain some of the clustering, the embeddings also capture meaningful

patterns in cross-domain relationships, such as between diseases and their associated treatments,

which are not strictly hierarchical. We perform a similar analysis for drug indications with estab-

lished first-line drug treatments. For example, non-Hodgkin's lymphoma and CHOP (cyclophos-

phamide, doxorubicin, vincristine, prednisone), testicular cancer and BEP (bleomycin, etoposide,

cisplatin), and major depressive disorder and selective serotonin reuptake inhibitors. Limiting re-

trieval over codes exclusively describing ATC5-level medications, for each disease, we perform

zero-shot retrieval across >2,000 drug codes and assess the codes with the highest cosine similar-

ity with the disease embedding. We find that the *ClinVec* embeddings outperform other ap-

proaches across a variety of values of *k* (Supplementary Table S4B).

Embedding space reveals clinically grounded diagnostic and symptom patterns

Many clinical applications require disease-level resolution, where models must distinguish be-

tween specific diagnoses and their associated symptom profiles. To evaluate how *ClinVec* cap-

tures these diagnostic patterns, we examine type 1 diabetes (T1D) and systemic lupus erythema-

tosus (Figure 3C). We compute the cosine similarity between the T1D embedding and ICD10CM

codes, CPT, LOINC, and SNOMED CT codes within the embedding space and visualize these

patterns by projecting the computed cosine similarity onto the latent space. Broadly, near the em-

bedding of T1D, we observe regions of high cosine similarity as shaded in red and orange. We

find that many codes within this region are consistent with relevant T1D laboratory tests, such as

'insulin tolerance panel', and common complications, including cardiovascular diseases (Meth-

ods). We also identify a cluster of eye-related tests for T1D, including codes for eye exams and

macular edema. This highlights the embedding space's ability to capture nuanced patterns that

extend beyond identifying codes associated with the same organ system, recapitulating patterns

aligned with established disease presentations. Repeating this process for lupus, regions with

high cosine similarity highlight relevant tests such as erythrocyte sedimentation rate, which is

used to assess systemic inflammation and nephritis, a common complication.

ClinVec contains the expressivity and flexibility to describe a wide range of clinical scenarios

within the embedding space. Through embedding arithmetic, embeddings can be combined

mathematically to form new meanings. For example, the similarity between the vector summa-

tion of common heart disease symptoms (*e.g., shortness of breath, chest pain)* and the disease

embedding of *common heart disease* yields a cosine similarity score of 0.66. These observations

mirror the geometric properties of word embeddings in natural language processing[91], effectively

capturing the relationship between concepts without explicitly defining it in the original vocabu-

lary. We refer to the aggregation of symptom embeddings in this manner as a *disease symptom*

embedding—denoting that the resulting vector is a composition of the symptoms of a given dis-

ease (Figure 4A, 4B).

Figure 4: Embedding operations mirror symptomatic manifestations of clinical conditions. **(A)** Overview of

the approach for constructing disease symptom embeddings. **(B)** Line plot showing the cosine similarity across four

autoimmune diseases and the aggregation of Graves' disease symptoms. Aggregated embeddings are computed by

performing a vector sum across the embeddings for each symptom. **(C)** Heatmap showing cosine similarity between each disease embedding and the aggregation of symptoms. Sizes of circles correspond to the magnitude of the cosine similarity.

We assess this pattern by examining nine diseases with significant health implications across different clinical specialties. Five conditions are among the top non-communicable diseases with the highest mortality rate identified by the World Health Organization[92] and four are among the most common autoimmune disorders in adult populations[93]. Using clinical descriptions of diseases from the Mayo Clinic[94–98] and the manual translation of symptom lists to diagnosis codes, we aggregate all disease symptoms in the form of ICD-9 code embeddings (Supplementary Table S5). Computing the cosine similarity between the disease symptom embedding and the target disease embedding across all nine diseases, we find that all pairs have positive similarity scores (*mean-cos-similarity*: 0.77, *SD*: 0.13) (Supplementary Table S7). Moreover, conditions with overlapping symptoms also exhibit high similarity scores. For instance, the phecode embedding for multiple sclerosis also has a high similarity score with the disease composition embedding for lupus (*cos-similarity*=0.58), as both diseases share symptoms such as fatigue and muscle pain. We observe high levels of congruence between diseases affecting the same organ system, such as lung cancer (target disease) and COPD (symptom embedding), which both affect the respiratory system (*cos-similarity*=0.86).

After identifying this pattern, we evaluated whether individual symptoms exhibit consistent syntactic and semantic structure within the embedding space. To approximate the disease specificity of each symptom, we ranked symptoms by their frequency in a sample of patients from Clalit Health Services (CHS), from most to least common. For each of the nine diseases, we incrementally aggregated symptom embeddings in order of decreasing frequency. As less common symptoms were added, the combined symptom embedding progressively aligned more closely with the target disease embedding (Supplementary Figures S2, S3). To test the robustness of this trend, we perturbed key components of the embedding aggregation process. Across variations, including swapping the target disease, substituting related symptoms, and introducing randomly selected symptoms to mimic real-world variability, the symptom embedding consistently moved closer to the corresponding disease embedding in the latent space (Supplementary Figure S4).

This process can help study diseases with similar symptoms by revealing subtle differences in clinical presentations. This level of granularity can be observed when comparing various autoimmune diseases due to the presentation of overlapping symptoms. For Graves' disease, we

compute the initial cosine similarity between the disease embedding for each of the four diseases
and the first symptom embedding, "palpitations", (the Graves' symptom found to be most preva-
lent in the sampled patient population), but no disease has a cosine similarity score > 0.40 (Fig-
ure 3B). Given the relatively high prevalence of this symptom in the general patient population
and lack of disease specificity (*freq*=0.232), it is unsurprising that initial symptoms do not show
a high correlation with any of the immune conditions. However, as we add symptoms that are
relatively less common within the general population, such as 'goiter' (*freq*=0.029), the composi-
tion of symptoms becomes increasingly similar to the representation of Graves' disease, and the
similarity with the other three autoimmune conditions begins to diverge. These patterns mirror
how individual symptoms may not provide sufficient information to assess the probability of a
specific condition, but as a patient accumulates more symptoms over time, the aggregation of
these symptoms can stratify patients by disease risk.

Clinical knowledge embeddings stratify patients by disease risk and severity

We next investigate how *ClinVec* can be utilized in the context of patient outcome prediction, in-
cluding disease progression and disease risk. Using only information derived from *ClinVec*, we
compute a disease-specific risk score for various conditions and the relative disease risk for each
patient. Analogous to polygenic risk score frameworks[99], we compute a phenotype risk score[100]
by scanning a patient's EHR and aggregating the embeddings across conditions with the highest
similarity to the disease of interest (Methods). We validated our approach using retrospective
EHR data from 4.57 million individuals[101] at CHS and specifically focused on patients listed in
the CHS chronic registry, a registry maintained by CHS that monitors individuals with specific
chronic conditions[102]. We examine three clinical conditions with the largest sample sizes within
the chronic registry: chronic kidney disease (CKD), chronic obstructive pulmonary disease
(COPD), and heart failure.

Figure 5: Clinical code embedding risk scores correlate with disease prevalence and severity. (A-C) We pro-

vide scatter plots showing the risk score percentiles of each disease versus the disease prevalence within each bin.

362

 valence. Columns are divided by diseases: heart failure, CKD, and COPD.

d a matched case-control cohort (Supplementary Table S6,

:d 5 years of clinical history to compute a relative risk score for

here represented by an ICD10CM embedding), we identify

nt to the disease by selecting all codes within a given radius in

s). Each patient's score is computed as a weighted sum of these

features, where the weight is calculated as the cosine similarity between the feature embedding

and target disease embedding. In practice, the size of the radius (k-neighbors) can be selected by

comparing a validation patient dataset, similar to choosing the optimal performing p-value

threshold in PRS[103]. This approach eliminates the need to pre-specify a list of features useful for

diseases with heterogeneous presentations and highly variable symptoms, such as many chronic

conditions.

Quantifying patients' disease risk according to their risk score percentile of the total score distri-

bution, we observe the separation of patients according to disease status across all three condi-

tions, particularly at the extreme end of the risk distribution (Figure 5). Within the group of indi-

viduals in the 10th percentile of the risk score distribution for CKD, there is a disease prevalence

of 6.2%. For patients above the 99th percentile, the disease prevalence increases to 23.4%. Top-

identified clinical code embeddings are consistent with each disease's known comorbidities, lab

test results, and medication usage. For example, among the top features of chronic kidney dis-

ease is *Diabetes mellitus*, which is a well-documented risk factor for the disease, and *Pro-*

teinuria, which can be an early disease indicator. Although we assess the population-level corre-

lation between disease prevalence and risk score percentile, these results suggest opportunities to

leverage clinical knowledge embeddings for patient monitoring in a way that is independent of
any training dataset.

Given the marked stratification by disease status, we evaluate whether the computed risk scores
could provide disease subtyping information. Intuitively, suppose individuals acquire a greater
number of highly relevant clinical conditions. In that case, this trend may indicate a later disease
stage and increased mortality rates. To prevent confounding from disease-specific effects with
age and sex, we restrict the assessment to individuals of the same sex and diagnosed at a similar
age (Methods). For each of the three conditions, we compute the mode age and sex and use this
as inclusion criteria for the survival analysis. Re-calibrating score percentiles based on the final
set of patients, we observe a striking stratification by 6-year survival rate (Supplementary Figure
S6). For CKD (age=72 sex=Male), individuals within the top quintile of this score distribution
for CKD had a relative 42.6% lower 6-year survival compared to those in the bottom quartile
(top-quartile: 56.8.3%, *bottom-quartile*: 76.5%). This trend is particularly remarkable consider-
ing the risk scores were inferred without any institution-specific, disease-specific, or patient-
level information during training.

***ClinVec* provides structured clinical knowledge to improve LLM performance**

Clinical embeddings provide a structured approach to incorporate domain-specific knowledge
into foundation models such as LLMs. One common strategy is knowledge injection, where em-
beddings from external knowledge sources are appended to the LLM input. Recent studies show
that this approach improves performance on tasks such as medical question answering by
grounding LLM outputs in a clinically relevant context[104–107]. We adapt MMed-Llama[106], an
open-source LLM composed of 8 billion parameters. To test whether *ClinVec* embeddings im-
prove LLM performance beyond what can be achieved with domain-specific training data alone,
we evaluated our knowledge token injection approach using an LLM already trained on medical
content. We used parameter-efficient fine-tuning to integrate 42,883 clinical knowledge tokens
into the LLM, where each token corresponded to a *ClinVec* embedding of a UMLS concept
(Supplementary Figure S7). This approach allows domain adaptation without retraining the en-
tire model or requiring a labeled clinical dataset. It provides a resource-efficient strategy for in-
corporating structured clinical knowledge into LLMs.

To assess the impact of clinical knowledge embeddings on LLM performance, we used the
MedQA[1–4] dataset, which contains questions from the US Medical Licensing Exams (USMLE).

We applied the UMLS MetaMap API to map question text to UMLS concepts, then retrieved the

corresponding *ClinVec* embeddings and appended them to the tokenized prompt (see Methods).

This approach incorporates structured, clinically grounded knowledge without retraining the un-

derlying LLM. Instead, *ClinVec* supports retrieval-augmented generation, where embeddings rel-

evant to the input are used to guide the LLM response.

Assessing performance with a held-out test set of MedQA (N=1,247 questions), we find a 10.3%

increase in question-answering accuracy when incorporating the clinical knowledge embeddings

(acc=0.64) compared to question answering without it (acc=0.58). We observe the largest perfor-

mance gains when questions are short, likely because the language model has limited contextual

information to generate accurate answers. Adding just one or two clinical knowledge embed-

dings leads to an average improvement of 11.7%, suggesting that the relationship information

encoded in these embeddings helps compensate for missing context. Performance continues to

improve as more tokens are added, reaching a peak at around 9 to 10 tokens. Beyond this point,

additional embeddings introduce less relevant or less specific information, which reduces overall

accuracy.

Figure 5: Integrating *ClinVec* with large language models improves medical question-answering. (A) Over-

view diagram of question-answering with knowledge injection using *ClinVec*. **(B)** We report the accuracy of

N=1,247 medical questions in the MedQA dataset. The red line denotes random performance with four candidate

answer options. **(C)** Accuracy of N=3,724 multiple-choice questions from AfriMed-QA dataset. The red line de-

notes baseline performance with five answer options.

To assess generalizability across different clinical scenarios, we also examined the recently re-

leased AfriMed-QA dataset[109], which consists of 3,724 multiple-choice questions collected from

healthcare settings across 16 African countries. Since the dataset was released in early 2025,

there is no data leakage between the training and fine-tuning datasets. We observe a similar mag-

nitude of performance improvement where we observe accuracy of 0.64 with the addition of

clinical knowledge embeddings compared to 0.59 without—a 8.5% increase. Breaking down per-

formance by clinical specialty (a label provided in the original dataset), we identify the special-

ties with the greatest performance gains, including hematology (+37.0%) and ophthalmology

(+20.3%). Given the specificity of these fields, the addition of clinical knowledge yields the most

substantial improvements in question-answering performance. Hematology shows the largest

gains, likely due to the distinct disease presentations encountered in African settings that are un-

derrepresented in the training data of most large language models. For instance, one correctly an-

swered question concerns antiretroviral treatment regimens for HIV-associated anemia, a clinical

scenario more common in regions with high HIV prevalence. This example illustrates how an-

choring model responses in structured, domain-specific knowledge from *ClinVec* helps address

regional variation and improves accuracy in specialized medical contexts. We observe consistent

performance improvements across both U.S.- and Africa-based clinical questions, suggesting

that *ClinVec* supports generalizable medical reasoning.

Discussion

We introduce *ClinGraph*, a clinical knowledge graph, and *ClinVec*, a corresponding set of

153,166 clinical vocabulary embeddings, that together translate structured clinical information

into a machine-readable format for use in AI models. These embeddings capture patterns among

clinical codes that reflect human anatomy, disease presentation, and healthcare organization.

They encode semantic relationships that support the combination and comparison of clinical con-

cepts. We demonstrate that the embeddings enable patient-level prediction across diverse condi-

tions without using patient data during training. Evaluations by inter-institutional panels of clini-

cians from the United States and Israel confirm that the embeddings align with current clinical

knowledge and practice. This resource offers a generalizable framework for sharing clinical
knowledge and developing transferable, knowledge-grounded AI models.

Clinical code embeddings offer a way to represent structured clinical knowledge for use in AI
models. By encoding relationships among diagnoses, procedures, medications, and laboratory
tests, the embeddings create a knowledge-grounded representation of clinical data that can be
used in downstream machine learning applications. These representations are well-suited to serve
as inputs to foundation models, large-scale models pre-trained on unlabeled data and adapted to
specific tasks through fine-tuning with labeled datasets[110]. The foundation model approach has
shown success in natural language processing and computer vision, supported in part by the
availability of publicly shared models such as DeepSeek[111] and LLaMA[112]. Our resource can be
used in retrieval-augmented generation[113] systems where embeddings serve as a structured
knowledge base. In this setting, relevant embeddings can be retrieved based on a user prompt to
provide clinical context and support more accurate and informed model outputs[41].

While this resource offers a foundation for advancing precision medicine, it has several limita-
tions. First, the current knowledge representations do not model uncertainty. Clinical knowledge
is derived from heterogeneous sources, and the frequency or relevance of specific observations
can vary across populations. For example, while disease guidelines may list several symptoms,
their prevalence and clinical importance often differ between individuals. Second, the quality of
the embeddings depends on the accuracy of the underlying KG. Errors such as incorrect or in-
complete edges can introduce noise and distort the learned representations. As clinical
knowledge evolves, the graph must be regularly updated to reflect current clinical standards and
practice. Third, the embeddings do not incorporate contextual information, such as age or sex,
which can influence the presentation and interpretation of clinical concepts. For example, the
clinical presentation of a heart attack can vary significantly between males and females[114], but
this delineation is not considered in the construction of the embeddings.

ClinVec embeddings cover common and chronic diseases, with limited representation of genetic
disorders and Mendelian conditions. Future work will incorporate codes from phecodeX[115], an
updated vocabulary that includes chromosomal anomalies, as well as resources focused on Men-
delian diseases, such as the Online Mendelian Inheritance in Man (OMIM)[116] and Human Pheno-
type Ontology (HPO)[74]. We also plan to integrate databases that capture biological mechanisms,

including those involving genes and proteins, to improve the representation of disease with com-
plex or poorly defined clinical features.

ClinGraph consolidates fragmented coding systems into a unified representation of clinical
knowledge, addressing interoperability challenges while protecting patient privacy. The embed-
dings are designed to capture clinical knowledge that generalizes across care settings and aligns
with established medical practices. Unlike datasets that only reflect recorded health states, *Clin-*
Vec embeddings incorporate information about clinical guidelines, mechanistic associations, and
disease-treatment pathways. Because the embeddings are derived from structured vocabularies
and not patient-level data, they can be shared across institutions without risk of exposing identifi-
able information. Unlike models pre-trained on patient records, which may inadvertently retain
or memorize sensitive information[117,118], *ClinVec* embeddings can be shared across healthcare
systems without risking patient privacy. This approach also reduces dependence on specific pa-
tient populations and supports diverse clinical applications. By embedding structured clinical
knowledge into AI models, this resource helps ensure that predictions are grounded in estab-
lished medical understanding[119]. Resources such as unified clinical vocabulary embeddings can
strengthen the reliability and generalizability of AI models.

Methods

Standardized medical vocabularies

509
510
We use standardized medical vocabularies to construct all clinical concepts in *ClinGraph* and
ClinVec, supporting broad applicability across clinical use cases: Unified Medical Language
System (UMLS), International Classification of Diseases (ICD)[120], Anatomical Therapeutic
Chemical (ATC) Classification[121], RxNorm[122], Systemized Nomenclature of Medicine – Clinical
Terms (SNOMED CT)[123], Current Procedural Terminology (CPT)[124], Logical Observation Iden-
tifiers Names and Codes (LOINC)[125], and phecodes[126]. Here, we define a clinical code as an en-
try within a medical vocabulary with a unique identifier.

We begin by integrating the clinical codes and relationships defined in the UMLS vocabulary.
We incorporate all UMLS CUIs (concept unique identifier) with a source vocabulary in
ICD10CM, SNOMED CT, LOINC, RxNorm, ATC, or CPT (N=42,883 nodes). Next, we inte-
grate all ICD10CM codes up to 2 decimal places (N=34,842) and all ICD9CM codes. We also
add information from the phecode coding system which represents clinical phenotypes as phe-
codes, formed by aggregating groups of diagnostic codes (i.e., ICD codes) into clinical sub-
groupings (N=1,817) [127–129]. Phecodes were developed to facilitate the secondary use of EHRs
for biomedical research rather than for patient monitoring or hospital administration. Numbers
after the decimal point reflect a hierarchical structure similar to the ICD code hierarchy. Under
each leaf phecode is the set of corresponding ICD-9/10 codes where each phecode has between 1
– 20+ associated ICD-9/10 codes. Next, we add nodes representing LOINC Part codes, which are
standardized attribute values used to construct the LOINC codes that specify a given laboratory
test. We restrict our inclusion to only LOINC Part component codes which refer to the substance
being tested (N=14,399). We also incorporate all CPT codes (N=4,377), ATC codes (levels 3-5:
N=5,179), and RxNorm drug groups (N=10,130).

Next, we integrate a subset of SNOMED CT codes as nodes in *ClinGraph*. Because the
SNOMED CT vocabulary includes many codes (>350,000), we wanted to restrict the inclusion
to the most clinically relevant codes. We begin by selecting all SNOMED CT codes from the
CORE (Clinical Observations Recording and Encoding) Subset, a set of most frequently used
codes provided by UMLS constructed to maximize data interoperability across institutions. Next,
we include SNOMED CT codes from the Convergent Medical Terminology subset diagnosis list,

a set of core terms originally curated by Kaiser Permanente and now used across numerous

healthcare systems.

Relationships between clinical concepts

To construct edges between pairs of clinical concepts (nodes), we first incorporate relationships

defined by the PheMap database, an existing knowledge base of biomedical knowledge that de-

fines a set of relationships between the codes and various clinical vocabularies[83]. This database

offers relationship pairs linking phecodes and clinical codes from other medical vocabularies, in-

cluding RxNorm, CPT, LOINC, and SNOMED CT. Relationships defined in PheMap were de-

termined through text mining and natural language processing of open-source biomedical litera-

ture. These relationships can be interpreted as a phenotype being "associated with" a given clini-

cal concept. To construct relationships between different medication codes, we use ATCPROD,

a product-level mapping of RxNorm to ATC-4 classes. Edges between ICD9CM and ICD10CM

codes are derived from the General equivalence mappings (GEM), the official crosswalk map-

ping diagnoses codes to and from ICD9CM and ICD10CM.

Constructing ClinGraph

To efficiently represent clinical knowledge in a format optimized for machine learning, we for-

mally organize the clinical codes and relationships, as described above, into a heterogenous

knowledge graph[130] (KG) called *ClinGraph.* We draw an undirected edge between two clinical

codes if they have a pairwise relationship as described above in the clinical vocabulary aggrega-

tion process. Multiple edges are drawn if two nodes have a relationship defined multiple times

(e.g., a relationship between a phecode and ICD-9CM code derived from the phecode hierarchy

and the PheMap knowledge base). The final graph comprises 153,166 nodes across seven node

types and 2,873,025 edges, and the distribution of nodes and edges can be found in Supplemen-

tary Table S1, S2.

We model 4 distinct node types: diagnosis codes (ICD9CM, ICD10CM, phecodes), medications

(ATC, RxNorm), laboratory tests/procedures (LNC, CPT), and clinical concepts/vocabularies

(SNOMED CT, UMLS). By grouping similar vocabularies (e.g., RxNorm and ATC), we allow

for information sharing across similar nodes. However, modeling distinct edge types would re-

quire the harmonization of relationship types across databases. For databases without defined

edge type semantics, such as PheMap, this harmonization process would likely require additional

resources and clinical expertise. For this reason, we only model distinct node types and leave the

implementation of edge-type specific embeddings as future work.

Heterogenous graph transformer

Graph notation

A heterogeneous graph, $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, is defined by a set of nodes $\mathcal{V}$ and edges $\mathcal{E}$. We define a

mapping function $f_v: \mathcal{V} \to \mathcal{T}^v$ where each node $v \in \mathcal{V}$ has an assigned node type $f_v(v) \in \mathcal{T}^v$.

Here, the node types represent different clinical vocabularies. For a given graph, $\mathcal{G}$, we denote

the graph neural network, $\mathcal{H}_{\mathcal{G}}$, as a function that maps a vector of features for a node u, written

as $\boldsymbol{x_u} \in \mathbb{R}^d$, to a vector of real numbers representing the latent space:

578
$$\mathcal{H}_{\mathcal{G}}: \boldsymbol{x_u} \to \boldsymbol{z_u}.$$

579 Here, d is the dimension of the input vector. This resulting mapped vector (also called an *embed-*
580 *ding*) is denoted by $\boldsymbol{z} \in \mathbb{R}^d$. For convenience of notation, we assume that the input and output
581 dimensions are equal. We provide a table with relevant notation and indicate whether they are an
582 inferred parameter within the model.
583

Variable	Description	Dimension	Trainable (Y/-)
$\mathcal{G}$	Graph	-	-
$\mathcal{V}$	Set of vertices or nodes	-	-
$\mathcal{E}$	Set of edges	-	-
$\mathcal{T}^v$	Space of node types	-	-
d	Input dimension	$\mathbb{R}^1$	-
L	Number of layers	$\mathbb{R}^1$	-
$\mathcal{H}_{\mathcal{G}}$	Graph neural network function	$\mathbb{R}^d \to \mathbb{R}^d$	Y
$\boldsymbol{x_u}$	Feature vector of node u	$\mathbb{R}^d$	-
$\boldsymbol{z_u}$	Embedding vector of node u	$\mathbb{R}^d$	Y
$\mathcal{N}(\boldsymbol{u})$	Neighborhood of node u	-	-
$\boldsymbol{m_u}$	Message feature of node u	$\mathbb{R}^d$	Y
$\boldsymbol{h_u^{(l)}}$	Embedding of node u at the lth layer	$\mathbb{R}^d$	Y
$\mathbf{ATT}(\boldsymbol{s}, \boldsymbol{t})$	Attention vector for node u	$\mathbb{R}^d$	Y
h	Number of heads	$\mathbb{R}^1$	-
$\boldsymbol{W_Q^i}, \boldsymbol{W_K^i}$	Weight matrices	$\mathbb{R}^{d \times \frac{d}{h}}$	Y
$\boldsymbol{head}(\boldsymbol{s}, \boldsymbol{t})^i$	Attention head vector for source node u and target node v	d/h	Y
$\boldsymbol{W_Q^i}, \boldsymbol{W_K^i}$	Weight matrices for attention computation	$\mathbb{R}^{d \times \frac{d}{h}}$	Y
$\boldsymbol{W_V}$	Weigh matrix for attention computation	$\mathbb{R}^{\frac{d}{h} \times \frac{d}{h}}$	Y

K_s^i, Q_t^i	Query and key vectors	$\mathbb{R}^{\frac{d}{h} \times 1}$	Y
$A \odot B$	Hadamard product between **A** and **B**	-	-
$\bigoplus$	Element-wise summation	-	-
$\|_n(x^i)$	Row-level concatenation of the set vectors	-	-
$f(u, v)$	Similarity scoring function	-	Y
$\|\cdot\|$	L2-norm	$\mathbb{R}^1$	-
v^+	Node forming a positive edge with u	-	-
v^-	Node that does not form an edge with u	-	-
$\mathcal{G}'$	Graph with masked edges	-	-

Table 1: Summary of notation. We provide a summary of the variables used in deriving the graph transformer network model, the dimension of each variable, and whether it is a learned or fixed parameter. Rows are sorted according to the order in which each variable is introduced.

 Overview

We model the architecture of our graph neural network (GNN) after the heterogeneous graph
transformer (HGT)[86]. In this work, we briefly describe the key model steps. The complete deri-
vation of HGT is detailed in previous work[86].

Learning $\mathcal{H}_\mathcal{G}$ involves aggregating information across the graph structure defined by $\mathcal{G}$. For a
target node t, we define its neighborhood, $\mathcal{N}(t)$, as the set of nodes with a direct connection or
edge with t. Information is propagated through the graph by gathering information from the
neighborhood of t, which is aggregated into a message feature $\boldsymbol{m}_t$. The embedding of t can be
updated with the resulting message feature, $\boldsymbol{h}_u^{(l+1)} = \text{UPD}\left(\boldsymbol{m}_t^{(l)}, \boldsymbol{h}_u^{(l)}\right)$ where $\boldsymbol{h}_t^{(l+1)}$ is the embed-
ding of node t at the $l+1$ layer and $\text{UPD}(\cdot)$ refers to an update function that integrates messages
with the current node embedding. Note that the input of the $l+1$ layer is the output of the previ-
ous layer, and by stacking L layers $\boldsymbol{h}_t^{(\cdot)}$, we represent the final HGT as a composition of these
functions across all layers:

$$\mathcal{H}_\mathcal{G}(\boldsymbol{x}_t) = \left(\boldsymbol{h}_t^{(L)} \circ \boldsymbol{h}_t^{(L-1)} \circ \dots \circ \boldsymbol{h}_t^{(1)}\right)(\boldsymbol{x}_t).$$

601 The input of the model is the set of node features, $\boldsymbol{x}_t \in \mathbb{R}^d$ for all nodes in $\mathcal{G}$ which is then used
602 to initialize the 0^{th} layer embedding of each node $\boldsymbol{h}_t^{(0)}$. In practice, each of the node features is
603 initialized using Xavier noise. The embedding represents the relational information learned from
604 the knowledge graph without additional information from the node features.

Multi-head attention mechanism

The HGT uses multi-head attention, which is a key feature of transformer architecture[87]. Multi-
head attention utilizes multiple attention mechanisms, or heads, in parallel to tend to different
parts of the input, where each head has its own set of learnable weights (parameters). Updating a
node's embedding involves aggregating messages across all h heads and weighting each mes-
sage by its attention score. This mechanism essentially up- and down-weights messages based on
their importance so that only necessary information is propagated to the target node. Although
the original HGT architecture allows the modeling of different relation types within heterogene-
ous graphs, we treat all nodes and edges as a single type during inference to maximize infor-
mation sharing across the knowledge graph.

For a target node t, a single attention head is a series of linear projections of the embedding from

the previous layer, normalized by the embedding dimension. Here, a linear projection for an in-

put $x \in \mathbb{R}^d$, is defined as an affine linear transformation, $y = W^T x + b$ where b is a bias term

and W is a learnable weight matrix. For convenience, we drop the bias term in the following der-

ivations, but in practice, the parameter corresponding to the bias term is absorbed into the esti-

mation of W.

The series of linear projections mirror the standard query, key, and value vectors used in the

standard transformer architecture. The attention score vector corresponding to the edge between

source node s and target node t, represented as $\mathbf{ATT}(s, t)$, is computed as the concatenation of

each head's output:

625
$$K_s^i = \left(W_K^i\right)^T h_s^{(l-1)},$$

626
$$Q_t^i = \left(W_Q^i\right)^T h_t^{(l-1)},$$

627
$$\mathbf{HEAD}(s, t)^i = \left(W_V^i\right)^T K_s^i \odot (Q_t^i) \cdot \frac{1}{d},$$

628
$$\mathbf{ATT}(s, t) = \Big\|_{i \in [0,h]} \mathbf{HEAD}(s, t)^i.$$

Here, the operator "$A \odot B$" represents the elementwise or Hadamard product between A and B,

and the operator "$\|_n (x^i)$" represents the row-level concatenation of the given set of vectors

$\{x^1, \ldots, x^n\}$.

The input vector is $h_s^{(l-1)} \in \mathbb{R}^{d \times 1}$, and the learnable weight matrices are $W_Q^i, W_K^i \in \mathbb{R}^{d \times \frac{d}{h}}$, and

$W_V \in \mathbb{R}^{\frac{d}{h} \times \frac{d}{h}}$ where $\frac{d}{h}$ is the input dimension divided by the number of heads. For these weight

matrices, the subscripts refer to the *query*, *key*, and *value* elements in the transformer. The result-

ing query and key vectors follow as $K_s^i, Q_t^i \in \mathbb{R}^{\frac{d}{h} \times 1}$. The resulting attention vectors from each

head and final multi-head attention vector are $\mathbf{HEAD}(s, t)^i \in \mathbb{R}^{\frac{d}{h} \times 1}$ and $\mathbf{ATT}(s, t) \in \mathbb{R}^{d \times 1}$. And

to ensure the attention scores for the target node t sum to 1, a $Softmax(\cdot)$ is applied across all

neighbors of t.

Message passing

For target node t, we first compute the message vectors across all heads for each neighbor of t.

This message is calculated as a linear projection of the embedding for source node s from the

prior layer multiplied by a weight matrix (W_T). Each head maintains its linear projection matrix

but W_T is shared across all attention heads.

The final message passed from $s \rightarrow t$ is a concatenation of messages produced from each of the

h heads. This resulting message vector is then multiplied by the multi-head attention vector. The

final updated embedding ($h_t^{(l)}$) is computed by aggregating across all neighbors of the node t

through an elementwise sum. This is followed by a linear projection (W_N), which creates sepa-

rate projection for each node type. We need a single matrix because we only model a single node

type. This is then followed by a residual connection and passed through an activation function:

651
$$m_s^{(l)} = \big\|_{i \in [1,h]} \left(W_T \left(W_M^{i^T} h_s^{(l-1)} \right) \right),$$

652
$$\widetilde{h}_t^{(l)} = \bigoplus_{\forall v \in N(u)} \text{ATT}(s,t) \odot m_s^{(l)},$$

650
$$h_t^{(l)} = \sigma \left(W_N \, \widetilde{h}_t^{(l)} + h_t^{(l-1)} \right).$$

The learnable weight matrices are $W_T \in \mathbb{R}^{\frac{d}{h} \times \frac{d}{h}}$, $W_M^i \in \mathbb{R}^{d \times \frac{d}{h}}$, and $W_N \in \mathbb{R}^{d \times d}$. The message

vector is $m_t^{(l)} \in \mathbb{R}^{d \times 1}$. The operator $\oplus$ represents the elementwise summation. Training the final

model involves optimizing the set of learnable weight matrices, $\{W_K^i, W_Q^i, W_V^i, W_M^i\}$ across h

heads and finding $\{W_T, W_N\}$ that minimizes the loss function $\mathcal{L}$.

Self-supervised learning

For a given node u, our goal is to generate an embedding z_u that quantifies the topological infor-

mation of the graph w.r.t u. The learning objective can be framed as a link prediction problem,

where given two nodes u and v, we want to train a function to predict whether an edge exists be-

tween these two nodes. This function can be described by,

665
$$f(u,v) = \frac{(z_u)^T z_v}{\| z_u \| \| z_v \|} = cos(z_u, z_v),$$

where $z_u = \mathcal{H}(u)$, and $\mathcal{H}(\cdot)$ represents the trained GNN function that provides the node em-

beddings. Note that because edges are undirected and the scoring function is symmetric,

$f(u,v) = f(v,u)$.

Optimizing this above scoring functions means solving for the parameters of $\mathcal{H}(\cdot)$. This can be

performed using contrastive learning. We mask a random subset of edges to create a modified

version of the graph, $\mathcal{G}'$. Then, given a source node u, we define a node where $v^+ \in \mathcal{N}(u)$ repre-

sents a target node that forms an edge with u in the original graph $\mathcal{G}$. We denote $v^- \notin \mathcal{N}(u)$ as a

node that does not form an edge with u in $\mathcal{G}$ and denote the set of these negative examples

as $\{v_1^-, v_2^-, \cdots, v_n^-\}$.

The function $f(u, v)$ is trained on $\mathcal{G}'$ to estimate whether a source node u forms an edge with tar-

get node v in the original graph $\mathcal{G}$. We can quantify the probability of an edge existing between

u and v^+ with negative edges $v_{\{1:n\}}^-$ as the probability,

679
$$p\left(u, v^+, v_{\{1:n\}}^-\right) = \frac{exp(\mathbf{z}_u^T \mathbf{z}^+)}{exp(\mathbf{z}_u^T \mathbf{z}^+ + \mathbf{z}_u^T \mathbf{z}_1^- + \cdots + \mathbf{z}_u^T \mathbf{z}_n^-)}.$$

675 Given a dataset of N source nodes, each with a corresponding set of candidate nodes as described

676 above, the negative log-likelihood over the dataset is equivalent to the cross-entropy loss where

677 the true "class" always corresponds to the positive node v^+. This type of contrastive loss func-

678 tion is well-established[88,131–133] and is formulated as follows:

680
$$\mathcal{L} = -\sum_u^N log\left(p(u, v^+, v_{\{1:n\}}^-)\right),$$

681
$$\text{where } v^+ \in \mathcal{N}(u) \text{ and } v_{\{1:n\}}^- \notin \mathcal{N}(u).$$

Node type-aware sampling of positive and negative edges

The contrastive learning requires specifying positive and negative edges during training, where a

positive edge is defined as a pair of nodes with an existing edge in *ClinGraph*, and a negative

edge is a pair of nodes that are not connected by an edge. To generate a training tuple comprised

of a single positive edge and a set of corresponding negative edges, we randomly sample an ex-

isting edge within *ClinGraph* denoted as (u, v) and $\mathcal{T}^V(v)$ is the node type of target node v. To

create a negative sample, we select a node r such that $\mathcal{T}^V(r) = \mathcal{T}^V(v)$ and $r \notin \mathcal{N}(u)$.

Stochastic mini-batch training with neighbor sampling

Because the topology and size of the GNN are determined by the KG, storing the entire network

and its hidden states onto a single GPU is impossible. Although training with mini-batches alle-

viates some of this issue, the computation graph (the set of nodes involved in message passing in

each iteration) for a GNN with L layers often still includes millions of parameters. To circumvent

this, we use node neighbor sampling to select only a subset of nodes to include at each layer

when computing a node's message vector. Specifically, we take a sample n of neighbors at each

k-hop neighborhood at each gradient descent step when computing messages during optimiza-

tion. Node types with a smaller set of nodes *ClinGraph* are upweighted to ensure they are repre-

sented in the sampling. The number of samples at each layer is a hyperparameter selected

through hyperparameter tuning. The final training was performed on an H100 GPU for ten

epochs, during which we trained on all 2,873,025 edges of the KG.

Hyperparameter tuning

We perform hyperparameter tuning in 2 steps: first for the model architecture and then for the

parameters involved in the contrastive learning objective. We select a random subset of 500,000

edges for training and 100,000 for validation from *ClinGraph*. We perform hyperparameter tun-

ing using Raytune where we fix the learning rate (1e-4), number of negative samples (10), batch

size (100), and sampling neighborhood (10) and vary the following parameters: number of layers

(2, 3, 4), input feature dimension (128, 256, 512), output embedding dimension (128, 256, 512),

head dimension (128, 256, 512), number of heads (2, 3, 4), and dropout (0, 0.1, 0.2). Perfor-

mance is assessed by measuring the prediction accuracy on the set of 100,000 validation edges

and 100,000 node pairs that are not linked in the KG (negative edges). The optimal set of GNN

parameters is 4 layers, 128 input dimensions, 128 output embedding dimensions, 512-dimension

head size, three heads, and a dropout of 0.0.

We repeat the hyperparameter selection process by fixing the parameters selected above and vary

the following: learning rate (1e-3, 1e-4, 1e-5), neighborhood sampling (5, 10, 20), and number of

negative samples (3, 5, 10). The final hyperparameter set selected is a learning rate of 1e-5,

neighborhood sampling of 20 nodes, and three negative samples. All experiments were per-

formed using the Ray Tune software (https://docs.ray.io/en/latest/tune/index.html).

Clinical evaluation study

A key transferability aspect is demonstrating that the inferred clinical knowledge embeddings

capture medical insights that align with established clinical consensus. Although the knowledge

graph construction was based on mined biomedical literature, the inferred embeddings and latent

space offer insight into relationships between codes beyond the direct edges in the KG. To

validate this, we perform a human pilot evaluation with groups of clinical experts from Brigham

Women's (N=1), Mass General (N=1), Boston Children's Hospital (N=1), and CHS (N=3).

To systematically assess this, we evaluate the association between different diseases and

SNOMEDCT US codes. We restrict the set of SNOMED codes to the Clinical Observations Re-

cordings and Encoding (CORE) Problem List Subset of SNOMED CT[48]. This subset of codes

has been identified as most informative in documenting and encoding clinical information. We

survey clinicians to select 90 disease phenotypes (phecodes) that broadly capture major disease

areas and are clinically relevant for potential clinical AI applications. For each disease, we com-

pute the cosine similarity between each SNOMED CT code that does not already form an edge

with the target phecode. We select the top 20 SNOMED CT codes for evaluation. A control set is

constructed by randomly selecting 20 SNOMED CT codes that are not in the top 20 nor already

form an edge in the KG. To prevent biases due to differences in the frequency of symptoms or

high degree and low degree within *ClinGraph*, we match control SNOMED CT codes based on

the case code's node degree.

Clinicians were provided with shuffled disease lists of case and control codes. For a given dis-

ease, a single clinician evaluated the full list of codes. They were provided a brief background of

SNOMED CT codes and a scoring rubric where they were asked to evaluate each SNOMED CT

code according to how related each code is to the given disease phenotype. We utilize a Likert

scale[134] based on scores 1 – 5: 'unrelated' (0) and ' highly related' (5). If a code is too broad or

non-specific (e.g. 'Clinical evaluation'), these are assigned a 0.

Visualizing the latent space

To visualize the *ClinVec* embedding space, we perform UMAP[135] directly on the embedding vec-

tors and plot the first two dimensions. When performing dimensionality reduction, we use phe-

codes, ICD10CM, ATC, LOINC, CPT, and SNOMED CT embeddings. Phecode categorizations

are pre-defined from the phecode v1.2 mapping[136]. To visualize the latent space of phecodes

within the digestive system, we performed UMAP only on the subset of ICD10CM embeddings

within the 'Digestive' category. We highlight ICD10CM codes broadly corresponding to

mouth/teeth conditions (phecodes 520-530), functional digestive disorders (560-570), and biliary

tract disorders (570-580). To highlight embeddings related to specific diseases, we compute the

cosine similarity between an ICD10CM embedding (representing a disease) and each embedding

within the latent space. We visualize this relationship by shading each embedding within the

UMAP space according to the cosine similarity. We highlight relevant codes for lupus and type 1

diabetes to provide additional interpretation of the latent space map. This information was de-

rived from the guidelines provided by the National Resource Center on Lupus[137] and the Centers

for Disease Control and Prevention[138].

Comparing embeddings from PrimeKG and SNOMED-CT KG

We generate embeddings for PrimeKG and SNOMED-CT KG using the same graph transformer

architecture and hyperparameters as *ClinGraph*. For PrimeKG, we modeled 10 node types as de-

fined by the KG. For SNOMED-CT KG, we only used a single node type (i.e. homogenous

graph) since all nodes represent SNOMED CT codes. We trained both models for 5 epochs and

generated embeddings of size 128 for all SNOMED CT codes in SNOMED-CT KG and all dis-

eases (MONDO, HPO nodes) and drugs (DrugBank nodes) for PrimeKG. Clustering metrics, in-

cluding silhouette score and adjusted mutual information, were computed according to ATC

level 1 and phecode category.

Because neither KG have ICD or ATC codes, we mapped the nodes as follows. For SNOMED-

CT KG, we mapped each SNOMED CT code to its UMLS CUI and then to its corresponding

ICD10CM code if present. If a UMLS CUI does not have a corresponding source ICD10CM

code, we removed the node embedding from the cluster calculation. To map SNOMED CT to

ATC, we first mapped SNOMED CT codes to its UMLS CUI. We then used UMLS to identify

UMLS CUI codes with 'ingredient-of' relationships that describe the active ingredient (repre-

sented as ATC) present in a given UMLS CUI drug. SNOMED CT codes that did not have a

mapped ATC ingredient were removed from the clustering calculation. Clustering metrics were

computed using all 128 dimensions from each set of embeddings, and cluster visualizations were

produced using UMAP.

Zero-shot embedding retrieval tasks

We downloaded embeddings from snomed2vec

(https://github.com/KhushbuAgarwal/Snomed2Vec) and cui2vec (https://github.com/beaman-

drew/cui2vec) directly from the original publications. We formulated a set of 12 retrieval tasks

using well-established disease-symptom and disease-indication lists (Supplementary Table S8).

Top ranked neighbors are determined using cosine similarity between embeddings. We report

each model's performance using 'hits @ k' which measures the proportion of diseases where a

relevant symptom/drug is ranked among the top k items within the embedding space.

Disease embedding arithmetic

Constructing disease symptom embeddings

To demonstrate the syntactic and semantic properties of *ClinVec*, we use vector-level arithmetic

to aggregate together disease symptoms to form a 'disease symptom embedding'. Aggregation is

performed using sum pooling, but any vector-level aggregation method could be used in practice.

For a given disease, we retrieve the list of symptoms from the Mayo Clinic Disease Description

Guidelines[139]. A clinician manually translates each symptom into its corresponding ICD10CM

code. We provide these translations for all nine diseases discussed within this analysis (Supple-

mentary Table S5). To demonstrate the trend of increased similarity between a disease embed-

ding and the disease symptom embedding, we order symptoms from highest to lowest preva-

lence. We approximate population prevalence using a random sample of 200,000 patients from

the CHS database.

Disease symptom embeddings are first initialized with a vector of zeros. We then add the embed-

dings from all symptoms (represented by an ICD10CM embedding). For visualization, we com-

pute the cosine similarity between the disease symptom embedding at each step and the target

disease embedding, represented using an ICD10CM embedding. Across diseases, we see a broad

trend of increased similarity with the disease embedding as more symptoms are aggregated.

Robustness analysis

To assess the robustness and generalizability of these trends, we perform the same analysis under

various conditions while perturbing different variables in the framework. This includes analyses

assessing the uncertainty in selecting disease symptoms, incorrect disease specification, and the

impact of random symptoms. First, due to the noise and uncertainty associated with using diag-

nosis codes as proxies for disease symptoms[13], we tried to model real-world circumstances by

varying the ICD10CM code used to represent each symptom. We selected a set of candidate

ICD10CM codes for each symptom by taking the original code from the clinician review and se-

lecting all ICD10CM codes with the same parent code by removing one decimal place. For ex-

ample, for code '786.2' (Cough), the candidate set would include '786.1' (Stridor), '786.0'

(Dyspnea and respiratory abnormalities), etc. Then, when selecting each symptom for aggrega-

tion, a random code from the candidate set is selected. This process is repeated 10 times, yielding

similarity curves constructed from 10 different disease symptoms.

Next, we wanted to simulate when the disease of interest is mis-specified compared to the symp-

tom list. This reflects situations where the symptoms do not describe the target disease of interest

but, instead, a closely related condition. To imitate this, we selected a set of diseases similar to

the target disease; this was done by looking at other ICD10CM with the same parent code. When

computing the similarity between symptom embedding and disease embedding composition, we

used the phecode embedding of the alternative disease. Finally, we wanted to assess the situation

where incorrect information is included in the symptom list. We simulated this by adding a ran-

domly selected ICD10CM code to the symptom list and included it in the computation of the ag-

gregated symptoms. Because we use vector addition to aggregate symptoms and addition is com-

mutative, we place the random symptom at the beginning of the aggregation procedure.

Phenotype risk score

Case/control construction

To define cases, we first selected all patients with at least one ICD9CM code from the list of in-

clusion codes (CHS encodes their EHR using ICD9CM). We then filter patients to include only

patients listed on the CHS chronic registry to confirm they have received the disease diagnosis.

Because patients are not guaranteed to be added to the chronic registry when they are first diag-

nosed, we treat the first occurrence of the inclusion ICD9CM code as the date of diagnosis. For

each patient, we set the index date as January 1 of the year of diagnosis, where only information

occurring before the index date will be included in the risk score computation. For prediction, we

select all EHRs recorded within the past 5 years of the index date.

To define controls, we begin with the phecode exclusion criteria provided by the phecode map-

ping v1.2. For each phecode, the mapping provides a list of exclusion phecodes that are typically

similar conditions or overlap with the target disease. We begin by selecting all individuals who

have never received any exclusion diagnoses at any point in their EHR. We also remove individ-

uals from the chronic disease registry for the specified disease. We select a matched control from

this set of candidate control patients for each case. Matching is based on the following criteria: 1)

same sex, 2) year of birth ±2 years, and 3) number of recorded diagnoses in the EHR (with at

least 1 diagnosis in the EHR). The complete case-control process is illustrated in Supplementary

Figure S5.

Risk score computation

For a given disease, a risk score is computed as the weighted sum of relevant clinical codes,

where the weight is the cosine similarity between the embedding of each code and the disease

embedding. We restricted the set of potential features to laboratory tests, medications, and

ICD9CM codes with at least a 0.1% prevalence within the CHS patient population. The CHS

EHR did not have SNOMED CT or CPT codes for analysis. To determine the clinical codes re-

lated to each disease, we compute the cosine similarity between all clinical codes within the la-

tent space and the target disease embedding, represented by a phecode. The final set of features

is the top k codes, where k=20, and the feature weights are the cosine similarity scores. In prac-

tice, the choice of k can be treated as a hyper-parameter and optimized with a validation dataset,

similar to the p-value thresholding of polygenic risk scores. Patient risk scores are computed as a

weighted sum where the associated weight is added to the sum if the patient has the given code

in their EHR and given a 0 otherwise. Features are counted once in the score computation, even

if a patient receives the codes multiple times.

Survival analysis

For each disease, we computed the most common age at diagnosis and the sex with the highest

disease prevalence. We restricted the survival analysis to patients meeting these age/sex criteria

and those with a diagnosis date from 2016 or earlier. We re-computed risk score quantiles based

only on this restricted set of patients. We looked at the 6 years of EHR after each patient's index

date and denoted a patient as deceased if they had a non-null death date. Patients were stratified

into risk score quartiles based on the risk score computed at the index date. Confidence intervals

for the survival curves were computed using 10,000 bootstrapped samples.

Integrating *ClinVec* with LLMs

We augment MMed-Llama[106]—an 8-billion-parameter open-source medical foundation model

that already incorporates domain-specific knowledge through pre-training—with 42,883 *ClinVec*

embeddings and a 4-layer MLP projector module to align embedding dimensions which is

trained with parameter efficient fine-tuning. We download the pre-trained model from Hugging

871 Face (https://huggingface.co/Henrychur/MMed-Llama-3-8B) and use the authors' fine-tuning

872 pipeline to perform parameter efficient fine-tuning with LoRA[140] (https://github.com/MAGIC-

873 AI4Med/MMedLM/tree/main). We used the same prompts and sets of hyper-parameters pro-

874 vided by MMed-Llama, specifically tuning the following target modules: 'q_proj', 'v_proj',

875 'v_proj', 'mlp'. Fine-tuning was performed on the training English subset of multiple-choice

876 questions from the MedQA dataset (https://huggingface.co/datasets/VodLM/medqa).

877 *MetaMap*

878 We annotate each multiple-choice question using the MetaMap[141] tool, which annotates natural

879 language text with UMLS CUI codes. For each question, we concatenated the text from the ques-

880 tion and the answer options and submitted the text to the MetaMapLite REST API

881 (https://ii.nlm.nih.gov/metamaplite/rest). We limit the choice of UMLS CUI codes to the follow-

882 ing semantic types: "Sign or Symptom", "Disease or Syndrome", "Pharmacological Substance",

883 "Mental or Behavioral Dysfunction", "Chemical", "Anatomical Structure".

884 *AfriMed-QA*

885 We also perform a validation study on the AfriMed-QA[109] dataset (https://huggingface.co/da-

886 tasets/intronhealth/afrimedqa_v2). We restricted to only multiple-choice questions and removed

887 questions that had more than one assigned correct answer. The original dataset provides clinical

888 subspecialty information for each question.

889 **Institutional Review Board approval**

890 Parts of this study that relate to the use of CHS data (for evaluating the predictive ability of the

891 KG-derived concept embeddings) were approved by the CHS Institutional Review Board (Hel-

892 sinki) committee.

Data availability

Data and clinical concept embeddings, as well as the *ClinGraph* knowledge graph, are available via Harvard Dataverse https://doi.org/10.7910/DVN/Z6H1A8. Due to national and organizational data privacy regulations, CHS individual-level data from this study cannot be shared publicly.

Code availability

The Python implementation of the heterogeneous graph transformer and the associated codebase for model training, (non-individual-level) analyses, and embedding evaluations are available at https://github.com/mims-harvard/Clinical-knowledge-embeddings. The project website is at https://zitniklab.hms.harvard.edu/projects/Clinical-knowledge-embeddings.

Acknowledgements

R.J., B.Y.R., R.D.B., N.D., and M.Z. are supported by the Berkowitz Family Living Laboratory at Harvard Medical School and the Clalit Research Institute. R.J. and M.Z. gratefully acknowledge the support of NIH R01-HD108794, NSF CAREER 2339524, US DoD FA8702-15-D-0001, awards from Harvard Data Science Initiative, Amazon Faculty Research, Google Research Scholar Program, AstraZeneca Research, Roche Alliance with Distinguished Scientists, Sanofi iDEA-iTECH, Pfizer Research, Chan Zuckerberg Initiative, John and Virginia Kaneb Fellowship at Harvard Medical School, Biswas Computational Biology Initiative in partnership with the Milken Institute, Harvard Medical School Dean's Innovation Fund for the Use of Artificial Intelligence, and Kempner Institute for the Study of Natural and Artificial Intelligence at Harvard University. Any opinions, findings, conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the funders. We gratefully acknowledge the resources provided by the Clalit Research Institute. We thank Michelle M. Li, Ayush Noori, Intae Moon, and Shvat Messica for contributing to the model development and analyses.

Author contributions

R.J. developed a unified knowledge graph representation of clinical concepts and designed, implemented, and benchmarked heterogeneous graph transformer models. U.G. implemented the approach and conducted detailed analyses using CHS individual-level data. L.H., J.W., S.D.,

C.R.G., P.H., and R.S. formed an inter-institutional panel of clinicians that evaluated the align-

ment of clinical concept representations with established clinical knowledge across 90 diseases

and 3,000 clinical codes. B.Y.R. and R.B. provided feedback on the methodology and evaluated

the clinical concept embeddings through large-scale phenotype risk scoring and alignment with

expert clinical knowledge. R.J., N.D., and M.Z. conceptualized and designed the study. All au-

thors contributed to writing the manuscript.

Competing interests

The authors declare no competing interests.

References

1. National Research Council (US) Committee on A Framework for Developing a NewTaxonomy of Disease. *Toward Precision Medicine: Building a Knowledge Network for Biomedical Research and a New Taxonomy of Disease*. (National Academies Press (US), Washington (DC), 2011).

2. Campbell, J. R. *et al.* Phase II Evaluation of Clinical Coding Schemes: Completeness, Taxonomy, Mapping, Definitions, and Clarity. *J. Am. Med. Inform. Assoc.* **4**, 238–251 (1997).

3. de Lusignan, S. Codes, classifications, terminologies and nomenclatures: definition, development and application in practice. *Inform. Prim. Care* **13**, 65–70 (2005).

4. Kather, J. N., Ferber, D., Wiest, I. C., Gilbert, S. & Truhn, D. Large language models could make natural language again the universal interface of healthcare. *Nat. Med.* 1–3 (2024) doi:10.1038/s41591-024-03199-w.

5. Hulsen, T. *et al.* From Big Data to Precision Medicine. *Front. Med.* **6**, 34 (2019).

6. Topol, E. J. High-performance medicine: the convergence of human and artificial intelligence. *Nat. Med.* **25**, 44–56 (2019).

7. The Shaky Foundations of Foundation Models in Healthcare. https://hai.stanford.edu/news/shaky-foundations-foundation-models-healthcare (2023).

8. Zech, J. R. *et al.* Variable generalization performance of a deep learning model to detect pneumonia in chest radiographs: A cross-sectional study. *PLOS Med.* **15**, e1002683 (2018).

9. Yang, J., Soltan, A. A. S. & Clifton, D. A. Machine learning generalizability across healthcare settings: insights from multi-site COVID-19 screening. *Npj Digit. Med.* **5**, 1–8 (2022).

10. Panch, T. *et al.* "Yes, but will it work for my patients?" Driving clinically relevant research with benchmark datasets. *Npj Digit. Med.* **3**, 1–4 (2020).

11. Goetz, L., Seedat, N., Vandersluis, R. & van der Schaar, M. Generalization—a key challenge for responsible AI in patient-facing clinical applications. *Npj Digit. Med.* **7**, 1–4 (2024).

12.   O'Malley, K. J. *et al.* Measuring Diagnoses: ICD Code Accuracy. *Health Serv. Res.* **40**,

1620 (2005).

13.   Botsis, T., Hartvigsen, G., Chen, F. & Weng, C. Secondary Use of EHR: Data Quality Is-

sues and Informatics Opportunities. *Summit Transl. Bioinforma.* **2010**, 1–5 (2010).

14.   Sudat, S. E., Robinson, S. C., Mudiganti, S., Mani, A. & Pressman, A. R. Mind the clini-

cal-analytic gap: Electronic health records and COVID-19 pandemic response. *J. Biomed. In-*

form. **116**, 103715 (2021).

15.   Binkheder, S. *et al.* Real-World Evidence of COVID-19 Patients' Data Quality in the

Electronic Health Records. *Healthcare* **9**, 1648 (2021).

16.   Chalmers, R. J. G. Health Care Terminology for the Electronic Era. *Mayo Clin. Proc.* **81**,

729–731 (2006).

17.   Song, Z. *et al.* Physician Practice Pattern Variations in Common Clinical Scenarios

Within 5 US Metropolitan Areas. *JAMA Health Forum* **3**, e214698 (2022).

18.   Baicker, K., Chandra, A., Skinner, J. S. & Wennberg, J. E. Who you are and where you

live: how race and geography affect the treatment of medicare beneficiaries. *Health Aff. Proj.*

Hope **Suppl Variation**, VAR33-44 (2004).

19.   Baicker, K., Chandra, A. & Skinner, J. S. Geographic variation in health care and the

problem of measuring racial disparities. *Perspect. Biol. Med.* **48**, S42-53 (2005).

20.   Medicine, I. of, Services, B. on H. C. & Programs, C. on R. H. I. P. M., Payment, and

Performance Improvement. *Rewarding Provider Performance: Aligning Incentives in Medi-*

care. (National Academies Press, 2007).

21.   Blumenthal, D. & Tavenner, M. The "Meaningful Use" Regulation for Electronic Health

Records. *N. Engl. J. Med.* **363**, 501–504 (2010).

22.   McIlvennan, C. K., Eapen, Z. J. & Allen, L. A. Hospital Readmissions Reduction Pro-

gram. *Circulation* **131**, 1796–1803 (2015).

23.   Morden, N. E., Colla, C. H., Sequist, T. D. & Rosenthal, M. B. Choosing Wisely — The

981   Politics and Economics of Labeling Low-Value Services. *N. Engl. J. Med.* **370**, 589–592

982   (2014).

983   24.   Fisher, E. S. *et al.* The implications of regional variations in Medicare spending. Part 1:

984   the content, quality, and accessibility of care. *Ann. Intern. Med.* **138**, 273–287 (2003).

985   25.   Charlesworth, C. J., Meath, T. H. A., Schwartz, A. L. & McConnell, K. J. Comparison of

986   Low-Value Care in Medicaid vs Commercially Insured Populations. *JAMA Intern. Med.* **176**,

987   998–1004 (2016).

988   26.   Baicker, K., Chernew, M. E. & Robbins, J. A. The spillover effects of Medicare managed

989   care: Medicare Advantage and hospital utilization. *J. Health Econ.* **32**, 1289–1300 (2013).

990   27.   Ancker, J. S. *et al.* How is the electronic health record being used? Use of EHR data to

991   assess physician-level variability in technology use. *J. Am. Med. Inform. Assoc.* **21**, 1001–

992   1008 (2014).

993   28.   Roland, M. Linking Physicians' Pay to the Quality of Care — A Major Experiment in the

994   United Kingdom. *N. Engl. J. Med.* **351**, 1448–1454 (2004).

995   29.   Sirovich, B. E., Gottlieb, D. J., Welch, H. G. & Fisher, E. S. Variation in the Tendency of

996   Primary Care Physicians to Intervene. *Arch. Intern. Med.* **165**, 2252–2256 (2005).

997   30.   Berner, E. S., Kasiraman, R. K., Yu, F., Ray, M. N. & Houston, T. K. Data quality in the

998   outpatient setting: impact on clinical decision support systems. *AMIA Annu. Symp. Proc.*

999   *AMIA Symp.* 41–45 (2005).

1000   31.   Verheij, R. A., Curcin, V., Delaney, B. C. & McGilchrist, M. M. Possible Sources of Bias

1001   in Primary Care Electronic Health Record Data Use and Reuse. *J. Med. Internet Res.* **20**, e185

1002   (2018).

1003 32. Agniel, D., Kohane, I. S. & Weber, G. M. Biases in electronic health record data due to

1004   processes within the healthcare system: retrospective observational study. *BMJ* **361**, k1479

1005   (2018).

1006 33. Tang, P. C., Ralston, M., Arrigotti, M. F., Qureshi, L. & Graham, J. Comparison of Meth-

1007   odologies for Calculating Quality Measures Based on Administrative Data versus Clinical

1008   Data from an Electronic Health Record System: Implications for Performance Measures. *J.*

1009   *Am. Med. Inform. Assoc.* **14**, 10–15 (2007).

1010 34. Hogan, W. R. & Wagner, M. M. Accuracy of Data in Computer-based Patient Records. *J.*

1011   *Am. Med. Inform. Assoc.* **4**, 342 (1997).

1012 35. Hripcsak, G. & Albers, D. J. Next-generation phenotyping of electronic health records. *J.*

1013   *Am. Med. Inform. Assoc. JAMIA* **20**, 117 (2012).

1014 36. Williams, R., Kontopantelis, E., Buchan, I. & Peek, N. Clinical code set engineering for

1015   reusing EHR data for research: A review. *J. Biomed. Inform.* **70**, 1–13 (2017).

1016 37. Delvaux, N. *et al.* Coding Systems for Clinical Decision Support: Theoretical and Real-

1017   World Comparative Analysis. *JMIR Form. Res.* **4**, e16094 (2020).

1018 38. Odigie, E. *et al.* Fast Healthcare Interoperability Resources, Clinical Quality Language,

1019   and Systematized Nomenclature of Medicine—Clinical Terms in Representing Clinical Evi-

1020   dence Logic Statements for the Use of Imaging Procedures: Descriptive Study. *JMIR Med. In-*

1021   *form.* **7**, e13590 (2019).

1022 39. Kokkinakis, D. What is the Coverage of SNOMED CT®on Scientific Medical Cor-

1023   pora? in *User Centred Networked Health Care* 814–818 (IOS Press, 2011). doi:10.3233/978-

1024   1-60750-806-9-814.

1025 40. Wiens, J. *et al.* Do no harm: a roadmap for responsible machine learning for health care.

1026   *Nat. Med.* **25**, 1337–1340 (2019).

41.   Yang, J. *et al.* Poisoning medical knowledge using large language models. *Nat. Mach. In-*

tell. **6**, 1156–1168 (2024).

42.   Omiye, J. A., Lester, J. C., Spichak, S., Rotemberg, V. & Daneshjou, R. Large language

models propagate race-based medicine. *Npj Digit. Med.* **6**, 1–4 (2023).

43.   Zack, T. *et al.* Assessing the potential of GPT-4 to perpetuate racial and gender biases in

health care: a model evaluation study. *Lancet Digit. Health* **6**, e12–e22 (2024).

44.   Soroush, A. *et al.* Large Language Models Are Poor Medical Coders — Benchmarking of

Medical Code Querying. *NEJM AI* **1**, AIdbp2300040 (2024).

45.   Huang, J. *et al.* A critical assessment of using ChatGPT for extracting structured data

from clinical notes. *Npj Digit. Med.* **7**, 1–13 (2024).

46.   Burford, K. G., Itzkowitz, N. G., Ortega, A. G., Teitler, J. O. & Rundle, A. G. Use of

Generative AI to Identify Helmet Status Among Patients With Micromobility-Related Injuries

From Unstructured Clinical Notes. *JAMA Netw. Open* **7**, e2425981 (2024).

47.   Lee, S. A. & Lindsey, T. Can Large Language Models abstract Medical Coded Language?

Preprint at https://doi.org/10.48550/arXiv.2403.10822 (2024).

48.   The CORE Problem List Subset of SNOMED CT®. https://www.nlm.nih.gov/re-

search/umls/Snomed/core_subset.html.

49.   von Rueden, L. *et al.* Informed Machine Learning – A Taxonomy and Survey of Integrat-

ing Prior Knowledge into Learning Systems. *IEEE Trans. Knowl. Data Eng.* **35**, 614–633

(2023).

50.   Sirocchi, C., Bogliolo, A. & Montagna, S. Medical-informed machine learning: integrat-

ing prior knowledge into medical decision systems. *BMC Med. Inform. Decis. Mak.* **24**, 186

(2024).

51.   General Cardiovascular Risk Profile for Use in Primary Care | Circulation.

https://www.ahajournals.org/doi/10.1161/CIRCULATIONAHA.107.699579.

52.   ACMG recommendations for standards for interpretation of sequence variations. *Genet.*

Med. **2**, 302–303 (2000).

53.   Poonacha, T. K. & Go, R. S. Scientific evidence underlying National Comprehensive

Cancer Network Clinical Practice Guidelines. *J. Clin. Oncol.* **28**, 6020–6020 (2010).

54.   Institute of Medicine (US) Committee on Standards for Developing Trustworthy Clinical

Practice Guidelines. *Clinical Practice Guidelines We Can Trust*. (National Academies Press

(US), Washington (DC), 2011).

55.   Zitnik, M., Agrawal, M. & Leskovec, J. Modeling polypharmacy side effects with graph

convolutional networks. *Bioinformatics* **34**, i457–i466 (2018).

56.   Nelson, W. *et al.* To Embed or Not: Network Embedding as a Paradigm in Computational

Biology. *Front. Genet.* **10**, (2019).

57.   Tshitoyan, V. *et al.* Unsupervised word embeddings capture latent knowledge from mate-

rials science literature. *Nature* **571**, 95–98 (2019).

58.   Zitnik, M. *et al.* Machine learning for integrating data in biology and medicine: Princi-

ples, practice, and opportunities. *Inf. Fusion* **50**, 71–91 (2019).

59.   Zhou, H. *et al.* Knowledge-guided convolutional networks for chemical-disease relation

extraction. *BMC Bioinformatics* **20**, 260 (2019).

60.   Nunes, S., Sousa, R. T. & Pesquita, C. Multi-domain knowledge graph embeddings for

gene-disease association prediction. *J. Biomed. Semant.* **14**, 11 (2023).

61.   Informatics, O. H. D. S. and. *Chapter 4 The Common Data Model | The Book of OHDSI*.

62.   Himmelstein, D. S. & Baranzini, S. E. Heterogeneous Network Edge Prediction: A Data

Integration Approach to Prioritize Disease-Associated Genes. *PLOS Comput. Biol.* **11**,

e1004259 (2015).

63.   Morris, J. H. *et al.* The scalable precision medicine open knowledge engine (SPOKE): a

massive knowledge graph of biomedical information. *Bioinformatics* **39**, btad080 (2023).

64.   Santos, A. *et al.* A knowledge graph to interpret clinical proteomics data. *Nat. Biotechnol.*

40, 692–702 (2022).

65.   Himmelstein, D. S. *et al.* Systematic integration of biomedical knowledge prioritizes

drugs for repurposing. *eLife* **6**, e26726 (2017).

66.   Gogleva, A. *et al.* Knowledge graph-based recommendation framework identifies drivers

of resistance in EGFR mutant non-small cell lung cancer. *Nat. Commun.* **13**, 1667 (2022).

67.   Zhu, Q. *et al.* An integrative knowledge graph for rare diseases, derived from the Genetic

and Rare Diseases Information Center (GARD). *J. Biomed. Semant.* **11**, 13 (2020).

68.   Sosa, D. N. *et al.* A Literature-Based Knowledge Graph Embedding Method for Identify-

ing Drug Repurposing Opportunities in Rare Diseases. *Pac. Symp. Biocomput. Pac. Symp. Bi-*

ocomput. **25**, 463–474 (2020).

69.   Feng, F. *et al.* GenomicKB: a knowledge graph for the human genome. *Nucleic Acids*

Res. **51**, D950–D956 (2023).

70.   Renaux, A. *et al.* A knowledge graph approach to predict and interpret disease-causing

gene interactions. *BMC Bioinformatics* **24**, 324 (2023).

71.   Percha, B. & Altman, R. B. A global network of biomedical relationships derived from

text. *Bioinformatics* **34**, 2614–2624 (2018).

72.   Ernst, P., Siu, A. & Weikum, G. KnowLife: a versatile approach for constructing a large

knowledge graph for biomedical sciences. *BMC Bioinformatics* **16**, 157 (2015).

73.   Zheng, S. *et al.* PharmKG: a dedicated knowledge graph benchmark for bomedical data

mining. *Brief. Bioinform.* **22**, bbaa344 (2021).

74.   Robinson, P. N. *et al.* The Human Phenotype Ontology: A Tool for Annotating and Ana-

lyzing Human Hereditary Disease. *Am. J. Hum. Genet.* **83**, 610–615 (2008).

75.   Vasilevsky, N. A. *et al.* Mondo: Unifying diseases for the world, by the world.

2022.04.13.22273750 Preprint at https://doi.org/10.1101/2022.04.13.22273750 (2022).

76. Chandak, P., Huang, K. & Zitnik, M. Building a knowledge graph to enable precision medicine. *Sci. Data* **10**, 67 (2023).

77. Wang, M. *et al.* PDD Graph: Bridging Electronic Medical Records and Biomedical Knowledge Graphs via Entity Linking. in *The Semantic Web – ISWC 2017* (eds. d'Amato, C. et al.) 219–227 (Springer International Publishing, Cham, 2017). doi:10.1007/978-3-319-68204-4_23.

78. Nelson, C. A., Butte, A. J. & Baranzini, S. E. Integrating biomedical research and electronic health records to create knowledge-based biologically meaningful machine-readable embeddings. *Nat. Commun.* **10**, 3045 (2019).

79. Huan, J.-M. *et al.* The biomedical knowledge graph of symptom phenotype in coronary artery plaque: machine learning-based analysis of real-world clinical data. *BioData Min.* **17**, 13 (2024).

80. Rotmensch, M., Halpern, Y., Tlimat, A., Horng, S. & Sontag, D. Learning a Health Knowledge Graph from Electronic Medical Records. *Sci. Rep.* **7**, 5994 (2017).

81. Murali, L., Gopakumar, G., Viswanathan, D. M. & Nedungadi, P. Towards electronic health record-based medical knowledge graph construction, completion, and applications: A literature study. *J. Biomed. Inform.* **143**, 104403 (2023).

82. Bodenreider, O. The Unified Medical Language System (UMLS): integrating biomedical terminology. *Nucleic Acids Res.* **32**, D267–D270 (2004).

83. Zheng, N. S. *et al.* PheMap: a multi-resource knowledge base for high-throughput phenotyping within electronic health records. *J. Am. Med. Inform. Assoc.* **27**, 1675–1687 (2020).

84. Königs, C., Friedrichs, M. & Dietrich, T. The heterogeneous pharmacological medical biochemical network PharMeBINet. *Sci. Data* **9**, 393 (2022).

85. Alber, D. A. *et al.* Medical large language models are vulnerable to data-poisoning attacks. *Nat. Med.* **31**, 618–626 (2025).

1127   86.   Hu, Z., Dong, Y., Wang, K. & Sun, Y. Heterogeneous Graph Transformer. Preprint at

1128   https://doi.org/10.48550/arXiv.2003.01332 (2020).

1129   87.   Vaswani, A. *et al.* Attention Is All You Need. Preprint at

1130   https://doi.org/10.48550/arXiv.1706.03762 (2023).

1131   88.   Oord, A. van den, Li, Y. & Vinyals, O. Representation Learning with Contrastive Predic-

1132   tive Coding. Preprint at https://doi.org/10.48550/arXiv.1807.03748 (2019).

1133   89.   Agarwal, K. *et al.* Snomed2Vec: Random Walk and Poincaré Embeddings of a Clinical

1134   Knowledge Base for Healthcare Analytics. Preprint at

1135   https://doi.org/10.48550/arXiv.1907.08650 (2019).

1136   90.   Beam, A. L. *et al.* Clinical Concept Embeddings Learned from Massive Sources of Multi-

1137   modal Medical Data. Preprint at https://doi.org/10.48550/arXiv.1804.01486 (2019).

1138   91.   Mikolov, T., Yih, S. W. & Zweig, G. Linguistic Regularities in Continuous Space Word

1139   Representations. in (2013).

1140   92.   The top 10 causes of death. https://www.who.int/news-room/fact-sheets/detail/the-top-10-

1141   causes-of-death.

1142   93.   Conrad, N. *et al.* Incidence, prevalence, and co-occurrence of autoimmune disorders over

1143   time and by age, sex, and socioeconomic status: a population-based cohort study of 22 million

1144   individuals in the UK. *Lancet Lond. Engl.* **401**, 1878–1890 (2023).

1145   94.   Heart disease - Symptoms and causes. *Mayo Clinic* https://www.mayoclinic.org/diseases-

1146   conditions/heart-disease/symptoms-causes/syc-20353118.

1147   95.   COPD - Symptoms and causes. *Mayo Clinic* https://www.mayoclinic.org/diseases-condi-

1148   tions/copd/symptoms-causes/syc-20353679.

1149   96.   Alzheimer's disease - Symptoms and causes. *Mayo Clinic* https://www.mayo-

1150   clinic.org/diseases-conditions/alzheimers-disease/symptoms-causes/syc-20350447.

97.   Lung cancer - Symptoms and causes. *Mayo Clinic* https://www.mayoclinic.org/diseases-

conditions/lung-cancer/symptoms-causes/syc-20374620.

98.   Stroke - Symptoms and causes. *Mayo Clinic* https://www.mayoclinic.org/diseases-condi-

tions/stroke/symptoms-causes/syc-20350113.

99.   Dudbridge, F. Power and Predictive Accuracy of Polygenic Risk Scores. *PLOS Genet.* **9**,

e1003348 (2013).

100.   Bastarache, L. *et al.* Phenotype risk scores identify patients with unrecognized Mendelian

disease patterns. *Science* **359**, 1233–1239 (2018).

101.   Balicer, R. D. & Afek, A. Digital health nation: Israel's global big data innovation hub.

The Lancet **389**, 2451–2453 (2017).

102.   Rennert, G. & Peterburg, Y. Prevalence of selected chronic diseases in Israel. *Isr. Med.*

Assoc. J. IMAJ **3**, 404–408 (2001).

103.   Choi, S. W., Mak, T. S. H. & O'Reilly, P. F. A guide to performing Polygenic Risk Score

analyses. *Nat. Protoc.* **15**, 2759–2772 (2020).

104.   Singhal, K. *et al.* Toward expert-level medical question answering with large language

models. *Nat. Med.* **31**, 943–950 (2025).

105.   Singhal, K. *et al.* Large language models encode clinical knowledge. *Nature* **620**, 172–

180 (2023).

106.   Qiu, P. *et al.* Towards Building Multilingual Language Model for Medicine. Preprint at

https://doi.org/10.48550/arXiv.2402.13963 (2024).

107.   Maharjan, J. *et al.* OpenMedLM: prompt engineering can out-perform fine-tuning in

medical question-answering with open-source large language models. *Sci. Rep.* **14**, 14156

(2024).

108.   Jin, D. *et al.* What Disease does this Patient Have? A Large-scale Open Domain Question

Answering Dataset from Medical Exams. Preprint at

https://doi.org/10.48550/arXiv.2009.13081 (2020).

109.   Olatunji, T. *et al.* AfriMed-QA: A Pan-African, Multi-Specialty, Medical Question-An-

swering Benchmark Dataset. Preprint at https://doi.org/10.48550/arXiv.2411.15640 (2025).

110.   Bommasani, R. *et al.* On the Opportunities and Risks of Foundation Models. Preprint at

https://doi.org/10.48550/arXiv.2108.07258 (2022).

111.   DeepSeek-AI *et al.* DeepSeek-V3 Technical Report. Preprint at

https://doi.org/10.48550/arXiv.2412.19437 (2025).

112.   Touvron, H. *et al.* LLaMA: Open and Efficient Foundation Language Models. Preprint at

https://doi.org/10.48550/arXiv.2302.13971 (2023).

113.   Lewis, P. *et al.* Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks.

Preprint at https://doi.org/10.48550/arXiv.2005.11401 (2021).

114.   Heart Disease in Men and Women. https://www.massgeneralbrigham.org/en/about/news-

room/articles/heart-disease-in-men-and-women.

115.   Shuey, M. M. *et al.* Next-generation phenotyping: introducing phecodeX for enhanced

discovery research in medical phenomics. *Bioinformatics* **39**, btad655 (2023).

116.   Amberger, J. S., Bocchini, C. A., Schiettecatte, F., Scott, A. F. & Hamosh, A. OMIM.org:

Online Mendelian Inheritance in Man (OMIM®), an online catalog of human genes and ge-

netic disorders. *Nucleic Acids Res.* **43**, D789-798 (2015).

117.   Lukas, N. *et al.* Analyzing Leakage of Personally Identifiable Information in Language

Models. in *2023 IEEE Symposium on Security and Privacy (SP)* 346–363 (2023).

doi:10.1109/SP46215.2023.10179300.

118. Pan, X., Zhang, M., Ji, S. & Yang, M. Privacy Risks of General-Purpose Language Mod-

els. in *2020 IEEE Symposium on Security and Privacy (SP)* 1314–1331 (2020).

doi:10.1109/SP40000.2020.00095.

119. Shevtsova, D. *et al.* Trust in and Acceptance of Artificial Intelligence Applications in

Medicine: Mixed Methods Study. *JMIR Hum. Factors* **11**, e47031 (2024).

120. International Classification of Diseases (ICD). https://www.who.int/standards/classifica-

tions/classification-of-diseases.

121. ATCDDD - Structure and principles. https://atcddd.fhi.no/atc/structure_and_principles/.

122. RxNorm. https://www.nlm.nih.gov/research/umls/rxnorm/index.html.

123. SNOMED CT. https://www.nlm.nih.gov/healthit/snomedct/index.html.

124. CPT® overview and code approval. *American Medical Association* https://www.ama-

assn.org/practice-management/cpt/cpt-overview-and-code-approval (2024).

125. Forrey, A. W. *et al.* Logical observation identifier names and codes (LOINC) database: a

public use set of codes and names for electronic reporting of clinical laboratory test results.

Clin. Chem. **42**, 81–90 (1996).

126. Denny, J. C. *et al.* PheWAS: demonstrating the feasibility of a phenome-wide scan to dis-

cover gene-disease associations. *Bioinforma. Oxf. Engl.* **26**, 1205–1210 (2010).

127. Wu, P. *et al.* Mapping ICD-10 and ICD-10-CM Codes to Phecodes: Workflow Develop-

ment and Initial Evaluation. *JMIR Med. Inform.* **7**, e14325 (2019).

128. Wei, W.-Q. *et al.* Evaluating phecodes, clinical classification software, and ICD-9-CM

codes for phenome-wide association studies in the electronic health record. *PLOS ONE* **12**,

e0175508 (2017).

129. Bastarache, L. Using Phecodes for Research with the Electronic Health Record: From

PheWAS to PheRS. *Annu. Rev. Biomed. Data Sci.* **4**, 1–19 (2021).

130.   Wilcke, X., Bloem, P. & de Boer, V. The knowledge graph as the default data model for

1222   learning on heterogeneous knowledge. *Data Sci.* **1**, 39–57 (2017).

1223   131.   Radford, A. *et al.* Learning Transferable Visual Models From Natural Language Supervi-

1224   sion. Preprint at https://doi.org/10.48550/arXiv.2103.00020 (2021).

1225   132.   Sohn, K. Improved Deep Metric Learning with Multi-class N-pair Loss Objective. in *Ad-*

1226   *vances in Neural Information Processing Systems* vol. 29 (Curran Associates, Inc., 2016).

1227   133.   Chen, T., Kornblith, S., Norouzi, M. & Hinton, G. A simple framework for contrastive

1228   learning of visual representations. in *Proceedings of the 37th International Conference on Ma-*

1229   *chine Learning* vol. 119 1597–1607 (JMLR.org, 2020).

1230   134.   Likert, R. A technique for the measurement of attitudes. *Arch. Psychol.* **22 140**, 55–55

1231   (1932).

1232   135.   McInnes, L., Healy, J. & Melville, J. UMAP: Uniform Manifold Approximation and Pro-

1233   jection for Dimension Reduction. Preprint at https://doi.org/10.48550/arXiv.1802.03426

1234   (2018).

1235   136.   PheWAS - Phenome Wide Association Studies. https://phewascatalog.org/phe-

1236   codes_v1_1.

1237   137.   Lab Tests for Lupus | Lupus Foundation of America. https://www.lupus.org/resources/lab-

1238   tests-for-lupus.

1239   138.   CDC. Type 1 Diabetes. *Diabetes* https://www.cdc.gov/diabetes/about/about-type-1-diabe-

1240   tes.html (2025).

1241   139.   Medical Diseases & Conditions. *Mayo Clinic* https://www.mayoclinic.org/diseases-condi-

1242   tions.

1243   140.   Hu, E. J. *et al.* LoRA: Low-Rank Adaptation of Large Language Models. Preprint at

1244   https://doi.org/10.48550/arXiv.2106.09685 (2021).

1245   141.   Aronson, A. R. Effective mapping of biomedical text to the UMLS Metathesaurus: the

1246   MetaMap program. *Proc. AMIA Symp.* 17–21 (2001).

1247