A Unified Flexible Large Polysomnography Model for Sleep Staging and Mental Disorder Diagnosis

Guifeng Deng [1,2], Mengfan Niu[1], Shuying Rao[1,2], Yuxi Luo[3], Jianjia Zhang[3], Junyi Xie[1], Zhenghe Yu[1], Wenjuan Liu[1], Junhang Zhang[1], Sha Zhao[4], Gang Pan[4], Xiaojing Li[1,4], Wei Deng[1,4], Wanjun Guo[1,4], Yaoyun Zhang[5], Tao Li [1,4*], Haiteng Jiang [1,4,6*]

[1]Affiliated Mental Health Center & Hangzhou Seventh People's Hospital, School of Brain Science and Brain Medicine, and Liangzhu Laboratory, Zhejiang University School of Medicine, Hangzhou, 310058, China.
[2]College of Biomedical Engineering & Instrument Science, Zhejiang University, Hangzhou, 310058, China.
[3]School of Biomedical Engineering, Shenzhen Campus of Sun Yat-sen University, Shenzhen, 518100, China.
[4]MOE Frontier Science Center for Brain Science and Brain-machine Integration, State Key Lab of Brain-Machine Intelligence, Zhejiang University, Hangzhou 311121, China.
[5] School of Biomedical Informatics, University of Texas at Dallas, 800 W Campbell Rd, Richardson, TX 75080, USA.
[6] Department of Psychiatry and Mental Health, Wenzhou Medical University, Wenzhou 325035, Zhejiang Province, China.

*Corresponding authors:
Tao Li   Email: litaozjusc@zju.edu.cn
Haiteng Jiang   Email: h.jiang@zju.edu.cn

Abstract

Sleep disorders affect billions worldwide, yet clinical polysomnography (PSG) analysis remains hindered by labor-intensive manual scoring and limited generalizability of automated sleep staging tools across heterogeneous protocols. We present LPSGM, a large-scale PSG model designed to address two critical challenges in sleep medicine: cross-center generalization and adaptable diagnosis of neuropsychiatric disorders. Trained on 220,500 hours of multi-center PSG data (24,000 full-night recordings from 16 public datasets), LPSGM integrates domain-adaptive pre-training, flexible channel configurations, and a unified architecture to mitigate variability in equipment, montages, and populations during sleep staging while enabling downstream fine-tuning for mental disorder detection. In prospective validation, LPSGM achieves expert-level consensus in sleep staging ($\kappa = 0.845 \pm 0.066$ vs. inter-expert $\kappa = 0.850 \pm 0.102$) and matches the performance of fully supervised models on two independent private cohorts. When fine-tuned, it attains 88.01% accuracy in narcolepsy detection and 100% accuracy in identifying major depressive disorder (MDD), highlighting shared physiological biomarkers between sleep architecture and neuropsychiatric symptoms. By bridging automated sleep staging with real-world clinical deployment, LPSGM establishes a scalable, data-efficient framework for integrated sleep and mental health diagnostics. The code and pre-trained model are publicly available at https://github.com/Deng-GuiFeng/LPSGM to advance reproducibility and translational research in sleep medicine.

Keywords: Polysomnography (PSG); Sleep staging; Narcolepsy; Major depressive disorder (MDD); Domain adaptation

Introduction

Sleep occupies nearly one-third of human life and serves as a critical determinant of overall health[1,2]. The escalating global burden of sleep disorders—including insomnia, obstructive sleep apnea (OSA), and narcolepsy—represents a major public health challenge. Epidemiological studies indicate that OSA affects approximately one billion adults worldwide[3], while insomnia disorder impacts 10% of the adult population, with an additional 20% experiencing transient symptoms[4].

Polysomnography (PSG), the gold-standard tool for sleep assessment, captures multimodal physiological signals—including electroencephalogram (EEG), electrooculogram (EOG), and electromyogram (EMG) to analyze sleep architecture according to American Academy of Sleep Medicine (AASM) guidelines[5], which classify sleep into wakefulness (W), non-rapid eye movement (NREM: N1–N3), and rapid eye movement (REM) stages. By mapping these stages, PSG reveals how deviations in sleep architecture—such as shortened REM latency in narcolepsy[6,7] or fragmented sleep, reduced slow-wave activity and disinhibition REM sleep in MDD[8–11]—serve as biomarkers for neuropsychiatric conditions, positioning it as a dual-purpose tool for both sleep staging and mental health diagnostics.

Conventional manual PSG scoring requires clinicians to annotate 30-second epochs, a process requiring approximately two hours per full-night recording (7–9 hours of PSG data). This labor-intensive method suffers from significant inter-rater variability due to subjective interpretation of ambiguous patterns, undermining diagnostic consistency across clinical setting[12–16]. Machine learning advances have partially addressed these inefficiencies through automated sleep staging[17–34]. Early approaches relied on hand-engineered features and traditional machine learning models (e.g., support vector machines, random forests), but struggled to capture complex patterns of sleep physiology[17–23]. Subsequent deep learning frameworks—notably convolutional and recurrent neural networks (CNNs/RNNs)—enabled end-to-end learning of hierarchical representations directly from raw physiological data, achieving accuracy comparable to human experts[24–34]. However, current studies prioritize intra-dataset performance using fixed PSG channel configurations, exhibiting marked performance degradation in cross-domain settings due to variability in PSG protocols and population demographics. Transfer learning strategies[28–32]—including domain adaptation[28,29,32] and adversarial training[31]—improve out-of-distribution (OOD) generalization but persistently underperform models trained on target-domain data. These limitations underscore the urgent need for robust, generalizable frameworks capable of adapting to heterogeneous clinical environments.

Despite recent progress, clinical adoption of automated sleep staging systems remains constrained by two interrelated challenges: domain shift and data scarcity. PSG heterogeneity—driven by variability in recording protocols, equipment, and populations—contravenes the independent and identically distributed (IID) assumption critical to conventional deep learning, while the labor-intensive nature of manual annotation impedes scalable dataset curation. Although numerous public sleep datasets exist[6,35–52], their collective utility is diminished by inconsistent signal montages and channel configurations (Supplementary Table 2). Drawing inspiration from recent advances in large language models (LLMs) [53–55] and EEG foundation models[56–58], we propose that a unified framework integrating multi-center PSG data through domain-adaptive pre-training could mitigate domain shifts while unlocking downstream clinical utility.

Here, we present LPSGM, a large PSG model designed to overcome two critical barriers in sleep medicine: (1) cross-center generalization in automated sleep staging and (2) adaptable PSG-based diagnosis of neuropsychiatric disorders. Our framework integrates three core innovations: (i) Unified training protocol for harmonizing heterogeneous datasets with variable montages and channel configurations, (ii) Flexible inference architecture that dynamically adapts to diverse clinical PSG setups, (iii) Hybrid pre-training on 220,500 hours of PSG data (24,000 recordings) aggregated from 16 public datasets. LPSGM achieves performance parity with fully supervised models trained on two independent private datasets (HANG7 and SYSU; see supplementary materials for additional details). In prospective validation, it matches human expert consensus (model vs. experts: $\kappa = 0.845 \pm 0.066$; inter-expert agreement: $\kappa = 0.850 \pm 0.102$), demonstrating clinical-grade reliability. When

fine-tuned for disease detection, LPSGM attains 88.01% accuracy in narcolepsy diagnosis and 100% accuracy in identifying MDD, highlighting its versatility for downstream applications. By unifying robust cross-domain generalization with clinical adaptability, LPSGM bridges the gap between automated sleep staging and real-world deployment, enabling scalable, data-efficient analysis of sleep physiology and its neuropsychiatric correlates.

Fig. 1: Overview of the LPSGM framework. Panel (a): Data harmonization schematizes the aggregation of 220,500 hours of PSG data from 16 public datasets and 2 independent clinical cohorts, spanning diverse geographic populations and recording protocols. Panel (b): Cross-center generalization outlines the training-evaluation pipeline: LPSGM is pre-trained on multi-center public datasets, validated for cross-domain sleep staging on two unseen private datasets, and fine-tuned for downstream tasks including narcolepsy diagnosis and MDD detection. Panel (c): Analytical validation details the study's three-pronged evaluation: (1) a prospective clinical trial benchmarking LPSGM against expert consensus, (2) interpretability analysis to decode decision-making patterns, and (3) ablation studies

147 quantifying the contribution of key components.

Results

Cross-Center Classification Performance of Sleep Staging

We evaluated LPSGM's cross-center sleep staging performance on the HANG7 and
SYSU datasets against two baselines (Table 1). Baseline 1 (lower bound) involved
direct application of a model trained on one center's data to another without
adaptation, while Baseline 2 (upper bound) used models fully trained on target-center
data via five-fold cross-validation. LPSGM-Small outperformed LPSGM in baseline
comparisons and was selected as the reference baseline. LPSGM achieved
near-upper-bound performance on both datasets. For HANG7, LPSGM reached 85.68%
accuracy, 82.88% macro-F1, and a kappa of 0.8138 (99.6%, 99.9%, and 99.5% of
Baseline 2, respectively). On SYSU, it attained 84.13% accuracy, 77.88% macro-F1,
and 0.7789 kappa (97.1%, 96.7%, and 95.7% of Baseline 2), demonstrating robust
generalization across clinical centers.
161

162 **Table 1:** Comparison of the sleep staging results between LPSGM and baselines on
163 two target private centers.

Center			Acc	MF1	Kappa	Per-class F1				
						W	N1	N2	N3	R
HANG7	Base. 1	LPSGM	0.7757	0.7313	0.7098	0.8420	0.4809	0.7870	0.8085	0.7383
		LPSGM-Small*	0.7840	0.7338	0.7223	0.8657	0.4430	0.7762	0.8176	0.7667
		LPSGM	0.8568	0.8288	0.8138	0.9356	0.6348	0.8455	0.8636	0.8644
	Base. 2	LPSGM	0.8493	0.8180	0.8039	0.9231	0.5996	0.8415	0.8643	0.8612
		LPSGM-Small*	0.8604	0.8300	0.8177	0.9321	0.6344	0.8545	0.8650	0.8641
	Rel. Base. 2		99.6%	99.9%	99.5%	100.4%	100.1%	98.9%	99.8%	100.0%
SYSU	Base. 1	LPSGM	0.7504	0.6821	0.6623	0.6648	0.4154	0.8019	0.7486	0.7497
		LPSGM-Small*	0.7612	0.6866	0.6666	0.6432	0.3808	0.8266	0.7972	0.7851
		LPSGM	0.8413	0.7788	0.7789	0.7888	0.4688	0.8676	0.8703	0.8986
	Base. 2	LPSGM	0.8568	0.7911	0.8012	0.8055	0.4833	0.8795	0.8965	0.8906
		LPSGM-Small*	0.8661	0.8057	0.8138	0.8314	0.5137	0.8862	0.8997	0.8975
	Rel. Base. 2		97.1%	96.7%	95.7%	94.9%	91.3%	97.9%	96.7%	100.1%

a. Base. 1 is trained on one center and directly tested on another without
adaptation, representing the lower bound of performance. Base. 2 is fully
trained on the target center using five-fold cross-validation, serving as the upper
bound.
b. LPSGM-Small is a smaller variant of LPSGM, with one Transformer block (Fig.
5c) instead of four.
c. Rel. Base. 2 measures LPSGM's performance relative to Base. 2, indicating its
generalization capability.
172

Notably, sleep staging performance exhibited variation across subject subgroups (Fig. 2b), suggesting potential demographic- or pathology-dependent effects on model generalizability. LPSGM achieved highest accuracy in healthy cohorts (88.99% on HANG7; 86.15% on SYSU) but declined slightly in populations with sleep or neurological disorders—notably, to 87.11% (hypersomnia) and 82.45% (narcolepsy) on HANG7, and 78.36% (MDD) on SYSU. This may reflect atypical sleep architecture in clinical populations.

Fig. 2: Performance of LPSGM on Sleep Staging. (a) Hypnogram comparison of a full-night PSG recording from the HANG7 dataset. The top panel illustrates sleep stages predicted by LPSGM, while the bottom panel shows the expert-annotated reference hypnogram. (b) Boxplots summarizing distributions of accuracy (Acc), macro-F1 (MF1), and Cohen's κ across subject groups in the HANG7 and SYSU datasets. (c) Trade-off between model performance and inference speed under varying channel configurations (8C, 4C, 2C, and 1C; C = channels) on the HANG7 dataset. The x-axis denotes inference time per full-night recording, and the y-axis reports performance metrics (Acc, MF1, κ). (d) Five-fold cross-validation results on the

HANG7 and SYSU datasets, comparing models trained with and without large-scale
hybrid pre-training. Blue circles denote models trained exclusively on target-center
data (without pre-training), while red squares represent models pre-trained on public
datasets before target-center fine-tuning (with pre-training).

During the inference stage, LPSGM dynamically balances accuracy and
computational efficiency by adjusting input channels without altering the model
structure. Fig. 2c demonstrates the trade-off between performance metrics and
inference time per recording across different EEG channel configurations (8C, 4C, 2C,
1C) obtained from the HANG7 dataset. When using eight channels (8C), LPSGM

achieves the highest accuracy of 85.68%, macro-F1 of 82.88%, and kappa of 81.38% ,

with an inference time of about 4 seconds per recording. As the number of channels
decreases, the inference time reduces while there is a corresponding drop in
performance metrics. When further reducing to two channels (2C), the accuracy is
$84.23\pm0.49\%$, macro-F1 $81.53\pm0.46\%$, kappa $79.57\pm0.61\%$, with the inference time
dropping to about 1 second per recording. Using a single channel (1C), the model's
accuracy drops more significantly to $82.03\pm0.74\%$, macro-F1 to $79.21\pm0.67\%$, and
kappa to $76.76\pm0.90\%$, but the inference time is the fastest at approximately 0.5
seconds per recording.
In addition to cross-center generalization, we investigate the role of large-scale
hybrid pre-training by comparing LPSGM models with and without pre-training
through five-fold cross-validation (Fig.2d). The pre-trained model—initially
developed on 220,500 hours of public, multi-center polysomnography (PSG)
data—demonstrated superior performance following fine-tuning on target-center
datasets. Quantitative analysis revealed consistent improvements across all evaluation
metrics: pre-training enhanced accuracy, macro-F1 score, and Cohen's kappa by
2.04%, 1.91%, and 2.67%, respectively, for the SYSU dataset, while comparable
improvements of 1.27%, 1.57%, and 1.62% were observed for the HANG7 dataset.
These systematic enhancements not only validate the efficacy of the pre-trained
LPSGM framework for domain adaptation but also demonstrate its practical
advantages, including faster convergence and significantly better performance
compared to models trained from scratch.
221

Comparison with State-of-the-Art Sleep Staging Methods
To our knowledge, LPSGM constitutes the largest PSG training framework to date
among existing sleep staging models, a scale we hypothesize underlies its superior
generalization performance. We systematically evaluated LPSGM against
contemporary methods using standardized dataset sizes, categorizing comparison
approaches as either non-transfer-based or transfer-based according to their original
published methodologies. Non-transfer-based methods included: DeepSleepNet[24] (a
classical CNN-BiLSTM network for extracting local features and learning transition
rules), TinySleepNet[25] (a classical model based on CNN and RNN with fewer model

parameters), U-Time[33] (a fully-CNN encoder-decoder architecture for time series
segmentation applied to sleep staging), and AttnSleep[34] (a hybrid architecture
composed of a multi-resolution CNN and multi-head self-attention with causal
convolutions). Transfer-based methods comprised SleepDG[32] (a combination of CNN
and Transformer architectures that incorporates a proposed multi-level feature
alignment technique to extract domain-invariant features) and RobustSleepNet[30]
(channel-adaptive architecture trained on heterogeneous configurations). Notably,
only RobustSleepNet and LPSGM supported flexible channel configurations. To
ensure fair comparison, we standardized input channels to the overlapping C3-M2 and
E1-M2 montages across all methods except RobustSleepNet and LPSGM, which were
evaluated under both 2-channel (2C) and 8-channel (8C) configurations.

We implemented these methods based on their public code and default
hyper-parameters under our cross-center protocol. LPSGM (8C) achieved
state-of-the-art performance across all metrics (Table 2), outperforming both LPSGM
(2C) and comparator methods. This demonstrates the value of multi-channel EEG
integration through complementary signal information. Remarkably, LPSGM (2C)
maintained superior performance over alternatives, highlighting the efficacy of
Transformer-based channel encoding and attention mechanisms compared to
conventional channel-stacking convolutional approaches. In non-transfer methods, we
observed a model size-performance correlation, implying capacity limitations in
large-scale training scenarios. Among transfer-based methods, SleepDG approached
LPSGM (2C) performance, while RobustSleepNet's compact architecture (0.2M
parameters) exhibited dataset-specific learning patterns, evidenced by pronounced
HANG7-SYSU performance discrepancies, suggesting constrained generalizability.

Table 2: Performance comparison with existing sleep staging methods.

Methods	Model Size	Transfer-based	HANG7			SYSU		
			Acc	MF1	Kappa	Acc	MF1	Kappa
DeepSleepNet	21M	×	0.8223	0.7779	0.7643	0.8053	0.7323	0.7174
TinySleepNet	1.3M	×	0.8132	0.7658	0.7534	0.7795	0.7055	0.6832
U-Time	1.2M	×	0.8061	0.763	0.7439	0.7897	0.7191	0.6998
AttnSleep	0.6M	×	0.7353	0.7079	0.6638	0.7325	0.6644	0.6376
SleepDG	6.5M	√	0.8285	0.7836	0.7725	0.8059	0.7461	0.7331
RobustSleepNet(2C)	0.2M	√	0.7291	0.7087	0.6556	0.8058	0.7397	0.7322
RobustSleepNet(8C)			0.7362	0.714	0.664	0.7942	0.7325	0.7174
LPSGM(2C)	9.9M	√	0.8365	0.8062	0.7865	0.8279	0.7514	0.7525
LPSGM(8C)			**0.8568**	**0.8288**	**0.8138**	**0.8413**	**0.7788**	**0.7789**

a. Model Size indicates the number of trainable parameters in each model,
reported in millions (M).
b. 2C and 8C refer to the number of EEG channels used for model training. 2C
includes the common channels across all datasets, C3-M2 and E1-M2. 8C
consists of the full set of available channels, including C3-M2, C4-M1, F3-M2,
F4-M1, O1-M2, O2-M1, E1-M2, and E2-M1.
c. RobustSleepNet and LPSGM support flexible input configurations, allowing

both 2C and 8C inputs. Other models are restricted to the 2C configuration.
265

Performance of Mental Disorder Diagnosis

Beyond sleep stage classification, we extended LPSGM to two clinical diagnostic
tasks: narcolepsy identification (HANG7 dataset, $n=$ 84) and MDD detection (SYSU
dataset, n = 44). Three fine-tuning strategies—partial (updating only the classifier
while freezing other parameters), full (optimizing the entire model for diagnosis), and
joint (simultaneously optimizing sleep staging and diagnosis)—were systematically
compared against models trained from scratch. Diagnostic outcomes were determined
via subject-level majority voting of sample-wise predictions, with five-fold
cross-validation ensuring strict training-test separation. As shown in Fig. 3, fine-tuned
LPSGM achieved 88.01% accuracy (90% sensitivity, 84.29% specificity) for
narcolepsy detection and 100% accuracy for MDD identification. Joint fine-tuning
yielded superior performance, with considerable improvement over training from
scratch. These results underscore the clinical viability of unified PSG frameworks for
multimodal diagnostics, bridging sleep physiology with neuropsychiatric disorder
detection.

Fig. 3: Performance of fine-tuned LPSGM on narcolepsy diagnosis (left panels: a, c, e)
and MDD detection (right panels: b, d, f). The model was fine-tuned using three
different strategies and compared against models trained from scratch. Partial
fine-tune, where only the classifier is fine-tuned for the disorder diagnosis; full
fine-tune, where the entire model is fine-tuned for disorder diagnosis; and joint

fine-tune, where the entire model is fine-tuned simultaneously for sleep staging and disorder diagnosis. Panels (a) and (b) display classification performance (accuracy, sensitivity, and specificity) evaluated at both sample-wise and subject-wise levels. Panels (c) and (d) present receiver operating characteristic (ROC) curves for sample-wise and subject-wise classification. Panels (e) and (f) illustrate sample-wise predictions of a full-night PSG. The blue line shows hypnograms scored by LPSGM. The red line represents sample-wise disorder diagnosis, where "Yes" denotes samples classified as positive for the disorder, and "No" denotes negative classifications. The subject-wise diagnosis is determined via majority voting.

Prospective Validation of LPSGM for Clinical Sleep Staging

We conducted a prospective validation study at the HANG7 center (protocol: Fig. 1c) to assess the clinical applicability of LPSGM. Three board-certified sleep experts independently scored twenty full-night PSG recordings, randomly selected over a one-month period. LPSGM predictions were generated for the same recordings, with comparative analyses evaluating: 1) Inter-expert variability: Each expert's annotations vs. consensus derived from the other two; 2) Model-expert agreement: LPSGM predictions vs. full expert consensus.

Classification metrics (Table 3) employed probabilistically adjusted accuracy and Cohen's κ (Supplementary Methods). Consensus labels were determined via epoch-wise majority voting, with tied probabilities evenly distributed. LPSGM achieved 89.2% accuracy ($\kappa = 0.845$), closely matching expert consensus (88.7% accuracy, $\kappa = 0.850$). Two-tailed t-tests revealed no significant differences between LPSGM and experts (accuracy: $p = 0.74$; κ: $p = 0.60$). Notably, LPSGM exhibited lower variability (SD: 4.6% accuracy, 6.6% κ) than individual experts (SD: 9.7% accuracy, 10.2% κ), highlighting superior consistency.

Hypnogram metrics (Table 4) quantified sleep architecture through stage transitions, categorized into: 1) Sleep latency: Time to enter specific stages. 2) Sleep duration: Total time per stage. 3) Stage distributions: Proportion relative to total sleep time. Mean absolute error (MAE) was calculated for each scorer against consensus contributors. For model-expert comparisons, MAE reflected LPSGM's deviation from individual experts, while inter-expert MAE captured pairwise differences. Statistical analysis identified significant discrepancies in N2 latency ($p < 0.05$) and N1 duration/distribution ($p < 0.01$), suggesting that while LPSGM robustly captures global sleep architecture, refining transient N1/N2 transition detection could further enhance clinical utility.

Table 3: Comparison of classification metrics between LPSGM and experts.

		Overall	Expert 1	Expert 2	Expert 3
Inter-Expert	Accuracy	88.7±9.7	89.1±10.3	88.5±9.2	88.5±9.4
	Kappa	85.0±10.2	87.2±5.0	83.9±11.7	84.0±12.0
Model vs. Experts	Accuracy (With Expert)	89.2±4.6	88.8±3.7	87.5±8.8	89.1±3.3
	Accuracy (Excluding Expert)	—	88.3±4.8	89.1±3.4	87.4±8.8

| | | | Kappa (With Expert) | 84.5±6.6 | 84.3±5.1 | 82.7±11.0 | 84.4±4.5 |
| | | | Kappa (Excluding Expert) | — | 83.3±6.8 | 84.5±4.6 | 82.4±10.9 |

a. Two-tailed *T*-test results showed no significant difference between LPSGM and experts ($p = 0.74$ for accuracy, $p = 0.60$ for kappa).

b. Consensus was obtained by majority voting; when ties occurred, probabilities were evenly distributed. Accuracy and kappa were computed using an extended probabilistic definition (Supplementary Methods).

c. "Inter-Expert" compares each expert with the consensus of the other two. "Model vs. Experts (With Expert)" compares LPSGM with an individual expert, while "Model vs. Experts (Excluding Expert)" compares LPSGM with the consensus of the other two experts.

Table 4: Mean absolute error (MAE) comparison of hypnogram metrics between LPSGM and experts.

Hypnogram Metrics	*T*-test *($p < 0.05$) **($p < 0.01$)	Model vs. Experts	Inter-Expert Overall	Expert 1	Expert 2	Expert 3
Sleep Latency (min)						
N1	—	0.0±0.0	0.0±0.0	0.0±0.0	0.0±0.0	0.0±0.0
N2	*	13.4±19.6	2.9±5.5	1.8±2.9	3.1±5.8	3.9±8.4
N3	—	22.8±31.2	7.7±14.7	8.7±21.3	6.2±11.6	8.1±12.8
REM	—	16.7±21.1	11.6±18.7	11.5±22.2	9.1±14.1	14.1±22.9
Sleep Duration (min)						
TST	—	14.3±34.8	16.1±35.0	15.2±32.3	10.0±20.9	23.0±52.8
REM	—	8.4±7.1	7.9±9.7	6.9±9.4	8.8±13.7	8.1±9.8
NREM	—	11.2±10.9	13.8±22.4	13.2±17.6	15.6±34.1	12.6±18.0
SWS	—	12.8±11.5	13.8±8.2	10.0±7.8	19.7±12.6	11.8±7.8
Sleep Stages						
W (SPT) Episodes (#)	—	5.0±4.4	4.7±3.2	5.4±4.2	4.0±3.1	4.9±5.3
W (SPT) Duration (min)	—	19.0±36.9	16.1±35.8	15.4±32.8	10.2±21.3	22.6±54.0
R Duration (min)	—	8.4±7.1	7.9±9.7	6.9±9.4	8.8±13.7	8.1±9.8
R TST (%)	—	2.0±1.4	1.8±1.9	2.0±2.5	2.0±2.4	1.5±1.8
N1 Duration (min)	**	22.3±10.6	6.9±4.3	7.9±6.5	7.3±6.9	5.6±4.6
N1 TST (%)	**	6.2±2.8	1.9±1.2	2.2±1.7	1.8±1.9	1.6±1.3
N2 Duration (min)	—	25.9±17.2	17.5±15.0	15.4±12.9	22.7±23.7	14.3±14.0
N2 TST (%)	—	6.7±4.8	4.6±3.4	4.6±5.3	5.6±3.7	3.6±2.9
N3 Duration (min)	—	12.8±11.5	13.8±8.2	10.0±7.8	19.7±12.6	11.8±7.8
N3 TST (%)	—	4.4±3.8	3.7±2.5	3.0±3.1	4.9±3.5	3.4±2.5

a. Bolded text represents hypnogram metric categories. See Supplementary Table 1 for detailed definitions.

b. MAE was computed by averaging the absolute differences between each scorer's results and those of the remaining scorers contributing to the consensus.

c. *T*-test evaluates the statistical significance of differences between MAE of model and experts (overall).

342   d. TST (%) represents the proportion of total sleep time spent in a given stage.
343

Interpretability Analysis of LPSGM

The black-box nature of deep learning models remains a critical barrier to clinical
adoption, where transparency in decision-making is essential. To decode LPSGM's
inference mechanisms, we applied gradient-weighted class activation mapping
(Grad-CAM)[59], a post hoc interpretability method that generates spatial heatmaps
highlighting input regions most salient to model predictions. Analyses focused on the
final convolutional layer of the Epoch Encoder's dual-branch CNN (Fig. 5b), with
activation maps resampled to EEG resolution and aggregated across branches to
visualize attention patterns during sleep staging.
Figure 4 illustrates Grad-CAM results for six representative 30-second EEG epochs.
Panels a–d showcase correct classifications, with attention peaks aligning with
clinical biomarkers per AASM guidelines: (a) Posterior dominant rhythm (PDR) in
occipital channels (>50% epoch coverage), pathognomonic of wakefulness. (b)
Frontal slow-wave activity diagnostic of N3 sleep. (c) Low-amplitude
mixed-frequency (LAMF) EEG with slow eye movements (SEM), indicative of N1
sleep. (d) Rapid eye movements (REMs) confirming REM sleep. In contrast, panels
e–f depict misclassifications where activation patterns diverge from established
biomarkers—either misallocating attention (e.g., transient artifacts) or lacking
discriminative features for ambiguous epochs.
These visualizations provide two key insights into LPSGM's interpretability: (1) the
model successfully attends to clinically relevant EEG features, confirming its
biological plausibility, yet (2) reveals limitations in processing ambiguous or complex
patterns,   suggesting   areas   for   future   improvement.

Fig. 4: Grad-CAM visualizations of LPSGM predictions for sleep staging. The figure presents six 30-second EEG epochs analyzed using Grad-CAM to highlight model-attended regions across eight EEG channels (F3, F4, C3, C4, O1, O2, E1, E2). Panels (a)-(d) depict correctly classified epochs, while panels (e)-(f) show misclassifications. Highlighted regions indicate features the model deemed relevant for classification. Black boxes mark physician-identified features consistent with AASM sleep staging criteria. (a) Posterior dominant rhythm (PDR) in occipital channels (>50% of the epoch), indicative of Wake. (b) Slow wave activity in frontal channels (>20% of the epoch), characteristic of N3. (c) Absence of PDR, low-amplitude mixed-frequency (LAMF) EEG, and slow eye movements (SEM), consistent with N1. (d) Rapid eye movements (REMs), indicative of REM sleep. (e)-(f) Misclassified epochs where model attention

Ablation Study

To validate key architectural decisions in LPSGM, we performed systematic ablation analyses focusing on two core components: channel & temporal encoding approaches, and feature fusion strategies. These innovations, described in detail in the Methods section, are designed to enhance the model's ability to process heterogeneous PSG datasets. We evaluated three encoding variants (no encoding, addition-based encoding, and concatenation-based encoding) alongside two fusion approaches (channel averaging versus CLS token-based fusion). As shown in Table 5, concatenation-based encoding paired with CLS token fusion achieved optimal performance. The baseline (no encoding) exhibited the weakest results, while

addition-based encoding showed partial improvement. This hierarchy underscores the necessity of preserving spatiotemporal information in Transformer architectures. We posit that addition-based encoding underperforms due to dimensional conflation during feature integration, which degrades discriminative signal retention. In contrast, concatenation prevents dimensional overlap, enabling robust representation of heterogeneous inputs. CLS token fusion outperformed channel averaging by replacing static linear aggregation with dynamic, attention-driven weighting. While naive averaging indiscriminately combines features, CLS tokens leverage self-attention to emphasize diagnostically salient patterns, thereby preserving feature distinctiveness while adaptively prioritizing clinically relevant biomarkers.

Table 5: Performance comparison of different channel & temporal encoding and feature fusion methods.

Channel & Temporal Encoding			Feature Fusion		HANG7			SYSU		
None	Add	Concat	Average	CLS	Acc	MF1	Kappa	Acc	MF1	Kappa
		√		√	**0.8568**	**0.8288**	**0.8138**	**0.8413**	**0.7788**	**0.7789**
		√	√		0.8416	0.8128	0.7950	0.8267	0.7572	0.7603
	√			√	0.8373	0.8093	0.7898	0.8252	0.7638	0.7601
√				√	0.8043	0.7655	0.7469	0.8045	0.7048	0.7252

To determine the optimal architecture for clinical deployment, we evaluated LPSGM's performance across varying numbers of Transformer blocks ($N = 1$–6). As shown in Table 6, increasing N yielded divergent outcomes: the HANG7 cohort exhibited consistent performance gains (accuracy: +2.32% from $N = 1$ to $N = 6$), while SYSU showed non-linear improvement, peaking at $N = 5$ (+3.90% vs. $N = 1$). This dataset-specific response suggests differing sensitivities to model complexity, likely arising from variations in data heterogeneity between clinical centers.

Balancing computational efficiency and performance, we selected $N = 4$ as the optimal configuration. This choice retained >99.5% of maximum achievable accuracy while reducing memory demands by 30.8% (9.9M parameters vs. 14.3M for $N = 6$). The diminishing returns beyond $N = 5$ highlight the necessity of architectural parsimony for real-world clinical applications, where resource constraints and deployment scalability are paramount.

Table 6: Performance comparison of different number of Transformer block.

Transformer Block (N)	Model Size	HANG7			SYSU		
		Acc	MF1	Kappa	Acc	MF1	Kappa
1	3.2M	0.8372	0.8078	0.7894	0.8026	0.7348	0.7281
2	5.4M	0.8452	0.8176	0.7997	0.8162	0.7446	0.7467
3	7.6M	0.8504	0.8243	0.8059	0.8206	0.7479	0.7479
4	9.9M	0.8568	0.8288	0.8138	0.8413	0.7788	0.7789

| 5 | 12.1M | 0.8546 | 0.8270 | 0.8114 | **0.8416** | **0.7807** | **0.7807** |
| 6 | 14.3M | **0.8604** | **0.8323** | **0.8188** | 0.8380 | 0.7793 | 0.7761 |

Discussion

LPSGM represents a transformative advance in automated sleep staging and mental disorder diagnosis through PSG. Trained on 220,500 hours of PSG data (24,000 full-night recordings aggregated across 16 public datasets)[6,35–52], LPSGM achieves robust cross-center generalization, matching the performance of models trained exclusively on target-center data. This capability stems from its ability to approximate real-world clinical diversity: multi-center training aggregates heterogeneous sampling distributions arising from variations in population demographics, recording protocols, and annotation criteria. While individual datasets offer limited snapshots of clinical reality, their integration yields a comprehensive approximation of true data distributions, enabling near-optimal performance (99.6% and 97.1% of center-specific accuracy on independent HANG7 and SYSU datasets, respectively). These results highlight coordinated multi-institutional data sharing as a critical pathway to enhance robustness and accelerate clinical adoption of automated sleep staging technologies.

LPSGM's dynamic channel adaptability addresses the inherent heterogeneity of PSG protocols across clinical environments, enabling scalable sleep assessment tailored to diverse diagnostic needs. In specialized sleep laboratories, the model maximizes precision by leveraging multi-channel EEG configurations to detect subtle neurological or psychiatric abnormalities. Conversely, in resource-constrained settings—such as primary care clinics or home-based monitoring—LPSGM maintains reliability even with reduced channel setups, facilitating accessible preliminary assessments and longitudinal compliance. This flexibility bridges the gap between high-resolution diagnostics and real-world practicality while establishing a foundation for future integration of multimodal physiological signals (e.g., ECG, respiratory metrics), which could refine diagnostic accuracy and enhance pathophysiological insights into sleep disorders.

Interpretability remains foundational to deploying deep learning models in clinical workflows[60–62]. Grad-CAM[59] analyses reveal that LPSGM prioritizes EEG features aligned with clinical biomarkers during sleep staging—for example, posterior dominant rhythms (PDR) for wakefulness and slow-wave activity for N3 sleep. This congruence with expert-defined criteria (AASM guidelines[5]) fosters trust in LPSGM's decision-making, as visualized in attention maps from the final convolutional layer of the Epoch Encoder (Fig. 5b). However, misclassifications correlate with divergent attention patterns, such as transient artifact focus or ambiguous EEG signatures (e.g., N1/N2 transitions). These cases highlight opportunities to refine temporal context modeling and artifact resilience. Future iterations could integrate clinician feedback loops during training and embed real-time saliency overlays into user interfaces, enabling practitioners to validate model attention against clinical intuition[63,64]. Such transparency enhancements are critical for adoption in routine workflows, bridging

the gap between algorithmic outputs and actionable clinical insights.

Sleep and mental health are bidirectionally linked[65–68] through neurochemical and
circadian pathways—disrupted sleep exacerbates psychiatric symptoms (e.g.,
depression, anxiety) by impairing emotional regulation, while mental disorders often
dysregulate sleep architecture, perpetuating a harmful cycle. Notably, our LPSGM
demonstrates promising potential for identifying neuropsychiatric disorders through
PSG, achieving 88.01% accuracy in narcolepsy detection and 100% accuracy in MDD
identification when fine-tuned for diagnostic tasks. These results suggest that
sleep-related physiological features may encode biomarkers for psychiatric conditions,
with joint optimization of sleep staging and diagnosis implying shared latent
representations between sleep architecture and symptom profiles. However, these
findings require cautious interpretation. Limited sample sizes ($n = 84$ for
narcolepsy; $n = 44$ for MDD) and absence of direct comparisons to gold-standard
clinical diagnostics necessitate validation in larger, diverse cohorts. Although the
perfect MDD classification is provocative, replication across populations and clinical
workflows is critical to confirm generalizability.

While LPSGM demonstrates promising performance, several limitations merit
consideration. First, hypnogram analysis revealed opportunities for refinement:
transient N1/N2 transitions—critical for assessing sleep fragmentation—were less
reliably detected by LPSGM compared to expert consensus. Future iterations could
prioritize temporal context modeling (e.g., attention to stage progression patterns) to
improve resolution of these clinically salient dynamics. Second, while LPSGM
achieves strong performance with multi-channel configurations, accuracy drops in
single-channel setups—a critical barrier for home or resource-limited applications.
Future work should prioritize optimizing feature extraction algorithms for
minimal-channel configurations to enhance accessibility. Furthermore, to advance
clinical utility, subsequent studies could extend LPSGM's scope to other disorders
such as sleep apnea and anxiety disorders, while integrating multimodal signals (e.g.,
chin electromyography, heart rate variability) to disentangle comorbidities and refine
diagnostic specificity. Finally, adaptation for wearable devices could facilitate broader
access to PSG-based monitoring, enabling scalable, real-world at-home sleep
assessments that bridge diagnostic gaps in underserved populations.

In conclusion, this work presents LPSGM as a unified, scalable framework for
automated PSG analysis, combining robust cross-domain sleep staging with a novel
extension to neuropsychiatric disorder diagnosis. By harmonizing large-scale
multi-center PSG data and enabling adaptive channel configurations, the model
bridges critical gaps between technical innovation and clinical applicability. To
facilitate further research and clinical translation, we release both the source code and
pre-trained models, offering the scientific community a foundation for advancing
generalizable, clinically adaptable PSG technologies.

Methods

Overview

LPSGM operates as a sequence-to-sequence model for automatic sleep staging using multichannel PSG signals (Fig. 5a). The architecture comprises three core components: an Epoch Encoder that extracts local intra-epoch features, a Sequence Encoder that models global inter-epoch dependencies via self-attention mechanisms, and a Classifier that assigns sleep stages to sequential 30-second PSG epochs.

Fig. 5: Overall architecture of LPSGM. (a) LPSGM consists of an Epoch Encoder, Sequence Encoder, and Classifier, designed for both sleep staging and disorder diagnosis. (b) The Epoch Encoder employs a dual-branch CNN to extract local intra-epoch features from each 30-second PSG segment, using small and large convolutional filters to capture high- and low-frequency EEG features, respectively. (c) The Sequence Encoder consists of a series of Transformer blocks to capture temporal dependencies across epochs in the sleep sequence. Each Transformer block consists of multi-head self-attention (MSA), feed-forward networks (FFN), and layer

517 normalization (LN). (d) Padding and masking strategy implemented to handle
518 samples with varying numbers of EEG channels, ensuring compatibility across
519 different PSG datasets.

Epoch Segmentation

To address heterogeneous channel configurations, PSG signals are segmented into
30-second epochs. For a multi-channel PSG sequence $x_i = \{x_i^1, x_i^2, \ldots, x_i^L\}$
containing L epochs, each epoch $x_i^l \in \mathbb{R}^{C_i \times n}$ comprises C_i channels and
$n = 30 \times f_s$ samples. Segmentation is performed across temporal and channel
dimensions, yielding $L \times C_i$ single-channel segments $x_i^{l,c} \in R^n$. This standardization
enables consistent input formatting for downstream encoding and classification.

Epoch Encoder

Each single-channel segment $x_i^{l,c} \in \mathbb{R}^n$ is processed by a dual-branch
convolutional neural network (CNN) inspired by DeepSleepNet[24]. The two branches
employ small and large filters to capture high- and low-frequency features,
respectively. Each branch consists of four convolutional layers (performing 1D
convolution, batch normalization and ReLU activation sequentially), two max pooling
layers for downsampling, and a global average pooling layer. Outputs from both
branches are concatenated along the feature dimension, resulting in a 512-dimensional
feature $e_i^{l,c} \in \mathbb{R}^d$ ($d = 512$). Details on the filter sizes, number of filters, stride sizes,
and pooling sizes are provided in Fig. 5b.

Channel & Temporal Encoding

Unlike recurrent neural networks (RNNs) that process sequences sequentially,
Transformer architectures lack inherent positional encoding mechanisms for capturing
temporal or channel-specific information. To address this, we introduce channel and
temporal embeddings inspired by LaBraM[58], but replace additive fusion with
concatenation to preserve dimensional distinctiveness (Fig. 5c).
Specifically, we maintain two embedding sets: a channel embedding set $CE = $
$\{ce_1, ce_2, \ldots, ce_{|C|}\}$ and a temporal embedding set $TE = \{te_1, te_2, \ldots, te_L\}$. Let d_{ce}
and d_{te} denote the dimension of the embedding vectors in the CE and TE,
respectively. For each feature vector $e_i^{l,c}$ from epoch encoder, we concatenate its
corresponding channel and temporal embeddings based on its channel c and
temporal position l within the sequence. This results in an embedded feature vector
$\widetilde{e_i^{l,c}} \in \mathbb{R}^{d+d_{ce}+d_{te}}$, described by the following equation:

$$\widetilde{e_i^{l,c}} = e_i^{l,c} \oplus ce_c \oplus te_l, \qquad c = 1,2,\dots,|C|; \quad l = 1,2,\dots,L \#(1)$$

where $\oplus$ denotes the concatenation operation along the feature dimension, $e_i^{l,c}$ is the original feature vector from the epoch encoder, ce_c is the channel embedding from the channel embedding list CE, and te_l is the temporal embedding from the temporal embedding list TE. The channel and temporal embedding list CE and TE are learnable parameters of the model, optimized during the training process.

Padding & Masking

In cross-dataset hybrid training, where input sequences maintain a fixed temporal length (L epochs) but exhibit variability in channel counts (C_i), we address hardware limitations in batch processing through a padding and masking strategy adapted from natural language processing (NLP). Following segmentation and encoding, feature sequences of variable length $L \times C_i$ are standardized by unfolding each batch of B sequences into $C_i \times T_i$ matrices ($T_i = L$, fixed to 10-minute epochs). These matrices are padded with zero vectors to a uniform dimension of $C_{max} \times T_{max}$, where C_{max} and T_{max} are the maximum number of channels and temporal length within the batch.

A binary mask $M \in \{0,1\}^{B \times (C_{max} \times T_{max})}$ is generated to distinguish valid data from padding:

$$M_{i,j} = \begin{cases} 1, & j > C_i \times T_i \\ 0, & j \le C_i \times T_i \end{cases} \#(2)$$

where $M_{ij} = 1$ indicates that the j-th element of the i-th sequence is padding while $M_{ij} = 0$ indicates valid data. The mask serves dual roles: suppressing padded positions during Transformer self-attention computations to prevent spurious feature interactions, and isolating loss calculations exclusively to valid data points during backpropagation. By enforcing $T_i = L$, we ensure temporal consistency across sequences while enabling efficient batch training.

Insertion of CLS token

To generate unified representations for variable-length sequences, we introduce the classification (CLS) token, a technique commonly used in Transformer-based architectures. Specifically, L learnable CLS tokens are prepended to each feature sequence $\widetilde{e}_i$. These tokens share the dimensionality of the encoded features $(d + d_{ce} + d_{te})$, thereby extending the sequence to $\widetilde{e}_i^{'}$ with a length of $L \times (C_i + 1)$. The CLS tokens are initialized randomly and optimized during training to capture global sequence characteristics.

Sequence Encoder

The sequence encoder processes the padded and masked feature sequences (including CLS tokens) to extract global temporal dependencies from multi-channel, multi-epoch sleep data. Built on the Transformer architecture, it comprises N identical Transformer blocks, each containing a multi-head self-attention (MSA) layer

585 and a feed-forward network (FFN), interleaved with layer normalization (LN).

586 Let E_0 denote the input feature sequence and E_{out} the output sequence. The
587 encoding process for each Transformer block (indexed $\ell = 1, ..., N$) is defined as:

$$E_{\ell}^{'} = \text{MSA}\big(\text{LN}(E_{\ell-1})\big) + E_{\ell-1}, \quad \ell = 1, ..., N \#(3)$$

$$E_{\ell} = \text{FFN}\left(\text{LN}\left(E_{\ell}^{'} \right) \right) + E_{\ell}^{'}, \quad \ell = 1, ..., N \#(4)$$

588 The final output is computed as:

$$E_{out} = \text{LN}(E_N) \#(5)$$

589 The sequence retains its original dimensions through this process. To generate
590 classification features E_{cls}, the first L elements of E_{out} (corresponding to CLS
591 tokens) are extracted:

$$E_{cls} = E_{out}[0:L] \#(6)$$

Classifier

Two classifiers are used: one for sleep staging and another for disease diagnosis.
Each classifier consists of a fully connected layer with a softmax function. The sleep
staging classifier is a five-class classifier responsible for assigning each epoch to one
of the five sleep stages. It takes E_{cls} as input and outputs the probabilities for the five
sleep stages corresponding to each of the L epochs. The disease diagnosis classifier
is a binary classifier designed to predict the presence or absence of a specific disorder.
This classifier takes the average feature vector of the sequence, E_{cls}, computed by
averaging the features across the L epochs, as input, and outputs the probability
indicating the likelihood of the presence or absence of the disorder.

Hybrid Training and Cross-Center Testing on Sleep Staging Task

We conducted hybrid training on source domain consisting of 16 public datasets
and evaluate the performance of our approach on 2 target domain datasets. We create
a validation set by stratified random sampling of 10% from each public dataset. The
model is evaluated on this validation set after every epoch, and the best performing
model parameters are saved. The length of the sleep sequence L is set to 20, meaning
that the context length of the considered sequence is 10 minutes. The feature
dimension d is set to 512. The dimension of channel encoding d_{ce} and temporal
encoding d_{te} are set to 32 and 64, respectively. The number of Transformer Block is
set to 4, the number of heads h is 8, and the dimension of feed-forward network is
608.

We use the weighted cross-entropy (WCE) function as the loss function for the
sleep staging task:

$$\mathcal{L}_{classify} = -\frac{1}{N} \sum_{i=1}^{N} \sum_{k=1}^{K} w_k \cdot y_i^k \log \hat{y}_i^k \#(7)$$

where y_i^k denotes the probability that x_i actually belongs to the k-th stage, and $\hat{y}_i^k$
denotes the probability that x_i is predicted to the k-th stage. The category weight
w_k is set to the normalized value of the reciprocal of the k-th stage proportion in the

training set.

We implemented LPSGM based on PyTorch. The model is trained using Adam
optimizer with default setting, the weight decay is set to 1e-3 and the mini-batch size
is set to 512. The training epochs is 35, with a warm-up phase of 15 epochs. The
learning rate undergoes linear increase from 0 to 1e-4 during the warm-up phase,
followed by decay according to a cosine annealing strategy to 1e-6. During training,
we employed a data augmentation technique that randomly drops channels to prevent
the model from over-relying on specific channels or too many channels. Specifically,
each channel in a sample x_i with C_i channels has a 50% chance of being dropped.
The model was trained on one machine with Intel Xeon Gold 6330 CPU and two
NVIDIA A800 GPUs.

Fine-tuning for Disorder Diagnosis Tasks

In addition to the sleep staging task, we further fine-tune the model for mental
disorder diagnosis tasks, using the cross-entropy loss function. We investigate three
fine-tuning paradigms: partial fine-tuning, full fine-tuning, and joint fine-tuning, and
compare them against a model trained from scratch. Partial fine-tuning: In this
paradigm, we freeze all modules of the pre-trained sleep staging model except for the
classifier, which is modified and fine-tuned specifically for the disorder diagnosis task.
Full fine-tuning: In this paradigm, both the classifier and the entire model are
fine-tuned for the disorder diagnosis task. Joint fine-tuning: This paradigm
simultaneously fine-tunes both the sleep staging task and the disorder diagnosis task
in parallel.

The training procedure for all fine-tuning paradigms consists of 10 epochs, whereas
training from scratch involves 30 epochs. In all four experimental paradigms, the
initial learning rate lr_0 for the disorder diagnosis classifier is set to 1e-3, while for all
other modules, the initial learning rate is set to 1e-5. The AdamW optimizer is used,
and the learning rate is adjusted using a cosine annealing strategy.

Data Availability

See Supplementary Methods and Supplementary Tables 2 and 3 for a detailed
description of the data.

The APPLES[35,36], STAGES[35], ABC[35,37], HOMEPAP[35,52], SHHS[35,38], PATS[35,39,40],
CHAT[35,41], CCSHS[35,42], CFS[35,43], MNC[6,35], NCHSDB[35,44] and MROS[35,45] datasets are
provided by the National Sleep Research Resource with appropriate deidentification.
Permission and access for these datasets can be obtained via the online portal:
https://www.sleepdata.org. The SVUH[46], HMC[47], P2018[48] and CAP[49] datasets are
available from PhysioNet at https://physionet.org/content/ucddb/1.0.0/,
https://physionet.org/content/hmc-sleep-staging/1.1/,
https://physionet.org/content/challenge-2018/1.0.0/   and
https://physionet.org/content/capslpdb/1.0.0/. The ISRUC[50] dataset can be accessed
from https://sleeptight.isr.uc.pt/. DOD-H and DOD-O datasets[51] can be downloaded at
https://github.com/Dreem-Organization/dreem-learning-open. Access to the HANG7
and SYSU dataset[69] is governed by data-use agreements, and it is therefore not

publicly available.

Code Availability

662　The source code and pre-trained models of our proposed LPSGM is made available

663　in GitHub: https://github.com/Deng-GuiFeng/LPSGM.

References

1.　Maquet, P. The role of sleep in learning and memory. *Science* **294**, 1048–1052 (2001).

2.　Irwin, M. R. Why sleep is important for health: a psychoneuroimmunology perspective.
Annu. Rev. Psychol. **66**, 143–172 (2015).

3.　Benjafield, A. V. *et al.* Estimation of the global prevalence and burden of obstructive sleep
apnoea: a literature-based analysis. *Lancet Respir. Med.* **7**, 687–698 (2019).

4.　Morin, C. M. & Jarrin, D. C. Epidemiology of insomnia: prevalence, course, risk factors,
and public health burden. *Sleep Med. Clin.* **17**, 173–191 (2022).

5.　American Academy of Sleep Medicine. *AASM Manual for the Scoring of Sleep and*
Associated Events: Rules, Terminology and Technical Specifications. 3rd edn (American
Academy of Sleep Medicine, Darien, IL, 2023).

6.　Stephansen, J. B. *et al.* Neural network analysis of sleep stages enables efficient diagnosis of
narcolepsy. *Nat. Commun.* **9**, 5229 (2018).

7.　Quinnell, T. G. & Smith, I. E. Narcolepsy, idiopathic hypersomnolence and related
conditions. *Clin. Med.* **11**, 282 (2011).

8.　Lopez, J. *et al.* Reduced sleep spindle activity in early-onset and elevated risk for depression.
J. Am. Acad. Child Adolesc. Psychiatry **49**, 934–943 (2010).

9.　Riemann, D., Krone, L. B., Wulff, K. & Nissen, C. Sleep, insomnia, and depression.
Neuropsychopharmacol. **45**, 74–89 (2020).

10.　Kupfer, D. J. REM latency: a psychobiologic marker for primary depressive disease. *Biol.*
Psychiatry **11**, 159–174 (1976).

11.　Kupfer, D. & Foster, F. G. Interval between onset of sleep and rapid-eye-movement sleep as
an indicator of depression. *Lancet* **300**, 684–686 (1972).

12.　Rosenberg, R. S. & Van Hout, S. The American Academy of Sleep Medicine Inter-scorer
Reliability Program: Sleep Stage Scoring. *Journal of Clinical Sleep Medicine* **09**, 81–87
(2013).

13.　Zhang, X. *et al.* Process and outcome for international reliability in sleep scoring. *Sleep*
Breath **19**, 191–195 (2015).

14.　Danker-Hopfe, H. *et al.* Interrater reliability for sleep scoring according to the Rechtschaffen
& Kales and the new AASM standard. *J. Sleep Res.* **18**, 74–84 (2009).

15.　MacLean, A. W., Lue, F. & Moldofsky, H. The reliability of visual scoring of alpha EEG
activity during sleep. *Sleep* **18**, 565–569 (1995).

16.　Kim, Y. D. *et al.* Agreement of visual scoring of sleep stages among many laboratories in
Japan: effect of a supplementary definition of slow wave on scoring of slow wave
sleep. *Psychiatry Clin. Neurosci.* **47**, 91–97 (1993).

17.　Hassan, A. R. & Bhuiyan, M. I. H. Automatic sleep stage classification. *In 2015 2nd Int.*
Conf. on Electr. Inf. Commun. Tech. (EICT) **211–216** (IEEE, 2015).

18. Rahman, M. A. *et al.* Optimization of sleep stage classification using single-channel EEG
signals. *In 2019 4th Int. Conf. on Electr. Inf. Commun. Tech. (EICT)* **1–6** (IEEE, 2019).

19. Hassan, A. R. & Bhuiyan, M. I. H. A decision support system for automatic sleep staging
from EEG signals using tunable Q-factor wavelet transform and spectral features. *J.*
Neurosci. Methods **271**, 107–118 (2016).

20. Fraiwan, L., Lweesy, K., Khasawneh, N., Wenz, H. & Dickhaus, H. Automated sleep stage
identification system based on time–frequency analysis of a single EEG channel and random
forest classifier. *Comput. Meth. Programs Biomed.* **108**, 10–19 (2012).

21. Şen, B., Peker, M., Çavuşoğlu, A. & Çelebi, F. V. A comparative study on classification of
sleep stage based on EEG signals using feature selection and classification algorithms. *J.*
Med. Syst. **38**, 1–21 (2014).

22. Zhao, S. *et al.* Evaluation of a single-channel EEG-based sleep staging algorithm. *Int. J.*
Environ. Res. Public Health **19**, 2845 (2022).

23. Touil, M., Bahatti, L. & El Magri, A. Sleep's depth detection using electroencephalogram
signal processing and neural network classification. *J. Med. Artif. Intell.* **5**, 9 (2022).

24. Supratak, A., Dong, H., Wu, C. & Guo, Y. DeepSleepNet: a model for automatic sleep stage
scoring based on raw single-channel EEG. *IEEE Trans. Neural Syst. Rehabil. Eng.* **25**,
1998–2008 (2017).

25. Supratak, A. & Guo, Y. TinySleepNet: an efficient deep learning model for sleep stage
scoring based on raw single-channel EEG. *In 2020 42nd Annu. Int. Conf. IEEE Eng. Med.*
Biol. Soc. (EMBC) **641–644** (IEEE, 2020).

26. Biswal, S. *et al.* Expert-level sleep scoring with deep neural networks. *J. Am. Med. Inform.*
Assoc. **25**, 1643–1650 (2018).

27. Phan, H. *et al.* XSleepNet: multi-view sequential model for automatic sleep staging. *IEEE*
Trans. Pattern Anal. Mach. Intell. **44**, 5903–5915 (2022).

28. Yoo, C., Lee, H. W. & Kang, J.-W. Transferring structured knowledge in unsupervised
domain adaptation of a sleep staging network. *IEEE J. Biomed. Health Inform.* **26**,
1273–1284 (2022).

29. Fan, J. *et al.* Unsupervised domain adaptation by statistics alignment for deep sleep staging
networks. *IEEE Trans. Neural Syst. Rehabil. Eng.* **30**, 205–216 (2022).

30. Guillot, A. & Thorey, V. RobustSleepNet: transfer learning for automated sleep staging at
scale. *IEEE Trans. Neural Syst. Rehabil. Eng.* **29**, 1441–1451 (2021).

31. Deng, Z. *et al.* Adversarial training helps transfer learning via better representations. *Adv.*
Neural Inf. Process. Syst. **34**, 25179–25191 (2021).

32. Wang, J. *et al.* Generalizable sleep staging via multi-level domain alignment. *Proc. AAAI*
Conf. Artif. Intell. **38**, 265–273 (2024).

33. Perslev, M. *et al.* U-Time: a fully convolutional network for time series segmentation
applied to sleep staging. *Adv. Neural Inf. Process. Syst.* **32**, – (2019).

34. Eldele, E. *et al.* An attention-based deep learning approach for sleep stage classification with
single-channel EEG. *IEEE Trans. Neural Syst. Rehabil. Eng.* **29**, 809–818 (2021).

35. Zhang, G.-Q. *et al.* The National Sleep Research Resource: towards a sleep data commons. *J.*
Am. Med. Inform. Assoc. **25**, 1351–1358 (2018).

36. Quan, S. F. *et al.* The association between obstructive sleep apnea and neurocognitive
performance—The Apnea Positive Pressure Long-term Efficacy Study (APPLES). *Sleep* **34**,

303–314 (2011).

37.   Bakker, J. P. *et al.* Gastric banding surgery versus continuous positive airway pressure for
obstructive sleep apnea: a randomized controlled trial. *Am. J. Respir. Crit. Care Med.* **197**,
1080–1083 (2018).

38.   Quan, S. F. *et al.* The sleep heart health study: design, rationale, and methods. *Sleep* **20**,
1077–1085 (1997).

39.   Wang, R. *et al.* Pediatric Adenotonsillectomy Trial for Snoring (PATS): protocol for a
randomised controlled trial to evaluate the effect of adenotonsillectomy in treating mild
obstructive sleep-disordered breathing. *BMJ Open* **10**, e033889 (2020).

40.   Redline, S. *et al.* Adenotonsillectomy for snoring and mild sleep apnea in children: a
randomized clinical trial. *JAMA* **330**, 2084–2095 (2023).

41.   Marcus, C. L. *et al.* A randomized trial of adenotonsillectomy for childhood sleep apnea. *N.*
Engl. J. Med. **368**, 2366–2376 (2013).

42.   Rosen, C. L. *et al.* Prevalence and risk factors for sleep-disordered breathing in 8-to
11-year-old children: association with race and prematurity. *J. Pediatr.* **142**, 383–389 (2003).

43.   Redline, S. *et al.* The familial aggregation of obstructive sleep apnea. *Am. J. Respir. Crit.*
Care Med. **151**, 682–687 (1995)..

44.   Lee, H. *et al.* A large collection of real-world pediatric sleep studies. *Sci. Data* **9**, 421
(2022).

45.   Blackwell, T. *et al.* Associations between sleep architecture and sleep-disordered breathing
and cognition in older community-dwelling men: the osteoporotic fractures in men sleep
study. *J. Am. Geriatr. Soc.* **59**, 2217–2225 (2011).

46.   Goldberger, A. L. *et al.* PhysioBank, PhysioToolkit, and PhysioNet: components of a new
research resource for complex physiologic signals. *Circulation* **101**, e215–e220 (2000).

47.   Alvarez-Estevez, D. & Rijsman, R. M. Haaglanden Medisch Centrum sleep staging database
(version 1.0.1). *PhysioNet* (2021).

48.   Ghassemi, M. *et al.* You snooze, you win: the PhysioNet/Computing in Cardiology
Challenge 2018. *In 2018 Comput. Cardiol. Conf. (CinC)* **45**, 1–4 (2018).

49.   Terzano, M. G. *et al.* Atlas, rules, and recording techniques for the scoring of cyclic
alternating pattern (CAP) in human sleep. *Sleep Med.* **2**, 537–554 (2001).

50.   Khalighi, S. *et al.* ISRUC-Sleep: a comprehensive public dataset for sleep researchers.
Comput. Meth. Programs Biomed. **124**, 180–192 (2016).

51.   Guillot, A. *et al.* Dreem open datasets: multi-scored sleep datasets to compare human and
automated sleep staging. *IEEE Trans. Neural Syst. Rehabil. Eng.* **28**, 1955–1965 (2020).

52.   Rosen, C. L. *et al.* A multisite randomized trial of portable sleep studies and positive airway
pressure autotitration versus laboratory-based polysomnography for the diagnosis and
treatment of obstructive sleep apnea: the HomePAP study. *Sleep* **35**, 757–767 (2012).

53.   Achiam, J. *et al.* GPT-4 technical report. Preprint at
https://doi.org/10.48550/arXiv.2303.08774 (2023).

54.   Lewis, M. *et al.* BART: Denoising sequence-to-sequence pre-training for natural language
generation, translation, and comprehension. *In Proc. 58th Annu. Meet. Assoc. Comput.*
Linguist. **7871–7880** (ACL, 2020).

55.   Devlin, J., Chang, M.-W., Lee, K. & Toutanova, K. BERT: Pre-training of Deep
Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019*

Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers) (eds Burstein, J., Doran, C. & Solorio, T.) 4171–4186 (Association for Computational Linguistics, Minneapolis, Minnesota, 2019).

56. Wang, J., Zhao, S., Luo, Z., Zhou, Y., Jiang, H., Li, S., Li, T. & Pan, G. CBraMod: A Criss–Cross Brain Foundation Model for EEG Decoding. In *Proceedings of the 13th International Conference on Learning Representations* (2025).

57. Yi, K. *et al.* Learning topology-agnostic EEG representations with geometry-aware modeling. *Adv. Neural Inf. Process. Syst.* **36** (2024).

58. Jiang, W.-B., Zhao, L.-M. & Lu, B.-L. Large brain model for learning generic representations with tremendous EEG data in BCI. In *The Twelfth International Conference on Learning Representations* (2024).

59. Selvaraju, R. R. *et al.* Grad-CAM: visual explanations from deep networks via gradient-based localization. *In 2017 IEEE Int. Conf. Computer Vision (ICCV)* **618–626** (IEEE, 2017).

60. Esser-Skala, W. & Fortelny, N. Reliable interpretability of biology-inspired deep neural networks. *NPJ Syst. Biol. Appl.* **9**, 50 (2023).

61. Sapoval, N. et al. Current progress and open challenges for applying deep learning across the biosciences. *Nat. Commun.* **13**, 1728 (2022).

62. Mamede, S. & Schmidt, H. G. Making large language models into reliable physician assistants. *Nat. Med.* **31**, 1071–1072 (2025).

63. Nasarian, E., Alizadehsani, R., Acharya, U. R. & Tsui, K.-L. Designing interpretable ML system to enhance trust in healthcare: a systematic review to proposed responsible clinician–AI–collaboration framework. *Info. Fusion* **108**, 102412 (2024).

64. Phan, H. *et al.* SleepTransformer: Automatic sleep staging with interpretability and uncertainty quantification. *IEEE Trans. Biomed. Eng.* **69**, 2456–2467 (2022).

65. Alvaro, P. K., Roberts, R. M. & Harris, J. K. A systematic review assessing bidirectionality between sleep disturbances, anxiety, and depression. *Sleep* **36**, 1059–1068 (2013)

66. Scott, A. J., Webb, T. L., Martyn-St James, M., Rowse, G. & Weich, S. Improving sleep quality leads to better mental health: a meta-analysis of randomised controlled trials. *Sleep Med. Rev.* **60**, 101556 (2021).

67. Tahmasian, M. *et al.* The interrelation of sleep and mental and physical health is anchored in grey-matter neuroanatomy and under genetic control. *Commun. Biol.* **3**, 171 (2020).

68. Meyer, N. *et al.* The sleep-circadian interface: a window into mental disorders. *Proc. Natl. Acad. Sci. U.S.A.* **121**, e2214756121 (2024).

69. Wei, Y., Zhu, Y., Zhou, Y., Yu, X. & Luo, Y. Automatic sleep staging based on contextual scalograms and attention convolution neural network using single-channel EEG. *IEEE J. Biomed. Health Inform.* **28**, 801–811 (2024).

Acknowledgements

This work was supported by STI2030-Major Projects (2022ZD0212400), National Natural Science Foundation of China (82371453), Key R&D Program of Zhejiang （2024C03006 ,2024C04024, 2024SSYS0017), Non-profit Central Research Institute Fund of Chinese Academy of Medical Sciences (2023-PT310-01) and Fundamental

Author Contributions

G.D. and H.J. designed the methodology. J.Z. and Y.Z provided critical insights into
the methodological design. G.D. conducted the experiments and performed the
primary analysis. G.D. and M.N. carried out the interpretability analysis. S.R., J.X.,
S.Z., and G.P. contributed to the analysis and interpretation of results. M.N., and Z.Y.
collected, organized, and preprocessed the HANG7 dataset. Y.L. collected, organized,
and preprocessed the SYSU dataset. W.L., X.L., W.D., W.G., and T.L. led the
prospective study.

Competing Interests

The authors declare no competing interests.

Additional Information