Quantifying Device Type and Handedness Biases in a Remote Parkinson's Disease AI-Powered Assessment

Zerin Nasrin Tumpa[1], Md Rahat Shahriar Zawad[1], Lydia Sollis[1], Shubham Parab[2], Irene Y. Chen[3,4], Peter Washington[5,*]

[1]Department of Information and Computer Sciences, University of Hawaii at Manoa

[2]Department of Computer Science, New York University

[3]Computational Precision Health, University of California – Berkeley and University of California - San Francisco

[4]Department of Electrical Engineering and Computer Science, University of California – Berkeley

[5]Division of Clinical Informatics and Digital Transformation, Department of Medicine, University of California - San Francisco

*Correspondence: peter.washington@ucsf.edu

Abstract

Early detection of Parkinson's Disease (PD) can enable early access to care, improving patient outcomes. We investigate the use of machine learning to predict PD using data recorded from a web application measuring structured mouse and keypress data through tests assessing finger and hand movement patterns. We evaluate the impact of demographic bias and bias related to device type and handedness, which are particularly relevant to our application. We collected data from 251 participants (99 PD, 152 non-PD). Using a random forest model, we observed an 84% F1 score, 86% sensitivity, and 92% specificity. When examining only F1-score differences across groups, no significant bias appears. However, conducting a more in-depth analysis using algorithmic fairness metrics uncovers bias regarding the positive prediction and error rates. In particular, we found that gender and ethnicity have no statistically significant impact on receiving a PD prediction. However, we observe biases regarding device type and dominant hand in terms of receiving a PD diagnosis, as evidenced by disparate impact and equalized odds fairness metrics. This work demonstrates that remote digital health diagnostics using consumer devices like desktops or laptops can exhibit nontraditional yet significant biases concerning understudied factors in algorithmic fairness, such as device type and handedness.

Introduction

PD is the fastest-growing neurological disorder in the world. It is projected that the number of individuals aged 50 years or older with PD in the USA will rise by 128 percent from about 340,000 in 2005 to around 610,000 by 2030[2]. Numerous studies have emphasized the possibility of diagnosing PD through motor patterns such as verbal fluency[3], voice signals-voice disorders[4,5], speech[6], handwritten trace[7], and gait patterns[8]. Finger tapping is one of the most reliable tests for motor performance [9]. The necessity for lab equipment and specialist supervision has made the detection process more complex and less cost-effective[10]. We, therefore, aim to develop a flexible

and cost-effective method for detecting PD using machine learning applied to mouse/trackpad and keyboard data.

We collected data from participants who engaged in structured interactive tasks on a remotely accessible web application that we created. Each assessment consisted of a series of mouse tracing and keyboard pressing tasks. For the key press tasks, metrics such as response time, accuracy, and accidental key presses from unintended movements were recorded. For the mouse trace tasks, where participants were asked to trace straight and curved paths displayed on-screen using a trackpad or mouse, we measured the stability and precision of two-dimensional hand movements, providing insights into motor control and coordination of the lower arm.

While prior studies have explored remote digital health assessments for PD, our study delves into issues of algorithmic fairness in remote PD assessments in particular and consumer digital health informatics more broadly by exploring the performance of machine learning models across diverse demographic groups in a web application for remote PD assessment. By examining factors such as gender, race, device type, and dominant hand using multiple fairness metrics, we aim to understand and highlight potential biases in the system's predictions. We note in particular that an exploration of algorithmic fairness concerning device type and dominant hand are understudied aspects of consumer digital health informatics.

Results

Novel Remotely Curated Dataset

We recruited 251 individuals, providing a comprehensive dataset to analyze the effectiveness of our gamified web-based application in detecting PD. Of these participants, 99 were diagnosed with PD, and 152 were non-PD controls (Figure 1a). The gender distribution included 39 females and 212 males.

There was significant underrepresentation of many groups in our dataset, and we sought to study the effect of this imbalance on disparities in performance across groups. Figure 1b depicts gender-based inequality. The majority of participants were White (185). There were 39 Black or African American participants. Smaller groups included 20 American Indian or Alaska Native individuals, 4 Native Hawaiian or other Pacific Islander individuals, and 2 Asian participants. Participants utilized various devices to access the gamified web-based application: 201 used Windows desktops, 41 used Mac desktops, and 8 used Linux desktops (Figure 1c). Seventy-five participants were left-handed, and 176 were right-handed. The device type distribution was roughly similar between White and non-White groups (Figure 1d). The heatmap in Figure 1e shows how individuals are distributed across different racial categories based on their PD status.

The gamified application included seven structured tasks: three involving mouse exercises, three involving keyboard interactions, and one testing working memory. Each task consisted of three levels of increasing difficulty. The mouse-based tasks involved tracing straight lines and spirals, while the keyboard-based tasks included single-letter presses, multiple-letter presses, and randomized sequences, forming a comprehensive set of activities designed to test different motor and cognitive skills. The working memory game assessed cognitive function. From these interactions, we extracted 80 features across five major categories.

Figure 1: **Data distributions before any upsampling.** (a) The dataset is class imbalanced, with approximately 39.4% PD patients and 60.6% non-PD participants. (b) The total number of male participants is much higher than that of

female participants, with differing class balances across gender groups. (c) Most of the participants used a Windows device. Two hundred-one participants used Windows, whereas only 41 users used a Mac, and eight used Linux. (d) Within the White group, Windows is the predominant device type, with 150 users, compared to only 28 users on Mac. Similarly, in the non-White group, Windows usage remains higher, with 45 users, while Mac usage is much lower, at 12 users. This pattern indicates a strong preference for Windows devices across racial groups, although the White group has a significantly larger sample size overall. (e) Of participants with PD, 51 are White, followed by Black or African American, with 33 responses. White participants consist of 134 responses in the non-PD group, with only six responses from Black or African American participants. (f) Distribution of race by disease status, specifically comparing White and Non-White groups.

Model Selection

We first sought to select high-performing models for subsequent analyses. Using manually engineered features, we tested six classical machine-learning models for predicting PD. The dataset was split into 70% training and 30% testing data. Each model was evaluated using 5-fold cross-validation on the training set, and the performance of the models was recorded using the mean F1 score across five folds (Figure 2).

Figure 2: Comparison of classical machine learning models. The results are generated by performing cross-validation on our training data only. We report the mean with standard deviation as error bars across all the folds.

Although all the experimental models exhibited promising performance during this model section stage, the LightGBM classifier outperformed the others by a small margin, achieving a 95.2% F1 score with a 4.19% standard deviation.

The Random Forest, XGBoost, and LightGBM classifiers were selected to test their performance further on held-out test data. The 30% test data were used to make predictions using the three trained models (Table 1, Figure 3).

Table 1: Performance of the top-performing ML models on held-out test data.

	F1 Score	Sensitivity	Specificity
Random Forest	84%	86%	92%
LightGBM	78%	78%	90%
XGBoost	77%	81%	88%

Figure 3: ROC curves and corresponding AUC scores for the random forest, LightGBM, and XGBoost classifiers. During the training phase, the three top-performing models were further tested on the held-out data to report their ROC curve and AUROC scores. The performance differences are minimal when comparing the ROC curves and the area under the curve (AUC). The Random Forest model achieved the highest AUC score of 94%, followed by XGBoost at 93% and LightGBM at 91%.

Model Bias and Fairness

To evaluate bias, we used traditional accuracy metrics like F1-score, sensitivity, specificity, and AUC and fairness-specific metrics such as Disparate Impact, Equal Opportunity, and Equalized Odds. A value of 1 for these fairness metrics indicates perfect fairness, with equal treatment of the

privileged and unprivileged groups. Values less than 1 signify biases against the unprivileged group, while values greater than 1 indicate potential biases favoring the unprivileged group.

We selected male, White, Mac, and right-handed individuals as the privileged groups in the study (Table 2). While the selection of unprivileged groups corresponded to underrepresentation in our dataset, we chose to set Mac users as the privileged group despite underrepresentation due to the homogeneity of Mac devices – a contrast to Windows devices created by a wide range of manufacturers.

Tables 3.1 and 3.2 display the F1-score, sensitivity, specificity, specificity, and AUROC metric differences between groups for four sensitive attributes: gender, race, device type, and dominant hand. Table 3.1 shows these metrics following upsampling by race, while Table 3.2 provides the values before any resampling was applied.

Notably, an unusual result highlighted how underrepresentation can mask underlying biases in machine learning. Before upsampling, the non-White group exhibited higher F1 scores than the White group, which was counter-intuitive given the underrepresentation of non-White data. Closer examination revealed that the "Non-White No Parkinson" group had substantially less data than the "White No Parkinson" group, likely resulting in an inflated F1 score for the non-White group overall. Figure 1f illustrates the distribution of participants by race and disease status, clearly highlighting the underrepresentation of the "Non-White No Parkinson" group. This is a salient example of how the underrepresentation of certain groups in machine-learning datasets can mask underlying biases.

To address this imbalance, we increased the data in the "Non-White No Parkinson" group to bring it closer in size to the White group using resampling with replacement. After race resampling, we observed that the F1 score gap between White and non-White groups significantly narrowed, with no significant differences between the groups after upsampling (Table 5.1). All sensitive categories no longer yielded statistically significant differences in F1 scores (Figure 4).

Most algorithms achieved disparate impact scores somewhat close to 1 for gender and race after race resampling (Table 4.1). However, due to a high standard deviation exceeding 55%, this result does not conclusively indicate fairness or bias towards either group. Such a high standard deviation undermines the reliability of the disparate impact scores, suggesting that while the average score may imply fairness, the variability within the data reveals a more complex distribution. This variability could indicate that certain gender subgroups experience differential outcomes depending on the specific scenario. This analysis suggests that neither gender nor race significantly influences the models' distribution of predictions towards any particular group.

Even after race upsampling, the models exhibit significant bias in other demographic groups, such as device and dominant hand, with disparate impact values ranging from 0.38 to 0.70 and tighter standard deviations than for race or gender. This indicates that the unprivileged groups (Windows, left hand) are 38% to 70% less likely to receive a PD diagnosis from the model than the privileged groups (Mac, right hand).

The models are promising in providing equal opportunity to both groups in each category, ranging from 0.87 to 1.22 but mainly close to 1.00. This result indicates that the models give almost equal optimistic predictions to the privileged and unprivileged groups in Gender, Race, Device, and Dominant Hand. The complex models such as Random Forest, XGBoost, and LightGBM seem to

have more balanced equal opportunity than the other models. The bias becomes more apparent when looking at the equalized odds metric. Surprisingly, all the models exhibited low equalized odds ranging from 0.06 to 0.74. This result indicates that the models show significant bias toward privileged groups, leading to higher misclassification rates for unprivileged groups.

Table 2: Our selection of "Privileged" and "Unprivileged" groups, in terms of the definitions of algorithmic fairness metrics, for Gender, Race, Device, and Dominant Hand categories.

Category	Unprivileged	Privileged
Gender	Female	Male
Race	Non-White (Black, Asian, Native Hawaiian etc.)	White
Device	Windows	Mac
Dominant Hand	Left	Right

Table 3.1: Model performance *after* race upsampling on each group based on four protected attributes: gender, race, device, and dominant hand.

	F1 Score		Sensitivity		Specificity		Precision		AUROC	
Gender	**Male**	**Female**	**Male**	**Female**	**Male**	**Female**	**Male**	**Female**	**Male**	**Female**
Logistic Regression	0.87 (0.03)	0.86 (0.12)	0.92 (0.07)	0.91 (0.13)	0.85 (0.04)	0.77 (0.25)	0.84 (0.02)	0.84 (0.15)	0.93 (0.01)	0.85 (0.16)
Decision Tree	0.91 (0.05)	0.82 (0.12)	0.92 (0.08)	0.93 (0.13)	0.92 (0.03)	0.66 (0.28)	0.91 (0.03)	0.76 (0.16)	0.95 (0.04)	0.78 (0.23)
Support Vector Machine	0.88 (0.03)	0.88 (0.08)	0.89 (0.06)	0.90 (0.09)	0.88 (0.04)	0.82 (0.20)	0.87 (0.04)	0.89 (0.11)	0.93 (0.02)	0.87 (0.13)
Random Forest	0.95 (0.03)	0.92 (0.06)	0.98 (0.03)	1.00 (0.00)	0.93 (0.03)	0.75 (0.28)	0.93 (0.04)	0.87 (0.11)	0.99 (0.02)	0.94 (0.10)
XGBoost	0.89 (0.10)	0.88 (0.10)	0.94 (0.05)	0.95 (0.06)	0.83 (0.23)	0.75 (0.25)	0.86 (0.15)	0.84 (0.14)	0.97 (0.02)	0.92 (0.11)
LightGBM	0.95 (0.06)	0.91 (0.11)	0.98 (0.02)	1.00 (0.00)	0.92 (0.12)	0.77 (0.25)	0.92 (0.11)	0.85 (0.17)	0.99 (0.01)	0.97 (0.03)
Race	**White**	**Non-White**	**White**	**Non-White**	**White**	**Non-White**	**White**	**Non-White**	**White**	**Non-White**
Logistic Regression	0.80 (0.10)	0.90 (0.08)	0.83 (0.08)	0.95 (0.04)	0.48 (0.40)	0.55 (0.45)	0.81 (0.16)	0.88 (0.15)	0.88 (0.02)	0.97 (0.02)
Decision Tree	0.88 (0.11)	0.89 (0.07)	0.92 (0.08)	0.90 (0.10)	0.51 (0.42)	0.56 (0.46)	0.84 (0.14)	0.90 (0.12)	0.89 (0.04)	0.98 (0.03)
Support Vector Machine	0.80 (0.06)	0.89 (0.08)	0.78 (0.05)	0.93 (0.03)	0.51 (0.42)	0.55 (0.45)	0.84 (0.13)	0.87 (0.15)	0.89 (0.02)	0.97 (0.02)
Random Forest	0.92 (0.07)	0.97 (0.02)	0.96 (0.03)	0.99 (0.02)	0.53 (0.43)	0.58 (0.47)	0.88 (0.10)	0.95 (0.04)	0.96 (0.05)	1.00 (0.00)
XGBoost	0.84 (0.17)	0.94 (0.01)	0.94 (0.05)	0.93 (0.06)	0.39 (0.42)	0.58 (0.47)	0.80 (0.23)	0.95 (0.05)	0.95 (0.03)	1.00 (0.00)

	F1 Score		Sensitivity		Specificity		Precision		AUROC	
LightGBM	0.89 (0.14)	1.00 (0.01)	0.96 (0.03)	0.99 (0.02)	0.46 (0.41)	0.60 (0.49)	0.84 (0.19)	1.00 (0.00)	0.95 (0.02)	AUC: 1.00 (0.00)
Device	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**
Logistic Regression	0.87 (0.09)	0.85 (0.07)	0.98 (0.04)	0.88 (0.10)	0.21 (0.25)	0.89 (0.05)	0.79 (0.15)	0.84 (0.07)	0.66 (0.30)	0.95 (0.04)
Decision Tree	0.94 (0.04)	0.86 (0.08)	0.92 (0.07)	0.90 (0.10)	0.80 (0.25)	0.89 (0.04)	0.97 (0.04)	0.83 (0.06)	0.91 (0.10)	0.93 (0.06)

	F1 Score		Sensitivity		Specificity		Precision		AUROC	
Device	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**
Support Vector Machine	0.86 (0.09)	0.85 (0.05)	0.97 (0.06)	0.84 (0.06)	0.19 (0.23)	0.92 (0.03)	0.79 (0.15)	0.87 (0.04)	0.54 (0.26)	0.95 (0.03)
Random Forest	0.99 (0.02)	0.92 (0.05)	1.00 (0.00)	0.97 (0.03)	0.82 (0.20)	0.92 (0.05)	0.98 (0.03)	0.89 (0.06)	1.00 (0.00)	0.98 (0.04)
XGBoost	0.97 (0.02)	0.85 (0.12)	0.98 (0.04)	0.91 (0.07)	0.79 (0.26)	0.84 (0.18)	0.97 (0.04)	0.81 (0.17)	1.00 (0.00)	0.97 (0.03)
LightGBM	0.98 (0.04)	0.92 (0.09)	1.00 (0.00)	0.97 (0.03)	0.80 (0.40)	0.91 (0.11)	0.97 (0.07)	0.89 (0.14)	1.00 (0.00)	0.98 (0.02)
Dominant Hand	**Right**	**Left**	**Right**	**Left**	**Right**	**Left**	**Right**	**Left**	**Right**	**Left**
Logistic Regression	0.89 (0.03)	0.79 (0.13)	0.93 (0.08)	0.88 (0.11)	0.85 (0.02)	0.90 (0.08)	0.86 (0.02)	0.76 (0.21)	0.93 (0.02)	0.96 (0.03)
Decision Tree	0.89 (0.05)	0.88 (0.10)	0.91 (0.08)	0.95 (0.06)	0.87 (0.04)	0.94 (0.06)	0.88 (0.04)	0.84 (0.14)	0.93 (0.05)	0.93 (0.08)
Support Vector Machine	0.89 (0.02)	0.79 (0.14)	0.90 (0.05)	0.88 (0.11)	0.88 (0.03)	0.91 (0.07)	0.88 (0.04)	0.78 (0.22)	0.93 (0.02)	0.96 (0.04)
Random Forest	0.95 (0.03)	0.88 (0.10)	0.98 (0.02)	0.94 (0.05)	0.90 (0.07)	0.96 (0.04)	0.92 (0.04)	0.85 (0.13)	0.99 (0.02)	0.96 (0.07)
XGBoost	0.91 (0.07)	0.79 (0.28)	0.94 (0.05)	0.96 (0.08)	0.84 (0.15)	0.84 (0.25)	0.88 (0.10)	0.76 (0.32)	0.97 (0.02)	0.98 (0.03)
LightGBM	0.95 (0.06)	0.86 (0.21)	0.98 (0.02)	0.98 (0.03)	0.90 (0.13)	0.92 (0.12)	0.93 (0.09)	0.82 (0.27)	0.99 (0.01)	0.99 (0.02)

Table 3.2: Model performance *before* race upsampling on each group based on four protected attributes: gender, race, device, and dominant hand.

	F1 Score		Sensitivity		Specificity		Precision		AUROC	
Gender	**Male**	**Female**	**Male**	**Female**	**Male**	**Female**	**Male**	**Female**	**Male**	**Female**
Logistic Regression	0.87 (0.03)	0.80 (0.18)	0.88 (0.10)	0.90 (0.13)	0.89 (0.06)	0.67 (0.31)	0.87 (0.07)	0.80 (0.25)	0.93 (0.04)	0.76 (0.19)
Decision Tree	0.82 (0.07)	0.67 (0.22)	0.84 (0.12)	0.76 (0.27)	0.84 (0.06)	0.55 (0.28)	0.82 (0.05)	0.69 (0.24)	0.85 (0.07)	0.74 (0.12)
Support Vector Machine	0.87 (0.03)	0.80 (0.18)	0.89 (0.09)	0.85 (0.20)	0.89 (0.05)	0.81 (0.25)	0.87 (0.05)	0.84 (0.24)	0.93 (0.04)	0.78 (0.24)
Random Forest	0.93 (0.03)	0.83 (0.15)	0.95 (0.05)	0.97 (0.06)	0.92 (0.05)	0.62 (0.21)	0.91 (0.06)	0.76 (0.21)	0.97 (0.03)	0.94 (0.08)
XGBoost	0.82 (0.12)	0.79 (0.13)	0.93 (0.07)	0.97 (0.06)	0.69 (0.35)	0.58 (0.13)	0.77 (0.20)	0.69 (0.18)	0.96 (0.03)	0.90 (0.09)
LightGBM	0.88 (0.04)	0.85 (0.11)	0.91 (0.08)	0.93 (0.08)	0.88 (0.08)	0.71 (0.17)	0.87 (0.08)	0.80 (0.16)	0.96 (0.05)	0.92 (0.08)
Race	**White**	**Non-White**	**White**	**Non-White**	**White**	**Non-White**	**White**	**Non-White**	**White**	**Non-White**

	Mac	Windows	Mac	Windows	Mac	Windows	Mac	Windows	Mac	Windows
Logistic Regression	0.71 (0.14)	0.92 (0.06)	0.74 (0.12)	0.97 (0.03)	0.92 (0.07)	0.27 (0.39)	0.77 (0.23)	0.89 (0.11)	0.92 (0.02)	0.88 (0.09)
Decision Tree	0.68 (0.10)	0.86 (0.06)	0.80 (0.15)	0.82 (0.07)	0.82 (0.05)	0.56 (0.33)	0.64 (0.14)	0.91 (0.09)	0.83 (0.08)	0.70 (0.06)
Support Vector Machine	0.73 (0.09)	0.93 (0.05)	0.75 (0.12)	0.97 (0.03)	0.92 (0.04)	0.29 (0.40)	0.77 (0.14)	0.90 (0.09)	0.91 (0.01)	0.87 (0.12)
Random Forest	0.84 (0.11)	0.94 (0.04)	0.93 (0.04)	0.98 (0.03)	0.92 (0.06)	0.44 (0.39)	0.80 (0.18)	0.91 (0.09)	0.97 (0.02)	0.86 (0.11)
XGBoost	0.71 (0.23)	0.89 (0.09)	0.94 (0.07)	0.90 (0.06)	0.71 (0.31)	0.46 (0.44)	0.65 (0.30)	0.90 (0.13)	0.95 (0.02)	0.91 (0.05)
LightGBM	0.79 (0.11)	0.91 (0.06)	0.88 (0.07)	0.95 (0.05)	0.91 (0.07)	0.41 (0.40)	0.78 (0.20)	0.90 (0.11)	0.94 (0.04)	0.94 (0.04)
Device	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**
Logistic Regression	0.95 (0.05)	0.80 (0.05)	1.00 (0.00)	0.81 (0.13)	0.16 (0.20)	0.89 (0.08)	0.91 (0.09)	0.84 (0.10)	0.72 (0.20)	0.90 (0.03)
Decision Tree	0.83 (0.19)	0.75 (0.04)	0.79 (0.26)	0.81 (0.12)	0.43 (0.39)	0.80 (0.07)	0.96 (0.05)	0.72 (0.05)	0.78 (0.05)	0.85 (0.03)

	F1 Score		**Sensitivity**		**Specificity**		**Precision**		**AUROC**	
Device	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**	**Mac**	**Windows**
Support Vector Machine	0.94 (0.04)	0.81 (0.06)	0.98 (0.04)	0.80 (0.13)	0.15 (0.20)	0.91 (0.04)	0.91 (0.08)	0.85 (0.05)	0.51 (0.00)	0.90 (0.04)
Random Forest	0.98 (0.03)	0.87 (0.04)	1.00 (0.00)	0.91 (0.06)	0.43 (0.39)	0.89 (0.08)	0.96 (0.05)	0.86 (0.08)	0.83 (0.09)	0.97 (0.04)
XGBoost	0.96 (0.05)	0.77 (0.12)	0.99 (0.03)	0.92 (0.08)	0.33 (0.42)	0.69 (0.30)	0.94 (0.08)	0.71 (0.20)	0.97 (0.03)	0.94 (0.02)
LightGBM	0.96 (0.03)	0.83 (0.03)	0.96 (0.05)	0.87 (0.08)	0.44 (0.39)	0.87 (0.07)	0.96 (0.05)	0.82 (0.08)	0.92 (0.11)	0.94 (0.04)
Dominant Hand	**Right**	**Left**	**Right**	**Left**	**Right**	**Left**	**Right**	**Left**	**Right**	**Left**
Logistic Regression	0.85 (0.02)	0.88 (0.06)	0.88 (0.10)	0.88 (0.09)	0.80 (0.12)	0.98 (0.03)	0.85 (0.08)	0.92 (0.13)	0.90 (0.03)	0.92 (0.04)
Decision Tree	0.80 (0.05)	0.64 (0.18)	0.81 (0.10)	0.73 (0.20)	0.78 (0.08)	0.85 (0.12)	0.82 (0.05)	0.66 (0.24)	0.82 (0.03)	0.77 (0.09)
Support Vector Machine	0.86 (0.03)	0.86 (0.07)	0.88 (0.10)	0.86 (0.10)	0.84 (0.08)	0.97 (0.04)	0.87 (0.07)	0.88 (0.12)	0.90 (0.03)	0.93 (0.03)
Random Forest	0.91 (0.02)	0.86 (0.14)	0.94 (0.03)	0.92 (0.08)	0.85 (0.09)	0.95 (0.07)	0.89 (0.05)	0.84 (0.20)	0.97 (0.03)	0.97 (0.03)
XGBoost	0.84 (0.07)	0.67 (0.32)	0.92 (0.06)	0.92 (0.10)	0.67 (0.27)	0.72 (0.35)	0.80 (0.13)	0.64 (0.38)	0.93 (0.04)	0.96 (0.03)
LightGBM	0.88 (0.03)	0.74 (0.17)	0.90 (0.03)	0.88 (0.10)	0.84 (0.09)	0.90 (0.10)	0.88 (0.06)	0.70 (0.25)	0.93 (0.04)	0.95 (0.04)

Table 4.1: Bias metrics of the models based on the demographic groups from the cross-validation with bootstrap sampling *after* race upsampling. All metrics are reported as ratios between the privileged and underprivileged groups.

Gender		
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	0.99 (0.55)	0.99 (0.11)	0.25 (0.17)
Decision Tree	1.18 (0.59)	1.02 (0.16)	0.30 (0.23)

	Disparate Impact	Equal Opportunity	Equalized Odds
Support Vector Machine	0.99 (0.57)	1.01 (0.04)	0.22 (0.12)
Random Forest	1.07 (0.59)	1.02 (0.03)	0.23 (0.22)
XGBoost	1.03 (0.59)	1.02 (0.03)	0.28 (0.21)
LightGBM	1.09 (0.55)	1.02 (0.03)	0.17 (0.21)
Race			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	1.44 (1.13)	1.17 (0.08)	0.20 (0.05)
Decision Tree	1.22 (0.87)	0.99 (0.07)	0.13 (0.05)
Support Vector Machine	1.59 (1.28)	1.22 (0.10)	0.21 (0.03)
Random Forest	1.41 (1.14)	1.03 (0.03)	0.09 (0.05)
XGBoost	1.24 (1.14)	0.99 (0.01)	0.22 (0.29)
LightGBM	1.44 (1.43)	1.03 (0.03)	0.15 (0.20)
Device			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	0.42 (0.03)	0.90 (0.07)	0.71 (0.27)
Decision Tree	0.60 (0.15)	0.99 (0.13)	0.24 (0.15)
Support Vector Machine	0.38 (0.04)	0.87 (0.04)	0.74 (0.24)
Random Forest	0.48 (0.05)	0.96 (0.03)	0.15 (0.14)
XGBoost	0.58 (0.14)	0.94 (0.08)	0.17 (0.15)
LightGBM	0.54 (0.10)	0.97 (0.03)	0.19 (0.27)
Dominant Hand			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	0.55 (0.18)	0.95 (0.10)	0.15 (0.05)
Decision Tree	0.57 (0.22)	1.06 (0.04)	0.11 (0.04)
Support Vector Machine	0.57 (0.14)	0.98 (0.12)	0.16 (0.05)
Random Forest	0.54 (0.22)	0.96 (0.04)	0.12 (0.06)
XGBoost	0.70 (0.24)	1.03 (0.10)	0.12 (0.06)
LightGBM	0.60 (0.18)	1.01 (0.04)	0.06 (0.05)

Table 4.2: Bias metrics of the models based on the demographic groups from the cross-validation with bootstrap sampling *before* race upsampling. All metrics are reported as ratios between the privileged and underprivileged groups.

Gender			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	1.42 (0.48)	1.03 (0.14)	0.34 (0.19)

	Disparate Impact	Equal Opportunity	Equalized Odds
Decision Tree	1.39 (0.68)	0.91 (0.32)	0.46 (0.13)
Support Vector Machine	1.21 (0.45)	0.96 (0.20)	0.29 (0.12)
Random Forest	1.51 (0.39)	1.03 (0.08)	0.34 (0.14)
XGBoost	1.37 (0.48)	1.06 (0.09)	0.34 (0.13)
LightGBM	1.35 (0.42)	1.04 (0.09)	0.27 (0.08)
Race			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	3.55 (0.76)	1.41 (0.25)	0.57 (0.28)
Decision Tree	2.29 (0.51)	1.09 (0.19)	0.24 (0.06)
Support Vector Machine	3.83 (1.45)	1.46 (0.33)	0.57 (0.29)
Random Forest	2.98 (0.87)	1.06 (0.07)	0.34 (0.29)
XGBoost	1.93 (0.68)	0.95 (0.09)	0.47 (0.29)
LightGBM	2.80 (0.48)	1.10 (0.14)	0.40 (0.29)
Device			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	0.39 (0.09)	0.81 (0.13)	0.52 (0.22)
Decision Tree	0.73 (0.39)	1.31 (0.83)	0.33 (0.13)
Support Vector Machine	0.38 (0.06)	0.81 (0.11)	0.49 (0.26)
Random Forest	0.45 (0.05)	0.91 (0.06)	0.26 (0.12)
XGBoost	0.58 (0.18)	0.93 (0.07)	0.23 (0.11)
LightGBM	0.47 (0.03)	0.91 (0.07)	0.24 (0.08)
Dominant Hand			
	Disparate Impact	**Equal Opportunity**	**Equalized Odds**
Logistic Regression	0.42 (0.18)	1.01 (0.05)	0.24 (0.03)
Decision Tree	0.54 (0.20)	0.92 (0.22)	0.27 (0.07)
Support Vector Machine	0.48 (0.21)	1.00 (0.05)	0.21 (0.04)
Random Forest	0.49 (0.22)	0.98 (0.09)	0.17 (0.04)
XGBoost	0.73 (0.18)	1.02 (0.15)	0.19 (0.06)
LightGBM	0.55 (0.16)	0.98 (0.10)	0.19 (0.05)

Table 5.1: Binary indicator of whether a statistically significant difference in F1-score is observed using a t-test between groups for each sensitive attribute (*after* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
	Gender	No	No	No	No	No	No

Statistically Significant F1 Score Differences	Race	No	No	No	No	No	No
	Device	No	No	No	Yes	No	No
	Dominant Hand	No	No	No	No	No	No

Table 5.2: Binary indicator of whether a statistically significance difference in precision is observed using a t-test between groups for each sensitive attribute (*after* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant Precision Score Differences	**Gender**	No	No	No	No	No	No
	Race	No	No	No	No	No	No
	Device	No	Yes	No	Yes	No	No
	Dominant Hand	No	No	No	No	No	No

Table 5.3: Binary indicator of whether a statistically significance difference in sensitivity is observed using a t-test between groups for each sensitive attribute (*after* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant Sensitivity Score Differences	**Gender**	No	No	No	No	No	No
	Race	Yes	No	Yes	No	No	No
	Device	No	No	Yes	No	No	Yes
	Dominant Hand	No	No	No	No	No	No

Table 5.4: Binary indicator of whether a statistically significance difference in specificity is observed using a t-test between groups for each sensitive attribute (*after* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant Specificity Score Differences	**Gender**	No	No	No	No	No	No
	Race	Yes	No	Yes	No	No	No
	Device	No	No	Yes	No	No	Yes
	Dominant Hand	No	No	No	No	No	No

Table 5.5: Binary indicator of whether a statistical difference in F1-score is observed using a t-test between groups for each sensitive attribute (*before* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant F1 Score Differences	**Gender**	No	No	No	No	No	No
	Race	Yes	Yes	Yes	No	No	No
	Device	Yes	No	Yes	Yes	Yes	Yes
	Dominant Hand	No	No	No	No	No	No

Table 5.6: Binary indicator of whether a statistically significance difference in precision is observed using a t-test between groups for each sensitive attribute (*before* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant Precision Score Differences	**Gender**	No	No	No	No	No	No
	Race	No	No	No	No	No	No
	Device	No	Yes	No	No	Yes	No
	Dominant Hand	No	No	No	No	No	No

Table 5.7: Binary indicator of whether a statistically significance difference in sensitivity is observed using a t-test between groups for each sensitive attribute (*before* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant Sensitivity Score Differences	**Gender**	No	No	No	No	No	No
	Race	Yes	No	Yes	No	No	No
	Device	Yes	No	Yes	Yes	No	No
	Dominant Hand	No	No	No	No	No	No

Table 5.8: Binary indicator of whether a statistically significance difference in specificity is observed using a t-test between groups for each sensitive attribute (*before* race upsampling).

		Logistic Regression	Decision Tree	Support Vector Machine	Random Forest	XGBoost	LightGBM
Statistically Significant Specificity Score Differences	**Gender**	No	No	No	No	No	No
	Race	Yes	No	Yes	No	No	No
	Device	Yes	No	Yes	Yes	No	No
	Dominant Hand	No	No	No	No	No	No

Figure 4: F1 score comparisons between the privileged and unprivileged groups for all protected attributes *after* **race upsampling. No significant differences exist** between the two groups in any category after upsampling by race.

Discussion

Our PD assessment encompasses a novel paradigm. While prior PD studies have focused on speech data[11,12,13], gait[14], and handwriting[15], our approach uniquely leverages data collected from a web application, enabling participants to contribute data remotely. This method aligns with the growing need for self-administered and non-invasive telemonitoring applications, which offer an accessible and convenient alternative to clinical examinations that are often challenging for elderly patients[20,21]. Moreover, prior studies have explored keyboard typing and touchscreen interactions for PD detection[16,17], but few have addressed the issue of algorithmic biases[18]. These biases, often stemming from tiny sample sizes for underrepresented groups[19], can compromise the fairness of machine learning models.

We collected mouse and keyboard interaction data from PD participants and non-PD controls using a remotely accessible web assessment to facilitate participation from diverse locations and at convenient times. Although our models were generally performant, our analyses uncovered critical performance disparities, particularly concerning device type and dominant hand. Despite the goal of using our PD classification website to promote affordable and equitable screening, these biases highlight the need for quantifying biases – including non-obvious biases – in consumer digital health informatics.

Despite showing biases toward privileged groups in terms of receiving a PD diagnosis for device type and dominant hand, the models exhibited strong performance in terms of Equal Opportunity across all demographic groups, with values ranging between 0.87 and 1.22. However, this metric only captures the true positive rate (sensitivity) across groups and does not account for false positive rates or overall fairness. The Equalized Odds metric highlighted substantial imbalances.

In some cases, F1 scores were higher for one group than another, but AUROC showed the opposite trend. This discrepancy often occurs when a group's specificity decreases significantly, affecting AUROC more than F1 scores. Conversely, there were instances where AUROC scores were higher despite lower F1 scores. In these cases, variations in precision mirrored those in F1 scores, while specificity and sensitivity remained strong, contributing to the higher AUROC values.

We note a few prominent limitations of our study. One significant limitation is that our model relied on data collected at a single point in time, thus failing to capture the progression of PD over time or symptomatic fluctuations. As PD is a degenerative condition, symptoms can vary due to factors such as medication, stress, and daily activities. Additionally, our study does not include detailed symptom quantification or information about participants' medication usage or timing, critical factors that can significantly influence symptom severity and, thus, model predictions. We did not control for these factors. In future work, we aim to address these limitations by collecting longitudinal data and controlling medication timing and dose. In these future studies, it will be necessary to consider differences in symptom presentation variability across demographic groups, with the temporal aspect potentially introducing additional biases that were not explored in this work.

Methods

Study Design and Participant Recruitment

We recruited individuals aged 50 and above. The recruitment pool comprised both adults diagnosed with PD and healthy controls. To facilitate recruitment, we partnered with local organizations dedicated to PD support and advocacy, including through recruitment efforts at the 2023 and 2024 Hawaii Parkinson's Association (HPA) Symposiums.

We invited participants to join the study using a web application accessible through a public link. The application provided detailed instructions about the research and its activities. Before commencing any activities, all participants provided informed consent electronically.

Figure 5 shows the overall procedure for collecting participant data, preprocessing the dataset to train the models, and evaluating the models for real-world application. The participants used the gamified website to play different games, which required them to use the mouse to click and trace different objects and press keyboard buttons at various times during the game. These mouse trace data and keyboard press data were stored in a cloud database along with the participant's demographic data (Figure 5a). The stored data were then analyzed and engineered to extract features from the mouse trace and keyboard press data. Finally, the dataset was split into 70% training and 30% testing data (Figure 5b). The dataset was trained using six common machine learning classification algorithms using 5-fold cross-validation, and the results were compared for further testing and evaluation on held-out data (Figure 5c). Afterward, the trained models were tested for bias in different demographic groups (Figure 6).

Figure 5: Study workflow. (a) We recorded hand movement data through a structured assessment on a publicly available website. The data are stored in a cloud database for further analysis. (b) Features are extracted from the hand movement data and organized into a tabular format. The features are preprocessed to remove any empty records. The categorical features were transformed using one-hot encoding, and numerical features were normalized using min-max scaling. (c) We trained the model with six machine learning algorithms using 5-fold cross-validation.

Figure 6: Bias evaluations. We quantified biases concerning gender, race, device type, and handedness.

Data Collection Procedure

We recorded the participant data using a web-based assessment by evaluating motor functions (Figure 7). This evaluation was conducted through short and structured tasks designed to assess various aspects of user interactions.

The mouse-based tasks included:

- **Straight-Line Tracing**: Participants were tasked with tracing straight lines on the screen to evaluate hand stability and precision. This task required participants to maintain consistent control and accuracy, reflecting fine motor skills.
- **Curved Line Tracing**: Participants traced spirals and other curved shapes during this activity, offering a more complex evaluation of hand stability and motor coordination.
- **Randomized Clicking Tasks**: Participants clicked on targets appearing at random locations on the screen in order to measure reaction time, hand-eye coordination, and accuracy.

The keyboard-based tasks consisted of:

- **Single-Letter Presses**: Participants were instructed to press designated keys immediately upon receiving a visual prompt, assessing their motor response speed and accuracy.
- **Multiple-Letter Presses**: This task involved replicating key sequences, evaluating participants' ability to execute complex motor tasks and process sequential information. In this phase, the task was confined to only two letters, and the user only needed to press one of the two letters that appear on the screen to pass.
- **Randomized Sequences**: Participants completed tasks involving sequences of randomized key presses, testing their adaptability, coordination, and cognitive flexibility.

We also added a Memory Game to assess cognitive function through progressively challenging levels. However, we did not use the cognitive assessment data in this study, and thus we do not include details about the assessment.

Figure 7: User interface of the web assessment. The user starts by filling out a consent form and records their demographic, health, and medication information. The users are then presented with shapes and required to trace the

shape with their mouse/trackpad. This is followed by a series of games where the user is asked to press a key on the keyboard immediately when prompted. The game ends with a memory test we did not incorporate into our analysis.

Data Up-sampling

The initial dataset used in our study comprised 152 healthy individuals (60.6%) and 99 participants diagnosed with PD (39.4%). While the model initially achieved a strong F1 score, its sensitivity remained low, around 50%, which is particularly concerning in healthcare applications where detecting true positive cases is crucial. To address this issue and to improve the sensitivity of the models, we applied the Synthetic Minority Over-sampling Technique (SMOTE) to balance the dataset by up-sampling the PD patient data (updated data distribution shown in Figure 8).

Moreover, there was a significant imbalance in the racial distribution within the PD label, with 131 White participants compared to only 15 Non-White participants. To mitigate this imbalance, we applied a random resampling technique to increase the number of Non-White participants in the PD category (updated data distribution without SMOTE shown in Figure 9 and with SMOTE shown in Figure 10).

(a) Number of Data Points Per Class

(b) Distribution of Gender based on PD Diagnosis

(c) Device Type Distribution

(d) Device Type Distribution for different races

(e) Heatmap of Race Distribution by Disease Status

(f) Heatmap of Race Distribution by Disease Status (White vs Non-White)

Figure 8: Data distribution after applying SMOTE.

(a) Number of Data Points Per Class

(b) Distribution of Gender based on PD Diagnosis

(c) Device Type Distribution

(d) Device Type Distribution for different races

(e) Heatmap of Race Distribution by Disease Status (White vs Non-White)

Figure 9: Data distribution after randomly resampling non-White data points with no PD (before SMOTE).

(a) Number of Data Points Per Class

(b) Distribution of Gender based on PD Diagnosis

(c) Device Type Distribution

(d) Device Type Distribution for different races

(f) Heatmap of Race Distribution by Disease Status (White vs Non-White)

Figure 10: Data distribution after randomly resampling non-White data points with no PD (after SMOTE).

Bootstrapped Sampling

We apply bootstrapped sampling with 100 samples in each iteration to generate error bars. In each bootstrapped sampling step, the sample set consists of an equal number of data points from both groups in each category while calculating the group-wise metrics for that category, e.g., gender, race, device, and dominant hand. For example, when calculating the F1 scores, sensitivity, specificity, precision, and AUROC for gender, the sample set was constructed by taking 50% of

the sample from the Male subset and 50% from the Female subset using resampling with replacement. Finally, we report the mean of the metrics.

Feature Engineering

We engineered 80 features related to Hand Stability - Straight Line Tracing, Hand Stability - Curved Line Tracing, Response Times and Accuracy, Dominant Hand Movement, and Wrong Clicks, all engineered from the raw data. Table 6 summarizes some of the key engineered features we used in our study to detect PD.

Table 6: List of engineered features.

Category	Feature Name	Feature Description	Unit	Key Notes
Tracing Accuracy Metrics	Time to Trace (Straight Line)	Time taken to trace straight line appeared on the desktop/laptop screen	Milliseconds	Indicates motor control speed and efficiency.
	Points Inside (Straight Line, %)	Percentage of mouse points traced inside straight line	Percentage	Assesses accuracy in tracing a simple shape.
	Time to Trace (Sine Wave)	Time taken to trace sine wave appeared on the desktop/laptop screen	Milliseconds	Evaluates motor control in more complex patterns.
	Points Inside (Sine Wave, %)	Percentage of mouse points traced inside sine wave	Percentage	Reflects precision in tracing a complex pattern.
	Time to Trace (Spiral)	Time taken to trace spiral appeared on the desktop/laptop screen	Milliseconds	Measures coordination in complex, continuous patterns.
	Points Inside (Spiral, %)	Percentage of mouse points traced inside spiral	Percentage	Evaluates accuracy in a complex tracing task.
Interaction Terms	Time vs Errors (Straight, Sine, Spiral)	Pearson correlation between tracing time of (straight line, sine wave, spiral) and false presses	Correlation Coefficient	Shows how the duration of the task affects the error rate.
Key Press Metrics	Correct Presses (Constant Key)	Number of correctly pressed button of keyboard when prompted with a constant key	Count	Reflects motor skills and cognitive speed.
	Correct Presses (Random Key)	Number of correctly pressed button of keyboard when prompted with a random key	Count	Evaluates accuracy under unpredictable conditions.
Hand Metrics	Avg Time (Dominant Hand p and q)	Mean time from dominant hand for pressing 'p' and 'q'	Milliseconds	Reflects time efficiency with the dominant hand.
	Avg Time (Non-Dominant Hand p and q)	Mean time from non-dominant hand for pressing 'p' and 'q'	Milliseconds	Assesses time efficiency with the non-dominant hand.
	Time Ratio (Dominant/Non-Dominant p and q)	Ratio of mean time from dominant and non-dominant hand for pressing 'p' and 'q'	Ratio	Compares time efficiency between hands.
Box Clicking Metrics	Avg Box Click Time	Mean time taken to click box on the screen	Milliseconds	Reflects time efficiency for box clicking.
	Box Click Variability	Standard deviation of time taken to click box on the screen	Milliseconds	Indicates variability in box clicking times.
Game Reaction Time Metrics	Avg Reaction Time	Mean reaction time for data collected from game	Milliseconds	Measures average responsiveness.
	Reaction Time Variability	Standard deviation of reaction times	Milliseconds	Shows variability in reaction times.
Click Metrics	Mean Right Clicks	Mean right number of clicks while clicking object on the screen	Count	Measures right-clicking behavior.

	Mean Wrong Clicks	Mean wrong number of clicks while clicking object on the screen	Count	Measures incorrect clicking behavior.
Participant Info	Gender	Gender of the participants	Male/Female	Demographic information.
	Race	Race or Ethnicity of the participants	African American, Native Hawaiian or Pacific Islander, black or African American, American Indian or Alaska Native, Asian	Demographic information.
	Dominant Hand	Dominant hand of the participant	Left/Right Hand	Demographic information.
	Device Type	Type of device used by the participant	Type	Technical information.

Evaluation Metrics

To evaluate the performance of our PD prediction model, we used a combination of standard performance metrics and fairness metrics to assess both accuracy and equity across demographic groups. This section provides a detailed description of these metrics.

Standard Performance Metrics

We compute the F1-score, sensitivity (recall), precision, and specificity for each group across all demographic categories to evaluate model performance. Precision represents the proportion of correctly identified positive cases out of all predicted positive cases. Sensitivity (recall) measures the proportion of true positive (TP) cases accurately determined by the model. At the same time, specificity quantifies the proportion of true negative (TN) cases correctly classified, where true negatives refer to actual negatives correctly identified. In these calculations, false positives (FP) represent cases incorrectly classified as positive, and false negatives (FN) are actual positives misclassified as unfavorable. The F1-score combines precision and recall into a single metric, calculated as their weighted harmonic mean. The formulas for these metrics are:

$$Precision = \frac{TP}{TP + FP}$$

$$Recall = \frac{TP}{TP + FN}$$

$$Specificity = \frac{TN}{TN + FP}$$

$$F1-score = \frac{2 * (Recall * Precision)}{(Recall + Precision)}$$

Fairness Metrics

To ensure equitable outcomes across protected groups, we employed the following fairness metrics:

Disparate impact

Disparate Impact (DI) is a fairness metric used to evaluate equity in model outcomes by comparing the rates of positive outcomes between a privileged and an unprivileged group [22,23]. It assesses

whether the unprivileged group is disproportionately less likely to receive favorable outcomes than the privileged group. DI is calculated as the ratio of the proportion of positive outcomes for the unprivileged group to that of the privileged group, defined as:

$$DI = \frac{(\dfrac{TP_u + FP_u}{N_u})}{(\dfrac{TP_P + FP_P}{N_P})}$$

TP_u and TP_p represent true positives while FP_u and FP_p denote false positives for the unprivileged (u) and privileged (p) groups. N_u and N_p denote the total number of individuals in the unprivileged and privileged groups, respectively.

To achieve fairness, the Disparate Impact (DI) value must equal 1, indicating equal rates of positive predictions for both groups[22]. A value below 1 signals potential bias against the unprivileged group, while a value above 1 suggests a potential bias favoring the unprivileged group.

Equal Opportunity

Equal Opportunity (EO) is a fairness concept requiring that privileged and unprivileged groups achieve equal true positive rates (TPR)[24]. This ensures that individuals from all demographic groups who qualify for a positive outcome are equally likely to receive it. EO is mathematically defined as the ratio of the TPRs between unprivileged and privileged groups and is expressed as:

$$EO = \frac{TPR_u}{TPR_p}$$

An Equal Opportunity (EO) value of 1 represents perfect fairness, signifying that true positive rate (TPR) are identical across both privileged and unprivileged groups. A value less than 1 indicates that the unprivileged group has a lower TPR than the privileged group, suggesting potential bias against the unprivileged group in receiving favorable outcomes. Conversely, a value greater than 1 indicates that the unprivileged group has a higher TPR than the privileged group, which may reflect a bias favoring the unprivileged group.

Equalized Odds

Equalized Odds require that both true positive rates (TPRs) and false positive rates (FPRs) are equal across privileged and unprivileged groups[24], ensuring that the model's predictions regarding successes and errors are fair. By extending the concept of Equal Opportunity, Equalized Odds ensures that predictions do not disproportionately favor or disadvantage any group. It can be mathematically represented as the ratio of TPRs and FPRs between the unprivileged and privileged groups:

$$EOdds = 0.5(\frac{TPR_u}{TPR_p} + \frac{FPR_u}{FPR_p})$$

An Equalized Odds value of 1 represents ideal fairness, signifying uniform error distribution and success rates across all demographic groups. Deviations from this standard, whether below or

above 1, indicate disparities in the model's predictions, pointing to potential biases in true positive rates (TPRs), false positive rates (FPRs), or both.

Ethical Considerations

This project received approval from the University of Hawaii Institutional Review Board (IRB), protocol #2022-00857.

Acknowledgments

This research was partly funded by the National Institutes of Health (NIH) Agreement No. 1OT2OD032581-01. The views and conclusions in this document are those of the authors and should not be interpreted as representing the NIH's official policies, either expressed or implied. The language and grammar of this manuscript were revised using AI tools such as ChatGPT and Grammarly. However, the authors thoroughly refined the language after the stylistic revisions provided by these tools.

References

1. Dorsey, E. R., Sherer, T., Okun, M. S., & Bloem, B. R. (2018). The emerging evidence of the Parkinson pandemic. *Journal of Parkinson's Disease, 8*(s1), S3–S8. https://doi.org/10.3233/JPD-181474
2. Dorsey, E. R., Constantinescu, R., Thompson, J. P., Biglan, K. M., Holloway, R. G., Kieburtz, K., Marshall, F. J., Ravina, B. M., Schifitto, G., Siderowf, A., & Tanner, C. M. (2007). Projected number of people with Parkinson disease in the most populous nations, 2005 through 2030. *Neurology, 68*(5), 384–386. https://doi.org/10.1212/01.wnl.0000247740.47667.03
3. Almalaq, A., Dai, X., Zhang, J., Hanrahan, S., & Nedrud, J. (2015). Causality graph learning on cortical information flow in Parkinson's disease patients during behaviour tests. In *Proceedings of the 2015 49th Asilomar Conference on Signals, Systems and Computers* (pp. 925–929). Pacific Grove, CA, USA, 8–11 November 2015.
4. Benba, A., Jilbab, A., Hammouch, A., & Sandabad, S. (2015). Voiceprints analysis using MFCC and SVM for detecting patients with Parkinson's disease. In *Proceedings of the IEEE 2015 International Conference on Electrical and Information Technologies (ICEIT)* (pp. 300–304). Marrakech, Morocco, 25–27 March 2015.
5. Sakar, C. O., Serbes, G., Gunduz, A., Tunc, H. C., Nizam, H., Sakar, B. E., Tutuncu, M., Aydin, T., Isenkul, M. E., & Apaydin, H. (2019). A comparative analysis of speech signal processing algorithms for Parkinson's disease classification and the use of the tunable-factor wavelet transform. *Applied Soft Computing, 74*, 255–263. https://doi.org/10.1016/j.asoc.2018.10.019
6. Alqahtani, E. J., Alshamrani, F. H., Syed, H. F., & Olatunji, S. O. (2018). Classification of Parkinson's disease using NNge classification algorithm. In *Proceedings of the 2018 21st Saudi Computer Society National Computer Conference (NCC)* (pp. 1–7). Riyadh, Saudi Arabia, 25–26 April 2018. https://doi.org/10.1109/NCG.2018.8593087
7. Pereira, C. R., Pereira, D. R., Silva, F. A., Masieiro, J. P., Weber, S. A., Hook, C., & Papa, J. P. (2016). A new computer vision-based approach to aid the diagnosis of Parkinson's

disease. *Computers in Biology and Medicine, 136,* 79–88. https://doi.org/10.1016/j.compbiomed.2016.09.006

8. Abdulhay, E., Arunkumar, N., Narasimhan, K., Vellaiappan, E., & Venkatraman, V. (2018). Gait and tremor investigation using machine learning techniques for the diagnosis of Parkinson's disease. *Future Generation Computer Systems, 83,* 366–373. https://doi.org/10.1016/j.future.2018.02.009

9. Asanza, V., Sánchez-Pozo, N. N., Lorente-Leyva, L. L., Peluffo-Ordóñez, D. H., Loayza, F. R., & Peláez, E. (2021). Classification of subjects with Parkinson's disease using finger tapping dataset. *IFAC-PapersOnLine, 54*(15), 376-381. https://doi.org/10.1016/j.ifacol.2021.08.321

10. Adams, W. R. (2017). High-accuracy detection of early Parkinson's disease using multiple characteristics of finger movement while typing. *PLoS One, 12*(11), e0188226. https://doi.org/10.1371/journal.pone.0188226

11. Neharika, D. B., & Anusuya, S. (2020). Machine learning algorithms for detection of Parkinson's disease using motor symptoms: Speech and tremor. *International Journal of Recent Technology and Engineering, 8,* 47–50.

12. Benba, A., Jilbab, A., Hammouch, A., & Sandabad, S. (2015). Voiceprints analysis using MFCC and SVM for detecting patients with Parkinson's disease. In *2015 International Conference on Electrical and Information Technologies (ICEIT)* (pp. 300-304). Marrakech, Morocco. https://doi.org/10.1109/EITech.2015.7163000

13. Sakar, B. E., Isenkul, M. E., Sakar, C. O., Sertbas, A., Gurgen, F., Delil, S., Apaydin, H., & Kursun, O. (2013). Collection and analysis of a Parkinson speech dataset with multiple types of sound recordings. *IEEE Journal of Biomedical and Health Informatics, 17*(4), 828–834. https://doi.org/10.1109/JBHI.2013.2245674

14. Abdulhay, E., Arunkumar, N., Narasimhan, K., Vellaiappan, E., & Venkatraman, V. (2018). Gait and tremor investigation using machine learning techniques for the diagnosis of Parkinson disease. *Future Generation Computer Systems, 83,* 366–373. https://doi.org/10.1016/j.future.2018.02.009

15. Al-Wahishi, A., Belal, N., & Ghanem, N. (2020). Diagnosis of Parkinson's disease by deep learning techniques using handwriting dataset. In *Proceedings of the International Symposium on Signal Processing and Intelligent Recognition Systems*. Chennai, India, 14–17 October 2020.

16. Arroyo-Gallego, T., et al. (2018). Detecting motor impairment in early Parkinson's disease via natural typing interaction with keyboards: Validation of the neuroQWERTY approach in an uncontrolled at-home setting. *Journal of Medical Internet Research, 20*(3), e89. https://doi.org/10.2196/jmir.9462

17. Bernardo, L. S., Damaševičius, R., Ling, S. H., de Albuquerque, V. H. C., & Tavares, J. M. R. S. (2022). Modified SqueezeNet architecture for Parkinson's disease detection based on keypress data. *Biomedicines, 10*(11), 2746. https://doi.org/10.3390/biomedicines10112746

18. Makarious, M. B., Leonard, H. L., Vitale, D., Iwaki, H., Sargent, L., Dadu, A., ... & Nalls, M. A. (2022). Multi-modality machine learning predicting Parkinson's disease. *NPJ Parkinson's Disease, 8*(1), 35. https://doi.org/10.1038/s41531-022-00290-3

19. Paul, S., Maindarkar, M., Saxena, S., Saba, L., Turk, M., Kalra, M., ... & Suri, J. S. (2022). Bias investigation in artificial intelligence systems for early detection of Parkinson's

disease: A narrative review. *Diagnostics, 12*(1), 166. https://doi.org/10.3390/diagnostics12010166

20. Isenkul, M., Sakar, B., & Kursun, O. (2014). Improved spiral test using digitized graphics tablet for monitoring Parkinson's disease. In *Proceedings of the 2nd International Conference on e-Health and Telemedicine (ICEHTM-2014)* (Vol. 5). https://doi.org/10.1109/ICEHTM.2014.7057397
21. Matarazzo, M., Arroyo-Gallego, T., Montero, P., Puertas-Martín, V., Butterworth, I., Mendoza, C. S., Ledesma-Carbayo, M. J., Catalán, M. J., Molina, J. A., Bermejo-Pareja, F., Martínez-Castrillo, J. C., López-Manzanares, L., Alonso-Cánovas, A., Rodríguez, J. H., Obeso, I., Martínez-Martín, P., Martínez-Ávila, J. C., de la Cámara, A. G., Gray, M., Obeso, J. A., & Sánchez-Ferro, Á. (2019). Remote monitoring of treatment response in Parkinson's disease: The habit of typing on a computer. *Movement Disorders, 34*(10), 1488–1495. https://doi.org/10.1002/mds.27772
22. Briscoe, Jarren, and Assefaw Gebremedhin. "Facets of Disparate Impact: Evaluating Legally Consistent Bias in Machine Learning." Proceedings of the 33rd ACM International Conference on Information and Knowledge Management. 2024.
23. Caton, Simon, and Christian Haas. "Fairness in machine learning: A survey." ACM Computing Surveys 56.7 (2024): 1-38.
24. Mehrabi, Ninareh, et al. "A survey on bias and fairness in machine learning." ACM computing surveys (CSUR) 54.6 (2021): 1-35.