Sparse Polygenic Risk Score Inference with the Spike-and-Slab LASSO

Junyi Song,[1,*] Shadi Zabad,[1,*] Archer Yang,[2] Simon Gravel[3] and Yue Li[1,§]

[1]School of Computer Science, McGill University, [2]Department of Mathematics and Statistics, McGill University and [3]Department of Human Genetics, McGill University

[*]Co-first authors [§]Corresponding author: yueli@cs.mcgill.ca

Abstract

Large-scale biobanks, with comprehensive phenotypic and genomic data across hundreds of thousands of samples, provide ample opportunities to elucidate the genetics of complex traits and diseases. Consequently, there is a growing demand for robust and scalable methods for disease risk prediction from genotype data. Performing inference in this setting is challenging due to the high-dimensionality of genomic data, especially when coupled with relatively smaller sample sizes. Popular Polygenic Risk Score (PRS) inference methods address this challenge by adopting sparse Bayesian priors or penalized regression techniques, such as the Least Absolute Shrinkage and Selection Operator ($LASSO$). However, the former class of methods are not as scalable and do not produce exact sparsity, while the latter tends to over-shrink large coefficients. In this study, we present $SSLPRS$, a novel PRS method based on the Spike-and-Slab LASSO (SSL) prior, which offers a theoretical bridge between the two frameworks. We extend previous work to derive a coordinate-ascent inference algorithm that operates on GWAS summary statistics, which is orders-of-magnitude more efficient than corresponding individual-level-based implementations. To illustrate the statistical properties of the proposed model, we conducted experiments involving 9 simulation configurations and 9 quantitative phenotypes from the UK Biobank. Our results demonstrate that $SSLPRS$ is competitive with state-of-the-art methods in terms of prediction accuracy and exhibits superior variable selection performance, especially in sparse genetic architectures. In simulations, this translates to upwards of 50% improvement in positive predictive value. In analysis of real phenotypes, we show that selected variants are highly enriched for meaningful genomic annotations and have better replication rates in larger meta-analyses.

Key words: Polygenic risk score, Variable selection, GWAS, High-dimensional analysis, Penalized regression, Spike-and-slab LASSO, Sparsity

Introduction

Polygenic risk scores are emerging as an important tool to quantify the heritable component of complex traits and diseases, with an array of promising clinical applications, including genetic risk stratification and personalized medicine (Torkamani et al., 2018; Lewis and Vassos, 2020). However, inference of polygenic scores from large-scale Genome-wide Association Study (GWAS) data is practically challenging due to two main factors. First, due to privacy concerns, individual-level data is rarely publicly available, and consequently, inference has to be carried out using "GWAS summary statistics" (Pasaniuc and Price, 2017), which are the marginal association statistics per variant, coupled with Linkage-Disequilibrium (LD) matrices that record the pairwise correlations between variants in the dataset. The second factor is the ultra high-dimensional nature of genetic data, with modern biobank initiatives routinely measuring and imputing data for upwards of 20 million genetic markers (Karczewski et al., 2024). Considering that GWAS sample sizes, even for the largest meta-analyses, rarely exceed two million samples (Zhou et al., 2022), this setup calls for robust and scalable regularized or Bayesian regression frameworks.

Previous work has explored various statistical and algorithmic approaches to meet these challenges (Jayasinghe et al., 2024). This includes sparse penalized regression methods, such as `Lassosum` (Mak et al., 2017), as well as a wide array of sparse Bayesian priors, including Horseshoe (`PRScs`) (Ge et al., 2019), Spike-and-slab (`LDPred`, `VIPRS`) (Privé et al., 2020; Zabad et al., 2023), and sparse mixture priors (`SBayesR`, `MegaPRS`) (Lloyd-Jones et al., 2019; Zhang et al., 2021). While the overall prediction accuracy of these individual methods is roughly comparable (Pain et al., 2021; Zabad et al., 2023), they can differ substantially in terms of computational resource utilization, the quality of selected variables, and the statistical properties of their inferred effect sizes. On typical GWAS datasets with 1 million genetic variants, the total wallclock time required can range from 15 minutes for optimization-based approaches ($VIPRS$) up to several hours for Markov-Chain Monte Carlo (MCMC)-based Bayesian methods (`PRScs`) (Zabad et al., 2023). While Bayesian methods can provide accurate and unbiased effect sizes estimates, their coefficients are not truly sparse, which can complicate interpretation and deploying these predictors in some practical settings. On the other hand, traditional penalized regression methods such as the $LASSO$ provide sparse effect sizes estimates, but they are known to over-shrink large coefficients, thus introducing a bias (James et al., 2019).

Here, we bridge the gap between sparse Bayesian methods and traditional penalized regression approaches by developing and testing a new PRS model based on the recently-proposed Spike-and-slab LASSO (SSL) prior (Ročková and George, 2018). The SSL prior is a mixture of two Laplace densities that together form a non-concave penalty, shrinking small coefficients to exactly zero while holding larger effect sizes steady (Ročková and George, 2018; Bai et al., 2021). In

Fig. 1. Overview of the statistical properties and inference dynamics of the *SSL* and *LASSO* on simulated genetic data. (a, b) Illustration of the densities $\psi(\beta \mid \lambda_0)$, $\psi(\beta \mid \lambda_1)$ of the *SSL* prior with (a) $\lambda_0 = 10$ and $\lambda_1 = 1$ (b) $\lambda_0 = \lambda_1 = 10$, which reduces to the *LASSO* case. (c) Simulated genetic data with 24 genetic variants with block-diagonal correlation structure. In this setup, 8 of the variants are causal (green) while 16 are non-causal (blue). Marginal effect sizes are shown in the top panel and absolute pairwise correlations between the variants are shown in the bottom panel. (d, e) Effect size estimates of (d) SSL and (e) *LASSO* models are shown along a ladder of increasing λ_0 values. Ground truth causal variants are shown in green, while non-causal ones are shown in blue. Non-zero effect size estimates at the end of λ ladder are labeled with their corresponding index. (f) Variable selection metrics, including precision, recall, and Matthews Correlation Coefficient (MCC), for the *LASSO* and *SSL* models across the λ ladder.

addition to fast coordinate-ascent inference algorithms, the *SSL* prior comes with many attractive theoretical properties, and, depending on the setting of its hyperparameters, can smoothly interpolate between the *LASSO* and Spike-and-slab priors (Ročková and George, 2018). Our contributions include the following: **(1)** Deriving a version of the *SSL* inference algorithms that operates on GWAS summary statistics. **(2)** Providing a fast and memory-efficient software implementation that incorporates state-of-the-art techniques (Zabad et al., 2025) for scaling PRS inference to millions of genetic markers. Open source code is available at `https://github.com/shz9/penprs`. **(3)** Examining the statistical and computational performance of the *SSLPRS* model on both simulated data and real quantitative phenotypes in the UK Biobank (Bycroft et al., 2018). In addition, we provide a new implementation of the *LASSO* model that takes advantage of highly-optimized data structures and algorithms (Zabad et al., 2025), which improves its runtime by more than an order of magnitude compared to the original version (`Lassosum`) (Mak et al., 2017; Zabad et al., 2023).

Methods

Overview of SSLPRS

In a sample of n individuals with paired genotype and phenotype data of p variants, the standard linear model is used

to parameterize the dependence of phenotype on the genotype,

$$\boldsymbol{y} = \boldsymbol{X}\boldsymbol{\beta} + \boldsymbol{\epsilon} \tag{1}$$

where $\mathbf{y}$ is an $n \times 1$ vector of phenotypic measurements for each individual, $\boldsymbol{X}$ is an $n \times p$ genotype matrix, $\boldsymbol{\beta}$ is a $p \times 1$ vector of effect sizes per variant, and $\boldsymbol{\epsilon}$ is an $n \times 1$ vector representing the residual effects of the phenotype for each individual. We adapted the *SSL* framework (Ročková and George, 2018), originally operating on individual level data, to support GWAS summary statistics for polygenic risk prediction.

The *SSL* prior primarily consists of two Laplace densities, $\psi(\beta \mid \lambda) = (\lambda/2)e^{-\lambda|\beta|}$ to model the "spike" and the "slab" respectively. This formulation facilitates the adaptive shrinkage of variants based on their covariance and the associations with the target phenotype:

$$p(\boldsymbol{\beta} \mid \boldsymbol{\gamma}) = \prod_{j=1}^{p} (1 - \gamma_j)\psi(\beta_j \mid \lambda_0) + \gamma_j \psi(\beta_j \mid \lambda_1),$$

$$p(\boldsymbol{\gamma} \mid \theta) = \prod_{j=1}^{p} \theta^{\gamma_j}(1 - \theta)^{1 - \gamma_j}, \tag{2}$$

where $\theta \sim Beta(a, b)$.

Typically, the scale parameters are chosen such that $\lambda_0 \gg \lambda_1$, so $\psi(\cdot \mid \lambda_1)$ is diffuse, representing a slab with respect to the spiky $\psi(\cdot \mid \lambda_0)$ that is dense around zero. The Laplace

distributions of the prior introduce essentially two *LASSO* components where effect sizes of variants assigned to the "spike" component can be driven to exact sparsity by a strong λ_0 penalty, whereas those in the "slab" component undergo usually minimal shrinkage by a relatively weaker λ_1 penalty. Here, $\theta \in (0,1)$ denotes the mixing proportion, and the shared θ prior in Equation 2 renders the *SSL* penalty non-separable, enabling *SSL* to borrow information across coefficients and adapt to sparsity patterns. (Bai et al., 2021; Ročková and George, 2018). The prior on $\boldsymbol{\beta}$ can be parameterized on θ by marginalizing out $\boldsymbol{\gamma}$:

$$p(\boldsymbol{\beta} \,|\, \theta) = \prod_{j=1}^{p} [(1-\theta)\psi(\beta_j \,|\, \lambda_0) + \theta\psi(\beta_j \,|\, \lambda_1)] \quad (3)$$

The selection of λ_0 and λ_1, specifically the ratio λ_0/λ_1 places *SSL* on the continuum of the *LASSO* case and the ideal spike-and-slab (Figure 1a). In the case where $\lambda_0 = \lambda_1$ or $\lambda_1 = 0$, *SSL* simplifies to the *LASSO* l_1 penalty (Figure 1b). On the other hand, choosing $\lambda_0 \to \infty$ gives a theoretical point-mass spike (Ročková and George, 2018).

SSLPRS inference

(Ročková and George, 2018; Moran et al., 2019) introduced an efficient coordinate ascent Maximum A Posteriori (MAP) algorithm for *SSL*. In this work, we developed an improved framework of the coordinate ascent algorithm with support for GWAS summary statistics, alongside inference optimizations. The objective function is the log posterior, under the assumptions that both the genotype matrix $\boldsymbol{X}$ and phenotype vector $\boldsymbol{y}$ have been standardized column-wise for unit variance and zero mean for GWAS summary statistics:

$$L(\boldsymbol{\beta}) = -\frac{N}{2\sigma^2}\left(1 - 2\sum_{j=1}^{p}\hat{\beta}_j\beta_j + 2\sum_{j=1}^{p}\sum_{m<j}R_{jm}\beta_j\beta_m + \sum_{j=1}^{p}\beta_j^2\right)$$
$$- (n+2)\log\sigma + \sum_{j=1}^{p}\text{pen}(\beta_j|\theta) \quad (4)$$

where N is the GWAS sample size. $\hat{\beta}_j = \frac{1}{N}X_j^T\boldsymbol{y}$ denotes the standardized marginal GWAS effect size for SNP j with X_j as the j-th column of $\boldsymbol{X}$. $\boldsymbol{R} = (R_{jm})$ defines the $p \times p$ Linkage Disequilibrium (LD) matrix with $R_{jm} = \frac{1}{N}X_j^\top X_m$. The last term in Equation (4) is the separable spike-and-slab Lasso penalty (Ročková and George, 2018):

$$\text{pen}(\beta_j \,|\, \theta) = -\lambda_1|\beta_j| + \log\left[\frac{p_\theta^*(0)}{p_\theta^*(\beta_j)}\right] \quad (5)$$

$$p_\theta^*(\beta_j) = \frac{\theta\psi(\beta_j \,|\, \lambda_1)}{\theta\psi(\beta_j \,|\, \lambda_1) + (1-\theta)\psi(\beta_j \,|\, \lambda_0)}. \quad (6)$$

In high-dimensional analysis, the posterior is likely to be multi-modal. The Karush–Kuhn–Tucker (KKT) conditions — which coincide with the standard *LASSO* estimate criteria (Zhao and Yu, 2006), only give the necessary conditions — via soft-thresholding on β_j — for $\boldsymbol{\beta^*}$ to be a global mode under the *SSL* prior (Eq. 2). Sufficient conditions require the filtering of sub-optimal local modes, which can be achieved through hard-thresholding with Δ (Moran et al., 2019; Ročková and George, 2018; Zhang and Zhang, 2012). Combining these conditions

gives

$$\beta_j^* = \frac{1}{n(1+\lambda_{\min})}\left[|z_j| - \sigma^2\lambda_\theta^*(\beta_j^*)\right]_+ \text{sign}(z_j)\mathbb{I}(|z_j| > \Delta) \quad (7)$$

where

$$z_j = N(\hat{\beta}_j - \Sigma_{k \neq j}R_{jk}\beta_k) \quad (8)$$

and λ_θ^* corresponds to the partial derivative of $\text{pen}(\beta_j \,|\, \theta)$ with respect to $|\beta_j|$ (Ročková and George, 2018), and is expressed as:

$$\lambda_\theta^*(\beta_j) = \lambda_1 p_\theta^*(\beta_j) + \lambda_0(1 - p_\theta^*(\beta_j)) \quad (9)$$

Here, $\Delta \equiv \inf_{t>0}[nt/2 - \sigma^2\text{pen}(t|\theta)/t]$, which can be approximated (Moran et al., 2019) by:

$$\Delta = \begin{cases} \sqrt{2n\sigma^2\log[1/p_\theta^*(0)]} + \sigma^2\lambda_1 & \text{if } g_\theta(0) > 0 \\ \sigma^2\lambda_\theta^*(0) & \text{otherwise} \end{cases} \quad (10)$$

where

$$g_\theta(\beta_j) = (\lambda_\theta^*(\beta_j) - \lambda_1)^2 + (2n/\sigma^2)\log p_\theta^*(\beta_j) \quad (11)$$

Fitting *SSLPRS* on sparsified LD matrices, which are not always positive semi-definite, may result in excessively large effect size estimates. We introduce an additional hyperparameter $\lambda_{\min}$ in Eq. (7) to ensure numerical stability by regularizing the β_j update and avoiding modes aligned with negative eigenvalues.

The global mode can subsequently be determined through an efficient coordinate ascent algorithm (Algorithm 1), applied to summary statistics, by iteratively updating the model parameters until convergence.

By Lemma 4 from (Ročková and George, 2018), $\theta^{(k)}$ can be approximated by

$$\theta = \frac{a + \hat{p}_\gamma}{a + b + p} \quad (12)$$

where $\hat{p}_\gamma$ is the number of non-zero coefficients.

Algorithm 1 SSLPRS Coordinate Ascent

1: Input: $\lambda_0, \lambda_1, a, b$
2: Initialize of $\boldsymbol{\beta}^{(0)} = \boldsymbol{0}_p, \theta^{(0)} = 0.5, \sigma^{2(0)}, M = 10$
3: **for** k in $1 \ldots k_{max}$ **do**
4:     Update $\Delta^{(k)}$ by (Eq. 10)
5:     **for** j in $1 \ldots p$ **do**
6:         Update each $\beta_j^{(k)}$ with (Eq. 7)
7:         **if** M updates of $\beta_j^{(k)}$ have occurred **then**
8:             Update $\theta^{(k)}$ by (Eq. 12)
9:         **end if**
10:    **end for**
11:    **if** $\forall j \; |\beta_j^{(k)} - \beta_j^{(k-1)}| \leq \epsilon$ **then**
12:       break
13:    **end if**
14: **end for**

Algorithm 2 SSLPRS Dynamic Warm-start.

1: Input: λ_1, a, b and ladder of $\lambda_0 = \{\lambda_0^1, \ldots, \lambda_0^L\}$
2: Initialize of $\boldsymbol{\beta}^{(0)} = \boldsymbol{0}_p, \theta^{(0)} = 0.5, \sigma^{2(0)}, M = 10$
3: **for** l in $1, \ldots, L$ **do**
4:    Initialize $\lambda_0 = \lambda_0^l, \boldsymbol{\beta} = \boldsymbol{\beta}^{(l-1)}, \sigma^2 = \sigma^{2(l-1)}, \theta = \theta^{(l-1)}$
5:    Run coordinate ascent with Algorithm 1.
6:    $(\boldsymbol{\beta}^{(l)} = \boldsymbol{\beta}, \sigma^{2(l)} = \sigma^2, \theta^{(l)} = \theta)$
7: **end for**

In this work, we kept σ^2 constant as a hyperparameter. A variation of the coordinate ascent algorithm is the unknown variance case (Bai et al., 2021), which we present in full for summary statistics in the supplemental methods section S3.2.

Hyperparameter choices

The default $SSLPRS$ model operates on the fixed variance case, where we set $\sigma^2 = 1$ based on the assumption that the data is standardized. For hyperparameters a, b in the θ update, we set $b = p$ and $a = \frac{0.05}{1-0.05}b$ so the beta prior mean is 0.05 (Eq. 2), reflecting an estimate of 5% causality in the dataset. The selection of penalty values λ_0, λ_1 scales with the data through $\lambda_{\max} = |N\hat{\beta}_j|$, which is the maximum penalty $LASSO$ can take before all effect sizes are shrunk to zero (Friedman et al., 2010). To ensure that the slab is sufficiently diffuse, λ_1 is set to $\epsilon\lambda_{\max}$, where $\epsilon = 10^{-3}$. λ_0 is scaled to be $\lambda_0 = 100\lambda_1$ or 10% of $\lambda_{\max}$. $\lambda_{\min}$ is set to the minimum value for the LD matrix to remain positive semi-definite and numerically stable (Zabad et al., 2023).

Dynamic posterior exploration

Since the choice of hyperparameters λ_0 and λ_1 greatly affects the shrinkage and degree of the spike and slab formulation of $SSLPRS$ on the continuum between $LASSO$ and the point mass spike and slab, optimizing the performance requires a precise selection of these hyperparameters. (Ročková and George, 2018) detailed a dynamic posterior exploration strategy, where a ladder of gradually increasing λ_0 values $\{\lambda_0^1, \ldots, \lambda_0^L\}$ are selected while λ_1 is kept at a sufficiently diffuse value relative to the choices of λ_0 in the ladder. The initial λ_0^1 value in the ladder is typically selected such that $(\lambda_1 - \lambda_0)^2 < 4$, which makes the objective (Eq. 4) convex (Bai et al., 2021). The convex solution can be used as a "warm-start" for non-convex problems, which occurs when $\lambda_0 \gg \lambda_1$. In particular, after fitting each λ_0^l on the ladder with Algorithm 1, the MAP estimation of $\boldsymbol{\beta}$, along with model parameters $(\Delta, \theta, \sigma^2)$ are used to "warm-start" the fit for λ_0^{l+1}. (Algorithm 2.)

Our experiments show that $\lambda_{\max}$ becomes the minimum penalty beyond which all negligible coefficients would be set to zero (Friedman et al., 2010), essentially "converging" along the coefficient path of the λ_0 ladder. This also provides a strict range of λ_0 values to search in for hyperparameter tuning. By default, $SSLPRS$ performs a warm-start exploration on a 20-step $\log_2$ scaled λ_0 ladder from λ_1 to $\lambda_{\max}$, which does not require grid search.

Hyperparameter search

In the grid-search ($SSLPRS$-GS) case, hyperparameter search is conducted independently for each chromosome, where effect size estimates are taken from the best performing λ_0 value of the warm-start ladder on the validation set. Since warm-start is performed to the end of the ladder, $SSLPRS$ can be concurrently fit as well. Hyperparameters a, b are kept at their default setting of $a = \frac{0.05}{1-0.05}b, b = p$ and σ^2 is set fixed to 1.

Software and runtime optimizations

$SSLPRS$ was implemented mainly in `Python`, except expensive computations in the coordinate ascent algorithm, which was implemented using the compiled language via the `Cython` interface for compatibility and optimal efficiency. We also employed similar optimization strategies used in $VIPRS$ (Zabad et al., 2023, 2025), including q-factors to access the LD matrix only once per iteration (Details can be found in Supplemental methods section S3.3). We also introduced parallelism in the form of multi-threading across SNP updates in the main coordinate ascent loop (Algorithm 1), which improves overall inference time by multi folds. To reduce overall model peak memory usage, we introduced a low memory mode, which reduces storage requirements by more than a factor of two by storing only the upper-triangular part of the symmetric LD matrix. Further memory optimizations were achieved through floating point quantization to integer representation, minimizing memory footprint for each entry of the LD while having a minimal impact on performance (Zabad et al., 2025).

A major model specific efficiency optimization we introduced leverages $SSLPRS$' ability to produce exactly sparse effect size estimates. For the subset of β_j coefficients that are identical after the update, we skip expensive computations such as q-factor updates that wouldn't have had any effects on the model parameters. (Supplemental methods section S3.3). This greatly speeds up the time per iteration of the coordinate ascent algorithm, especially for large λ_1 penalty values, where many of the effect sizes are shrunk to zero.

Baseline models and their specifications

To assess the relative performance of the $SSLPRS$ model on real GWAS data, we compared it to two state-of-the-art PRS inference methods: `Lassosum` (Mak et al., 2017) and $VIPRS$ (Zabad et al., 2023). Similar to $SSLPRS$, both methods use coordinate-wise optimization for inference, but they differ in the priors on the effect size as well as their inference strategies. The $LASSO$ uses a single Laplace density, i.e. ℓ_1 penalty, on the effect sizes and performs coordinate ascent on the penalized loglikelihood to estimate the coefficients. $VIPRS$, on the other hand, assigns a Gaussian Spike-and-slab prior on the effect size and uses Coordinate Ascent Variational Inference (CAVI) to approximate the posterior for the effect sizes. As stated previously, theoretically, the SSL can interpolate between these two priors by adjusting its hyperparameters (Ročková and George, 2018), and thus comparing it to these two models in particular can shed light on its statistical and computational properties.

To ensure consistent and fair comparisons across the three models, we used our own optimized implementation of the `Lassosum` model (Mak et al., 2017), as provided in the open source software package `penprs v0.0.1`. By default, the $LASSO$ model performs coordinate ascent inference using the pathwise algorithm (Friedman et al., 2010). For all the experiments, we used a grid of 20 values for the penalty hyperparameter λ, ranging from λ_{max} to $10^{-3}\lambda_{max}$ on a $\log_2$ scale. The coordinate-ascent inference step was parallelized across four threads similar to $SSLPRS$.

For the $VIPRS$ method (Zabad et al., 2023, 2025), we tested the standard EM algorithm that does not require any hyperparameter tuning as well as a Grid Search ($VIPRS$-GS) version that tunes the hyperparameter π, which corresponds to the prior mean on the proportion of causal variants. We used a 20 point grid for π on a $\log_{10}$ scale from 1^{-p} to $1 - 1^{-p}$, where p is the number of variants used during inference. In our experiments, we used the latest version of the software `VIPRS v0.1.3`, which includes optimized and parallel coordinate ascent inference algorithms. The software was run with four threads.

UK Biobank data

Real phenotype analyses

To empirically examine the performance of the *SSLPRS* model on real complex traits and diseases, we leveraged paired genotype and phenotype data from 337 205 unrelated White British samples in the UK Biobank (Bycroft et al., 2018). The data pre-processing and Quality Control (QC) pipeline were described in detail in earlier reports by the same group (Zabad et al., 2023, 2025) and we briefly summarize below.

The genotype data, which represents the features used for prediction, was extracted by applying standard quality control filters along the sample and variant dimensions. For the samples, in addition to filtering to unrelated White British individuals, we excluded samples with sex chromosome aneuploidy or missing genotype call rate exceeding 5%. The genetic variants were filtered to retain variants in the HapMap3 reference panel (Altshuler et al., 2010), while excluding markers with minor allele count (MAC) <5, minor allele frequency (MAF) <0.1%, imputation score <0.3, Hardy-Weinberg Equilibrium p-value $<10^{-10}$, or genotype missingness rate exceeding 5%. Furthermore, we removed variants with duplicated `rsID`s, ambiguous strand, or those found in long-range LD regions (Zabad et al., 2023). This resulted in a set of 1 093 308 high quality SNPs that we used in subsequent analyses. Most of these filtering steps were done with `plink2` (Chang et al., 2015).

For the complex traits, which represent the target of our predictors, we extracted measurements for nine quantitative phenotypes for the White British samples described earlier. The phenotypes are standing height (HEIGHT), body mass index (BMI), hip circumference (HC), waist circumference (WC), birth weight (BW), Forced Vital Capacity (FVC), Forced Expiratory Volume in the first second (FEV1), High-density Lipoprotein (HDL), and Low-density Lipoprotein (LDL). Each phenotype was pre-processed by removing outliers (z-score >5), and then within each sex separately, the phenotype was adjusted for age, sex, and 10 Principal Components (PCs) of the genotype matrix. As a final step, we applied the Rank-based Inverse Normal Transform (RINT) to ensure that the distribution of the phenotype is approximately Gaussian.

To facilitate robust analyses of the predictive performance of the *SSLPRS* and baseline models, we performed 5-fold cross-validation per phenotype. In each round, 80% of the data was used for training the models while the remaining 20% are used for testing; the training set was further split into 90% training and 10% validation for models requiring hyperparameter tuning. Since our methods use GWAS summary data to perform PRS inference, we performed genome-wide association testing within each split and generated GWAS summary statistics for the training, validation, and test sets. The 5-fold cross-validation GWAS data are available at `https://zenodo.org/records/14612130`. The association testing within each split was done with `plink2` (Chang et al., 2015).

Finally, for the Linkage-Disequilibrium (LD) matrices used to record pairwise correlations between genetic variants, we utilized LD matrices for European samples published in a recent study (Zabad et al., 2025), where they served as input to PRS inference methods: `https://shz9.github.io/viprs/download_ld/`. The matrices were estimated from 362 446 unrelated European samples in the UK Biobank (Bycroft et al., 2018).

Simulation experiments

To assess the variable selection performance and capabilities of the *SSLPRS* model under controlled conditions, we used the `magenpy v0.1.5` package (Zabad et al., 2023, 2025) to simulate phenotype data for the UKB participants described above according to a variety of genetic architectures. The phenotypes were simulated using heritability values $h^2 = \{0.1, 0.3, 0.5\}$, and causal proportion of variants $\theta = \{0.01, 0.001, 0.0001\}$, for a total of 9 simulation settings. Note that the `magenpy` simulator draws effect sizes according to the Gaussian spike-and-slab generative model (Zabad et al., 2023). For each setting, we simulated five independent replicates, for a total of 45 simulated phenotypes. The `magenpy` simulator outputs the true causal variants and their effect sizes, and this information was used to examine the variable selection accuracy of each method.

To examine predictive performance in the simulation experiments, the UKB samples were split into 70% training, 15% validation, and 15% testing. The validation set was used for hyperparameter tuning of the grid search (GS) models. These sub-cohorts were then used to perform GWAS using `plink2` (Chang et al., 2015) to obtain marginal association statistics.

Evaluation metrics and criteria

We evaluated the *SSLPRS* and baseline models based on a number of metrics that account for both computational and statistical performance. The statistical evaluation criteria include prediction accuracy on held-out test sets as well as a number of metrics that quantify variable selection accuracy. In the context of our simulation analyses, the latter includes metrics such as precision ($\frac{TP}{TP+FP}$), recall ($\frac{TP}{TP+FN}$), and the Matthews Correlation Coefficient (Ročková and George, 2018),

$$MCC = \frac{TP \cdot TN - FP \cdot FN}{\sqrt{(TP+FP)(TP+FN)(TN+FP)(TN+FN)}}$$

which accounts for all confusion matrix components and thus offers a balanced measure of selection accuracy. Here, TP refers to true positives, TN true negatives, FP false positives, and FN false negatives. For Bayesian models, to examine variable selection performance, we applied the median rule and selected variants whose Posterior Inclusion Probability (PIP) is greater than 0.5 (Ishwaran and Rao, 2005).

To assess the biological significance and replicability of the selected variants, we measure the fold enrichment, defined as

$$\text{Fold Enrichment} = \frac{\frac{\text{Number of selected variants in annotation}}{\text{Total number of variants in annotation}}}{\frac{\text{Number of selected variants overall}}{\text{Total number of variants overall}}}$$

for quantifying the relative concentration of selected variants within a specific annotation compared to their prevalence in the overall background, and the replication rate, which is the proportion of selected variants that is also considered significant in an separate, independent study.

To quantify predictive performance, we report prediction accuracy in terms of the proportion of variance explained (R-squared). Given a set of inferred coefficients $\boldsymbol{\beta}^*$, the R-Squared on the held-out test set can be approximated from GWAS summary statistics via the pseudo-R^2 metric (Mak et al., 2017; Zabad et al., 2023):

$$\text{pseudo-}R^2 = 2\boldsymbol{\beta}^{*\top}\widehat{\boldsymbol{\beta}}_{test} - \boldsymbol{\beta}^{*\top}\widehat{\boldsymbol{R}}_{test}\boldsymbol{\beta}^* \tag{13}$$

Where $\widehat{\boldsymbol{\beta}}_{test}$ are the standardized marginal GWAS effect sizes from the test set and $\widehat{\boldsymbol{R}}_{test}$ is the corresponding LD matrix.

This metric is implemented in the software package `viprs v0.1.3`.

In addition to these statistical performance metrics, we examined total wallclock time (in minutes), peak memory utilization (in MB), and inference time (in seconds). Total wallclock time includes the time to load the GWAS and LD data, perform harmonization, load software dependencies, perform inference, and finally conduct cross-validation for model selection (Zabad et al., 2025). Peak memory utilization records the maximum amount of Random Access Memory (RAM) used throughout the lifetime of the program in Megabytes. Finally, inference/fit time records the number of seconds it takes to reach convergence using the coordinate-ascent inference procedure.

Results

Simple simulation study

To illustrate the properties of the SSL prior, we designed a simple simulation experiment similar to the setup presented by (Bai et al., 2021), visually illustrated in Figure 1c. A sample of $N = 50$ with $p = 24$ SNPs was taken. The genotype matrix follows a multi-variate Gaussian $\boldsymbol{X} \sim \mathcal{N}_p(0, \boldsymbol{\Sigma})$, and to approximate tight LD blocks, the covariance matrix was constructed by aggregating 8 highly correlated 3x3 blocks $\boldsymbol{\Sigma} = \{\sigma_{ij}\}_{i,j=1}^{3}$, $\sigma_{ij} = 0.95$ if $i \neq j$ and $\sigma_{ii} = 1$. 8 causal variants were distributed across the 8 tight LD blocks, and the remaining variants are designated to be non-causal. Variants have effect sizes of ± 1.5 on the phenotype $\boldsymbol{y}$, which was simulated following the linear model: $\boldsymbol{y} \sim \mathcal{N}_n(\boldsymbol{X}\boldsymbol{\beta}, \boldsymbol{I})$.

Fitting $SSLPRS$ on this simulated data with an increasing λ_0 ladder through warm-start reveals the model's ability to simultaneously perform variable selection and stable effect size estimation, i.e. the effects of selected variants are held steady and the rest are shrunk to zero (Figure. 1d). Despite the tight correlation structure, $SSLPRS$ performs well across the ladder in variable selection in terms of MCC. (Figure. 1f). In contrast, the $LASSO$ exhibits the issue of over-shrinking effects with increasing penalization(Figure 1e), which in turn also leads to unstable and degraded variable selection performance across the ladder.

Simulation of UK Biobank data

To evaluate variable selection and predictive capabilities under diverse genetic architectures, we conducted a 5-replicate analysis on each of the 9 simulation settings (Section 2.6.2). In these analyses, the base $SSLPRS$ model is compared to its grid-search version $SSLPRS$-GS and the baseline models in Section 2.5. As the VIPRS models do not provide exact sparse estimates, the median rule (Ishwaran and Rao, 2005) is used, where Variants with a posterior inclusion probability (PIP) exceeding 0.5 were considered as selected.

To illustrate the variable selection behavior of $SSLPRS$ and $LASSO$ across the λ_0 ladder, we first focus on chromosome 1 of the balanced $h^2 = 0.3, \theta = 0.001$ setting. In Figure 2, a tradeoff between the precision and recall emerges as λ_0 increases. In the earlier steps of the ladder, where the difference between λ_0 and λ_1 is marginal, $SSLPRS$ remains effectively in the LASSO regime — yielding good recall, but suboptimal precision due to over-selection (Zhao and Yu, 2006). As $SSLPRS$ warm-starts through the ladder, negligible coefficients are progressively shrunk to zero, and significant variants are retained with increasing confidence. This leads to a substantial gain in

Fig. 2. Variable selection performance across the λ_0 ladder under simulation setting of $h^2 = 0.3, \theta = 0.001$ on chromosome 1. Three variable selection metrics are shown in different colors: Precision (green), Recall (orange), Matthews Correlation Coefficient (MCC) (blue). The $LASSO$ trends are shown as dotted lines, whereas the $SSLPRS$ trends are shown as solid lines. For reference, the performance of the $VIPRS$ model on these same metrics are shown as horizontal dashed lines. The 20 ladder steps of are indicated as scatter points. The vertical dotted cyan or purple line shows the grid-search-selected λ_0 or λ by $SSLPRS$ or $LASSO$ respectively, annotated as "GS_λ" or "GS_λ_0".

precision, but a decrease in recall. While $LASSO$ exhibits a similar tradeoff, the absence of a stabilizing slab results in a sharp deterioration of recall without a commensurate increase in precision. Notably, the λ_0 selected by $SSLPRS$-GS and $LASSO$, which is coincidentally the same in this case, occurs earlier in the ladder, optimizing pseudo-R^2 but may not yield the best variable selection in terms of MCC. As a result, $SSLPRS$, which warm-starts to the end of the ladder, achieves superior overall performance with respect to MCC compared to baseline models.

We now extend this analysis to the 45 simulated phenotypes across 9 different genetic architecture to assess the robustness of these findings. The 5-replicate results are shown in Figure 3. Across all settings, $SSLPRS$ exhibits lower recall but substantially higher precision compared to $LASSO$ and $SSLPRS$-GS. This difference arises because $SSLPRS$ selects variants at the end of the λ_0 ladder, resulting in fewer but more confidently identified causal variants. In contrast, the grid-search based $LASSO$ and $SSLPRS$-GS typically select lower penalty values, leading to broader but less precise variant selection. Compared to the $VIPRS$ models, $SSLPRS$ achieves better precision and recall across nearly all settings, possibly from the benefit of the warm-start exploration search space. Overall, $SSLPRS$ performs a balanced variant selection, resulting in a superior MCC performance across most settings. Though, in the less sparse settings ($\theta = 0.01$), causal variants are more numerous but have smaller effect sizes, especially under low heritability. Although, $SSLPRS$ has slightly lower but still competitive MCC compared to the best performing model in these challenging polygenic settings, it still achieves high precision among the models.

In terms of predictive performance, Figure 3 reveals that in the polygenic ($\theta = 0.01$) scenario, $SSLPRS$-GS is more robust in terms of predictive performance compared to $SSLPRS$. $SSLPRS$-GS achieves pseudo-R^2 scores that are

Fig. 3. Variable selection and predictive performance of summary statistics-based PRS methods on simulated phenotypes with different genetic architectures. Performance is evaluated using four metrics: Precision (top-left), Recall/sensitivity (top-right), Matthews correlation coefficient (MCC, bottom-left), and pseudo-R^2 (prediction accuracy, bottom-right) on held-out test set. The simulation configurations span three heritability settings, $h^2 = \{0.1, 0.3, 0.5\}$, and three proportions of causal variants, $\theta = \{0.01, 0.001, 0.0001\}$. Five summary statistics-based PRS methods are included in this figure: *LASSO*, our proposed *SSLPRS* and *SSLPRS-GS* (grid search), as well as *VIPRS* and *VIPRS-GS* (grid search). Bars represent the mean value over 5 independent replicates. The black vertical lines denote the standard error across the replicates. For the variable selection metrics, the median rule was applied for the *VIPRS* models, where variants with Posterior Inclusion Probability (PIP) > 0.5 were considered as selected.

comparable to or exceed those of the baseline models. Notably, *SSLPRS-GS* is either on-par or outperforms *LASSO* in all settings. While *SSLPRS* performs well in variable selection,

Fig. 4. Predictive performance of summary statistics-based PRS methods on real quantitative phenotypes in the UK Biobank. Prediction accuracy (Pseudo R^2) on held-out test sets in an analysis of 9 quantitative phenotypes: standing height (HEIGHT), high-density lipoprotein (HDL), body mass index (BMI), forced vital capacity (FVC), forced expiratory volume in 1 s (FEV1), hip circumference (HC), waist circumference (WC), low-density lipoprotein (LDL), and birth weight (BW). The bars represent the average model performance based on 5-fold cross-validation, with black vertical lines indicating the associated standard errors. Four summary statistics-based PRS models are shown with different colors: *LASSO*, our proposed *SSLPRS-GS* (grid search), *VIPRS*, *VIPRS-GS* (grid search).

incorporating grid search may further enhance predictive performance, particularly in complex genetic architectures where optimization of pseudo-R^2 should be optimized

Real phenotype analysis in the UK Biobank

To examine the predictive performance of the *SSLPRS* model on real data, we conducted a 5-fold cross-validation analysis on 9 quantitative phenotypes from the UK Biobank (Bycroft et al., 2018). In these analyses, we focused on *SSLPRS-GS*, for the best *SSLPRS* performance, and was compared to the main baseline models (Section 2.5).

Our results show that across all the phenotypes examined, *SSLPRS-GS* shows competitive prediction accuracy compared to the baseline models (Figure 4). Small, but significant differences between the models are observed for some of the phenotypes, such as standing height, where models that use grid search to tune their hyperparameters outperform the EM version of *VIPRS* by up to 10%. Interestingly, the only phenotype where *SSLPRS-GS* significantly outperforms the *LASSO* is for LDL cholesterol (Figure 4), a trait that is known to be modulated by some large effect variants (Graham et al., 2021). This may be a case where bias due to excessive shrinkage hurts the performance of the *LASSO*, as discussed earlier.

Enrichment and replication of selected variants

To assess the biological relevance of selected variants, we evaluated the functional enrichment across 39 genomic annotations (Finucane et al., 2015) and replicability in large-scale GWAS studies. Figure 5b reveals that top performing models in variable selection scenarios, *SSLPRS* and *VIPRS*,

exhibit substantial fold-enrichment in some of the biological annotations typically used in partitioning trait heritability (Finucane et al., 2015). Notably, the variants are most enriched in non-synonymous sites, altering amino acid sequence and thus protein function in lipid-regulating genes, and regulatory elements such as promoters and enhancers, underscoring their functional relevance for traits such as HDL and LDL.

To see if selected variants are replicated in large-scale GWAS analyses, we examined summary statistics provided by the Global Lipids Genetics Consortium (GLGC) (Graham et al., 2021), with samples sizes exceeding 1.6 million. We assumed that significant associations reported by that study (p-values $< 5 \times 10^{-8}$) as our reference and examined how many of our selected variants from the UK Biobank data are replicated in that larger study. Figure 5b reveals that a substantial proportion of selected variants attain genome-wide significance in the GLGC meta-analysis; *SSLPRS* exhibits the highest replication rate, followed by *VIPRS* in both the LDL and HDL traits. The number of selected, significant, and replicated variants for each model across the 5-folds can be found in Supplemental Table S2.1.

Scalability and computational performance

To assess the computational performance of *SSLPRS*, we compared our summary statistics implementation of *SSL* to the individual-level R-based `SSLASSO` by the original authors (Ročková and George, 2018). Both implementations were benchmarked on identical subsets of chromosome 22 (16 296 SNPs) from the UK Biobank standing-height data, across sample sizes $n \in \{10000, 25000, 50000\}$, and SNP counts $p \in \{5000, 10000, 16296\}$. For each (n, p) combination, we recorded the total inference time and peak memory usage, across the default *SSLPRS* warm-start ladder (Section 2.3.1). As seen in Table 3.5, across all settings, *SSLPRS* had an average inference time of 5.3 s and peak memory usage of 73 MB, whereas the original individual-level *SSL* required 22.4 min and 4100 MB, respectively. Notably, our summary statistics implementation maintained near-constant inference time as sample size increased, and scaled efficiently with growing SNP counts. In contrast, the individual-level `SSLASSO` exhibits approximately linear scaling of inference time and peak memory usage as sample size or SNP count increases. These results underscore a significant improvement in computational efficiency and scalability through summary statistics and optimizations. A comprehensive comparison between *SSLPRS* and the baseline summary statistics models regarding computational performance are present in Supplementary Figure S1.5.

Discussion

In this work, we presented the novel PRS method *SSLPRS* for sparse and accurate prediction of complex traits from GWAS summary data. Our experiments on real and simulated traits show that *SSLPRS* excels in terms of variable selection performance and is competitive with state-of-the-art methods in prediction accuracy. Through its dynamic posterior exploration with the mode-targeted MAP coordinate ascent algorithm, *SSLPRS*'s performance is complemented by its ability to produce truly sparse effect size estimates — retaining biologically significant variants without excessive shrinkage. In addition *SSLPRS* comes with fast, memory-efficient, and highly scalable algorithms for genome-wide inference, available in `penprs v0.0.1`. Overall, we believe that *SSLPRS* provides

(a)

(b)

Fig. 5. Functional enrichment and biological relevance of selected variants in real complex trait analyses. (a) Heatmap of fold enrichment, defined as the ratio between the proportion of selected SNPs in a given annotation and the background proportion of all SNPs in that annotation. Enrichments are shown across 39 functional annotations (x-axis), stratified by model (left y-axis) and trait (right y-axis). (b) Replication rate of selected variants during training on UK Biobank data for high- and low-density lipoprotein (HDL and LDL) phenotypes in the Global Lipids Genetics Consortium (GLGC) meta-analysis. Replication is defined in terms of the variants being significantly associated with the phenotype (p-value $< 5 \times 10^{-8}$) in the GLGC. Bars represent mean replication rate across the 5-fold cross-validation analyses. Black vertical bars represent standard errors across the 5 folds. Five summary statistics-based PRS methods are included in this figure: *LASSO*, our proposed *SSLPRS* and *SSLPRS-GS* (grid search), as well as *VIPRS* and *VIPRS-GS* (grid search). For Bayesian models like *VIPRS*, the median rule was applied for variable selection, retaining only variants with Posterior Inclusion Probability (PIP) > 0.5.

effective analytical tools for predicting and understanding the genetic underpinnings of complex traits and diseases.

n	p	SSLPRS		SSL individual	
		Time (s)	PMU (MB)	Time (s)	PMU(MB)
10000	5000	3.10	56.4	259.03	961.8
10000	10000	5.76	72.6	561.53	1934.3
10000	16296	10.11	89.9	864.93	3139.6
25000	5000	2.29	56.4	673.22	2389.3
25000	10000	3.88	72.6	1409.36	4777.2
25000	16296	7.48	89.8	2667.05	6236.3
50000	5000	1.85	56.4	1419.00	4763.8
50000	10000	3.92	72.6	3098.53	9530.0
50000	16296	5.00	89.9	4269.00	12503.7
Average	–	5.29	72.95	1343.2	4099.3

Table 1. Comparison of inference time (seconds) and peak memory usage (PMU, MB) between summary statistics-based *SSLPRS* and individual-level `SSLASSO` implementation in `R/Rcpp` (Ročková and George, 2018). We compare computational performance while varying sample sizes (n) in the UK Biobank and number of variants (p) on chromosome 22.

Competing interests

None declared.

Acknowledgments

We thank members of the Li lab for their feedback and comments on earlier iterations of this work. Y.L. is supported by Canada Research Chair (Tier 2) in Machine Learning for Genomics and Healthcare (CRC-2021-00547) and Natural Sciences and Engineering Research Council (NSERC) Discovery Grant (RGPIN-2016-05174). This research used the NeuroHub infrastructure and was undertaken thanks in part to funding from the Canada First Research Excellence Fund, awarded through the Healthy Brains, Healthy Lives initiative at McGill University. This research was enabled in part by support provided by Calcul Québec and the Digital Research Alliance of Canada. This research has been conducted using the UK Biobank Resource under Application Number 45551.

References

David M. Altshuler, Richard A. Gibbs, Leena Peltonen, Stephen F. Schaffner, and et al. Integrating common and rare genetic variation in diverse human populations. *Nature*, 467, 2010. ISSN 14764687. doi: 10.1038/nature09298.

Ray Bai, Veronika Ročková, and Edward I George. Spike-and-slab meets lasso: A review of the spike-and-slab lasso. *Handbook of Bayesian variable selection*, pages 81–108, 2021.

Clare Bycroft, Colin Freeman, Desislava Petkova, Gavin Band, Lloyd T. Elliott, Kevin Sharp, Allan Motyer, Damjan Vukcevic, Olivier Delaneau, Jared O'Connell, Adrian Cortes, Samantha Welsh, Alan Young, Mark Effingham, Gil McVean, Stephen Leslie, Naomi Allen, Peter Donnelly, and Jonathan Marchini. The uk biobank resource with deep phenotyping and genomic data. *Nature*, 562, 2018. ISSN 14764687. doi: 10.1038/s41586-018-0579-z.

Christopher C. Chang, Carson C. Chow, Laurent C.A.M. Tellier, Shashaank Vattikuti, Shaun M. Purcell, and James J. Lee. Second-generation plink: Rising to the challenge of larger and richer datasets. *GigaScience*, 4, 2015. ISSN 2047217X. doi: 10.1186/s13742-015-0047-8.

Hilary K. Finucane, Brendan Bulik-Sullivan, Alexander Gusev, Gosia Trynka, Yakir Reshef, Po Ru Loh, Verneri Anttila, Han Xu, Chongzhi Zang, Kyle Farh, Stephan Ripke, Felix R. Day, Shaun Purcell, Eli Stahl, Sara Lindstrom, John R.B. Perry, Yukinori Okada, Soumya Raychaudhuri, Mark J. Daly, Nick Patterson, Benjamin M. Neale, and Alkes L. Price. Partitioning heritability by functional annotation using genome-wide association summary statistics. *Nature Genetics*, 47, 2015. ISSN 15461718. doi: 10.1038/ng.3404.

Jerome H. Friedman, Trevor Hastie, and Rob Tibshirani. Regularization paths for generalized linear models via coordinate descent. *Journal of Statistical Software*, 33 (1):1–22, 2010. doi: 10.18637/jss.v033.i01. URL `https://www.jstatsoft.org/index.php/jss/article/view/v033i01`.

Tian Ge, Chia Yen Chen, Yang Ni, Yen Chen Anne Feng, and Jordan W. Smoller. Polygenic prediction via bayesian regression and continuous shrinkage priors. *Nature Communications*, 10, 2019. ISSN 20411723. doi: 10.1038/s41467-019-09718-5.

Sarah E. Graham, Shoa L. Clarke, Kuan-Han H. Wu, Stavroula Kanoni, Greg J. M. Zajac, and Shweta et al. Ramdas. The power of genetic diversity in genome-wide association studies of lipids. *Nature*, 600(7890):675–679, 2021. doi: 10.1038/s41586-021-04064-3. URL `https://doi.org/10.1038/s41586-021-04064-3`.

Hemant Ishwaran and J Sunil Rao. Spike and slab variable selection: frequentist and bayesian strategies. *The Annals of Statistics*, 33(2):730–773, 2005.

Gareth James, Daniela Witten, Trevor Hastie, and Robert Tibshirani. *Introduction to Statistical Learning with Applications in R*, volume 11. Springer, 2019.

Dovini Jayasinghe, Setegn Eshetie, Kerri Beckmann, Beben Benyamin, and S. Hong Lee. Advancements and limitations in polygenic risk score methods for genomic prediction: a scoping review. *Human Genetics*, 2024. doi: 10.1007/s00439-024-02716-8. URL `https://doi.org/10.1007/s00439-024-02716-8`.

Konrad J. Karczewski, Rahul Gupta, Masahiro Kanai, and et al. Pan-uk biobank gwas improves discovery, analysis of genetic architecture, and resolution into ancestry-enriched effects. *medRxiv*, 2024. doi: 10.1101/2024.03.13.24303864. URL `https://www.medrxiv.org/content/early/2024/03/15/2024.03.13.24303864`.

Cathryn M. Lewis and Evangelos Vassos. Polygenic risk scores: From research tools to clinical instruments. *Genome Medicine*, 12, 2020. ISSN 1756994X. doi: 10.1186/s13073-020-00742-5.

Luke R. Lloyd-Jones, Jian Zeng, Julia Sidorenko, Loïc Yengo, Gerhard Moser, Kathryn E. Kemper, Huanwei Wang, Zhili Zheng, Reedik Magi, Tõnu Esko, Andres Metspalu, Naomi R. Wray, Michael E. Goddard, Jian Yang, and Peter M. Visscher. Improved polygenic prediction by bayesian multiple regression on summary statistics. *Nature Communications*, 10, 2019. ISSN 20411723. doi: 10.1038/s41467-019-12653-0.

Timothy Shin Heng Mak, Robert Milan Porsch, Shing Wan Choi, Xueya Zhou, and Pak Chung Sham. Polygenic scores via penalized regression on summary statistics. *Genetic epidemiology*, 41(6):469—480, September 2017. ISSN 0741-0395. doi: 10.1002/gepi.22050. URL `https://www.biorxiv.org/content/biorxiv/early/2017/03/22/058214.full.pdf`.

Gemma E. Moran, Veronika Ročková, and Edward I. George. Variance prior forms for high-dimensional bayesian variable selection. *Bayesian Analysis*, 14(4):1091–1119, December 2019. doi: 10.1214/19-BA1149.

Oliver Pain, Kylie P. Glanville, Saskia P. Hagenaars, Saskia Selzam, Anna E. Fürtjes, Héléna A. Gaspar, Jonathan R. I. Coleman, Kaili Rimfeld, Gerome Breen, Robert Plomin, Lasse Folkersen, and Cathryn M. Lewis. Evaluation of polygenic prediction methodology within a reference-standardized framework. *PLOS Genetics*, 17(5):1–22, 05 2021. doi: 10.1371/journal.pgen.1009021. URL `https://doi.org/10.1371/journal.pgen.1009021`.

Bogdan Pasaniuc and Alkes L. Price. Dissecting the genetics of complex traits using summary association statistics. *Nature Reviews Genetics*, 18, 2017. ISSN 14710064. doi: 10.1038/nrg.2016.142.

Florian Privé, Julyan Arbel, and Bjarni J. Vilhjálmsson. Ldpred2: Better, faster, stronger. *Bioinformatics*, 36, 2020. ISSN 14602059. doi: 10.1093/bioinformatics/btaa1029.

Veronika Ročková and Edward I. George. The spike-and-slab lasso. *Journal of the American Statistical Association*, 113 (521):431–444, 2018. doi: 10.1080/01621459.2016.1260469.

Ali Torkamani, Nathan E. Wineinger, and Eric J. Topol. The personal and clinical utility of polygenic risk scores. *Nature Reviews Genetics*, 19, 2018. ISSN 14710064. doi: 10.1038/s41576-018-0018-x.

Shadi Zabad, Simon Gravel, and Yue Li. Fast and accurate bayesian polygenic risk modeling with variational inference. *The American Journal of Human Genetics*, 110(5):741–761, 2023. ISSN 0002-9297. doi: https://doi.org/10.1016/j.ajhg.2023.03.009. URL `https://www.sciencedirect.com/science/article/pii/S0002929723000939`.

Shadi Zabad, Chirayu Anant Haryan, Simon Gravel, Sanchit Misra, and Yue Li. Towards whole-genome inference of polygenic scores with fast and memory-efficient algorithms. *bioRxiv*, 2025. doi: 10.1101/2025.01.19.633789. URL `https://www.biorxiv.org/content/early/2025/01/22/2025.01.19.633789`.

Cun-Hui Zhang and Tong Zhang. A General Theory of Concave Regularization for High-Dimensional Sparse Estimation Problems. *Statistical Science*, 27(4):576 – 593, 2012. doi: 10.1214/12-STS399. URL `https://doi.org/10.1214/12-STS399`.

Qianqian Zhang, Florian Privé, Bjarni Vilhjálmsson, and Doug Speed. Improved genetic prediction of complex traits from individual-level data or summary statistics. *Nature Communications*, 12(1):4192, 2021. doi: 10.1038/s41467-021-24485-y. URL `https://doi.org/10.1038/s41467-021-24485-y`.

Peng Zhao and Bin Yu. On model selection consistency of lasso. *Journal of Machine Learning Research*, 7(90):2541–2563, 2006. URL `http://jmlr.org/papers/v7/zhao06a.html`.

Wei Zhou, Masahiro Kanai, Kuan-Han H. Wu, Humaira Rasheed, Kristin Tsuo, and et al. Global biobank meta-analysis initiative: Powering genetic discovery across human disease. *Cell Genomics*, 2(10):100192, 2022. ISSN 2666-979X. doi: https://doi.org/10.1016/j.xgen.2022.100192. URL `https://www.sciencedirect.com/science/article/pii/S2666979X22001410`.