Optimizing the Clinical Application of Rheumatology Guidelines Using Large Language Models: A Retrieval-Augmented Generation Framework Integrating ACR and EULAR Recommendations

Alfredo Madrid-García[1,§,*], Diego Benavent[2,3,§], Beatriz Merino-Barbancho[4,†,*], Dalifer Freites-Núnez[5,†]

[1] No affiliation

[2] Rheumatology Department, Hospital Universitari de Bellvitge, Barcelona, Spain

[3] Medical Department, Savana Research SL, Madrid, Spain

[4] Escuela Técnica Superior de Ingenieros de Telecomunicación. Universidad Politécnica de Madrid. Avenida Complutense, Madrid, Spain

[5] Grupo de Patología Musculoesquelética. Hospital Clínico San Carlos. Instituto de Investigación Sanitaria San Carlos (IdISSC), Madrid, Spain

§ Have contributed equally

† Have contributed equally

* Corresponding author details:

Alfredo Madrid García, PhD.

e-mail: alfredo.madrid.garcia@alumnos.upm.es

Beatriz Merino Barbancho, PhD.

Universidad Politécnica de Madrid

Escuela Técnica Superior de Ingenieros de Telecomunicación. Universidad Politécnica de

Madrid, Avenida Complutense, 30, Madrid, 28040, Spain

e-mail: bmerino@lst.tfo.upm.es

ORCiD

Alfredo Madrid García: 0000-0002-1591-0467

Beatriz Merino-Barbancho: 0000-0001-5070-4178

Diego Benavent: 0000-0001-9119-5330

Dalifer Freites Nuñez: 0000-0002-0966-2778

Abstract (202 words)

Objectives:

To develop and evaluate a Retrieval-Augmented Generation (RAG) system integrating European Alliance of Associations for Rheumatology (EULAR) and American College of Rheumatology (ACR) guidelines to provide rheumatologists with timely, evidence-based recommendations at the point of care.

Methods:

EULAR and ACR and management guidelines were selected by rheumatologists according to relevance to clinical decision making, processed, and chunked. A RAG system using *LangChain* framework, voyage-3 embedding model, and a *Qdrant* vector database was implemented. Answers to 740 guideline-specific questions were generated by ChatGPT-o3-mini with context retrieval (RAG) and without (baseline). Performance was evaluated using an LLM-as-a-judge (Gemini 2.0 Flash) assessing factual accuracy, safety, completeness, faithfulness, and preference, with Wilcoxon signed-rank and Binomial tests for statistical significance.

Results:

After agreement, 74 guidelines were included. The RAG-based system received consistently higher or comparable medians than the baseline across all criteria, relevance, factual accuracy, safety, completeness and conciseness (p<0.001). Moreover, the RAG-based system was significantly preferred by the LLM-judge in 92.8% of comparisons (p<0.001).

Conclusion:

This study demonstrates the successful development and validation of a RAG system integrating extensive ACR/EULAR guidelines. The system significantly improves answer quality compared to a baseline LLM, providing a promising foundation for reliable, AI-driven clinical decision support tools in rheumatology to enhance guideline adherence.

Graphical abstract

Key words: Retrieval augmented generation, large language models, rheumatology, clinical guidelines, clinical decision support system, artificial intelligence

Key messages:

- Large language models, combined with EULAR and ACR guidelines, may enhance rheumatology clinical decision support.

- Retrieval augmented generation (RAG) responses showed significantly greater accuracy, safety and completeness than baseline LLMs.

- RAG is a promising architecture for reducing hallucinations and providing grounded, reliable answers.

Introduction

Large language models (LLMs) have emerged as a key component of modern generative artificial intelligence (AI). These models, trained on extensive text corpora, leverage advanced natural language processing (NLP) techniques to generate human-like text, positioning them as essential tools in various disciplines, including medicine [1–3] .

Over the past years, LLMs have experienced growth in size, capability, availability, context window, and cost-efficiency. In parallel, advanced reasoning models integrating multimodal inputs and enhanced contextual awareness have emerged, further broadening the scope of their applications [4,5]. LLMs have demonstrated their capacity to generate coherent responses to free-text queries, even when not explicitly trained for specific tasks. Their adaptability makes them attractive candidates for applications in clinical practice, ranging from differential diagnosis support to the synthesis of structured medical reports. Moreover, Agents integrating these advancements are now capable of performing sophisticated, autonomous tasks across diverse sectors [6].

These advances have catalysed interest among medical professionals, particularly in fields requiring extensive textual interpretation and with wide practice pattern variation, such as rheumatology [7]. To manage this inherent complexity and strive for standardized, evidence-based care, the field places significant emphasis on the use of clinical guidelines that incorporate the diverse expertise and perspectives of multiple stakeholders, to promote consistent decision-making. Therefore, these clinical guidelines issued by entities like the European Alliance of Associations for Rheumatology (EULAR) and the American College of Rheumatology (ACR) play a key role in guiding complex treatment decisions.

Nevertheless, LLMs associated challenges remain. A key limitation of current LLMs is their tendency to generate "hallucinations"—plausible yet inaccurate or misleading information, a particularly concerning issue in clinical settings where erroneous outputs could impact patient safety [8]. Medical hallucinations pose a critical challenge by using plausible-sounding clinical language and domain-specific terminology to hide errors in diagnostics, treatment planning, and test result interpretation—areas where mistakes can have immediate consequences [9]. Their coherent logic makes these inaccuracies difficult to spot without expert scrutiny, and

unrecognized errors can delay proper treatment or misdirect care, especially in settings that increasingly rely on AI-generated recommendations.

Recent studies have demonstrated that while LLMs can assist in drafting patient information and generating preliminary clinical documentation, their outputs require meticulous human validation to ensure accuracy and reliability [10,11]. Within rheumatology, where diseases exhibit multifaceted clinical presentations, diagnostic and therapeutic decisions depend on synthesizing diverse data sources—clinical history, laboratory findings, imaging, and patient-reported outcomes—making the precision of AI-generated recommendations even more critical [12,13].

To mitigate these challenges, advanced methodologies such as retrieval-augmented generation (RAG) have been proposed [14]. RAG architectures enhance the accuracy of AI models by anchoring generative outputs to verified sources, thereby reducing the likelihood of hallucinations and improving clinical reliability [15,16]. Given these considerations, our study aims to develop and validate a novel RAG framework integrating ACR and EULAR recommendations. This framework is designed to facilitate the automated extraction and synthesis of key recommendations from complex guideline documents, aiding clinicians in making informed, evidence-based decisions. While clinical guidelines are essential for standardizing care and translating research into practice, their effective adoption by clinicians faces significant hurdles, including the time required to synthesize complex information. By providing rapid, synthesized, and context-specific access to guideline recommendations, we aim to bridge the gap between guideline availability and practical implementation, directly tackling the challenge of embedding evidence-based medicine into daily clinical decision-making, while reinforcing both the quality and consistency of care.

Primary objective

The primary objective of this study is to integrate ACR and EULAR rheumatology recommendations into a RAG system enabling clinicians to access timely, evidence-based recommendations at the point of care. By seamlessly merging established guidelines with LLMs, we aim to enhance clinical decision-making and improve adherence to best practices

in rheumatology. Hence, the solution proposed is intended to prove how RAG architectures and LLMs could assist the rheumatologist in its daily activities.

Retrieval-augmented generation

RAG is not a new concept [17]. However, only in recent years with the popularisation of LLMs, has it been widely adopted as a means to enhance LLM performance by integrating external knowledge sources into the generation process [18], RAG enables LLMs to access external knowledge bases and incorporate that information as context for generating grounded and factual responses. This approach offers several advantages: it allows the integration of proprietary and private data without additional training, produces more grounded responses mitigating medical hallucinations [9,19], and enables the use of up-to-date information beyond the model's training cutoff. Additionally, it enhances user trust by clearly indicating the sources from which the information was extracted increasing user's reliability. Various RAG architectures have been proposed in recent years, incorporating modifications to their different components [20]. A general RAG schema is shown in **Figure 1** and contains the following elements:

A) Retriever

1. Documents intended for storage in the vector database, which serve as contextual support for enhancing LLM-generated responses, undergo collection, processing, and chunking. The chunking step is crucial, as it facilitates more accurate alignment between user queries and relevant text segments, thereby reducing noise and filtering out irrelevant information. These text chunks are then converted into vector representations, subsequently stored and indexed within the vector database for efficient retrieval.

2. User queries submitted to the LLM are also embedded into vector representations using the same embedding model employed for document embedding, ensuring consistency and improving matching accuracy.

3. The vector representation of the user query is compared against vectors stored in the vector database through similarity search techniques, retrieving the k most similar document chunks relevant to the query.

B) Generator

4. An enhanced prompt is constructed by combining the user query and the retrieved chunks from the vector database. This prompt is then provided to

the LLM, enabling it to generate an informed and contextually grounded response.

Modifications to this schema leads to the different RAG architectures. However, all of them share the same core idea: to create a module that runs before the LLM is called that gets relevant textual data to enhance the answer.

RAG performance is determined by multiple factors, including the type of retrieved documents, the extent to which the system accurately recalls relevant content, the number of retrieved documents appended to the prompt, and the prompt design itself, among others. Recent work shows that distracting documents degrade performance while well-aligned documents and prompt techniques can boost correctness and confidence [21]. For instance, recently, Barnett at al. identified seven common failure points of RAG systems, underscoring that every component—from data preprocessing to chunking, retrieval, and final answer extraction—must be carefully designed [22].

To overcome some of these challenges different RAG architectures have been proposed in recent years [23–25].

In healthcare, RAG has gained considerable traction because it promotes equity, reliability, and personalization [14–16] Recently, a comprehensive introduction to RAG architecture in healthcare along with a detailed explanation of its underlying mechanisms was published by Ng et al [14] The authors highlighted how RAG can enhance both patient care (e.g., personalized discharge summaries) and pharmaceutical research (e.g., clinical trial screenings), demonstrating its versatility and impact across multiple medical domains.

Methods

1. Data selection

Two independent rheumatologists, DFN and DB, reviewed the full set of EULAR and ACR recommendations to identify those most relevant to clinical decision-making within a potential rheumatology clinical support system decision used during daily consultations. The list of available guidelines was extracted from EULAR [26] and ACR [27] websites, see **Supplementary Excel Initial List of Recommendations**. Initially, only the *Classification and diagnosis criteria/response criteria* and the *Recommendations for management* sections were considered. After agreement, the established consensus-based criteria followed for selecting the guidelines were:

- Classification criteria guidelines were excluded, as they were considered less relevant for specialized rheumatological practice.

- Guidelines targeting other healthcare professionals (e.g., nurses) or pediatric populations were excluded, as the system was designed to support adult rheumatologist consultations.

- To ensure clinical relevance and accuracy, only the most recent versions of each identified guideline were included, and outdated recommendations were excluded. The rationale was that new versions incorporate the most pertinent information from earlier iterations.

Upon completing the independent selection, the recommendations chosen by the two rheumatologists were compared, and any discrepancies were resolved by mutual agreement.

2. Data collection and processing

After selection, the agreed recommendations were retrieved in *.PDF* format (i.e., published scientific articles). Supplementary information from the recommendations was not retrieved. Various parsing tools were evaluated based on their ability to accurately and efficiently extract text from PDFs, and subsequently convert it into a machine-readable format, see **Supplementary Table 1**. Ultimately, *LlamaParse* was selected due to its performance, customizable options, and community support. The *LlamaParse* API was used, and the output

was downloaded in *markdown .md* format to preserve structural clarity and semantic sections. After download, a manual cleaning of the clinical recommendations was conducted: non-essential sections (e.g., references, affiliation listings) were manually removed to minimize noise and eliminate redundancy, the headings and subheadings were reviewed, and the tables and boxes were moved to the end. To preserve the figures' information an advanced reasoning model, *ChatGPT o1*, was employed to describe them. *Prompt A* was used, see **Table 1.**

The description of the figures was attached at the end of the markdown *.md* file. Once the guidelines were cleaned, *Prompt B* was used to automatically generate a set of 10 questions per recommendation—designed to simulate realistic user interactions— that later could be used for evaluating the RAG architecture. *ChatGPT 4.5* was employed for enhanced creativity. to simulate realistic user interactions

The generated questions were manually reviewed by DFN and DB, those out of the scope of the guideline were replaced with new ones (n = 14).

Moreover, PubMed metadata for each recommendation was retrieved using PubMed API and *E-utilities*. Metadata included the PMID, title, publication year, DOI, society (i.e., EULAR, ACR), authors, citation, first author, journal, create date, NIHMS ID, PMC, MeSH terms, and abstract.

LangChain served as the default framework for both experimentation and the development of the RAG architecture. Text-splitting (i.e., chunking) was guided by Markdown demarcations, ensuring a coherent segmentation of the guidelines -based on headings- for subsequent embedding. The rationale was that information grouped under specific headings is thematically cohesive, which in turn enhances retrieval accuracy and contextual relevance in downstream tasks. *UnstructuredMarkdownLoader* was used for that purpose. Finally, the length of the chunks was measured to ensure they fit within the context window.

3. Embeddings, vectorstore deployment and data ingestion

The chunked text was transformed into embeddings—numerical vector representations of words that capture their semantic properties in a continuous space—. The choice of the embedding model was guided by the *MTEB* (Massive Text Embedding Benchmark) leaderboard on *Hugging Face*, prioritizing models that demonstrated superior performance

on retrieval tasks. The final selection balanced factors such as accuracy, availability, domain relevance, embedding dimensionality, cost, and requests per minute. Consequently, *voyage-3* from Voyage AI—the second best performing embedding model in the MTEB and optimized for general-purpose and multilingual retrieval quality—was chosen. This model has a context length of 32,000 tokens and a 1024 embedding dimension.

All chunks, together with the PubMed metadata were subsequently vectorized using *voyage-3* and stored in *Qdrant* vector database, a scalable vector database capable of storing, indexing, and retrieving the guidelines chunks according to semantic similarity [28,29].

The vector database was deployed locally using *Docker*, enabling efficient retrieval of guideline segments. This setup ensured secure and rapid access without relying on external infrastructure.

4. Hybrid search

The RAG system was implemented via the *LangChain* framework. An initial similarity search was performed based on the user query to retrieve the top k=4 most relevant chunks, leveraging the semantic embeddings stored in *Qdrant*. In this process, dense embeddings were computed using *voyage-3*, while sparse embeddings were derived with BM25. Finally, only chunks with a similarity score above 0.5 were retained. The distance metric for quantifying the similarity between the user's questions and the vector embeddings was the cosine distance.

5. Answer generation

To generate concise, evidence-informed answers, *Prompt C* adapted from *LangChain* documentation was used. Moreover, a predefined schema was integrated into the answer generation step to present a list of sources including title, year and DOI, drawn from the retrieved guidelines. This schema ensured transparent attribution of the guidelines utilized in formulating the final answer, thus enhancing the trustworthiness of the system.

OpenAI API was used to generate the answers, and the chosen model was *ChatGPT o3-mini* (i.e., LLM_1). The rationale was that utilizing a reasoning model could provide enhanced answers both with and without the application of RAG. Additionally, costs were considered in

the selection of the model, balancing performance with affordability. Temperature parameter was not supported by this model.

6. System testing and evaluation

Different evaluation techniques have been proposed for RAG systems [30]. To evaluate the performance of the RAG system, the LLM-as-a-judge paradigm was used—where a LLM is prompted to act as a reviewer and quantitatively score the model-generated responses [31]. *Gemini 2.0 Flash* was the LLM used as a judge (i.e., LLM_2). The rationale behind choosing *Gemini 2.0 Flash* was based on its performance, reduced cost, and large context window, which was crucial to include all the required information. Moreover, *LangSmith* was used as the observability framework to monitor and trace the entire RAG pipeline execution, capturing intermediate steps such as document retrieval, prompt composition, and LLM outputs.

The evaluation was conducted in tree steps:

1. **Creation of answers with RAG:** *o3-mini* (LLM_1) was prompted, *Prompt C*, along with the set of questions previously generated by *ChatGPT-4.5*. In this configuration, relevant documents were retrieved and included as context in the prompt, allowing the model to generate grounded responses based on external information. Therefore, the input to the system consisted of the user question and the retrieved context.

2. **Creation of answers without RAG:** *o3-mini* (LLM_1) was prompted, *Prompt D*, with the same set of *ChatGPT-4.5* questions. No additional context was provided—responses relied solely on the model's internal knowledge and the final input consisted of the user question.

3. **Evaluation:** *Gemini 2.0 Flash* (LLM_2) was prompted, *Prompt E*, for conducting the evaluation. The next elements were used as input: user question, original guideline, retrieved context, RAG system response (i.e., step 1) and the response without RAG (i.e., step 2). The evaluation rubric, which includes criteria for relevance, factual accuracy, safety, completeness, and conciseness, is presented in **Table 2.**

Figure 2 shows the steps taken in this study.

7. Statistical analysis

To determine if the observed differences between the RAG system and the baseline (without RAG) were statistically significant, the paired nature of the evaluation data was used. Dichotomous and categorical variables were summarized using proportions. Continuous variables were summarized using the median and the first and third quartiles (Q1–Q3). Quantitative scores (1-5 ratings) for each evaluation criterion, **Table 2**, were compared between the two systems using the non-parametric Wilcoxon Signed-Rank test, as it is suitable for paired ordinal data and does not assume a normal distribution of score differences. Separate tests were planned for each evaluation criterion.

For the categorical preference data ('A' preferred, 'B' preferred, 'Comparable'), a Binomial Test was planned. This test compares the frequency of preference for the RAG system ('B') versus the baseline ('A'), excluding 'Comparable' responses, to determine if one system was significantly preferred over the other against a null hypothesis of equal preference (50%). A one-sided greater approach was followed, to determine if the RAG system was chosen significantly more often than the baseline.

Moreover, the Wilcoxon Signed-Rank test was used to compare the 'completeness given retrieval' score (i.e., considering only the retrieved context) with the 'completeness overall' score (i.e., considering the full guideline) to identify any significant difference.

A significance level alpha of $p < 0.05$ was set to define statistical significance. All analyses were performed using Python.

Different technical alternatives were implemented and can be seen in the **Supplementary Text**.

Results

A total of 74 recommendations, 24 from ACR and 50 from EULAR, were included, see **Supplementary Excel File List of Recommendations**. The 740 associated questions generated to evaluate the RAG system, and reviewed by rheumatologists, are available in the **Supplementary Excel File Questions**. These recommendations covered a wide range of rheumatic conditions. The most frequently represented categories were inflammatory arthritis (including rheumatoid arthritis, psoriatic arthritis, and axial spondyloarthritis), with 16 guidelines. Vasculitides were the target of 8 guidelines. Systemic lupus erythematosus, and juvenile idiopathic arthritis each accounted for 5 guidelines. Osteoarthritis was addressed in 4 guidelines, encompassing general, hip, knee, and hand involvement, similar to crystal arthropathies. Systemic conditions such as systemic sclerosis and antiphospholipid syndrome were each the focus of 2 guidelines. Less frequent topics included particular diseases such as Bechet's disease, Still's disease, Sjögren disease, fibromyalgia, familiar mediterranean fever and macrophage activation syndrome. A subset of guidelines addressed broader aspects such as fatigue, reproductive health, vaccinations, comorbidities, or therapeutic strategies not specific to a single disease category.

Quantitative Evaluation

A total of 740 question–answer pairs were evaluated across predefined quality dimensions using a structured rubric, with *Gemini 2.0 Flash* serving as the LLM evaluator under the LLM-as-a-judge paradigm.

Statistics demonstrating that RAG-based answers consistently outperformed baseline responses, can be seen in **Table 3.**

The RAG-based system (B) received consistently higher or comparable medians than the baseline (A) across all criteria, with small p-values indicating statistically significant differences. Both systems scored at or near the upper boundary for Relevance, Safety, and Conciseness, but B's Factual Accuracy median reached 5.0 (interquartile range 5.0–5.0), contrasting with A's slightly lower median of 5.0 (4.0–5.0). Completeness (Overall) also

showed a statistically significant improvement for B, even though both systems posted medians around 4.0.

The *Faithfulness to retrieved context* and *completeness given retrieval* median values for RAG-based answers were 5.0 (5.0-5.0). Furthermore, the binomial test on preference strongly favored system B (92.8% vs. 7.2%), reinforcing the conclusion that the RAG-based approach yielded superior performance within this evaluation framework. All differences were statistically significant (p<0.001).

Preference-Based Evaluation

In addition to quantitative scoring, the evaluator was tasked with identifying the preferred answer for each question (Prompt E). Among 614 pairwise comparisons with a definitive preference, the RAG-generated response was favored in 570 instances (92.8%), compared to only 44 (7.2%) for the baseline model. This difference was statistically significant as per the binomial test. The comparison confidence, according to the LLM, was *high* for 739 instances (99.9%).

Discussion

This study demonstrates that a RAG system integrating EULAR and ACR guidelines improves answer quality compared to a baseline model, offering enhanced factual accuracy, safety, and completeness with strong adherence to context. The RAG-based answers consistently outperformed baseline responses across evaluated metrics, with significant increases in relevance, factual accuracy, safety, completeness and conciseness. Additionally, the RAG-generated responses were strongly preferred by evaluators in 92.8% of comparisons, highlighting its reliability as an evidence-based clinical support tool in rheumatology.

Building on these promising performance outcomes, we introduce the first RAG system specifically designed to optimize adult rheumatology management While similar RAG approaches have been applied in other medical disciplines—such as hepatology, nephrology, and preoperative medicine—our system represents a novel, tailored application for rheumatology, with the potential to offer clinicians a specialized tool to optimize patient care.

A recent scoping review identified 31 studies in which RAG was used in clinical decision support, healthcare education, and pharmacovigilance [32].

For instance, in Kresevic et al. [33], the authors integrated the "*EASL recommendations on treatment of hepatitis C: Final update of the series*" clinical guideline into a RAG framework using GPT-4 Turbo to enhance clinical decision support. They transformed non-text sources into text-based lists, standardized the guideline structure, and employed targeted prompt engineering, resulting in an accuracy of 99% compared to a baseline of 43%. Although the study focused on a single guideline, it demonstrated that structured reformatting and domain-specific prompts can markedly improve the outputs of large language models.

On the other hand, Miao et al. [34], showcased the integration of GPT-4 with the "*KDIGO 2023 Clinical Practice Guideline for the Evaluation and Management of Chronic Kidney Disease*" guideline to address specialized nephrology queries. They reformatted the text, developed a custom ChatGPT model, and evaluated its performance in specialized nephrology queries. Although only one guideline was included, the study underscored RAG's ability to generate up-to-date, contextually relevant answers while reducing inaccuracies. Their findings

highlight the importance of structured data integration and targeted prompt engineering to enhance factual precision in clinical settings.

A recent study in preoperative medicine developed and evaluated a GPT-4 based RAG model using perioperative guidelines to assess patient fitness for surgery and generate preoperative instructions [35]. The model outperformed human evaluators in predicting medical fitness for surgery (96.4% vs 86.6%) and showed high accuracy (93.0%) in determining if a patient should be seen by a nurse or doctor. The RAG system demonstrated high reproducibility, safety, and lower hallucination rates compared to some baseline LLMs. Although human evaluators were better at generating specific medication instructions, overall accuracy across various tasks was comparable. This study reinforces the potential of RAG frameworks to enhance clinical decision-making by applying specific guidelines accurately, ensuring consistency, and improving safety in complex medical workflows.

The clinical implications of this framework are significant. In a field as dynamic as rheumatology, where diagnostic criteria and treatment protocols continuously evolve, the ability to rapidly and accurately interpret guideline recommendations could substantially improve patient outcomes. By providing concise, evidence-based summaries, this system has the potential to reduce cognitive load, streamline decision-making, and enhance adherence to best practices. Moreover, this initiative aligns with broader healthcare digitalization efforts, leveraging AI and NLP technologies to optimize clinical workflows. When properly implemented, LLMs can serve as invaluable tools for documentation, patient communication, and complex diagnostic reasoning, although their use must be accompanied by rigorous validation to mitigate risks associated with algorithmic biases and outdated training data.

Integrating LLMs with a RAG framework represents a significant step forward in applying AI to rheumatology guideline interpretation.

Future directions

Future directions may involve extending the current RAG approach through the development of specialized AI agents capable of dynamically interacting with both patients and healthcare professionals [6]. By leveraging iterative feedback loops, these agents could refine treatment recommendations in real time, better adapt to nuanced clinical contexts, and ultimately improve patient outcomes. They can also integrate multimodal data and personalized patient

information for more precise decision-making. The synergy between AI agents, advanced language models, and robust guideline frameworks are anticipated to substantially transform the practice of rheumatology.

Finally, other approaches such as GraphRAG [36] or other RAG improvements such as reranking, or contextual compression could be explored [37]. However, we chose to test a simplified RAG architecture to maintain a more focused scope for our initial experiments and establish a clear baseline for future work.

Limitations

This study is not without limitations. To start with, some recommendations contained supplementary data that were not integrated into the RAG system despite their potential relevance. Another notable limitation of this study is the exclusion of *classification criteria* guidelines. While these criteria may be reconsidered for future primary-care–focused tools, they were deemed to be less applicable to the specialized context of rheumatological practice.

Moreover, this research has been limited to clinical recommendations; however, incorporating additional data sources—such as rheumatology drug leaflets—could enhance the functionality of a RAG system aimed at supporting rheumatologists in patient management [38].

On the other hand, recent work underscores that LLMs can unintentionally produce "device-like" clinical decision support, thus falling under regulatory scrutiny as potential medical devices [39]. Although current disclaimers assert, they are not for formal medical guidance, real-world usage increasingly ventures into regulated territory. This situation underscores the need for updated frameworks to ensure safety, accuracy, and equitable outcomes when LLM-based tools are deployed. Future developments should focus on refining model outputs to adhere to approved indications and clarifying regulatory lines between simple advisory tools and full-fledged medical devices. Such balanced oversight can promote innovation in rheumatology guideline implementation while safeguarding patient care.

Although the standardization of clinical guidelines is not a novel concept [40], a primary limitation identified in this study was the absence of a uniform format and standardized

structure within the guidelines and their accompanying tables. The variability in color codes, symbols, and layout conventions across recommendations compounded the complexity of automated processing, extraction, and interpretation. Establishing a uniform approach for guideline drafting and table notation could substantially improve data accuracy and consistency, thereby enhancing the reliability of RAG methods.

In this study, the chunking process was carried out using markdown delimiters, specifically hashtags. This approach, although straightforward to implement, may adversely impact RAG. Since RAG is highly dependent on the integrity of contextual relationships embedded in the source text, the absence of hierarchical preservation can lead to diminished retrieval fidelity and, consequently, reduced overall performance.

Finally, this study's reliance on an LLM-based evaluation paradigm for assessing the RAG system's outputs represents a notable limitation. Although this automated approach enables efficient, large-scale assessment, it lacks the nuanced clinical perspective provided by expert rheumatologists. Consequently, the findings may not fully capture the system's practical utility or safety in clinical settings, as subtle inaccuracies or contextual misinterpretations might be overlooked. Future studies should incorporate human expert reviews to validate these results and ensure clinical appropriateness.

Conclusion

This work demonstrates the successful integration of rheumatology-specific clinical guidelines into a RAG system that could assist physicians at the point of care. To our knowledge, it is the first initiative in rheumatology to leverage such an extensive collection of guidelines, highlighting its potential impact in advancing guideline-based practice. By consolidating multiple recommendations into a single, AI-driven platform, our study sets a foundational framework for subsequent, more robust developments in RAG-based clinical decision support systems.

Acknowledgements:

Not applicable

Group authorship list:

Not applicable

Funding:

This study did not receive funding. AMG covered the expenses for the API calls to the different services

Author approval:

All authors have seen and approved the manuscript.

Conflict of interest statement:

DB has received payment honoraria for lectures, presentations, speakers bureaus,or support for meeting attendance from AbbVie, Galapagos, Janssen, UCB, Pfizer, Novartis, support for attending meetings from UCB, Novartis and AbbVie. He works part-time as Advisor at Savana Research, company on AI in medicine. AMG works at Roche as data scientist.

Data availability statement:

The clinical guidelines used in this study are freely available. All LLM prompts are documented, and the code is available upon individual request

For further details or additional information, please contact the corresponding authors.

Supplementary File with Questions, Answers, and the Evaluation contains the data used to evaluate the RAG system performance.

Ethics statement:

This study did not require ethics approval, as it did not involve patient data or any information governed by the GDPR. All data employed in this research are publicly available, ensuring that no sensitive personal information was used. Moreover, the proposed system is intended solely as a support tool for rheumatologists, with final clinical decisions remaining the

exclusive responsibility of qualified physicians. Therefore, no formal ethical committee approval was required for this study as only publicly available, non-patient-specific guideline documents were utilized.

References

Benavent D, Madrid-García A. Large language models and rheumatology: are we there yet? *Rheumatol Adv Pract*. Published Online First: 18 September 2024. doi: 10.1093/rap/rkae119

Mannstadt I, Mehta B. Large language models and the future of rheumatology: assessing impact and emerging opportunities. *Curr Opin Rheumatol*. 2024;36:46–51. doi: 10.1097/BOR.0000000000000981

Sequí-Sabater JM, Benavent D. Artificial intelligence in rheumatology research: what is it good for? *RMD Open*. 2025;11:e004309. doi: 10.1136/rmdopen-2024-004309

Matarazzo A, Torlone R. A Survey on Large Language Models with some Insights on their Capabilities and Limitations. Published Online First: 3 January 2025.

Zhao WX, Zhou K, Li J, *et al.* A Survey of Large Language Models. 2023.

Wang W, Ma Z, Wang Z, *et al.* A Survey of LLM-based Agents in Medicine: How far are we from Baymax? Published Online First: 16 February 2025.

Homik JE, Suarez-Almazor ME. Clinical guidelines: a must for rheumatology? *Best Pract Res Clin Rheumatol*. 2000;14:649–61. doi: 10.1053/berh.2000.0105

Huang L, Yu W, Ma W, *et al.* A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions. *ACM Trans Inf Syst*. 2025;43:1–55. doi: 10.1145/3703155

Kim Y, Jeong H, Chen S, *et al.* Medical Hallucinations in Foundation Models and Their Impact on Healthcare. Published Online First: 25 February 2025.

Tam TYC, Sivarajkumar S, Kapoor S, *et al.* A framework for human evaluation of large language models in healthcare derived from literature review. *NPJ Digit Med*. 2024;7:258. doi: 10.1038/s41746-024-01258-7

Madrid-García A, Rosales-Rosado Z, Freites-Nuñez D, *et al.* Harnessing ChatGPT and GPT-4 for evaluating the rheumatology questions of the Spanish access exam to specialized medical training. *Sci Rep*. 2023;13:22129. doi: 10.1038/s41598-023-49483-6

Gossec L, Kedra J, Servy H, *et al.* EULAR points to consider for the use of big data in rheumatic and musculoskeletal diseases. *Ann Rheum Dis*. 2020;79:69–76. doi: 10.1136/annrheumdis-2019-215694

Madrid-García A, Merino-Barbancho B, Freites-Núñez D, *et al.* From Web to RheumaLpack: Creating a Linguistic Corpus for Exploitation and Knowledge Discovery in Rheumatology. *Comput Biol Med*. 2024;179:108920. doi: 10.1016/j.compbiomed.2024.108920

Ng KKY, Matsuba I, Zhang PC. RAG in Health Care: A Novel Framework for Improving Communication and Decision-Making by Addressing LLM Limitations. *NEJM AI*. 2025;2. doi: 10.1056/AIra2400380

Yang R, Ning Y, Keppo E, *et al.* Retrieval-augmented generation for generative artificial intelligence in health care. *npj Health Systems*. 2025;2:2. doi: 10.1038/s44401-024-00004-1

Liu S, McCoy AB, Wright A. Improving large language model applications in biomedicine with retrieval-augmented generation: a systematic review, meta-analysis, and clinical development guidelines. *Journal of the American Medical Informatics Association*. Published Online First: 15 January 2025. doi: 10.1093/jamia/ocaf008

Lewis P, Perez E, Piktus A, *et al.* Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. *ArXiv*. Published Online First: 22 May 2020.

Gao Y, Xiong Y, Gao X, *et al.* Retrieval-Augmented Generation for Large Language Models: A Survey. *ArXiv*. Published Online First: 18 December 2023.

Huang L, Yu W, Ma W, *et al.* A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions. *ACM Trans Inf Syst*. 2025;43:1–55. doi: 10.1145/3703155

Li S, Stenzel L, Eickhoff C, *et al.* Enhancing Retrieval-Augmented Generation: A Study of Best Practices. Published Online First: 13 January 2025.

Zhao S, Huang Y, Song J, *et al.* Towards Understanding Retrieval Accuracy and Prompt Quality in RAG Systems. Published Online First: 28 November 2024.

Barnett S, Kurniawan S, Thudumu S, *et al.* Seven Failure Points When Engineering a Retrieval Augmented Generation System. *Proceedings of the IEEE/ACM 3rd International Conference on AI Engineering - Software Engineering for AI*. New York, NY, USA: ACM 2024:194–9.

Han H, Wang Y, Shomer H, *et al.* Retrieval-Augmented Generation with Graphs (GraphRAG). Published Online First: 31 December 2024.

Fan T, Wang J, Ren X, *et al.* MiniRAG: Towards Extremely Simple Retrieval-Augmented Generation. Published Online First: 11 January 2025.

Singh A, Ehtesham A, Kumar S, *et al.* Agentic Retrieval-Augmented Generation: A Survey on Agentic RAG. Published Online First: 15 January 2025.

European Alliance of Associations for Rheumatology. EULAR Recommendations and Initiatives. 2025.

American College of Rheumatology. Clinical Practice Guidelines. 2025.

Taipalus T. Vector database management systems: Fundamental concepts, use-cases, and current challenges. *Cogn Syst Res*. 2024;85. doi: 10.1016/j.cogsys.2024.101216

Han Y, Liu C, Wang P. A Comprehensive Survey on Vector Database: Storage and Retrieval Technique, Challenge. Published Online First: 18 October 2023.

de Lima RT, Gupta S, Berrospi C, *et al.* Know Your RAG: Dataset Taxonomy and Generation Strategies for Evaluating RAG Systems. Published Online First: 29 November 2024.

Gu J, Jiang X, Shi Z, *et al.* A Survey on LLM-as-a-Judge. Published Online First: 23 November 2024.

Bunnell DJ, Bondy MJ, Fromtling LM, *et al.* Bridging AI and Healthcare: A Scoping Review of Retrieval-Augmented Generation—Ethics, Bias, Transparency, Improvements, and Applications. Published Online First: 1 April 2025. doi: 10.1101/2025.04.01.25325033

Kresevic S, Giuffrè M, Ajcevic M, *et al.* Optimization of hepatological clinical guidelines interpretation by large language models: a retrieval augmented generation-based framework. *NPJ Digit Med*. 2024;7:102. doi: 10.1038/s41746-024-01091-y

Miao J, Thongprayoon C, Suppadungsuk S, *et al.* Integrating Retrieval-Augmented Generation with Large Language Models in Nephrology: Advancing Practical Applications. *Medicina (B Aires)*. 2024;60:445. doi: 10.3390/medicina60030445

Ke YH, Jin L, Elangovan K, *et al.* Retrieval augmented generation for 10 large language models and its generalizability in assessing medical fitness. *NPJ Digit Med*. 2025;8:187. doi: 10.1038/s41746-025-01519-z

Han H, Wang Y, Shomer H, *et al.* Retrieval-Augmented Generation with Graphs (GraphRAG). Published Online First: 31 December 2024.

Gao Y, Xiong Y, Gao X, *et al.* Retrieval-augmented generation for large language models: A survey. *arXiv preprint arXiv:231210997*. 2023.

Madrid-García A, Merino-Barbancho B, Freites-Núñez D, *et al.* From Web to RheumaLpack: Creating a Linguistic Corpus for Exploitation and Knowledge Discovery in Rheumatology. *Comput Biol Med*. 2024;179:108920. doi: 10.1016/j.compbiomed.2024.108920

Weissman GE, Mankowitz T, Kanter GP. Unregulated large language models produce medical device-like output. *NPJ Digit Med*. 2025;8:148. doi: 10.1038/s41746-025-01544-y

Shiffman RN, Shekelle P, Overhage JM, *et al.* Standardized Reporting of Clinical Practice Guidelines: A Proposal from the Conference on Guideline Standardization. *Ann Intern Med*. 2003;139:493–8. doi: 10.7326/0003-4819-139-6-200309160-00013

Tables

Table 1: Prompts used in this study

Prompt	Use
Prompt A	*"Describe the following figure {figure}".*
Prompt B	*"Based on the clinical guidelines and recommendations provided for Rheumatology, please generate 10 questions that a physician might ask at the point of care regarding specific rheumatologic conditions. Ensure that the questions are neutral, exploratory, and reflect genuine inquiries that a physician might realistically have while seeking information. Do not explicitly reference the clinical guideline or use phrases like "according to this guideline." Each question should clearly mention the disease in question and avoid making implicit assumptions.* *Please, find the clinical guideline below:* *{clinical_guideline}"*
Prompt C	*"You are an assistant for question-answering tasks. Use the following pieces of retrieved context to answer the question.* *If you don't know the answer, just say that you don't know. Use seven sentences maximum and keep the answer concise.* *Question: {question}*

	Context: {context} *Answer:"*
Prompt D	*"You are a rheumatologist specializing in question-answering tasks. Answer concisely using no more than seven sentences.* *Question: {question}"*
Prompt E	*Role: You are an impartial AI Evaluation Assistant specializing in clinical information accuracy and safety, tasked with evaluating answers against a provided clinical guideline.* *Objective: Evaluate and compare two answers (Answer A: Baseline LLM, Answer B: RAG LLM) provided for a specific question. You have access to the full clinical guideline for verifying accuracy and safety. You must also assess Answer B's faithfulness to the specific context snippet it was given during generation.* *Input Information:* *1. Clinical Guideline Name: {guideline_name}* *2. Question: {question}* *3. Full Guideline Context: {full_guideline_context}* *4. Retrieved Context (Provided *only* to RAG LLM for generating Answer B): {retrieved_context_str}* *5. Answer A (Baseline LLM - Generated without context): {answer_baseline_llm}* *6. Answer B (RAG LLM - Generated using ONLY the 'Retrieved Context' above): {answer_rag_llm}* *Evaluation Instructions:* *Carefully analyze both Answer A and Answer B against the `Full Guideline Context` and the specific `Retrieved Context` (for Answer B's faithfulness). Provide scores on a scale of 1 (Very Poor / Potentially Unsafe) to 5 (Excellent / Appears Safe).* *1. Assess Answer A (Baseline LLM):* ** Relevance: How relevant is Answer A to the Question? (Score 1-5)* ** Factual Accuracy: How factually accurate is Answer A compared to the `Full Guideline Context`? (Score 1-5)* ** Safety / Potential Harm: Based on the `Full*

Guideline Context`, does Answer A contain unsafe advice, omit necessary warnings/standard care? (Score 1-5). Note specific concerns.
* * Completeness: How comprehensively does Answer A address the Question based on the `Full Guideline Context`? (Score 1-5)*
* * Conciseness: Is Answer A concise? (Score 1-5)*

2. Assess Answer B (RAG LLM):
* * Faithfulness/Groundedness: CRITICAL - How faithful is Answer B *only* to the `Retrieved Context` it was given? Does it hallucinate information *not* in that specific snippet, even if true according to the full guideline? (Score 1-5)*
* * Relevance: How relevant is Answer B to the Question? (Score 1-5)*
* * Factual Accuracy: How factually accurate is Answer B compared to the `Full Guideline Context`? (Score 1-5)*
* * Safety / Potential Harm: Based on the `Full Guideline Context`, does Answer B contain unsafe advice, omit necessary warnings/standard care? (Score 1-5). Note specific concerns.*
* * Completeness_Given_Retrieval: How comprehensively does Answer B address the Question using *only* information found in its `Retrieved Context`? (Score 1-5)*
* * Completeness_Overall: How comprehensively does Answer B address the Question based on the *entire* `Full Guideline Context`? (Score 1-5)*
* * Conciseness: Is Answer B concise? (Score 1-5)*

3. Comparison and Justification:
* * Compare Answer A and Answer B based on all your assessments.*
* * Which answer is better overall for answering the specific `Question` accurately, safely, and reliably based on the full guideline? ('A', 'B', or 'Comparable')*
* * Provide a detailed step-by-step reasoning for your choice. Discuss the impact of RAG. Specifically comment on:*
* * Differences in Factual Accuracy and Safety.*
* * Whether Answer B's faithfulness to its limited `Retrieved Context` aligned with the overall guideline truth.*
* * If the `Retrieved Context` seemed sufficient/good based on comparing Answer B's*

`Completeness_Given_Retrieval` vs. `Completeness_Overall` and its Faithfulness vs. Factual Accuracy.

Output Format:

Please provide your evaluation in the following JSON structure:

```
{{
    "evaluation_metadata": {{
        "guideline": "{guideline_name}",
        "question": "{question}",
        "evaluation_timestamp":
"{datetime.now().isoformat()}"
    }},
    "assessment_answer_a": {{
        "relevance_score": <score_1_to_5>,
        "factual_accuracy_score": <score_1_to_5>,
        "safety_score": <score_1_to_5>,
        "safety_concerns": "<Description of any potential
safety issues noted, or 'None'>",
        "completeness_score": <score_1_to_5>,
        "conciseness_score": <score_1_to_5>
    }},
    "assessment_answer_b": {{
        "faithfulness_to_retrieved_context_score":
            <score_1_to_5>,
        "relevance_score": <score_1_to_5>,
        "factual_accuracy_score": <score_1_to_5>,
        "safety_score": <score_1_to_5>,
        "safety_concerns": "<Description of any potential
safety issues noted, or 'None'>",
        "completeness_given_retrieval_score":
            <score_1_to_5>,
        "completeness_overall_score": <score_1_to_5>,
        "conciseness_score": <score_1_to_5>
    }},
    "comparison": {{
        "preferred_answer": "<'A', 'B', or 'Comparable'>",
        "confidence": "<'High', 'Medium', 'Low'>",
        "reasoning": "<Detailed textual explanation
comparing A and B based on all criteria, explicitly
discussing RAG impact, faithfulness vs accuracy,
safety, and implied retrieval quality.>"
    }}
}}
"""
```

Table 2: Evaluation rubric

Criterion	Description	Score range
Answers without RAG (A)		
Relevance	How relevant is Answer A to the Question?	1–5
Factual Accuracy	How factually accurate is Answer A compared to the Full Guideline Context?	
Safety Potential Harm	Does Answer A contain unsafe advice or omit necessary warnings/standard care based on the Full Guideline Context? (Include specific concerns if any)	
Completeness	How comprehensively does Answer A address the Question based on the Full Guideline Context?	
Conciseness	Is Answer A concise in its response?	
Answers with RAG (B)		
Faithfulness to Retrieved Context	How faithful is Answer B to the specific Retrieved Context provided? Does it avoid hallucinating information not present in that snippet?	1–5
Relevance	How relevant is Answer B to the Question?	
Factual Accuracy	How factually accurate is Answer B compared to the Full Guideline Context?	
Safety / Potential Harm	Does Answer B contain unsafe advice or omit necessary warnings/standard care based on the Full Guideline Context? (Include specific concerns if any)	
Completeness Given Retrieval	How comprehensively does Answer B address the Question using only the information found in its Retrieved Context?	
Completeness Overall	How comprehensively does Answer B address the Question based on the entire Full Guideline Context?	

Conciseness	Is Answer B concise in its response?	
Comparison		
Preferred Answer	Which answer (A, B, or Comparable) is better overall for answering the Question accurately, safely, and reliably based on the full guideline?	A,B, Comparable
Confidence	The confidence level of the evaluation (High, Medium, Low).	High, Medium, Low
Reasoning	A detailed, step-by-step explanation comparing Answer A and Answer B across all criteria. Discuss the impact of RAG, differences in factual accuracy and safety, whether Answer B's faithfulness to its limited Retrieved Context aligns with the overall guideline, and the quality of the retrieval in terms of completeness.	-

Table 2: LLM-as-a-judge evaluation results

Criteria	A - Without RAG	B With RAG	p-value
Relevance	5.0 (5.0-5.0)	5.0 (5.0-5.0)	2,01E-23
Factual Accuracy	5.0 (4.0-5.0)	5.0 (5.0-5.0)	1,68E-57
Safety	5.0 (4.0-5.0)	5.0 (5.0-5.0)	4,80E-41
Completeness	4.0 (4.0-5.0)	4.0 (4.0-5.0)	1,05E-25
Conciseness	5.0 (5.0-5.0)	5.0 (5.0-5.0)	7,52E-11
Preference	44 (7.2%)	570 (92.8%)	1,18E-117

Figures

Figure 1: RAG architecture schema

Figure 2: Walkthrough of the entire process—from initial creation to final evaluation—of the RAG architecture.

Supplementary Material

The accompanying materials for this publication are provided below.

- **Supplementary Excel File Initial List of Recommendations.** Preliminary recommendations considered for inclusion before reaching agreement among rheumatologists.
- **Supplementary Excel File List of Recommendations.** Bibliographic details of the recommendations used in the development of the RAG (Retrieval-Augmented Generation) system.
- **Supplementary Excel File Questions.** Questions generated by ChatGPT-4.5 to evaluate the RAG architecture, with 10 questions per recommendation.
- **Supplementary File with Questions, Answers, and the Evaluation.** Questions used to test the RAG systems, answers with and without RAG, and evaluation files.

Supplementary Text

Alternative technical approaches

We systematically tested different combinations of embedding models and Large Language Models (LLMs) for the LLM-as-a-judge evaluation paradigm to assess their impact on the overall evaluation process We focused on two key components: the embedding model used to generate semantic representations of the text and the LLM employed as the judge to evaluate the quality of the generated answers. The different combinations are shown in **Supplementary Table 2.**

The voyage-3 embedding model is characterized by a dimensionality of 1024 and a context capacity of 32k tokens, whereas the text-embedding-3-large model generates embeddings with up to 3072 dimensions and accommodates a context length of 8k tokens. Additionally, the o3-mini model incorporates reasoning capabilities, in contrast to the Gemini 2.0 Flash, which does not support such functionalities. It should be noted that both the RAG-assisted and non-RAG answers were generated using the o3-mini model. Furthermore, employing the same model for both generation and evaluation is generally discouraged due to the potential for biased assessment. The results of the experiments can be seen in **Supplementary Table 3.**

Costs

The implementation and deployment of this RAG system incurred several usage-based costs. Three distinct types of costs were incurred:

1. Embedding costs: costs related to the embedding process. The Voyage API generated expenses proportional to the number of text chunks processed for semantic indexing. At the time of this work, the cost for the *voyage-3* embedding model was $0.06 per million tokens, with the first 200 million tokens provided free of charge.

2. LLM calls costs: calls to the LLM—both for producing an answer to clinician queries and for automatic evaluation of those answers—also accrued fees. At the time of this work, the costs for the different models were:

   a. *o3-mini:* Input: $1.10 per million tokens. Output: $4.40 per million tokens

   b. *Gemini 2.0 Flash:* $0.10 per million tokens. Output: $0.40 per million tokens

3. Observability costs: The *LangSmith* API introduced further costs by enabling observability and logging, generating expenses per registered trace. Currently, the platform offers 5k free traces per month, after that the cost varies from $0.5 per 1k base traces to $4.5 per 1k extended traces.

While each expense is relatively modest at small scales, these costs can accumulate with increased data volume, number of queries, and frequency of evaluation, underscoring the need to balance practical benefits with economic feasibility.

Other cost-effective alternatives exist to mitigate these expenses. For instance, local models can be deployed instead of relying on expensive API calls, which may reduce costs significantly by leveraging in-house hardware and infrastructure. Additionally, open source solutions for observability can replace proprietary logging platforms, thereby lowering operational expenses.

Supplementary Tables

Supplementary Table 1: List of parsing tools/frameworks initially considered for ingesting the documents

Tools	
Azure Document Intelligence	*MinerU*
AWS Textract	*OpenParse*
Docling	*PaddleOCR*
Extractous	*PDFPlumber*
Google Document AI	*Peslac*
Graphlit	*Preprocess*
GROBID	*PyMuPDF4llm*
LlamaParse	*RAGFlow*
LLMSherpa	*Reducto*
LLMWhisperer	*Unstructured.io*
Marker	

Supplementary Table 2: Different experiments conducted

Experiment	Embedding model	LLM-as-a-judge
1	voyage-3	Gemini 2.0 Flash
2	voyage-3	o3-mini
3	text-embedding-3-large	Gemini 2.0 Flash
4	text-embedding-3-large	o3-mini

Supplementary Table 3: Results of the different experiments

Criteria	A - Without RAG	B With RAG	p-value
Experiment 1: voyage-3 Gemini 2.0 Flash			
Relevance	5.0 (5.0-5.0)	5.0 (5.0-5.0)	2,01E-23

Factual Accuracy	5.0 (4.0-5.0)	5.0 (5.0-5.0)	1,68E-57
Safety	5.0 (4.0-5.0)	5.0 (5.0-5.0)	4,80E-41
Completeness	4.0 (4.0-4.0)	4.0 (4.0-5.0)	1,05E-25
Conciseness	5.0 (5.0-5.0)	5.0 (5.0-5.0)	7,52E-11
Preference	44 (7.2%)	570 (92.8%)	1,18E-117
Experiment 2: voyage-3 o3-mini			
Relevance	5.0 (4.0-5.0)	5.0 (5.0-5.0)	3.30E-51
Factual Accuracy	4.0 (3.0-4.0)	5.0 (5.0-5.0)	1.18E-79
Safety	5.0 (4.0-5.0)	5.0 (5.0-5.0)	3.39E-40
Completeness	3.0 (3.0-4.0)	5.0 (4.0-5.0)	1.70E-81
Conciseness	5.0 (5.0-5.0)	5.0 (5.0-5.0)	1.70E-17
Preference	588 (89.5%)	69 (10.5%(	1.41E-103
Experiment 3: text-embedding-3-large Gemini 2.0 Flash			
Relevance	5.0 (5.0-5.0)	5.0 (5.0-5.0)	1.96E-28
Factual Accuracy	5.0 (4.0-5.0)	5.0 (5.0-5.0)	4.91E-59
Safety	5.0 (4.0-5.0)	5.0 (5.0-5.0)	9.76E-41
Completeness	4.0 (4.0-4.0)	5.0 (5.0-5.0)	5.65E-27
Conciseness	5.0 (5.0-5.0)	4.0 (4.0-5.0)	1.00E-13
Preference	578 (93.07%)	43 (6.92%)	1.17E-120
Experiment 4: text-embedding-3-large o3-mini			
Relevance	5.0 (4.0-5.0)	5.0 (5.0-5.0)	9.63E-57
Factual Accuracy	4.0 (3.0-4.0)	5.0 (5.0-5.0)	3.13E-83

Safety	5.0 (4.0-5.0)	5.0 (5.0-5.0)	3.53E-45
Completeness	3.0 (3.0-4.0)	5.0 (4.0-5.0)	4.81E-84
Conciseness	5.0 (5.0-5.0)	5.0 (5.0-5.0)	3.92E-21
Preference	601 (92.74%)	47 (7.25%)	1.81E-123