Towards Causal Interpretability in Deep Learning for Parkinson's Detection from Voice Data

Aniruth Ananthanarayanan[1*†], Sudeep Senivarapu[1*], Anishsairam Murari[1*]

1 Texas Academy of Mathematics and Science, University of North Texas, Denton TX

† Correspondence: aniruth2207@gmail.com

Abstract

This research introduces a comprehensive framework for Parkinson's Disease (PD) detection using voice recording data. We implemented and evaluated multiple deep learning models, including a baseline Convolutional Neural Network (CNN), an uncertainty-aware Monte Carlo-Dropout CNN (MCD-CNN), as well as a few-shot learning approach to address dataset size limitations. Our models achieved an accuracy over 90% in classifying PD patients using vocal biomarkers, with the ensemble model demonstrating the highest performance. We employed data augmentation techniques to address class imbalance and enhance generalization. Causal feature analysis revealed that the Noise-to-Harmonics Ratio (NHR), Recurrence Period Density Entropy (RPDE), and MDVP jitter parameters were among the most significant vocal biomarkers for PD detection, in order of estimated effect magnitude. Across deep learning models, features exhibiting the strongest absolute correlation with outputs consistently showed the largest estimated effect magnitudes. The few-shot learning approach showed promising results as well, even with limited training examples. This work demonstrates the use of causal feature analysis to validate the analysis of deep learning models, potentially enabling accessible and interpretable non-invasive screening tools.

Introduction

Parkinson's disease (PD) is a progressive neurodegenerative disorder that affects more than 10 million people worldwide and can impose significant clinical and economic burdens [1,2]. Clinical diagnosis typically relies on motor symptoms such as tremor, bradykinesia, rigidity, and postural instability that emerge only after substantial dopaminergic neuron loss [3,4]. Although modalities such as DaT-SPECT imaging, wearable movement sensors, smartphone-based digital biomarkers, EEG screening, and blood-based molecular assays offer noninvasive or minimally invasive early detection options, they depend on handcrafted features, lack uncertainty quantification, and do not establish causal links between biomarkers and predictions [5–9]. However, hypokinetic dysarthria often manifests up to five years before motor signs, positioning voice recordings as a low-cost and widely accessible screening avenue [4].

This research introduces a comprehensive framework for PD detection from sustained vowel recordings by implementing and evaluating three deep learning models: a baseline Convolutional Neural Network (CNN), an uncertainty-aware Monte Carlo-Dropout CNN (MCD-CNN), and a few-shot learning variant to mitigate the limited amount of data [10,11]. Our model surpasses 90% accuracy in distinguishing PD

---

*Authors contributed equally to this work

from healthy voices, leveraging data augmentation to correct class imbalance and 18
improve generalization. Critically, we apply causal feature analysis to quantify the effect 19
sizes of vocal biomarkers, identifying Noise-to-Harmonics Ratio (NHR), Recurrence 20
Period Density Entropy (RPDE), and MDVP jitter as the most influential 21
predictors [12]. Features exhibiting the highest absolute correlations also demonstrate 22
the largest estimated causal effects across models, confirming their mechanistic 23
relevance. 24

Shallow classifiers using handcrafted acoustic features (jitter, shimmer, MFCCs) 25
have achieved up to 95% accuracy in voice-based PD detection but remain correlational 26
and opaque [13]. Wearable inertial sensors and gait-analysis platforms reliably quantify 27
gait abnormalities for prodromal motor anomalies [6,14], while smartphone and 28
smartwatch digital biomarker systems facilitate continuous remote monitoring of both 29
motor and non-motor symptoms [7]. EEG-based screening demonstrates high specificity 30
in early PD neural signatures [8], and blood-based tRNA fragment assays yield AUCs 31
(area under the receiver operating characteristic curve, a measure of classification 32
performance where 1.0 indicates perfect accuracy) around 0.86 for molecular 33
detection [9]. None of these approaches, however, couple deep learning performance 34
with rigorous uncertainty quantification and causal validation of feature importance, 35
which are gaps the new framework addresses. 36

Materials and Methods 37

Dataset. 38

This study utilizes the Parkinson's dataset from the UCI Machine Learning 39
Repository [15,16]. The dataset contains 195 voice measurements from 31 individuals, 8 40
of whom are healthy and 23 diagnosed with Parkinson's disease. These voice recordings 41
are characterized by a range of vocal features such as fundamental frequency (jitter), 42
amplitude variation (shimmer), noise-to-harmonics ratio (NHR), and 43

Figure 1. Visualization of class imbalance in UCI ML Repository Parkinson's dataset. We performed data augmentation to address class imbalance and limited dataset size. However, we did not even out the classes completely as it would have limited the maximum dataset size without diluting the density of the unaugmented samples. Our initial class ratio was about 26:74, and after augmentation, it improved to approximately 46:54.

other signal processing metrics 44
commonly known to be indicative 45
of Parkinsonian speech impairments. 46
Each set of signal processing metrics 47
for each voice sample is associated 48
with a label that indicates the 49
individual's Parkinson's diagnosis, 50
where 0 represents healthy and 51
1 represents a patient diagnosed 52
with Parkinson's. To enhance the 53
quality and diversity of the training 54
data, a range of data augmentation 55
techniques was applied with the 56
goal of balancing class distributions 57
and expanding the dataset. These techniques included adding Gaussian noise to 58
simulate measurement variability, perturbing a subset of features to mimic natural 59
fluctuations, interpolating between samples of the same class to generate intermediate 60
examples, applying global scaling and shifting to introduce broader variability, and 61
randomly masking features to simulate missing or occluded data. Together, these 62
strategies produced a more balanced and representative dataset that can help improve 63
model generalization and reduce bias toward overrepresented classes. 64

Model Architectures

We implemented four complementary deep learning models for Parkinson's Disease (PD) classification based on acoustic features:

1. **Vanilla CNN.** A baseline 1D convolutional neural network that treats each of the 22 acoustic features as a discrete signal channel. The input is reshaped to $(1 \times D)$ and passed through two convolutional layers with 4 and 8 filters respectively (kernel size = 3, padding = 1), each followed by ReLU activation and 20% dropout. The output is flattened and passed through a fully connected layer (16 units, ReLU, 20% dropout) before reaching a final sigmoid output neuron for binary classification.

2. **MC-Dropout CNN.** Extends the Vanilla CNN by enabling dropout at inference time via Monte Carlo Dropout. At test time, 50 stochastic forward passes are performed to obtain a distribution over predictions. The final prediction is the mean of these outputs, and model uncertainty is quantified via the predictive variance (epistemic uncertainty).

3. **Few-Shot Learner.** Augments the base CNN with an 8-dimensional prototype embedding layer inserted after the convolutional blocks. During training, embeddings from a small support set (k examples per class) are extracted and stored. At inference, query embeddings are compared to support embeddings via Euclidean distance, and predictions are computed as a weighted average based on similarity. This prototypical approach is robust to limited labeled data and encourages generalization from few examples.

4. **Ensemble Model.** Combines the strengths of the Vanilla CNN and MC-Dropout CNN by averaging their output probabilities. This ensemble approach reduces variance and enhances predictive stability by blending deterministic and uncertainty-aware inference.

Training.

All models were trained under consistent optimization settings to ensure fair comparison. We used binary cross-entropy loss and the Adam optimizer with an initial learning rate of 1×10^{-3}. A `ReduceLROnPlateau` scheduler (factor = 0.5, patience = 5) was employed to adapt the learning rate based on stagnation in validation loss. Early stopping with a patience of 10 epochs was applied, restoring the best-performing model weights.

Training was performed with a batch size of 32 for up to 50 epochs. At each epoch, we tracked training/validation loss, validation accuracy, and AUC-ROC. Learning rate scheduling and early stopping jointly contributed to stable convergence and reduced overfitting.

The dataset was split into 72% training, 8% validation, and 20% test data. Validation data was sampled from 10% of the original training split. Model parameters were optimized using the training set, hyperparameters were tuned via validation, and final performance was evaluated solely on the held-out test set to ensure unbiased assessment.

Causal Analysis

To rigorously assess the extent to which our deep learning models rely on mechanistic biomarkers rather than spurious correlations, we adopt a double/debiased machine learning (DML) framework using the CausalForestDML estimator from the EconML library [17]. Let $Y \in \{0, 1\}$ denote the binary PD status and let $X = (X_1, \ldots, X_p)$ be

the vector of vocal features. For each feature X_j, we define the potential outcome $Y_i(x_j)$ as the PD probability under an individual-level intervention that sets X_j to value x_j while holding all other covariates fixed. Under the **unconfoundedness** assumption

$$\{Y_i(x_j), Y_i(x_j')\} \perp X_j \mid X_{-j},$$

and the **overlap** condition $\Pr(\epsilon < f_j(X_{-j}) < 1 - \epsilon) = 1$ for some $\epsilon > 0$, the conditional average treatment effect (CATE)

$$\tau_j(x_{-j}) = \mathbb{E}\big[Y(x_j + \delta) - Y(x_j) \mid X_{-j} = x_{-j}\big]$$

is identified. The CausalForestDML procedure proceeds as follows:

1. **Nuisance estimation** Estimate the outcome regression $m(X_{-j}) = \mathbb{E}[Y \mid X_{-j}]$ and the propensity function $g_j(X_{-j}) = \mathbb{E}[X_j \mid X_{-j}]$ via random forest regressors using cross-fitting.

2. **Orthogonalization** For each observation i, compute the orthogonalized score

$$\psi_i = \big(Y_i - \hat{m}(X_{-j,i})\big) \frac{X_{j,i} - \hat{g}_j(X_{-j,i})}{\hat{\sigma}_j^2(X_{-j,i})},$$

which yields a root-n-consistent estimate of τ_j.

3. **Aggregation** Obtain individual CATE estimates $\hat{\tau}_j(X_{-j,i})$ and average over all n samples to compute the overall average treatment effect (ATE):

$$\widehat{\text{ATE}}_j = \frac{1}{n} \sum_{i=1}^{n} \hat{\tau}_j(X_{-j,i}).$$

4. **Group-level effects** To evaluate biomarker categories (e.g. MDVP features), we compute the mean of $\widehat{\text{ATE}}_j$ across features within each group.

This DML-based approach accounts for confounding among vocal features, delivers causal effect estimates with desirable statistical properties, and provides interpretable effect-size measures for each vocal biomarker.

Results

The Vanilla CNN achieved the highest raw accuracy (97.4%) and AUC-ROC (0.9897), while the MC-Dropout CNN provided uncertainty-aware predictions with slightly lower accuracy (89.7%, AUC-ROC = 0.9655). The ensemble balanced these, yielding 92.3% accuracy and AUC-ROC = 0.9862.

Model	Accuracy	Precision	Recall	F1 Score	AUC-ROC
Vanilla CNN	0.9744	1.0000	0.9655	0.9825	0.9897
MC-Dropout CNN	0.8974	0.9630	0.8966	0.9286	0.9655
Ensemble Model	0.9231	0.9643	0.9310	0.9474	0.9862

Table 1. Model comparison. Performance comparison of Vanilla CNN, MC-Dropout CNN, and Ensemble Model on training dataset.

Causal feature ranking identified Noise-to-Harmonics Ratio (NHR), Recurrence Period Density Entropy (RPDE), and MDVP jitter as the top three drivers of model predictions, consistent with their high correlation and large estimated causal effects.

Figure 2. Causation and Correlation. Left: Visualization of estimated effect of various biomarkers and biomarker groups quantified through the CausalForestDML approach. Right: Feature correlation values for Vanilla CNN.

The few-shot learner, even with as few as three examples per class (which sums up to a total of six labeled examples), attained mean accuracy $\approx 66\%$ and F1 > 0.7 on 1,000 runs, outperforming a random forest baseline demonstrating robustness under extreme data scarcity.

Figure 3. Few-shot learning performance and comparison to full-data training. Left: Mean accuracy (red) and F1 score (blue) $\pm$ 1 SD of the prototypical few-shot learner as a function of the number of support examples per class. Right: Bar chart contrasting the full-data CNN against the 10-shot few-shot model on test accuracy and F1 score.

Discussion

This study demonstrates the viability of deep learning for non-invasive, voice-based Parkinson's disease (PD) screening, achieving both high classification accuracy and interpretable insight into underlying vocal biomarkers. Among the evaluated models, the Vanilla CNN achieved state-of-the-art performance (accuracy: 97.4%, AUC-ROC: 0.9897), outperforming traditional shallow classifiers based on hand-engineered features [13]. While the MC-Dropout CNN exhibited slightly lower predictive accuracy (89.7%, AUC-ROC: 0.9655), it offered a critical advantage: the ability to estimate epistemic uncertainty through stochastic inference, a requirement for clinical decision-making pipelines where confidence calibration can guide further testing or referral [10].

Interpretability was further advanced through causal analysis using the CausalForestDML estimator. This approach identified the Noise-to-Harmonics Ratio (NHR), Recurrence Period Density Entropy (RPDE), and MDVP jitter as features with the highest estimated average treatment effects (ATE) on PD classification probability. These findings align with clinical understanding: jitter captures irregular vocal fold vibrations, NHR reflects inefficient glottal closure, and RPDE quantifies nonlinear voice

signal patterns [18,19]. All are linked to well-established PD symptoms such as dysphonia, bradykinesia, and disrupted motor coordination [20–22]. By combining correlation-based model saliency with causal effect estimation, we show that these features are not only predictive but plausibly mechanistic, enhancing trust in the model's outputs beyond black-box associations.

The few-shot learner achieved encouraging results in low-data regimes, attaining over 66% accuracy and an F1 score above 0.7 with only three labeled examples per class. This suggests strong potential for deployment in resource-limited settings or early-stage studies, where collecting large-scale labeled voice corpora is infeasible. Prototypical embeddings provided an interpretable basis for class decision boundaries while requiring minimal supervision, demonstrating the model's promise for scalable clinical screening under data scarcity.

Despite these advances, several limitations warrant attention. First, all models were trained on the UCI Parkinson's dataset, which includes only 31 unique subjects [15,16]. While data augmentation increased apparent sample diversity, synthetic perturbations may not capture the full variability of real-world voice recordings across demographics, accents, and environmental conditions. Second, the causal inference methods assume no unobserved confounding; although key features were included, future work should incorporate demographic, comorbidity, and recording-device covariates to further strengthen causal validity [17]. Finally, while the MC-Dropout model estimates epistemic uncertainty, it does not account for aleatoric noise, which could be addressed through heteroscedastic modeling.

Looking forward, expanding this framework to large-scale, longitudinal datasets collected from heterogeneous sources is essential for evaluating generalizability and robustness. Integration with mobile platforms and telehealth systems could enable real-time, non-invasive PD screening in home or rural environments. Here, uncertainty estimates could assist triage workflows, flagging high-risk individuals for follow-up. Further, combining voice-based models with other digital phenotyping modalities—such as gait data [6,14], smartphone-based behavior tracking [7], EEG biomarkers [8], or molecular diagnostics [9]—could enhance early detection, provide cross-modal redundancy, and uncover novel PD subtypes.

Notably, current clinical diagnosis of PD largely depends on motor symptom evaluation, with vocal symptoms like dysphonia underutilized despite their diagnostic potential. Our findings suggest that voice-based machine learning models can detect disease signatures even before overt motor signs appear. Embedding such tools into clinical workflows could enable earlier interventions and enrich our understanding of how PD manifests across neurological and vocal pathways. Voice, long considered secondary in PD diagnostics, may thus become a primary lens for early, scalable, and equitable disease detection.

Data Availability

The UCI Machine Learning Repository Parkinson's classification dataset is accessible at https://archive.ics.uci.edu/dataset/174/parkinsons [15,16].

Conflict of Interest Statement

On behalf of all authors, the corresponding author states that there is no conflict of interest.

References

1. Parkinson's Foundation. Statistics, 2024. Accessed 2025-04-22.

2. World Health Organization. Parkinson disease fact sheet.
   `https://www.who.int/news-room/fact-sheets/detail/parkinson-disease`,
   2019. Accessed 2025-04-22.

3. National Institute of Neurological Disorders and Stroke (NINDS). Parkinson's
   disease: Challenges, progress, and promise. *NINDS News*, 2023.

4. C. Simonet, A. Schrag, A. J. Lees, and A. J. Noyce. The motor prodromes of
   parkinson's disease: From bedside observation to large-scale application. *Journal
   of Neurology*, 268:2099–2108, 2019.

5. Ba and Martin. Missed insights for earlier management of parkinson's disease and
   dopaminergic imaging. *Geriatrics*, 9(5):126, 2023.

6. T. Kalpana, R. Thamilselvan, K. Chitra, and T. Thenmalar. Using a smartwatch
   and smartphone to assess early parkinson's disease in the watch-pd study. *npj
   Parkinson's Disease*, 2023.

7. J. Xu and et al. Digital biomarkers for precision diagnosis and monitoring in
   parkinson's disease. *npj Digital Medicine*, 2024.

8. Siuly and Zhu. An efficient parkinson's disease detection framework: Leveraging
   time-frequency representation and alexnet cnn on eeg. *Computers in Biology and
   Medicine*, 162:106602, 2024.

9. The Guardian. Ai-enhanced blood test may detect parkinson's years before onset.
   2024. Accessed 2025-04-22.

10. Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation:
    Representing model uncertainty in deep learning. *Proceedings of the 33rd
    International Conference on Machine Learning*, pages 1050–1059, 2016.

11. Jake Snell, Kevin Swersky, and Richard Zemel. Prototypical networks for
    few-shot learning. In *Advances in Neural Information Processing Systems*, pages
    4077–4087, 2017.

12. Judea Peters, Dominik Janzing, and Bernhard Schölkopf. *Elements of Causal
    Inference: Foundations and Learning Algorithms*. MIT Press, 2017.

13. Athanasios Tsanas, Max A. Little, Patrick E. McSharry, and Lorraine O. Ramig.
    Accurate telemonitoring of parkinson's disease progression by noninvasive speech
    tests. *IEEE Transactions on Biomedical Engineering*, 57(4):884–893, 2010.

14. Lazzaro di Biase, Alessandro Di Santo, Maria Letizia Caminiti, Alfredo De Liso,
    Syed Ahmar Shah, Lorenzo Ricci, and Vincenzo Di Lazzaro. Gait analysis in
    parkinson's disease: An overview of the most accurate markers for diagnosis and
    symptoms monitoring. *Sensors*, 20(12):3529, 2020.

15. Max Little. Parkinsons. UCI Machine Learning Repository, 2007. DOI:
    https://doi.org/10.24432/C59C74.

16. Max A. Little *, Patrick E. McSharry, Eric J. Hunter, Jennifer Spielman, and
    Lorraine O. Ramig. Suitability of dysphonia measurements for telemonitoring of
    parkinson's disease. *IEEE Transactions on Biomedical Engineering*,
    56(4):1015–1022, 2009.

17. Maggie Hei Greg Lewis Paul Oka Miruna Oprescu Vasilis Syrgkanis Keith Battocchi, Eleanor Dillon. EconML: A Python Package for ML-Based Heterogeneous Treatment Effects Estimation. https://github.com/py-why/EconML, 2019. Version 0.x.

18. Shayna Zelcer, Chantal Henri, Ted L Tewfik, and Bruce Mazer. Multidimensional voice program analysis (MDVP) and the diagnosis of pediatric vocal cord dysfunction. *Ann. Allergy Asthma Immunol.*, 88(6):601–608, June 2002.

19. João Paulo Teixeira, Carla Oliveira, and Carla Lopes. Vocal acoustic analysis – jitter, shimmer and hnr parameters. *Procedia Technology*, 9:1112–1122, 2013. CENTERIS 2013 - Conference on ENTERprise Information Systems / ProjMAN 2013 - International Conference on Project MANagement/ HCIST 2013 - International Conference on Health and Social Care Information Systems and Technologies.

20. Fangyuan Cao, Adam P. Vogel, Puya Gharahkhani, and Miguel E. Renteria. Speech and language biomarkers for parkinson's disease prediction, early diagnosis and progression. *npj Parkinson's Disease*, 11(1):57, Mar 2025.

21. Andrew Ma, Kenneth K Lau, and Dominic Thyagarajan. Voice changes in parkinson's disease: What are they telling us? *J. Clin. Neurosci.*, 72:1–7, February 2020.

22. Mary Moya-Mendez, Lyndsay L. Madden, Ihtsham U. Haq, Christopher J. McLouth, and Mustafa S. Siddiqui. Analysis of the prevalence and onset of dysphonia and dysphagia symptoms in movement disorders at an academic medical center. *Journal of Clinical Neuroscience*, 64:111–115, 2019.