Multiple instance learning using pathology foundation models effectively predicts kidney disease

diagnosis and clinical classification

Yu Kurata[1], Imari Mimura[1, 2]*, Satoshi Kodera[3], Hiroyuki Abe[4], Daisuke Yamada[5], Haruki Kume[5],

Tetsuo Ushiku[4], Tetsuhiro Tanaka[6], Norihiko Takeda[2, 3], Masaomi Nangaku[1, 2].

1. Division of Nephrology and Endocrinology, The University of Tokyo Graduate School of

Medicine, Japan.

2. Organ Pathophysiology Program, The University of Tokyo Graduate School of Medicine, Japan

3. Department of Cardiovascular Medicine, The University of Tokyo Graduate School of Medicine,

Japan.

4. Department of Pathology, The University of Tokyo Graduate School of Medicine, Japan.

5. Division of Urology, The University of Tokyo Graduate School of Medicine, Japan.

6. Department of Nephrology, Tohoku University Graduate School of Medicine, Japan.

* **The corresponding author**: Imari Mimura

Address: 7-3-1 Hongo Bunkyo-ku Tokyo, JAPAN 113-8655

Phone No: +81-3-3815-5411, Fax No: +81-3-5800-9826,

E-mail address; imimura@m.u-tokyo.ac.jp

Abstract

Introduction

Histological analysis of kidney biopsies is crucial in diagnosing kidney diseases and predicting

clinical outcomes. Recently developed pathology foundation models, pretrained on large-scale

pathology datasets, have demonstrated excellent performance in various downstream applications.

This study evaluated the utility of pathology foundation models combined with multiple instance

learning (MIL) for kidney pathology analysis.

Methods

We used 242 hematoxylin and eosin (H&E)-stained whole slide images (WSIs) from the Kidney

Precision Medicine Project (KPMP) and Japan-Pathology Artificial Intelligence Diagnostics Project

(JP-AID) databases as the development cohort, comprising 47 healthy controls, 35 acute interstitial

nephritis, and 160 diabetic kidney disease (DKD) slides. External validation was performed using 83

WSIs from the University of Tokyo Hospital (UT dataset). Diagnoses were based on adjudicated

diagnoses (KPMP) or expert pathologists-derived diagnoses (JP-AID and UT). Pretrained pathology

foundation models were utilized as patch encoders and compared with ImageNet-pretrained

ResNet50.

Results

In internal validation, all foundation models outperformed ResNet50, achieving area under the

receiver operating characteristic curve (AUROC) over 0.980. In external validation, the performance

of ResNet50 markedly dropped (AUROC = 0.768), whereas all foundation models maintained

higher performance (AUROC over 0.800). Visualization with attention heatmaps confirmed that

foundation models accurately recognized diagnostically relevant structures. Additionally, foundation

models outperformed ResNet50 in predicting severe proteinuria among DKD cases from KPMP

dataset.

Conclusion

We successfully integrated pathology foundation models with MIL to achieve robust diagnostic

performance, even when trained on a relatively small dataset, highlighting their potential for real-

world clinical applications.

Key words: artificial intelligence, renal pathology, foundation model, multiple instance learning

Introduction

The diagnosis of kidney diseases requires interpreting diverse pathological features, such as

inflammation, atherosclerosis, and metabolic changes, which demands significant effort and

expertise. The advent of whole-slide imaging (WSI) and advances in deep learning have spurred

intensive research in digital pathology. In particular, image analysis with convolutional neural

networks (CNNs) has been successfully applied to kidney pathology, enabling segmentation of

functional structures such as glomeruli and tubules, as well as quantitative analysis of kidney

pathology and its association with clinical outcomes[1-3]. These approaches are expected to facilitate

efficient kidney histopathological analysis and reduce the time and effort required for evaluation.

However, these segmentation-based approaches heavily depend on manually annotated datasets for

supervised training, posing a significant limitation to scalability. Self-supervised learning (SSL)[4] has

been introduced as a powerful approach for extracting meaningful representations from unlabeled

large datasets. In kidney pathology, the use of SSL for effective feature extraction from glomerular

images with limited annotations has been reported[5]. Recently, pathology foundation models, trained

using SSL with Vision Transformer (ViT)[6] architectures, have demonstrated remarkable

performance in various downstream tasks compared with ImageNet-trained CNN-based models[7-11].

A key difference between CNNs and ViTs is their inductive biases. CNNs extract spatial patterns

using small convolutional kernels across multiple layers and have strong inductive biases, which

leads to high performance even with small datasets. However, this inductive bias in turn prevents

CNNs from fully leveraging large-scale datasets. In contrast, ViTs have minimal inductive biases,

which enable them to outperform CNNs when trained on large-scale datasets[12]. Pathology

foundation models can be used as patch-level encoders to extract meaningful features from image

patches, and these extracted features can be applied to downstream tasks such as classification and

segmentation.

One of the major computational challenges in WSI analysis is the massive data size, making direct

slide-level analysis infeasible. The standard solution is dividing each slide into smaller image

patches to facilitate computational processing. Multiple instance learning (MIL) is an effective

approach for slide-level classification, as it aggregates information from individual patches without

requiring patch-level annotations. In heterogeneous tissue slides, where diagnostic value varies

widely among patches, MIL excels by learning to focus on important patches for classification.

In this study, we utilized pathology foundation models as encoders to extract features from image

patches and employed MIL to aggregate patch-level features for classifying expert pathologist-

derived disease categorizations and clinical outcome. Regarding clinical outcome, we evaluated

severe proteinuria (albuminuria $\geq$300 mg/gCre or proteinuria $\geq$1000 mg/gCre). We then

benchmarked the performance of these foundation models against ResNet50[13], a widely used CNN-

based model, to determine their utility in kidney pathology analysis.

Methods

Dataset

Main experiment

In the main experiment, we developed a diagnostic model for classifying healthy control (HC), acute

interstitial nephritis (AIN), and diabetic kidney disease (DKD) using H&E-stained WSIs (Figure 1a).

Training data were obtained from two publicly available datasets: the Kidney Precision Medicine

Project (KPMP, accessed on 20th January 2025)[14] and the Japan-Pathology Artificial Intelligence

Diagnostics Project (JP-AID, accessed on 20th January 2025)[15]. The KPMP dataset comprised 26

HC slides from 21 patients, 26 AIN slides from 12 patients, and 151 DKD slides from 70 patients.

From the JP-AID database, we collected H&E-stained WSIs comprising 21 HC slides, nine DKD

slides, and nine AIN slides. For external validation, an independent dataset of H&E-stained WSIs

was obtained from biopsy slides collected between 2009 and 2025 at the University of Tokyo

Hospital (the UT dataset). The UT dataset included 39 HC slides, 17 AIN slides, and 30 DKD slides.

Patients with other coexisting kidney diseases were excluded. Diagnoses were based on adjudicated

diagnoses (KPMP) and expert pathologist-derived diagnoses (JP-AID and UT). Most HC cases were

derived from transplanted kidney biopsies. Detailed dataset description and selection flowcharts are

presented in Supplementary Methods and Figures S1-S3. This study protocol adhered to the

Declaration of Helsinki and was approved by the University of Tokyo Institutional Review Board

(approval number: 2024526NI).

Exploratory experiment

As an exploratory experiment, we evaluated our pipeline's ability to predict clinical outcome (severe

proteinuria defined as albuminuria ≥300 mg/gCre or proteinuria ≥1000 mg/gCre) using DKD slides

from the KPMP dataset (Figure 1b). Six slides from three cases were excluded because of missing

values. In this exploratory experiment, external validation using the UT dataset was not performed

due to significant class imbalance. Most DKD cases in the UT dataset had severe proteinuria.

Image preprocessing

To prepare images for analysis, each WSI was divided into non-overlapping tiles using Slideflow

version 3.02[16] with the Libvips backend at 20x (128 μm, 256 pixels). Background was removed

using Otsu's thresholding[17], Gaussian blur filtering (sigma = 2, threshold = 0.02), and whitespace

filtering (<45% tissue content). Slides containing fewer than 100 patches were excluded to ensure

consistent image quality and diagnostic reliability. Analyses were primarily performed without stain

normalization, and in the main study we compared performance with and without stain

normalization. Thumbnails of representative slides from each dataset are shown in Supplementary

Figure S4. Variations in staining protocols and slide scanning methods introduce color heterogeneity,

posing challenges in digital pathology analysis[18]. However, recently developed pathology foundation

models trained on pathology slides with diverse color variations have demonstrated robust

performance even without stain normalization[7, 9, 19, 20]. Given these findings, we opted to primarily

analyze the images without stain normalization and assess the robustness of foundation models.

Multiple instance learning

For slide-level classification tasks, we adopted the MIL approach. MIL is a weakly supervised

learning framework that leverages slide-level labels rather than instance-level labels for learning. In

the MIL framework, each WSI is treated as a bag with a slide-level label, whereas the individual

patches within the slide that serve as an instance are not labeled. The overall workflow is illustrated

in Figure 1c. First, feature vectors were extracted from the extracted patches using pretrained

pathology foundation models, including UNI[7], UNI2-h[7], Prov-Gigapath[10], Phikon[11], Virchow[8], and

Virchow2[9], which were pretrained on large-scale pathology slides using SSL. As a baseline, we used

ResNet50[13] pretrained on the ImageNet. A summary of the encoders is presented in Table 1.

ResNet50 was built from the Torchvision library with ImageNet-pretrained weghts[21]. The pretrained

weights of pathology foundation models were downloaded from Huggingface[22]. In this study, we

employed four aggregation methods: max pooling, attention-based MIL (ABMIL)[23], transformer-

based MIL (TransMIL)[24], clustering-constraint attention multiple instance learning (CLAM)[25]. Max

pooling assumes that the single most indicative patch in a bag determines the bag label. ABMIL uses

an attention mechanism to perform weighted aggregation of patch features, with weights trained by a

neural network. TransMIL utilizes a transformer mechanism to learn spatial relationships between

patches via self-attention. CLAM incorporates instance-level clustering into its attention mechanism

to enhance feature representation learning. Among the two variants of CLAM, we employed the

multi-branch variant of CLAM (CLAM-MB), which computes the class-specific attention weights

for each class.

Model development and validation

Main experiment

Each model was trained to predict the diagnostic category among HC, AIN, and DKD. The

hyperparameters used for model development are listed in Supplementary Table S1. To develop the

model, we performed five-fold cross-validation, in which the dataset was randomly split into five

subsets while ensuring a balanced distribution of diagnostic categories across the folds. Multiple

slides from the same patient were kept in the same subset. In each fold, four subsets were used for

training and the remaining subset was used for validation. This process was repeated five times. The

model was trained for 50 epochs per-fold, and the model with the lowest validation loss was selected.

The five trained models were subsequently validated using the external UT dataset to assess their

generalizability.

Exploratory experiment

Five-fold cross validation using DKD cases from the KPMP dataset was performed to predict severe

proteinuria. The hyperparameters used in the exploratory experiment were the same as those in the

main experiment (Supplementary Table S1). The model was trained for 50 epochs per-fold, and the

model with the lowest loss on the internal validation cohort was selected. In this exploratory

experiment, aggregation of patch features was performed using CLAM.

Visualization

Among the four aggregation methods, CLAM-based models were used for visualization. CLAM-MB

leverages an attention mechanism to assign a weight to each patch. Based on these attention scores,

an attention heatmap is generated to visualize diagnostically relevant regions within the slide.

CLAM-MB employs a multi-branch design to learn class-specific attention weights. For each class

label, the model generates a distinct attention map that highlights important regions for its

classification. We used Slideflow-Studio[16] to visualize attention maps with the Turbo colormap,

where warmer colors (yellow to red) represent higher attention scores while cooler colors (green to

blue) indicate lower attention scores. Additionally, we identified the top nine important patches for

classification according to their attention scores.

Statistical analysis

Quantitative or ordinal data are expressed using medians and interquartile ranges or means and 95%

confidence intervals (95%CI). Qualitative data are expressed as numbers and percentages.

Performance metrics, including accuracy, macro-averaged F1 score, and area under the receiver

operating characteristic curve (AUROC) were calculated to assess the predictive performance of the

trained models. Accuracy is the proportion of correct classifications out of total classifications. F1

score is the harmonic mean of precision (the proportion of true positive predictions out of all positive

predictions) and recall (the proportion of true positive predictions out of all actual positive samples).

Macro-averaged F1 score is the arithmetic mean of all per-class F1 scores. The results from the five

cross-validation folds were aggregated and reported as the mean and 95%CI from 1000 bootstrap

iterations. All metric calculations and statistical analyses were conducted using the scikit-learn

package.

Results

Main experiment

Clinical characteristics of the development cohort

The clinical characteristics of the KPMP and JP-AID cohorts used in the main experiment are

presented in Tables 2 and 3. The JP-AID cohort does not provide detailed clinical information other

than age, sex, and diagnosis. For eGFR calculations in the KPMP dataset, where eGFR data are

provided in ranges (e.g., 40–50 ml/min/1.73 m²), the midpoint eGFR was used (e.g., 45.5

ml/min/1.73 m^2). For AIN cases in the KPMP cohort, baseline eGFR values and AKI severity were

presented. Regarding AKI severity of AIN cases, Kidney Disease: Improving Global Outcomes

(KDIGO) AKI stages[26] were provided, with four patients classified as Stage 2 and eight patients as

Stage 3. In the KPMP cohort, DKD cases were characterized by older age and a higher prevalence of

hypertension.

Model development and internal validation

Based on the development cohort (the KPMP and JP-AID datasets), we developed and evaluated

models to predict slide-level diagnosis (HC, AIN, or DKD) using 5-fold cross validation. We

performed a comparative evaluation of seven encoders (ResNet50, UNI, UNI2-h, Phikon, Prov-

Gigapath, Virchow, Virchow2) with four MIL methods (max pooling, ABMIL, TransMIL, and

CLAM). The results are summarized in Figure 2. Among the MIL methods tested, CLAM

consistently showed high performance across all seven encoders. In contrast, max pooling

underperformed relative to the other MIL methods, although the performance did not decline when

Virchow and UNI2-h were used as encoders. Regarding encoders, all pathology foundation models

outperformed ResNet50.

External validation

To investigate the robustness and generalizability of the developed models, we assessed their

performance on the external validation cohort (the UT dataset). The characteristics of the UT dataset

are described in Table 4. Compared with the development cohort, the AIN cases in the UT dataset

consisted of older patients, with a greater proportion of females. Additionally, patients with DKD in

the UT dataset had lower eGFR levels and a higher prevalence of severe proteinuria. The model

performance is summarized in Figure 3. The external validation results followed a similar trend to

those observed in the development cohort: CLAM outperformed the other MIL methods, and all

pathology foundation models surpassed ResNet50. The performance of max pooling-based models

declined substantially in external validation, whereas ABMIL, TransMIL, and CLAM maintained

comparable performance. Regarding encoders, ResNet50 exhibited a marked performance decline in

the external validation cohort. In contrast, UNI, UNI2-h, Virchow, and Virchow2 maintained high

performance. We next assessed the impact of stain variability by applying Macenko stain

normalization to all patches[27]. After stain normalization, each model was trained on the development

cohort and validated on the external validation cohort using CLAM. As shown in Table 5, stain

normalization had a negligible impact on the performance of models based on UNI, UNI2-h,

Virchow, and Virchow2, whereas other encoder-based models demonstrated improved performance

after stain normalization. These findings indicate the limited generalizability of ImageNet-pretrained

ResNet50 and highlight the advantages of pathology foundation models, particularly UNI, UNI2-h,

Virchow and Virchow2, for external applicability.

Visualization of the developed models

To understand how the developed models identified diagnostically important pathological features,

we sampled slides from patients diagnosed with HC, AIN, and DKD in the UT cohort. Using CLAM,

which outperformed other MIL methods, we evaluated seven encoders. For each encoder, the best

model with the highest AUROC out of five folds in the external validation was used. We created

attention heat maps and identified the top nine patches with the highest attention scores per slide

(Figure 4). Analysis of these high-attention patches revealed that classification of HC generally

relied on recognizing healthy tubules (Figure 4a). Notably, the Phikon-based model did not assign

high attention scores to tubular structures, which may explain its inferior performance in the external

validation. Interestingly, UNI2-, Prov-Gigapath-, Virchow-, and Virchow2-based models highlighted

patches exhibiting coagulative tubular cell necrosis. This is consistent with the fact that HC samples

obtained from transplanted kidneys frequently show ischemia-reperfusion injury. Since normal

tubules may also appear in varying degrees in AIN and DKD, ischemia-reperfusion injury is more

specific to transplanted kidneys. Regarding AIN classification (Figure 4b), all models focused on

regions of inflammatory cell infiltration, except for the ResNet50-based model, which incorrectly

emphasized largely normal tubules. For diagnosing DKD (Figure 4c), Virchow- and Vichow2-based

models specifically focused on glomerular alterations, whereas other encoders highlighted

tubulointerstitial and vascular changes. More detailed observations of heat maps from ResNet50-

and Virchow2-based models are presented in Figure 5. A sample slide was obtained from a patient

diagnosed with AIN in the UT cohort, which is the same slide as shown in Figure 4b. The Virchow2-

based model correctly classified this slide as AIN, whereas the ResNet50-based model misclassified

it as HC. Attention scores for each diagnostic label (HC, AIN, and DKD) were used to visualize the

regions of focus for the models in the disease classification task. In the whole slide view, the

Virchow2-based model appropriately captured AIN-related histological features with high attention

scores shown in red, covering most of the tissue in the attention map for AIN (Figure 5a). In Region

A, where the tissue structure remained relatively intact, the attention map for HC assigned high

scores, whereas the attention maps for AIN and DKD assigned low scores. Region B exhibited

prominent inflammatory cell infiltration within the interstitium, with high attention scores for AIN

and low scores for HC. The attention map for DKD showed elevated scores only in the glomerular

regions. These findings indicate that the Virchow2-based model successfully identified key

histological patterns associated with each diagnostic category. In contrast, the attention maps

generated by the ResNet50-based model failed to capture diagnostically important structures, leading

to misclassification of this slide as HC (Figure 5b). While this model correctly assigned high

attention scores to Region A for HC classification, it also assigned high scores to Region B,

indicating a failure to recognize inflammatory cell infiltration.

Exploratory experiment

In the exploratory experiment, we developed predictive models with DKD cases from the KPMP

dataset using 5-fold cross-validation, focusing on severe proteinuria (albuminuria $\geq$300 mg/gCre or

proteinuria $\geq$1000 mg/gCre). In the exploratory experiment, we employed CLAM as the MIL

method. The results of the exploratory experiment are summarized in Figure 6. All foundation

models showed higher performance than ResNet50, and in particular, UNI2-h demonstrated the

highest performance with an AUROC of 0.872 (95%CI 0.794-0.949).

Discussion

In this study, we demonstrated that pathology foundation models pretrained on large-scale pathological image datasets are highly effective feature extractors for kidney pathology analysis compared with ResNet50 pretrained on ImageNet. Furthermore, we successfully integrated foundation models with the MIL framework to achieve high diagnostic performance without requiring patch-level annotations. MIL aggregates patch-level features without relying on patch-level labels, making it a practical approach for large-scale histopathological analysis, where detailed manual annotation is infeasible. Among the MIL methods evaluated, CLAM showed the best performance. CLAM aggregates patch-level features through attention pooling and calculates both slide-level classification and instance-level losses to better separate positive and negative instances, enabling the model to efficiently learn discriminative features from important patches.

As for disease diagnosis prediction, foundation models' superiority was consistent when applied to the external validation cohort from a different institution. A major challenge in computational pathology is inter-institutional staining variability, which has been shown to hinder robust feature extraction[28]. Remarkably, our findings indicate that foundation models effectively extracted meaningful features, even without stain normalization, demonstrating robustness against staining variations. This advantage was particularly evident when compared with ResNet50, which exhibited a marked performance drop in external validation. Among the pathology foundation models, UNI,

UNI2-h, Virchow, and Virchow2 showed robust performance regardless of whether stain

normalization was applied. This finding is consistent with a recent study showing greater robustness

of UNI2-h and Virchow2[29]. Attention heat map analysis further revealed that ResNet50 was less

effective in extracting pathological features compared with the pathology foundation models. Of

note, Virchow and Virchow2 specifically focused on glomeruli in DKD classification, suggesting

that these encoders successfully recognized glomerular structures. This finding may be attributed to

their substantially larger training datasets compared with other pathology foundation models.

Understanding the factors that influence the performance of foundation models in kidney pathology

analysis is crucial for optimizing pretraining strategies and developing more effective models.

Diagnosis of kidney pathology typically relies on a combination of multiple stains. In this study, we

focused on AIN and DKD, both of which exhibit distinct morphological features on H&E-stained

slides. This explains why the model for the disease classification task demonstrated a good

performance despite being trained solely on H&E-stained slides. For other kidney diseases such as

lupus nephritis and membranous glomerulonephritis, integrating multiple stains may be crucial for

improving diagnostic accuracy. Indeed, a recent study showed that combining multiple stains

enhanced the prediction of clinical remission in lupus nephritis[30]. The foundation models used in this

study were trained primarily on H&E slides. Therefore, to improve the diagnostic performance in

kidney pathology, developing domain-specific pathology foundation models trained on large-scale,

multi-stained slides is an important next step.

In the exploratory experiment, we attempted to predict severe proteinuria in patients with DKD

using the same pipeline as in the main experiment. Pathology foundation models also demonstrated

higher performance than ResNet50. Because the majority of patients with DKD in the UT cohort had

severe proteinuria, we could not perform external validation. Therefore, a larger and more diverse

external cohort is needed to assess the model's generalizability.

This study has several limitations that warrant consideration. First, post-transplantation cases used as

healthy controls exhibited mild ischemia-reperfusion injury, indicating that they may not fully

represent normal kidney histology. Second, while we excluded cases with coexisting kidney diseases

based on pathology reports, some DKD and AIN slides contained atherosclerotic lesions, likely

attributable to aging or hypertension, raising the possibility that the model learns hypertensive

changes rather than diabetic changes. In fact, visualization analysis revealed that the models

identified patches with interstitial fibrosis as important for DKD classification (Figure 2c). Of note,

the models based on Virchow and Virchow2 recognized glomerular alterations as important features

for DKD diagnosis, indicating that the pathological features prioritized by the model may differ

depending on the encoder. Third, our model was limited to classifying HC, AIN, and DKD. In

clinical practice, patients often present with mixed pathological features, complicating categorization

into a single diagnosis. Fourth, the relatively small number of slides used in this study may limit the

generalizability of our findings. However, even with this limited training set, the pathology

foundation models effectively extracted meaningful features and demonstrated good diagnostic

performance in the external cohort.

In conclusion, we utilized pathology foundation models as feature extractors and demonstrated

superior performance in the slide-level classification of kidney specimens compared with ImageNet-

pretrained ResNet50. Their robustness against staining variability and inter-institutional differences

highlights their potential for real-world clinical implementation. Since detailed annotations are not

required, this approach can be readily extended to diagnosis of other diseases and prediction of

clinical outcomes. This approach will facilitate the development of diverse kidney pathology

analysis models, which can be particularly valuable in regions with limited access to pathologists

and as an educational support tool for trainees.

Disclosure

All the authors declared no competing interest.

Data sharing statement

The results here are in part based upon data generated by the Kidney Precision Medicine Project, accessed on January 20, 2025 (https://www.kpmp.org). KPMP is funded by the National Institute of Diabetes and Digestive and Kidney Diseases (Grant numbers: U01DK133081, U01DK133091, U01DK133092, U01DK133093, U01DK133095, U01DK133097, U01DK114866, U01DK114908, U01DK133090, U01DK133113, U01DK133766, U01DK133768, U01DK114907, U01DK114920, U01DK114923, U01DK114933, U24DK114886, UH3DK114926, UH3DK114861, UH3DK114915, UH3DK114937). The KPMP dataset used in this study is publicly available at https://atlas.kpmp.org/.

The JP-AID dataset is available at https://jpaid.jp/ upon request, following the prescribed procedures.

The UT dataset is not publicly available due to data protection regulations.

Acknowledgement

We sincerely thank Prof. Matthias Kretzler from Division of Computational Medicine and Bioinformatics, University of Michigan, Ann Arbor, Michigan for his helpful advice. We also thank

Dr. Isao Matsui from Osaka University, Dr. Ryo Inuzuka, Dr. Masaya Sato, Dr. Hiroaki Ikushima,

and Dr. Syohei Hanaoka from the University of Tokyo Hospital for their guidance and insightful

discussions that have contributed to the completion of this study. We appreciate Kenichi Hashimoto

from Division of Urology of the University of Tokyo in collecting the materials. This research was

conducted using the JP-AID database of the Japanese Society of Pathology.

Funding

This study was supported by Cross-ministerial Strategic Innovation Promotion Program (SIP) on

"Integrated Health Care System" Grant Number JPJ012425.

Author contributions

YK and IM conceived and designed the study. YK, IM, and DY collected clinical data and kidney

biopsy specimens. YK, IM, and HA digitized kidney biopsy sections. YK performed data analysis,

deep learning, and visualization. Y.K. wrote the manuscript. IM, SK, and TT edited the manuscript.

SK, HK, TU, NT, TT, and MN supervised the study.

Supplementary Material

Supplementary Figure S1   Flowcharts for patients' inclusion and exclusion in the KPMP dataset

Supplementary Figure S2   Flowcharts for patients' inclusion and exclusion in the JP-AID dataset

Supplementary Figure S3   Flowcharts for patients' inclusion and exclusion in the UT dataset

Supplementary Figure S4   Thumbnails of example slides form each dataset

Supplementary Table S1   Hyperparameters for MIL models

Supplementary Methods   Dataset description

References

1. Jayapandian CP, Chen Y, Janowczyk AR*, et al.* Development and evaluation of deep learning–based segmentation of histologic structures in the kidney cortex with multiple histologic stains. *Kidney Int* 2021; **99:** 86-101.

2. Holscher DL, Bouteldja N, Joodaki M*, et al.* Next-Generation Morphometry for pathomics-data mining in histopathology. *Nat Commun* 2023; **14:** 470.

3. Pilva P, Bulow R, Boor P. Deep learning applications for kidney histology analysis. *Curr Opin Nephrol Hypertens* 2024; **33:** 291-297.

4. Chen T, Kornblith S, Norouzi M*, et al.*: A Simple Framework for Contrastive Learning of Visual Representations. In *Proceedings of the 37th International Conference on Machine Learning* (vol 119), edited by Hal D, III, Aarti S, Proceedings of Machine Learning Research, PMLR, 2020, pp 1597-1607

5. Abe M, Niioka H, Matsumoto A*, et al.* Self-Supervised Learning for Feature Extraction from Glomerular Images and Disease Classification with Minimal Annotations. *J Am Soc Nephrol* 2025; **36:** 471-486.

6. Dosovitskiy A, Beyer L, Kolesnikov A*, et al.* An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale. *arXiv* 2020; **abs/2010.11929**.

7. Chen RJ, Ding T, Lu MY*, et al.* Towards a general-purpose foundation model for computational pathology. *Nat Med* 2024; **30:** 850-862.

8. Vorontsov E, Bozkurt A, Casson A*, et al.* Virchow: A Million-Slide Digital Pathology Foundation Model. *arXiv* 2023; **abs/2309.07778**.

9. Zimmermann E, Vorontsov E, Viret J*, et al.* Virchow2: Scaling Self-Supervised Mixed Magnification Models in Pathology. *arXiv* 2024; **abs/2408.00738**.

10. Xu H, Usuyama N, Bagga J*, et al.* A whole-slide foundation model for digital pathology from real-world data. *Nature* 2024; **630:** 181-188.

423   11.   Filiot A, Ghermi R, Olivier A*, et al.* Scaling Self-Supervised Learning for Histopathology
424   with Masked Image Modeling. *medRxiv* **2023.07.21.23292757**.

426   12.   Li J, Chen J, Tang Y*, et al.* Transforming medical imaging with Transformers? A
427   comparative review of key properties, current progresses, and future perspectives. *Med*
428   *Image Anal* 2023; **85:** 102762.

430   13.   He K, Zhang X, Ren S*, et al.* Deep Residual Learning for Image Recognition. *2016 IEEE*
431   *Conference on Computer Vision and Pattern Recognition (CVPR)* 2015**:** 770-778.

433   14.   de Boer IH, Alpers CE, Azeloglu EU*, et al.* Rationale and design of the Kidney Precision
434   Medicine Project. *Kidney Int* 2021; **99:** 498-510.

436   15.   Sakai Yasuhiro KM, Fukayama Masashi, Yoshizawa Akihiko. Development of artificial
437   intelligence to help pathological diagnosis-Japan pathology AI diagnostics (JP-AID) project.
438   *Impact* 2019; **6:** 40-42.

440   16.   Dolezal JM, Kochanny S, Dyer E*, et al.* Slideflow: deep learning for digital histopathology
441   with real-time whole-slide visualization. *BMC Bioinformatics* 2024; **25:** 134.

443   17.   Otsu N. A threshold selection method from gray-level histograms. *IEEE Trans Syst Man*
444   *Cybern* 1979; **9:** 62-66.

446   18.   Schömig-Markiefka B, Pryalukhin A, Hulla W*, et al.* Quality control stress test for deep
447   learning-based diagnostic model in digital pathology. *Mod Pathol* 2021; **34:** 2098-2108.

449   19.   Vorontsov E, Bozkurt A, Casson A*, et al.* A foundation model for clinical-grade
450   computational pathology and rare cancers detection. *Nat Med* 2024; **30:** 2924-2935.

452   20.   Wolflein G, Ferber D, Meneghetti AR*, et al.* Benchmarking Pathology Feature Extractors
453   for Whole Slide Image Classification. *arXiv* 2024; **arXiv:2311.11772v5**.

455   21.   TorchVision: PyTorch's Computer Vision library. In, GitHub repository, GitHub, 2016

457   22.   Wolf T, Debut L, Sanh V*, et al.* HuggingFace's Transformers: State-of-the-art Natural
458   Language Processing. *arXiv* 2019; **abs/1910.03771**.

23. Maximilian Ilse JMT, Max Welling. Attention-based Deep Multiple Instance Learning. *arXiv* 2018; **1802.04712v4**.

24. Zhuchen Shao HB, Yang Chen, Yifeng Wang, Jian Zhang, Xiangyang Ji, Yongbing Zhang. TransMIL: Transformer based Correlated Multiple Instance Learning for Whole Slide Image Classification. *arXiv* 2021; **2106.00908v2**.

25. Lu MY, Williamson DFK, Chen TY*, et al.* Data-efficient and weakly supervised computational pathology on whole-slide images. *Nat Biomed Eng* 2021; **5:** 555-570.

26. KDIGO Clinical Practice Guideline for Acute Kidney Injury. *Kidney Int Suppl* 2012; **2**.

27. Macenko M, Niethammer M, Marron JS*, et al.* A method for normalizing histology slides for quantitative analysis. *2009 IEEE International Symposium on Biomedical Imaging: From Nano to Macro* 2009**:** 1107-1110.

28. Boschman J, Farahani H, Darbandsari A*, et al.* The utility of color normalization for AI-based diagnosis of hematoxylin and eosin-stained pathology images. *J Pathol* 2022; **256:** 15-24.

29. Edwin D. de Jong EM, Jonas Teuwen. Current Pathology Foundation Models are unrobust to Medical Center Differences. *arXiv* 2025; **arXiv:2501.18055**.

30. Cheng C, Li B, Li J*, et al.* Multi-stain deep learning prediction model of treatment response in lupus nephritis based on renal histopathology. *Kidney Int* 2025; **107:** 714-727.

Legends

Figure 1. Overview of study cohorts and workflow of slide-level classification using multiple

instance learning

(a) The diagram illustrates the diagnostic model training and evaluation process. The KPMP dataset

(total 203 HE WSIs from 103 patients) and the JP-AID dataset (total 39 HE WSIs from 39 patients)

across three diagnostic categories were used for model training and internal validation via 5-fold

cross validation. The development cohort was randomly split into five subsets while ensuring a

balanced distribution of diagnostic categories across the folds. Multiple slides from the same patient

were kept in the same subset. In each fold, four subsets were used for training and the remaining

subset was used for validation. The 5 trained models were subsequently evaluated on the UT dataset,

an external validation cohort comprising 86 H&E-stained WSIs from 86 patients. (b) DKD cases

from the KPMP dataset were used for developing the classification model for severe proteinuria in

the exploratory experiment. Severe proteinuria was defined as proteinuria ≥ 1000 mg/gCre or

albuminuria ≥ 300 mg/gCre. For proteinuria classification, six slides from three patients were

excluded due to missing data. (c) The workflow for WSI analysis involves four steps: (1) Patch

extraction is conducted by dividing WSIs into patches (256x256 pixels) at 20x magnification.

Background patches are removed during preprocessing. (2) Feature extraction is performed using

pretrained encoders (ResNet50, UNI, UNI2-h, Prov-Gigapath, Phikon, Virchow, and Virchow2). (3)

The extracted patch features are aggregated using four MIL methods (max-pooling, ABMIL,

TransMIL, and CLAM). (4) The slide-level classifier predicts the diagnostic category.

KPMP, kidney precision medicine project; H&E, hematoxylin and eosin; WSIs, whole slide images;

JP-AID, Japan-Pathology Artificial Intelligence Diagnostics; HC, healthy control; AIN, acute

interstitial nephritis; DKD, diabetic kidney disease; UT, the University of Tokyo Hospital; MIL,

multiple instance learning; ABMIL, attention-based MIL; TransMIL, Transformer based MIL;

CLAM, clustering-constrained attention multiple instance learning.

Figure 2. Model performance for disease classification in the development cohort

Performance metrics (Accuracy, F1 score, and AUROC) of models using seven encoders (ResNet50,

UNI, UNI2-h, Prov-Gigapath, Phikon, Virchow, and Virchow2) and four aggregation methods (max

pooling, ABMIL, TransMIL, and CLAM) in the internal validation cohort are presented. Data are

reported as means and 95% confidence intervals.

AUROC, area under the receiver operating characteristic curve; ABMIL, attention-based multiple

instance learning; TransMIL, transformer-based multiple instance learning: CLAM, clustering-

constraint attention multiple instance learning.

Figure 3. Model performance for disease classification in the external validation cohort

Performance metrics (Accuracy, F1 score, and AUROC) of models using seven encoders (ResNet50,

UNI, UNI2-h, Prov-Gigapath, Phikon, Virchow, and Virchow2) and four aggregation methods (max

pooling, ABMIL, TransMIL, and CLAM) in the external validation cohort are presented. Data are

reported as means and 95% confidence intervals.

AUROC, area under the receiver operating characteristic curve; ABMIL, attention-based multiple

instance learning; TransMIL, transformer-based multiple instance learning: CLAM, clustering-

constraint attention multiple instance learning.

Figure 4. Attention heatmaps and top nine high-attention patches

HC (a), AIN (b), and DKD (c) slides in the UT dataset were used to visualize how each model built

on seven encoders (ResNet50, UNI, UNI2-h, Prov-Gigapath, Phikon, Virchow, and Virchow2)

extracted features from image patches. Attention scores for the true label (HC, AIN, or DKD) were

used to visualize attention heatmaps with Turbo colormap, where warmer colors (yellow to red)

represent higher attention scores, and cooler colors (green to blue) indicate lower attention scores.

The top nine patches with the highest attention scores were identified.

Scale bar=500 μm. HC, healthy control; AIN, acute interstitial nephritis; DKD, diabetic kidney

disease

Figure 5. Attention heatmaps of models using Virchow2 and ResNet50 in the disease

classification task

A sample slide was obtained from a patient diagnosed with AIN in the UT cohort. Attention scores

for each diagnostic label (HC, AIN, and DKD) were used to visualize the regions of focus for the

models in the disease classification task. Heatmaps were generated using the Turbo colormap.

Attention heatmaps of the Virchow2-based model (a) and the ResNet50-based model (b) for each

label (HC, AIN, and DKD) are shown. The original H&E-stained images were used as references.

H&E, hematoxylin-eosin; HC, healthy control; AIN, acute interstitial nephritis; DKD, diabetic

kidney disease. Scale bar=100 μm.

Figure 6. Model performance for classification of severe proteinuria

Performance metrics (Accuracy, F1 score, and AUROC) of models using seven encoders (ResNet50,

UNI, UNI2-h, Prov-Gigapath, Phikon, Virchow, and Virchow2) with CLAM in the KPMP-DKD

cohort for the severe proteinuria classification task are presented. Data are reported as means and

95% confidence intervals.

AUROC, area under the receiver operating characteristic curve.

Data are shown in mean (95%CI)

Table 1. Summary of encoders used in this study

Model	Training data	Architecture	Model size	Feature dimension
ResNet50	ImageNet (1400K images)	CNN	25.6M	1024
UNI	100K WSIs	ViT-L	303M	1024
UNI2-h	350K WSIs	ViT-H	681M	1536
Prov-Gigapath	170K WSIs	ViT-G	1134M	1536
Phikon	6.1K WSIs	ViT-B	86M	768
Virchow	1500K WSIs	ViT-H	632M	2560
Virchow2	3100K WSIs	ViT-H	632M	2560

559   WSI, whole slide images; CNN, convolutional neural network; ViT, vision transformer.

Table 2. The characteristics of cases in the KPMP cohort

	HC	AIN	DKD
N	21	12	70
Age, yr			
20-29	2 (9.5)	0 (0.0)	0 (0.0)
30-39	6 (28.6)	7 (58.3)	6 (8.6)
40-49	7 (33.3)	1 (8.3)	12 (17.1)
50-59	6 (28.6)	4 (33.3)	15 (21.4)
60-69	0 (0.0)	0 (0.0)	29 (41.4)
70-79	0 (0.0)	0 (0.0)	8 (11.4)
Sex			
Male	10 (47.6)	10 (83.3)	41 (58.6)
Female	11 (52.4)	2 (16.7)	29 (41.4)
History of diabetes	0 (0.0)	3 (25)	70 (100)
History of hypertension	4 (19.0)	4 (33.3)	65 (92.9)
eGFR[a]	NA	79.5 (74.5-89.5)	44.5 (34.5-64.5)
Proteinuria[b]			
Severe	0 (0.0)	2 (16.7)	44 (62.9)
Moderate	0 (0.0)	1 (8.3)	17 (24.3)
Normal	0 (0.0)	2 (16.7)	6 (8.6)
NA	21 (100)	7 (58.3)	3 (4.3)
KDIGO AKI Stage			
Stage 3		8 (66.7)	
Stage 2		4 (33.3)	

KPMP, the Kidney Precision Medicine Project; HC, healthy control; AIN, acute interstitial nephritis;

DKD, diabetic kidney disease; NA, not available; KDIGO, Kidney Disease: Improving Global

Outcomes; AKI, acute kidney injury.

[a]Since eGFR data were provided as categorical data (e.g. 40-50 ml/min/1.73 m²). The midpoint of

each range was used as the estimated value. For the AIN group, the eGFR values represented

baseline values.

[b]Proteinuria severity was classified as follows:

Severe: proteinuria $\geq$ 1000 mg/gCre or albuminuria $\geq$ 300 mg/gCre

Moderate: 150 mg/gCre $\leq$ proteinuria < 1000 mg/gCre or 30 mg/gCre $\leq$ albuminuria < 300 mg/gCre

Normal: proteinuria < 150 mg/gCre or albuminuria < 30 mg/gCre

If both proteinuria and albuminuria data were available, the more severe category was assigned.

Data are expressed as median (interquartile range) or n (%).

Table 3. The characteristics of cases in the JP-AID cohort

	HC[a]	AIN	DKD
N	21	9	9
Age, yr			
10-19	1 (4.8)	2 (22.2)	0 (0.0)
20-29	7 (33.3)	1 (11.1)	0 (0.0)
30-39	4 (19.0)	1 (11.1)	1 (11.1)
40-49	3 (14.3)	0 (0.0)	0 (0.0)
50-59	4 (19.0)	1 (11.1)	2 (22.2)
60-69	2 (9.5)	1 (11.1)	3 (33.3)
70-79	0 (0.0)	1 (11.1)	4 (44.4)
80-89	0 (0.0)	2 (22.2)	0 (0.0)
Sex			
Male	13 (61.9)	6 (66.7)	6 (66.7)
Female	8 (38.1)	3 (33.3)	3 (33.3)

JP-AID, Japan-Pathology Artificial Intelligence Diagnostics Project; HC, healthy control; AIN, acute

interstitial nephritis; DKD, diabetic kidney disease.

[a]The demographic information for the transplanted kidneys in the JP-AID HC group may originate

from the recipients rather than the donors. Since the database does not provide detailed clarification,

this remains uncertain and should be interpreted with caution.

Data are expressed as median (interquartile range) or n (%).

Table 4. The characteristics of the UT dataset

	HC	AIN	DKD
N	39	17	27
Age, yr			
10-19	0 (0.0)	1 (5.9)	0 (0.0)
20-29	0 (0.0)	1 (5.9)	0 (0.0)
30-39	2 (5.1)	1 (5.9)	3 (17.6)
40-49	8 (20.5)	1 (5.9)	4 (23.5)
50-59	11 (28.2)	4 (23.5)	2 (11.8)
60-69	13 (33.3)	1 (5.9)	12 (70.6)
70-79	4 (10.3)	6 (35.3)	4 (23.5)
80-89	1 (2.6)	1 (5.9)	2 (11.8)
Sex			
Male	15 (38.5)	5 (29.4)	15 (55.6)
Female	24 (61.5)	12 (70.6)	12 (44.4)
History of diabetes	1 (2.6)	3 (17.6)	27 (100)
History of hypertension	9 (23.1)	4 (23.5)	22 (81.5)
eGFR	80.9 (66.6-86.2)	22.2 (18.6-33.0)	41.4 (25.8-52.4)
Proteinuria			
Severe	0 (0.0)	8 (47.1)	22 (81.5)
Moderate	0 (0.0)	8 (47.1)	5 (18.5)
Normal	39 (100)	1 (5.9)	0 (0.0)

581   UT, the University of Tokyo Hospital; HC, healthy control; AIN, acute interstitial nephritis; DKD,

582   diabetic kidney disease

583   Data are expressed as median (interquartile range) or n (%)

584 **Table 5. Model performance for disease classification in the validation cohort with or without**

585 **color normalization**

AUROC	without stain normalization	with stain normalization
ResNet50	0.768 (0.740 - 0.798)	0.815 (0.784 - 0.846)
UNI	0.942 (0.933 - 0.953)	0.945 (0.925 - 0.964)
UNI-2h	0.958 (0.945 - 0.967)	0.966 (0.960 - 0.972)
Prov-Gigapath	0.918 (0.896 - 0.935)	0.944 (0.924 - 0.960)
Phikon	0.844 (0.820 - 0.869)	0.902 (0.883 - 0.926)
Virchow	0.949 (0.939 - 0.960)	0.946 (0.934 - 0.957)
Virchow2	0.953 (0.940 - 0.966)	0.964 (0.959 - 0.969)

586 AUROC, area under the receiver operating characteristic curve.

587 Data are shown in mean (95%CI)

a **Main experiment**

Development cohort

Total 242 HE WSIs
HC: 47 slides
AIN: 35 slides
DKD: 160 slides

KPMP dataset
203 HE WSIs
HC: 26 slides
AIN: 26 slides
DKD: 151 slides

JP-AID dataset
39 HE WSIs
HC: 21 slides
AIN: 9 slides
DKD: 9 slides

Model development and internal validation

Classification: HC or AIN or DKD

5-fold cross validation
1st ⇒ Model 1
2nd ⇒ Model 2
3rd ⇒ Model 3
4th ⇒ Model 4
5th ⇒ Model 5

Training fold   Validation fold

External validation cohort

UT dataset
83 HE WSIs
HC: 39 slides
AIN: 17 slides
DKD: 27 slides

b **Exploratory experiment**

Model development and internal validation

KPMP dataset
DKD: 145 slides

Severe proteinuria

5-fold cross validation
1st ⇒ Model 1
2nd ⇒ Model 2
3rd ⇒ Model 3
4th ⇒ Model 4
5th ⇒ Model 5

Training fold   Validation fold

c

1. Tissue segmentation Patch extraction

True label: AIN

Foreground-background separation
Divided into non-overlapping tiles
(256x256 px at 20x)

2. Feature extraction

Encoders
ResNet50
UNI
UNI2-h
Prov-Gigapath
Phikon
Virchow
Virchow2

Feature vectors

3. Aggregation

MIL models
Max pooling
ABMIL
TransMIL
CLAM

4. Slide-level prediction

Prediction

HC	0.000
AIN	0.987
DKD	0.013
Final prediction	AIN

Attention heat maps and top 9 high attention patches

a HC — ResNet50, UNI, UNI2-h, Prov-Gigapath, Phikon, Virchow, Virchow2

b AIN

c DKD