Baseline nowcasting methods for handling delays in epidemiological data

Authors: Kaitlyn E. Johnson[1], Maria L. Tang[2], Emily Tyszka[3], Laura Jones[3], Barbora Nemcova[4], Daniel Wolffram[4], Rosa Ergas[3], Nicholas G. Reich[5], Sebastian Funk[1], Jonathon Mellor[2], Johannes Bracher[2], Sam Abbott[1]

1. Department of Infectious Disease Epidemiology and Dynamics, London School of Hygiene and Tropical Medicine, London, United Kingdom
2. Chief Data Officer Group, UK Health Security Agency, London, United Kingdom
3. Massachusetts Department of Public Health, Boston, United States of America
4. Institute of Statistics, Karlsruhe Institute of Technology (KIT), Karlsruhe, Germany
5. School of Public Health and Health Sciences, University of Massachusetts, Amherst, United States of America

*Corresponding author

E-mail: kaitlyn.johnson@lshtm.ac.uk (KJ)

Abstract

Up-to-date real-time disease surveillance data can provide critical public health insights, however reporting delays can create downward bias in the latest data. Nowcasting methods designed to correct for this bias remain underused in public health practice due to their complexity, lack of tailored documentation, or technical barriers. Methodological advances in nowcasting are also hampered by the absence of standardised benchmarks for evaluating new methods. We propose an empirically motivated family of nowcasting methods and accompanying R package, *baselinenowcast*, which addresses these dual needs. We validated our default method specification against the baseline method that was used in the German COVID-19 Nowcast Hub and on which our approach was based. Using these data, we conducted an analysis to compare different ways of configuring the method and evaluated performance against our method's default specification. We then used our approach on norovirus surveillance data from the United Kingdom Health Security Agency (UKHSA) and compared performance against three methods evaluated in a previous study. Our baseline method improved estimates compared to unadjusted data across all case studies. We found that the optimal choice of baseline method specification depends on context but that our default performed well in a range of settings. Applied to UKHSA norovirus data, our method helped us understand performance differences for the model currently used in public health practice. Our method and software can be used both as a straightforward nowcasting method and provides a benchmark for nowcasting model development.

Author Summary

Reporting delays in public health surveillance systems can create a misleading impression of declining trends in recent data. While a number of "nowcasting" methods have been developed

to correct for this bias, widespread adoption in public health practice has yet to be realized.

Currently, there is no simple method to perform nowcasting that both meets the needs of public

health practice and can be used as a benchmark for further methodological advancement. In

this paper, we present a family of baseline nowcasting methods and an accompanying software

package designed specifically to address these two gaps. We evaluate the performance of the

default method against other methods used in previous studies and assess the performance of

different method specifications. Our findings indicate that our baseline methods improve

performance over unadjusted data or more ad-hoc baseline nowcasting approaches, provide an

interpretable and accessible nowcasting solution for public health practice, and are useful as a

standard benchmark for more advanced methods.

52   Introduction

Delays in epidemiological data present a challenge in public health surveillance, as they can

create a misleading impression of declining trends in recent data. This bias is due to "right-

truncation" of primary events (e.g. symptom onset or hospital admission), where recent events

are systematically under-represented because reporting delays cause some portion of these

events to not yet be present in the real-time surveillance data. This affects numerous

surveillance systems across pathogens, including COVID-19, mpox, and norovirus [1–7].

Recently, there have been several applications of nowcasting methods aimed at correcting for

this downward bias. Examples include public facing data dashboards such as at Massachusetts

Department of Public Health [8], Dutch National Institute for Public Health and the Environment

(RIVM) [9], and the U.S. Centers for Disease Control and Prevention (U.S. CDC) [10], and

internally at UK Health Security Agency (UKHSA) for norovirus, flu, and RSV nowcasting,

Robert Koch Institute (RKI) for acute respiratory incidence nowcasting, and the U.S. CDC for

estimation of the effective reproductive number for flu and COVID-19, on publicly available data

[3,11,12], and as part of outbreak responses [13,14]. However, these applications still remain

the exception, with the majority of potential use-cases handled by showing uncorrected data or

shortening time series to remove partially complete data, which has the effect of reducing the

amount of information available on the latest trends [2,15].

Several challenges remain in addressing systematic downward bias in surveillance systems due

to right-truncation of primary epidemiological events in public health practice. Frontline

practitioners require methods that are statistically rigorous, straightforward to implement, and

can be easily communicated to stakeholders. However, no currently available tools meet these

needs fully. The chain ladder method [16] is an empirically-driven approach that could meet the

needs of practitioners as it is close to the kinds of methods often implemented in real world

settings. However, current implementations of the method either lack domain-specific features

and documentation (e.g. the *chainladder* R package [17] designed for nowcasting insurance

claims) or have been implemented in an ad-hoc manner rather than intended for general

applicability [3,8]. Other methods designed specifically for nowcasting epidemiological data are

often complex due to the flexibility and feature set that supporting a range of epidemiological

settings requires [18–22], leading to a high barrier to entry. This means practitioners may have

to choose between delaying insights (by not making full use of recent data), risk misleading

interpretations from unadjusted data, developing methods that may lack reusability across

different contexts or not be fully validated, or use methods not appropriate for their context.

For methodological research, the absence of standardised benchmarks makes understanding

the value of novel methods more challenging. In other fields and other settings, baseline

methods, which are relatively straightforward methods to implement and serve as a reference

point for evaluating other methods [23], have been suggested as a potential solution for this

issue [24]. Without consistent baselines for evaluation, researchers and public health

practitioners may struggle to quantify incremental improvements or understand trade-offs

between model complexity and performance across different epidemiological contexts [23].

The chain ladder approach has been used on an ad-hoc basis to meet this need in [3,8,25]. For

wider usage, a standardised method is needed.

We propose a family of baseline nowcasting methods and an accompanying R package,

baselinenowcast, designed to address these dual needs in infectious disease surveillance,

building on the empirically-driven chain ladder implementation described by Wolffram et al.

[3,16,17]. In this work, we validate our approach by comparing the Wolffram et al. [3] method

against our baseline method with a matching specification using German COVID-19 data. We

then compare the performance of our different method specifications applied to both the

German COVID-19 data and UKHSA norovirus surveillance data [2] alongside existing

nowcasting methods.

Methods

Input data requirements: reporting triangle

Our method requires the number of incident cases indexed by the reference time (e.g. date of

symptom onset, specimen collection, or hospital admission) and report time (e.g. the date a

positive test is reported into a surveillance system). Data in this format allows us to reconstruct

reporting delays (i.e. the time from the reference time to the report time). Combining these

reporting delays results in a reporting delay distribution (i.e the distribution of times from the

reference time to the time that a case is reported) for each reference time. In wide format, where

each reference time is a row and each reporting delay is a column, this data is known as the

"reporting triangle" [26] because the observations form a triangle with the bottom right elements

not yet observed as of the most recent reference time. The goal of nowcasting is to estimate

these unobserved events. If we do not do so, and instead sum only the observed columns, then

our case counts will be systematically downward biased. The fully observed version of these

data, the "complete reporting matrix", can be used to estimate the reporting delay distribution as

each row can be normalised by the sum of that row to give the proportion reported at a given

reporting delay. It is data of this format, or reconstructions thereof, that we use in our

nowcasting method.

Figure 1. Illustration of the reporting triangle and corresponding case counts aggregated
by reference time. Rows of the reporting triangle represent reference times and columns
represent reporting delays with numbers indicating the incident case count at that reference
time and reporting delay. Colors indicate the delay, with solid shading indicating observed case
counts and transparent shading indicating not yet observed cases, as of the most recent
reference time. The bar chart shows the cases summed by reference time, with gray lines
indicating the total number of cases reported at each reference time as of the most recent
reference time, and black lines indicating the eventually observed number of cases.

Figure 1 depicts a visual representation of the reporting triangle on the left and the

corresponding case counts aggregated by reference time on the right. The solid shading

indicates what has been observed as of the most recent reference time, and the lighter shading

indicates what will eventually be observed. If we were to aggregate cases by reference time as

of the most recent reference time, we would be missing cases from delays 1, 2, and 3 for the

most recent reference time, delays 2 and 3 from the second most recent reference time, etc.,

resulting in systematic downward bias in the recent trend, as indicated by the gray line in the bar

chart. Eventually, the counts would be revised upwards as the elements of the reporting triangle

are observed at later delays, resulting in the trend in the final counts being corrected (black

lines).

Statistical framework

Overview

Our approach, based on the chain ladder method in the version described by Wolffram et al. [3],

consists of five key steps, each of which are separate modular operations that can be modified

(Figure 2). In the following, we give a high-level overview of the "default" specification of our

method, its data ingestion settings and supported variations. For the full details see the SI Text.

Mathematical model.

Step 1: Delay estimation

● The empirical delay distribution can be estimated directly from a complete reporting

matrix by dividing the sum of each column by the total count.

● By default we use the partial observations from the most recent data points in order to

incorporate the most up-to-date data on the delay distribution. To do so, we need to first

155	"fill in" the missing observations in the reporting triangle (white boxes in bottom right of
156	reporting triangle, Figure 2) by assuming that the delay distribution is constant over time
157	and:

a.   First compute the ratio between the first delay and the second delay for all

reference times when both delays are fully observed (e.g. the ratio of the sum of

the first 5 green vs yellow rows in Figure 1 (4+2+2+3+4)/(3+2+1+2+3) = 1.36)

b.   Divide the partially observed row of the first delay column by the ratio to impute

the missing component of the second delay (e.g. the case count at reference

time = 5 and delay = 0, 4, from Figure 1, is used to impute the case count at

reference time = 5, delay = 1 as 4/1.36 = 2.93)

c.   Repeat for the missing elements of each column filling in from left to right.

Figure 2. Schematic illustration of the *baselinenowcast* method. The reporting triangle
contains the number of cases by reference time (rows) and reporting delay (columns), where
colors represent the delays, and with white indicating observations that have not yet been
observed and shading here indicating whether values have been observed (solid) or imputed
(shaded). The delay distribution is estimated empirically from the reporting triangle. Point
nowcasts are generated using the delay distribution and the partial observations at each
reference time to impute the missing values in the bottom right of the triangle. Uncertainty is
quantified by repeating this procedure for a number of past retrospective nowcast times and
comparing the estimates to the observations. The point nowcast predictions and the uncertainty
parameters are used to generate probabilistic predictions, and these are combined with the
observations to generate probabilistic nowcasts.

Step 2: Point nowcast generation

● Given a delay distribution and a reporting triangle, we impute the missing observations

to generate a point nowcast matrix: a complete reporting matrix where the missing

observations have been filled in with point estimates (indicated by the shaded bottom

right of the triangle in Figure 2, step 2). The rows sum to a point estimate of the final

counts at each reference time.

● We use a similar approach to that used to impute the missing elements of the reporting

triangle in step 1 but now we:

a. Estimate the final case counts by dividing the current total reported counts by the

proportion estimated to be reported by this time (e.g. if there are 4 case counts

observed so far at a reference time of 5 and a delay of 0 from Figure 1, which is

estimated to represent 40% of eventual cases from the delay distribution in step

1 of Figure 2, we expect 4 / 0.40 = 10 total final cases)

b. For each unobserved delay, we multiply the estimated final case counts by the

proportion of cases observed on that delay (e.g. if an estimated 10% of cases are

reported with a delay of 3 from the delay distribution in step 1 of Figure 2 and we

expect 10 total cases, we expect 10 * 0.1 = 1 to be reported with a delay of 3)

● We implement a slightly more complex version of this to account for zero reported cases

observed so far.

Step 3: Uncertainty estimation

● We use past nowcast errors compared to observed values as of the current nowcast

date to quantify uncertainty.

a. We generate retrospective point nowcasts (light shaded bars and blue lines in

Figure 2, step 3) by repeating steps 1 and 2 for a number of past, retrospective

nowcast times.

b. An observation model, which is by default a negative binomial, is fit to the

predicted (shaded bars, blue lines Figure 2, step 3) and observed (solid bars,

black lines Figure 2, step 3) components for each nowcast horizon.

Step 4: Predicted probabilistic nowcast

● We generate probabilistic predictions by sampling draws (indicated by the stacked

shaded bottom right reporting triangles in Figure 2, step 4) from the observation model at

each horizon with a mean given by the point nowcast and the horizon specific

uncertainty parameter (bar chart with distributional overlay in Figure 2, step 4) estimated

in step 3.

● By default, the target we compare to is the sum of the not-yet observed components of

the point nowcast for each reference time.

Step 5: Combine with observations

● We then add what has already been observed (reporting triangle Figure 2, step 5) to

each draw (shaded bottom right of reporting triangle Figure 2, step 5) of the predicted

probabilistic nowcast for what has yet to be observed to create a complete probabilistic

nowcast of the final counts for each reference time point (indicated by gray shading in

line plot Figure 2, step 5).

As well as model choices, we also make data ingestion assumptions in our default approach.

These are all conditioned on the maximum delay observed in the data making them more robust

to different datasets. The maximum delay is set by the user when creating the reporting triangle

based on when the data is expected to stabilize, with shorter maximum delays being more

computationally efficient.

1. **Overall data use:** We use three times the maximum delay number of reference times (in

line with Wolffram et al. [3]).

2. **Delay distribution estimation:** 50% of the reference times are used for delay

estimation, with a minimum requirement of at least one more than the number of

reference times with partial observations.

3. **Uncertainty Estimation:** 50% of the reference times are used as retrospective point

nowcast times. If there is insufficient data, the method uses the oldest retrospective

nowcast time with at least the same amount of historical data for delay estimation as is

used for the point nowcast at the current nowcast time, and requires that there are at

least two retrospective nowcasts containing sufficient data.

Available options for model specification

As our method is modular with each step being independent, there are a large number of

potential variations, designed with common scenarios in infectious disease surveillance in mind.

We have implemented the following:

Input data options:

- Use of a complete reporting matrix or a reporting triangle.

- Changing the total number of reference time points used to estimate the delay

distribution and uncertainty parameters, balancing precision (from more data) against

capturing recent variability (from more current data).

- Reference and report dates of different temporal granularities, e.g. daily reporting of

weekly reference dates, weekly reporting of daily reference dates, and weekly reference

and report dates.

Delay estimation approaches:

- Estimate delays from the same data set / stratum being nowcasted or "borrow" estimates

from another reporting triangle. This may be useful for sparse data sets, such as in small

subpopulations or locations or for rare pathogens and emerging outbreaks.

-    Changing the proportion of data used to estimate the delay with the same tradeoffs as

for changing the overall amount of data input.

-    Adjusting the maximum delay, but this should be based on empirically observed delay

rather than being viewed as a modelling option.

Uncertainty quantification variations:

-    Observation models can be fit using different datasets than those used for delay

estimation or for the nowcast.

-    Changing the proportion of data used to estimate the observation model with the same

tradeoffs as in the delay estimation case.

-    The parametric form of the observation model can be changed.

-    The observation model can be fit jointly for any grouping of observations. The target

choice for the final nowcast can be specified such that the uncertainty estimation occurs

on this target (i.e. 7-day rolling sum).

Software implementation

Our baseline nowcasting methods are implemented in the R package *baselinenowcast*, which

provides a modular pipe-friendly interface for nowcasting right-truncated surveillance. The

package has minimal dependencies, primarily relying on base R functionality [27]. A primary

workflow function *baselinenowcast()* implements the default method, whilst individual

component functions enable customisation of specific steps through a consistent interface. The

package accepts input data in a standard data frame format with columns for reference date,

report date, and count. An additional feature is its compatibility with the *epinowcast* R package

objects [19], allowing users to leverage that package's preprocessing and data conversion

functions and facilitating comparison to more *epinowcast* nowcasting models. Low-level

functions use a matrix input for efficiency. We followed software best practices, including unit

testing, continuous integration, code review via pull requests, and documentation driven

development throughout the package's development

(https://github.com/epinowcast/baselinenowcast) [28,29].

Evaluation analysis

To evaluate nowcast performance from quantile-based outputs, we use the weighted interval

score (WIS). WIS is a widely used proper scoring rule used to assess forecast quality of

probabilistic quantile-based forecasts [23,30,31] and is the probabilistic equivalent of the

absolute error of point forecasts. We decompose WIS into overprediction, underprediction, and

dispersion components. As WIS is an absolute measure of error, we compute the relative WIS

throughout, with the default specification of our baseline method used as a comparison unless

otherwise noted. We assess forecast calibration using coverage metrics, where we compute the

proportion of all observations within a specified prediction interval. For example, a well-

calibrated forecast would have 50% of the observations fall within the 50% prediction intervals

(between the 25th and 75th quantiles). See the following sections for details on the quantiles

used to compute the WIS scores and coverage metrics.

German COVID-19 Nowcast Hub validation

To verify that our *baselinenowcast* implementation worked as expected and to characterize the

performance of our method overall and across age groups and nowcast dates, we produced

nowcasts using our method's default specification and compared them to the nowcasts

produced using the the baseline nowcasting method described in Wolffram et al. [3] (referred to

in that paper as KIT simple nowcast) which our method and default model settings were based

upon. Both methods were applied to the COVID-19 hospitalization data from the German

COVID-19 Nowcast Hub (the Hub) [32]. The dataset represents 7-day rolling sums of

hospitalisation incidences due to COVID-19 in Germany, which were used to guide public health

policy. German hospitalization counts were aggregated by the date of positive test result rather

than admission (see Wolffram et al. [3] for details). They were hence particularly affected by

delays, as these not only comprised the time from hospitalization to report, but also from

positive test to hospitalization. Data then sometimes took several weeks or months to fully

stabilize. We used all the available data spanning from 22 November 2021 to 29 April 2022, with

preliminary data available from 1 July 2021. We used the pre-processed dataset available in the

Hub's GitHub repository [32], which contains a cleaned version of the reporting triangle that

teams submitting to the Hub were instructed to use.

We generated nowcasts of the 7-day rolling sum of COVID-19 hospitalisation incidence in

Germany each day for national-level aggregated data and age-stratified data. We applied our

baseline nowcast with a maximum delay of 40 days, consistent with the specification of the KIT

simple nowcast model used in [3], and with a training volume of 120 reference dates used by

each nowcast (this means that 60 reference dates were used for delay estimation and 60

retrospective nowcast datasets were created for uncertainty estimation). For consistency with

the KIT simple nowcast model, we estimated uncertainty in the predicted components of the

final "target", which in this case was the 7-day rolling sum of the partial expectation of

hospitalisation incidence. This made our baseline approach theoretically equivalent to the KIT

simple nowcast model described in [3], except that they did not include a correction for zero

counts in the partial observations for a given reference time.

However, when verifying our method against the KIT simple nowcast codebase, we identified an

issue impacting the dispersion estimate (see SI Text. *Description of KIT simple nowcast*

implementation issue and revised nowcasts for more details). We fixed the issue in our fork of

the repository and retrospectively generated new nowcasts, which we labeled as the "revised

KIT simple nowcast". We use this as a point of comparison in the main text results, with a

comparison to the original implementation detailed in the supplement and referred to as the

"original KIT simple nowcast".

We visualised summary statistics derived from the data. We plotted the mean reporting delay

over time for national-level aggregations and individual age groups to identify any temporal

patterns. We also visualised the full distribution of delays nationally and by age group to

characterise differences in reporting processes across strata.

We then visualised the nowcasts against the eventually observed values to qualitatively verify

equivalence for a subset of nowcast dates. We then quantitatively evaluated both sets of

nowcasts using a rolling evaluation dataset of 40 days after each nowcast date, restricted to a

maximum delay of 40 days for each reference date, consistent with the analysis performed in

section 3.7 of Wolffram et al. [3]. This means that for each nowcast date, we used a different

evaluation dataset corresponding to the data available 40 days after that nowcast date. We

evaluated nowcasts for horizon days 0 to - 28 days. We used the same quantiles as in [3]

(0.025, 0.1, 0.25, 0.5, 0.75, 0.9, 0.975) to compute the WIS. We computed WIS scores for our

baseline method, the revised KIT simple nowcast, and the original KIT simple nowcast. We also

calculated the empirical coverage at the 50% and 95% prediction intervals. We calculated the

relative WIS across multiple dimensions: by nowcast horizon (from 0 to - 28 days), by nowcast

date, and by age group.

Performance of different *baselinenowcast* method specifications applied to

German COVID-19 data

To assess whether other possible *baselinenowcast* method specifications designed specifically

for the epidemiological context could further improve performance, we performed a sensitivity

analysis of the following pairwise method comparisons: borrowing delay and uncertainty

estimates from national-level data when nowcasting for specific age groups, using only

complete reporting matrices versus reporting triangles, using shorter (50%) and longer (200%)

training periods than those used in the default specification, and estimating delays

independently for each weekday and combining.

We generated nowcasts of the 7-day rolling sum of COVID-19 hospitalisation incidence in

Germany each day for the same period as in the validation study for all age groups with each

method specification. We visualised predictions against the 40-day ahead rolling evaluation

dataset values, focusing on same-day nowcasts, and again used the weighted interval score

(WIS) and coverage metrics for quantitative assessment, using the same quantiles and

prediction intervals as described in the validation section. We again stratified our analysis by

nowcast horizon (from 0 to - 28 days), and by age group. We calculated WIS for all method

specifications and relative WIS compared to the default method specification.

369 Case study: UKHSA norovirus surveillance

To further validate our approach and explore its utility as a baseline method we produced

nowcasts using three specifications of our baseline method for UKHSA's norovirus surveillance

data, and compared the performance of those nowcasts to the performance of three models in

Mellor et al. [2] including an alternative baseline approach. These data consist of laboratory-

confirmed norovirus cases in England from winter 2023/2024. Each case record includes a

specimen date (when the sample was collected) and a report date (when the test result was

ingested into the surveillance system). The difference between these dates forms the reporting

delay, which typically peaks at 1-2 days with most reports occurring within 7 days. However,

approximately 20% of specimens obtained in a given week were not reported by the end of that

week, creating a substantial right-truncation effect in recent data. Because of the variable

results across days of the week observed in the original study, we assumed that the dataset

exhibited strong day-of-week-periodicity, with reporting patterns varying systematically across

weekdays.

We implemented our baseline nowcasting method using three different method specifications.

All method specifications used a maximum delay of 14 days to match the approach in the

original study for the Generalized Additive Model (GAM) model. The first method was our

default baseline method, except that we fit to the most recent 56 days of data rather than the

default of 42 days (3 times the maximum delay of 14 days). This was motivated by following the

settings used for the GAM model so that the methods used equivalent amounts of training data

and so were more directly comparable. We refer to this method specification as the base

specification. Based on our hypothesis that day of the week variations in the delays were

present we used two further methods. The second method independently estimates nowcasts

for each day of the week, using the most recent 11 weeks of data (11 data points per day of

week), to use a similar amount of data to the base specification (56 days), though in practice we

needed more than 56 days of data due to data sparsity in some weekdays. The third model had

the same structure as the second model but with more training data, instead using the 56 latest

data points from each particular day of the week (spanning approximately 56 weeks of historical

data) or as much as was available, to use the same amount of training data as the base

specification for each weekday's delay estimation. We refer to these method specifications as

the *baselinenowcast* weekday filter small/large training volume specifications respectively.

Following Mellor et al. [2], we nowcast each Sunday from November 5th 2023, to March 10

2024 and evaluated performance on horizons 0 to -7 days using rolling 50-day ahead of the

nowcast date evaluation datasets (similar to the rolling evaluation applied to the German

COVID-19 data). For consistency with the evaluation in Mellor et al. [2], we did not restrict the

evaluation dataset to only reports within the maximum delay. We then compared nowcast

performance from three of the models considered in Mellor et al. [2]: a GAM, an implementation

of epinowcast, and a naive baseline method. The GAM was developed by the authors of the

original study [2] and uses a latent model of the number of cases as a function of reference time

and delay, accounting for weekday effects in the reference time and the reporting delay. The

epinowcast implementation uses the R package *epinowcast* [19] to estimate a Bayesian

hierarchical model of the number of observed cases by reference time and delay, using a latent

variable approach to model the underlying trend in the epidemic growth rate accounting for

weekday effects in the underlying infections. The Mellor et al. [2] baseline implementation

assumes that the cases predicted each day of this week will be equal to the observed count

from the previous week (essentially propagates the previous week forward), producing only a

median nowcast.

We first visualised the nowcasts against the eventually observed values to qualitatively assess

performance. To align with Mellor et al. [2], we calculated WIS using only the 50% and 90%

prediction intervals. Coverage metrics were also calculated using the 50% and 90% prediction

intervals. We otherwise followed the evaluation approach of our earlier case studies, using our

base specification as the baseline for the relative WIS calculation. We stratified by day of week

in addition to week of nowcast, and stratified empirical delays by day of week as well as over

time. Unlike the original paper, which examined both daily and weekly aggregated scores, we

focused on daily scores.

Evaluation analysis implementation

427 Our analysis pipeline was implemented using *targets* [33] for reproducible workflow

428 management, with *scoringutils* [31,34] used for nowcast evaluation. All analyses were

429   performed in R [27] with key dependencies including *dplyr* [35] for data manipulation and

430   *ggplot2* [36] for visualisation. The code and analyses are available at

431   https://githhub.com/epinowcast/baselinenowcast-paper [37,38].

Results

German COVID-19 Nowcast Hub validation

Because our baseline method's implementation is a generalization of the KIT simple nowcast

used by Wolffram et al. [3], we initially verified our method by comparing our baseline method's

results against retrospective nowcasts generated directly from the KIT simple nowcast

codebase using the same input data. In this process, we identified a difference in the outputs

despite following identical model specifications and having nearly identical mathematical

methods, which led us to further investigate the method implemented in the original KIT simple

nowcast codebase. We then identified a bug in the original implementation (see SI Text.

Description of KIT simple nowcast implementation issue and revised nowcasts for more details).

We consulted with the authors, whom are co-authors of this work, fixed the bug in our fork of the

repository, and regenerated retrospective nowcasts which we have labeled as the revised KIT

simple nowcast, with comparisons to the original implementation in the Supplement labeled as

the original KIT simple nowcast (SI Figure 1).

Our method produced equivalent nowcasts to the revised KIT simple nowcast (Figure 3A, 3B,

3C). Compared to the original KIT simple nowcast, our baseline method performed better, with

an overall relative WIS of 0.88 nationally and 0.91 by age groups (SI Figure 1A, B), indicating

that the bug fix improved nowcast performance. Exploratory data analysis indicated that the

delay distribution (Figure 3E) differed between age groups, with the 00-04 age group having the

shortest mean delay of 3.71 days whilst the 35-59 age group experienced the longest delays,

averaging 5.88 days. The mean reporting delay showed changes over time roughly on the time

scale of changes in case counts (Figure 3E, 3A).

Our baseline method was consistently less biased than no adjustment (gray line Figure 3A).

Underprediction, overprediction, and dispersion contributed approximately 32%, 18%, and 50%

respectively of the total score across age groups. Our method had 55% coverage at 50%

prediction intervals and 96% coverage at 95% prediction intervals, indicating it had slightly wider

prediction intervals than observed in the data (SI Figure 6,7). There was moderate variation

across nowcast dates that appeared to be correlated with changes in reporting delays and

peaks in case counts (Figure 3A, 3C, 3E), as is to be expected as higher case counts will be

associated with scores of a higher magnitude. Across age groups, WIS ranged from 4.05 for the

00-04 age group to 45.76 for the 60-79 age-group, again reflecting the magnitude in case

counts with 00-04 contributing the fewest hospital admissions and 60-79 year olds contributing

the most admissions (Figure 3D).

Figure 3: Validation of our baseline nowcasting method using German COVID-19 data compared to the revised KIT simple nowcast model. A. Nowcasts from our baseline model and the revised KIT simple nowcast model for all age groups plotted against eventually observed values aggregated across all age groups, coloured by model. Because both sets of nowcasts were nearly identical, coloring and shading is not distinguishable between the two. Observed data are shown as solid lines with gray indicating data available at the nowcast date and red indicating the final evaluation data. Dashed vertical lines indicate the date of the nowcasts. Shading indicates prediction intervals of each nowcast. Nowcasts are shown from horizons 0 to -28 days. B. Decomposed overall WIS aggregated across age strata. Shading indicates WIS component (dispersion, overprediction, underprediction), colour indicates model. C. Daily mean WIS scores summarised across age strata and 28 horizon days, coloured by model. Identical WIS scores over time renders the two lines indistinguishable. D. Decomposed WIS scores across age groups. Shading indicates WIS component, colour indicates model. E. Mean reporting delay over time. Colour indicates age group, with the national average highlighted in black. Mean reporting delays were calculated using the last 40 reference dates, corresponding to the maximum delay, for each nowcast date and age group. F. Cumulative distribution functions (CDFs) of the mean delay distribution across the entire study period. Colour indicates age group with the national average highlighted in black.

Performance of different *baselinenowcast* model specifications applied to German COVID-19 data

We found varying patterns of relative performance compared to the default configuration,

depending on age group and method specification (Figure 3). Borrowing delay and uncertainty

estimates for each age group from aggregate data reduced nowcast performance (relative WIS

(rWIS) of 1.14, Figure 4B). Using only the complete reporting matrices resulted in a slight

reduction in performance overall (rWIS 1.04, Figure 4B). Doubling the training volume used for

delay and uncertainty estimation improved performance (rWIS 0.94, Figure 4B), while reducing

it by half decreased performance (rWIS 1.08, Figure 4B). Applying the weekday filter method

improved performance most of all the method specifications we explored (rWIS 0.93, Figure

4B).

Borrowing delay and uncertainty estimates from national data for each age group had the most

pronounced reduction in performance in the sparsest age group (00-04) (rWIS 2.28), with the

degradation in performance compared to the default specification driven by overprediction

(Figure 4Ai, 4Aix, 4E, SI Figure 10). This reduction in performance when borrowing delay and

uncertainty from all age groups is possibly due to the lower delay in the 00-04 age group

compared to the overall delay across all age groups (Figure 3E, 3F). The greatest improvement

amongst the age strata from borrowing delay and uncertainty estimates was modest, occurring

in the 60-79 age group (rWIS 0.99)(Figure 4E, SI Figure 10). Borrowing strategies showed

reduced coverage compared to the default (Figure 4C). Borrowing strategies also resulted in

reduced performance at early horizons (Figure 4D) with the least available data, likely reflecting

the reduced performance for the 00-04 age group at a horizon of 0 (Figure 4A). Averaging

across age strata, performance was reduced due to borrowing for nearly all nowcast dates,

except for at the beginning of February when we saw a slight improvement from borrowing (SI

Figure 12), which might be due to the rapid fluctuation in the mean delay in the 05-14 age group

a few weeks prior (Figure 4E).

Compared to the default, which uses the reporting triangle, visual inspection of nowcasts using

only complete reporting matrices showed slightly improved performance in the 00-04 age group

and degraded performance in the 60-79 age group (Figure 4Aiii, 4Aiv, 4Axi, 4Axii). The greatest

improvement from using complete reporting matrices was in the 00-04 age group (rWIS 0.90,

Figure 4Aiii, 4Aiv) and the greatest reduction in performance was in the 35-59 age group (rWIS

1.24) (Figure 4E, SI Figure 10). Across all age strata, complete reporting matrices demonstrated

improved performance at the end of December 2021 and February 2022, with reduced

performance elsewhere, suggesting improved performance of this specification during times of

stable reporting delays (SI Figure 12). Reporting triangle completeness resulted in

improvements near intermediate horizons -8 to -15 (Figure 4D) and increased coverage (Figure

4C).

Varying training data volume resulted in the most substantial differences in performance in the

00-04 age group which had the lowest counts. For this age group, doubling training volume

showed improved performance (rWIS 0.89), while reducing the training volume by 50% reduced

performance (rWIS 1.16)(Figure 4E, SI Figure 10). Visual inspection of the nowcast

performance over time in the 00-04 and 60-79 year old age groups shows that trends in

performance from increased and decreased training volume tend to oppose one another (Figure

4Av, 4Avi, 4Axiii, 4Axiv), indicating that there might not be a single optimal setting due to

tradeoffs between overfitting to noise in reporting delays versus failing to incorporate the most

recent temporal changes in reporting delay (SI Figure 12). Doubling the training volume resulted

in improved performance at horizons between -8 and -15, whereas a 50% reduction in the

training volume had considerably worse performance at distant horizons (-20 to -28) (Figure

4D). Increasing training data volume resulted in higher coverage (98% coverage), while

reducing training volume reduced coverage (90% coverage), compared to the default (96%

coverage) at 95% prediction intervals (Figure 4C).

Performing independent nowcasts of each weekday and combining them improved nowcast

performance by reducing the large day-of-week variation observed in the default method (Figure

4Avii, 4Aviii, 4Axv, 4Axvi). Accounting for weekday effects in reporting had the greatest

performance improvement in the most recent 7 horizon days (Figure 4D, SI Figure 9). Across

age groups, the greatest performance improvement was observed in the 80+ age group (rWIS

of 0.89), followed by the 60-79 age group (rWIS 0.92), with reductions in performance observed

in the 00-04 and 05-14 age groups (rWIS of 1.09 and 1.11 respectively), which may be due to

less of a consistent weekday effect in the sparser age groups compared to the larger age

groups (Figure 3E).

Figure 4: Performance comparison of different *baselinenowcast* method specifications compared to the default method. A. Upper plots show the daily same-day (0- horizon) nowcasts from the 00-04 (left) and 60-79 (right) age group for each method specification grouping showing the default validation model alongside variants from a specific permutation category: first row shows borrowing strategy variations (i, ix), second row shows reporting triangle completeness variations (iii, xi), third row shows training data volume variations (v, xiii), and the fourth row shows weekday filter variations (vii, xv). Observed data are shown as solid lines with gray indicating data available at the nowcast date and red indicating the final evaluation data. Colours indicate the method specification throughout, with the default approach in purple. Lower subplots show the relative WIS over time from the 00-04 (left) and 60-79 (right) age group relative to our default model with first row showing borrowing strategy variations (ii, x), second row showing reporting triangle completeness variations (iv, xii), third row showing training data volume variations (vi, xiv), and the fourth row showing weekday filter variations (viii, xvi). The horizontal reference line at 1.0 indicates performance parity with the validation default, values below 1.0 indicate improved performance of the method specification being considered. B. Overall performance comparison between all model configurations across all age groups, with decomposed absolute WIS (dispersion, overprediction, underprediction). Colour indicates method specification, with the default approach in purple. C. Empirical coverage for age group stratified nowcasts at 50% and 95% prediction intervals by method specification. Horizontal reference lines indicate the nominal coverage levels (50% and 95%). D. Relative WIS by nowcast horizon summarised across age groups. The horizontal reference line at 1.0

592 indicates performance parity with the default with values lower than 1.0 indicating improved
593 performance of the method specification being considered. E. Relative decomposed WIS by age
594 group, faceted by method specification grouping. Shape indicates relative WIS component
595 (underprediction, dispersion, and overprediction).

Case study: UKHSA norovirus surveillance

Visual inspection indicates that nowcasts from our base specification showed better alignment

with eventual observed data compared to the naive baseline approach used in Mellor et al. [2]

which was based on projecting the previous week's data forward (Figure 5A, 5B, SI Figure 13).

Comparing the external model implementations to our base specification, the epinowcast model

had slightly better performance than our base specification (Figure 5E, 5F, SI Figure 13), with

similarly high levels of uncertainty, while the GAM model showed reduced uncertainty and better

overall performance compared to our base specification (Figure 5C, 5D, SI Figure 13).

Overall, compared to our base specification, the Mellor et al. [2] baseline performed worse

(rWIS 2.29), and both the the GAM model (rWIS 0.65) and the epinowcast implementation

performed better (rWIS 0.89) (Figure 5I). The GAM model performed best relative to our base

specification in December 2023 and late January to early February 2024 (Figure 5D), whereas

the epinowcast implementation performed best relative to our base specification early

December (Figure 5F). The absolute WIS of our base specification and the Mellor et al. models

was consistent over time except for on January 14, 2024 (SI Figure 13), where all models

performed poorly due to what appears to be initial underreporting in the most recent two days

resulting in underpredictions by all models. Relatively speaking the GAM and epinowcast

models both performed better than our base specification at this point (Figure 5D, 5F, SI Figure

13).

Our base specification and the GAM model were similarly calibrated (SI Figure 15) with slightly

different coverage patterns. All models had 50% prediction intervals that were too wide with

69% (base specification), 59% (GAM), and 58% (epinowcast) coverage. At 90% prediction

intervals, all models were well covered at 90% (base specification), 91% (GAM) and 88%

(epinowcast) coverage (SI Figure 15). The Mellor et al. [2] baseline predictably undercovered

for all prediction intervals and weekdays since it contained only a median estimate (SI Figure

15,16).

Performance varied substantially by day of week in the Mellor et al. models compared to our

base specification (Figure 5J, 5L). As nowcasts were only conducted on Sundays, weekdays

effectively reflect performance by nowcast horizon, though weekday effects in both specimen

collection date and reporting also play a role. As expected, the most recent day with the least

amount of data (Sunday, 0 horizon) showed the worst performance across models, whilst days

further in the past showed progressively improved performance (Figure 5L). When comparing

the GAM method and our base configuration, the most pronounced relative reduction in

performance of our base specification was on Sunday, largely driven by reduced dispersion in

the GAM compared to our base specification (Figure 5J, 5L), which had high dispersion on

Sundays. Both the GAM and our method performed similarly for horizons -7 to -4 (weekdays

Mon-Thurs, Figure 5J, 5L). Comparing the epinowcast implementation to our base specification

revealed the largest relative improvement in performance of the epinowcast implementation was

on Friday, when our base specification tended to underpredict (Figure 5L). Our base

specification performed better than the epinowcast implementation for horizons -7 to -4

(weekdays Mon-Thur, Figure 5L).

Comparing our model variants to the base configuration, both weekday filter small and large

training volume configurations reduced performance (rWIS 1.51 and 1.26 respectively) (Figure

5G, 5H, 5I). The visual differences were most notable in December 31, 2023 and January 7,

2024, where the weekday-filter variants appeared to exhibit more dispersion and overprediction

than our base specification (Figure 5G, 5H, SI Figure 13). Overall, our base specification

underpredicted whereas the weekday filter variations had higher dispersion and over prediction

(Figure 5I). At 50% prediction intervals the weekday filter small and large training volume

configurations had 74% and 76% coverage respectively compared to 58% coverage in our base

specification (SI Figure 15). Our weekday-filter configurations performed less stably than our

base model specification over time, with particularly poor relative performance of the weekday-

filter with small training volume on November 26, 2023, and both configurations on December

31, 2023 and January 7, 2024 (Figure 5G, 5H, SI Figure 13). Similar to the GAM and

epinowcast models, the relative performance differences were most pronounced on Sunday.

Both weekday-filter variants performed worse relatively on Sunday compared to our base

specification (Figure 5J), but generally performed similarly on other days of the week (Figure

5J,L). The reduction in performance on Sunday appeared to be due in large part to dispersion

for both weekday-filter variants, and in particular overprediction for the weekday-filter variant

with a small training volume (Figure 5L).

Figure 5: Nowcasting performance applied to UKHSA norovirus surveillance data. A-C-E-G. Weekly nowcasts compared to our base configuration, for three models used in Mellor et al. and compared to our two day-of-week filtered configurations. Observed data are shown as solid lines with gray indicating data available at the nowcast date and red indicating evaluation data. Nowcasts are shown out to 7 days as in Mellor et al. Shading indicates prediction intervals and colour indicates model, with the base specification in purple. B-D-F-H. Relative WIS over time (by week) compared to our base configuration. colours indicate models. Horizontal dashed line at 1.0 indicates performance parity with our base configuration, with value less than 1.0 indicating performance improvement of the method being considered. I. Overall performance comparison between all models, with decomposed absolute WIS (dispersion, overprediction, underprediction) displayed as stacked bar charts for direct comparison across our three variants and the three reference models from Mellor et al. Colour indicates model. J. Relative WIS by

day of week for each model compared to our base specification with colour indicating model.
Horizontal dashed line at 1.0 indicates performance parity with our base configuration. K.
Distribution of mean reporting delays by weekday shown as violin plots with colours indicating
the weekday. Black triangle indicates the mean delay for that weekday across nowcast dates. L.
Mean reporting delays were calculated using the last 14 days of data (corresponding to the
maximum delay). M. Mean reporting delay over time, with colours indicating the day of week
and black indicating the mean reporting delay averaged across all weekdays. Mean reporting
delays were calculated using the last 14 days of data (corresponding to the maximum delay).
N. Cumulative distribution functions (CDFs) of the mean delay distribution. colours indicate date
of the week with black indicating the mean reporting delay averaged across all week days.

682 Discussion

Our baseline nowcasting method improved estimates of recent disease incidence compared to

unadjusted data across all datasets evaluated. We verified that our *baselinenowcast*

implementation was equivalent to nowcasts produced using a revised bug-fixed implementation

of the original baseline method used in the German Nowcast Hub, and confirmed that it

improved performance compared to the original implementation, highlighting the value of

developing reproducible software for methods implementation to prevent the propagation of

errors. As the original implementation of the KIT simple nowcast, despite the implementation

bug, was competitive with more complex methods in German Nowcast Hub [3], ours is likely to

have been even more competitive. Our base specification substantially improved performance

over the baseline used in the Mellor et al. [2] study, and helped to identify the horizons,

weekdays, and nowcast dates in which the more complex models differed in performance

compared to our baseline.

When we analysed the performance of different model specifications to understand tradeoffs

and discover whether other specifications could improve nowcast performance in the context of

the German COVID-19 data used in the Hub, we found modest improvements from applying a

weekday filter to account for day of week effects in reporting and from increasing the amount of

training volume used for delay and uncertainty estimation. Had these features been

implemented in the German Nowcast Hub, this model would have been even more competitive,

approaching the performance of the top performing model. This highlights the importance of

exploratory data analysis to identify patterns, such as weekday effects and the time scale of

changing reporting delays, to help determine optimal method specifications. We found reduced

performance when deploying a strategy to borrow delay and uncertainty estimates from across

all age groups. This approach reduced performance in the age groups with a greater difference

in their average delay compared to the national average, as using a misspecified delay

generally led to overprediction, again highlighting the importance of exploratory data analysis.

However, at times of rapidly fluctuating reporting delays we would expect borrowing to be more

beneficial as it will act to reduce noise in the delay estimate due to within-strata outliers.

In the UKHSA norovirus dataset, our model specifications fitting delay estimates independently

to each weekday didn't result in improved performance compared to our base configuration,

likely because these methods required that we use a longer historical time period to have

sufficient historical data for delay and uncertainty estimation. The reporting delay shifted enough

over time to favor a more recent delay estimate, with less drastic weekday effects in delays than

we had initially anticipated. These findings highlight that the distribution of delay estimates

across strata, weekdays, and nowcast dates are key considerations when choosing model

specifications, and can likely be used as a heuristic [39] to choose which model specifications

are most appropriate in different epidemiological contexts.

Whilst we evaluated our approach across several datasets and through a range of method

specifications, we did not consider a range of other possible method specifications. For

example, users might also wish to use a different parametric distribution to model nowcast

uncertainty. In this analysis we only considered negative binomial observation models applied to

the target dataset, which in this case were always count data. Other valid error models can be

readily explored, given the modular design of our baseline package. Additionally, users might

wish to use our existing functionality in different combinations. For example, in this paper, we

have only considered sharing information across all groups for both delay estimates and

uncertainty, compared to independent estimates of both. A user might instead want to pool

information for delay estimation but estimate uncertainty separately for each strata, or vice

versa. We also only considered increasing training volume for both delay and uncertainty

estimation together, and a user may wish to modify the combination of training data used for

each task. A strength of our framework is that it supports these alternatives through its modular

design.

For consistency and comparability with the original studies, we used the same evaluation

metrics as those studies. This approach facilitated direct comparisons but meant we did not

explore potentially more appropriate metrics, such as evaluating on log-transformed scales [40],

which can more effectively capture relative differences when counts span multiple orders of

magnitude, such as in the different age strata in the German Nowcast Hub COVID-19 data.

Similarly, whilst WIS is a valid choice, we could have used Continuous Ranked Probability

Score (CRPS), which scores probabilistic forecasts based on a full distribution of samples from

the predictive distribution, avoiding information loss from using a limited set of quantiles. This

was a particular issue in the Mellor et al. [2] comparison, where we followed their approach of

using just two intervals (50th and 90th) when calculating WIS, where additional intervals may

have better reflected the distribution of predictions. While this reduces the breadth of evaluation

of the full predictive distribution, it has the benefit of focusing on evaluating only the prediction

intervals that drive decision-making, namely those that are being visualised and presented to

decision-makers. Another issue is that the use of retrospective datasets may not fully capture

performance in truly prospective settings where evolving data availability and reporting changes

create additional challenges. This is particularly true of the German COVID-19 data, where we

used a final pre-processed reporting triangle for all analyses as vintages of that reporting

triangle available each day were not systematically archived. However, we mitigated this issue

by using case studies where data on reference and report times was available, as much as

possible, as it would have been in real-time, and not tuning our models based on performance

against these case studies. Additionally, our focus on proper scoring rules provides a

standardised assessment but might not capture all dimensions of nowcast quality relevant to

decision-making [41]. Finally, the datasets selected, while diverse, do not represent the full

spectrum of delay structures and reporting processes encountered in public health surveillance.

Multiple methods have been proposed as nowcasting approaches in infectious disease

surveillance. Most of these methods jointly estimate reporting delays and the final number of

cases [18,21,22,26,42], though other methods for nowcasting are similar to ours in that they

require specifying an independently estimated delay distribution [43]. The joint approach has the

advantage that the full set of training data is used to estimate both delays and uncertainty,

whereas our baseline method requires use of a proportion of the training data for delay

estimation, so that we have sufficient data to estimate uncertainty using the same amount of

training data applied at different retrospective nowcast times. Other methods differ in how they

model the time evolution of the final number of cases, the delay distribution, and the observation

model. For example, some assume a parametric form for the reporting delay distribution, while

others assume a non-parametric delay. A few methods enable estimation of time-varying delays

[7,42]. Commonly, hazard-based formulations are used [18,21,44]. Methods also take varying

approaches to smoothing, including the use of geometric random walks [21,26,42] and B-

splines [22]. Individual methods have also been extended to support modelling day of the week

variation, covariate inclusion, public holiday anomalous reporting, and transmission processes

[4,6,7,19,20]. Bayesian methods [6,7,18,19,26,44,45] can be particularly useful in settings with

sparse data, where the ability to specify priors and expected reporting patterns is critical, for

example, in novel outbreaks or situations with very low case counts. However, many of these

methods are relatively complex which can make them difficult to inspect, validate, or extend,

and may make it unclear when these models are inappropriate and prone to failure due to

reasons such as unidentifiability or non-convergence. While other domains have

implementations of a similar multiplicative approach, such as the *chainladder* R [16,17] package

designed for nowcasting insurance claims, we have not seen widespread adoption likely due to

the lack of examples in epidemiological contexts or the addition of features specific to the

infectious disease context.

In contrast, our approach focuses on a minimal set of well-defined, modular components that

are simple and easy to explain. The method has a modular, pipe-friendly design enabling users

to customise specific components. By breaking the nowcasting method into distinct

components, users can adapt, inspect and validate each part of the model. This simplicity

makes implementation and model fitting straightforward without requiring specialist knowledge,

making it suitable for implementation in public health agencies with moderate statistical

expertise. A key advantage of our method over similar methods, such as the chainladder R

package [17], is simply that it is tailored to common epidemiological contexts; with its modular

design enabling the ability to generate nowcasts for different temporal granularities in reference

and report dates, ease and demonstration of how to "borrow" delays and uncertainty across

different strata, and the ability to independently fit each weekday to account for weekday effects

in reporting, all of which are common scenarios of age and location stratified epidemiological

surveillance data with different levels of data sparsity and delay patterns that *baselinenowcast*

was designed to handle. Additionally, based on retrospective performance, the uncertainty

quantification approach provides relatively well-calibrated nowcasts. We note this was not the

case for many of the models submitted to the original German Nowcast Hub [3] and we consider

this to be a key advantage of this baseline approach over other baseline methods such as the

method used by Mellor et al. [2] which propagated the previous week's data forward with no

uncertainty. Lastly, by providing a standardised R package with comprehensive documentation,

our method aims to address challenges in reproducing and re-implementing different baseline

methods, ensuring that analyses applied in one context can be readily extended to other

pathogens/surveillance systems with relative ease and standardized approaches.

However, important limitations in our method exist. The method follows a pipeline approach

where delay distributions are estimated independently from case occurrence processes. As

demonstrated by [5], such approaches can propagate errors and may not fully account for

interdependencies between these processes. The method also lacks flexibility for incorporating

time-varying delay distributions or partially pooled estimates across strata, which may be crucial

during periods of changing surveillance intensity or for rare diseases where flexibly borrowing

information is essential.

Our approach to handling day-of-week effects in the norovirus case study highlights an

important trade-off. By filtering data to use only observations from the same day of the week, we

provide a simple solution that avoids complex modelling whilst effectively capturing weekly

patterns. However, this simplicity comes at the cost of discarding potentially valuable data on

recent trends in delay estimation, which proved to be problematic when performing independent

estimates of the delay across a large time frame. More sophisticated approaches, such as those

incorporating day-of-week terms in statistical models [19], as was used by the GAM

implementation in [2], can utilise all available data but require greater statistical complexity. This

illustrates a broader tension in nowcasting between accessible methods that may sacrifice

efficiency and complex methods that maximise statistical power but may be less accessible to

practitioners.

More fully featured nowcasting frameworks, such as the *epinowcast* R package (a semi-

mechanistic Bayesian approach [19], which was used in the Mellor et al study [2]), and

generalised additive model-based approaches [4], encompass the functionality of other

nowcasting approaches whilst offering greater flexibility, often via formula interfaces, and

standardised tooling. This increased flexibility allows users to customise models for their specific

problem reflecting their familiarity with details of the data and how they are collected, but has

the downside of increasing model, software, and interface complexity. The evidence supporting

the benefits of this increased flexibility is currently limited, as little work has been done to

evaluate framework-based approaches.

Future research should focus on five key areas. First, developing standardised benchmarks and

datasets would enable rigorous evaluation of nowcasting methods, quantifying trade-offs

between simplicity and performance across different surveillance contexts. Second, research

addressing practitioners' needs through decision support tools could guide method selection

based on data characteristics and available resources. Relatedly, co-creation of documentation

with public health practitioners, as well as evaluation in the real-world public health context will

be critical to help address implementation barriers. Thirdly, research is needed to implement a

wider array of error models for improved uncertainty quantification. Fourthly, reporting

processes can be complex, for example they can include upwards revisions or spatial drop out

in reporting. Both the type of empirically based methods we discuss in this work and more

complex methods need to be adapted for these settings. Finally, advancements in model

composition could enable seamless transitions between nowcasting and forecasting and

address error propagation issues inherent in pipeline methods [5,46].

In conclusion, our baseline nowcasting method addresses gaps in the epidemiological toolbox

by providing both a practical nowcasting solution for infectious disease surveillance and a

standard benchmark for further model development. Its performance across datasets

demonstrates that straightforward approaches can provide substantial improvements over

unadjusted data whilst remaining accessible to practitioners. Our discovery of the

implementation issue in the KIT simple nowcast method highlights the value of implementing

reproducible, tested, and validated software. The performance of different method specifications

highlighted the importance of exploratory data analysis to identify patterns in the delay

distributions across time and strata. The method's pipe-friendly, modular design enables simple

yet effective adaptations, such as the day-of-week stratification, without requiring complex

statistical frameworks. Our method, developed with public health practitioners, is robust,

interpretable, and relatively straightforward. By establishing this benchmark, we aim to reduce

the barriers to implementing nowcasting solutions in public health practice and provide a

resource for improving nowcasting methods, ultimately contributing to more timely and effective

public health responses.

871   Data availability statement

Code to reproduce results and figures are provided at

https://github.com/epinowcast/baselinenowast-paper with a stable release published at

10.5281/zenodo.16792463. Functions used to generate nowcasts are available as in the

baselinenowcast package at https://github.com/epinowcast/baselinenowcast with a stable release

published at 10.5281/zenodo.16792456. Input data used to generate COVID-19 nowcasts from

Germany is available at https://github.com/KITmetricslab/hospitalization-nowcast-hub. Data on

norovirus cases in England anonymized and with statistical noise added is available at

https://github.com/jonathonmellor/norovirus-nowcast-baselinenowcast.

Financial Disclosure Statement

We acknowledge the financial support from CDC Grant NU38FT00008 (K.J., S.A, S.F., L.J., R.E., E.T., N.G.R.). This project was made possible by cooperative agreement CDC-RFA-FT-23-0069 from the CDC's Center for Forecasting and Outbreak Analytics. Its contents are solely the responsibility of the authors and do not necessarily represent the official views of the Centers for Disease Control and Prevention. N.G.R. discloses a consulting relationship with Google LLC, although this funding and research are unrelated to the current publication. J.B. and B.N. acknowledge support by Deutsche Forschungsgemeinschaft (DFG, German Research Foundation, project 512483310). D.W. and B.N. were moreover supported by the Helmholtz Association under the joint research school HIDSS4Health – Helmholtz Information and Data Science School for Health. All other authors declare no conflicts of interest.

References

1.   Ward T, Overton CE, Paton RS, Christie R, Cumming F, Fyles M. Understanding the

infection severity and epidemiological characteristics of mpox in the UK. Nat Commun.

2024;15: 2199.

2.   Mellor J, Tang ML, Finch E, Christie R, Polhill O, Overton CE, et al. An application of

nowcasting methods: Cases of norovirus during the winter 2023/2024 in England. PLoS

Comput Biol. 2025;21: e1012849.

3.   Wolffram D, Abbott S, An der Heiden M, Funk S, Günther F, Hailer D, et al. Collaborative

nowcasting of COVID-19 hospitalization incidences in Germany. PLoS Comput Biol.

2023;19: e1011394.

4.   van de Kassteele J, Eilers PHC, Wallinga J. Nowcasting the number of new symptomatic

cases during infectious disease outbreaks using constrained P-spline smoothing.

Epidemiology. 2019;30: 737–745.

5.   Lison A, Abbott S, Huisman J, Stadler T. Generative Bayesian modeling to nowcast the

effective reproduction number from line list data with missing symptom onset dates. PLoS

Comput Biol. 2024;20: e1012021.

6.   Bergström F, Günther F, Höhle M, Britton T. Bayesian nowcasting with leading indicators

applied to COVID-19 fatalities in Sweden. PLoS Comput Biol. 2022;18: e1010767.

7.   Günther F, Bender A, Katz K, Küchenhoff H, Höhle M. Nowcasting the COVID-19 pandemic

in Bavaria. Biom J. 2021;63: 490–502.

8.   Massachusetts syndromic surveillance data and moving epidemic method. In: Mass.gov.

9.   Monitoring mortality figures in the Netherlands. In: rivm.nl [Internet]. [cited 15 May 2025].

Available: https://www.rivm.nl/monitoring-sterftecijfers-nederland

10.   Respiratory Virus Hospitalization Surveillance Network (RESP-NET). In: CDC RESP-NET.

10 Oct 2025.

11.   Scholler S, Wuensche H, Fesser A. COVID-19 Hospitalisierungen in Deutschland. In:

GitHub [Internet]. 15 May 2025 [cited 15 May 2025]. Available: https://github.com/robert-

koch-institut/COVID-19-Hospitalisierungen_in_Deutschland/

12.   Wolffram D, Bracher J, The RESPINOW Study Group, Schienle M. Integrating nowcasts

into an ensemble of data-driven forecasting models for SARI hospitalizations in Germany.

medRxiv. 2025. p. 2025.02.21.25322655. doi:10.1101/2025.02.21.25322655

13.   Overton CE, Abbott S, Christie R, Cumming F, Day J, Jones O, et al. Nowcasting the 2022

mpox outbreak in England. PLoS Comput Biol. 2023;19: e1011463.

14.   Tang ML, McFarlane IS, Overton CE, Hani E, Saliba V, Hughes GJ, et al. Nowcasting

cases and trends during the measles 2023/24 outbreak in England. medRxiv. 2025. p.

2025.04.08.25325363. doi:10.1101/2025.04.08.25325363

15.   Measles outbreak – July 15, 2025. [cited 16 Jul 2025]. Available:

https://www.dshs.texas.gov/news-alerts/measles-outbreak-2025

16.   Gesmann M, Tsanakas A. Conference Report: R in Insurance 2014. R J.

17.   ChainLadder: Claims reserving with R. [cited 25 Jul 2025]. Available:

https://mages.github.io/ChainLadder/articles/ChainLadder.html

18.   Meyer S, Held L, Höhle M. Spatio-Temporal Analysis of Epidemic Phenomena Using the R

Package surveillance. Journal of Statistical Software. 2017. pp. 1–55.

doi:10.18637/jss.v077.i11

19. Sam Abbott, Lison A, Funk S, Pearson C, Gruson H, Guenther F, et al. epinowcast:

Flexible Hierarchical Nowcasting. doi:10.5281/zenodo.5637165

20. Lopes R, Bastos L. nowcaster: Nowcaster. 2025. Available:

https://covid19br.github.io/nowcaster

21. McGough SF, Johansson MA, Lipsitch M, Menzies NA. Nowcasting by Bayesian

Smoothing: A flexible, generalizable model for real-time epidemic tracking. PLoS Comput

Biol. 2020;16: e1007735.

22. Gressani O. EpiLPS: A Fast and Flexible Bayesian Tool for Estimating Epidemiological

Parameters. [Computer Software]. 2021. Available: https://epilps.com/

23. Cramer EY, Ray EL, Lopez VK, Bracher J, Brennen A, Castro Rivadeneira AJ, et al.

Evaluation of individual and ensemble probabilistic forecasts of COVID-19 mortality in the

United States. Proc Natl Acad Sci U S A. 2022;119: e2113561119.

24. Morasso C, Dolci G, Galazzo IB, Plis SM, Menegaz G. Guidelines for the choice of the

baseline in XAI attribution methods. arXiv [cs.AI]. 2025. Available:

http://arxiv.org/abs/2503.19813

25. European CDC Respiratory Diseases Forecasting Hub. Respicast. [cited 8 Aug 2025].

Available: https://respicast.ecdc.europa.eu/

26. Höhle M, an der Heiden M. Bayesian nowcasting during the STEC O104:H4 outbreak in

Germany, 2011. Biometrics. 2014;70: 993–1002.

27. The R project for statistical computing. [cited 15 Apr 2025]. Available: https://www.r-

project.org/

28. Johnson K, Abbott S, Bracher J, Funk S. baselinenowcast: Baseline nowcast. Available:

https://baselinenowcast.epinowcast.org

29. Johnson K, Abbott S, Funk S, Bracher J. baselinenowcast: Baseline nowcast from right-

truncated epidemiological data. Zenodo; 2025. doi:10.5281/ZENODO.16792456

30. Bracher J, Ray EL, Gneiting T, Reich NG. Evaluating epidemic forecasts in an interval

format. PLoS Comput Biol. 2021;17: e1008618.

31. Bosse NI, Gruson H, Cori A, van Leeuwen E, Funk S, Abbott S. Evaluating forecasts with

scoringutils in R. arXiv [stat.ME]. 2022. Available: http://arxiv.org/abs/2205.07090

32. Lab KM, Bracher J, Wolffram D. hospitalization-nowcast-hub: Collecting nowcasts of the 7-

day hospitalization incidence in Germany. GitHub; Available:

https://github.com/KITmetricslab/hospitalization-nowcast-hub

33. Landau W. The {targets} R package user manual. [cited 15 Apr 2025]. Available:

https://books.ropensci.org/targets/

34. Bosse N, Abbott S, Gruson H, Bracher J, Asakura T, Azam JM, et al. scoringutils: Utilities

for Scoring and Assessing Predictions. 2025. Available: https://epiforecasts.io/scoringutils/

35. Wickham H, François R, Henry L, Müller K, Vaughan D. dplyr: A Grammar of Data

Manipulation. CRAN: Contributed Packages. The R Foundation; 2014.

doi:10.32614/cran.package.dplyr

36. Wickham H. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York; 2016.

Available: https://ggplot2.tidyverse.org

37. Johnson K, Abbott S. baselinenowcastpaper. 2025. Available:

https://github.com/epinowcast/baselinenowcast-paper

38. Johnson K, Abbott S, Bracher J. epinowcast/baselinenowcast-paper: Initial submission.

Zenodo; 2025. doi:10.5281/ZENODO.16792463

39. Gelman A, Vehtari A, Simpson D, Margossian CC, Carpenter B, Yao Y, et al. Bayesian

Workflow. arXiv [stat.ME]. 2020. Available: http://arxiv.org/abs/2011.01808

40. Bosse NI, Abbott S, Cori A, van Leeuwen E, Bracher J, Funk S. Scoring epidemiological

forecasts on transformed scales. PLoS Comput Biol. 2023;19: e1011393.

41. Gerding A, Reich NG, Rogers B, Ray EL. Evaluating infectious disease forecasts with

allocation scoring rules. J R Stat Soc Ser A Stat Soc. 2024. doi:10.1093/jrsssa/qnae136

42. Hinch R, Panovska-Griffiths J, Ward T, Charlett A, Watkins N, Fraser C. Quantification of

the time-varying epidemic growth rate and of the delays between symptom onset and

presenting to healthcare for the mpox epidemic in the UK in 2022. Sci Rep. 2024;14:

19755.

43. Abbott, S., Hellewell, J., Sherratt, K., Gostic, K., Hickson, J., Badr, H.S., DeWitt, M., Azam,

J.M., Funk, S. EpiNow2: Estimate real-time case counts and time-varying epidemiological

parameters. 2025. Available: https://epiforecasts.io/EpiNow2/dev/

44. Salmon M, Schumacher D, Höhle M. Monitoring Count Time Series in R: Aberration

Detection in Public Health Surveillance. Journal of Statistical Software. 2016. pp. 1–35.

doi:10.18637/jss.v070.i10

45. Gressani O, Wallinga J, Althaus CL, Hens N, Faes C. EpiLPS: A fast and flexible Bayesian

tool for estimation of the time-varying reproduction number. PLoS Comput Biol. 2022;18:

e1010618.

46. Nicholson G, Blangiardo M, Briers M, Diggle PJ, Fjelde TE, Ge H, et al. Interoperability of

statistical models in pandemic preparedness: principles and reality. Stat Sci. 2022;37: 183–

206.

1003

1. Delay estimation

P(d)

d

2. Point nowcast generation

3. Uncertainty estimation

estimates   observations

Past point estimates
Fully observed counts

cases

t

4. Predicted probabilistic nowcast

horizon

+

5. Combine with observations

+

Initial reports
Final counts
Nowcasts

cases

t