A Hybrid CNN-Transformer Deep Learning Model for Differentiating Benign and

Malignant Breast Tumors Using Multi-View Ultrasound Images

Qi Zhang[1,#], Ruizhuo Li[1#], Pan Tang[1], Jianxing Zhang[1], Guangxu Yang[3], Lin Ziyi[4],

Mengjian Zhang[2]*,Miao Chen[1]*,

[1]Department of Medical Ultrasonics, The Second Affiliated Hospital of Guangzhou University of

Chinese Medicine, Guangzhou, 510120,China.

[2]School of Artificial Intelligence and Information Technology, Nanjing University of Chinese

Medicine, Nanjing, 210023, China;

[3]Department of Medical Ultrasonics, The Affiliated Hospital of Zunyi Medical University, Zunyi,

Guizhou 563099, China

[4]School of Medicine, Guangzhou University of Chinese Medicine, Guangzhou, 510120, China

[#]Authors contributed equally to this work and share the first authorship.

*Corresponding Author: Miao Chen, Email: 297170770@qq.com; Mengjian Zhang,

Email:380805@njucm.edu.cn.

Abstract

Breast cancer is a leading malignancy threatening women's health globally, making early and

accurate diagnosis crucial. Ultrasound is a key screening and diagnostic tool due to its non-

invasive, real-time, and cost-effective nature. However, its diagnostic accuracy is highly

dependent on operator experience, and conventional single-image analysis often fails to capture

the comprehensive features of a lesion. This study introduces a computer-aided diagnosis (CAD)

system that emulates a clinician's multi-view diagnostic process. We developed a novel hybrid

deep learning model that integrates a Convolutional Neural Network (CNN) with a Transformer

architecture. The model uses a pretrained EfficientNetV2 to extract spatial features from

multiple, unordered ultrasound images of a single lesion. These features are then processed by a

Transformer encoder, whose self-attention mechanism globally models and fuses their intrinsic

correlations. To prevent data leakage, a strict lesion-level data partitioning strategy ensured a

rigorous evaluation. On an internal test set, our hybrid CNN-Transformer achieved an accuracy

of 0.960, a sensitivity of 0.967, a specificity of 0.954, and an Area Under the Curve (AUC) of

0.9788. On an external dataset, it demonstrated an accuracy of 0.940, a sensitivity of 0.952, a

specificity of 0.929, and an AUC of 0.9730. Furthermore, in a prospective validation on a newly

collected independent dataset, the model maintained robust performance with an accuracy of

0.952 and an AUC of 0.9801. These results significantly outperform those of a baseline single-

image model, which achieved accuracies of 0.88 and 0.89 and AUC of 0.95 and 0.94 on the

internal and external dataset, respectively. This study demonstrates that combining CNN with

Transformers yields a highly accurate and robust diagnostic system for breast ultrasound. By

effectively fusing multi-view information, our model aligns with clinical logic and shows

potential for improving diagnostic reliability.

Keywords: Breast cancer, EfficientNetV2, Transformer, Deep learning, Ultrasound imaging

1. Introduction

Breast cancer stands as the most frequently diagnosed malignancy among women worldwide,

posing a significant threat to their lives and health(1). Clinical evidence indicates that early

detection, diagnosis, and treatment are paramount for improving patient prognosis and achieving

higher five-year survival rates(2). Among the various imaging modalities, breast ultrasound has

emerged as an pivotal first-line tool for the screening, diagnosis, and follow-up of breast

diseases, owing to its unique advantages of being non-invasive, radiation-free, highly repeatable,

real-time, and cost-effective(3).

However, the traditional ultrasound diagnostic process has notable limitations. The accuracy of a

diagnosis is heavily reliant on the sonographer's expertise, technical skill, and subjective

judgment, which can lead to inter-observer variability and diagnostic discrepancies(4). In clinical

practice, an experienced physician does not rely on a single, static image to assess a suspicious

lesion. Instead, they perform a scan from multiple angles and planes to comprehensively observe

multi-dimensional features such as the lesion's margins, shape, internal echo pattern, and

posterior acoustic characteristics(5). This process allows them to build a holistic, three-

dimensional impression of the lesion before arriving at a final diagnosis. This integrative analysis

is central to diagnostic accuracy, and a key challenge in intelligent medical imaging is to develop

artificial intelligence (AI) that can effectively simulate and enhance this complex cognitive

process.

In recent years, AI technologies, particularly deep learning (DL), have made transformative

breakthroughs in medical image analysis(6, 7). Convolutional Neural Networks (CNNs), with

their powerful ability to automatically learn hierarchical feature representations, have become the

gold standard for processing grid-like data such as images(8-10). In the context of breast cancer

diagnosis, various classic CNN architectures like VGG and ResNet have been successfully

applied to classification tasks using mammography, histopathology, and ultrasound images,

demonstrating performance comparable to, or even superior to, that of human experts on specific

datasets(11-15). These models can autonomously learn subtle textural, morphological, and

boundary features associated with malignancy, reducing the reliance on manually engineered

features and paving the way for objective, efficient, and automated diagnosis.

Despite the remarkable success of CNN-based models, the majority of existing studies treat each

2D ultrasound image as an independent sample(16, 17). This methodology tends to diverge from

standard clinical workflows, where diagnosis relies on the cumulative evidence derived from a

sequence of images rather than isolated frames. Unlike single-image models that analyze specific

views in isolation, clinical reasoning involves determining how collective findings contribute to

a final assessment. Addressing this disparity—by evolving from static, single-view analysis to

holistic, patient-level integration—represents a significant avenue for advancing intelligent

medical imaging. This study is motivated by the need to bridge this gap, positing that the

intelligent analysis of breast ultrasound should treat the complete set of multi-view images from

a single lesion as a holistic, information-rich sequence.

To model image sequences, some researchers have explored hybrid architectures, such as

combining a CNN with a Recurrent Neural Network (RNN) or its variant, Long Short-Term

Memory (LSTM)(18). While valuable for data with a clear temporal or spatial order, these

models are ill-suited for the unordered sets of images typical in a breast ultrasound examination.

The arbitrary acquisition order of these images is less compatible with the inherent sequential

dependency of RNN. To overcome this, we introduce the Transformer model, originally

developed for natural language processing(19, 20). The Transformer's core self-attention

mechanism allows it to weigh the importance of all elements in a sequence simultaneously,

regardless of their position. This property, known as permutation invariance, closely aligns with

the clinical need to synthesize information from a collection of unordered images.

Based on this analysis, this study proposes a new intelligent diagnostic paradigm that more

closely mirrors clinical logic. The primary contributions are:

- We developed an end-to-end hybrid model combining EfficientNetV2 and a Transformer

    for breast ultrasound classification.

- We innovatively treats multiple images originating from a single tumor as a sequence,

    leveraging the Transformer's global relationship modeling capabilities for comprehensive

    analysis.

• Rigorous, tumor-level experiments demonstrated the superior performance (an AUC of

0.9730 on an external dataset) of the model, which surpassed traditional single-image

models.

• The solution offers a computationally effective approach to the core clinical challenge of

multi-view information integration, and it indicates potential for future high-precision,

reliable Computer-Aided Diagnosis (CAD) systems.

2. Materials and Methods

This section provides a detailed description of the data sources, preprocessing pipeline, model

architecture, experimental configuration, and performance evaluation standards to ensure the

study's reproducibility. The overall workflow, illustrated in Fig 1, comprises three main stages:

data preparation, model construction and training, and performance evaluation.

2.1. Study Population and Ethical Approval

This retrospective study was conducted in accordance with the Declaration of Helsinki and

approved by the Institutional Ethics Committee of The Second Affiliated Hospital of Guangzhou

University of Chinese Medicine (Approval No. ZE2023-427, 05/12/2023). The requirement for

informed consent was waived due to the retrospective nature of the study.

The case inclusion process is illustrated in Fig 2. We assessed medical records from two

independent sources. The primary dataset was derived from The Second Affiliated Hospital of

Guangzhou University of Chinese Medicine between June 2023 and April 2025. Inclusion

criteria were: (1) patients with complete clinical and final pathological results who underwent

preoperative ultrasound; (2) preoperative ultrasound with transverse or sagittal views and high-

quality images; (3) patients who had not received neoadjuvant chemotherapy or radiotherapy.

Exclusion criteria were: (1) poor ultrasound image quality; (2) an interval between ultrasound

and pathology greater than two weeks; (3) prior surgery, biopsy, or chemotherapy. Out of 980

initially screened patients, 140 were excluded. The final primary dataset comprised 840

patients(age range: 11–88 years; mean age: 51.28 ± 13.55 years), consisting of 430 benign

patients (1566 images) and 410 malignant patients (2220 images).

The external dataset was collected from the The Affiliated Hospital of Zunyi Medical University

from October 2024 to April 2025. Following the same exclusion criteria, 47 out of 180 screened

patients were excluded. The final external dataset included 133 patients, comprising 70 benign

patients (223 images) and 63 malignant patients (440 images).

For model development, the datasets were categorized into training, validation, test, and external

sets. Detailed clinical characteristics, including patient age distribution and clinical tumor size (

T1≤2.0cm and T2 2.1–5.0cm), are summarized in Table 1.

2.2. Data Acquisition and Preprocessing

Ultrasound examinations were performed by experienced physicians using GE LOGIQ E9 and

Philips EPIQ 7C systems with high-frequency linear probes (7.5–13.0 MHz). Standard images of

each lesion were acquired and stored in the picture archiving and communication system (PACS).

The raw DICOM images were converted to JPG format. Two physicians, each with over five

years of experience in breast ultrasound diagnosis, manually cropped the images to isolate the

lesion and remove extraneous information, such as patient data and measurement markers in Fig

3. This step ensures the model focuses on relevant pathological features. All images were then

resized to 300×300 pixels to match the model's input dimensions, and pixel values were

normalized to a range of [0, 1].

2.3. Dataset Partitioning Strategy

A scientifically rigorous dataset partitioning strategy is fundamental to the objective and reliable

evaluation of AI models in medical imaging. A common pitfall is the random allocation of

multiple images from the same patient's tumor into the training, validation, and test sets. This

practice leads to severe data leakage, as the model may learn to identify patient-specific artifacts

rather than generalizable pathological features. This results in an artificially inflated performance

on the test set, which plummets when the model is exposed to new data in a real-world setting.

To address this issue, this study employed a strict per-lesion partitioning methodology.

Specifically, all images associated with a single tumor were treated as an indivisible unit and

assigned exclusively to one of the three sets: training, validation, or test. The internal dataset was

partitioned using a 70%:15%:15% ratio, ensuring complete independence at the lesion level. The

entire external dataset was held out as a separate, independent test set to evaluate the model's

generalization performance. The data distribution is detailed in Table 2.

2.4. Handling Multi-View Data

A critical challenge in multi-view learning is the variable number of images available per lesion

(ranging from 2 to 10). We implemented a robust technical strategy to handle this variability:

2.4.1. Fixed Max Length and Padding

We defined a hyperparameter max_images_per_lesion = 10.

● Truncation: If a lesion has >10 images, only the first 10 are used.

● Zero-Padding: If a lesion has $N < 10$ images, we generate 10 - N dummy images consisting

of all-zero tensors. This ensures that the input tensor to the model always has a fixed shape .

2.5.1. Baseline Model: EfficientNetV2 Single-Image Classifier

The baseline model was implemented using a standard transfer learning paradigm to establish a

performance benchmark for a conventional single-image approach.

- **Backbone:** The efficientnet_v2_s model, pre-trained on the ImageNet dataset, was selected as the feature extractor due to its excellent balance between performance and efficiency.

- **Feature Extraction:** The parameters of the convolutional layers in the backbone were frozen, allowing it to function as a fixed feature extraction tool.

- **Classification Head:** The original fully connected layer was replaced with a custom head consisting of a linear layer (1280 input dimensions) and a single output neuron with a sigmoid activation function to produce a binary probability of malignancy.

2.4.2. Attention Masking

To ensure the zero-padding does not influence the diagnosis, we generated a binary Attention Mask for each sample. The mask contains 1 for real images and 0 for padded images. In the Transformer's self-attention calculation, the similarity scores corresponding to padded positions are set to negative infinity before the Softmax operation. This forces the attention weights for padded images to become effectively zero, meaning they contribute nothing to the feature aggregation.

2.4.3. Classification Token Aggregation

Instead of simple averaging, which dilutes strong signals, we prepend a learnable token to the sequence of image features. The Transformer learns to update this token with information aggregated from all valid views. The final classification is performed solely on the state of this token.

2.5. Model Architectures

This study designed and compared two distinct models: a single-image classification baseline and the proposed hybrid CNN-Transformer model.

2.5.2. Proposed Hybrid Model

This model consists of two stages:

● **Local Feature Extraction:** Each of the N images in a patient's lesion is passed

independently through the EfficientNetV2 backbone, resulting in a sequence of feature

vectors $F=\{f_1, f_2, \ldots, f_N\}$, where $f_i \Box \Box^{1280}$.

● **Global Feature Fusion:** The sequence was fed into a Transformer Encoder.

○ Hyper parameter: To ensure optimal performance, we conducted a systematic grid

search for hyperparameter optimization. We evaluated dropout rates of

$\{0.0, 0.1, 0.2, 0.3, 0.4, 0.5\}$, attention heads of $\{4, 8, 16\}$, and network depths of

$\{4, 6, 8, 12, 16\}$ layers. Based on the validation set performance of AUC, the final model

was configured with 8 layers, 8 attention heads, and a dropout rate of 0.1 in Fig 4.

○ **Positional Encoding:** Crucially, we removed the positional encoding typically used in

NLP Transformers. This enforces permutation invariance, ensuring the model treats the

input as an unordered set rather than a sequence.

○ **Output:** The final embedding of the token is passed to a Multi-Layer Perceptron (MLP)

head with a Sigmoid activation to predict the probability of malignancy.

2.5.3. Ablation Study

To strictly evaluate the contribution of the Transformer architecture and verify the optimal fusion

strategy for multi-view ultrasound data, we implemented two comparative baseline models using

the same EfficientNetV2 backbone.

● CNN-Only (Global Average Pooling Baseline): This baseline represents a bag-of-features

approach that aggregates multi-view information without modeling inter-view relationships.

○ Batch Processing: The input tensor of shape $[B, N, C, H, W]$ is reshaped to $[B \Box N, C, H, W]$

to treat all images across the batch as independent samples.

○ Feature Extraction: The shared CNN backbone extracts high-dimensional features from

these images.

○ Reshaping & Masking: The features are reshaped back to [B,N,D] (where D=1280

○). A binary mask is applied to zero out features corresponding to padded dummy

images, ensuring they do not affect the calculation.

○ Aggregation: We apply Global Average Pooling along the view dimension for valid

images only. This produces a single, averaged feature vector for the patient, which is

fed into the classification head. This model assumes all views contribute equally and

independently to the diagnosis.

● CNN-RNN (Sequential Modeling Baseline): This model tests the hypothesis that sequential

dependencies (temporal logic) exist within the multi-view acquisition process.

○ Sequential Modeling: Unlike the parallel processing of the Transformer or the simple

averaging of the CNN-Only model, this architecture utilizes a Long Short-Term

Memory (LSTM) network.

○ Temporal Dependencies: The sequence of image features extracted by the CNN is fed

into the LSTM, which updates its hidden state step-by-step, attempting to capture

temporal correlations between successive ultrasound frames.

○ Final Representation: Instead of using all states, we extract the hidden state of the last

valid time step (determined by the sequence length of non-padded images) to serve as

the comprehensive representation of the lesion. This vector is then passed to the

classifier to output the final prediction.

2.5.4. State-of-the-Art Benchmarks

To validate the competitiveness of our proposed method against established solutions in medical image analysis, we benchmarked our model against three advanced architectures representing different fusion paradigms, all comparative models were retrained on our training set using their official implementations and optimal hyperparameters recommended in their original papers:

- VGG-ViT: A classic hybrid architecture that combines a VGG convolutional backbone with a Vision Transformer (ViT). This model serves as a benchmark for early CNN-Transformer integration strategies.

- TransMed: Originally designed for multi-modal medical image fusion, this model was adapted to process multi-view single-modality data. It serves to compare our method against complex, general-purpose medical transformers.

- MedFormer: A specialized Transformer architecture optimized for medical imaging tasks. Comparing against MedFormer allows us to assess whether our lightweight EfficientNetV2-Transformer design can compete with or outperform purpose-built medical transformers in specific breast ultrasound applications.

2.6. Experimental Settings and Training Parameters

All experiments were conducted in the following environment:

- **Hardware Platform:** NVIDIA GeForce RTX 4060Ti GPU

- **Software Environment:** Python 3.10, PyTorch 2.7.1, torchvision, scikit-learn, pandas, numpy

To ensure the reproducibility of the experiments, the detailed hyperparameters are provided in Table 3.

2.7. Evaluation Metrics

Model performance was assessed using five standard binary classification metrics.

254   ●   Accuracy: Measures the proportion of all predictions that are correct.

$$Accuracy = \frac{TP+TN}{TP+TN+FP+FN}$$

256   ●   Sensitivity: Measures the model's ability to correctly identify malignant samples.

$$Sensitivity = \frac{TP}{TP+FN}$$

257   ●   Specificity: Measures the model's ability to correctly identify benign samples.

$$Specificity = \frac{TN}{TN+FP}$$

where TP, TN, FP, and FN represent correctly classified malignant lesions, correctly classified

benign lesions, benign lesions misclassified as malignant, and malignant lesions misclassified as

benign, respectively.

●   **AUC :** Measures the model's overall discriminative ability across all classification

thresholds. An AUC closer to 1 indicates better performance.

2.8. Evaluation Metrics and Statistical Analysis

Performance was assessed using Accuracy, Sensitivity, Specificity, and AUC.

Statistical Rigor:

●   **Confidence Intervals (CI):** We calculated 95% CIs for all metrics using bootstrapping

(n=1000 resamples) to demonstrate the stability of our results.

●   **DeLong Test:** Used to statistically compare the AUC of different models. A p-value <0.05

was considered significant.

3. Results

3.1. Overall Model Performance Comparison

The proposed hybrid CNN-Transformer demonstrated a significant improvement in diagnostic

performance over the conventional single-image baseline model across all evaluation metrics.

This advantage was consistent on both the internal test set and, crucially, on the independent

external dataset, underscoring the model's robustness and generalization capabilities.

On the internal test set, which was partitioned at the tumor level to prevent data leakage, the

hybrid model achieved an accuracy of 0.960 and an AUC of 0.9788. When challenged with the

external dataset, comprising data acquired with different equipment, the model's performance

remained remarkably stable, yielding an accuracy of 0.940 and an AUC of 0.9730. In contrast,

the baseline EfficientNetV2 model, which classifies each image independently, achieved lower

metrics on both test sets. These results, detailed in Table 4, provide strong evidence that the

fusion of multi-view information through the Transformer architecture leads to a significant leap

in diagnostic power.

3.2. Analysis of Generalization Ability

To assess the model's learning dynamics and potential for overfitting, the AUC was tracked for

both the training and validation sets throughout the training process in Fig 5. The training and

validation AUC curves rose in tandem and remained closely aligned, ultimately converging at a

high level of performance (AUC>0.97). This indicates that the model did not overfit to the

training data; instead, it learned generalizable features applicable to unseen data.

The ultimate test of generalization is performance on entirely new data. The Receiver Operating

Characteristic (ROC) curves for the validation, internal test, and external dataset are presented in

Fig 6. The curves are nearly superimposed, with high AUC values of 0.9708, 0.9788, and

0.9730, respectively. This significant consistency across three independent datasets strongly

suggests that the model has learned robust, broadly applicable diagnostic features, validating

both the architectural design and the rigorous data partitioning strategy.

To address the concern that deep learning models may overfit to specific device artifacts (e.g.,

speckle patterns specific to a vendor) and to ensure clinical generalization, we evaluated the

model's performance stratified by ultrasound machine manufacturer. The internal dataset was

acquired using two distinct high-end systems: GE LOGIQ E9 and Philips EPIQ 7C, which

employ different beamforming and post-processing algorithms. The model achieved an AUC of

0.9875 on the GE system and 0.9722 on the Philips system in Fig 7. The curves are nearly

identical, and the high AUC across both vendors confirm that the model extracts robust,

biologically relevant features rather than relying on equipment-specific noise or post-processing

signatures. This minimal performance discrepancy ($\Delta AUC < 0.02$) demonstrates that the proposed

architecture successfully mitigates the influence of machine heterogeneity, validating its

potential for widespread deployment in multi-vendor clinical environments.

3.3. Detailed Classification Performance

A detailed breakdown of the model's classification performance is presented via confusion

matrices for the internal and external dataset (Fig 8) and a comprehensive classification report

(Table 5).

On the internal test set, the confusion matrix shows the model correctly identified 62 of 65

benign lesions and 59 of 61 malignant lesions in Fig 8a. As detailed in Table 5, this performance

corresponds to a recall of 0.954 (specificity) and a precision of 0.969 for benign cases. For the

crucial task of identifying malignancy, the model achieved a Sensitivity of 0.967 and a precision

of 0.952. The excellent F1-scores of 0.960 for both classes highlight a strong and desirable

balance between precision and recall.

The model's robustness was further validated on the external dataset in Fig 8b. It achieved a

recall (specificity) of 0.929 and a precision of 0.956 for benign lesions. For malignant lesions, it

demonstrated an even higher recall (sensitivity) of 0.952, with a corresponding precision of

0.923. This indicates a very low rate of missed malignant cases. The resulting F1-scores of 0.942

for benign and 0.938 for malignant classes confirm the model's strong diagnostic capability on

unseen data.

In summary, the consistently high performance across both datasets, highlighted by macro-

averaged F1-scores of 0.960 (internal) and 0.940 (external), affirms the model's reliability and

strong generalization potential.

3.4. Analysis of Prediction Probability and Confidence

Beyond standard classification metrics, the confidence of a model's predictions is a critical

dimension of its clinical reliability. Fig. 9 illustrates the frequency distribution of predicted

malignancy probabilities for all benign and malignant samples in the test sets. The histograms

reveal a distinct separation: probabilities for benign samples (blue) are highly concentrated near

0.0, while those for malignant samples (red) are predominantly clustered near 1.0. This distinct

lack of overlap between the two distributions visually confirms the model's strong discriminative

ability. It demonstrates that the model does not merely achieve high accuracy but renders

diagnostic decisions with high confidence.

3.5. Confidence Intervals Analysis

The proposed hybrid CNN-Transformer demonstrated robust performance on both internal and

external dataset. The results, including 95% Confidence Intervals, are presented in Table 6.

The model achieved an AUC of 0.9788 on the internal set and maintained an AUC of 0.9730 on

the external dataset. The overlap in the 95% CIs between internal and external performance

indicates excellent generalization; the model did not simply memorize the training data

distribution or specific hospital artifacts. The high Sensitivity (>0.95 in both sets) is clinically

pivotal, ensuring that malignant cases are rarely missed.

3.6. Ablation Study Results

To determine the optimal mechanism for multi-view information integration, a comprehensive

component-wise ablation study was conducted. The objective was to evaluate the hypothesis that

modeling ultrasound views as an unordered set—via a Transformer-based architecture—yields

superior performance compared to sequential modeling using RNNs or view-independent

processing with CNNs alone (Table 7).

The CNN-Only model achieved an AUC of 0.9576, establishing a competitive baseline; however,

it is limited to post-hoc aggregation of view-specific features without cross-view feature

synthesis. The CNN-RNN model (AUC 0.9659) introduces feature-level fusion through

sequential modeling, yet it is outperformed by the CNN-Transformer model (AUC 0.9788). This

statistically significant improvement supports our hypothesis: the permutation invariance

inherent in the Transformer architecture is more suitable for multi-view ultrasound analysis than

the ordered assumption underlying RNNs. By employing self-attention, the Transformer

dynamically prioritizes the most informative views irrespective of their positional order, thereby

emulating a cognitive integration process free from artificial temporal constraints.

3.7. Computational Efficiency

To assess clinical feasibility, our hybrid CNN-Transformer measured inference time on an

NVIDIA RTX 4060Ti.

● Total Time (126 samples): 4.2249 seconds.

● Average Time per Patient: 0.0335 seconds.

This ultra-low latency (<40ms) confirms the model is suitable for real-time integration into

clinical workflows.

3.8. Comparison with State-of-the-Art Architectures

To strictly validate the competitiveness of our proposed method, we benchmarked it against three

advanced architectures representing different fusion paradigms: VGG-ViT (classic hybrid),

TransMed (multi-modal fusion), and MedFormer (specialized medical transformer). As detailed

in Table 8, our EfficientNetV2-Transformer hybrid model achieved the highest Test AUC of

0.9788, outperforming all comparative baselines. A deeper analysis reveals the architectural

reasons behind this performance gap:

3.8.1. Superior Generalization vs. VGG-ViT

The VGG-ViT model exhibited a high Validation performance of AUC with 0.9702, but its

performance dropped sharply on the Test set (0.9541). This suggests that the heavy parameter

count of the VGG backbone, combined with a standard Vision Transformer, led to overfitting on

the ultrasound dataset. In stark contrast, our model achieved superior generalization, improving

from a Validation AUC of 0.9702 to a Test AUC of 0.9788. This confirms that our choice of the

lightweight EfficientNetV2 backbone combined with a shallow (8-layer) Transformer strikes a

better balance between model complexity and data efficiency, learning robust pathological

features rather than memorizing noise.

3.8.2. Task-Specific Optimization vs. TransMed and MedFormer

TransMed (Test AUC 0.9684) and MedFormer (Test AUC 0.9697) represent complex, heavy-

weight architectures originally designed for multi-modal tasks (e.g., MRI-CT fusion) or general

medical segmentation. While they performed well, they did not surpass our proposed model.

● The Bag-of-Images Advantage: TransMed assumes complex inter-modal relationships that

are unnecessary for single-modality ultrasound. Our model, by removing positional

encoding, enforces permutation invariance. This design is specifically optimized for the

unordered nature of multi-view ultrasound (where the order of images does not matter),

allowing the model to focus purely on aggregating complementary diagnostic evidence.

• Efficiency: Our model achieves superior accuracy without the computational burden of

these heavy transformers. This demonstrates that a focused, task-specific architecture is

more effective for breast ultrasound classification than adapting large-scale, general-purpose

medical transformers.

In summary, the benchmarking results demonstrate that increased model complexity does not

necessarily translate to superior diagnostic performance. Our model's success stems from

aligning the network architecture with the clinical reality of breast ultrasound—treating views

as an unordered set and prioritizing feature robustness over model complexity.

3.9. Model Interpretability using Gradient-weighted Class Activation Mapping (Grad-

CAM)

To investigate the model's decision-making basis, Grad-CAM was used to visualize the regions

of interest the CNN feature extractor focused on clinical ultrasound features. Although the final

diagnosis results from the Transformer's fusion of features, Grad-CAM provides insight into

whether the foundational feature extraction is clinically relevant.

As shown in Fig 10 and Fig 11, when the model correctly classifies a lesion, the high-attention

areas (heatmaps) precisely overlap with clinically significant pathological features, such as

irregular margins, internal microcalcifications, and angular contours. This visualization confirms

that the CNN component effectively learns to identify meaningful biomarkers, providing a

reliable and interpretable foundation for the Transformer's subsequent global analysis. This

enhances trust in the model's decisions by demonstrating that its reasoning is aligned with

established clinical diagnostic criteria.

4. Expert Validation Test

To validate the clinical relevance of our model and address concerns regarding human-machine

comparison, we conducted a blind test using the internal test set (n=126). Three ultrasound

physicians participated: two junior doctors (3-5 years of experience) and one senior doctor (>15

years of experience). They independently classified the 126 lesions without access to the model's

predictions or pathology results (Table 9).

As presented in Table 9, the proposed model significantly outperformed all human readers. The

model achieved an accuracy of 0.960, surpassing the senior expert (0.849) by over 11 percentage

points. Notably, the model's sensitivity (0.967) was substantially higher than even the senior

doctor (0.8689), indicating a superior capability in detecting malignancies and reducing false

negatives. This suggests that the model can serve as a highly effective suggestion to reduce

missed diagnoses in clinical practice.

To understand the source of this performance gap, we analyzed discordant cases where human

experts erred but the model succeeded. Fig 12 illustrates a challenging diagnostic scenario

involving a hypoechoic mass with ambiguous features. The original grayscale image (Fig 12a)

and Color Doppler (Fig 12b) show a hypoechoic mass with somewhat ambiguous features,

possibly exhibiting minor irregularities or shadowing that mimics malignancy, leading to a

potential human misdiagnosis (False Positive).

● Grad-CAM Insight: The heatmap reveals that the model's attention was not distracted by the

internal heterogeneity. Instead, it focused strongly on the upper and lateral boundaries of the

lesion. By accurately identifying the continuity of the tumor and the distinct tissue interface

(highlighted in red), the model confirmed the well-circumscribed nature of the tumor.

●   Clinical Significance: This case exemplifies the model's robustness in reducing unnecessary

biopsies. While human eyes might be misled by suspicious-looking artifacts, the Grad-CAM

confirms that the model grounds its decision on subtle but definitive markers of benignity,

effectively serving as a gatekeeper to improve specificity.

5. Prospective Validation on a Newly Collected Dataset

5.1. Rationale and Data Collection and Inclusion

To rigorously address potential concerns regarding model generalization and data leakage, we

performed a stringent prospective validation of the final hybrid CNN-Transformer. This test

used a completely new, independent dataset collected after the development and finalization of

the model, mimicking a real-world clinical deployment scenario.

Data for this prospective test were collected consecutively from September 2025 to December

2025. A total of 188 new lesions (including 122 benign and 66 malignant cases, confirmed by

pathology) were collected during this period, ensuring no overlap with the initial training,

validation, or internal test sets. All data collection and image acquisition protocols remained

identical to the procedures outlined in Section 2.

5.2. Prospective Test Results

The hybrid CNN-Transformer was applied to the newly collected prospective test set. The

results, visualized by the Classification Report, Confusion Matrix, and ROC Curve (Fig 13),

demonstrate the model's robust generalization capability.

The model achieved an overall accuracy of 95.2% and AUC of 98.01%.Specifically, the model

demonstrated a strong capability to correctly identify 65 of 66 malignant lesions and 114 of 122

benign lesions.

These results are comparable to the performance observed on the internal test set (Section 3.1),

confirming that the multi-view CNN-Transformer architecture is highly effective and stable

across distinct, temporally separated, real-world clinical data.

6. Discussion

The results of this study indicate that the proposed hybrid CNN-Transformer is significantly

superior to conventional single-image CNN approaches for classifying breast tumors in

ultrasound images. The core reason for this performance gain lies in an architecture that more

faithfully emulates the cognitive process of clinical experts.

The effectiveness of multi-view fusion is the central finding. A single-image model processes

each view in isolation, whereas the Transformer encoder in our hybrid model functions as a

virtual expert panel. Its self-attention mechanism allows the model to dynamically weigh and

integrate information from the entire set of images for a given lesion(21, 22). For instance, it can

learn to assign greater importance to a view that clearly depicts spiculated margins while down-

weighting another view obscured by acoustic artifacts. This dynamic, global evidence integration

is a powerful analogy for expert diagnostic reasoning and is the key driver behind the model's

performance leap. This architecture also confers greater robustness to the variations inherent in

real-world clinical data, such as differences in image quality or the number of available views, as

the model can learn to prioritize high-quality, informative images(23, 24).

The clinical implications of the model's performance are substantial. The high specificity

achieved on both internal (0.954) and external (0.929) dataset indicates a strong ability to

correctly identify benign lesions. This could translate to a significant reduction in false-positive

findings, potentially sparing many women from the anxiety, physical discomfort, and cost of

unnecessary biopsies. Concurrently, the model's high sensitivity (0.967 internal, 0.952 external)

facilitates a low rate of missed malignant tumors, which is critical for facilitating early diagnosis

and treatment.

Despite its promising results, this study has limitations that outline directions for future research.

First, although the model demonstrated robust generalization on an independent external dataset

and across two different ultrasound vendors (GE and Philips). To fully establish the model's

reliability in diverse clinical settings, large-scale multi-center validation encompassing a wider

array of equipment manufacturers and patient demographics is necessary. Second, while our

Grad-CAM analysis confirmed that the model focuses on clinically relevant features and the

expert validation study demonstrated its superiority over human readers, the current system

provides only visual heatmaps and probability scores. It does not yet generate structured text

explanations or Breast Imaging-Reporting and Data System(BI-RADS ） descriptors, which

would further enhance trust and facilitate seamless integration into the radiologist's reporting

workflow. Finally, although our prospective validation verified the model's stability on real-

world data, a long-term randomized clinical trial (RCT) is required to quantitatively assess its

actual impact on reducing unnecessary biopsies and improving clinical workflow efficiency.

By using a shallow Transformer (8 layers) on top of an efficient backbone (EfficientNetV2), we

achieve a sweet spot between depth and speed. This model does not require a supercomputer; it

can run on a standard medical workstation equipped with a mid-range GPU.

7. Conclusion

This study successfully developed and validated a novel hybrid CNN-Transformer deep learning

model for breast ultrasound diagnosis. By synergistically combining the powerful local feature

extraction of a CNN with the sophisticated global information fusion capabilities of a

Transformer, the model effectively simulates the multi-view diagnostic process of clinical

experts. Using a rigorous, tumor-level evaluation methodology, the proposed model

demonstrated outstanding classification performance on an internal test set (AUC 0.9788) and

proved its excellent generalization on an independent external dataset (AUC 0.9730). The

consistently high accuracy, sensitivity, and specificity across diverse datasets significantly

exceed those of traditional single-image methods. This work not only validates a superior

technical architecture but also underscores the methodological importance of multi-view analysis

and robust external validation. The model shows potential as a reliable tool to assist clinicians in

making more accurate diagnoses of breast cancer, with the ultimate aim of improving patient

health and well-being.

In future work, we will focus on developing a large scale study with more external validations .

Ultimately, the goal is to integrate this technology into a user-friendly CAD system and conduct

prospective clinical trials to evaluate its real-world impact on diagnostic accuracy, workflow

efficiency, and patient outcomes.

References

1.Xiong X, Zheng LW, Ding Y, Chen YF, Cai YW, Wang LP, et al. Breast cancer: pathogenesis

and treatments. Signal Transduct Target Ther. 2025-02-19;10(1):49.DOI: 10.1038/s41392-024-

02108-4.

2.Sung H, Ferlay J, Siegel RL, Laversanne M, Soerjomataram I, Jemal A, et al. Global Cancer

Statistics 2020: GLOBOCAN Estimates of Incidence and Mortality Worldwide for 36 Cancers

in 185 Countries. CA Cancer J Clin. 2021-05-01;71(3):209-49.DOI: 10.3322/caac.21660.

3.Wang Y, Li Y, Song Y, Chen C, Wang Z, Li L, et al. Comparison of ultrasound and

mammography for early diagnosis of breast cancer among Chinese women with suspected

breast lesions: A prospective trial. THORAC CANCER. 2022-11-01;13(22):3145-

51. DOI: 10.1111/1759-7714.14666.

4.Wang H, Yang X, Ma S, Zhu K, Guo S. An Optimized Radiomics Model Based on Automated

Breast Volume Scan Images to Identify Breast Lesions: Comparison of Machine Learning

Methods: Comparison of Machine Learning Methods. J Ultrasound Med. 2022 2022-07-

01;41(7):1643-55. DOI: 10.1002/jum.15845.

5.Evans A, Trimboli RM, Athanasiou A, Balleyguier C, Baltzer PA, Bick U, et al. Breast

ultrasound: recommendations for information to women and referring physicians by the

European Society of Breast Imaging. Insights Imaging. 2018 2018-08-01;9(4):449-

61. DOI: 10.1007/s13244-018-0636-z.

6.Rajpurkar P, Lungren MP. The Current and Future State of AI Interpretation of Medical

Images. N Engl J Med.2023 2023-05-25;388(21):1981-90. DOI: 10.1056/NEJMra2301725.

7.Assié G, Allassonnière S. Artificial Intelligence in Endocrinology: On Track Toward Great

Opportunities. J Clin Endocrinol Metab.2024 2024-05-17;109(6):e1462-

7.DOI: 10.1210/clinem/dgae154.

8.Rawat W, Wang Z. Deep Convolutional Neural Networks for Image Classification: A

Comprehensive Review. NEURAL COMPUT. 2017 2017-09-01;29(9):2352-

449.DOI: 10.1162/NECO_a_00990.

9.Haenssle HA, Fink C, Schneiderbauer R, Toberer F, Buhl T, Blum A, et al. Man against

machine: diagnostic performance of a deep learning convolutional neural network for

dermoscopic melanoma recognition in comparison to 58 dermatologists. ANN ONCOL. 2018

2018-08-01;29(8):1836-42.DOI: 10.1093/annonc/mdy166.

10.Shin HC, Roth HR, Gao M, Lu L, Xu Z, Nogues I, et al. Deep Convolutional Neural

Networks for Computer-Aided Detection: CNN Architectures, Dataset Characteristics and

Transfer Learning. IEEE Trans Med Imaging. 2016 2016-05-01;35(5):1285-

98.DOI: 10.1109/TMI.2016.2528162.

11.Qu X, Lu H, Tang W, Wang S, Zheng D, Hou Y, et al. A VGG attention vision transformer

network for benign and malignant classification of breast ultrasound images. MED PHYS. 2022

2022-09-01;49(9):5787-98.DOI: 10.1002/mp.15852.

12.An F, Li X, Ma X. Medical Image Classification Algorithm Based on Visual Attention

Mechanism-MCNN. OXID MED CELL LONGEV. 2021 2021-01-

20;2021:6280690.DOI: 10.1155/2021/6280690.

13.Yousif M, van Diest PJ, Laurinavicius A, Rimm D, van der Laak J, Madabhushi A, et al.

Artificial intelligence applied to breast pathology. VIRCHOWS ARCH. 2022 2022-01-

01;480(1):191-209.DOI: 10.1007/s00428-021-03213-3.

14.Harrison P, Hasan R, Park K. State-of-the-Art of Breast Cancer Diagnosis in Medical Images

via Convolutional Neural Networks (CNNs). J Healthc Inform Res. 2023 2023-12-01;7(4):387-

432. DOI: 10.1007/s41666-023-00144-3.

15.Sechopoulos I, Teuwen J, Mann R. Artificial intelligence for breast cancer detection in

mammography and digital breast tomosynthesis: State of the art. SEMIN CANCER BIOL. 2021

2021-07-01;72:214-25.DOI: 10.1016/j.semcancer.2020.06.002.

16.Howard JP, Tan J, Shun-Shin MJ, Mahdi D, Nowbar AN, Arnold AD, et al. Improving

ultrasound video classification: an evaluation of novel deep learning methods in

echocardiography. J Med Artif Intell. 2020 2020-03-25;3:4.DOI: 10.21037/jmai.2019.10.03.

17.Xiang K, Shang D. Construction of a Multi-View Deep Learning Model for the Severity

Classification of Acute Pancreatitis. DISCOV MED. 2025 2025-01-01;37(192):73-

92.DOI: 10.24976/Discov.Med.202537192.7.

18. Kaddes M, Ayid YM, Elshewey AM, Fouad Y. Breast cancer classification based on hybrid

CNN with LSTM model. Sci Rep. 2025-02-05;15(1):4409. DOI: 10.1038/s41598-025-88459-6.

19. Wu G, Zheng WS, Lu Y, Tian Q. PSLT: A Light-Weight Vision Transformer With Ladder

Self-Attention and Progressive Shift. IEEE Trans Pattern Anal Mach Intell. 2023 2023-09-

01;45(9):11120-35. DOI: 10.1109/TPAMI.2023.3265499.

20. Maziarka Ł, Majchrowski D, Danel T, Gaiński P, Tabor J, Podolak I, et al. Relative molecule

self-attention transformer. J Cheminform. 2024 2024-01-03;16(1):3. DOI: 10.1186/s13321-023-

00789-7.

21. Li J, Chen J, Tang Y, Wang C, Landman BA, Zhou SK. Transforming medical imaging with

Transformers? A comparative review of key properties, current progresses, and future

perspectives. MED IMAGE ANAL. 2023 2023-04-

01;85:102762. DOI: 10.1016/j.media.2023.102762.

22. Liu X, Zhu X, Li M, Wang L, Tang C, Yin J, et al. Late Fusion Incomplete Multi-View

Clustering. IEEE Trans Pattern Anal Mach Intell. 2019 2019-10-01;41(10):2410-

23. DOI: 10.1109/TPAMI.2018.2879108.

23. Kumar A, Yadav SP, Kumar A. An improved feature extraction algorithm for robust Swin

Transformer model in high-dimensional medical image analysis. COMPUT BIOL MED. 2025

2025-04-01;188:109822. DOI: 10.1016/j.compbiomed.2025.109822.

24. Gong P, Cheng L, Zhang Z, Meng A, Li E, Chen J, et al. Multi-omics integration method

based on attention deep learning network for biomedical data classification. Comput Methods

Programs Biomed. 2023 2023-04-01;231:107377. DOI: 10.1016/j.cmpb.2023.107377.

Footnote

Ethical Statement: The authors are accountable for all aspects of the work in ensuring that

questions related to the accuracy or integrity of any part of the work are appropriately

investigated and resolved. This study was conducted in accordance with the Declaration of

Helsinki (as revised in 2013). The medical ethics committee of the Second Affiliated Hospital of

Guangzhou University of Chinese Medicine approved the study (Approval No. ZE2023-

427).The requirement for informed consent was waived due to the retrospective nature of the

study.

Funding: the Guangdong Province Traditional Chinese Medicine Bureau Scientific Research

Project (No. 20242032).

Data Availability: The data that support the findings of this study are available from the

corresponding author upon reasonable request.

Competing Interests:The authors declare no competing interests.

Table 1:The clinical characteristics of all patients.

Characteristic	Training Set	Validation Set	Test Set	External Dataset
No. of patients(images)	588	126	126	133
Age				
<40y	126(21)	32(25)	37(30)	43(32)
40-49y	141(24)	36(29)	32(25)	34(26)
50-59y	155(26)	36(29)	29(23)	35(26)
60-69y	111(19)	16(12)	22(17)	11(8)
≥70y	55(10)	6(5)	6(5)	10(8)
Clinical tumor size (No. of tumors)				
T1≤2.0cm	288	56	49	61
T2（2.1-5.0cm）	300	70	77	72

605   Note.—Unless otherwise specified, data in parentheses are percentages.

607   Table 2: Dataset distribution for the baseline and hybrid models.

Model Type	Data Unit	Training Set	Validation Set	Test Set	External Dataset	Total
Baseline	Images	2657	590	539	663	4449
Hybrid	Tumors	588	126	126	133	973

609   Table 3: Hyperparameter configuration for model training.

Parameter	Baseline Model	Hybrid Model
Optimizer	AdamW	AdamW
Initial Learning Rate	$1\times10{-4}$	$5\times10{-5}$
Learning Rate Scheduler	Cosine Annealing	Cosine Annealing
Batch Size	32 (images)	4 (lesions)

Epochs	100 (with Early Stopping)	100 (with Early Stopping)
Early Stopping Patience	5	5
Monitored Metric	Validation AUC	Validation AUC
Loss Function	Binary Cross-Entropy	Binary Cross-Entropy

611   Table 4: Performance comparison of the two models on the test sets.

Model	Test Set	Accuracy	Sensitivity	Specificity	AUC
Baseline Model	Internal	0.881	0.863	0.914	0.9521
	External	0.894	0.909	0.818	0.9437
CNN-Transformer	Internal	0.960	0.967	0.954	0.9788
	External	0.940	0.952	0.929	0.9730

613   Table 5: Detailed Classification Report on the Internal and External dataset.

Test Set	Class	Precision	Recall	F1-Score	Support
Internal	Benign	0.969	0.954	0.961	65
	Malignant	0.952	0.967	0.959	61
	Macro Avg	0.960	0.961	0.960	126
External	Benign	0.956	0.929	0.942	70
	Malignant	0.923	0.952	0.938	63
	Macro Avg	0.939	0.940	0.940	133

615   Table 6:Confidence interval analysis results.

Test Set	Accuracy	AUC	Sensitivity	Specificity
Internal	0.9603	0.9788(95%CI: 0.9508 - 0.9990)	0.967(95%CI:0.917 - 1.0000)	0.954(95%CI: 0.900 - 1.000)
External	0.9398	0.9730(95%CI: 0.9414 - 0.9937)	0.952(95%CI:0.894 - 1.000)	0.929(95%CI: 0.864 - 0.985)

617   Table 7:Ablation study results

Model Architecture	Fusion Strategy	Validation AUC	Test AUC
CNN-Only	Max Pooling (Post-hoc)	0.9502	0.9576
CNN-RNN	Bi-Directional LSTM	0.9676	0.9659
CNN-Transformer	Self-Attention (Proposed)	**0.9708**	**0.9788**

619   Table 8:Comparison results of similar models

Model	Validation AUC	Test AUC
VGG-ViT	0.9702	0.9541
TransMed	0.9701	0.9684
MedFormer	0.9695	0.9697
CNN-Transformer	**0.9708**	**0.9788**

621   Table 9:Comparison with Human Experts

Method	Correct Cases	Accuracy	Sensitivity	Specificity
Junior Doctor 1	103	0.818	0.820	0.815
Junior Doctor 2	104	0.825	0.803	0.846
Senior Doctor	107	0.849	0.869	0.831
Average Human	104.7	0.831	0.831	0.831

Figure legends:

Fig 1: overall workflow.

Fig 2:The case inclusion Process.

a   **b**

Fig 3. Pre- and Post-processing of Ultrasound Images; Example of the image preparation

workflow. (a) The original ultrasound image as exported from the PACS, containing patient

information and measurement markers. (b) The image after being manually cropped by an expert

physician to isolate the lesion of interest for model input.

Fig 4. Hyperparameter Sensitivity Analysis.

Fig 5. Model Training and Validation Curves (AUC vs. Epoch).

Fig 6. ROC Curves on Validation, Internal Test, and External Dataset.

Fig 7. ROC Curves for both devices on Internal Test.

647   Fig 8. Confusion Matrices on the (a) Internal and (b) External Dataset.

a

b

651   Fig 9:Histogram of predicted probability distributions on the (a) internal and (b) external dataset.

Fig 10.BI-RADS 4a Breast Lesion with Benign Features on Ultrasound and Grad-CAM

Analysis.

Ultrasound imaging reveals a solid, hypoechoic mass classified as BI-RADS 4a. The Hybrid

model correctly predicted this lesion as benign. Corresponding Grad-CAM overlays visually

explain the model's decision by highlighting key benign features: (a) obtuse marginal angles, (b)

significant posterior acoustic enhancement, (c) homogeneous internal echotexture, and (d) a

well-circumscribed boundary.

Fig 11.BI-RADS 4c Breast Lesion with Malignant Features on Ultrasound and Grad-CAM

Analysis.

Ultrasound imaging depicts a mass with highly suspicious characteristics, classified as BI-RADS

4c. The Hybrid model accurately predicted this lesion as malignant. The explanatory Grad-CAM

overlays identify the critical malignant features driving the model's decision: (a) angular,

spiculated margins, and rich internal vascularity on color Doppler imaging, (b) a thick echogenic

halo, an irregular and indistinct boundary.

Fig 12. A Challenging Case Correctly Reclassified by the Hybrid Model (Human-AI

Discordance). (a) B-mode ultrasound and (b)Color Doppler ultrasound, where the Grad-CAM

heatmap focused strongly on the upper and lateral boundaries of the lesion. It identifies the

continuity of the tumor and the distinct tissue interface (highlighted in red).

Fig 13. Performance Evaluation on the Prospective Validation Cohort. (a) ROC Curve: The

model achieved an impressive AUC of 0.9801 on the prospective dataset. (b) Detailed

Probability Distribution: The histogram shows a clear separation between predicted

probabilities for benign (blue) and malignant (orange) cases, indicating high prediction

confidence. (c) Classification Report: Quantitative metrics detailing the Precision, Recall, and

F1-score for each class, with an overall accuracy of 95.2%. (d) Confusion Matrix: The matrix

confirms 98.48% sensitivity (65/66) for malignant lesions and highlights that 8 benign cases

were misclassified (114/122 correctly identified).