Neuro: Machine Learning Optimized to Detect Neurodegenerative Diseases Pilot Study

Ilana Liu[1] Kun Liu[1,2] Morris Bell[1,2,3]
[1]Yale University
[2]Yale School of Medicine
[3]VA Connecticut Healthcare System

Abstract

Alzheimer's Disease (AD) is a progressive neurodegenerative disorder that primarily affects cognitive function. Early detection is a crucial factor in slowing the disease's progression, improving quality of life, and retaining cognitive function for years beyond diagnosis. Traditional detection methods have included a mix of mental tests, Magnetic Resonance Imaging (MRI) scans, and Positron Emission Tomography (PET) scans. While machine scanning methods boast an accuracy rate of up to 85%. These processes are relatively expensive, and language barriers often hinder cognitive function tests. Neuro is a study program that utilizes artificial intelligence and machine learning to analyze vocal cognitive tests for biomarkers of Alzheimer's Disease. Using a blend of traditional machine learning (random forest, SVM, Gradient Boosting) mixed with neural networks, such as Recurring Neural Networks (RNNs) and Convolution Neural Networks (CNNs), allows Neuro to retain its accuracy within its study. Neuro boasts an accuracy rate of 95%, an 88.3% F1 Score, 95% recall, 82.6% precision, and an AUC (Area Under the Curve) of 0.931. Working in tandem with diagnosis is the explanation of data; for this, we utilized SHAP (SHapley Additive exPlanations) for individual predictions. Machine Learning programming is both cost-effective and accessible, allowing it to be utilized in various clinical settings.

Introduction

Alzheimer's Disease is characterized by a buildup of beta-amyloid plaques (Aβ) and twisted tau (microtubule-associated protein) proteins within nerves and neurons, respectively. Symptoms include, but are not limited to, emotional instability, speech changes, and confusion. The primary indicator of the disorder is memory loss, both short and long-term. As of 2025, there are no known cures for Alzheimer's Disease, but there are treatments to slow progression and improve quality of life. However, these treatments become difficult if the disease is not detected in its early stages. Early diagnosis is key to providing patients with the highest level of care and preserving their minds. Unfortunately, there is a lack of accessible and accurate early detection methods. Whilst Cerebrospinal Fluid (CSF) testing and PET scans can be effective, they're extremely expensive and require expert knowledge to interpret. However, the rapidly developing field of AI may provide a new method. Through innovative machine learning models such as neural networks (RNN, CNN, FNN), support vector machines (SVM), and traditional tree-based models, massive improvements in pattern recognition, natural language processing (NLP), and time-series forecasting (prediction) have been made. Neuro utilizes hybrid machine learning models, combining RNN, CNN, RF, SVM, Multi-layer Perceptron (MLP, a type of FNN), and

GB to provide the most accurate possible results. Neuro also makes use of OpenAI's automatic speech recognition (ASR) model, Whisper, for accurate transcription/translation. These processes come together to form a machine that is both cost-effective and precise, despite difficulties like differences in language.

Recently, artificial intelligence-related developments in the field of neuroscience have been gaining traction. Garcia-Gutierrez et al.[1] were one of the earliest teams to develop tools for speech-based Alzheimer's analysis, using extreme gradient boosting (XGB) as their central model. This study displayed an impressive accuracy rate of 87%. However, Garcia-Guiterrez did not include a multilingual aspect. Ceyhan et al.[2] developed a machine based on multilingual AI speech analysis using RF and MLP. Despite boasting an accuracy rate of 72% for English and 76% for Spanish, this study lacked crucial Mel-Frequency Cepstral Coefficients (MFCCs). MFCCs are a small set of features that represent the important characteristics of a sound as it is perceived by the human ear. Despite how helpful their precision can be in detecting traits of Alzheimer's in speech, MFCCs have been overlooked in countless studies. The ASR model Whisper is also an overlooked tool for this process. Created by Radford et al[3], Whisper is a robust tool capable of multilingual analysis, allowing for the implementation of these methods of detection across a wide variety of languages. Garcia-Guiterrez et al. and Ceyhan et al. highlight the success of the use of AI -- particularly tree-based models and neural networks -- in the detection of neurodegenerative diseases. Neuro is a novel twist on such studies, utilizing tree-based, ensemble, and neural networks in conjunction with MFCCs and Whisper AI to deliver the best results possible.

A common issue among machine learning models is their inability to explain their results. To avoid this, Neuro uses SHAP. SHAP is a game-theory-based methodology that explains machine learning outputs through Shapley values. The method is unique due to its ability to provide global and local explanations for machine learning models as well as its versatility and precision. Through SHAP's capabilities as an explanation technique, Neuro is better able to communicate with study participants about unique biomarkers that may stand out during diagnosis. Personalization is also a unique tool that SHAP utilizes; its skills to provide individualized reports are extremely crucial in a clinical setting where symptoms may vary from patient to patient. By providing individualized reports, Neuro, working in tandem with SHAP, can display reports tailored to patients, creating a streamlined diagnosis to treatment methods.

Results

Neuro's study was centered around simulated data. To account for skewed data, we simulated data within real-world noisy situations. We based our model's predictions on people already diagnosed with Alzheimer's and compared similar biomarkers. From that, we utilized SHAP to construct a graph of values that displayed correspondence to Alzheimer's. To validate such data, Neuro evaluated consistency between the 151 biomarkers used as well as the consistency of the value ranges. The metrics used to display accuracy for Neuro were primarily

the accuracy rate and cross-entropy loss rate. The accuracy rate was favored because a high accuracy rate could indicate how correctly Neuro could distinguish between correct diagnoses across all possible cases. Cross-entropy loss rate is also a metric utilized because a high cross-entropy loss rate indicates predictions with a strong deviation from actual labels. These three metrics will provide a reliable estimate of our model's performance to a high degree.

The most accurate model was the hybridized model. Blending models that work accurately within small groups with models that are scalable to a large degree provides our study with an increased accuracy rate, even with a small participant pool of 100 simulated participants. This model also shows potential for scalability, especially through the usage of RNN and CNN for larger participant pools. The average accuracy rate through 5-fold cross-validation was around 94% ± 1.8%; to make note of this, a study by James et al. researching PET scans regarding Alzheimer's during 2020 yielded accuracy rates of 85%. Neuro's high accuracy shows promise for its future integration into clinical trials. Cross-entropy loss stayed at an all-time low of about 0.2072 for our best model. The accuracy and cross-entropy loss are displayed below in Figures 1 and 2.

(Figure 1.)

(Figure 2.)

The AUC was 0.931 and displays the discriminative power of Neuro. A high AUC represents high accuracy and a high rate of true positives as well as a low rate of false positives. It relates in correlation to ROC, which shows the relationship between the rate of true positives versus false positives. The higher the ROC, the better the performance of a model, just like Neuro. Below, Figure 3 below shows the ROC and the AUC, respectively, of every model, with our hybridized model having the highest ROC and AUC.

Figure 3.

Discussion

Our study on Neuro proposed a multimodal approach to detect Alzheimer's disease using machine learning. The framework is robust and capable of handling diverse groups, providing flexibility and explainability within diagnoses. Out of the 80 healthy control (HC) synthetic audio files, an average of 76 were correctly classified as such, while 4 were incorrectly classified as having signs of Alzheimer's. This resulted in an accuracy rate of 95% ± 1.2% for HC predictions. The misclassification of the 4 HC files can be attributed to several factors, such as overlap between normal aging and early pathological changes. However, the most likely explanation lies in the subtle distinction between these groups compared to the pronounced differences seen in severe dementia stages. While HC participants may show pause durations on average of 1.5 seconds, early AD participants may show a similar but slightly higher pause duration of around 2 seconds. This inherent similarity in pause timing creates borderline cases in which normal processing delays show resemblance to Alzheimer's disease. The overlap in numerical biomarker values due to acoustic similarity proves to be a fundamental challenge in early detection. The synthetic data generation process realistically created HC participants with speech changes like AD patterns, which proved to be an issue for Neuro to properly detect, particularly with people aged 86-95 years. Our AI model correctly classified 19 out of 20 AD participants' voice samples, with one incorrectly classified as healthy. This gave us an accuracy rate of 95% ± 0.8%, indicating a few risk instances of missed diagnosis. Table 1, featured below, shows the accuracy rates of our various AI models, displaying the hybrid model as the best with

Algorithm	True Negatives	False Positives	Healthy Total	True Positives	False Negatives	At-Risk Total	Accuracy (%)	Error Rate (%)
Random Forest	72.8	7.2	80	15.2	4.8	20	88.0	12.0
Gradient Boosting	69.6	10.4	80	14.4	5.6	20	84.0	16.0
SVM	66.4	13.6	80	15.2	4.8	20	81.6	18.4
MLP	64.0	16.0	80	14.0	6.0	20	78.0	22.0
CNN	61.6	18.4	80	12.8	7.2	20	74.4	25.6
RNN	63.2	16.8	80	13.6	6.4	20	76.8	23.2
Ensemble (All 6)	76.0	4.0	80	19.0	1.0	20	95.0	5.0

the data explained above.

(Table 1.)

Beyond diagnosis, explanations were created through SHAP explanations to provide an interpretation of our model's predictions. The explanations offered insight into how biomarkers contributed to diagnostic decisions, providing validation of the algorithm's reasoning process.

The SHAP summary displays the most influential features used by our ensemble model (refer to Figure 6 below for reference).

(Figure 4.)

Error analysis reveals opportunities for improved diagnostic accuracy through targeted biomarker enhancement. The overlap between aging and AD shows that age-corrected normalization algorithms can create false positive rates whilst maintaining heightened sensitivity for true cognitive decline. Incorporating biomarker tracking rather than single-point assessment may better distinguish temporary fluctuations. SHAP insights guide prospects for model iterations featuring live patients, showing that pattern analysis can receive computational focus whilst certain spectral features may be de-emphasized, if necessary, combined to create one robust measure. Semantic similarity analysis and working memory markers can address false negative cases by capturing cognitive domains not fully represented in current acoustic measures. These improvements could enhance Neuro's ability to detect the entire spectrum of Alzheimer's disease whilst maintaining accessibility, which makes voice screening a necessity.

Limitations

While Neuro displayed promising results, it currently utilizes synthetic data, which is our most significant limitation. While synthetic data can use evidence-based mathematical modeling of cognitive decline, it is incapable of fully encapsulating the spectrum of individual variability. From comorbidity effects to environmental factors, a variety of factors influence speech

production within AD participants. The synthetic biomarkers, while statistically rigorous, can oversimplify complex interactions within the brain that cause neurodegeneration, as well as an individual's characterization of a disease. Through such an error, our accuracy rate might be heightened, and we would need real human data to confirm this.

While our relatively small sample size of 100 synthetic participants can be used as a pilot study, it is an oversimplification of the entire Alzheimer's population. Improvements are necessary; an increased training data set is the most crucial one. Tens of thousands of participants are needed to create a generalization necessary to categorize millions of patients. The limited sample size also restricts our ability to perform comprehensive analyses across varied populations. To account for twelve different languages, gender, HC versus AD, and age, the subgroups typically consisted of one to two people. This amount of data is insufficient to properly analyze a disease affecting millions.

Our hybrid model, which combined RF, GB, SVM, MLP, CNN, and RNN, introduced computational complexity, which contributed to the risk of overfitting. Despite achieving 95% ± 2.2% accuracy, it specifically proved effective for synthetic data classification; further testing is required to check for accuracy among live patients. Our hybrid weight optimization, weighted from highest accuracy to lowest, created layers of complexity that were not balanced against dataset limitations, which also contributed to overfitting. This overcomplexity of data size warrants future work to improve the hybrid model balance through live training data.

Finally, another critical predicament for implementing Neuro is the consideration of cognitive disorders beyond Alzheimer's disease. Our hybrid model has displayed accuracy in the detection of early cognitive decline, but its applicability to other neurodegenerative diseases is uncertain. Neuro has strengths within biomarker detection, yet those biomarkers may potentially overlap with profiles from other diseases. For conditions that may affect speech systems, such as Parkinson's, transferability may be higher, yet for diseases such as Lewy body disease or vascular dementia, the results are unknown and require further testing. A further comprehensive multimodal approach, which includes additional cognitive testing and access to electronic health records, could improve Neuro's abilities to take notice of diseases besides Alzheimer's. The ability to detect a disease outside of Alzheimer's is critical to avoid misdiagnosis, as well as expand the range of its capabilities.

Methodology

Participant Demographics

Patient Demographics Summary
Alzheimer's Detection Study Cohort (N=100)

Demographic Category	Count	Percentage	Distribution Details
Total Participants	100	100%	-
Age Distribution			
45-65 years	40	40%	Mean: 55.0 ± 10.0
66-95 years	60	60%	Mean: 75.5 ± 9.5
Overall Age Range	45-95 years	Mean: 67.2 ± 14.8	-
Age at Diagnosis (At-Risk)	52-88 years	Mean: 71.3 ± 11.2	n=20
Gender Distribution			
Male	45	45%	36 Healthy, 9 At-Risk
Female	55	55%	44 Healthy, 11 At-Risk
Cognitive Status			
Healthy Controls	80	80%	MMSE: 28.2 ± 1.4
At-Risk/MCI	20	20%	MMSE: 24.1 ± 2.8
Language Background			
English Native	60	60%	48 Healthy, 12 At-Risk
Multilingual	40	40%	32 Healthy, 8 At-Risk
Speech Characteristics			
Normal Speech Rate	75	75%	62 Healthy, 13 At-Risk
Slow Speech Rate	25	25%	18 Healthy, 7 At-Risk
Word-Finding Difficulties	15	15%	3 Healthy, 12 At-Risk

(Table 2.)

Our dataset represented clinically realistic patients, displaying disparities such as language differences and underrepresented populations within the healthcare sphere.

Data Preprocessing

Our dataset was synthetically generated. We created 100 simulated patients, and of those patients, 20 were diagnosed with Alzheimer's, making up the AD group, whilst the rest were the HC group. The 80/20 split was utilized as it represented epidemiologically accurate real-world scenarios. The biomarker generation process incorporated mathematical modeling to simulate cognitive decline patterns. General parameters were created, situated by health status categories. The HC group contained data that indicated low word error rates as well as high semantic similarity. On the other hand, the AD group had the opposite, a high word error rate and low semantic similarity. Beyond the baseline details, age-related cognitive decline was mathematically modeled linearly to simulate realistic aging effects. UTF-8 encoding was utilized to standardize the 12 diverse languages. Neuro generated 151 biomarkers for the simulated data, whilst also accounting for language-specific and sex-specific acoustic adjustments.

Data Analysis

Neuro processes .wav files exceptionally well, utilizing LibRosa, an audio library that extracts auditory biomarkers from our synthetic audio models. While it does not actually synthesize any sound, we use NumPy to extract audio signals and then use LibRosa to generate spectrograms as well as extract MFCC data. In such a way, we can mimic real biomarkers from

patients for Neuro to analyze. Our synthetic audio generation creates NumPy arrays representing speech signals at 16kHz. We also incorporated realistic amplitude variations, frequency modulations, and temporal patterns of both HC and AD participants' speech production. LibRosa's comprehensive feature extraction process transforms these synthetic signals through short-time Fourier transformations for spectrogram generation and Mel-Scale filter bank analysis for MFCC computation. First, our system processes audio files labeled participant_name.wav, enabling batch processing whilst also maintaining individual tracking. Standard naming allows for result correlation, as well as automated file handling across our diverse dataset. The extract_audio_features method is the core processing engine, analyzing each participant through LibRosa's feature extraction. This method handles the biomarker extraction process, and its architecture allows for cross-linguistic analysis and processing consistency. After extraction, we cleaned missing values with median imputation as well as removed outliers through the 3-sigma rule (68-95-99.7). We also normalized our data through z-score standardization, then filtered our data through correlation and variance analysis, reducing redundancy. Feature selection was the next step, processing biomarkers by ranking, lassoing the best features, and then utilizing recursive feature elimination to remove less significant features. After selection, we retain 45-60 biomarkers that are later stratified into training, validation, and test sets with 5-fold cross-validation. Our models were then trained, and their predictions were combined to make the hybridized model.

To explain Neuro's predictions, we utilized SHAP, which interpreted our model's predictions by quantifying biomarker influence. As noted in Fig. 9, pause duration (0.185), fundamental frequency stability (0.162), and MFCC coefficient (0.148) were the strongest

discriminators, provided as global rankings of feature importance.

(Figure 5.)

       Spectrogram analysis also plays a key role in detection. Through short-time Fourier transformation analysis, which creates a time-frequency representation for capturing temporal patterns of speech degradation, a spectrogram is created. Our spectrogram features are integrated with traditional biomarkers made into quantitative features. Quantitative features such as spectral entropy and flux, formant trajectory variability, harmonic to noise ratio, and pauses provide markers of cognitive decline. Figure 8 below shows the variances between an HC and an AD patient; the frequency variability is much lower for the AD patient in comparison to our HC

(Figure 6.)

Acknowledgements

I want to thank Kilynn Mason for her editorial assistance in preparing this paper. I would also like to thank Kun Liu, Laura LaRosa, Saida Elmy, Morris Bell, and Freddie Ramirez for their guidance and support during this research.

References

1.

K. Ioannou, M. Bucci, Antonios Tzortzakakis, I. Savitcheva, A. Nordberg, and Konstantinos Chiotis: "Tau PET positivity predicts clinically relevant cognitive decline driven by Alzheimer's disease compared to comorbid cases; proof of concept in the ADNI study." *Molecular Psychiatry*. 2024.

2.

F. García-Gutiérrez, Montserrat Alegret, M. Marquié, Nathalia Muñoz, G. Ortega, A. Cano, Itziar De Rojas, P. García-González, Clàudia Olivé, R. Puerta, Ainhoa García-Sanchez, María Capdevila-Bayo, L. Montrreal, V. Pytel, Maitee Rosende-Roca, C. Zaldua, Peru Gabirondo, Lluís Tárraga, A. Ruiz, and M. Boada: "Unveiling the sound of the cognitive status: Machine Learning-based speech analysis in the Alzheimer's disease spectrum." *Alzheimer's Research & Therapy*. vol. 16, no. 1, 2024.

3.

B. Ceyhan, S. Bek, and T. Önal-Süzek: "Machine Learning-Based Prediction Models for Cognitive Decline Progression: A Comparative Study in Multilingual Settings Using Speech Analysis." *The Journal of Aging Research & Lifestyle*. Vol. PMC11106089, no. 1, 2024.

4.

C. Howard, A. Johnson, S. Baratono, K. Faust, J. Peedicail, and M. Ng: "Machine Learning-Based Cognitive Assessment with the Autonomous Cognitive Examination: Randomized Controlled Trial." *Journal of medical Internet research*. Vol. 27, no. 1, pp. e67446, 2025.

5.

S. Amini, B. Hao, J. Yang, C. Karjadi, V.B. Kolachalama, R. Au, and I.C. Paschalidis: "Prediction of Alzheimer's disease progression within 6 years using speech: A novel approach leveraging language models." *Alzheimer's & Dementia*. Vol. 1, 2024.

6.

H.J. James, C.H. Van Houtven, S. Lippmann, J.R. Burke, M. Shepherd-Banigan, E. Belanger, T.F. Wetle, and B.L. Plassman: "How Accurately Do Patients and Their Care Partners Report Results of Amyloid-β PET Scans for Alzheimer's Disease Assessment?" *Journal of Alzheimer's Disease*. vol. 74, no. 2, pp. 625–636, 2020.

7.

A. Radford, J. Kim, T. Xu, G. Brockman, C. Mcleavey, and I. Sutskever: "Robust Speech Recognition via Large-Scale Weak Supervision.", 2022.