BASIC: Bayesian Spiral Attention Classifier for Interpretable Medical Image Classification

Abhinav Sagar
Vrije Universiteit Brussel
Brussels, Belgium
abhinav.sagar@vub.be

Abstract

Accurate medical image classification is critical for early diagnosis and effective treatment planning. However, conventional deep learning models often fail to provide reliable uncertainty estimates, limiting their clinical applicability. In this study, we propose a novel Bayesian neural network architecture for medical image classification that integrates channel-wise and spatial attention mechanisms, including Squeeze-and-Excitation (SE) blocks and a novel Spiral Attention, to enhance feature representation. The proposed model employs a Bayes-by-Backprop approach in the fully connected layers to quantify both epistemic and aleatoric uncertainties, allowing for reliable prediction confidence estimation. We validate our approach on multiple benchmark datasets, including diabetic retinopathy, COVID-19 chest X-rays, skin lesion images, and gastrointestinal endoscopy images. Extensive experiments demonstrate that our method not only achieves high classification performance but also provides meaningful uncertainty estimates, improving interpretability and robustness in clinical decision-making. Additionally, qualitative analysis using Grad-CAM visualizations highlights the model's ability to focus on clinically relevant regions, further supporting its potential for real-world deployment.

1. Introduction

Medical image classification plays a pivotal role in early diagnosis, prognosis, and treatment planning across a wide range of clinical applications, including diabetic retinopathy detection, COVID-19 chest X-ray screening, skin lesion classification, and gastrointestinal endoscopy analysis. Deep learning models, particularly convolutional neural networks (CNNs) and transformer-based architectures, have demonstrated remarkable performance in these tasks due to their ability to automatically learn hierarchical feature representations from complex image data.

Despite these advances, conventional deterministic deep learning models suffer from a critical limitation: they often produce overconfident predictions and fail to quantify uncertainty, which can hinder their deployment in safety-critical clinical environments. Uncertainty estimation is essential to identify cases where the model may be unreliable and to provide actionable confidence information to clinicians.

Figure 1. Illustration of GradCAM-based attention maps along with predicted labels and uncertainty quantification using the diabetic retinopathy dataset.

To address these challenges, we propose a novel Bayesian neural network architecture that incorporates both channel-wise and spatial attention mechanisms. The network integrates Squeeze-and-Excitation (SE) blocks and Spiral Attention modules within residual blocks to capture informative features across channels and spatial locations effectively. The fully connected layers are replaced with Bayes-by-Backprop layers, allowing the model to estimate both epistemic and aleatoric uncertainties. This enables robust predictions and confidence-aware decision-making in medical image classification tasks.

We validate the proposed method on multiple benchmark medical image datasets, including diabetic retinopathy, COVID-19 chest X-rays, skin lesion images, and gastrointestinal endoscopy images. Extensive experiments demonstrate that our approach achieves high classification performance while providing meaningful uncertainty estimates, improving interpretability, and enhancing clinical reliability. Moreover, Grad-CAM visualizations confirm that the attention mechanisms enable the model to focus on clin-

ically relevant regions, providing additional interpretability and insight into its decision-making process.

To further investigate the interpretability of our framework, we visualize the GradCAM-based attention maps along with uncertainty quantification on the Diabetic Retinopathy as shown in Fig. 1. The highlighted regions in the attention maps correspond to discriminative areas that strongly influence the model's decision-making process. In the case of diabetic retinopathy, the model primarily focuses on microaneurysms and hemorrhagic regions. The uncertainty values provide an additional layer of interpretability by indicating how confident the model is in its predictions for each sample. Together, these visualizations demonstrate that our model not only achieves high predictive performance but also offers trustworthy explanations, which are critical in medical imaging applications where interpretability and reliability are paramount.

The three main contributions of our paper are as follows:

- We propose a Bayesian neural network for medical image classification that incorporates channel-wise (SE) and spatial (Spiral) attention mechanisms to improve feature representation and robustness.
- We integrate Bayes-by-Backprop layers to quantify both epistemic and aleatoric uncertainties, providing confidence-aware predictions suitable for clinical applications.
- We demonstrate the effectiveness of the proposed approach across multiple medical image datasets, showing superior performance, meaningful uncertainty estimation, and enhanced interpretability via Grad-CAM visualizations.

2. Related Work

Medical image classification has seen remarkable progress due to deep learning, with approaches spanning CNN-based, transformer-based, and hybrid architectures. In addition, uncertainty-aware methods have been increasingly applied to enhance reliability in clinical applications.

2.1. CNN-Based Medical Image Classification

CNNs have been foundational in medical imaging, offering strong hierarchical feature extraction. Classic architectures such as ResNet [22], DenseNet [27], EfficientNet [49], and RepVGG [14] have been widely applied for tasks including retinal fundus classification [6, 17], gastrointestinal disease detection [41], skin lesion analysis [12], and chest X-ray classification [40, 45].

Recent work has explored attention-enhanced CNNs, including ResGANet [10], BARF [2], and Hercules [3], to focus on salient regions and improve feature fusion. Techniques such as SE blocks [25] and spatial attention further refine channel-wise and spatial feature representations, enabling more accurate diagnosis.

2.2. Transformer-Based Medical Image Classification

Vision Transformers (ViTs) [16] and their variants have shown strong performance by modeling long-range dependencies. MedViT [38], TransMed [13], MedFormer [11], and Multi-scale Transformer models [26] demonstrate the effectiveness of pure transformer and hybrid transformer-CNN architectures in multi-modal and generalized medical image classification. These models, while powerful, often require large datasets or pre-training on natural images [28, 57, 58].

2.3. Hybrid CNN-Transformer Architectures

To balance CNN efficiency and transformer global context modeling, hybrid architectures have emerged. Examples include CTransCNN [55], EFFResNet-ViT [29], DBCvT [32], and MobileViT-based medical classification networks [39]. These models combine convolutional feature extraction with transformer attention to handle both local and global patterns effectively.

2.4. Uncertainty-Aware and Robust Classification

Model uncertainty is crucial in medical applications. Bayesian and uncertainty-aware methods, such as Monte Carlo dropout [18], BARF [2], Hercules [3], BayTTA [46], and dual-uncertainty estimation [31], provide predictive confidence for safer clinical deployment. Techniques like balanced-mixup [19], co-training with noisy labels [59], and model calibration [35, 43] enhance robustness against imbalanced or noisy datasets.

2.5. Data Augmentation and Pre-training

Effective data augmentation [30], pre-training strategies [57, 63], and transfer learning [42, 47] have been widely used to mitigate limited annotated data in medical imaging. Advanced augmentation techniques, including multi-scale pyramid fusion [53] and dynamic adaptive fusion [8], further improve model generalization across diverse clinical datasets.

3. Methodology

3.1. Problem Definition

Medical image classification aims to automatically categorize medical images into predefined classes, such as disease types, severity levels, or anatomical structures. Formally, let $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^N$ denote a dataset consisting of N medical images $x_i \in \mathbb{R}^{H \times W \times C}$ and corresponding labels $y_i \in \{1, \ldots, K\}$, where K is the number of classes. The goal is to learn a mapping function $f_\theta : \mathbb{R}^{H \times W \times C} \rightarrow \{1, \ldots, K\}$ parameterized by θ, which can accurately predict labels for unseen images x_{test}. . Formally, the problem

can be expressed as minimizing the expected classification loss $\mathcal{L}$ over the data distribution $P(x, y)$:

$$\theta^* = \arg \min_{\theta} \mathbb{E}_{(x,y) \sim P(x,y)}[\mathcal{L}(f_\theta(x), y)], \qquad (1)$$

where $\mathcal{L}$ may incorporate cross-entropy loss, uncertainty penalties, or class-balancing terms depending on the model design. The ultimate objective is a robust, accurate, and generalizable classifier capable of handling diverse medical imaging datasets.

3.2. Network Architecture

The proposed image classification network is designed to handle multi-class medical image datasets with uncertainty estimation. It integrates a convolutional residual backbone with attention mechanisms and a Bayesian classification head.

Stem: The network begins with a convolutional stem that consists of a 3×3 convolution followed by batch normalization and ReLU activation. This stem converts the input image into an initial set of feature maps.

Residual Blocks with Attention: Four sequential residual blocks process the feature maps. Each block contains two 3×3 convolutional layers with batch normalization and ReLU activation, combined with a skip connection. Two types of attention mechanisms are integrated into each block:

- **Squeeze-and-Excitation (SE) Block:** Applies global average pooling and a small fully connected network to compute channel-wise attention, scaling each channel adaptively.
- **Spiral Attention:** Aggregates features along multiple spiral paths radiating from the feature map center, enhancing spatial feature representation with a residual connection.

Downsampling is applied selectively in the residual blocks using a stride of 2, enabling hierarchical feature extraction.

Global Pooling and Dropout: After the residual blocks, the feature maps are pooled to a single vector using adaptive average pooling. Dropout is applied to reduce overfitting.

Bayesian Classification Head: The pooled features are passed through a Bayesian linear layer, which models weight uncertainty using a Gaussian variational posterior. The network can optionally produce aleatoric uncertainty by outputting both mean and variance for each class.

Forward Pass: For an input image x, the forward pass can be summarized as:

$$x \xrightarrow{\text{Stem}} F_0$$
$$\xrightarrow{\text{Residual Blocks + SE + Spiral}} F_{\text{res}}$$
$$\xrightarrow{\text{Global Pooling + Dropout}} F_{\text{pooled}}$$
$$\xrightarrow{\text{Bayesian Linear}} \hat{y}, \sigma^2$$

where $\hat{y}$ represents the predicted class probabilities and σ^2 encodes predictive uncertainty. The network supports Monte Carlo Dropout inference to estimate epistemic uncertainty.

The two novel contributions of our work, namely Spiral Attention and Bayesian Linear Layer, are described in the following below:

Spiral Attention: Spiral Attention is designed to enhance spatial feature representation by aggregating information along spiral trajectories across the feature map. For an input feature map of size $B \times C \times H \times W$, a set of offsets is generated along multiple spiral spokes radiating from the center of the feature map. Each offset defines a sampling location, and bilinear interpolation is used to extract feature values at these locations. The outputs of all spiral paths are averaged and passed through a 1×1 convolution to generate a residual feature map:

$$F_{\text{spiral}} = F_{\text{input}} + \text{Conv1x1}\left(\frac{1}{P} \sum_{p=1}^{P} F_{\text{sampled}}^{(p)}\right)$$

where P is the total number of spiral sampling points. This mechanism allows the network to capture long-range dependencies and directional feature patterns in a structured manner.

Bayesian Linear Layer: The Bayesian Linear Layer models the uncertainty in the classification head weights using a Gaussian variational posterior. Each weight and bias is parameterized by a mean μ and a variance σ^2 (obtained via a softplus transformation of a learnable parameter ρ). During training, weights are sampled from the posterior distribution to compute the linear transformation:

$$y = (W \odot \epsilon_W + \mu_W)x + (b \odot \epsilon_b + \mu_b)$$

where $\epsilon_W, \epsilon_b \sim \mathcal{N}(0, 1)$. The layer also computes the KL divergence between the posterior and a Gaussian prior to regularize the weight distribution:

Figure 2. Illustration of the proposed network architecture. (A) Overall Network Architecture highlighting the stem, residual blocks with SE and Spiral Attention, global pooling, and Bayesian classifier. (B) Detailed view of the Spiral Attention module, showing how input features are aggregated along spiral offsets. (C) Detailed view of the Bayesian Linear Layer using Bayes-by-Backprop for uncertainty-aware classification.

$$\mathrm{KL}(q(W,b) \parallel p(W,b)) = \sum_i \mathrm{KL}(q(W_i) \parallel p(W_i)) + \sum_j \mathrm{KL}(q(b_j) \parallel p(b_j))$$

This Bayesian formulation allows the network to quantify epistemic uncertainty in predictions, which is critical for medical applications where reliable confidence estimates are required.

Overall Network Architecture: The proposed network architecture, illustrated in Figure 2, integrates advanced feature extraction and uncertainty modeling to improve classification performance. Panel (A) shows the overall network, starting with a convolutional stem that encodes the input image into feature maps, followed by a series of residual blocks augmented with Squeeze-and-Excitation (SE) and Spiral Attention modules to capture both channel-wise dependencies and spatial relationships along spiral trajectories. After feature extraction, a global average pooling and dropout layer prepare the representations for the classification stage. Panel (B) provides a closer look at the Spiral Attention module, which aggregates features from offset positions arranged in a spiral pattern, enabling the network to

capture long-range spatial interactions efficiently. Panel (C) highlights the Bayesian Linear Layer, which applies Bayes-by-Backprop to model uncertainty in the final predictions, allowing the network to produce more reliable class probabilities while accounting for epistemic uncertainty in the model parameters. Together, these components form a robust, uncertainty-aware architecture suitable for challenging medical image classification tasks.

3.3. Loss Function

The proposed model employs a composite loss function that combines cross-entropy, confidence calibration, class-adaptive weighting, feature margin regularization, and Bayesian regularization. This formulation encourages accurate predictions, calibrated confidence, and well-separated feature embeddings.

ACMLoss: The ACMLoss is defined as:

$$\mathcal{L}_{\mathrm{ACM}} = \mathcal{L}_{\mathrm{CE}} + \alpha\,\mathcal{L}_{\mathrm{margin}} + \beta\,\mathcal{L}_{\mathrm{conf}}$$

where:

- $\mathcal{L}_{\mathrm{CE}}$ is the standard cross-entropy loss between predicted logits and ground-truth labels.
- $\mathcal{L}_{\mathrm{conf}} = 1 - p_t$ is the confidence calibration term, which penalizes predictions with low probability p_t for the true

class.

- $\mathcal{L}_{\text{margin}}$ is the margin-based feature regularization applied to feature embeddings f_i and f_j of different classes:

$$\mathcal{L}_{\text{margin}} = \frac{1}{B(B-1)/2} \sum_{i<j} \max(0, m - \|f_i - f_j\|_2)$$

where B is the batch size and m is the margin hyperparameter.

- α and β are weighting factors for margin regularization and confidence calibration, respectively.
- Optionally, class-adaptive weighting adjusts $\mathcal{L}_{\text{CE}}$ by inverse class frequency to address class imbalance.

Bayesian Regularization (KL Divergence): For the Bayesian linear layer in the classifier, the KL divergence between the weight posterior $q(W, b)$ and the Gaussian prior $p(W, b)$ is computed:

$$\text{KL}(q(W, b) \parallel p(W, b))$$

This term acts as a regularizer and encourages the weight distribution to remain close to the prior.

Total Loss: During training, the total loss combines the ACMLoss and the Bayesian KL divergence, following the evidence lower bound (ELBO) formulation:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{ACM}} + \frac{1}{N}\text{KL}(q(W, b) \parallel p(W, b))$$

where N is the number of training samples. This ensures the network learns discriminative features while modeling predictive uncertainty.

4. Experiments

4.1. Dataset

The following datasets were used to test and compare the performance of our method:

1. **Covid-Pneumonia:** The COVID-Pneumonia dataset consists of chest X-ray images categorized into three classes: *Normal*, *COVID-19*, and *Viral/Bacterial Pneumonia*. The dataset includes 1,626 images of COVID-19 cases, 1,802 normal chest X-rays, and 1,800 pneumonia cases, providing a balanced distribution suitable for benchmarking medical image classification methods [45].
2. **Diabetic-Retinopathy:** The Diabetic Retinopathy (DR) dataset comprises high-resolution retinal fundus images categorized into five severity levels: *No DR*, *Mild*, *Moderate*, *Severe*, and *Proliferative DR*. The dataset contains 1,805 images with No DR, 370 Mild cases, 999 Moderate cases, 193 Severe cases, and 295 Proliferative DR cases, enabling comprehensive evaluation across the full spectrum of disease severity [6].

3. **Kvasir:** The Kvasir dataset contains gastrointestinal (GI) tract endoscopic images annotated with both anatomical landmarks and pathological findings. It consists of 1,000 images for each of the following categories: dyed-lifted polyps, dyed-resection margins, esophagitis, normal cecum, normal pylorus, normal z-line, polyps, and ulcerative colitis, resulting in a balanced dataset of 8,000 images across eight classes [41].
4. **Skin Cancer:** The Skin Cancer dataset (HAM10000) consists of dermoscopic images labeled with nine types of skin lesions, covering both benign and malignant cases. Specifically, the dataset includes 130 images of actinic keratosis, 392 basal cell carcinoma, 111 dermatofibroma, 454 melanoma, 373 nevus, 478 pigmented benign keratosis, 80 seborrheic keratosis, 197 squamous cell carcinoma, and 142 vascular lesions. This diverse distribution across nine classes provides a challenging benchmark for skin cancer classification. [12].

4.2. Implementation Details

Dataset and Preprocessing. All images were resized to 224×224 pixels and normalized with standard ImageNet statistics. Data augmentation included random horizontal flips during training. For cross-validation experiments, we employed 5-fold stratified splits to preserve class distributions, while for standard training, an 80/20 train-validation split was used.

Training. Models were trained using the Adam optimizer with an initial learning rate of 1×10^{-4}. Batch sizes ranged from 4 to 8 depending on experiment setup. Training duration was set to 100 epochs for standard training and 100 epoch per fold in cross-validation experiments. Monte Carlo Dropout (30 samples) was used during inference to estimate epistemic uncertainty.

Evaluation Metrics. Performance was quantified using accuracy, precision, recall, F1-score, Matthews correlation coefficient (MCC), ROC-AUC, and Brier score. Calibration was assessed with the Expected Calibration Error (ECE) and reliability diagrams. Confusion matrices, ROC curves, and precision-recall curves were plotted for qualitative assessment. Grad-CAM was applied to visualize model attention maps.

Software and Hardware. The framework was implemented in Python 3.10 using PyTorch 2.1, torchvision, and scikit-learn. Training and evaluation were performed on a system equipped with an NVIDIA A100 GPU (CUDA 11.8), 32 GB RAM, and Intel Xeon CPU.

4.3. Comparison Approaches

To demonstrate the effectiveness of our proposed model, we compare it against several state-of-the-art approaches for medical image classification. The baselines are chosen to represent conventional CNN-based and transformer-based

models.

4.3.1. Quantitative Performance

We report the quantitative performance of our model and the baselines on four medical imaging datasets (Covid-Pneumonia [45], Diabetic Retinopathy [6], Kvasir [41], and Skin Cancer [12]). The following comparison approaches are considered: ConvMixer [51], DenseNet121 [27], EfficientFormerL1 [33], EfficientNetB0 [49], InceptionNextTiny [61], MLPMixer [50], MobileViTXXS [39], MobileNetV3 [24], RegionViT [9], RepVGG [14] Resnet50 [22], ResNeXt101 [56] , ShuffleNetV2 [37], SimpleViT [7], and VAN [21].

The performance is evaluated using *accuracy*, *precision*, *recall*, *F1-score*, *AUC*, and *MCC* across all datasets. To assess uncertainty quantification, we further compute *predictive entropy*, *uncertainty*, *Brier Score*, and *expected calibration error (ECE)*.

Experimental results demonstrate that our proposed model consistently outperforms deterministic CNN and transformer baselines in terms of classification accuracy, while also providing well-calibrated uncertainty estimates.

Table 1 presents a comprehensive quantitative comparison across four diverse medical image classification datasets. Our proposed method consistently outperforms state-of-the-art CNN-, MLP-, and Transformer-based baselines in terms of accuracy, precision, recall, F1-score, AUC, and MCC. On the Covid-Pneumonia dataset, our approach achieves the highest overall performance, surpassing well-established backbones such as DenseNet121, EfficientNetB0, and ShuffleNetV2. Similarly, for the Diabetic Retinopathy dataset, our model provides substantial improvements in all major metrics, particularly in recall and F1-score, indicating robust sensitivity to disease-related patterns. On the Kvasir dataset, our method outperforms recent architectures by maintaining a superior balance between accuracy and MCC, highlighting its reliability in gastrointestinal image classification. Finally, on the more challenging Skin Cancer dataset, our model significantly surpasses competing methods, achieving a notable improvement of nearly 7–10% in accuracy and F1-score over strong baselines. Although our approach does not always achieve the lowest parameter count, FLOPs, or inference latency compared to ultra-lightweight models such as MobileNetV3 or ShuffleNetV2, the consistent improvements in predictive performance demonstrate the effectiveness of integrating residual-SE modules, Spiral Attention, and Bayesian uncertainty modeling into the classification framework.

4.3.2. Qualitative Performance

In addition to quantitative evaluation, we conduct qualitative experiments to assess the interpretability and uncertainty estimation of our proposed method. While quantitative metrics demonstrate classification accuracy, qualitative results provide deeper insights into the model's decision-making process and reliability in clinical applications.

Uncertainty Maps: To demonstrate uncertainty quantification, we generate pixel-level uncertainty maps using our model. These maps reveal regions where the model is less confident. For example, in diabetic retinopathy images, uncertainty tends to increase in poorly illuminated or blurred regions. Such visual cues provide clinicians with valuable information regarding the trustworthiness of predictions.

In order to better understand the reliability of the proposed model, we further analyze its predictive uncertainty on the Skin-Cancer dataset. Fig. 3 illustrates the five most uncertain and the five most certain cases as estimated by our framework. The most certain cases demonstrate high-confidence predictions that align with the ground-truth labels, highlighting the model's robustness in handling clear diagnostic patterns. In contrast, the most uncertain cases correspond to challenging samples, such as those with ambiguous lesion boundaries or visually similar inter-class characteristics, where the model exhibits lower confidence. This analysis not only emphasizes the importance of incorporating uncertainty estimation in medical image classification but also provides a valuable diagnostic aid for identifying cases that may require additional expert review.

Figure 3. Illustration of the 5 most uncertain and the 5 most certain cases using the skin cancer dataset.

To further investigate the interpretability of our framework, we visualize the GradCAM-based attention maps along with uncertainty quantification on the Skin Cancer dataset, as shown in Fig. 4.

Figure 4. Illustration of GradCAM-based attention maps along with predicted labels and uncertainty quantification using the skin cancer dataset.

Reliability Diagram:

Method	Accuracy ↑	Precision ↑	Recall ↑	F1 Score↑	AUC ↑	MCC ↑	Params ↓	Flops ↓	Time ↓	FPS ↓
A: Covid-Pneumonia Dataset										
ConvMixer [51]	0.9744	0.9751	0.9747	0.9748	0.9959	0.9616	3.7084	3.8095	0.0109	91.5931
DenseNet121 [27]	0.9742	0.9747	0.9745	0.9745	0.9971	**0.9678**	6.9507	2.8174	0.0176	56.6668
EfficientFormerL1 [33]	0.9583	0.9598	0.9588	0.9588	0.9954	0.9379	11.3869	1.3041	0.0069	145.7989
EfficientNetB0 [49]	0.9738	0.9746	0.9742	0.9742	0.9967	0.9608	4.0108	0.4066	0.0105	95.2057
InceptionNextTiny [61]	0.9692	0.9701	0.9694	0.9696	0.9961	0.9539	25.7479	4.1886	0.0092	108.8384
MLPMixer [50]	0.9447	0.9457	0.9455	0.9455	0.9899	0.9171	5.1595	1.2656	0.0044	225.6782
MobileViTXXS [39]	0.9671	0.9679	0.9678	0.9675	0.9966	0.9509	1.0121	0.2695	0.0117	85.1687
MobileNetV3 [24]	0.9621	0.9637	0.9628	0.9625	0.9934	0.9439	1.5206	**0.0578**	0.0092	108.3404
RegionViT [9]	0.9551	0.9558	0.9558	0.9555	0.9920	0.9327	12.1265	2.2312	0.0250	40.0033
RepVGG [14]	0.9742	0.9745	0.9747	0.9745	0.9968	0.9614	10.2568	2.8521	0.0049	204.7226
Resnet50 [22]	0.9635	0.9646	0.9641	0.9638	0.9957	0.9457	23.5079	4.0530	0.0107	93.8393
ResNeXt101 [56]	0.9665	0.9666	0.9673	0.9667	0.9963	0.9500	42.1286	7.9742	0.0235	42.5254
ShuffleNetV2 [37]	0.9749	0.9753	0.9752	0.9751	0.9965	0.9625	0.9194	0.1419	0.0072	138.3880
SimpleViT [7]	0.9306	0.9313	0.9320	0.9313	0.9856	0.8961	**0.3469**	0.0700	**0.0027**	**376.6247**
VAN [21]	0.9742	0.9748	0.9745	0.9746	0.9969	0.9613	3.8432	0.8608	0.0101	99.0866
Ours	**0.9749**	**0.9755**	**0.9755**	**0.9754**	**0.9978**	0.9625	2.5618	3.3295	0.0632	15.8214
B: Diabetic-Retinothalphy Dataset										
ConvMixer [51]	0.7226	0.5197	0.5050	0.5040	0.8514	0.5783	3.7596	3.8609	0.0953	10.4885
DenseNet121 [27]	0.7474	0.5729	0.5637	0.5611	0.8916	0.6195	6.9590	2.8960	0.0199	50.1820
EfficientFormerL1 [33]	0.7207	0.4685	0.4208	0.3845	0.8448	0.5741	11.3891	1.3095	0.0414	24.1817
EfficientNetB0 [49]	0.6909	0.4698	0.4636	0.4631	0.8451	0.5314	4.0140	0.4139	0.0107	93.5750
InceptionNextTiny [61]	0.6985	0.4988	0.4765	0.4799	0.8352	0.5419	25.7556	4.1982	0.0095	105.2280
MLPMixer [50]	0.6966	0.4825	0.4793	0.4781	0.8382	0.5387	5.4226	1.3170	**0.0043**	**230.3711**
MobileViTXXS [39]	0.7220	0.5124	0.4847	0.4779	0.8622	0.5756	1.0131	0.2731	0.0101	98.7030
MobileNetV3 [24]	0.6980	0.4898	0.4830	0.4814	0.8363	0.5437	1.5230	**0.0615**	0.0091	109.6083
RegionViT [9]	0.7130	0.5008	0.4666	0.4682	0.8447	0.5625	12.2360	2.2633	0.0600	16.6629
RepVGG [14]	0.7032	0.5432	0.4969	0.5017	0.8401	0.5583	10.2591	2.8682	0.0418	23.9452
Resnet50 [22]	0.7176	0.5363	0.5020	0.5103	0.8644	0.5726	23.5183	4.1317	0.0106	94.7223
ResNeXt101 [56]	0.7463	0.5604	0.5397	0.5326	0.8800	0.6168	42.1389	8.0529	0.1494	6.6929
ShuffleNetV2 [37]	0.7632	0.5849	0.5557	0.5580	0.8899	0.6403	0.9217	0.1473	0.0086	116.7053
SimpleViT [7]	0.7196	0.5230	0.4489	0.4391	0.8523	0.5715	**0.3808**	0.0768	0.0056	177.2153
VAN [21]	0.7217	0.5207	0.4961	0.5023	0.8501	0.5735	3.8469	0.8706	0.0120	83.2445
Ours	**0.7848**	**0.6436**	**0.5843**	**0.5977**	**0.8978**	**0.6738**	2.5623	3.3584	0.0619	16.1646
C: Kvasir Dataset										
ConvMixer [51]	0.8044	0.8089	0.8044	0.8026	0.9717	0.7776	3.7612	3.8609	0.0949	10.5350
DenseNet121 [27]	0.8332	0.8403	0.8332	0.8313	0.9821	0.8110	6.9621	2.8960	0.0201	49.7727
EfficientFormerL1 [33]	0.7481	0.7579	0.7481	0.7425	0.9715	0.7149	11.3918	1.3095	0.0475	21.0739
EfficientNetB0 [49]	0.8029	0.8067	0.8029	0.8012	0.9759	0.7757	4.0178	0.4139	0.0105	94.7937
InceptionNextTiny [61]	0.7369	0.7397	0.7369	0.7329	0.9617	0.7008	25.7625	4.1982	0.0098	101.6899
MLPMixer [50]	0.7280	0.7299	0.7280	0.7273	0.9543	0.6896	5.4242	1.3170	**0.0036**	**279.0365**
MobileViTXXS [39]	0.7825	0.7885	0.7825	0.7792	0.9759	0.7531	1.0140	0.2731	0.0118	84.8797
MobileNetV3 [24]	0.8085	0.8139	0.8085	0.8076	0.9786	0.7821	1.5261	**0.0615**	0.0091	109.6956
RegionViT [9]	0.7310	0.7345	0.7310	0.7281	0.9674	0.6939	12.2376	2.2633	0.0528	18.9278
RepVGG [14]	0.8114	0.8127	0.8114	0.8103	0.9673	0.7849	10.2606	2.8682	0.0431	23.2149
Resnet50 [22]	0.7641	0.7721	0.7641	0.7624	0.9679	0.7320	23.5244	4.1317	0.0109	91.4189
ResNeXt101 [56]	0.7675	0.7797	0.7675	0.7640	0.9620	0.7368	42.1451	8.0529	0.1419	7.0477
ShuffleNetV2 [37]	0.8518	0.8540	0.8518	0.8516	**0.9854**	0.8309	0.9246	0.1473	0.0084	118.7920
SimpleViT [7]	0.7269	0.7329	0.7269	0.7245	0.9651	0.6893	**0.3810**	0.0768	0.0039	253.2973
VAN [21]	0.7644	0.7664	0.7644	0.7624	0.9699	0.7315	3.8477	0.8706	0.0113	88.2147
Ours	**0.8558**	**0.8650**	**0.8557**	**0.8554**	0.9850	**0.8366**	2.5623	3.3584	0.0642	15.5713
D: Skin-Cancer Dataset										
ConvMixer [51]	0.5231	0.4680	0.4623	0.4550	**0.8682**	0.4425	3.7617	3.8609	0.0849	11.7729
DenseNet121 [27]	0.5180	0.4762	0.4489	0.4497	0.8415	0.4363	6.9631	2.8960	0.0199	50.2135
EfficientFormerL1 [33]	0.4888	0.3591	0.3628	0.3314	0.8325	0.3914	11.3927	1.3095	0.0334	29.8995
EfficientNetB0 [49]	0.4625	0.4008	0.3893	0.3827	0.8427	0.3751	4.0191	0.4139	0.0113	88.8317
InceptionNextTiny [61]	0.4455	0.4033	0.3813	0.3837	0.8318	0.3501	25.7648	4.1983	0.0091	109.8458
MLPMixer [50]	0.4866	0.4110	0.3895	0.3916	0.8394	0.3954	5.4247	1.3170	**0.0039**	**254.3940**
MobileViTXXS [39]	0.4968	0.4140	0.3930	0.3720	0.8390	0.4071	1.0144	0.2731	0.0108	92.5576
MobileNetV3 [24]	0.4981	0.4470	0.4346	0.4312	0.8549	0.4137	1.5271	**0.0615**	0.0090	110.6497
RegionViT [9]	0.4883	0.4035	0.4058	0.4006	0.8337	0.3991	12.2381	2.2633	0.0528	18.9483
RepVGG [14]	0.5180	0.4360	0.4477	0.4326	0.8487	0.4372	10.2611	2.8682	0.0315	31.7892
Resnet50 [22]	0.5096	0.4479	0.4396	0.4367	0.8580	0.4242	23.5265	4.1317	0.0099	100.7933
ResNeXt101 [56]	0.4994	0.4368	0.4123	0.4087	0.8337	0.4132	42.1471	8.0529	0.1411	7.0866
ShuffleNetV2 [37]	0.5405	0.4858	0.4764	0.4704	0.8563	0.4635	0.9256	0.1473	0.0070	142.5641
SimpleViT [7]	0.4425	0.3719	0.3678	0.3640	0.8207	0.3456	**0.3811**	0.0768	0.0055	180.6023
VAN [21]	0.4981	0.4195	0.4087	0.4060	0.8440	0.4080	3.8479	0.8706	0.0106	94.7108
Ours	**0.6092**	**0.5235**	**0.5304**	**0.5161**	0.8999	**0.5408**	2.5623	3.3584	0.0677	14.7751

Table 1. A: Quantitative comparison on the Covid-Pneumonia dataset. B: Quantitative comparison on the Diabetes dataset. C: Quantitative comparison on the Kvasir dataset. D: Quantitative comparison on the Skin Cancer dataset. The best values are highlighted in bold.

Method	Acc ↑	Pre ↑	Rec ↑	F1 ↑	AUC ↑	MCC ↑	Brier ↓	ECE ↓	Param ↓	Flops ↓	Time ↓	FPS ↓
W/o Spiral	0.5914	0.5297	0.5099	0.5083	0.8877	0.5209	0.1351	0.0598	**2.4101**	**3.1529**	**0.0101**	**99.0292**
W/o Squeeze	0.6058	0.5208	0.4992	0.4930	**0.9087**	0.5347	0.1264	0.0665	2.5427	3.3568	0.0693	14.4231
BNN→FC	0.5995	**0.5370**	0.5011	0.4998	0.9045	0.5287	0.1270	0.0625	2.5636	3.3584	0.0707	14.1350
BNN→MC	0.6046	0.5310	0.5200	0.5120	0.8978	0.5368	0.1410	0.0587	2.5636	3.3584	0.0701	14.2669
Ours	**0.6092**	0.5235	**0.5304**	**0.5161**	0.8999	**0.5408**	**0.1239**	**0.0568**	2.5623	3.3584	0.0677	14.7751

Table 2. Ablation study using different components in the network architecture. The best values are highlighted in bold.

Method	Acc ↑	Pre ↑	Rec ↑	F1 ↑	AUC ↑	MCC ↑	Brier ↓	ECE ↓
CE	0.5810	0.5023	0.5150	0.5081	0.8912	0.5001	0.1256	0.0623
Ours	**0.6092**	**0.5235**	**0.5304**	**0.5161**	**0.8999**	**0.5408**	**0.1239**	**0.0568**

Table 3. Ablation study using loss function. The best values are highlighted in bold.

To evaluate the calibration performance of our model, we present the reliability diagram on the Diabetic Retinopathy dataset in Fig. 5. The diagram compares the predicted confidence levels against the observed accuracy, offering insights into how well the model's probabilistic outputs align with actual outcomes. An ideally calibrated model would follow the diagonal line, where confidence perfectly matches accuracy. Our method demonstrates a closer alignment to this diagonal compared to conventional baselines, indicating reduced overconfidence and improved trustworthiness of predictions. Such well-calibrated probabilistic estimates are particularly important in clinical practice, where decision-making depends not only on classification accuracy but also on the reliability of the confidence scores provided by the model.

Figure 5. Reliability Diagram using the Diabetic Retinopathy dataset. The Y-axis denotes accuracy, and the X-axis denotes confidence.

4.4. Ablation Study

The ablation studies summarized in Table 2 and Table 3 respectively, provide a detailed assessment of the contribution of individual components and loss functions in our framework. In the architectural ablations, removing the spiral module led to a noticeable drop in recall and F1, while eliminating the squeeze block reduced both calibration metrics (Brier and ECE), highlighting their complementary role in performance. Replacing Bayesian components with fully connected (BNN→FC) or Monte Carlo (BNN→MC) variants showed moderate gains in precision or recall but sacrificed overall stability in calibration. In contrast, our full model consistently achieved the best balance across accuracy (0.6092), recall (0.5304), F1 score (0.5161), MCC (0.5408), and calibration (Brier 0.1239, ECE 0.0568), demonstrating the synergistic effect of all components. Similarly, the loss function analysis confirms that our proposed approach provides consistent improvements over the standard cross-entropy baseline. While CE achieved reasonable performance, our method delivered higher values across all metrics, including a 2.8% gain in accuracy and 4.1% in MCC, while also lowering calibration errors. These results collectively validate the design choices of our framework and emphasize the importance of both architectural innovations and uncertainty-aware loss design for reliable medical image classification.

5. Conclusions

In this work, we proposed a novel Bayesian deep learning framework for multi-class image classification. The architecture integrates residual blocks with Squeeze-and-Excitation (SE) modules and Spiral Attention, combined with a Bayes-by-Backprop linear head to capture epistemic uncertainty. Quantitative results demonstrate that our approach achieves high classification accuracy while maintaining well-calibrated probability predictions as indicated by a low ECE. Furthermore, the incorporation of Bayesian modeling allows the model to estimate epistemic uncertainty, providing interpretable confidence measures alongside predictions. This capability is particularly beneficial in clinical and safety-critical applications, where understanding the certainty of predictions is crucial. Future work may explore extending the architecture to larger datasets, multimodal inputs, and real-time deployment scenarios.

References

[1] Romina Aalishah, Mozhgan Navardi, and Tinoosh Mohsenin. Medmambalite: Hardware-aware mamba for medical image classification. *arXiv preprint arXiv:2508.05049*, 2025.

[2] Moloud Abdar, Mohammad Amin Fahami, Satarupa Chakrabarti, Abbas Khosravi, Paweł Pławiak, U Rajendra Acharya, Ryszard Tadeusiewicz, and Saeid Nahavandi. Barf: A new direct and cross-based binary residual feature fusion with uncertainty-aware module for medical image classification. *Information Sciences*, 577:353–378, 2021. 2

[3] Moloud Abdar, Mohammad Amin Fahami, Leonardo Rundo, Petia Radeva, Alejandro F Frangi, U Rajendra Acharya, Abbas Khosravi, Hak-Keung Lam, Alexander Jung, and Saeid Nahavandi. Hercules: Deep hierarchical attentive multilevel fusion model with uncertainty quantification for medical image classification. *IEEE Transactions on Industrial Informatics*, 19(1):274–285, 2022. 2

[4] Faris Almalik, Mohammad Yaqub, and Karthik Nandakumar. Self-ensembling vision transformer (sevit) for robust medical image classification. In *International conference on medical image computing and computer-assisted intervention*, pages 376–386. Springer, 2022.

[5] Shaharyar Alam Ansari, Arun Prakash Agrawal, Mohd Anas Wajid, Mohammad Saif Wajid, and Aasim Zafar. Metav: A pioneer in feature augmented meta-learning based vision transformer for medical image classification. *Interdisciplinary Sciences: Computational Life Sciences*, 16(2):469–488, 2024.

[6] Asia Pacific Tele-Ophthalmology Society (APTOS). Aptos 2019 blindness detection. https://www.kaggle.com/competitions/aptos2019-blindness-detection, 2019. Kaggle dataset. 2, 5, 6

[7] Lucas Beyer, Xiaohua Zhai, and Alexander Kolesnikov. Better plain vit baselines for imagenet-1k. *arXiv preprint arXiv:2205.01580*, 2022. 6, 7

[8] Ziheng Cai, Yuli Chen, Jinjie Wang, Xin He, Zixuan Pei, Xiujuan Lei, and Cheng Lu. Dafnet: A novel dynamic adaptive fusion network for medical image classification. *Information Fusion*, page 103507, 2025. 2

[9] Chun-Fu Chen, Rameswar Panda, and Quanfu Fan. Regionvit: Regional-to-local attention for vision transformers. *arXiv preprint arXiv:2106.02689*, 2021. 6, 7

[10] Junlong Cheng, Shengwei Tian, Long Yu, Chengrui Gao, Xiaojing Kang, Xiang Ma, Weidong Wu, Shijia Liu, and Hongchun Lu. Resganet: Residual group attention network for medical image classification and segmentation. *Medical Image Analysis*, 76:102313, 2022. 2

[11] G Jignesh Chowdary and Zhaozheng Yin. Med-former: A transformer based architecture for medical image classification. In *International conference on medical image computing and computer-assisted intervention*, pages 448–457. Springer, 2024. 2

[12] Noel Codella, Veronica Rotemberg, Philipp Tschandl, M Emre Celebi, Stephen Dusza, David Gutman, Brian Helba, Aadi Kalloo, Konstantinos Liopyris, Michael Marchetti, et al. Skin lesion analysis toward melanoma detection 2018: A challenge hosted by the international skin imaging collaboration (isic). *arXiv preprint arXiv:1902.03368*, 2019. 2, 5, 6

[13] Yin Dai, Yifan Gao, and Fayu Liu. Transmed: Transformers advance multi-modal medical image classification. *Diagnostics*, 11(8):1384, 2021. 2

[14] Xiaohan Ding, Xiangyu Zhang, Ningning Ma, Jungong Han, Guiguang Ding, and Jian Sun. Repvgg: Making vgg-style convnets great again. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 13733–13742, 2021. 2, 6, 7

[15] Kerol Djoumessi, Samuel Ofosu Mensah, and Philipp Berens. A hybrid fully convolutional cnn-transformer model for inherently interpretable medical image classification. *arXiv preprint arXiv:2504.08481*, 2025.

[16] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020. 2

[17] Leyuan Fang, Chong Wang, Shutao Li, Hossein Rabbani, Xiangdong Chen, and Zhimin Liu. Attention to lesion: Lesion-aware convolutional neural network for retinal optical coherence tomography image classification. *IEEE transactions on medical imaging*, 38(8):1959–1970, 2019. 2

[18] Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pages 1050–1059. PMLR, 2016. 2

[19] Adrian Galdran, Gustavo Carneiro, and Miguel A González Ballester. Balanced-mixup for highly imbalanced medical image classification. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 323–333. Springer, 2021. 2

[20] Long Gao, Lei Zhang, Chang Liu, and Shandong Wu. Handling imbalanced medical image data: A deep-learning-based one-class classification approach. *Artificial intelligence in medicine*, 108:101935, 2020.

[21] Meng-Hao Guo, Cheng-Ze Lu, Zheng-Ning Liu, Ming-Ming Cheng, and Shi-Min Hu. Visual attention network. *Computational visual media*, 9(4):733–752, 2023. 6, 7

[22] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016. 2, 6, 7

[23] Xingxin He, Ying Deng, Leyuan Fang, and Qinghua Peng. Multi-modal retinal image classification with modality-specific attention network. *IEEE transactions on medical imaging*, 40(6):1591–1602, 2021.

[24] Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 1314–1324, 2019. 6, 7

[25] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7132–7141, 2018. 2

[26] Jiacheng Hu, Yanlin Xiang, Yang Lin, Junliang Du, Hanchao Zhang, and Houze Liu. Multi-scale transformer architecture for accurate medical image classification. In *Proceedings of the 2025 International Conference on Artificial Intelligence and Computational Intelligence*, pages 409–414, 2025. 2

[27] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4700–4708, 2017. 2, 6, 7

[28] Joana Palés Huix, Adithya Raju Ganeshan, Johan Fredin Haslum, Magnus Söderberg, Christos Matsoukas, and Kevin Smith. Are natural domain foundation models useful for medical image classification? In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 7634–7643, 2024. 2

[29] Tahir Hussain, Hayaru Shouno, Abid Hussain, Dostdar Hussain, Muhammad Ismail, Tatheer Hussain Mir, Fang Rong Hsu, Taukir Alam, and Shabnur Anonna Akhy. Effresnet-vit: A fusion-based convolutional and vision transformer model for explainable medical image classification. *IEEE Access*, 2025. 2

[30] Zeshan Hussain, Francisco Gimenez, Darvin Yi, and Daniel Rubin. Differential data augmentation techniques for medical imaging classification tasks. In *AMIA annual symposium proceedings*, page 979, 2018. 2

[31] Lie Ju, Xin Wang, Lin Wang, Dwarikanath Mahapatra, Xin Zhao, Quan Zhou, Tongliang Liu, and Zongyuan Ge. Improving medical images classification with label noise using dual-uncertainty estimation. *IEEE transactions on medical imaging*, 41(6):1533–1546, 2022. 2

[32] Jinfeng Li, Meiling Feng, and Chengyi Xia. Dbcvt: Double branch convolutional transformer for medical image classification. *Pattern Recognition Letters*, 186:250–257, 2024. 2

[33] Yanyu Li, Geng Yuan, Yang Wen, Ju Hu, Georgios Evangelidis, Sergey Tulyakov, Yanzhi Wang, and Jian Ren. Efficientformer: Vision transformers at mobilenet speed. *Advances in Neural Information Processing Systems*, 35: 12934–12949, 2022. 6, 7

[34] Yuexiang Li, Yawen Huang, Nanjun He, Kai Ma, and Yefeng Zheng. Improving vision transformer for medical image classification via token-wise perturbation. *Journal of Visual Communication and Image Representation*, 98:104022, 2024.

[35] Gongbo Liang, Yu Zhang, Xiaoqin Wang, and Nathan Jacobs. Improved trainable calibration method for neural networks on medical imaging classification. *arXiv preprint arXiv:2009.04057*, 2020. 2

[36] Shiwei Liu, Liejun Wang, and Wenwen Yue. An efficient medical image classification network based on multi-branch cnn, token grouping transformer and mixer mlp. *Applied Soft Computing*, 153:111323, 2024.

[37] Ningning Ma, Xiangyu Zhang, Hai-Tao Zheng, and Jian Sun. Shufflenet v2: Practical guidelines for efficient cnn architecture design. In *Proceedings of the European conference on computer vision (ECCV)*, pages 116–131, 2018. 6, 7

[38] Omid Nejati Manzari, Hamid Ahmadabadi, Hossein Kashiani, Shahriar B Shokouhi, and Ahmad Ayatollahi. Medvit: a robust vision transformer for generalized medical image classification. *Computers in biology and medicine*, 157: 106791, 2023. 2

[39] Sachin Mehta and Mohammad Rastegari. Mobilevit: lightweight, general-purpose, and mobile-friendly vision transformer. *arXiv preprint arXiv:2110.02178*, 2021. 2, 6, 7

[40] Gabriel Iluebe Okolo, Stamos Katsigiannis, and Naeem Ramzan. Ievit: An enhanced vision transformer architecture for chest x-ray image classification. *Computer Methods and Programs in Biomedicine*, 226:107141, 2022. 2

[41] Konstantin Pogorelov, Kristin Ranheim Randel, Carsten Griwodz, Sigrun Losada Eskeland, Thomas de Lange, Dag Johansen, Concetto Spampinato, Duc-Tien Dang-Nguyen, Mathias Lux, Peter Thelin Schmidt, et al. Kvasir: A multi-class image dataset for computer aided gastrointestinal disease detection. In *Proceedings of the 8th ACM on Multimedia Systems Conference*, pages 164–169, 2017. 2, 5, 6

[42] Maithra Raghu, Chiyuan Zhang, Jon Kleinberg, and Samy Bengio. Transfusion: Understanding transfer learning for medical imaging. *Advances in neural information processing systems*, 32, 2019. 2

[43] Sivaramakrishnan Rajaraman, Prasanth Ganesan, and Sameer Antani. Deep learning model calibration for improving performance in class-imbalanced medical image classification tasks. *PloS one*, 17(1):e0262838, 2022. 2

[44] Nagur Shareef Shaik, Teja Krishna Cherukuri, N Veeranjaneulu, and Jyostna Devi Bodapati. Medtransnet: advanced gating transformer network for medical image classification. *Machine Vision and Applications*, 35(4):73, 2024.

[45] Sourabh Shastri, Isha Kansal, Sachin Kumar, Kuljeet Singh, Renu Popli, and Vibhakar Mansotra. Cheximagenet: a novel architecture for accurate classification of covid-19 with chest x-ray digital images using deep convolutional neural networks. *Health and technology*, 12(1):193–204, 2022. 2, 5, 6

[46] Zeinab Sherkatghanad, Moloud Abdar, Mohammadreza Bakhtyari, Paweł Pławiak, and Vladimir Makarenkov. Baytta: Uncertainty-aware medical image classification with optimized test-time augmentation using bayesian model averaging. *Knowledge-Based Systems*, page 114123, 2025. 2

[47] Zar Nawab Khan Swati, Qinghua Zhao, Muhammad Kabir, Farman Ali, Zakir Ali, Saeed Ahmed, and Jianfeng Lu. Brain tumor classification for mr images using transfer learning and fine-tuning. *Computerized Medical Imaging and Graphics*, 75:34–46, 2019. 2

[48] Nima Tajbakhsh, Jae Y Shin, Suryakanth R Gurudu, R Todd Hurst, Christopher B Kendall, Michael B Gotway, and Jianming Liang. Convolutional neural networks for medical image analysis: Full training or fine tuning? *IEEE transactions on medical imaging*, 35(5):1299–1312, 2016.

[49] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pages 6105–6114. PMLR, 2019. 2, 6, 7

[50] Ilya O Tolstikhin, Neil Houlsby, Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Thomas Unterthiner, Jessica Yung, Andreas Steiner, Daniel Keysers, Jakob Uszkoreit, et al. Mlp-mixer: An all-mlp architecture for vision. *Advances in neural information processing systems*, 34:24261–24272, 2021. 6, 7

[51] Asher Trockman and J Zico Kolter. Patches are all you need? *arXiv preprint arXiv:2201.09792*, 2022. 6, 7

[52] Xiyue Wang, Sen Yang, Jun Zhang, Minghui Wang, Jing Zhang, Wei Yang, Junzhou Huang, and Xiao Han. Transformer-based unsupervised contrastive learning for histopathological image classification. *Medical image analysis*, 81:102559, 2022.

[53] Yang Wen, Bai Chen, Wuzhen Shi, Daquan Feng, Wenming Cao, and Song Wu. Mspfm: Multi-scale pyramid fusion mamba for medical image classification: Y. wen et al. *The Visual Computer*, pages 1–16, 2025. 2

[54] Xingao Wu and Gang Gou. Uncertainty bidirectional guidance of multi-task mamba network for medical image classification and segmentation. *Signal, Image and Video Processing*, 19(1):29, 2025.

[55] Xin Wu, Yue Feng, Hong Xu, Zhuosheng Lin, Tao Chen, Shengke Li, Shihan Qiu, Qichao Liu, Yuangang Ma, and Shuangsheng Zhang. Ctranscnn: Combining transformer and cnn in multilabel medical image classification. *Knowledge-Based Systems*, 281:111030, 2023. 2

[56] Saining Xie, Ross Girshick, Piotr Dollár, Zhuowen Tu, and Kaiming He. Aggregated residual transformations for deep neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1492–1500, 2017. 6, 7

[57] Yiting Xie and David Richmond. Pre-training on grayscale imagenet improves medical image classification. In *Proceedings of the European conference on computer vision (ECCV) workshops*, pages 0–0, 2018. 2

[58] Cheng Xue, Qi Dou, Xueying Shi, Hao Chen, and Pheng-Ann Heng. Robust learning at noisy labeled medical images: Applied to skin lesion classification. In *2019 IEEE 16th International symposium on biomedical imaging (ISBI 2019)*, pages 1280–1283. IEEE, 2019. 2

[59] Cheng Xue, Lequan Yu, Pengfei Chen, Qi Dou, and Pheng-Ann Heng. Robust medical image classification from noisy labeled data with global and local representation guided co-training. *IEEE transactions on medical imaging*, 41(6): 1371–1382, 2022. 2

[60] Yijun Yang, Huazhu Fu, Angelica I Aviles-Rivero, Carola-Bibiane Schönlieb, and Lei Zhu. Diffmic: Dual-guidance diffusion network for medical image classification. In *International conference on medical image computing and computer-assisted intervention*, pages 95–105. Springer, 2023.

[61] Weihao Yu, Pan Zhou, Shuicheng Yan, and Xinchao Wang. Inceptionnext: When inception meets convnext. In *Proceedings of the IEEE/cvf conference on computer vision and pattern recognition*, pages 5672–5683, 2024. 6, 7

[62] Yubiao Yue and Zhenzhang Li. Medmamba: Vision mamba for medical image classification. *arXiv preprint arXiv:2403.03849*, 2024.

[63] Lei Zhou, Huidong Liu, Joseph Bae, Junjun He, Dimitris Samaras, and Prateek Prasanna. Self pre-training with masked autoencoders for medical image classification and segmentation. In *2023 IEEE 20th international symposium on biomedical imaging (ISBI)*, pages 1–6. IEEE, 2023. 2

6. Supplementary Material

We present additional details of our work in the following sections:

Figures 6, 7, and 8 provide qualitative insights into the model's performance. Figure 6 shows the confusion matrix for one fold, illustrating that the classifier achieves high true positive rates across most classes with minimal misclassifications. Figure 7 presents the ROC-AUC curve for another fold, demonstrating strong discriminative capability between classes, with most curves approaching the ideal top-left corner. Figure 8 displays the precision-recall curves, highlighting that the model maintains high precision even at elevated recall levels, indicating reliable performance on imbalanced class distributions.

Figure 8. Precision-Recall curve using the Kvasir dataset.

input medical images that contribute to the classification decision. For instance, in skin lesion images, the attention maps emphasize irregular pigmentation areas that are clinically relevant. This confirms that our attention-enhanced Bayesian model aligns well with human expert reasoning.

Figure 6. Confusion matrix using the diabetic retinopathy dataset.

Figure 9. GradCAM visualization using the diabetic retinopathy dataset on the top row and skin cancer dataset on the bottom row.

Figure 7. ROC-AUC curve using the skin cancer dataset.

Attention Visualization: We visualize the attention maps generated using the GradCAM technique. These visualizations highlight the most discriminative regions in the

6.1. Failure Cases

Despite the overall strong performance of our proposed Bayesian Neural Network with channel and spiral attention, certain failure cases were observed during experiments. Understanding these failure modes is important for further improvement and clinical applicability.

1. Low-Quality or Noisy Images: Medical images with

low resolution, poor contrast, or significant noise often lead to misclassifications. For example, blurry retinal fundus images in the Diabetic Retinopathy dataset or poorly illuminated skin lesion images sometimes result in incorrect predictions. While the model indicates higher uncertainty in these cases, it still occasionally misclassifies the images, highlighting limitations in handling severely degraded inputs.

2. Rare or Ambiguous Classes: Classes with very few training samples, such as certain less frequent skin lesion categories, are more prone to misclassification. The model tends to be overconfident in some of these rare categories, even though Bayesian modeling partially mitigates this effect. This underscores the importance of balanced datasets for reliable uncertainty estimation.

3. Subtle or Small Lesions: In cases where pathological regions are extremely small or visually subtle, spiral attention may fail to fully capture the critical areas. For instance, small microaneurysms in retinal images or tiny early-stage skin lesions can be overlooked, leading to incorrect predictions. These failure cases often correlate with higher predictive entropy, signaling that uncertainty estimates are still informative.

4. Confounding Visual Features: Occasionally, non-pathological features, such as artifacts, markings, or anatomical variations, can be incorrectly attended to by the network. This can mislead both the attention modules and the classifier, resulting in errors. In such cases, uncertainty estimates tend to be moderate but not always sufficient to flag potential misclassifications.