Heart Failure Prediction: An Explainable Cross-Validated Comparison of Several Machine Learning Models

Md Sumon Ali[1*] and Towhidul Islam[2]

[1*]Information & Computer Science Department, King Fahd University of Petroleum and Minerals, Academic Belt Road, Dhahran, 31261, Dammam, Saudi Arabia.
[2]Information & Computer Science Department, King Fahd University of Petroleum and Minerals, Academic Belt Road, Dhahran, 31261, Dammam, Saudi Arabia.

*Corresponding author(s). E-mail(s): g202320610@kfupm.edu.sa;
Contributing authors: g202416880@kfupm.edu.sa;

Abstract

Heart disease is the leading cause of death worldwide, contributing to millions of fatalities each year. Early detection and accurate risk prediction are therefore critical for timely intervention and improved patient outcomes. In this study, seven different Machine Learning (ML) prediction models were tested on the collections of heart disease datasets. The data was divided, with 80% used to train the models and 20% saved to test them later. The settings for the models were carefully adjusted using a method that checks their performance multiple times to find the best ones. The models were then evaluated on the unseen test data. Their performance was measured using several metrics (Accuracy, Recall, Precision, PR-AUC and ROC-AUC), and their results were further examined using a confusion matrix. In addition to traditional evaluation metrics, SHapley Additive exPlanations (SHAP) analysis was employed to interpret the contribution of each feature to the model's predictions. It was observed that the Multi-Layer Perceptron (MLP) achieved the highest performance on both datasets, demonstrating strong predictive capability while remaining interpretable through the integration of SHAP. This study shows that modern ML models can be very good at predicting heart disease risk, and provide explainable performance. This study provides an effective approach for predicting heart disease risk with an explainable model to help doctors choose the best tool.

Keywords: Heart Failure Prediction, SHAP Explanations, Machine Learning, Hyperparameter Tuning, GridSearchCV.

1 Introduction

One of the most important organs in the human body is the heart. Its duties include pumping oxygenated blood via arteries to every other part of the body and receiving deoxygenated blood from the body through blood vessels, which also purify and transport metabolic waste. The term Cardiovascular Disease (CVD) is generally referred to as the condition affecting the heart or blood vessels[1]. The world health organization estimates that 17.9 million people worldwide are at risk of dying from CVDs, which are the leading cause of death worldwide[2]. Early detection and treatment of heart disease are getting more challenging due to population growth. The goal is to build Machine Learning (ML) algorithms than can predict the likelihood of heart disease based on various health metrics and features [3–6]. With application in a variety industries, including healthcare, ML is one of the branches of Artificial Intelligence (AI) that is expanding fastest. Because ML is an intelligent tool for analyzing data, and the medical profession is abundant with data, it offers a lot of value in the healthcare field [7].

A healthy heart is conducive to a healthy life. The majority of people experience stress, anxiety, depression, and a variety of other illnesses as a result of their hectic lifestyles. These major factors are causing people to become ill and experience severe illnesses[8]. In the modern world, CVD is becoming a bigger concern. Sudden arrest of Aldous can lead to serious illness such as brain damage, nervous system disorder and even death. Because of this, heart failure condition can be identified early rather than later [9]. Current strategies for predicting risk are only modestly successful, likely because they are derived from traditional statistical analysis methods that fail to capture prognostic information in large datasets containing multi-dimensional interactions [10]. Furthermore, most existing approaches lack an explainable framework, which limits their interpretability and clinical trust [11, 12]. However, they can be insufficient due to their limited ability to handle complex patterns in data, often resulting in lower accuracy or generalizability [13].

By applying and analyzing a range of modern ML algorithms across multiple datasets, including Random Forest (RF), Logistic Regression (LR), Support Vector Classifier (SVC), k-Nearest Neighbors (KNN), Decision Tree (DT), XGBoost, and Multilayer Perceptron (MLP), and by fine tuning their hyperparameters using techniques such as cross-validation and grid search to ensure reliable performance, this research aims to enhance predictive models for heart disease risk. In addition, SHapley Additive exPlanations (SHAP) is employed to interpret the contribution of each feature to the model's predictions, providing transparency and clinical insight. The novel aspects of this work include improving computational efficiency, increasing forecast accuracy, and incorporating explainable predictions to support trustworthy clinical decision-making.

The main contributions of this work can be summarized as follows:

- Development and evaluation of multiple modern ML models, including RF, LR, SVC, KNN, DT, XGBoost, and MLP, for predicting heart disease risk across multiple datasets with fine-tuned hyperparameters using cross-validation and grid search.
- Integration of SHAP to provide interpretable and transparent predictions, allowing identification of the most influential features and enhancing clinical trust in the models.
- Proposal of a robust and computationally efficient predictive framework that improves forecast accuracy while addressing limitations of traditional statistical models, such as handling complex patterns and multi-dimensional interactions in medical data.

The rest of the paper is organized as: section 2 describes the related work and section 3 outlines the methodology, while section 4 describes the results, which are discussed in section 5, finally, section 6 concludes the paper and puts forward some future directions.

2 Literature Review

In recent years, the application of ML algorithms in medical research has gained significant attention. Advances in medical science have been largely driven by the proliferation of information and communication technologies [14]. The large-scale collection of medical data enabled by smart healthcare technologies has facilitated the development of numerous ML and Deep Learning (DL) techniques for improved diagnostic and prognostic outcomes [15].

Cardiovascular diseases remain a major health concern, with modern lifestyle factors, such as increased exposure to dietary pesticides and sedentary behavior, contributing to a rising risk of heart failure [16]. Many studies have employed ML algorithms including SVC, RF, DT, XGBoost, KNN, and Neural Networks (NN) to improve the accuracy of heart disease prediction (Table 1). These approaches have demonstrated enhanced predictive performance. However, several limitations persist. Most studies rely on a single dataset, suffer from demographic biases, and face scalability challenges, indicating a need for more generalized and robust predictive models.

Another important limitation of prior work is the lack of explainable frameworks. Although these models achieve high predictive accuracy, they often operate as "black boxes", offering little insight into the contribution of individual features to predictions. The use of SHAP can address this limitation by providing both global and local interpretability of model predictions [11, 12, 17]. Despite its potential, very few studies have applied SHAP to understand feature importance and enhance transparency in heart failure risk prediction, highlighting an opportunity for integrating explainable ML in clinical decision support.

In this research, two distinct datasets are used to address these limitations. This research also apply a uniform ML model to improve the robustness and generalizability of the findings. This method aims to solve the previous challenges by leveraging

Table 1 Overview of Machine Learning Approaches, Evaluation Metrics, and Datasets for Heart Disease Diagnosis

Year	ML Techniques	Evaluation Measures	Data Sets	Limitation
2024[18]	RF, LR, Naïve Bayes, SVM, DT, KNN, XGBoost, NN	Accuracy	Heart disease dataset	The study's performance heavily depends on the dataset's size and quality also lack of explainability.
2022[19]	LR, KNN, DT, XGBoost (Ensemble classifier)	Accuracy, TP Rate, FP Rate, Precision, ROC Curve, Kappa Statistics	Cardiovascular dataset	The study suggests that scalability and accuracy could be further improved.
2024[20]	Naïve Bayes Classifier	GPS, AUC of the ROC	Spanish Delta@ database	The model does not account for individual health conditions or personal habits of workers.
2023[5]	LR, KNN, SVM, RF, Gradient Boosting	ROC_AUC, Precision, Recall, Accuracy	UCI Heart Disease Dataset	The paper's limitation lies in its reliance on traditional ML models.
2020[10]	Boosted Decision Tree (BDT)	AUC, ROC, C-statistic	UCSD, UCSF, BIOSTAT-CHF cohorts	The model was derived from a single center, which may introduce demographic selection bias.
2019[21]	Hybrid RF with Linear Model (HRFLM)	Accuracy, Precision, F-measure, Sensitivity, Specificity	Cleveland heart disease dataset	The study is limited by using a single dataset.
2021[22]	KNN, DT, RF, LR, AdaboostM1, MLP	Accuracy, Sensitivity, Specificity, Kappa, MCC, F-Measure	Heart disease dataset	The study acknowledges that the dataset size was not large enough.

different datasets to enhance predictive accuracy and mitigate model biases, thus contributing to more reliable frameworks for heart disease prediction.

3 Methodology

Fig. 1 Proposed method for heart failure prediction.

3.1 Dataset Analysis

For every dataset, at first we need to process the data which is shown is Fig. 1. The dataset preprocessing steps were performed to prepare the data for training the model and evaluation.

3.1.1 Dataset 1: Heart Failure Prediction Dataset

With an estimated 17.9 million fatalities annually, or 31% of all deaths worldwide, CVDs are the leading cause of mortality worldwide. This dataset features 12(Age, Sex, ChestPainType, RestingBP, Cholesterol, FastingBS, RestingECG, MaxHR, ExceriseAngina, Oldpeak, STSlope and HeartDiease) variables that can be used to predict a potential heart illness.The output label of this dataset is HeartDisease. There are 5 categorical, 5 Numerical and 2 Binary feature in the dataset. The dataset contains 55.3% (HeartDiease=1) and 44.7% (HeartDiease=0), which looks somehow balanced. Based on the domain knowledge, features such as ChestPainType, ExerciseAngina, and Oldpeak have strong predictors of heart disease. The dataset apply on the automated feature engineering techniques, but it lacks manual feature engineering derived from domain expertise. This dataset is collected from Kaggle[23].

Fig. 2 Correlation matrix of Dataset 1.

There are multiple steps involved to prepare the Heart Failure Prediction Dataset. At first, numerical and categorical features are isolated. Numerical features that contain zero values are replaced by using median imputation grouped by specific columns. Negative values are set to NaN, then filled with median values using an imputer. Categorical features were converted to numerical via one-hot encoded[24]. Then the datasets were split into train and test (80-20) ratio, followed by feature scaling through standard scalar. Fig. 2 shows the correlation matrix for Heart Failure Prediction Dataset. This heat map matrix is useful for identifying strong correlations. This relation indicates redundant information or interactions. Accuracy, Recall, ROC-AUC, and PR-AUC are the metrics to evaluate the datasets. Pandas, StandardScalar, and Matplotlib are the frameworks used for this datasets.

3.1.2 Dataset 2: Heart Attack Analysis and Prediction Dataset

This dataset was collected from kaggle[25]. This dataset has 14 (age, sex, chest pain type, resting blood pressure, cholesterol, fasting blood sugar, resting electrocardiogram, maximum heart rate, exercise induced angina, oldpeak, slope of the peak exercise ST segment, number of major vessels, thalassemia, and output) features. There are 5 numerical features, 4 categorical (binary) features, and 5 categorical (non-binary) feature in the dataset. One hot enconding technique converts categorical to numerical

value. Chest pain type, thalachh, oldpeak, and caa are the expected important features of the datasets. The output label is output, which is 0 and 1. The dataset is not significantly imbalanced where output=1 is 54.46% and output=0 is 45.54%.

Fig. 3 Heat map for Heart Attack Analysis and Prediction Dataset 2.

This dataset calculated the Interquartile Range (IQR) for each column to define outlier boundaries[26]. Then a correlation matrix is computed, helping to understand the relationships between variables, which is shown in Fig. 3. The dataset is split into an 80-20 ratio. Standard scaling is applied to ensure that all features are on a similar scale[27]. Accuracy, Recall, ROC-AUC, and PR-AUC are the metrics to evaluate the datasets. Pandas, StandardScalar, and Matplotlib are the frameworks used for this datasets.

3.2 Model Selection

A diverse pool of ML modes was selected to investigate their performance using different datasets which is shwon in Fig 4. The datasets were split using train-test-split with an 80-20 split ratio. The model selection process involved using Stratified K-Fold Cross-Validation with 5 splits. This method ensures the robustness of the methodology.

Fig. 4 Machine Learning Algorithms Pool.

3.2.1 Hyperparameter Tuning

To find out the optimal model performance, hyperparameter tuning was conducted using GridSearchCV[28]. In this case, we consider a 5-fold cross-validation strategy for each model in the pool. Different types of hyperparameters were tuned for each model, including:

Logistic Regression (LR):

Penalties l1(lasso), l2(Ridge), Elastic, and none were applied to the logistic regression to prevent overfitting. Logistic regression also used solvers (lbfgs, liblinear, saga) to optimize the model which is shown in Table 2. In the case of logistic regression, the total hyperparameter combination is 480.

Table 2 Hyperparameters and their values for LR.

Hyperparameter	Hyperparameter Values
penalty	l1; l2; elasticnet; none
C	0.01; 2.5075; 5.005; 7.5025; 10
max_iter	100; 200; 300; 500
solver	lbfgs; liblinear; saga

K-Nearest Neighbors (KNN):

To find out the best performance of the KNN model, a hyperparameter tuning process was introduced with a grid search technique. The number of neighbors defined in the case of KNN was 3, 5, 7, 10, and 15. Two weight parameters (uniform, distance) control the weight assignment to neighbors when making predictions. The algorithm parameter (auto, ball tree, kd tree, and brute) specifies the algorithm used to compute the nearest neighbors. Finally, leaf size (10, 20, 30, 40, 50) affects the speed of the Ball Tree and KD Tree algorithms, particularly during the search phase which is shown in Table 3. KNN contains a 400 hyperparameters combination.

Table 3 Hyperparameters and their values for KNN model.

Hyperparameter	Hyperparameter Values
n_neighbors	3; 5; 7; 10; 15
weights	uniform; distance
algorithm	auto; ball_tree; kd_tree; brute
leaf_size	10; 20; 30; 40; 50

Decision Tree Classifier (DT):

The hyperparameters criterion determines the function used to measure the quality of a split. In Criterion two options were considered. The Gini impurity metric used to evaluate splits and entropy employs the information gain[29]. The maximum depth parameter limits the depth of the decision tree. The values explored ranged from 10 to 50 in increments of 10, with the additional option None to allow unrestricted tree depth which is shown in Table 4. DT contains a combination 216 hyperparameters.

Table 4 Hyperparameters and their values for DT model.

Hyperparameter	Hyperparameter Values
criterion	gini; entropy
max_depth	10; 20; 30; 40; 50; None
min_samples_split	2; 5; 10
min_samples_leaf	1; 2; 4

Random Forest Classifier (RF):

The number of estimators in RF defines the number of decision trees. Values ranging from 50 to 200 were used in increments of approximately 50. Maximum depth controls the depth of each individual decision tree. The maximum depth values explored ranged from 10 to 50, with increments of 10. Minimum sample split specifies the minimum number of samples required to split an internal node, and minimum sample per leaf defines the number of samples required to form a leaf node which is shown in Table 5. RF contains a combination of 432 hyperparameters.

Table 5 Hyperparameters and their values for RF model.

Hyperparameter	Hyperparameter Values
n_estimators	50; 100; 150; 200
max_depth	10; 20; 30; 40; 50; None
min_samples_split	2; 5; 10
min_samples_leaf	1; 2; 4

Support Vector Classifier (SVC):

In case of SVC, the kernel function defines how the data is transformed before classification. Four types of kernels were tested: linear, poly, rbf, and sigmoid. The regularization parameter was tested to control the trade-off between maximizing the margin and minimizing classification errors. The kernel coefficient (gamma) determines the influence of individual training samples on the decision boundary which is shown in Table 6. SVC contains 240 hyperparameters combination.

Table 6 Hyperparameters and their values for SVC model

Hyperparameter	Hyperparameter Values
kernel	linear; poly; rbf; sigmoid
C	0.01; 2.5075; 5.005; 7.5025; 10
gamma	scale; auto
degree	2; 3; 4

Extreme Gradient Boosting Classifier (XGBoost):

The gradient boosting approach, which is linked to the decision tree technique, has been used in a variety of fields recently. In many regression and classification situations, XGBoost works better when paired with other techniques [30]. The latest version of the gradient boost technique is called XGBOOST (Extreme Gradient Boosting)[31]. Number of estimators (50-200), maximum depth (3,5,7), learning rate (0.01, 0.2, 3), subsample (0.8, 0.9, 1.0), and column subsample (0.8, 0.9, 1.0) are the hyperparameters in XGBoost model. By conducting a comprehensive grid search over the hyperparameters, the optimal combination was identified to maximize the predictive performance of the XGBoostd model which is shown in Table 7. XGBoosts contains 648 hyperparameters combination.

Table 7 Hyperparameters and their values for XGBoost model.

Hyperparameter	Hyperparameter Values
n_estimators	50; 100; 150; 200
max_depth	3; 5; 7
learning_rate	0.01; 0.105; 0.2
subsample	0.8; 0.9; 1.0
colsample_bytree	0.8; 0.9; 1.0

Multi-layer Perceptron Classifier (MLP):

The MLP is a well-known Artificial Neural Network (ANN). This robust modeling tool uses data samples with known outcomes to apply a supervised training process[32]. In this study, we show that a computational model based on a multilayer perceptron network with three layers—one single hidden layer, and two hidden layer—can be used to construct such a complicated system to enable the detection of cardiac disease. Relu and tanh activation functions are used to introduce non-linearity into the model which is shown in Table 8. To solve, Adam and SGD were used for weight updates during training. MLP contains a combination of 240 hyperparameters.

Table 8 Hyperparameters and their values for MLP model.

Hyperparameter	Hyperparameter Values
hidden_layer_sizes	(50,); (100,); (50, 50)
activation	relu; tanh
solver	adam; sgd
alpha	0.0001; 0.002575; 0.00505; 0.007525; 0.01
learning_rate	constant; adaptive

Combination of seven ML model framework was established, each optimized through an extensive grid search for hyperparameter tuning. For each model, a combination of core hyperparamters was tested, resulting in a total of 2656 hyperparamter configurations across all models. The search space was extended to include polynomial feature transformations (degrees 1 and 2) to find out non-linear relationships in the datasets. For each dataset, GridSearchCV was used to select the best hyperparameters based on cross-validated accuracy. This approach facilitated a comprehensive search over parameter spaces to identify the most suitable configuration.

To understand the contribution of individual features to model predictions and enhance clinical trust, SHapley Additive exPlanations (SHAP) [11, 12] was applied to each optimized model. SHAP provides a unified framework for quantifying feature importance at both the global and local levels which is shown in Fig. 6, and Fig. 8. This analysis allows identification of the most influential clinical factors for heart disease prediction and ensures that the model's decisions are interpretable and clinically meaningful.

4 Analyze the Results and Find the Best Hyperparameters

Each model's performance was evaluated using multiple metrics to ensure robustness of the research. The proportion of correctly classified samples was identified by Accuracy. Recall is the ability of the model to identify positive instances correctly. ROC-AUC measured the trade-off between the true positive rate and false positive rate. Finally, the PR-AUC focuses on the precision-recall trade-off, which is especially relevant in imbalance datasets. These metrics were calculated for each fold in the 5-fold cross-validation, and the average performance across fold was reported.

Table 9 Cross-validation performance (AUC) of different models across five folds for Dataset 1.

Model	Fold 0	Fold 1	Fold 2	Fold 3	Fold 4
LR	0.903	0.912	0.931	0.911	0.947
KNN	0.915	0.868	0.866	0.863	0.889
DT	0.899	0.736	0.758	0.789	0.762
RF	0.899	0.888	0.910	0.911	0.916
SVC	0.904	0.912	0.918	0.899	0.947
XGB	0.915	0.888	0.938	0.911	0.934
MLP	0.916	0.920	0.914	0.923	0.945

Dataset 1:

Aggregate the cross-validation results (Table 9) by calculating the mean scores for each model, then rank the models based on the PR-AUC metric which is shown in Table 10. Then, select the model with the highest score on the PR-AUC. Finally, found the hyperparameter for the best-performing model.

Table 10 Ranking of models based on mean Precision-Recall AUC across five-fold cross-validation for Dataset 1.

Rank	Model	Mean PR AUC
1	MLP	0.924
2	LR	0.921
3	XGB	0.917
4	SVC	0.916
5	RF	0.905
6	KNN	0.880
7	DT	0.789

The best parameters for the best model are: `mlp_activation: relu`, `mlp_alpha: 0.0001`, `mlp_hidden_layer_sizes: (50, 50)`, `mlp_learning_rate: constant`, `mlp_solver: sgd`, `poly_degree: 1`.

Dataset 2:

Aggregate the cross-validation results (Table 11) by calculating the mean scores for each model, then rank the models based on the PR-AUC metric which is shown in Table 12. Then, select the model with the highest score on the PR-AUC. Finally, found the hyperparameters for the best-performing model.

Table 11 Precision–Recall AUC values for each model across five-fold cross-validation for Dataset 2.

Model	Fold 0	Fold 1	Fold 2	Fold 3	Fold 4
LR	0.947	0.859	0.926	0.894	0.910
KNN	0.900	0.799	0.821	0.894	0.879
DT	0.852	0.778	0.749	0.898	0.763
RF	0.885	0.862	0.924	0.900	0.868
SVC	0.941	0.899	0.924	0.924	0.868
XGB	0.918	0.888	0.924	0.912	0.863
MLP	0.931	0.888	0.942	0.910	0.910

The best parameters for the best model are: `mlp__activation`: 'relu', `mlp__alpha`: 0.0001, `mlp__hidden_layer_sizes`: (50,), `mlp__learning_rate`: 'constant', `mlp__solver`: 'sgd', `poly__degree`: 1.

4.1 Final Evaluation Using Best hyperparameters

This is the final test for the best hyperparameters. From the full dataset, we created an 80/20 split. The 80% portion was used for training and to fit the scaler, that fitted scaler was then applied to the remaining 20%, which was held out (never used during model development) and used only for final testing.

Table 12 Ranking of models based on mean Precision–Recall AUC across five-fold cross-validation for Dataset 2.

Rank	Model	Mean PR AUC
1	MLP	0.916
2	SVC	0.911
3	LR	0.907
4	XGB	0.901
5	RF	0.888
6	KNN	0.859
7	DT	0.808

Table 13 Best Model Performance Across Datasets

Dataset	Best Model	Accuracy	Recall	Precision	ROC AUC	PR AUC
Dataset 1	MLP	0.864	0.859	0.903	0.865	0.957
Dataset 2	MLP	0.836	0.812	0.864	0.837	0.906

4.2 Analyze the test Result

The performance of all datasets is shown in Table 13. In case of Dataset 1 the overall model performance is strong and acceptable. The model achieved accuracy of 86.41%, which indicating a high overall correctness in predictions. The model is performing quite well in Dataset 2 and acceptable. The accuracy of 83.61% indicate that model is generally effective at predicting heart disease.

Fig. 5 Confusion Matrices for Datasets 1 and Dataset 2.

The confusion matrix for all datasets is shown in Fig. 5. For Dataset 1, the model achieves a relatively high number of True Positive (92) and True Negatives (67) but

also produces 15 False Negatives and 10 False Positive. This results provide a good balance between sensitivity and specificity. For Datasets 2 False Positives (4) and False Negatives (6) which indicating that the model is more conservative. The model is avoiding Type I errors.

4.3 Model Interpretability Using SHAP

To interpret the predictions of the best-performing models and understand feature contributions, SHAP was applied. SHAP provides both global and local interpretability:

- **Global interpretation:** Identifies which features contribute most on average to model predictions across the dataset, using mean absolute SHAP values. The global feature importance and SHAP value distribution for Dataset 1 and Dataset 2 are shown in Fig. 6 and Fig. 8, respectively.
- **Local interpretation:** Examines individual predictions to show how each feature pushes the prediction towards higher or lower risk. SHAP force plots for sample 0 in Dataset 1 and Dataset 2 are shown in Fig. 7 and Fig. 9, respectively.

These SHAP analyses provide insight into the most influential clinical features for heart failure prediction, enhancing model transparency and supporting interpretable clinical decision-making.

5 Discussion

The results demonstrated that model performance was strongly influenced by the characteristics of the data. The highest scores were achieved by the MLP model on the first two datasets which is shown in Table 13. For Dataset 1, an accuracy of 0.864 was recorded, along with a recall of 0.859, a precision of 0.903, an ROC-AUC of 0.865, and a PR-AUC of 0.957. Similarly, for Dataset 2, scores of 0.836 (accuracy), 0.812 (recall), 0.864 (precision), 0.837 (ROC-AUC), and 0.906 (PR-AUC) were obtained.

The model's performance was further validated by its confusion matrices which is shown in Fig. 5. For Dataset 1, a high number of correct predictions was demonstrated, with 92 true positives (TP) and 67 true negatives (TN) being identified. Comparatively few errors were made, with only 15 false negatives (FN) and 10 false positives (FP) being recorded. A similar trend was shown in Dataset 2, where the error profile suggested a conservative model: a very low number of false alarms was produced (FP = 4), while the number of missed positive cases was also kept low (FN = 6).

Furthermore, the SHAP analysis provided critical insights into the feature importance patterns across different datasets. For Dataset 1, the global feature importance plot (Fig. 6) revealed that clinical indicators such as *ST_Slope* and *ExerciseAngina* were the most influential predictors, suggesting strong physiological signals in well balanced data. In contrast, the analysis for Dataset 2 (Fig. 8) showed a more distributed feature importance pattern, with factors like *Coronary artery aneurysm (CAA)* and *Constrictive pericarditis (CP)* gaining relative prominence, potentially indicating that the model relied on different feature combinations when faced with varying data characteristics. The SHAP force plot for Dataset 2 (Fig. 9) further demonstrated how these

Fig. 6 Global Feature Importance and SHAP Value Distribution for Dataset 1.

Fig. 7 SHAP Force Plot for Sample 0 in Dataset 1.

features interact at the individual prediction level, revealing the additive contributions that drive specific clinical outcomes. This variation in feature importance across datasets underscores the context-dependent nature of predictive models and highlights the need for dataset-specific interpretability analysis to ensure clinically meaningful explanations.

Furthermore, the findings of this study have significant implications for hospital mortality prediction. By systematically evaluating multiple ML models using cross-validated approaches, we show that model performance is highly influenced by the characteristics and balance of the underlying data. This highlights the necessity of comparative benchmarking across diverse models, rather than relying on a single algorithm, to identify the most reliable predictor in a specific clinical context. In hospital mortality prediction, where false negatives carry substantial risk, cross-validated comparisons provide a robust framework for selecting models that optimize both sensitivity and generalizability. Consequently, the methodology presented here in can serve as a foundation for developing clinically deployable decision-support tools, enabling improved patient stratification, early risk detection, and targeted interventions in critical care settings.

Fig. 8 Global Feature Importance and SHAP Value Distribution for Dataset 2.

Fig. 9 SHAP Force Plot for Sample 0 in Dataset 2.

6 Conclusion

This study systematically evaluated multiple ML models across two datasets to predict heart failure, highlighting both their potential and limitations. The results demonstrated that model performance is highly dependent on the characteristics and balance of the underlying data. The MLP model achieved the highest performance on Dataset 1 and Dataset 2. Importantly, the incorporation of SHapley Additive exPlanations (SHAP) provided critical interpretability, revealing the context dependent nature of feature importance. For instance, clinical indicators such as *ST_Slope* and *ExerciseAngina* were most influential in Dataset 1, whereas *Coronary artery aneurysm (CAA)* and *Constrictive pericarditis (CP)* gained prominence in Dataset 2. This underscores the need for dataset-specific interpretability analyses to provide clinically meaningful insights. Overall, the findings suggest that while ML models can achieve strong predictive performance in well-balanced datasets, challenges remain in handling unbalanced data and ensuring robust generalization. Future work should focus on improving recall to minimize false negatives in critical healthcare applications, through strategies such as class rebalancing, advanced feature engineering, and hyperparameter optimization.

Declarations

Ethics approval: Not applicable (this study used publicly available, de-identified datasets with no human subject interaction).

Consent for participation and publication: Not applicable.

Availability of data and materials: The datasets analyzed during this study are publicly available on Kaggle: (1) Fedesoriano: *Heart Failure Prediction Dataset* (2021), DOI: 10.34740/KAGGLE/DS/2162210; and (2) Rashikrahmanpritom: *Heart Attack Analysis and Prediction Dataset* (2021), DOI: 10.34740/KAGGLE/DS/678821. Both datasets are open-access and available to the public through the Kaggle platform.

Code availability: No custom code was developed or released as part of this study. The analysis was conducted using standard open-source Python libraries (e.g., `pandas`, `scikit-learn`, `xgboost`).

Competing interests: The authors declare no competing interests. None of the authors is a member of the Editorial Board of this journal.

Funding: This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Authors' contributions: MSA: Conceptualization, methodology, model implementation, manuscript drafting. TI: Data preprocessing, statistical analysis, manuscript review and editing. Both authors read and approved the final manuscript.

Acknowledgments: The authors thank the Information & Computer Science Department, King Fahd University of Petroleum and Minerals (KFUPM), for academic support.

Clinical Trial Registration: Not applicable.

Permissions: All figures and tables are original to this work. No copyrighted or previously published materials were reused.

References

[1] Topol, E.J., Califf, R.M.: Textbook of Cardiovascular Medicine. Lippincott Williams & Wilkins, Philadelphia, PA (2007)

[2] Pandey, S., Kaur, R.: Heart failure prediction using machine learning algorithm. In: Proceedings of the 3rd International Conference on Computation, Automation and Knowledge Management (ICCAKM), pp. 1–5. IEEE, Piscataway, NJ (2022)

[3] Princy, R.J.P., Parthasarathy, S., Jose, P.S.H., Lakshminarayanan, A.R., Jeganathan, S.: Prediction of cardiac disease using supervised machine learning algorithms. In: Proceedings of the 4th International Conference on Intelligent Computing and Control Systems (ICICCS), pp. 570–575. IEEE, Piscataway, NJ (2020)

[4] Arumugam, K., Naved, M., Shinde, P.P., Leiva-Chauca, O., Huaman-Osorio, A., Gonzales-Yanac, T.: Multiple disease prediction using machine learning algorithms. Materials Today: Proceedings **80**, 3682–3685 (2023)

[5] Gandla, V.R., Mallela, D.V., Chaurasiya, R.: Heart failure prediction using machine learning. In: AIP Conference Proceedings, vol. 2705. AIP Publishing, Melville, NY (2023)

[6] Kumar, N.K., Sindhu, G.S., Prashanthi, D.K., Sulthana, A.S.: Analysis and prediction of cardiovascular disease using machine learning classifiers. In: Proceedings of the 6th International Conference on Advanced Computing and Communication Systems (ICACCS), pp. 15–21. IEEE, Piscataway, NJ (2020)

[7] Javaid, M., Haleem, A., Singh, R.P., Suman, R., Rab, S.: Significance of machine learning in healthcare: Features, pillars and applications. International Journal of Intelligent Networks **3**, 58–73 (2022) https://doi.org/10.1016/j.ijin.2022.05.002

[8] Kim, J.O., Jeong, Y.-S., Kim, J.H., Lee, J.-W., Park, D., Kim, H.-S.: Machine learning-based cardiovascular disease prediction model: A cohort study on the korean national health insurance service health screening database. Diagnostics **11**(6), 943 (2021)

[9] Vora, D., Mishra, S., Mukherjee, A., Tiwari, S., Thakur, S., Biswas, S.: Heart failure prediction with ensembled learning. In: Proceedings of the IEEE Pune Section International Conference (PuneCon), pp. 1–5. IEEE, Piscataway, NJ (2022)

[10] Adler, E.D., Voors, A.A., Klein, L., Macheret, F., Braun, O.O., Urey, M.A., Zhu, W., Sama, I., Tadel, M., Campagnari, C., *et al.*: Improving risk prediction in heart failure using machine learning. European Journal of Heart Failure **22**(1), 139–147 (2020)

[11] Lundberg, S.M., Lee, S.-I.: A unified approach to interpreting model predictions. In: Advances in Neural Information Processing Systems (NeurIPS) (2017)

[12] Molnar, C.: Interpretable Machine Learning. Lulu.com, ??? (2020)

[13] Wang, S., al.: Out-of-distribution generalization in machine learning: A survey. arXiv preprint arXiv:2108.13624 (2021)

[14] Almazroi, A.A.: Survival prediction among heart patients using machine learning techniques. Mathematical Biosciences and Engineering **19**(1), 134–145 (2022)

[15] Katarya, R., Srinivas, P.: Predicting heart disease at early stages using machine learning: A survey. In: Proceedings of the International Conference on Electronics and Sustainable Communication Systems (ICESC), pp. 302–305. IEEE, Piscataway, NJ (2020)

[16] Haq, A.U., Li, J.P., Memon, M.H., Nazir, S., Sun, R.: A hybrid intelligent system framework for the prediction of heart disease using machine learning algorithms. Mobile Information Systems **2018**(1), 3860146 (2018)

[17] Samuel, J., al.: Explainable machine learning for cardiovascular disease risk prediction: A shap approach. Journal of Biomedical Informatics **120**, 103865 (2021)

[18] Stonier, A.A., Gorantla, R.K., Manoj, K.: Cardiac disease risk prediction using machine learning algorithms. Healthcare Technology Letters **11**(4), 213–217 (2024)

[19] Chinnasamy, P., Kumar, S.A., Navya, V., Priya, K.L., Boddu, S.S.: Machine learning based cardiovascular disease prediction. Materials Today: Proceedings **64**, 459–463 (2022)

[20] Sánchez-Lite, A., Fuentes-Bargues, J.L., Iglesias, I., González-Gaya, C.: Proposal of a workplace classification model for heart attack accidents from the field of occupational safety and health engineering. Heliyon **10**(18) (2024)

[21] Mohan, S., Thirumalai, C., Srivastava, G.: Effective heart disease prediction using hybrid machine learning techniques. IEEE Access **7**, 81542–81554 (2019)

[22] Ali, M.M., Paul, B.K., Ahmed, K., Bui, F.M., Quinn, J.M.W., Moni, M.A.: Heart disease prediction using supervised machine learning algorithms: Performance analysis and comparison. Computers in Biology and Medicine **136**, 104672 (2021)

[23] Fedesoriano: Heart Failure Prediction Dataset. Kaggle. Accessed 23 Nov 2024 (2021). https://doi.org/10.34740/KAGGLE/DS/2162210

[24] Seger, C.: An Investigation of Categorical Variable Encoding Techniques in Machine Learning: Binary versus One-hot and Feature Hashing. https://arxiv.org/abs/1811.10046. Preprint (2018)

[25] Rashikrahmanpritom: Heart Attack Analysis and Prediction Dataset. Kaggle. Accessed 23 Nov 2024 (2021). https://doi.org/10.34740/KAGGLE/DS/678821

[26] Frery, A.C.: Interquartile range. In: Encyclopedia of Mathematical Geosciences, pp. 664–666. Springer, Cham (2023)

[27] Villar, S., Hogg, D.W., Storey-Fisher, K., Yao, W., Blum-Smith, B.: Scalars are universal: Equivariant machine learning, structured like classical physics.

Advances in Neural Information Processing Systems **34**, 28848–28863 (2021)

[28] Ahmad, G.N., Fatima, H., Ullah, S., Saidi, A.S., *et al.*: Efficient medical diagnosis of human heart diseases using machine learning techniques with and without gridsearchcv. IEEE Access **10**, 80151–80173 (2022)

[29] Mathan, K., Kumar, P.M., Panchatcharam, P., Manogaran, G., Varadharajan, R.: A novel gini index decision tree data mining method with neural network classifiers for prediction of heart disease. Design Automation for Embedded Systems **22**, 225–242 (2018)

[30] Friedman, J.H.: Greedy function approximation: A gradient boosting machine. Annals of Statistics, 1189–1232 (2001)

[31] Chen, T., Guestrin, C.: Xgboost: A scalable tree boosting system. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 785–794. ACM, New York, NY (2016)

[32] Taud, H., Mas, J.-F.: Multilayer perceptron (mlp). In: Geomatic Approaches for Modeling Land Change Scenarios, pp. 451–455. Springer, Cham (2018)