# A Multicancer AI Framework for Comprehensive Cancer Surveillance from Pathology Reports

Nan-Haw Chow, M.D., Ph.D.[1+], Han Chang, M.D., Ph.D.[2,3+], Hung-Kai Chen[2], Chen-Yuan Lin, B.S.[4], Ying-Lung Liu, B.S.[5], Po-Yen Tseng[2], Li-Ju Shiu, Ph.D.[6], Yen-Wei Chu, Ph.D.[7], Pau-Choo Chung, Ph.D.[8], Kai-Po Chang, M.D., Ph.D.[2,3]*

[1] Center for Precision Medicine, China Medical University Hospital, Taichung, Taiwan

[2] School of Medicine, China Medical University, Taichung, Taiwan

[3] Department of Pathology, China Medical University Hospital, Taichung, Taiwan

[4] Signal1, Toronto, Canada

[5] Department of Computer Science and Information Engineering, National Taiwan University of Science and Technology, Taipei, Taiwan

[6] Department of Foreign Languages and Literature, National Chi Nan University, Nantou, Taiwan

[7] Graduate Institute of Genomics and Bioinformatics, National Chung Hsing University, Taichung, Taiwan

[8] Department of Electrical Engineering, National Cheng Kung University, Tainan, Taiwan

[+] These authors contributed equally to this work

**\* Corresponding Author:**

Kai-Po Chang

017179@tool.caaumed.org.tw

+886-4-2205-2121 #12678

2 Yude Rd., Taichung, Taiwan

## Abstract

Cancer registries are essential infrastructures for population-level surveillance, yet existing AI efforts remain constrained by narrow tasks and proprietary dependence. We present a model-agnostic, privacy-first framework that transforms cancer registration into a scalable and globally accessible process. Running entirely on local, low-cost hardware, the system performs end-to-end abstraction of unstructured pathology reports, integrating multi-step reasoning with a DSPy-based prompting engine co-designed with pathologists. In validation across ten cancer types, it achieved 96.6% triage accuracy and 93.9% mean extraction accuracy across 193 CAP-aligned fields, in addition to capturing complex variable-length data for surgical margins, lymph nodes, and breast biomarkers with high fidelity. This framework resolves the clinical AI "implementation trilemma"—balancing comprehensive scope, strict privacy, and computational feasibility. By restoring data completeness on accessible workstation GPUs, we provide a democratized blueprint for unbiased surveillance that unlocks the rich diagnostic granularity of pathology reports for real-time public health action.

## 1. Introduction

Cancer registries serve as critical infrastructures for public health surveillance and clinical decision making. Their data underpin epidemiological research, policy design, and treatment evaluation[1–3]. However, the system has long relied on manual abstraction of information from unstructured pathology reports—a process that is time consuming, error prone, and increasingly unsustainable as case volumes surge and manpower declines. Studies have shown that over 80% of clinically relevant information resides in

free☐text pathology reports. Manual abstraction typically introduces months of delay and substantial error rates, degrading both surveillance and research quality. As case volumes and reporting requirements expand, the system's workload has grown exponentially, rendering manual maintenance unsustainable[4–6].

We categorize this structural crisis as a threefold systemic failure:

(1) Failure of Completeness — insufficient manpower and growing caseloads lead to missing diagnostic and treatment information, systematically under☐representing certain patient groups[4,5,7]

(2) Failure of Ethics and Efficiency — manual abstraction repeatedly exposes complete medical records, heightening privacy risks and increasing operational costs[8–10]

(3) Failure of Granularity — temporal dynamics and biological detail are compressed into single field values during registration, leaving only a coarse "skeleton" of the patient record for analysis[11–13].

Together, these systemic failures highlight the urgent need for scalable, automated solutions that can match the complexity and volume of modern cancer registries. Recent studies have made meaningful progress in applying large language models (LLMs) to oncology workflows, with several reports demonstrating near-expert performance in well-defined information extraction tasks. However, these advances have largely been achieved in constrained problem settings, often tackling one narrow subtask at a time[14–16]. Existing on-premises deployments, while safeguarding patient privacy, typically address only a narrow subset of cancer registry requirements[17–20].

For example, one locally deployed system parsed surgical pathology reports but

extracted only six high-level diagnostic variables across multiple tumor types[21–25]. Other

multi-cancer efforts expanded disease coverage but still focused on a limited synoptic

report schema, extracting only about 22 standardized data elements [26]. Even the most

comprehensive single-cancer study to date—targeting breast pathology—captured 51

structured fields and required an enormous ~405-billion-parameter model to achieve

expert-level accuracy, a configuration far beyond the computational capacity of routine

hospital environments [14,24]. Cloud-based LLMs (e.g. GPT-4) have likewise shown strong

performance on oncology benchmarks[27],  yet their practical deployment remains limited.

Strict data-privacy regulations (e.g. HIPAA and GDPR) generally preclude routine

transmission of protected health information to external AI services[17],  and current

generative models can exhibit instability when handling long clinical texts, making

deterministic and reproducible extraction outputs difficult to obtain[28]. Together, these

findings highlight both the progress and the persistent gaps in the field: despite promising

prototypes, no existing system yet provides a comprehensive, end-to-end abstraction

solution suitable for real-world cancer registry operations[14].

Still, no framework simultaneously satisfies all three essentials: comprehensive scope,

ethical privacy, and computational feasibility. These define the central bottleneck of

registry automation and mirror the threefold systemic failures noted above. We posit that

earlier systems failed to meet the three core requirements because they lacked a

prompting engine co designed with pathologists, while local LLMs at the time were

limited in scale and reasoning, preventing stable clinical extraction. With advances from

2023 to 2025, local LLMs have become efficient enough to support modular,

scientifically grounded prompting engines.

To address the limitations of brittle manual prompting, we utilized DSPy, a framework

that abstracts language model interactions into programmable, modular primitives[29].

Building upon this programmatic approach, this study enables clinician☐engineer

co☐design of extraction logic and applies it to ten major cancers under CAP☐standard

field structures. This yields a reproducible and auditable registry architecture that

overcomes the challenges of completeness, ethical integrity, granularity, feasibility, and

generality:

(1) Restoring Completeness : The system extracts over 193 registry fields across ten

major cancer types with a mean exact-match accuracy of 93.9%. By capturing variable-

length items such as margin and lymph node status according to CAP templates, the

system systematically corrects the omissions and selection biases often introduced by

manual abstraction.

(2) Restoring Ethical Integrity : By enabling strictly on☐premise computation, the

system keeps all processing within the institution, eliminating the risks of PHI

transmission. Our single☐GPU inference approach balances cost efficiency with rigorous

regulatory compliance.

(3) Restoring Granularity : Leveraging DSPy's multi☐step reasoning capabilities, the

pipeline reconstructs complex semantic dependencies and temporal details often lost in

broad classification tasks. This programmatic logic ensures that fine-grained pathological

features are extracted with high consistency, moving beyond simple keyword matching.

(4) Ensuring Feasibility: We demonstrated architectural independence by

benchmarking the pipeline across three diverse, resource-efficient open-weight models

(GPT-OSS[30], Qwen3[31], and Gemma3[32]). By focusing on this compact 20B–30B

parameter class, our comparative analysis confirms that the system can be successfully

deployed on standard clinical workstations (48GB VRAM), ensuring the technology is

accessible without requiring high-performance datacenter infrastructure.

(5) Extending Generality: We validated the system's transportability through a

rigorous Independent External Validation (IEV) using the multi-institutional TCGA (The

Cancer Genome Atlas) dataset[33]. By testing on breast, colorectal, and esophageal cohorts

from diverse institutions, the system maintained high extraction fidelity (>92% accuracy)

despite unseen data structures and linguistic styles.

In summary, the proposed framework restores completeness, ethical integrity, and

informational granularity, while establishing cross☐model generality validated on

standard hardware. This achievement enables the technical realization of truly

comprehensive structured pathology☐report abstraction, laying the groundwork for

future real☐time clinical data infrastructures.

## 2. Results

**2.1 Assessment of Model Agnosticism and Computational Feasibility**

To determine the optimal engine for clinical deployment, we benchmarked the extraction framework across three distinct open-weight architectures (gpt-oss:20b, qwen3-30b, and gemma3:27b). The objective was to validate the model-agnostic nature of the pipeline while identifying the configuration that best balances registry-grade accuracy with the hardware constraints of a standard medical workstation (single GPU, 48GB VRAM).

As shown in **Table 1**, the framework achieved high exact-match accuracy across all tested architectures, confirming its agnosticism. However, a decisive divergence emerged in operational efficiency. The gpt-oss:20b model maintained the highest accuracy (94.3%) while processing complex reports 2–3 times faster than the alternatives. This efficiency gap reveals a critical hardware threshold: while the Qwen3-30B-A3B utilizes a fast sparse MoE architecture, its total parameter footprint (30B) approaches the memory limit of the A6000 GPU, causing bottlenecks that tripling latency. In contrast, gpt-oss:20b fits comfortably within the "48GB VRAM sweet spot," enabling high-speed, on-chip inference.

Based on this efficiency analysis, gpt-oss:20b was identified as the optimal candidate for the 'Digital Registrar' framework, being the only architecture capable of delivering registry-grade accuracy (94.3%) while maintaining the high-throughput performance required for routine hospital operations on standard workstation hardware (48GB VRAM). Consequently, to reflect the performance of a truly deployable

150 clinical system, all subsequent results reported in this study—including eligibility

151 triage, organ classification, and granular field extraction (Sections 2.2–2.4) are derived

152 exclusively from the gpt-oss:20b pipeline.

**2.2 Automated Report Triage and Organ Classification**

To ensure the pipeline selectively processes valid cancer registries, the system was

first evaluated on its ability to triage unstructured pathology reports—distinguishing

eligible cancer excision cases from a background of biopsies and non-malignant

specimens. As detailed in **Table 2**, the eligibility classifier demonstrated robust

reliability across the full validation cohort (N = 893). Crucially for a screening tool,

the model exhibited near-perfect sensitivity; out of 694 eligible cancer excision

reports, only a single breast excision case was missed (False Negative), confirming its

safety as an automated filter. The specificity was similarly high, with most

discrepancies (29 False Positives) restricted to clinically ambiguous cases—such as

large metastatic deposits or extensive biopsies—that mimic the linguistic complexity

of primary resections. These results confirm that the model operates with the high

sensitivity required to ensure that virtually no eligible cancer surgery report is

overlooked during the initial screening process.).

The subsequent organ-labeling sub-model demonstrated similarly strong

performance, achieving precision F1-scores ≥ 0.955 across all ten target organs, with

an average accuracy of 0.978 and a macro average F1 score of 0.955. As illustrated in

**Figure 2**, eight organ classes—breast, cervix, colorectal, liver, pancreas, prostate,

stomach, and thyroid—achieved perfect recall (1.000), while both lung and esophagus

reached F1 ≥ 0.955. Misclassifications were rare and distinctively patterned:

qualitative review revealed these were often cases with double primary

malignancies—such as reports describing independent tumors in both lung lobes—

which were intentionally excluded from the automated staging logic (ground truth

"Others") but were occasionally interpreted by the model as belonging to the specific

organ class (e.g., "Lung"). Collectively, these results confirm that foundational

classification layers of the DSPy pipeline operate with registry-grade reliability,

providing clean input for downstream extraction. Detailed confusion matrices for all

three test runs are provided in **Supplementary Tables S12–S14**.

**2.3 Per-organ extraction accuracy for various registry item**

After classification, 893 cancer surgery reports were parsed through organ-specific

extraction modules, each aligned to a JSON schema of variable fields according to

different organ system (procedure, histology, grade, AJCC T/N/M categories, and vice

versa, please see **Supplementary Tables S14–S23** for detail). Exact-match accuracies

across all ten organ systems (totally 193 fields) ranged between 88.9 % and 96.2 %,

with an overall mean of 94.3%±8.32%. **Table 3** summarizes the cohort size, field

count, and mean performance for each organ. Surgical margins, lymph nodes and

biomarkers are extracted by separate modules and discussed in later section.

High-performing fields (≥ 95 %) were consistent across organs expect thyroid

(where frequent referrance to other reports caused some model difficulty) and included

procedure histology, grade, and presence of vascular invasion, indicating that the

pipeline captures core oncologic variables with near-perfect fidelity even in organs

with extensive schema complexity ($\geq$ 24 fields).

In contrast, performance on TNM staging fields showed greater variability across

organs, reflecting the inherent complexity and inter-organ heterogeneity of staging

schemas. Occasional ambiguities in clinical phrasing—such as "anatomic staging" and

"pathologic staging" in breast—also contributed to minor discrepancies. A

representative example is provided in **Supplementary Appendix S25.3** (Sample

S25.3.1–S25.3.2). Nevertheless, overall accuracy for T, N, and M fields remained

high, typically exceeding 90% across test runs.

Lower-accuracy fields (60–90 %) were limited to poorly documented or

quantitative attributes—such as surgical technique in stomach and cervix or tumor

percentage and prostate weight in prostate reports—where textual variability is high.

A representative example and extra discussion is provided in **Supplementary**

**Appendix S25.4** (Sample S25.4.1–S25.4.2).

In summary, the organ-specific modules sustain $\geq$ 90 % mean exact-match

accuracy across varying schema sizes, reaffirming the scalability of the one-shot LLM

pipeline for comprehensive extraction of structured oncologic data. Full per-field

extraction results for each organ, including exact-match accuracy for all schema items,

are provided in the **Supplementary Tables S15–S24**.

**2.4 Lymph Node and Surgical Margin Status**

The pipeline demonstrated strong performance in extracting prognostically critical

data on lymph node (LN) and surgical margin status, as summarized in **Figures 2 and**

3. For LN evaluation, the system achieved a mean total-node concordance of over 80% across all ten organ systems. Performance was highest in organs with well-defined nodal basins such as the breast and liver, while it was more variable in anatomically complex sites like the lung and esophagus, where occasional omissions were the primary source of error rather than misclassification. Detailed per-organ LN metrics, including both total and station-level analyses, are provided in Supplementary Table S25. Examples of LN extraction performance are provided in **Supplementary Appendix S25.5**. (Samples S25.5.1.1-S25.5.2.2).

For surgical margins, the model achieved a mean accuracy of 91·2% for determining margin positivity. Concordance was excellent (≥95%) for several major cancers, including breast, colorectal, and lung. In cases with lower accuracy, such as pancreas resections, discrepancies were primarily attributable to challenges in mapping variably named margin categories rather than incorrect identification of tumor involvement. As expected, the accuracy for extracting the exact margin distance was lower, reflecting the inherent ambiguity of inequality notations and unit variations in the source reports. Representative margin-status extraction results the show complexity of pancreatic cancer are shown in **Supplementary Appendix S25.6** (Samples S25.6.1–S25.6.2). Because prostate cancer reports do not define multiple margin stations and instead document margin involvement using only overall positivity, extent of involvement, and the specific anatomic sites involved, prostate margins were excluded from this station-based margin accuracy evaluation.

**2.5 Breast biomarker extraction performance**

Breast cancer biomarker fields were extracted with near-perfect accuracy across 75

reports. ER positivity and percentage were correct in 75/75 and 73/75 cases,

respectively. PR positivity and percentage were correct in 74/75 and 73/75 cases.

HER2 score was correctly extracted in all 75 cases, and Ki-67 percentage in 74/75

cases. These results confirm the robustness of field-level extraction and validation

under exact string matching.

**2.6 External Validation Performance (TCGA Cohort)**

In the external TCGA cohort, the model maintained performance comparable to the

internal validation set, confirming strong cross-domain robustness. Across 150 reports,

triage and organ classification achieved 97.3% accuracy, with near-perfect

discrimination for major cancers (F1 = 1.000 for colorectal; 0.990 for esophagus). The

few discrepancies were administrative rather than interpretative: three reports labeled

as "Others" in the ground truth were predicted as breast cancer but were subsequently

verified as synchronous bilateral breast cancers—cases intentionally excluded from

organ-level staging due to the system's single-primary design. Field-level extraction

across 53 pathological variables reached a mean exact-match accuracy of 92.35% ±

11.04%, closely mirroring internal-set performance (93.9% ± 8.6%) and

demonstrating that the extraction logic generalizes effectively beyond the institution

where it was developed.

## 3. Discussion

This study demonstrates the successful development and validation of a resource-efficient, privacy-preserving, and autonomous AI pipeline that achieves cancer-registry-grade accuracy for multi-cancer data extraction from unstructured pathology reports. By operating on a single GPU and leveraging a locally deployed open-weight model, our system provides a practical solution to the long-standing informatics bottleneck that has constrained the scalability and timeliness of cancer surveillance for decades. The pipeline's robust performance—achieving a mean exact-match accuracy of 93.9%±8.6% across ten distinct malignancies and 193 registry fields—underscores its potential for real-world clinical deployment, offering a comprehensive, end-to-end workflow that encompasses document triage, cancer-type classification, and granular data abstraction.

While large language models (LLMs) now demonstrate human-level accuracy for information extraction from clinical texts[24], their clinical deployment is hindered by a critical trilemma: proprietary models raise significant data privacy and cost concerns, while open-source alternatives have historically required computationally prohibitive hardware[34]. Our study directly addresses this implementation gap by presenting a fully autonomous pipeline that is simultaneously accurate, privacy-preserving, and resource-efficient. This work is situated at the confluence of two recent technological shifts. First, the emergence of powerful, open-weight models like gpt-oss:20b that are optimized for local deployment on a single GPU, which resolves the hardware barrier and ensures data sovereignty[30]. Second, the maturation of programmatic LLM development frameworks like DSPy, which enables a paradigm shift from brittle prompt engineering to the construction of robust, reliable, and scalable AI systems[29]. By integrating these advances,

our work moves beyond single-cancer benchmarks to deliver a comprehensive, multi-organ abstraction system. It provides an economically viable and generalizable blueprint for a "digital registrar," demonstrating a practical path to overcoming the technological and organizational barriers that have stalled widespread AI adoption in healthcare informatics.

The framework's demonstrated capacity for model agnosticism—validated by the successful interchange of gpt-oss, Qwen3, and gemma3—provides crucial flexibility for healthcare deployment. However, our comparative analysis reveals a critical hardware threshold that defines the feasibility of widespread democratization: the 48GB VRAM limit of professional-grade workstation GPUs. The performance disparity observed between gpt-oss:20b and qwen3-30b is fundamentally a consequence of this hardware boundary. While qwen3-30b is theoretically efficient due to its low active parameter count (~3B), its total state of 30B parameters imposes a memory footprint that strains the 48GB limit of standard medical workstations. This forces the system to offload data to slower system RAM or saturate interconnect bandwidth, tripling inference latency (>140 seconds).

In contrast, gpt-oss:20b operates comfortably within the "workstation envelope," maintaining high speed (40–70 seconds) without requiring the >80GB GPUs (e.g., NVIDIA A100/H100) typical of datacenters. This distinction is vital for equity in global health informatics: by optimizing for the 48GB threshold, we ensure the "Digital Registrar" remains a deployable tool for individual hospitals and laboratories, rather than an elite capability restricted to institutions with dedicated datacenter infrastructure.

The Independent External Validation (IEV) results confirm the model's stability when

applied to a structurally and institutionally diverse patient cohort. The total mean

extraction accuracy of 92.35% in the external TCGA cohort is quantitatively similar to

the 93.9% reported for the internal development cohort. This finding is significant as it

indicates that the model has learned fundamental pathological principles rather than

mimicking institutional reporting artifacts, retaining high performance without the need

for site-specific fine-tuning.

While overall performance was high, error analysis highlighted challenges inherent to

multi-institutional data curation. The highest variability was observed in fields such as

surgical_technique in colorectal cancer (48.0% accuracy) and pm_category (distant

metastasis) in esophageal cancer (62.5% accuracy). These discrepancies largely reflect

known limitations in the ground truth definitions within the TCGA metadata (e.g.,

inconsistent M1 status annotations) rather than model failure. Furthermore, classification

errors were largely attributable to complex bilateral breast cancer cases which, while

correctly identified by the model as breast tissue, fell outside the current single-primary

schema scope. On core oncological variables such as histology and grade, the model

maintained 100% accuracy, supporting its utility as a reliable "digital registrar."

A key future direction is the extension of this framework into a multimodal system.

While our system excels at abstracting data from textual reports, the "digital registrar" of

the future must integrate information from various data streams to build a comprehensive

patient model. The integration of genomic data and digital pathology images, as

highlighted in recent reviews of multimodal AI in oncology, represents the next frontier

in automated cancer surveillance[35]. The development of pathology-specific multimodal

LLMs, such as PathChat+, which can reason directly over high-resolution pathology images, represents a pivotal technological enabler for this vision[36]. A future system built on our framework could leverage such models to correlate histologic patterns with molecular markers and clinical outcomes at an unprecedented scale, moving beyond mere data extraction to true integrated diagnostics and prognostication[37].

In conclusion, by solving the critical implementation challenges of resource efficiency and data privacy, this work provides a deployable and economically viable blueprint that democratizes access to state-of-the-art AI for cancer surveillance. This research marks a pivotal step in transforming this essential public health function from a slow, retrospective, and manual process into a near-real-time, intelligent system. Such a system is poised to accelerate clinical research, enhance the precision of public health action, and ultimately improve patient outcomes on a global scale.

## 4. Methods

### 4.1 Data Source and Annotation

This study was conducted under research ethics committee approval (REC #CMUH114-REC2-037) from China Medical University Hospital. The dataset comprised a total of 893 de-identified surgical pathology reports from the years 2023–2024. The final validation cohort consisted of 694 reports describing resected, invasive primary malignancies across ten major organ systems, with the detailed composition summarized in **Table 4**. An additional 199 reports describing biopsies, non-invasive tumors, or benign conditions served as negative controls for the initial classification stages of the pipeline.

To establish an expert-verified gold standard for evaluation, a semi-automated

annotation process was employed. First, an initial structured JSON summary was

generated for each report using a single inference pass of the gpt-oss:20b model.

Subsequently, two board-certified pathologists independently reviewed and corrected

these preliminary outputs in a side-by-side interface displaying the original report text

and the structured data. All discrepancies between the two reviewers were resolved

through a final blinded consensus, producing the definitive reference dataset used for

all performance evaluations.

**4.2 Schema definition**

All data extracted by the system conform to a strictly typed, hierarchical JSON

schema designed for clinical precision and computational reliability. The schema is

composed of two layers: (1) a universal core layer that defines attributes common to

all surgical pathology reports, such as report eligibility and primary tumor site, and (2)

ten organ-specific extension layers that capture the detailed variables unique to each

malignancy.

Each organ-specific schema was developed to be in strict alignment with the

College of American Pathologists (CAP) Cancer Protocols[38], ensuring that all

extracted data fields, terminologies, and logical dependencies meet established

standards for cancer reporting and registry submission. To enable deterministic, exact-

match evaluation and prevent ambiguity, all schema fields are strictly typed using

Pydantic-style models. Categorical fields are defined by enumerated string literals

(Literal[...]), binary fields as booleans (bool), and numeric values as integers (int),

with missing data explicitly represented as None. This approach eliminates

inconsistencies arising from synonyms, rounding, or fuzzy text matching.

CAP Cancer Reporting Protocols corresponding to each organ-specific schema is

shown in **Table 5**. The complete field definitions, enumerated values, validation

constraints, and specifications for variable-length lists (e.g., for surgical margins and

lymph nodes) for all ten organ-specific schemas, are provided in **Supplementary**

**Tables S1-S10**.

**4.3  Model architecture and workflow.**

The deterministic extraction workflow was implemented in DSPy 2.1 using

dspy.Predict() module, with predefined dspy.Signature that contains essential

instructions and definitions and executed on-premises using the gpt-oss:20b model

served via Ollama.

No model training, fine-tuning or few-shot prompting was applied; each report was

processed in a single forward pass.

**4.3.1 Eligibility classification**

The EligibilitySignature predicts whether a report represents a cancer surgery

(cancer_excision_report: bool), the organ category (cancer_category), and a free-text

descriptor when "others".

**4.3.2 Organ detection**

If cancer_excision_report = True, a secondary signature (CancerTypeSignature)

verifies or refines the organ label prior to extraction.

### 4.3.3 Organ-specific extraction

Ten sets of organ-specific DSPy modules (for example, for breastcancer, for

modules, BreastCancerNonnested, BreastCancerMargins, BreastCancerLN,

BreastCancerBiomarkers, was used) receive both original pathology report and the

json summary, previously generated by gpt-oss:20b, as input and output a validated

JSON matching their schema. The pipeline is illustrated in **Figure 4**. Please see

**Figure 5-8** for a successful example on organ-specific extraction. Modules will

attempt to extract tumor characteristics, AJCC/TNM staging, surgical margins and

lymph-node details for each cancer type. For breast and colorectal cancer, biomarker

statuses are extracted as well.

### 4.3.4 Validation of Model Agnosticity and Hardware Feasibility

To validate the architectural independence of the extraction framework and assess the

feasibility of deployment on standard workstation hardware, the identical pipeline

structure was instantiated and executed using two alternative open-weight transformer

architectures: qwen3-30b (Sparse Mixture-of-Experts) and gemma3:27b (Dense). The

foundational design of the AI pipeline explicitly embraces principles of model

agnosticism, utilizing the DSPy 2.1 framework to decouple the extraction logic from

specific model weights.

All comparative models were executed on-premises using the same dedicated

NVIDIA RTX A6000 Ada Generation GPU (48 GB VRAM). This hardware

constraint was strictly enforced to evaluate whether models could operate efficiently

within the memory envelope of a standard high-end medical workstation, without

requiring multi-GPU datacenter configurations.

**4.4  Evaluation metrics**

Model performance was evaluated by comparing each generated JSON output

against the expert-verified reference standard. Given that all schema variables are

strictly typed (i.e., Literal, bool, int, or None), evaluation was conducted using

deterministic, exact-string matching rather than similarity-based metrics. For list-type

variables, such as surgical margins and lymph node stations, corresponding elements

were aligned by field name before comparison. All statistical analyses were performed

using the scikit-learn library (version 1.5.0) in Python 3.11.

The primary metrics included accuracy, precision, recall, and the F1 score. The F1

score is calculated as the harmonic mean of precision and recall, providing a single,

balanced measure of a test's accuracy. For multiclass classification tasks, such as the

organ-type identification performed by the CancerTypeSignature classifier, the macro-

average F1 score was computed as the unweighted mean of the F1 scores for each

class, thereby giving equal weight to each category regardless of its frequency. Overall

accuracy was defined as the proportion of all extracted fields that exactly matched the

reference standard across the validation cohort. The specific definitions for composite

metrics applied to the extraction modules, such as margin status correctness and total

lymph node accuracy, are detailed in **Table 6**.

**4.5 Independent external validation**

To assess the robustness and transportability of the extraction model to external, non-institutional data, we utilized the TCGA-Reports dataset [33]from The Cancer Genome Atlas (TCGA) repository. This dataset serves as a rigorous gold standard for external validation, comprising machine-readable pathology reports from 32 tissues/cancer types generated by a wide variety of institutions, ensuring high structural and linguistic heterogeneity.

The model was applied in an "off-the-shelf" capacity, without any further training or fine-tuning, to a validation subset of 150 reports spanning Breast, Colorectal, Esophagus, Stomach, and "Others" categories. We evaluated both the classification (triage) performance and the extraction fidelity for 53 specific pathological fields across the Breast (22 fields), Colorectal (17 fields), and Esophagus (14 fields) cohorts.

**4.6 Role of the funding source**

**4.7 Ethical oversight**

This study was approved by the research ethics committee of China Medical University & Hospital, under REC number of CMUH114-REC2-037. All reports were fully de-identified and processed on encrypted institutional servers. No re-identification was attempted.

**4.8 Usage of large language models in manuscript**

This manuscript was prepared with partial drafting assistance from large language models. OpenAI GPT-5 was used for non-confidential sections to improve structure and clarity; gpt-oss:20b was used to draft and revise paragraphs describing proprietary schema design and extraction logic under a controlled, offline environment; and Gemini Pro 2.5 with Deep Research was used to identify and summarize peer-reviewed literature cited in the Introduction. All analytical workflows, data interpretation, and final text approval were performed by the authors. No LLM generated, altered, or fabricated experimental data.

## 5. Data availability

**5.1 Internal Development Cohort**

The primary dataset consists of de-identified surgical pathology reports from China Medical University Hospital. Due to patient privacy protections, these data are not publicly available but may be accessed by qualified researchers upon reasonable request to the corresponding author, subject to a Data Use Agreement (DUA).

**5.2 External Validation Cohort (TCGA Benchmark)**

To facilitate reproducibility and benchmarking, the complete external validation dataset—including the 150 selected TCGA pathology reports, the expert-annotated ground truth labels, and the model outputs—has been deposited in Zenodo and is publicly available at https://doi.org/10.5281/zenodo.17689361 . The original source data remains accessible via the NCI Genomic Data Commons (GDC) Data Portal.

## 6. Code availability

The complete source code for the "Digital Registrar" extraction pipeline, including all DSPy signatures, organ-specific schema definitions, and the orchestration logic used for this study, is openly available on GitHub at https://github.com/kblab2024/digitalregistrar . The repository includes instructions for reproducing the environment and deploying the specific open-weight models (gpt-oss:20b, qwen3-30b, gemma3:27b) utilized in the benchmarking and validation experiments. Upon acceptance, a permanent DOI will be minted via Zenodo to ensure long-term archival stability.

## 7. Acknowledgments

We are deeply grateful to Dr. Ting-Sung Hsieh of UT Southwestern Medical Center, as well as Dr. Ching-Hang Chien and Dr. Yi-Chung Dzeng of the Research Center for Applied Sciences, Academia Sinica. Their insightful feedback and critical suggestions were invaluable to the intellectual development and final refinement of this manuscript.

This work was supported by the National Science and Technology Council (NSTC) of Taiwan, under grant number NSTC 113-2221-E-039-017, and the NSTC College Student Research Grant, number 114-2813-C-039-132-E

## 8. Author contributions

K.P.C. conceived the study, oversaw the project, and wrote the original draft. H.K.C. developed the core deep learning algorithms and performed the technical

implementation. C.Y.L. and Y.L.L. provided technical consultation and optimized the

software architecture. N.H.C. and H.C. provided clinical resources, pathological data,

and supervised the clinical interpretation. P.Y.T. assisted in data curation and

validation. P.C.C. provided critical guidance on the methodology and revised the

manuscript. Y.W.C. contributed to the bioinformatics analysis. L.J.S. assisted with

manuscript editing and linguistic refinement. All authors read and approved the final

manuscript.

## 9. Competing Interests

503    We declare no competing interests.

## 10. Reference

1. Piñeros, M. *et al.* The role and utility of population-based cancer registries in cervical
cancer surveillance and control. *Preventive Medicine* **144**, 106237 (2021).

2. Lancet, T. Cancer registries: the bedrock of global cancer care. *The Lancet* **405**, 353
(2025).

3. Nair, S., Ngwa, W., Addai, B. W., Addai, A. O. & Oti, B. A. The role of a national
cancer registry in effective implementation and monitoring of the Global Breast Cancer
Initiative (GBCI) framework in Ghana: a narrative review. *Translational Breast Cancer*
*Research* **6**, (2025).

4. Gondara, L., Simkin, J., Arbour, G., Devji, S. & Ng, R. Classifying Tumor
Reportability Status From Unstructured Electronic Pathology Reports Using Language

Models in a Population-Based Cancer Registry Setting. *JCO Clin Cancer Inform* e2400110 (2024) doi:10.1200/CCI.24.00110.

5. Hands, I. & Kavuluru, R. A survey of NLP methods for oncology in the past decade with a focus on cancer registry applications. *Artif Intell Rev* **58**, 314 (2025).

6. Hailer, L., Miller, J. & Chapman, S. Cancer Registrar Workload and Staffing Study: Guidelines for Hospital Cancer Registry Programs. (2024).

7. Penberthy, L. T., Rivera, D. R., Lund, J. L., Bruno, M. A. & Meyer, A.-M. An overview of real-world data sources for oncology and considerations for research. *CA: A Cancer Journal for Clinicians* **72**, 287–300 (2022).

8. Moor, M. *et al.* Foundation models for generalist medical artificial intelligence. *Nature* **616**, 259–265 (2023).

9. Singhal, K. *et al.* Large language models encode clinical knowledge. *Nature* **620**, 172–180 (2023).

10. Tertulino, R., Antunes, N. & Morais, H. Privacy in electronic health records: a systematic mapping study. *J Public Health (Berl.)* **32**, 435–454 (2024).

11. Hernandez-Boussard, T., Blayney, D. W. & Brooks, J. D. Leveraging Digital Data to Inform and Improve Quality Cancer Care. *Cancer Epidemiol Biomarkers Prev* **29**, 816–822 (2020).

12. Bagherzadeh, P., Sultanem, K., Batist, G. & Abbasinejad Enger, S. An automatic pipeline for temporal monitoring of radiotherapy-induced toxicities in head and neck cancer patients. *npj Precis. Onc.* **9**, 40 (2025).

13. Paiva, B. *et al.* A New Natural Language Processing–Inspired Methodology

(Detection, Initial Characterization, and Semantic Characterization) to Investigate

Temporal Shifts (Drifts) in Health Care Data: Quantitative Study. *JMIR Medical*

*Informatics* **12**, e54246 (2024).

14. Saluja, R. *et al.* Cancer type, stage and prognosis assessment from pathology reports

using LLMs. *Sci Rep* **15**, 27300 (2025).

15. Chen, D., Alnassar, S. A., Avison, K. E., Huang, R. S. & Raman, S. Large Language

Model Applications for Health Information Extraction in Oncology: Scoping Review.

*JMIR Cancer* **11**, e65984 (2025).

16. Hung, T. K. W. *et al.* Human vs. AI: A comparative effectiveness study of large

language models for automated biomarker extraction. *J Clin Oncol* **43**, e13605–e13605

(2025).

17. Wiest, I. C. *et al.* A software pipeline for medical information extraction with large

language models, open source and suitable for oncology. *npj Precis. Onc.* **9**, 313 (2025).

18. Bartels, S. & Carus, J. From text to data: Open-source large language models in

extracting cancer related medical attributes from German pathology reports. *Int J Med*

*Inform* **203**, 106022 (2025).

19. Wiest, I. C. *et al.* Privacy-preserving large language models for structured medical

information retrieval. *npj Digit. Med.* **7**, 257 (2024).

20. Bednarczyk, L. *et al.* Scientific Evidence for Clinical Text Summarization Using

Large Language Models: Scoping Review. *Journal of Medical Internet Research* **27**,

e68998 (2025).

21. Tripathi, A. *et al.* Employing Consensus-Based Reasoning with Locally Deployed

LLMs for Enabling Structured Data Extraction from Surgical Pathology Reports.

*medRxiv* 2025.04.22.25326217 (2025) doi:10.1101/2025.04.22.25326217.

22. Bumgardner, V. K. C., Mullen, A., Armstrong, S., Hickey, C. & Talbert, J. Local

Large Language Models for Complex Structured Medical Tasks. Preprint at

https://doi.org/10.48550/arXiv.2308.01727 (2023).

23. Lee, D. *et al.* Using Large Language Models to Automate Data Extraction From

Surgical Pathology Reports: Retrospective Cohort Study. *JMIR Formative Research* **9**,

e64544 (2025).

24. Balasubramanian, J. B. *et al.* Leveraging large language models for structured

information extraction from pathology reports. Preprint at

https://doi.org/10.48550/arXiv.2502.12183 (2025).

25. Grothey, B. *et al.* Comprehensive testing of large language models for extraction of

structured data in pathology. *Commun Med* **5**, 96 (2025).

26. Rajaganapathy, S. *et al.* Synoptic Reporting by Summarizing Cancer Pathology

Reports using Large Language Models. *medRxiv* 2024.04.26.24306452 (2024)

doi:10.1101/2024.04.26.24306452.

27. Hao, Y. *et al.* Large language model integrations in cancer decision-making: a

systematic review and meta-analysis. *npj Digit. Med.* **8**, 450 (2025).

28. Atil, B. *et al.* Non-Determinism of 'Deterministic' LLM Settings. Preprint at

https://doi.org/10.48550/arXiv.2408.04667 (2025).

29. Khattab, O. *et al.* Dspy: Compiling declarative language model calls into state-of-the-

art pipelines. in *The Twelfth International Conference on Learning Representations*

(2024).

30. Kumar, D., Yadav, D. & Patel, Y. GPT-OSS-20B: A Comprehensive Deployment-

Centric Analysis of OpenAI's Open-Weight Mixture of Experts Model. Preprint at

https://doi.org/10.48550/arXiv.2508.16700 (2025).

31. Yang, A. *et al.* Qwen3 Technical Report. Preprint at

https://doi.org/10.48550/arXiv.2505.09388 (2025).

32. Team, G. *et al.* Gemma 3 Technical Report. Preprint at

https://doi.org/10.48550/arXiv.2503.19786 (2025).

33. Kefeli, J. & Tatonetti, N. TCGA-Reports: A machine-readable pathology report

resource for benchmarking text-based AI models. *Patterns (N Y)* **5**, 100933 (2024).

34. Dennstädt, F., Hastings, J., Putora, P. M., Schmerder, M. & Cihoric, N. Implementing

large language models in healthcare while balancing control, collaboration, costs and

security. *NPJ Digit Med* **8**, 143 (2025).

35. Waqas, A., Tripathi, A., Ramachandran, R., Stewart, P. & Rasool, G. Multimodal

data integration for oncology in the era of deep neural networks: a review. *Frontiers in*

*Artificial Intelligence* **7**, (2023).

36. Chen, C. *et al.* Evidence-based diagnostic reasoning with multi-agent copilot for

human pathology. Preprint at https://doi.org/10.48550/arXiv.2506.20964 (2025).

37. Witowski, J. *et al.* Multi-modal AI for comprehensive breast cancer prognostication.

*ArXiv* **abs/2410.21256**, (2024).

38. Torous, V. F. *et al.* College of American Pathologists Cancer Protocols: From

Optimizing Cancer Patient Care to Facilitating Interoperable Reporting and Downstream

Data Use. *JCO Clinical Cancer Informatics* 47–55 (2021) doi:10.1200/CCI.20.00104.

## Figure Legends

**Figure 1. Per-organ classification performance metrics.** Bar chart summarizing the classification fidelity across ten target organ systems (N=893). The model achieved perfect recall (1.0) for eight distinct organ classes. High precision and F1-scores (>0.95) were maintained across all categories, confirming the model's reliability as a routing engine for downstream extraction modules. Slight performance dips in the "Lung" and "Esophagus" categories were largely attributable to the administrative exclusion of complex double-primary malignancies (labeled as "Others" in ground truth).

**Figure 2. Lymph-node extraction accuracy across organ systems.** Bar plots show the model's performance in extracting lymph-node information across ten organ systems. The blue bars represent total lymph-node accuracy, defined as the exact-match concordance rate for the aggregated examined and positive lymph-node counts within each organ's regional nodal basin. The red bars represent station-level accuracy, which requires an exact match for every individual lymph-node station, including station name, examined count, and positive count.

**Figure 3. Surgical margin extraction accuracy across organ systems.** Bar plots

compare two levels of surgical-margin extraction performance across ten organ systems.

The blue bars represent margin-positivity accuracy, defined as the exact-match

concordance for determining whether each reported surgical margin is involved by tumor.

The red bars represent margin-distance accuracy, a stricter metric that requires exact

matching of both the margin involvement status and the reported tumor-to-margin

distance (in millimeters) for every margin element. Because prostate cancer reports do

not define multiple margin stations and instead document margin involvement using only

overall positivity, extent of involvement, and the specific anatomic sites involved,

prostate margins were excluded from this station-based margin accuracy evaluation.

**Figure 4. Extraction pipeline for structured cancer data from surgical pathology
reports.**

**Figure 5. Example for a successful (but not perfect) generation by models related to
breast cancer. Original pathology report without lymph node submitted (excerpt,
specimen 2-1-17)**

**Figure 6. Example for a successful (but not perfect) generation by models related to
breast cancer. Original pathology report without lymph node submitted (excerpt,
specimen 2-1-17)**

**Figure 7. Example for a successful (but not perfect) generation by models related to
breast cancer. Model output for signature BreastCancerMargins**

**Figure 8. Example for a successful (but not perfect) generation by models related to
breast cancer. Model output for signature BreastCancerBiomarkers (excerpt,
specimen 2-1-17)**

644    **Figures**

645    **Figure 1**

648    **Figure 2**

651     **Figure 3**

653 **Figure 4**

**Figure 5**

```
● ● ●                          2-1-17

1. Breast, left, s/p neoadjuvant chemotherapy with targeted therapy and partial mastectomy,
nipple-areola-complex sparing mastectomy, invasive carcinoma of no special type, grade 3,
multiple foci.
2. Soft tissue, axillary tail, left, excision, no lymph node included.
3. Immunohistochemical study: ER (negative), PgR (negative), Her2/neu (positive, score 3+) and
Ki67 proliferation index (up to 50%).
4. Pathologic AJCC Stage Group: ypT1c(m) NX, cM0, (prognostic stage group IA , Anatomic stage
group IA , AJCC 8ed).
…
1. Procedure: Nipple-areola-complex sparing mastectomy
2. Specimen Laterality: Left
3. Tumor Site: at least two foci
-  1/1 from nipple
-  5/3 from nipple
4. Gross description:

     The specimen fixed in formalin is submitted in one bag, labeled as left whole breast
excluding nipple-areolar complex and axillary fibroadipose tissue.
…
Microscopic Examination:
1. Histologic Type: Invasive carcinoma of no special type (ductal)
2. Histologic Grade (Nottingham Histologic Score):
Nottingham Score
(A) Glandular (Acinar) / Tubular Differentiation: Score 3.
(B) Nuclear Pleomorphism: Score 3.
(C) Mitotic Rate: Score 3.
(D) Overall Grade: Grade 3 (scores of 8 or 9)
3. Tumor Size:
…
```

659    **Figure 6**

662 **Figure 7**

664 **Figure 8**

## Tables

**Table 1. Comparative Performance and Efficiency of Locally Deployed LLMs**

Benchmarks were conducted on a single NVIDIA RTX A6000 (48GB VRAM). Note that while Qwen3 offers high accuracy, its memory footprint exceeds the optimal efficiency envelope for single-GPU workstations, resulting in significantly higher latency.

| Model | Architecture Type | Total Parameters | Mean Exact-Match Accuracy (193 Registry Fields) | Typical Processing Speed(Per Complex Report) |
|---|---|---|---|---|
| **gpt-oss:20b** | Sparse MoE | 20B | 94.30% | 40 – 70 seconds |
| **qwen3-30b-A3B** | Sparse MoE | 30B | 92.90% | 140 – >200 seconds |
| **gemma3:27b** | Dense | 27B | 89.80% | 50 – 130 seconds |

**Table 2. Confusion Matrix of the Eligibility Triage Classifier (Run 1)**

The classifier was evaluated on 893 real-world pathology reports. "Positive" indicates the

report was identified as a valid cancer excision case eligible for registry abstraction.

| | Predicted Eligible (Cancer Excision) | Predicted Ineligible (Biopsy / Benign / Other) | Total |
|---|---|---|---|
| **Actual Eligible** | 693 (TP) | 1 (FN) | 694 |
| **Actual Ineligible** | 29 (FP) | 170 (TN) | 199 |
| **Total** | 722 | 171 | 893 |

679    **Table 3. Per-organ extraction accuracy for various registry item**

| Organ | n Reports | # Fields Evaluated | Mean Accuracy ± SD (%) |
|---|---|---|---|
| **Breast** | 75 | 26 | **93·5 ± 9·7** |
| **Uterine cervix** | 29 | 16 | **90.9 ± 9.7** |
| **Colon and rectum** | 70 | 20 | **96.6 ± 5.3** |
| **Esophagus** | 73 | 16 | **96.2 ± 4.8** |
| **Liver – HCC** | 79 | 17 | **94.1 ± 9.0** |
| **Lung** | 63 | 20 | **92.5 ± 7.1** |
| **Pancreas** | 28 | 15 | **91.7 ± 12.9** |
| **Prostate** | 94 | 25 | **97.0 ± 3.4** |
| **Stomach** | 79 | 18 | **93.2 ± 11.6** |
| **Thyroid** | 74 | 20 | **92.3 ± 9.5** |

682     **Table 4. Composition of the cancer excision cohort (n = 694)**

| Organ site | Number of reports (n) |
|---|---|
| Esophagus | 75 |
| Stomach | 80 |
| Colorectum | 71 |
| Breast | 76 |
| Uterine cervix | 30 |
| Pancreas | 29 |
| Prostate | 95 |
| Lung | 64 |
| Liver | 80 |
| Thyroid | 75 |
| Others (dual or out-of-scope cancers) | 30 |
| Total | 694 |

685 **Table 5. CAP Cancer Reporting Protocols corresponding to each organ-specific**

686 **schema**

| Organ site | CAP Cancer Reporting Protocol (version / release year) |
|---|---|
| Esophagus | Esophagus, Version 4.2.0.1 (June 2022) |
| Stomach | Stomach, Version 4.4.0.0 (March 2023) |
| Colorectum | Colon and Rectum, Resection, Version 4.3.1.0 (June 2024) |
| Breast | Breast Invasive, Resection, Version 4.10.0.0 (June 2024) |
| Uterine cervix | Uterine Cervix, Resection, Version 5.1.1.0 (April 2023) |
| Pancreas | Pancreas (Exocrine), Version 4.2.0.2 (November 2021) |
| Prostate | Prostate, Resection, Version 4.3.0.0 (September 2023) |
| Lung | Lung, Resection, Version 4.3.0.1 (September 2022) |
| Liver | Hepatocellular Carcinoma, Version 4.3.0.0 (June 2022) |
| Thyroid | Thyroid, Version 4.4.0.0 (March 2023) |
| Others (dual / out-of-scope) | Not applicable — excluded from schema alignment |

689    **Table 6. Evaluation metrics and definitions**

| Metric | Definition |
| --- | --- |
| Margin status correctness | Exact match of both margin_category and margin_involved for every reported margin element. |
| Margin distance correctness | Exact match of margin_category, margin_involved, and distance (integer, mm) for each margin element. |
| Total lymph-node accuracy | Exact match of examined and involved integer counts within each organ's regional_lymph_node list. |
| Lymph-node station accuracy | Exact match of station_name, examined, and involved values for each lymph-node group ("station"). |
| Accuracy of other fields | Proportion of all remaining scalar fields (e.g., histological_type, tumor_size, grade, biomarker results, and stage-group entries) that exactly match the expert reference. |

1. Breast, left, s/p neoadjuvant chemotherapy with targeted therapy and partial mastectomy, nipple-areola-complex sparing mastectomy, invasive carcinoma of no special type, grade 3, multiple foci.

2. Soft tissue, axillary tail, left, excision, no lymph node included.

3. Immunohistochemical study: ER (negative), PgR (negative), Her2/neu (positive, score 3+) and Ki67 proliferation index (up to 50%).

4. Pathologic AJCC Stage Group: ypTis(m) NX, cM0, (prognostic stage group IA , Anatomic stage group IA , AJCC 8ed).

1. Procedure: Nipple-areola-complex sparing mastectomy

2. Specimen Laterality: Left

3. Tumor Site: at least two foci
   - 1/1 from nipple
   - 5/3 from nipple
   - 2/3 from nipple

4. Gross description:

The specimen fixed in formalin is submitted in one bag, labeled as left whole breast excluding nipple-areolar complex and axillary fibroadipose tissue.

Microscopic Examination:

1. Histologic Type: Invasive carcinoma of no special type (ductal)

2. Histologic Grade (Nottingham Histologic Score):

Nottingham Score

(A) Glandular (Acinar) / Tubular Differentiation: Score 3.

(B) Nuclear Pleomorphism: Score 3.

(C) Mitotic Rate: Score 2.

(D) Overall Grade: Grade 3 (scores of 8 or 9)

3. Tumor Size:

```json
  "margins": [
    {
      "margin_category": "base",
      "margin_involved": false,
      "distance": 20,
      "description": "Free of tumor, with the distance of 2.0 cm"
    },
    {
      "margin_category": "superficial",
      "margin_involved": false,
      "distance": 14,
      "description": "Free of tumor, with the distance of 1.4 cm"
    },
    {
      "margin_category": "12_3_clock",
      "margin_involved": false,
      "distance": null,
      "description": "Free of tumor"
    },
```