Network topology outweighs emergence probability in surveillance sentinel placement

Xiaolu Wang[1], Victor Del Rio Vilas[2], Qi Li[1], Qu Cheng[1*]

[1] Department of Epidemiology and Biostatistics, School of Public Health, Tongji Medical College, Huazhong University of Science and Technology, Wuhan, Hubei, People's Republic of China

[2] UK-Public Health Rapid Support Team, UK Health Security Agency, London, United Kingdom

Correspondence to:

Dr. Qu Cheng, chengqu@hust.edu.cn

Abstract

Background: Many studies have focused on understanding spatial heterogeneity in infectious disease emergence probability; however, how this information can be leveraged to optimize sentinel node selection for early outbreak detection on complex networks remains largely unexplored.

Methods: We simulated outbreaks on diverse synthetic and empirical networks, and quantified early detection performance as the average reduction in outbreak size when detected by a given sentinel set. We first used genetic algorithms to identify optimal sentinel sets and understand characteristics potentially relevant to early detection performance. We then trained a Random Forest-based Surrogate Model (RFSM) with the identified characteristics to assess the relative importance of different network features and to enable a rapid prediction of node selection rank. RFSM was benchmarked against five alternative surveillance strategies on networks not used in training to evaluate generalizability. Sensitivity analyses were conducted to examine how feature importance varied with network structure and epidemiological parameters.

Results: Surveillance strategies incorporating emergence probability outperformed those based solely on network topology, but the improvement was modest across all examined scenarios. Dynamic selection features capturing overlapping information among sentinel sites, such as the proportion of a candidate node's neighbors that have

already been selected, were the most important determinant of early detection, followed by global and node

topology-related features. Emergence probability-related features were less influential but gained importance with

greater node degree heterogeneity, larger variability in the emergence probability distribution, and greater negative

correlation between node degree and emergence probability. Selecting only six sentinels achieved approximately 90%

of the performance of full-network surveillance. RFSM achieved comparable performance to Genetic Algorithm

(GA), while requiring only 1/24,000 of GA's computational time on a network with 200 nodes.

Conclusions: Information about spatial heterogeneity in emergence probability provided limited additional benefit

beyond network topology in selecting sentinel nodes for early outbreak detection on complex networks. The online

tool RFSM offers a ready-to-use, computationally efficient and robust framework to support the design of effective

disease surveillance networks.

Introduction

In recent decades, the frequency, geographic spread, and impact of emerging infectious diseases (EIDs) have escalated notably, driven by factors such as climate change, urbanization, and ecological disruption [1-3]. Since the beginning of the 21st century, more than 50 EIDs have emerged, with at least one EID appearing nearly every year [2], some leading to large outbreaks. Beyond the direct health impacts, EIDs have also resulted in substantial socioeconomic burdens, including increased healthcare costs, disrupted trade, and widespread societal consequences. For example, the COVID-19 pandemic resulted in $52 billion in healthcare costs in low- and middle-income countries in the first 4 weeks alone [4], and led to a 3.4% decline in the world's collective gross domestic product (GDP) in 2020 [5]. These challenges highlight the need for improved early detection of EIDs to strengthen global health security.

Early detection of EIDs has been addressed by researchers from two main perspectives. The first focuses on the spatial heterogeneity of disease emergence risks [6]. EIDs most frequently occur in remote, ecologically diverse regions (e.g., forests and wetlands) characterized by high wildlife density and low human population density, since most EIDs originate from zoonotic spillover events before its persistent transmission in humans, with over 60% arising from wildlife reservoirs such as bats, rodents, and primates [1]. Occasionally, these localized transmissions further spill over into densely connected urban centers, fueling larger outbreaks [7]. For example, human immunodeficiency virus (HIV) emerged from cross-species transmission of simian immunodeficiency viruses (SIVs) in African primates, spread to urban populations in Central Africa, and was later identified in multiple regions worldwide in the late 20th century [8,9]. Considerable efforts have been made to understand the geographic distribution of the emergence probability and identify disease emergence hotspots. The PREDICT project of the United States Agency for International Development's Emerging Pandemic Threat (EPT) program conducted extensive wildlife sampling in regions with high zoonotic pathogen diversity and frequent human-animal contacts to enhance global surveillance and preparedness for EIDs [10]. Similarly, modeling studies have been developed to predict global hotspots and determinants of zoonotic disease emergence based on historical EID events [1,6,11]. However, how this information can be leveraged to optimize sentinel site selection for early outbreak detection on complex networks (i.e., neither purely regular nor random in structure) remains largely unexplored.

The other perspective emphasizes the critical role of network topology. Highly connected individuals or locations within a network are often infected earlier, thus offering timely signals of epidemic outbreaks [12,13]. In scale-free networks, for instance, monitoring highest-degree nodes can predict outbreak peaking time earlier than monitoring randomly selected nodes, reducing the peak detection time by up to 85.7% relative to random monitoring [12].

Beyond node degree, other network metrics—such as the degree of neighboring nodes [14,15] and the entropy of

random walk from node to each community in networks with distinct community structure [16]—have also been

leveraged to enhance EID surveillance system design, since they require less information of the complete network

structure and remain robust to changes in network topology or missing information. However, these network-based

studies typically assume uniform disease emergence risk across all nodes and rarely account for the spatial

heterogeneity of such risks.

In this study, we integrated these two key perspectives—spatial heterogeneity of disease emergence risks and

network topology—to identify the optimal set of sentinel nodes for early detection of EIDs in complex networks.

By simulating outbreaks on diverse synthetic and empirical networks under different node-specific emergence

probability scenarios, we evaluated the potential benefits of incorporating heterogenous emergence probability,

proposed a computationally efficient method to identify optimal nodes without simulation, and examined how

surveillance performance changes with the number of sentinel nodes and network size. We also developed an

online platform implementing this analytical framework to facilitate evidence-based surveillance system design.

This framework is also applicable to non-endemic but outbreak-prone infectious diseases.

Methods

Simulation settings

Network structures

We simulated infectious disease spreads on undirected and unweighted graphs $G = (V, E)$, where $v_i \in V$ represents a vertex (also known as a node) such as an individual, a farm, or a city, and $(v_i, v_j) \in E$ represents contacts between vertices, such as co-location in physical space, livestock exchange, or direct flight. The degree of a vertex is defined as the number of edges attached to it. We used synthetic modular networks for the main analyses due to its flexibility in reflecting diverse real-world network structures through changing key parameters [13], while further validated the results on simpler synthetic scale-free networks [17] and four empirical networks reflecting actual patterns of interaction and social structure [18-22].

Synthetic modular networks. Modular networks are ubiquitous in real-world, since they reflect the naturally occurring groups or community structure in society [13,23]. In such networks, connections are dense within groups (i.e., modules or communities), while relatively sparse between groups. We used Modular Configuration Model with predefined mean degree (μ), variance of the degree (σ), and within-module connection probability (p) (see instances in Fig. 1A-i) to generate synthetic modular networks [13,24]. We drew 1,000 sets of these parameters from predefined ranges (Table 1) to generate random networks and simulate disease outbreaks on them, ensuring sufficient diversity in the training data for the *Random forest-based surrogate model*.

Table 1. Parameter values related to network topology and emergence probability used to generate simulated networks and outbreak scenarios.

Category	Parameter	Definition	Range
Network topology	N_m	Number of modules	3–8
	N_n	Number of nodes per module	15–30
	μ	Mean degree	3–8
	σ	Variance of degree	1–15
	p	Within-module connection probability	0.2–0.9
Emergence probability	a	Beta distribution parameter defining the distribution of the emergence probability	0.05–2

b	Beta distribution parameter defining the distribution of the emergence probability	2–10
ρ	Correlation coefficient between node degree and emergence probability	-0.9–0.9

Synthetic scale-free networks. Scale-free networks, characterized by the existence of highly connected hubs, are another typical type of complex networks [17]. The degree distribution of these networks follows a power law, which means that most nodes have only a small number of connections, while a few nodes (i.e., hubs) have a large number of connections [17]. We generated synthetic scale-free networks with 100 nodes with the Barabási-Albert model to validate our surrogate model [17,25], beginning with an initial set of 2 nodes and iteratively adding new nodes, each connecting randomly to 2 existing nodes with the connection probability proportional to each existing node degree (Fig. 1A-ii).

Empirical networks. We used four medium-sized empirical networks to validate our findings (Fig. 1A-iii), chosen primarily for computational feasibility. Since most of empirical networks are not fully connected, we restricted our analyses to the largest connected components of each network.

- *University network.* The university network was collected via smartphones as part of the Copenhagen Network Study and contains information about physical contacts between university students defined as the reception of mutual Bluetooth scans between two students [18]. Since the original dataset is dynamic (i.e., every 5 minutes over 4 weeks) and using aggregated data across all time points will contain too many edges and obscure important network structures, we chose data from the time point $t = 139,800$s when student users were most active, resulting in a network with 143 nodes and 635 edges.

- *High school network.* This network captures physical contacts recorded by wearable sensors between students at a high school in Marseille, France during a 7-day period in November 2012, comprising 180 nodes and 2,220 edges [19].

- *Facebook network.* This dataset comprises an anonymous Facebook friends network collected in Fall 2014, containing 362 nodes (each representing a unique Facebook profile) and 1,988 edges (denoting Facebook friendship connection between profiles) [20].

- *Wild bird interaction network.* This network was derived from a socio-ecological study of wild birds at Witham Woods, Oxford, UK, conducted over a 24-day period in March 2014 [21,22]. It contains 202 nodes

and 4,574 edges, where nodes represent wild birds and edges represent simultaneous presence of two birds at

the same nest box.

The degree distributions of these empirical networks show different structural patterns (Fig. S1). The Facebook

network exhibits degree distributions consistent with scale-free networks, while university and high school

networks show more homogeneous degree distribution across nodes. Notably, the wild bird network shows a

bimodal degree distribution, probably because some birds form larger groups for breeding and brood rearing during

the breeding season [21].

Figure 1. Simulation settings. (A) Example synthetic and empirical networks. (i) Four representative networks with 20 nodes (5 modules, 4 nodes per module) generated with the Modular Configuration Model, where p denotes the within-module connection probability and σ represents degree heterogeneity (Table 1). Colors distinguish different modules. (ii) A random synthetic scale-free network with 20 nodes generated with the Barabási-Albert model. (iii) Four empirical networks: human contact networks including university, high school, and Facebook social networks, and an ecological interaction network of wild birds. (B) Node-specific emergence probability assignment. (i) An example scatterplot of the emergence probability and node degree centrality when $N_m = 5$, $N_n = 20$, $\mu = 5$, $\sigma = 8$, $p = 0.8$, $a = 0.1$, $b = 5$, and $\rho = -0.7$. (ii) An example synthetic modular network, whose node size represents degree centrality and node color represents emergence probability. (C) Simulated infectious disease spread on a modular synthetic network with the same parameters as above using a stochastic SIR (Susceptible-Infectious-Recovered) model. The outbreak was seeded from a node randomly selected based on its emergence probability.

Node-specific emergence probability assignment

We first randomly sampled N emergence probabilities from a predefined distribution, then assigned these probabilities to nodes based on a predefined correlation between node degree and emergence probability (Table 1) with the process described below.

Sampling emergence probabilities. We assumed that the emergence probabilities of all nodes follow a Beta distribution, chosen for its flexibility in approximating common distributions, such as uniform, exponential, gamma, and normal distributions, through changing its parameters. We randomly sampled N emergence probabilities $\{p_1, p_2, \ldots, p_N\}$ from Beta (a, b), where N is the number of nodes, and a and b are the parameters of Beta distribution. The ranges for a and b are provided in Table 1.

Assigning emergence probabilities to nodes. We then assigned the sampled emergence probabilities to nodes using the method described below to achieve the predefined correlation coefficient ρ between node degree and emergence probability. Various correlation strengths were examined to compare the relative importance of emergence probability and network topology (Table 1). Under a strong positive correlation scenario, it is intuitively that nodes with both high emergence probabilities and large degrees will be prioritized.While under a strong negative correlation scenario, nodes with high degrees tend to have low emergence probabilities, and vice versa. In this setting, the prioritized characteristic (i.e., network topology or emergence probability) directly demonstrates its

importance for early detection performance. To achieve the predefined correlation strength ρ, we first sampled N

data points $Q = \{(x_1, y_1), (x_2, y_2), \ldots, (x_N, y_N)\}$ from a standard bivariate normal distribution with a correlation

coefficient ρ. Then, for each node V_i with degree D_i, we determined its rank $R(D_i)$ relative to all other nodes'

degrees and identified the data point (x_t, y_t) in Q where the rank of x_t matched $R(D_i)$, and determined the rank of y_t,

$R(y_t)$ among all y_s in Q. Finally, the emergence probability with the rank $R(y_t)$ was assigned to V_i. Ranks for nodes

with identical degrees (e.g., $\{V_{i_1}, V_{i_2}, \ldots, V_{i_s}\}$) were assigned based on their original order in the node list ($i_1 < i_2$

$< \ldots < i_s$) to ensure distinct emergence probabilities. Since the original node order was randomly assigned, this

arbitrary rank allocation scheme should not bias the results.

Outbreak simulation on networks

We simulated 1,000 random disease outbreaks with a stochastic Susceptible-Infectious-Recovered (SIR) process on

each synthetic or empirical network. For each simulation, we first sampled and assigned an emergence probability

to each node, following the method described above. Then, we initialized the state of all nodes to S (susceptible)

and randomly selected a seed node by sampling with probability proportional to its emergence probability, set its

state to I (infectious), and simulated the onward transmission from this seed node (Fig. 1C). During each step,

infectious nodes independently attempted to infect their susceptible neighbors with a transmission rate β, and

transitioned to R (recovered) after an infectious duration γ. We fixed γ at 1 following previous studies [13,26]

and calculated β to achieve target R_0 values using the relationship $\beta = R_0/((< k^2 > - < k >)/< k >)$, where

$< k >$ and $< k^2 >$ are the mean degree and the mean squared degree, respectively [27]. To explore varying

transmissibility on the results, we used $R_0=3.0$ for the main analyses to represent a moderately high transmission

scenario that ensures sufficient epidemic spread for robust comparison across surveillance strategies. Sensitivity

analyses were conducted using $R_0=1.5, 2.0, 2.5$.

Surveillance performance assessment

The surveillance performance of a sentinel network was evaluated as its ability to enable early detection of ongoing

infectious disease transmission following previous studies [13,28-30]. Formally, given a predefined number of

sentinel nodes l, we seek a subset $S = \{\theta_1, \theta_2, \ldots, \theta_l\}$ of nodes in the network that maximize the objective function

$\Phi(S)$, which was defined as the average difference between the full outbreak size and the outbreak size at the time

of detection (i.e., when the outbreak first reaches any node in S) across 1,000 simulated disease outbreaks.

Conceptually, Φ(S) can be treated as the average number of cases that can be prevented by S when timely control

measures are implemented after detection. Mathematically, Φ(S) can be expressed as:

$$\Phi(S) = \sum_{i=1}^{1000}[IR(\infty)_i - IR(\min_{s \in S}(infection\,time\,of\,s))_i] \qquad (1)$$

197 where $IR(t)$ is the total number of nodes in the states I and R at time t. We additionally defined Φ(S_{all}) as the

198 objective function value when all nodes were included in S, representing the ideal surveillance performance under

199 unlimited resources and serves as a benchmark for quantifying the relative performance of a given surveillance

200 design. The impact of sentinel network size l on surveillance performance was further examined in *Changes of*

201 *early detection performance with the number of sentinel nodes.*

Optimal sentinel node selection using a genetic algorithm

We first used a genetic algorithm (GA), widely applied in surveillance system optimization [31-34], to identify the

optimal subset of l nodes in the network that maximizes the objective function Φ(S), as exhaustive enumeration is

computationally infeasible in large networks. The results of GA provide a benchmark for evaluating less

computationally intensive node selection strategies; also, the optimal sentinel subset identified by GA can be used

to understand key node characteristics contributing to early detection performance.

The GA process began by randomly generating 100 sets of l nodes as the initial population and evaluating the

objective function value (also referred to as *fitness* in the context of GA) for each set (referred to as *individual* in

GA). Then, these initial 100 individuals were sampled with replacement with the sampling probability of each

individual proportional to its fitness, and randomly matched to 50 pairs. Each pair then produced two offspring for

the next generation, with crossover and mutation happened with probabilities of $p_{crossover} = 0.8$ and $p_{mutation} = 0.05$,

respectively, consistent with previous studies [35-37]. We applied the uniform crossover method to recombine

parent solutions [38]. Specifically, if the two parent individuals are $F_1 = \{F_{11}, F_{12}, …, F_{1l}\}$ and $F_2 = \{F_{21}, F_{22}, …,$

$F_{2l}\}$, where each F_{ij} represent a node ID, the two offspring (O_1 and O_2) were generated by independently

determining node inheritance at each position through random number generation. For each position i ($1 \leq i \leq l$), a

random number was drawn from a uniform distribution between 0 and 1. If the number was less than 0.5, O_1

inherited F_{1i} and O_2 inherited F_{2i}, otherwise the assignments were swapped. When duplicate nodes appeared in an

offspring, they were removed and the gaps were filled by randomly selecting unused nodes from the network G.

When mutation occurred, a randomly chosen node in the offspring was replaced with a randomly selected unused

node from network *G*. This evolutionary process was repeated iteratively until both the fitness value and node

composition kept stable over 30 consecutive generations.

Random forest-based surrogate model

Since the optimization process is computationally intensive and time consuming, we attempted to develop less

demanding surrogate models to facilitate sentinel nodes selection within a shorter time frame. By observing the

optimal node sets selected by GA under various settings and drawing on previous literature [13,39-50], we

identified 28 characteristics that may influence the surveillance performance of a given node set, which were

further grouped into 6 categories (Table 2). We chose to use a random forest given its ability in learning complex

nonlinear relationships and high-order interactions between predictors, resisting overfitting via ensembling and

providing accessible measures for variable importance [51,52]. The model was trained based on simulation data

generated from synthetic modular networks and validated on both synthetic scale-free and empirical networks. We

also used the fitted model to quantify the relative importance of these characteristics in determining node

surveillance performance (see *Key node characteristics determining early detection performance*).

Table 2. All candidate global- and node-specific characteristics considered in RFSM. Characteristics shown in bold indicate those selected in the final model.

Category	Characteristic	Description	Source
Global emergence probability-related (Global prob.)	**prob_mean**	**Mean emergence probability of all nodes**	[39]
	prob_std	Standard deviation of emergence probabilities across all nodes	[39]
	prob_skewness	Skewness of the distribution of node emergence probabilities	[39]
	prob_kurtosis	Kurtosis of the distribution of node emergence probabilities	[39]
Global network topology-related (Global topo.)	**density**	**The ratio of the actual number of edges in the network to the maximum number of edges it can accommodate:$2E/N(N–1)$, where N and E refer to the number of nodes and edges in the**	[40,41]

		network, respectively	
	avg_clustering	Mean local clustering coefficient across all nodes	[42]
	avg_degree	**Mean number of connections per node**	**[41]**
	degree_variance	Variance of the degree distribution	[39,41]
	degree_skewness	**Skewness of the degree distribution**	**[39]**
	degree_kurtosis	Kurtosis of the degree distribution	[39]
	avg_path_length	Average shortest path length between node pairs (calculated on the largest connected component)	[40,42]
Node emergence probability-related (Node prob.)	**probability**	**Emergence probability of the node**	**GA**
	avg_neighbor_prob	Mean emergence probability of the node's neighbors	[43]
	std_neighbor_prob	Standard Variation in emergence probabilities among the node's neighbors	[43]
Node network topology-related (Node topo.)	**degree_centrality**	**Node degree normalized by maximum possible degree (N–1): $degree(i)/(N–1)$, where N refer to the number of nodes in the network**	**GA, [13,44]**
	betweenness_centrality	**The proportion of all node-pairs' shortest paths that pass through the node**	**[42,44]**
	eigenvector_centrality	**Node's influence based on being connected to other high-influence nodes: $\sum_{u \in neighbor(i)} EC_u/\lambda$, where EC_u and λ refer to the eigenvector centrality of node u and largest eigenvalue of the adjacency matrix, respectively**	**[44]**
	clustering_coeff	The proportion of a node's neighbors that are also connected to each other	[42]
	local_density	**Edge density of the subgraph formed by the node and its neighbors**	**[44]**
	avg_neighbor_degree	Mean degree of the node's neighbors	[42]

Node emergence-weighted topology (Node prob.& topo.)	**prob_weighted_degree**	**Node degree multiplied by its emergence probability**	[45]
	prob_weighted_clustering	Node clustering coefficient multiplied by its emergence probability	[46]
	prob_weighted_distance	Probability-weighted closeness centrality: inverse distance to all nodes, weighted by their emergence probabilities	[47]
Dynamic selection-related (Selection dynamics)	min_dist_to_selected	Minimum shortest-path distance from the node to the nearest selected sentinel node	[48]
	neighbor_selected_ratio	**The proportion of a node's neighbors that have already been selected as sentinel nodes**	[13,49]
	synergy_score	**Average reciprocal distance to already-selected nodes that are more than two hops away (captures complementary coverage)**	GA, [13,50]
	redundancy_score	**Average reciprocal distance to already-selected nodes within two hops (captures overlap or redundancy)**	GA, [13,49,50]
	new_coverage_ratio	**The proportion of nodes newly covered (itself and its neighbors) beyond the coverage provided by the already-selected surveillance set**	GA, [13]

Training data. We first generated 1,000 random modular networks using parameter sets randomly sampled from the ranges in Table 1 to ensure network structure diversity in the training data. To maintain sufficient complexity for meaningful pattern learning, we excluded four networks with fewer than 20 nodes or exhibiting extremely low emergence probability variance ($\sigma_p < 0.005$). For each remaining network, we simulated 1,000 outbreaks and calculated the node characteristics listed in Table 2 as the independent variables. Near-optimal sentinel nodes were identified stepwise using a greedy algorithm that selects one node at a time iteratively from the remaining unmonitored nodes to maximize the marginal gain in $\Phi(S)$, and the relative selection order of each node was

recorded as the dependent variable for model fitting (e.g., a node selected in the 3rd step was assigned a value of

3/N where N is the network size), since we found that the greedy algorithm performs comparably to the GA while

being more computationally efficient (Fig. 5). We used relative rank order, rather than the surveillance performance

value $\Phi(S)$, as the dependent variable, since in real-world applications the order of sentinel node selection will be

used to guide sentinel site selection rather than the absolute value of $\Phi(S)$. In addition, the value of $\Phi(S)$ varied

substantially with network size and R_0, introducing unnecessary variability into model training. Only nodes ranked

the top 30% from each network were used to fit the model, since the primary objective was to identify the most

influential nodes rather than establishing a complete network-wide ordering. This process yielded a final dataset of

30,815 node-ranking pairs. We also repeated the analyses using the top 20% and 10% nodes, resulting in 20,800

and 10,663 node-ranking pairs, respectively.

Model fitting. We randomly split the dataset into a training (70%) and a testing set (30%) based on network

membership, ensuring that all nodes from the same network were assigned to the same partition. A random forest

model was fitted to the training set using all features listed in Table 2 as independent variables and the selection

order derived from the greedy algorithm as the dependent variable. Hyperparameters, including the number of trees,

maximum tree depth, minimum split and leaf sizes, feature sampling ratio, and bootstrap sample ratio, were tuned

by Bayesian optimization with five-fold cross-validation to minimize the normalized discounted cumulative gain

(NDCG@k) between observed and predicted ranks as the optimization metric [53]. NDCG was chosen over the

commonly used mean squared error (MSE) because it directly measures the consistency between predicted and

observed ranks, which better aligns with real-world applications, where the ordering of sentinel node selection

matters more than the absolute magnitude of prediction errors. NDCG@k was calculated as:

267
$$\text{NDCG@k} = \frac{\sum_{i=1}^{\lceil k \cdot n \rceil} \frac{rel(pred_i)}{\log_2(i+1)}}{\sum_{i=1}^{\lceil k \cdot n \rceil} \frac{rel(observed_i)}{\log_2(i+1)}}$$
(2)

where k represents the percentage of top-ranking nodes considered in the performance measure, n represents the

total number of nodes in the network, $\lceil \cdot \rceil$ is the ceiling function, $pred_i$ and $observed_i$ represent the ith node in the

ranking lists produced by the model and the *greedy* algorithm, respectively, and $rel(\cdot)$ represents the relevance

scoring function of a node, which refers to the inverse rank of the node within the observed list (e.g. the relevance

score of the first node in the observed list $rel(observed_1)$ is N for a network with N nodes). NDCG@k ranges from

0 and 1, with 1 indicating that the predicted ranking matches the observed ranking. Permutation importance scores,

defined as the decrease in NDCG after randomly permuting a given feature while keeping the other features

unchanged, were obtained from the trained model with the optimal hyperparameters. Features with importance

scores less than 0.01, a threshold value chosen based on a natural elbow in the importance ranking distribution (Fig.

S2) that clearly distinguished influential features from other features, were excluded and hyperparameters were

reoptimized on this reduced feature set using the same procedure. After evaluating the model performance on the

testing dataset, the final model was refitted on the entire dataset with the optimal hyperparameters and used for

further analyses.

Model validation. We externally validated the performance of RFSM on the unseen synthetic scale-free and

empirical networks. For each network, node characteristics listed in Table 2 were computed as the inputs to the

trained RFSM. Sentinel node sets were then defined based on the predicted selection ranks, and their performance

was evaluated and compared against alternative surveillance strategies described below.

Benchmarking against alternative surveillance strategies. We evaluated the performance and computational

efficiency of RFSM against five alternative surveillance strategies (Fig. 2), including selection of nodes with the

highest degree in the whole network (*Global*), selection of nodes with the highest degree within their module

(*Modular*, for synthetic scale-free and empirical networks, modules were partitioned by an improved version of the

Louvain modularity algorithm [54] in Gephi [55]), random selection (*Random*), genetic algorithm-based selection

(*GA*), and stepwise greedy selection (*Greedy*). These alternative strategies fall into two board categories: those

relying solely on network topology without outbreak simulations (Figs. 2A–C, *Global*, *Modular* and *Random*) and

those requiring outbreak simulations (Figs. 2E–F, *GA* and *Greedy*). Although the first group is computationally

efficient, they may ignore nodes with high emergence probabilities or with high transmission capacity but moderate

degree, such as bridge nodes with high betweenness centrality that connect different modules, or nodes embedded

in high-risk neighborhoods that can accelerate secondary spread. In contrast, the second group, which involves

outbreak simulations, can dynamically adjust sentinel node selection strategy by simulating the epidemic

propagation process, enabling more accurate assessment of each node's surveillance potential, but are at

substantially higher computational cost. RFSM lies between these two categories as it requires simulations during

model training by the developers, but not during applications by end users once the model is fitted. To ensure

comparability, all strategies were benchmarked on identical network configurations and emergence probability

settings.

Performance with incomplete network structure data. In real-world applications, the network structures are often

only partially observed. To evaluate the robustness of the RFSM results to incomplete network structure

observation, we randomly removed 10–90% of the nodes or edges from the complete network and applied RFSM

to the resulting incomplete networks. Surveillance performance was evaluated on the original complete network

prior to node (or edge) removal. The removal process was repeated 10 times to account for uncertainty in the

removal process. Network and model parameters were set as $N_m = 5$, $N_n = 20$, $\mu = 5$, $\sigma = 8$, $p = 0.8$, $a = 0.1$, $b = 5$, ρ

$= -0.7$ and $R_0 = 3.0$, as in the baseline scenario. We examined the scenarios when selecting 3, 6, or 9 sentinel nodes,

since we found selecting only 6 sentinels can already achieve a high surveillance performance (Fig. 7).

Figure 2. Schematic representation of six surveillance strategies. Red circles indicate nodes that are selected to

be sentinel nodes, and colored backgrounds denote network modules.

Online platform for RFSM. To support real-world applications of RFSM, especially in resource- and

research-limited regions, we further developed an online platform

(https://lunawang.shinyapps.io/sentinel_nodes_selection/). After uploading the network structure and node-specific

emergence probability and specify the desired number of sentinel nodes, the platform can provide the optimal

sentinel node set selected by RFSM, as well as visualizes the selected nodes within the network to aid

interpretation.

Changes of early detection performance with the number of sentinel nodes

We further investigated how early detection performance evolved with the number of sentinel nodes across each surveillance strategy. Specifically, we began with a single sentinel node and gradually increased the number of sentinel nodes until further additions yielded negligible performance gains. This approach allowed us to identify an optimal threshold that minimize the number of sentinel nodes to conserve resources while maintaining reasonable surveillance performance. Additionally, we examined whether this optimal threshold varied with network structure and size by using diverse synthetic and empirical networks with varying topology and sizes.

Key node characteristics determining early detection performance

Overall feature and category importance. We obtained the permutation importance score for each feature in the final model with the method described above. To further assess the relative contribution of network topology and emergence probabilities, we calculated the group importance of each characteristic category (Table 2) through simultaneously permuted all features within the category while keeping features in the other categories unchanged. The resulting decrease in NDCG was recorded at the permutation importance for the entire category.

Rank-specific feature and category importance. To understand how the relative contributions of node characteristics evolved across selection steps (i.e., which characteristics were prioritized when only few sites were chosen, and which became more important as the sentinel set expanded), we trained separate random forest models for each selection rank k (i.e., $k = 1$ corresponds to the first node selected in the stepwise process). In each model, nodes whose rank $k_i = k$ were labeled as positive, nodes with $k_i > k$ as negative, while nodes with $k_i < k$ (i.e., nodes already chosen at earlier ranks) were excluded, ensuring that each model specifically learned to identify the next sentinel from the remaining pool. When $k = 1$, dynamic selection-related features were excluded because no nodes had yet been chosen; otherwise, all features were included. Permutation importance was then computed for each rank-specific model and normalized within each rank so that the scores summed to 1. We focused on the first ten sentinel nodes, since changes in the relative importance of characteristics became negligible thereafter (Fig. S8).

Sensitivity analysis of feature importance. To examine whether the relative contributions of node characteristics remained stable across diverse network structure and emergence probability distribution, we conducted sensitivity analyses through refitting models after stratifying the dataset into quintiles based on total number of nodes ($N=N_m \times N_n$), mean degree (μ), variance of degree (σ), within-module connection probability (p), kurtosis of the emergence probability distribution (derived from parameters a and b, quantifying the shape and heterogeneity of

assigned probabilities), and correlation coefficient between node degree and emergence probability (ρ). For each

parameter, the quintile-based datasets were labeled G1–G5, with G1 representing the lowest and G5 the highest

values. Thresholds used for stratification for each parameter are shown in Fig. S3. We also performed sensitivity

analysis by varying the basic reproduction number (R_0) used in the SIR simulations to assess the robustness of

feature importance under varying epidemic transmissibility. While the main training dataset corresponded to $R_0 = $

3.0, three additional datasets were generated under $R_0 = $ 1.5, 2.0, and 2.5 and the remaining network and probability

parameters were also randomly sampled from the ranges listed in Table 1. These four datasets were labeled G1–G4

in ascending order of R_0 (i.e., G1 = 1.5, G2 = 2.0, G3 = 2.5, and G4 = 3.0).

All the analyses in this study were conducted using Python 3.12.4 and R 4.4.1. In Python, we used packages

networkx 3.3 [25] for generating and loading networks, EoN 1.2 [56] for disease simulation and surveillance

performance assessment, scikit-learn 1.7.0 [57] for RFSM and permutation importance, pandas 2.2.2 [58] and

numpy 2.0.1 [59] for data processing. Visualizations were primarily generated using matplotlib 3.9.1 [60] and

seaborn 0.13.2 [61] in Python, and further refined using packages ggplot2 3.5.2 [62], cowplot 1.2.0 [63] and ggsci

4.0.0 [64] in R. All the code and data used in the analyses are publicly available at:

https://github.com/qu-cheng/EID_optimization.

Results

Optimal sentinel nodes selected by GA

We examined the optimal sentinel node sets selected by GA across various synthetic networks to identify key node characteristics associated with early detection performance. For illustrative purposes, we only present results of $l = 6$ sentinel nodes for a modular network with $N_m = 5$, $N_n = 20$, $\mu = 5$, $\sigma = 8$, $p = 0.8$, $a = 0.1$, and $b = 5$ (Figs. 3A and 3B) and a synthetic scale-free network (Figs. 3C and 3D), both with a correlation of $\rho = -0.7$ between node degree and emergence probability. When emergence probabilities were homogenous across all nodes, sentinel selection prioritized nodes with the highest degrees (Figs. 3A and 3C). By contrast, when emergence probabilities were heterogenous, the optimal set reflected a balance between node degree and emergence probability (Figs. 3B and 3D). For example, in the baseline network, the optimal sentinel set include the node with the highest emergence probability (Fig. 3B), while in the scale-free network, selected nodes include both the node with the highest emergence probability and its neighbor (Fig. 3D). Furthermore, optimal sentinel nodes were typically distributed across the network, reducing redundancy and maximizing surveillance coverage. Based on these findings, we included characteristics related to node centrality, emergence probability, and especially dynamic aspects such as redundancy and coverage into subsequent analyses (Table 2).

Figure 3. Optimal sentinel nodes selected by GA on synthetic networks. Comparison of GA-selected optimal

sentinel nodes in (A) a modular network and (B) a scale-free network under homogenous emergence probabilities,

and in (C) a modular network and (D) a scale-free network under heterogenous emergence probabilities. In (A) and

(C), each node was assigned the same emergence probability of 0.1, while in (B) and (D), they were sampled from

Beta (0.1, 5) with a correlation of ρ = -0.7 between node degree and emergence probability. The basic reproduction

number R_0 was set to 3.0. Node color and size indicate their emergence probability and degree, respectively.

Optimal sentinel nodes selected by GA were highlighted in green for the homogenous scenario, while in red for the

heterogenous scenario.

Random forest-based surrogate model performance

During feature selection, 14 of the 28 features were retained for further analysis (highlighted in Table 2 in bold, Fig.

S2). The final RFSM demonstrated strong predictive performance on both the training and testing datasets for the

synthetic modular networks, achieving NDCG@30% values of 0.978 and 0.954, respectively (Fig. 4A). Moreover,

the model also performed well on various validation networks, with NDCG@30% ranging between 0.943 for the

university network to 0.996 for the high school network. These consistently high values underscore the model's

robust predictive capability on unseen data, even across networks with entirely different topological patterns.

Figure 4. Performance of the final RFSM. (A) Model performance on the training and test datasets (vertical

dashed line indicates the top 30%). (B–F) Evaluation of the trained RFSM across five networks: (B) synthetic

scale-free, (C) university, (D) high school, (E) Facebook, and (F) wild bird contact networks. Each panel shows the

relationship between observed and predicted node rankings, with model accuracy summarized by the normalized

discounted cumulative gain (NDCG@30%) metric.

Benchmarking RFSM against alternative surveillance strategies

When compared with alternative sentinel site selection strategies across diverse synthetic and empirical networks,

the GA consistently has the highest early detection performance, followed by the *greedy* algorithm. The RFSM

demonstrated comparable performance relative to *greedy*, and outperformed the network structure-based

approaches, including g*lobal*, *modular,* and *random* selection, especially on the empirical networks (Figs. 5 and S4

for *random*). While achieving near-optimal surveillance performance across diverse network topologies, RFSM's

most notable advantage lies in its exceptional computational efficiency (Fig. 5A), which scales nearly linearly with

network size. It required less than 0.08 seconds for networks with 200 nodes, compared with 8 seconds for *greedy*

algorithm and 1,965 seconds for the *GA* for the same network on a high-performance cluster node with 256 GB of

RAM and two 28-core 2.7 GHz Intel Xeon Gold 6258R processors (Supported by High Performance Computing

Platform of Huazhong University of Science and Technology). The network structure-based methods demonstrated

superior computational efficiency with near-constant runtime, but their performance tend to be lower than RFSM.

Figure 5. Surveillance and computational performance comparison across different networks. (A) Runtime

(y-axis) is plotted against network size (x-axis) for RFSM, *Greedy*, *Global* and *Modular*. All synthetic networks

maintain same topological properties ($N_m = 5$, $N_n = 20$, $\mu = 5$, $\sigma = 8$, and $p = 0.8$) to the modular network with only

node count varying from 50 to 500 and all measurements represent average runtime over 100 runs for selecting 6

sentinel nodes. (B–G) Each panel shows the surveillance performance (y-axis, defined as the number of infected

nodes prevented) as a function of the number of sentinel nodes (x-axis) for different node selection strategies. The

blue dashed line represents the surveillance performance of monitoring all nodes in networks. Error bars indicate

standard deviation across 100 simulation runs. For each network, node emergence probabilities were sampled from

Beta (0.1, 5) distribution, with correlation coefficient (ρ) of -0.7 between node degree and emergence probability,

and basic reproduction number (R_0) set to 3.0.

Although the surveillance performance of RFSM decreased with increasing proportion of node and edge removal,

as expected, it remained comparable to that of GA, *global*, *greedy*, and *modular* strategies, and consistently

outperformed the *random* strategy (Fig. 6). Similar patterns were observed when selecting 3 or 9 sentinel nodes

(Figs. S5–6).

Figure 6. Surveillance performance under incomplete network structure observation when 6 sentinel nodes were selected. (A) shows results for edge removal, while (B) shows results for node removal. Columns (i–vi) correspond to different network types: Modular, Scale-free, University, High school, Facebook, and Wildbird. For each panel, the x-axis denotes the proportion of removed edges or nodes, and the y-axis represents mean surveillance performance, defined as the number of infected nodes prevented. Solid lines indicate average performance across simulations, and shaded areas represent variability across 10 repetitions.

Changes of early detection performance with the number of sentinel nodes

Across all examined synthetic and empirical networks, the surveillance performance of all strategies improved with the number of sentinel nodes increased, though the marginal gain diminished as the sentinel set grew, especially beyond 6 sentinel nodes, where additional nodes yielded minimal improvement (Fig. 5B–G). To assess whether this

optimal number of sentinel nodes scales with network size, we generated modular and scale-free networks of

varying sizes and compared surveillance performance when all nodes, 6 nodes, or 6% of nodes were included as

sentinels (Fig. 7). Results showed that while monitoring all nodes provided the best performance, using just 6

sentinel nodes offered substantial efficiency, performing comparable to monitoring 6% of nodes, suggesting that a

small set of strategically chosen sentinels can achieve high surveillance performance without requiring proportional

increase in the number of nodes.

Figure 7. Surveillance performance comparison across network scales and types. Surveillance performance

comparison across three monitoring scenarios: complete surveillance where all nodes are monitored, targeted

surveillance using 6 RFSM-selected sentinels, and targeted surveillance using 6% of RFSM-selected sentinels.

Performance comparisons are shown for (A) modular networks of different sizes, (B) scale-free networks of

different sizes, and (C) four empirical networks (university, high school, Facebook, and wild bird contact networks).

Surveillance performance (y-axis) represents the number of infected nodes prevented through early detection by the

selected sentinel nodes. Each data point represents mean performance over 100 simulation runs, with error bars

indicating standard deviation. For each network, node emergence probabilities were sampled from Beta (0.1, 5)

distribution, with correlation coefficient (ρ) of -0.7 between node degree and emergence probability, and R_0 set to

3.0.

Key node characteristics determining early detection performance

Overall feature and category importance. Feature importance analysis of the retained features highlighted dynamic

selection features as the dominant determinants of early detection performance (Fig. 8B), among which the

proportion of a node's neighbors already chosen as sentinels (*neighbor_selected_ratio*) was the most influential,

showing a negative effect that nodes with many sentinel neighbors were less likely to be chosen (Fig. S7),

reflecting the model's tendency to minimize redundancy in coverage. Other important dynamic features included

the average reciprocal distance to already-selected nodes beyond two hops away (*synergy_score*) and the proportion

newly covered nodes (*new_coverage_ratio*), both suggesting a preference for nodes that extend cooperative

coverage and extend monitoring into previously unobserved regions. Global network topology-related features

ranked second in importance (Fig. 8B), with network density (*density*) being the most important variable in this

category (Fig. 8A), highlighting the role of overall network connectivity in shaping sentinel selection dynamics.

Node network topology-related features are the third most important (Fig. 8B), with centrality and local

connectivity features (e.g., degree centrality *degree_centrality*, betweenness centrality *betweenness_centrality*,

eigenvector centrality *eigenvecgtor_centrality*) providing modest improvements in predictive accuracy (Fig. 8A). In

contrast, features related to emergence probability, both direct and topology weighted, contributed relatively little to

the predicted surveillance performance (Fig. 8).

Figure 8. Overall feature and category importance of the RFSM. (A) Permutation importance of individual

features, colored by category. (B) Grouped permutation importance of feature categories ordered by importance

scores. Bars represent the mean permutation importance scores across 100 repetitions, with error bars showing the

standard deviations.

Rank-specific feature and category importance. Stratifying feature importance by rank of selection revealed a clear

shift in the determinants of early detection performance across selection stages (Fig. 9). For the first sentinel site,

node and global-level network topology features dominated, with *betweenness_centrality* as the most important

individual feature (Fig. S8). At later stages, dynamic selection features became the primary determinants, though

their relative contribution gradually decreased with increasing selection rank (Figs. 9 and S8). Within this category,

neighbor_selected_ratio, *redundancy_score* and *synergy_score* were more important than *new_coverage_ratio*.

Node-level and global topology contributed modestly to early detection performance, but tended to gain slightly

higher relative importance as additional sites were selected. In contrast, all emergence probability-related categories,

including global and node emergence probability related, and node emergence probability-weighted topology

measures, played only minor roles across all selection stages.

Figure 9. Rank-specific feature importance at the category level. Heatmap shows the contribution of each

feature category across sentinel selection ranks. Rank-specific feature importance at the feature level can be found

in Fig. S8.

Sensitivity analyses. Across all sensitivity analyses, selection dynamics, global network topology, and node topology consistently showed the highest overall importance, while emergence probability-related categories remained comparatively less influential (Fig. 10). However, their exact relative contributions varied across stratifications. When stratified by the total number of nodes (N, Fig. 10A) or the within-module connection probability (p, Fig. 10D), node topology became slightly more important, whereas selection dynamics and node emergence probability showed a modest decline with increasing values of N or p. In contrast, increasing mean degree (μ, Fig. 10B) led to a continuous increase in the contribution of selection dynamics, accompanied by a reduction in probability-related importance. Although emergence probability-related categories were generally less influential, their importance tended to rise with increasing degree heterogeneity (σ, Fig. 10C) and kurtosis of the emergence probability distribution (Fig. 10E), while the importance of selection dynamics first increased and then decreased. When stratified by the correlation between node degree and emergence probability (ρ), node emergence probability became less important as ρ increases (Fig. 10F). After stratification based on the basic reproduction number (R_0), no differences were observed among categories (Fig. 10G). Individual feature-level results for each category are presented in Fig. S9.

When stratified by rank, at rank=1, structural features were consistently the most important category across all groups (Fig. S10). From rank=2 onward, although the importance of selection dynamics showed a declining trend, it remains the most significant category, whereas the importance of emergence probability-related categories tended to rise. The relative importance among all categories varied with stratification parameters in a manner consistent with non-rank specific comparisons. However, when stratified by degree heterogeneity (σ) and kurtosis of emergence probability distribution, the trend of reduced node topological importance becomes more obvious than in the non-rank analysis (Fig. S10). Rank-specific feature importance sensitivity analysis stratified by parameters were shown in Figs. S11–S17.

Finally, when using different proportion of top-ranked nodes for model training, dynamic features remained the most influential. As the proportion increased, node topology became less while emergence probability became more important, possibly because lower-ranked nodes are noisier and less informative, since their objective function values are very close to each other (Figs. S18–19).

Figure 10. Sensitivity of category-level feature importance under different stratification parameters. Mean

normalized importance of 6 categories across stratifications by (A) total number of nodes (N), (B) mean degree (μ),

(C) degree heterogeneity (σ), (D) within-module connection probability (p), (E) kurtosis of the emergence

probability distribution, (F) correlation between node degree and emergence probability (ρ), and (G) basic

reproduction number (R_0). Each bar represents the mean importance within one parameter group (G1–G5), with

error bars indicating standard errors across 100 repetitions.

Discussion

Nodes in complex networks often exhibit varying probabilities of being the initial seed for infectious disease outbreaks, determined by their environmental, behavioral or biological characteristics (e.g., animal markets, transportation hubs). This important heterogeneity is however typically overlooked in studies about the selection of sentinel surveillance nodes on complex networks. In this study, through simulations of outbreaks on both synthetic and empirical networks, we demonstrated that early detection performance was affected by both network topology and emergence probability, with the former playing a dominant role. We developed a computationally efficient random forest-based surrogate model for selecting sentinel nodes, validated its surveillance performance and computational feasibility across different networks, and implemented an online platform to facilitate its real-world applications. These findings highlight the moderate added value of incorporating node-specific emergence probabilities into sentinel surveillance design on complex networks and offer practical guidance for improving early outbreak detection.

Our findings confirmed the critical role of network topology in determining early detection performance. For example, topological and dynamic selection features consistently contributed more to node selection than features related solely to node or global emergence probability across all ranks (Figs. 8–10). Importantly, rank□specific analyses revealed a strategic shift: at the first selection stage, sentinel choice is dominated by topological features, favoring structurally central nodes such as transportation hubs or dense marketplaces, which align epidemiologically with "superspreader" roles [65]. As the sentinel set expands, however, dynamic selection features like neighbor□selected ratio and synergy score become increasingly decisive, identifying nodes that maximize coverage while mitigating overlap. For instance, neighbor□selected ratio quantifies neighboring nodes already selected, thereby guiding an efficient, non□redundant expansion of surveillance coverage. This shift mirrors adaptive, subregional surveillance strategies and resonates with modeling studies advocating dynamic intervention on networks [66-68].

Although emergence probability-related features were consistently less influential, they still provided meaningful contributions, particularly under conditions of high degree heterogeneity or uneven emergence probability distributions (Fig. 10). These features capture spatial or nodal variability in outbreak likelihoods, which can refine sentinel placement by highlighting regions with elevated emergence potential. However, their overall importance remained lower than topological or dynamic features because network connectivity largely governs transmission reach and detection opportunities, often overshadowing intrinsic emergence probabilities. Moreover, when emergence probability strongly correlates with node degree, its information content becomes partially redundant

with structural attributes. Thus, effective surveillance design ultimately depends more on structural integration and

dynamic adaptability than on static emergence probability.

The strong predictive performance of the RFSM indicates that data-driven surrogate modeling can effectively

approximate the behavior of optimization-based approaches in sentinel site selection. By integrating key structural

and dynamic features, the RFSM achieves near-optimal early detection performance comparable to the greedy

algorithm while maintaining robust generalization across diverse networks. Its accuracy is particularly reliable for

the early stages of sentinel selection, where it was trained to emulate the greedy algorithm's decisions, but its

predictions become less precise in later selection steps as the underlying relationships between features and

performance weaken. As with most data-driven models, the RFSM's accuracy may also decline when applied to

networks whose structural or epidemiological relationships deviate substantially from those represented in the

training data. Furthermore, the effectiveness of different sentinel selection strategies, including RFSM, was also

closely tied to the heterogeneity of network structure. For instance, in the case of the university network, where

high-degree nodes are closely interconnected, the *global* strategy performed even worse than the *Random* strategy

as the number of sentinel nodes increased, likely due to the selection of neighboring nodes that capture essentially

redundant information (Fig. S4C). This observation highlights the importance of understanding network structure

when designing surveillance strategies, as densely interconnected high-degree nodes may lead to information

overlap, reducing the efficiency gains of topology-based strategies in heterogeneous networks [69,70]. Nevertheless,

the RFSM provides a practical balance between accuracy and computational efficiency, making it particularly

valuable for scalable or time-sensitive surveillance design.

Although the *greedy*, *GA*, and RFSM strategies all achieved high performance in early outbreak detection, their

computational burden differed substantially. The *greedy* algorithm iteratively evaluated all remaining candidate

nodes (n) at each of the l selection steps through s Monte Carlo simulations (Eq(1)), resulting in a time complexity

of $O(n{\times}l{\times}s)$. This process quickly becomes infeasible as network size or the number of simulations increases. GA

further amplifies this computational demand by evaluating multiple candidate solutions per generation and often

requires hundreds of generations to converge. In contrast, the RFSM replaces these iterative simulations with

predictive inference using a pre-trained model that performs well even on unseen networks. Each selection step

only requires computing node-level features and performing predictions, yielding a linear complexity of $O(n{\times}l)$.

This substantial reduction in computational cost highlights RFSM's suitability for large-scale, dynamic, or real-time

surveillance applications where traditional optimization methods are computationally prohibitive.

A key challenge in network epidemiology is the difficulty of obtaining the complete contact networks. Our analysis showed that sentinels selected from highly incomplete networks (e.g., missing 50% of edges) by RFSM performed nearly as well as those selected from complete networks, which implies that disease surveillance systems can be effectively designed even using data from rapid, partial assessments or sampled surveys, without requiring a full mapping of the contact network, thereby lowering barriers to implementation. This robustness likely arises because RFSM captures robust topological roles (such as bridge nodes or local connectivity patterns) rather than overfitting to specific, fragile connections. In contrast, strategies that rely solely on identifying the highest-degree nodes (*global*) can be more brittle if the true hubs are unobserved.

Our sensitivity analyses demonstrate how network topology and emergence probability characteristics affect the contribution of different features (Figs. 10 and S9–17). We found that the importance of selection dynamics increased with higher mean degree (μ) (Figs. 10B and S9), likely because nodes in more highly connected networks tend to convey overlapping information, which should be minimized during the node selection process. The rising importance of emergence probability-related features under greater degree heterogeneity (σ) and higher kurtosis of emergence probability distribution indicates that when risks are highly uneven or heavy-tailed, node-level emergence variability becomes more informative for monitoring placement. However, when degree and emergence probability are strongly correlated (ρ), this information is largely redundant with structural metrics, leading to reduced relative importance. The absence of clear R_0 effects suggests that variations in transmission potential do not fundamentally shift the structural-dynamic balance.

Our results also suggest that monitoring a small number of strategically selected nodes can achieve a high level of surveillance performance, as adding more sentinels yields progressively smaller performance gains. More specifically, we found that monitoring just six nodes can capture about 90% of the performance of the complete surveillance network monitoring all nodes, and notably, the required number of sentinel nodes did not scale with network size (Fig. 7). This conclusion is consistent with a global wastewater surveillance study, which found that 10–20 optimally placed wastewater sentinel sites across more than 4,000 international airports were sufficient to provide timely situational awareness [71]. One possible explanation is that, when sentinel nodes cover nodes with high emergence probabilities, even a small number of nodes can effectively interrupt the most potential transmission chains.

Several limitations must be acknowledged when interpretating the results. First, we assumed that node-specific emergence probabilities are known, which may not be directly observable in practice. Although some studies have attempted to infer spatial heterogeneity in emergence probabilities based on past emerging infectious disease events

and factors like land use patterns, human population density, and wildlife and livestock distributions [1,6,11], more

detailed data, such as wildlife habitat, villagers' hunting trajectories, and forest contact frequencies, can be further

incorporated to better characterize the spatial distribution of EID emergence probabilities [72,73]. Second, we

represented contact patterns as unweighted, undirected and static graphs, which may not fully capture the

complexity of real-world interactions. Extending the RFSM framework to temporal [29], weighted, or multilayer

networks [74,75] would further enhance its applicability to practical surveillance system design. Third, we assumed

that the cost of placing each sentinel node is the same. Future work can assign different costs to different nodes

based on their accessibility and introduce constraints on total cost or incorporate total cost as an additional

objective in a multi-objective optimization framework. Fourth, our simulations considered only single-seed

outbreaks, whereas in reality multiple introductions may occur simultaneously or repeatedly. Under such scenarios,

the relative importance of emergence probabilities may increase, as multiple seeding events amplify the influence

of initial outbreak locations on surveillance performance. Finally, we focused exclusively on respiratory infections

and used the simplest SIR model, assuming perfect detection for the infectious nodes. Future studies can

incorporate more complex transmission dynamics and detection rate to improve the generalizability of the

framework to a wider range of infectious diseases.

In conclusion, through simulations and machine learning models, we found that node-specific emergence

probabilities significantly enhance early outbreak detection performance, though their influence is secondary to

network topology. Notably, approximately 90 percent of the surveillance performance can be achieved with as few

as six sentinel nodes, and the required sentinel size does not scale with network size. Leveraging key node

characteristics identified in our analysis, we developed a computationally efficient surrogate model for optimal

sentinel selection on complex networks and validated its surveillance and computational performance on empirical

networks. This model was further implemented as an online platform. Our findings underscore the importance of

accounting for heterogeneity in node-specific emergence probability when designing sentinel surveillance system

on complex networks and provide a practical and scalable solution that can be readily applied in real-world settings,

especially when resources and technical capacity are limited.

References

1. Jones K E, Patel N G, Levy M A, Storeygard A, Balk D, Gittleman J L, *et.al.* Global trends in emerging infectious diseases. *Nature*, 2008, 451(7181): 990-3.

2. GOV.UK. Emerging infections: how and why they arise. [2025-05-01]. https://www.gov.uk/government/publications/emerging-infections-characteristics-epidemiology-and-global-distribution/emerging-infections-how-and-why-they-arise.

3. Morens D M, Fauci A S. Emerging Pandemic Diseases: How We Got to COVID-19. *Cell*, 2020, 182(5): 1077-1092.

4. Tan-Torres Edejer T, Hanssen O, Mirelman A, Verboom P, Lolong G, Watson O J, *et.al.* Projected health-care resource needs for an effective response to COVID-19 in 73 low-income and middle-income countries: a modelling study. *Lancet Global Health*, 2020, 8(11): e1372-e1379.

5. Statista. Impact of the coronavirus pandemic on the global economy - Statistics & Facts. [2025-05-20]. https://www.statista.com/topics/6139/covid-19-impact-on-the-global-economy/#topicOverview.

6. Allen T, Murray K A, Zambrana-Torrelio C, Morse S S, Rondinini C, Di Marco M, *et.al.* Global hotspots and correlates of emerging zoonotic diseases. *Nature Communications*, 2017, 8(1): 1124.

7. Mollentze N, Streicker D G. Viral zoonotic risk is homogenous among taxonomic orders of mammalian and avian reservoir hosts. *Proceedings of the National Academy of Sciences of the United States of America*, 2020, 117(17): 9423-9430.

8. Sharp P M, Hahn B H. Origins of HIV and the AIDS pandemic. *Cold Spring Harb Perspect Med*, 2011, 1(1): a006841.

9. Ayala G, Spieldenner A. HIV Is a Story First Written on the Bodies of Gay and Bisexual Men. *American Journal of Public Health*, 2021, 111(7): 1240-1242.

10. Conservation Medicine. Report 2009-14: Reducing Pandemic Risk, Promoting Global Health. (accessed June 20, 2025). https://conservationmedicine.org/projects/predict/.

11. Meisner J, Baines A, Ngere I, Garcia P J, Sa-Nguansilp C, Nguyen N, *et.al.* Mapping hotspots of zoonotic pathogen emergence: an integrated model-based and participatory-based approach. *Lancet Planet Health*, 2025, 9(1): e14-e22.

12. Herrera J L, Srinivasan R, Brownstein J S, Galvani A P, Meyers L A. Disease Surveillance on Complex Social Networks. *PLoS Computational biology*, 2016, 12(7): e1004928.

13. Colman E, Holme P, Sayama H, Gershenson C. Efficient sentinel surveillance strategies for preventing epidemics on networks. *PLoS Computational biology*, 2019, 15(11): e1007517.

14. Berahmand K, Bouyer A, Samadi N. A new local and multidimensional ranking measure to detect spreaders in social networks. *Computing*, 2019, 101(11): 1711-1733.

15. Zhong S, Zhang H T, Deng Y. Identification of influential nodes in complex networks: A local degree dimension approach. *Information Sciences*, 2022, 610: 994-1009.

16. Tulu M M, Hou R H, Younas T. Identifying Influential Nodes Based on Community Structure to Speed up the Dissemination of Information in Complex Network. *Ieee Access*, 2018, 6: 7390-7401.

17. Barabási A L, Albert R. Emergence of scaling in random networks. *Science*, 1999, 286(5439): 509-512.

18. Sapiezynski P, Stopczynski A, Lassen D D, Lehmann S. Interaction data from the Copenhagen Networks Study. *Scientific Data*, 2019, 6.

19. Fournet J, Barrat A. Contact Patterns among High School Students. *Plos One*, 2014, 9(9).

20. Maier B F, Brockmann D. Cover time for random walks on arbitrary complex networks. *Physical*
Review E, 2017, 96(4).

21. Firth J A, Sheldon B C. Experimental manipulation of avian social structure reveals segregation is
carried over across contexts. *Proceedings of the Royal Society B-Biological Sciences*, 2015,
282(1802).

22. Ryan A. Rossi, Nesreen K. Ahmed. The Network Data Repository with Interactive Graph Analytics
and Visualization. 2015. https://networkrepository.com.

23. Newman M E J. Modularity and community structure in networks. *Proceedings of the National*
Academy of Sciences of the United States of America, 2006, 103(23): 8577-8582.

24. Molloy M, Reed B. A critical point for random graphs with a given degree sequence. *Random*
Structures & Algorithms, 2007, 6(2-3): 161-180.

25. Hagberg, A., Swart, P., Schult, D., NetworkX Developers. NetworkX (Version 3.3).
https://networkx.org/.

26. Ball F, Britton T, Leung K Y, Sirl D. A stochastic SIR network epidemic model with preventive
dropping of edges. *Journal of Mathematical Biology*, 2019, 78(6): 1875-1951.

27. Meyers L. Contact network epidemiology: Bond percolation applied to infectious disease prediction
and control. *Bulletin of the American Mathematical Society*, 2007, 44.

28. Holme P. Objective measures for sentinel surveillance in network epidemiology. *Phys Rev E*, 2018,
98(2-1): 022313.

29. Bai Y, Yang B, Lin L, Herrera J L, Du Z, Holme P. Optimizing sentinel surveillance in temporal
network epidemiology. *Scientific Reports*, 2017, 7(1): 4804.

30. Schirdewahn F, Lentz H H K, Colizza V, Koher A, Hovel P, Vidondo B. Early warning of infectious
disease outbreaks on cattle-transport networks. *Plos One*, 2021, 16(1): e0244999.

31. Cheng Q, Collender P A, Heaney A K, Li X, Dasan R, Li C*, et.al.* The DIOS framework for
optimizing infectious disease surveillance: Numerical methods for simulation and multi-objective
optimization of surveillance network architectures. *PLoS Comput Biol*, 2020, 16(12): e1008477.

32. Cheng Q, Collender P A, Heaney A K, Mcloughlin A, Yang Y, Zhang Y*, et.al.* Optimizing
laboratory-based surveillance networks for monitoring multi-genotype or multi-serotype infections.
PLoS Comput Biol, 2022, 18(9): e1010575.

33. Sanchez C H, Smith D L, Marshall J M. MGSurvE: A framework to optimize trap placement for
genetic surveillance of mosquito populations. *PLoS Comput Biol*, 2024, 20(5): e1012046.

34. Holland J H. Genetic Algorithms and Adaptation, Adaptive Control of Ill-Defined Systems, 1984:
317-333.

35. Goldberg D E. Genetic Algorithms in Search, Optimization, and Machine Learning. *Addison-Wesley*
Pub, 1989.

36. Matrajt L, Halloran M E, Longini I. Optimal Vaccine Allocation for the Early Mitigation of Pandemic
Influenza. *PLOS Computational Biology*, 2013, 9(3).

37. Chattoraj M, Vinayakamurthy U R. A dynamic approach for parameter tuning in genetic algorithm
using crossover and mutation ratios. *Indonesian Journal of Electrical Engineering and Computer*
Science, 2022, 28(1).

38. Syswerda G. Uniform Crossover in Genetic Algorithms. *Proceedings of the 3rd International*
Conference on Genetic Algorithms, 1989: 2–9.

39. Lloyd-Smith J O, Schreiber S J, Kopp P E, Getz W M. Superspreading and the effect of individual
variation on disease emergence. *Nature*, 2005, 438(7066): 355-9.

40. Perez-Ortiz M, Manescu P, Caccioli F, Fernandez-Reyes D, Nachev P, Shawe-Taylor J. Network topological determinants of pathogen spread. *Sci Rep*, 2022, 12(1): 7692.

41. Poisot T, Gravel D. When is an ecological network complex? Connectance drives degree distribution and emerging network properties. *PeerJ*, 2014, 2: e251.

42. Danon L, Ford A P, House T, Jewell C P, Keeling M J, Roberts G O, *et.al.* Networks and the epidemiology of infectious disease. *Interdiscip Perspect Infect Dis*, 2011, 2011: 284909.

43. Newman M E J. Assortative mixing in networks. *Physical Review Letters*, 2002, 89(20).

44. Holme P. Three faces of node importance in network epidemiology: Exact results for small graphs. *Phys Rev E*, 2017, 96(6-1): 062305.

45. Candeloro L, Savini L, Conte A. A New Weighted Degree Centrality Measure: The Application in an Animal Disease Epidemic. *Plos One*, 2016, 11(11): e0165781.

46. Barrat A, Barthélemy M, Pastor-Satorras R, Vespignani A. The architecture of complex weighted networks. *Proceedings of the National Academy of Sciences*, 2004, 101(11): 3747-3752.

47. Donker T, Smieszek T, Henderson K L, Johnson A P, Walker A S, Robotham J V. Measuring distance through dense weighted networks: The case of hospital-associated pathogens. *PLOS Computational Biology*, 2017, 13(8): e1005622.

48. Hakimi S L. Optimum Locations of Switching Centers and the Absolute Centers and Medians of a Graph. *Operations Research*, 1964, 12: 450-459.

49. Yuan H, Gao C. Minimizing Redundancy in Wireless Sensor Networks Using Sparse Vectors. *Sensors (Basel)*, 2025, 25(5).

50. Luppi A I, Olbrich E, Finn C, Suárez L E, Rosas F E, Mediano P A M, *et.al.* Quantifying synergy and redundancy between networks. *Cell Reports Physical Science*, 2024, 5(4): 101892.

51. Breiman L. Random Forests. *Machine Learning*, 2001, 45(1): 5-32.

52. Boulesteix A L, Janitza S, Kruppa J, König I R. Overview of random forest methodology and practical guidance with emphasis on computational biology and bioinformatics. *Wiley Interdisciplinary Reviews-Data Mining and Knowledge Discovery*, 2012, 2(6): 493-507.

53. Järvelin K, Kekäläinen J. Cumulated gain-based evaluation of IR techniques. *ACM Transactions on Information Systems*, 2002, 20(4): 422–446.

54. Lambiotte R, Delvenne J C, Barahona M. Random Walks, Markov Processes and the Multiscale Modular Organization of Complex Networks. *IEEE Transactions on Network Science and Engineering*, 2014, 1(2): 76-90.

55. Bastian M, Heymann S, Jacomy M. Gephi: An Open Source Software for Exploring and Manipulating Networks. *Proceedings of the International AAAI Conference on Web and Social Media*, 2009, 3(1): 361-362.

56. Miller, J. C., Ting, T., EoN Contributors. EoN (Epidemics on Networks, Version 1.2). https://github.com/springer-math/Mathematics-of-Epidemics-on-Networks.

57. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, *et.al.* Scikit-learn: Machine Learning in Python (Version 1.7.0). *Journal of Machine Learning Research*, 2011, 12: 2825-2830.

58. McKinney, W., pandas Development Team. pandas (Version 2.2.2). https://pandas.pydata.org/.

59. Harris, C. R., Millman, K. J., van der Walt, S. J., NumPy Developers. NumPy (Version 2.0.1). https://numpy.org/.

60. Hunter, J. D., Matplotlib Development Team. Matplotlib (Version 3.9.1). https://matplotlib.org/.

61. Waskom, M. L., Seaborn Development Team. Seaborn (Version 0.13.2). https://seaborn.pydata.org/.

62. Wickham H. ggplot2: Elegant Graphics for Data Analysis. Springer-Verlag New York, 2016.
https://ggplot2.tidyverse.org.

63. Wilke C O. cowplot: Streamlined Plot Theme and Plot Annotations for 'ggplot2'. 2025.
https://CRAN.R-project.org/package=cowplot.

64. Xiao N. ggsci: Scientific Journal and Sci-Fi Themed Color Palettes for 'ggplot2'. 2025.
https://CRAN.R-project.org/package=ggsci.

65. Lieberthal B, Gardner A M. Connectivity, reproduction number, and mobility interact to determine
communities' epidemiological superspreader potential in a metapopulation network. *PLoS Comput*
Biol, 2021, 17(3): e1008674.

66. Sélley F, Besenyei A, Kiss I Z, Simon P L. Dynamic Control of Modern, Network-Based Epidemic
Models. *Siam Journal on Applied Dynamical Systems*, 2015, 14(1): 168-187.

67. Tsui J L H, Zhang M Y, Sambaturu P, Busch-Moreno S, Suchard M A, Pybus O G*, et.al.* Toward
optimal disease surveillance with graph- based active learning. *Proceedings of the National Academy*
of Sciences of the United States of America, 2024, 121(52).

68. Mastin A J, Gottwald T R, Van Den Bosch F, Cunniffe N J, Parnell S. Optimising risk-based
surveillance for early detection of invasive plant pathogens. *PLoS Biology*, 2020, 18(10): e3000863.

69. Chakraborty D, Singh A, Cherifi H. Immunization Strategies Based on the Overlapping Nodes in
Networks with Community Structure. *Computational Social Networks, Csonet 2016*, 2016, 9795:
62-73.

70. Sun C C, Wang Z X, Rui X B, Yu P S, Sun L C. An in-depth study on key nodes in social networks.
Intelligent Data Analysis, 2023, 27(6): 1811-1838.

71. St-Onge G, Davis J T, Hebert-Dufresne L, Allard A, Urbinati A, Scarpino S V*, et.al.* Pandemic
monitoring with global aircraft-based wastewater surveillance networks. *Nature Medicine*, 2025,
31(3).

72. Golchin M, Di Marco M, Horwood P F, Paini D R, Hoskins A J, Hickson R I. Prediction of viral
spillover risk based on the mass action principle. *One Health*, 2024, 18.

73. Grange Z L, Goldstein T, Johnson C K, Anthony S, Gilardi K, Daszak P*, et.al.* Ranking the risk of
animal-to-human spillover for newly discovered viruses. *Proceedings of the National Academy of*
Sciences of the United States of America, 2021, 118(15). https://spillover.global/.

74. Mossong J, Hens N, Jit M, Beutels P, Auranen K, Mikolajczyk R*, et.al.* Social contacts and mixing
patterns relevant to the spread of infectious diseases. *PloS Medicine*, 2008, 5(3): 381-391.

75. Patwardhan S, Rao V K, Fortunato S, Radicchi F. Epidemic Spreading in Group-Structured
Populations. *Physical Review X*, 2023, 13(4).