A Comparative Analysis in a Clinical Cohort: Multiple Imputation by

Chained Equations and a Novel Super Learner-Based Imputation

Approach

Tony Zbysinski[1], PhD ; Lezhou Wu[1], PhD; Justin Dale[1], BBA; James Coates[1], MS;

Karan Sapiah[1], MS; Jamie Reuben[1], MPH; Frank Markson[1], BA; Ujjwal Kulkarni[1], MS;

Nazmul Islam[1], PhD

[1]RefinedScience, Aurora, Colorado

Corresponding author:

Tony Zbysinski III, PhD

RefinedScience, 2115 N Scranton Street, Suite 2-70

Aurora Colorado, 80045, USA

Phone: +17637428523

Email: tony.zbysinski@refinedscience.com

Abstract

Background: Missing data is a challenge in clinical research, especially in real-world data (RWD), where complete case analysis can bias results and reduce power. Ensemble learning approaches like Super Learner (SL) show strong numerical performance for prediction problems, but their use for missing value imputation (MVI) in oncology datasets is unexplored. We sought to develop and evaluate a novel SL-based imputation function that can impute multiple variables and quantify observation-specific uncertainty.

Methods: We analyzed two independent cohorts of acute myeloid leukemia patients (n=1641), 546 patients from the University of Colorado and 1095 from an external real-world cohort. The SL-based MVI function includes data processing, predictor selection, binary and continuous variable pipelines, and automatic performance measurement. Ensembles for both binary and continuous variables integrate diverse base learners, such as generalized linear models, random forests, and neural networks, via a meta learner that optimizes predictive accuracy. The binary variable pipeline's SL ensemble was optimized using area under the curve (AUC), while the continuous variable pipeline's SL ensemble was optimized via non-negative least squares. Performance was compared to multiple imputation by chained equations (MICE) using balanced accuracy, F_1-score, root mean square error (RMSE), and visualizations. Observation-specific uncertainty was quantified for all imputations of both binary and continuous variables, with both additionally having lower and upper resampling-based potential imputation values. The SL cross-validation loop, SL ensemble trained for imputation,

and resampling all supported parallelization. Clinically significant features of the cohorts

were selected *a priori* based on prior literature.

Results: In a numerical experiment with 9 clinically important binary features, the

proposed MVI function imputed and achieved higher balanced accuracy than MICE for

7/9 variables (mean balanced accuracy 89.04% vs 80.75%) with comparable

performance for the other 2 variables. The continuous variable SL ensemble, across 4

variables, showed an average 24.45% lower RMSE than MICE. On average, the SL

ensemble trained for prediction took 145.02 seconds to process for binary targets.

Conclusions: This study demonstrates that the SL-based imputation function has

improved performance over MICE in high-dimensional RWD while providing novel,

observation-level uncertainty quantification.

MeSH keywords: Acute Myeloid Leukemia, Data Science, Machine Learning,

Uncertainty, Imputation, Missingness

Background

Data missingness is a common occurrence in clinical research and poses a
persistent threat to the validity of statistical inference and the strength of predictive
models. Missing values can arise for several reasons such as instrument failure, patient
dropout, or recording decisions driven by underlying patient characteristics (1,2). These
challenges lead to reduced statistical power, biased effect estimates, and compromised
precision, ultimately undermining predictive modeling efforts (3,4). As real-world data
(RWD) sources grow in volume and complexity, particularly in high-dimensional settings
such as electronic health records or genomic repositories, the challenge of appropriately
handling missingness increases. Traditional approaches like complete-case analysis
become unrealistic in many scenarios and can propagate selection bias (5).

Early work on missing data classified the mechanisms by which values are
missing. These include missing completely at random (MCAR), missing at random
(MAR), and missing not at random (MNAR). Such mechanisms are one part of
understanding which imputation approach is needed (3). Classical single and multiple
imputation techniques, such as mean/median/mode substitution or multiple imputation
via chained equations (MICE), provide straightforward and satisfactory solutions under
MCAR and MAR assumptions, but can perform poorly when these assumptions are
violated or when variable interdependencies are complex (6,7). Machine learning (ML)
methods including k-nearest neighbors (k-NN), random forests, support vector
machines, and others have typically demonstrated improved performance over purely
statistical methods, particularly for moderate missingness and MAR settings (7–9).
Deep learning approaches, such as generative adversarial imputation networks and

variational autoencoders, offer promise in capturing nonlinear relationships and high-

order interactions (5,10), but comparative studies against well-established algorithms

like missForest and MICE in RWD scenarios have shown that conventional methods

remain competitive or superior in practice at this time. This is likely due to the volume of

tuning parameters and the dataset size requirements of deep learning approaches (11).

Despite the broad array of available imputation strategies, no single method

uniformly or consistently outperforms others across mechanisms, domains, and

dimensionalities (12). In clinical settings, where variable distributions may be skewed

and the mechanisms of missingness are frequently a complex mix of MCAR, MAR, and

MNAR, ensemble learning techniques hold particular promise by combining multiple

base learners to hedge against model-specific weaknesses (12). The Super Learner

(SL) framework implements a stacking ensemble that uses cross-validation (CV)

specific risk estimates, risk being a term used for brevity when referring to objective

functions to optimally weight ML algorithms (e.g. minimizing mean squared error). In this

approach it combines the strengths of multiple semi-parametric or non-parametric

models to make a balanced single weighted imputation of missing values (13,14), unlike

MICE which is a more iterative process. It has been applied and tested for missing

value imputation (MVI) in previous literature, showing superior performance in at least

synthetic data compared to more popular methods such as MICE (15). Outside of MVI,

but within the clinical domain, SL-based approaches have yielded strong results for

numerous prediction-related tasks (16–20). However, SL's adoption for imputation in

clinical RWD has been limited despite its ability to outperform traditional methods. This

advancement is critical given the potential impact of imputation on downstream tasks,

such as treatment effect estimation, risk stratification, and clinical decision-making.

This study addresses a key gap in application by evaluating the performance of

MVI techniques using a SL-based approach on a high-dimensional dataset. In addition,

we build on this approach by introducing a novel function designed to greatly simplify

the imputation process with SL and provide measures of uncertainty for other modeling

tasks. The evaluation is conducted on clinical data comprising acute myeloid leukemia

(AML) patients treated with venetoclax plus azacitidine (Ven/Aza) or cytarabine plus

anthracycline (7+3). We experiment with varying missingness ratios and mixed or

unknown missingness mechanisms to reflect realistic challenges in clinical data

analysis. By benchmarking our SL-based imputation function against a conventional

statistical technique and selected ML methods, we aim to determine whether a SL-

based approach can deliver more robust and accurate imputations under clinical RWD

conditions and provide uncertainty measures for downstream tasks. Our specific

objectives are threefold: 1. Develop a novel user-friendly SL-based imputation function

capable of iteratively imputing multiple target variables while quantifying uncertainty

measures for other modeling purposes; 2. Apply the SL-based imputation function to

impute missing diagnostic patient AML data and quantify numerical performance of

singular learners of the ensemble; 3. Compare the SL-based imputation function's

predictive performance to state-of-the-art MICE performance. Note the proposed model

is disease-agnostic, much like most imputation approaches such as MICE, and thus can

be applied beyond AML without loss of generalizability. While we confine our objectives

to imputing baseline features for convenience, the function can be generalized and

extended to imputing values at other clinically relevant time-points.

Methods

Data Description

This study leveraged data from two cohorts (n=1641) of adult patients (aged ≥ 18

years) with newly diagnosed AML. Briefly, these patients were treated with Ven/Aza or

7+3. The University of Colorado (CU) cohort included 546 patients that began treatment

in a clinical trial between January 2015 and March 2024 in the UCHealth system. Data

is continuously updated over time as follow-up progresses, where follow-up ends at

date of death, loss to follow-up, or until the most recent follow-up update. We censor

patients only to their last known alive date. The Real World Cohort (RWC) was derived

from the nationwide Flatiron Health electronic health record-derived, de-identified,

longitudinal database consisting of patient-level structured and unstructured data

curated via technology enabled abstraction and was comprised of 1095 patients from 87

unique sites of care (21,22). Flatiron Health dataset patients had a minimum of two

documented clinical visits between January 2014 and December 2023 and received the

Ven/Aza treatment as frontline therapy. The de-identified data is sourced from

approximately 280 cancer clinics across the United States, including 800 sites of care

primarily within community oncology settings. Inclusion and exclusion criteria were

applied to minimize systematic differences between the cohorts, as discussed by Islam

et al (23). Specifically, patients were excluded if they had acute promyelocytic leukemia,

biphenotypic leukemia, chronic myeloid leukemia in blast crisis, or central nervous

system involvement at diagnosis. A more thorough description of this data can be found

in previous literature (23). Additional file 1, Figure S1, describes via a visual summary

the genetic alteration patterns of both the RWC and the CU cohorts. Figure 1 illustrates

the 5 key steps of our novel SL-based imputation framework, providing an overview of

the processes detailed in the following sections on specification and data processing,

imputation pipelines, performance assessment, and our application in high-dimensional

clinical data.

Specification and Data Processing

Step 1 includes all manual data pre-processing for the purpose of having correct

data format and structure for the developed SL-based imputation function. Data pre-

processing included, for our analysis, only variables measured at baseline (e.g.,

cytogenetic testing or laboratory measured values at diagnosis or treatment start date).

The function accepts input data containing continuous and binary variable types;

multinomial and ordinal features need to be transformed into a design matrix with binary

columns before applying the MVI function. In our application, diagnostic clinical

variables were harmonized between cohorts by merging on identified common

Figure 1. SL-based MVI imputation function methods flow diagram. *Abbreviations:* Median Absolute Deviation (MAD), Multiple Imputation by Chained Equations (MICE), Missing Value Imputation (MVI), Super Learner (SL).

variables. All dichotomous variables were made binary following traditional conventions

for reference groups, coding values such as "No" or "Wild Type" as 0. To enhance

imputation performance and reduce noise, variables considered irrelevant to modeling,

including patient identifiers, upper and lower reference ranges for laboratory values,

unknown data flags, and non-binary or non-continuous variables, were excluded during

preprocessing, leaving 124 variables.

Step 2 specifies the SL-based imputation function and its interim preprocessing

steps. This function accepts 4 parameters. The $target\_vars$ parameter takes a vector of

binary or continuous variables for imputation. We recommend ordering these variables

from least to most missingness, or from least to most importance, as the function's

iterative imputation scheme can leverage earlier imputations to improve subsequent

estimates. The learners and screeners parameters are user-defined character vectors

listing the base learners and screening wrappers to be incorporated into the SL calls. A

comprehensive list of available wrappers can be retrieved using the $listWrappers$

function in the $SuperLearner$ package (13). The final parameter, df_input, specifies the

input dataset, formatted according to the structure described in step 1.

In step 3, interim processing, the SL-based imputation function constructs the SL

library, removes variables produced by earlier imputations that are irrelevant for

subsequent targets, identifies the top predictors for each target variable, handles

missingness in those predictors, and identifies the target variable as binary or

continuous. An embedded utility function generates all possible combinations of user-

specified base learners and screening wrappers. For example, if conditional forest and

neural network learners are selected alongside correlation- and t-test-based screeners,

each learner is paired with each screener to create a SL library of four unique algorithm

inputs. It is important to note that the function has a built-in method of identifying and

ranking top potential predictors based on missingness and correlation, reducing the

demand for screener specification. To enhance interpretability in downstream outputs, a

mapping of learner names is also established. If a user does not specify any base

learning or screening wrappers, a default library of 19 learners is used with no

screeners. These learners are listed with a brief description and reference in additional

file 2, Table S1. While users may incorporate most available base learner wrappers and

screeners within the SL framework, doing so may quickly become computationally

infeasible, particularly in high-dimensional settings. Predictor selection is performed by

first excluding variables generated during previous iterations (e.g., row ID trackers,

uncertainty weights, confidence interval outputs) that do not inform estimation. For the

remaining candidate predictors, a predictor score is computed as the product of (i) the

absolute Pearson correlation with the target variable and (ii) the proportion of observed

(non-missing) data, elevating predictors that are both informative and well-represented

in the dataset. By default, the top 10 predictors ranked by this score are selected,

keeping the next steps informed, parsimonious, and reducing overfitting. The number of

predictors to use in modeling is a customizable parameter. Since the SL framework

requires complete predictor data and missingness is prevalent in RWD, simple internal

imputation is applied, median imputation for continuous variables and mode imputation

for binary variables. This simple imputation step is used solely within the function and is

not returned in the final output. Target variables with >80% missingness are flagged,

and then the top predictor's and target variable's data is subset for subsequent SL-

based methods to reduce dimensionality.

SL-based Binary Imputation Pipeline

Step 4a defines the binary target variable pipeline, encompassing several key

processes: (i) class balance checks, (ii) performance benchmarking via MICE, (iii) the

core SL prediction process with CV, (iv) optimal threshold selection for classification, (v)

resampling for accuracy variability, (vi) imputation of missing data, and (vii) generation

of uncertainty weights. A class balance check identifies severely imbalanced binary

variables. If one class comprises more than 92.5% of observations, or a class has equal

to or less than 20 observations, a flag is triggered, and mode imputation is applied

instead of SL-based modeling, as extreme imbalance can cause k-fold cross-validation

to fail. In this case, a simple weight is assigned equal to the observed class proportion

to reflect reduced uncertainty. For performance benchmarking of MICE, 30% of

observed values are randomly masked, and MICE, using 5 imputations, is applied using

a predictor matrix built from the input data. This provides a reference for comparison

against the SL-based approach. The SL process then performs nested modeling and

validation, where each base learner is trained and validated within cross-validation folds

to generate predictions. These predictions are then combined by the meta-learner to

optimize ensemble performance and minimize error (13). Within this pipeline, each

learner undergoes 10-fold CV to estimate accuracy, and an outer CV loop (via

$CV.SuperLearner$) evaluates the entire SL estimation process to provide performance

estimates. The model uses the top 10 predictors identified in step 3, with simple internal

imputation applied to handle missingness, and optimizes predictions for the area under

the ROC curve (AUC). We next find the optimal threshold for classifying predicted

probabilities by maximizing AUC when class imbalance is below 90%. In scenarios of

90-92.5% class imbalance, the F_1-score was prioritized over AUC as it better reflects the

trade-off between precision and recall and provides a more informative measure of

performance for the minority class. Estimated probabilities obtained from the CV

process are resampled 1000 times with replacement. This resampling enables

calculation of confidence intervals for balanced accuracy, quantifying between subject

variability in classification performance by applying the same threshold to each

bootstrap replicate. Additionally, by resampling from the predicted distribution,

computational feasibility is increased while accounting for uncertainty to an extent. The

CV.SuperLearner object cannot directly estimate unseen data, we therefore rerun the SL

process using snowSuperLearner with identical arguments to generate imputations for

truly missing values.

SL-based Binary Imputation Uncertainty

A similar 1000 resampling scheme is applied and the 2.5th and 97.5th percentiles

of these samples form 95% observation-specific uncertainty intervals, reflecting

variability in potential imputed predicted probabilities. The previously determined optimal

threshold is applied to classify the original predicted probability and the lower 2.5th and

upper 97.5th predicted probabilities. Finally, uncertainty weights are assigned to each

imputed observation's predicted probabilities to reflect classification confidence. These

weights are calculated, as seen in Equation 1, by taking the absolute difference

between the predicted probability of each observation, $\hat{p}_i$ and the optimal threshold τ,

scaled by the maximum possible distance to that threshold.

$$\text{weight}_i = |\hat{p}_i - \tau| \, / \, \max(\tau, 1 - \tau) \tag{1}$$

Predicted probabilities closer to the threshold receive lower weights, reflecting higher

uncertainty, while those further away approach a weight of 1, normalizing uncertainty

values between 0 and 1 while observed data is assigned a weight of 1.

SL-based Continuous Imputation Pipeline

Step 4b describes the continuous target variable pipeline, which mirrors the

binary pipeline but is adapted for continuous outcomes. After selecting the top 10

predictors and applying simple internal imputations to handle missingness among these

predictors, a MICE-based comparison is conducted with specifications consistent with

Step 4a. The SL CV process is then performed using 10-fold CV, a Gaussian family, and

a non-negative least squares (NNLS) loss function to estimate performance for each

base learner and the ensemble. The final SL ensemble model is subsequently trained

on all observed data for the selected predictors and used to impute missing values in

the target variable, producing direct value imputations rather than probabilities.

SL-based Continuous Imputation Uncertainty

Imputation uncertainty for each imputed observation is quantified using a

residual-based bootstrap approach, generating 1000 resampled imputations by adding

resampled residuals to model-predicted values. To account for heteroskedasticity, the

bootstrap resampling process selects the 50 residuals closest to each predicted value

based on Euclidean distance from the observed target values, ensuring that resampled

errors are drawn from observations with similar outcome magnitudes. The 2.5th and

97.5th percentiles of these samples form 95% observation-specific uncertainty intervals,

reflecting variability in potential imputed values. Observation-specific uncertainty

weights for continuous variables are shown in equation 2, calculated as the inverse of 1

plus the median absolute deviation (MAD) of the bootstrap sample distribution per

observation, B_i, normalized by the mean predicted value of the observation-specific

bootstrap distribution $\bar{p_i}$, thereby assigning higher weights to imputed values with lower

relative variability.

$$\text{weight}_i = 1 \:/\: (1 + (\text{MAD}(B_i) \:/\: \bar{p_i})) \tag{2}$$

These outputs provide both a point estimate and observation-specific uncertainty

intervals, enabling other analyses to account for uncertainty and down-weight less

certain imputations.

Performance Assessment and Application

Step 5 involves data output, iterative imputation, and comprehensive

performance assessment. The SL-based imputation function produces an interim

dataset in which each target variable is sequentially replaced by its imputed counterpart,

supplemented with observation-specific uncertainty weights. The output additionally

includes observation-specific 95% estimation uncertainty intervals that capture model

uncertainty, enabling downstream analyses to consider a plausible range of imputed

values rather than relying on single-point estimates. This augmented dataset is

iteratively updated as each variable in the input vector is imputed, ultimately yielding a

complete dataset supported with uncertainty-aware outputs. In addition to the final

imputed data, the proposed imputation function returns a suite of diagnostic metrics and

visualizations, providing strong transparency into the imputation process over standard

methods like MICE. These include visualizations of top predictor scores for each target

variable, flags for variables with >80% missingness, benchmark MICE performance

metrics (confusion matrices and F_1-scores for binary variables, RMSE, root mean

square error, for continuous variables), and illustration of average CV risk estimates for

every base learner in the SL ensemble (risk being RMSE for continuous variables, AUC

for binary variable). The function also reports ensemble-level performance measures,

balanced accuracy with bootstrap-based confidence intervals for binary targets, optimal

thresholds for classification, and visualization of average ensemble weights based on

nested CV folds illustrating each learner's contribution to the SL model. Predicted

values or probabilities are visualized along with resampling distributions. Furthermore,

computing time is provided for both the independent MICE run and the final SL

ensemble that is trained for imputation. Collectively, these outputs deliver not only a fully

imputed dataset but also a novel, uncertainty-aware, and performance-benchmarked

framework, offering users enhanced interpretability and awareness in the resulting

imputations compared to conventional MVI approaches.

We summarize general descriptives of our merged 1641 patient cohort via counts

for categorical variables and median and IQR for continuous variables. Additionally we

describe missingness of the entire cohort leveraging the naniar R package (24).

Missingness descriptives include missingness prevalence and visualizations to aid in

identification of missingness patterns. In our initial testing application of this novel SL-

based imputation function, we selected variables that have been previously identified in

analyses of our data as high priority for upfront risk stratification and clinical relevance

(23). These binary flag variables include NPM1 mutation, IDH1 mutation, IDH2

mutation, good risk cytogenetics as based on SWOG (25), inv(3) abnormality, TP53

mutation, -17 abnormality, t(9;11) abnormality, -5 abnormality, complex cytogenetics,

and FLT3-ITD mutation. Given that these variables do not include a continuous data

type, we additionally selected the laboratory-measured lactate dehydrogenase (LDH)

variable for continuous variable evaluation due to its prognostic importance (26), with

additional continuous variables of laboratory measured hemoglobin, platelets, and

absolute neutrophil count (ANC). We ordered all selected variables from least to most

missingness and supplied this vector to the MVI function, reporting summarizations of

the previously mentioned performance metrics. In our application, we used the default

19 learner algorithms library. This diverse selection of learners ensures that the SL

library balances simple benchmarks, linear and nonlinear models, tree-based

approaches, penalized regression, and modern machine learning methods, enhancing

flexibility and robustness in the estimation procedure and accounting for algorithmic

uncertainty. To enable deeper insight into the SL-based imputation's behavior and

output data, we further isolated TP53 mutation and LDH to conduct a more detailed

evaluation of SL predictive performance. This deeper comparison examined the

performance of individual base learners, highlighting one algorithm that emerged as the

top-performing single learner, referred to as the discrete learner. For SL processes,

parallelization was configured using the $parallel$ R package, and for resampling

parallelization was configured using the $future$ R package (27), both leveraging

maximum cores. Lastly, to demonstrate how the SL-based imputations may compare to

the MICE-based imputations in downstream work, we applied risk stratification logic,

methodology detailed in a previous publication (28), to the cohort using these risk

stratification variables. Differences between the imputation strategies' influences on risk

stratification were explored via the proportion of patients changing risk stratification, the

change in median overall survival (OS) days for different risk stratifications, and Kaplan

Meier survival curve visualizations. We also evaluated the prognostic utility of the

derived risk stratifications using multivariable Cox proportional hazards models for

overall survival, time from diagnosis to death or last follow-up, adjusting for age at

diagnosis. Separate models were fit using the three-level risk stratification variable

constructed from either MICE- or SL-imputed data, with the favorable category as the

referent. All statistical analyses were performed in R version 4.4.1 (29). This study

follows STROBE guidelines for reporting observational research (30).

Results

Descriptive Results

General cohort and target variable descriptive statistics are available in Table 1.

Most of the 1641 patient cohort were male (703, 57.16%), White (1211, 73.8%), not

Hispanic or Latino (1302, 79.34%), deceased at follow-up (1042, 63.5%), on the

Ven/Aza treatment regime (1454, 88.60%), and are de novo AML (1076, 65.57%).

Median age at enrollment was 74 (IQR 67-79). The target variables had missingness

ratios that ranged from as low as 0.18% for good risk cytogenetics (3/1641) to high

missingness of 54.17% for LDH (889/1641). Additional file 3, Figure S2 displays

missingness ratios across all variables in the merged dataset, missingness across all

variables can be summarized as highly diverse. Broadly, most variables were binary and

had 40-80% missingness. Additional files 4-6, Figures S3-5, demonstrate missingness

feature categories of cytogenetics, mutations, and lab values, respectively. Taken

together, these missingness figures indicate primarily arbitrary and block patterns of

missingness.

Table 1. Merged cohort and target variable descriptive results and missingness.

Variable and Type	Count (%, n=1641)	Missingness Count and Ratio
Categorical		
Sex		0%
Female	703 (42.84)	
Male	938 (57.16)	
Race		201 (12.25)
Asian	17 (1.04)	
Black	76 (4.63)	
Other	136 (8.29)	
White	1211 (73.80)	
Ethnicity		256 (15.60)
Hispanic or Latino	78 (4.75)	
Not Hispanic or Latino	1302 (79.34)	
Not Reported	5 (0.30)	
Secondary AML		0%
No	1076 (65.57)	
Yes	565 (34.43)	
Vital Status		0%
Censored To Last Known Alive Date	599 (36.50)	
Deceased	1042 (63.50)	
Treatment		0%
7+3	187 (11.40)	
Ven/Aza	1454 (88.60)	
Data Source		0%
CU Cohort	546 (33.27)	
Real World Cohort	1095 (66.73)	
Good Risk Cytogenetics	88 (5.36)	3 (0.18)
Complex Cytogenetics	269 (16.39)	38 (2.32)
Inv(3) abnormality	21 (1.28)	362 (22.06)
T(9;11) abnormality	17 (1.04)	362 (22.06)
-5 abnormality	182 (11.09)	367 (22.36)
-17 abnormality	109 (6.64)	368 (22.43)
IDH2 Mutation	182 (11.09)	584 (35.59)
IDH1 Mutation	104 (6.34)	592 (36.08)
NPM1 Mutation	193 (11.76)	617 (37.60)
FLT3-ITD Mutation	123 (7.50)	700 (40.27)
TP53 Mutation	249 (15.17)	744 (45.34)
Continuous	**Median (IQR)**	
Age at Enrollment	74 (67-79)	0
Hemoglobin	8.40 (7.70-9.40)	481 (29.31)
Platelets	53.00 (31.00-101.00)	553 (33.70)
Absolute Neutrophil Count	0.70 (0.27-2.00)	684 (41.68)
LDH	285 (190-487)	889 (54.17)

Abbreviations: Acute Myeloid Leukemia (AML), University of Colorado (CU), Lactate Dehydrogenase (LDH).

380 **Table 2.** Performance of all binary target variables of interest compared between MICE
381 and the SL-based imputation function approach.

Variable	MICE Balanced Accuracy (%)	SL Balanced Accuracy (95% CI[a], %)	MICE F$_1$-score (%)	SL F$_1$-score (%)	MICE Time (seconds)	SL-based Time[b] (seconds)
Good Risk Cytogenetics	92.68	96.93 (94.11-99.15)	98.91	99.61	0.79	137.67
Complex Cytogenetics	95.04	98.88 (98.45-99.26)	98.08	98.86	0.72	203.89
-5 abnormality	63.1	82.69 (79.89-85.36)	90.47	87.82	0.42	190.88
-17 abnormality	58.03	57.58 (54.38-61.16)	92.53	95.98	0.55	116.01
IDH2 Mutation	69.63	94.93 (92.87-96.63)	88.93	97.52	0.51	131.08
IDH1 Mutation	95.99	95.19 (92.05-97.69)	98.57	99.47	0.46	178.63
NPM1 Mutation	86.69	93.65 (91.54-95.71)	95.95	97.22	0.48	123.61
TP53 Mutation	91.78	95.27	94.68	98.02	0.44	127.77
FLT3-ITD Mutation	87.22	95.67 (93.12-97.81)	90.91	91.71	0.53	95.65

[a] 95% confidence intervals represent the SL CV loop's 1000 resamples with classified via the optimal threshold for measures of precision for balanced accuracy.
[b] SL-based time refers to only the SL model trained for prediction and not the CV loop for performance measures.
Abbreviations: Multiple Imputation by Chained Equations (MICE), Super Learner (SL), Cross-Validation (CV).

Primary Results

Table 2 details the performance for nearly all binary target variables of interest,

comparing the performance of the SL-based ensemble approach to MICE. Variables

inv(3) and t(9;11) abnormalities are not shown as they had high class imbalance and as

a result were defaulted to the simple imputation pipeline. Performance measures

included balanced accuracy, F$_1$-score, and computational time. The SL-based ensemble

approach had a greater mean balanced accuracy, 89.04%, than MICE, 80.75% and had

superior balanced accuracy for 7 out of 9 variables, with 2 out of 9 variables having

comparable (<1% difference) balanced accuracy. The mean F$_1$-score for MICE, 94.34%,

and the SL-based ensemble approach, 96.25%, were more mixed and slightly favoring

the SL-based ensemble approach. Lastly, computational time was on average longer for

the SL ensemble trained for imputation, 145 seconds, compared to MICE, 0.5 seconds.

In our specific performance analysis of the SL-based ensemble and MICE

approaches of TP53 mutation and LDH imputation, we found that the SL-based

approach was mostly superior to MICE. For TP53 mutation imputation, MICE had a

balanced accuracy of 91.8%, sensitivity 93.7%, specificity 89.9%, and an F_1-score of

94.7% while the SL-based ensemble approach had respective values of 95.3%, 99.4%,

91.2%, and 98.0%. Compared to the SL-based ensemble approach, the discrete learner

of the ensemble had comparable performance (balanced accuracy 95.3%; sensitivity

99.4%; specificity 91.2%; F_1-score 97.9%) and another select algorithm for comparison,

GLM interaction, had worse performance (balanced accuracy 91.7%; sensitivity 96.6%;

specificity 87.8%; F_1-score 95.8%). Additional file 7, Figure S6, shows the top 10

predictors of the TP53 mutation variable that were used in the SL-based approach,

indicating that several previous target variables that were imputed supported the

imputation of TP53 mutation. Figure 2 shows the CV-specific base learner risks, in other

words individual model performance, for TP53 mutation, suggesting that most base

learners performed well (>0.9 AUC) with conditional forest having the absolute minimum

risk observed. Figure 3 demonstrates the subsequent average assigned weights of the

SL-based ensemble's learners where many of the learners can be perceived to receive

comparable weights as the SL technique aims to reduce overfitting. Lastly, for TP53

mutation, Figure 4 shows the predicted probability and corresponding resampled

distribution of predicted probabilities based on 1000 resamples. With a calculated

Figure 2. Cross-validated base learner risks for binary TP53 mutation variable prediction, risk measured as AUC. *Note:* multiple points may appear because of multiple default hyperparameter settings. *Abbreviations:* Area Under the Curve (AUC).

Figure 3. Cross-validated SL ensemble weight averages for binary variable TP53 mutation. *Abbreviations:* Super Learner (SL).

Figure 4. SL-based ensemble's predicted probability density distribution for TP53 mutation binary variable data with overlapping 1000 resampled density distribution. *Abbreviations:* Super Learner (SL).

optimal threshold of 0.38 and the observed predicted probabilities, we would estimate

that most classifications were 0 and were likely assigned moderate uncertainty weights.

This is validated when analyzing the distribution of the TP53 mutation uncertainty

weights (median 0.52, IQR 0.45-0.53). With respect to LDH, results were more mixed.

MICE had a RMSE of 597, higher than that of the SL-based ensemble's RMSE of 582.

Furthermore, the discrete learner of the ensemble performed best with 557 RMSE, and

other algorithms including neural network and all GLM algorithms, performed far worse

with >5000 RMSE. Additional file 8, Figure S7, displays the top 10 predictors of the LDH

variable that were used in the SL-based approach. Figure 5 shows the average CV-

specific base learner risks for LDH. The SL-based ensemble's learner's average

weights are shown in Figure 6, supporting a narrower range of base learners unequally.

Figure 5. Cross-validated base learner average risks for continuous variable LDH, risk measured as RMSE. *Abbreviations:* Root Mean Square Error (RMSE), Lactate Dehydrogenase (LDH).

Figure 6. Cross-validated SL-based ensemble average weights for continuous variable LDH. *Abbreviations:* Super Learner (SL), Lactate Dehydrogenase (LDH).

Figure 7 displays the SL ensemble's predicted values density distribution for LDH and

the corresponding density distribution of resampled values based on 1000 resamples,

suggesting introduced variation. Subsequent weights indicate moderate to high certainty

and relatively small variability of imputations across resamples compared to the

observed data's variation (median 0.81, IQR 0.80-0.83). Lastly, for laboratory measured

hemoglobin (SL RMSE: 1.37, MICE RMSE 2.10), platelets (SL RMSE 82.75, MICE

RMSE 114.93), and ANC (SL RMSE 2.80, MICE RMSE 4.15) the SL-based ensemble

outperformed MICE. Across all 4 continuous variables, this represents an average

24.45% lower RMSE for the SL-based ensemble. The downstream risk stratification

comparison between the SL-based imputations and the MICE-based imputations of

these risk stratification variables is visualized as survival curve differences in Additional

Figure 7. SL-based ensemble's predicted values density distribution for missing LDH continuous variable data, overlayed with the 1000 resampled density distribution. Figure was log transformed after running the function for interpretability. *Abbreviations:* Lactate Dehydrogenase (LDH).

File 9, Figure S8. Using SL-based imputations instead of MICE imputations resulted in

7.78% of patients changing risk classification and a notable increase in separation of

median OS days between risk stratifications was observed. Risk group associations

with overall survival were consistently stronger under the SL-based imputation.

Compared with the favorable group, intermediate risk showed higher hazards under SL

(MICE HR 1.21, 95% CI 1.05–1.41; SL HR 1.41, 95% CI 1.21–1.64), and adverse risk

was similarly amplified (MICE HR 2.06, 95% CI 1.76–2.41; SL HR 2.36, 95% CI 1.98–

2.80), corresponding to an average 25% increase in hazard ratio relative to MICE-

derived stratifications. Our computing setup with 48 cores and 188 GB of RAM, with

parallelization and a 19-learner library, processed 11 binary targets and a continuous

target in approximately 2.5 hours.

Discussion

In this study we evaluated a SL-based ensemble imputation approach for

handling missing diagnostic data in a dataset comprised of 1641 newly diagnosed AML

patients treated with Ven/Aza or 7+3. Leveraging the SL framework, we demonstrated

consistently improved imputation performance over a commonly used statistical

method, MICE, specifically for binary genetic variables, even when they had substantial

missingness. On average, the SL-based ensemble achieved higher balanced accuracy

(89.0% vs 80.8%) and F1 score (96.3% vs 94.3%) compared to MICE across 9 binary

genetic features. In focused evaluations of TP53 mutation and LDH laboratory values,

the SL-based ensemble approach led to superior or comparable performance to

singular algorithms and uncertainty weights. Lastly, in downstream analyses, changes in

Kaplan-Meier survival curves and multivariable Cox regression results were noteworthy.

These results underscore the potential of SL-based methods to enhance data integrity

in clinical prediction pipelines, especially in high-dimensional electronic health record

derived datasets where conventional single-model approaches may struggle. To our

knowledge, this study represents one of the first applications of the SL-based ensemble

for missing value imputation in a clinical oncology context. Furthermore, we

demonstrate the method's utility by achieving strong performance while introducing

novel, observation-level uncertainty estimates which quantify variation, while being

delivered through a streamlined, user-friendly function that automates imputation,

performance evaluation, and data output.

Prior studies into missing value imputation in clinical cohorts have repeatedly

shown that standard approaches such as MICE can yield reasonable accuracy when

data are moderately complete and missingness mechanisms approximate MAR, but

their performance often deteriorates in high-dimensional or block-missing contexts

(7,31). MICE has strong advantages such as being well-documented and easily applied

(32). These strengths are evident by the notable abundance of MICE's application in

health research literature, with MICE serving as either the primary imputation method or

the benchmark comparison. An earlier 2015 review by Rezvan et al. with narrow search

criteria showed the dominance of MICE in imputation methodology in medical research,

with 53% (20/38) of research articles reporting methods of imputation using MICE (33).

ML-based methods like random forest and k-NN have improved on MICE's limitations in

several ways such as by capturing nonlinear feature relationships (5,8). In the

systematic review of 94 ML performance assessing research articles by Alabadla et al. it

was found that across most studies k-NN, random forest, and support vector machine

methods performed best, these results would agree with our rankings of ML algorithms

by AUC and RMSE. This study also noted though the lack of, and need for,

computational time reporting and consistency across performance measures to best

evaluate overall performance (7). Another study that analyzed high dimensional genetic

data compared ML-based approaches to MICE and simple mean imputation, also

finding that k-NN and random forest typically performed far better than both of these

approaches (34). Such popularity for k-NN, and other algorithms, is explained by a

systematic review of 117 research articles by Thomas and Rajabi. The review clarifies

that these algorithm's easy implementation across knowledge domains make them an

attractive option. However, these authors also note that despite such popularity there

continues to be no single universal solution to the missing data problem (35). While ML-

based methods have grown immensely in popularity and application frequency since

2015 (7), in part due to improvements over MICE and simple imputation, as previously

mentioned these methods remain relatively constrained by the reliance on a single

learner that may have varying performance for different missingness scenarios.

Ensemble learning approaches may prove an effective next step to overcome these

challenges. While using a more typical ensemble strategy compared to our SL-based

strategy, our results would concur with those found by Batra et al. who found that a

stacked ensemble strategy proved superior to simple imputation and several singular

ML algorithms (12). In a different context than imputation, a 2023 review of 45 articles

evaluated ensemble learning approaches in highly researched disease prediction. They

concluded that amongst these studies, those that employed the stacking method of

ensemble learning performed best compared to other ensemble methods. This work

gives us greater confidence in our findings using a SL-based approach (14). Prior

literature using super learning for missing data imputation is sparse, however, one study

showed that multiple imputation by super learning yielded superior results compared to

traditional methods in a comparative analysis. Albeit, this application was limited by

synthetic data, not having quantified uncertainty, and a process that did not

automatically generate performance measures (15). Lastly, our results extend prior work

by demonstrating that a CV-specific stacking ensemble can more effectively integrate

varying base learners to handle diverse variable missingness contexts, and when

incorporated into a function, can also output measures of uncertainty. Such measures of

uncertainty are intended as a practical guardrail for imputation confidence. Uncertainty

weights can highlight subject-specific cases where imputations may remain uncertain

due to deviating assumptions from cross-validation induced missingness, where

uncertainty could be high even when imputation performance across folds is strong.

Despite the promising performance of our SL-based approach, our study has

several limitations. First, we employed default SL hyperparameters for all base learners

rather than performing extensive tuning. While this decision simplified the pipeline and

demonstrated robust gains over MICE by default, it may have missed additional

opportunities to further improve performance. Second, the computational burden of

training the CV-specific ensemble represents the greatest practical hurdle to routine

deployment. However, this cost is justified in settings where imputation accuracy and

uncertainty quantification materially impact other modeling tasks in high stakes clinical

applications such as risk stratification. As we demonstrated, using the SL-based

approach instead of MICE showed noteworthy changes in risk classification, which

could have great impacts on clinical treatment planning and health outcomes for

patients, especially for aggressive diseases like AML. Regarding the computational time

of the whole process, it was also longer than MICE but to quantify uncertainty from

MICE using traditional approaches of bootstrapping would likely incur even more

computational costs. Lastly, prior to ensemble fitting we perform simple imputation on

the top 10 predictors for each target, which may propagate initial error and contribute to

cumulative uncertainty. We partially mitigate this through our resampling-based

uncertainty weights, observations with high variance can be down-weighted in

downstream models. However, such bootstrapping-based uncertainty does not capture

within-subject variability and may be susceptible to the amount of missing data and

representation of the true missing data pattern in the bootstrap samples. More rigorous

initial imputation of predictors, such as using MICE (36), and incorporation of initial

subject-specific uncertainty measures in imputation of target variables would further

reduce this concern. Conversely, our SL-based imputation function offers several key

strengths. By vectorizing imputation across diverse base learners, it provides a nearly

fully automated, scalable framework that consistently outperforms single-method

approaches in our application in high-dimensional clinical data. Additionally, while we

applied the function to AML data for evaluation, there stands no reason it cannot be

applied to other datasets. The model's ability to generate observation-specific

uncertainty weights and uncertainty intervals allow end-users to conduct a variety of

sensitivity analyses using these values across different settings. The flexibility of the SL

framework allows inclusion of new algorithms as they emerge, ensuring that the pipeline

can adapt to evolving patterns of data complexity and missingness. Finally, in line with

identified gaps in performance assessment in the literature (37) and combined with

descriptive statistics of missingness, the SL-based imputation function's performance

output allows a user to well understand key aspects of MVI including computational time

and common performance measures.

Conclusions

In summary, our work demonstrates that a SL-based imputation function can

significantly improve the accuracy and robustness of missing-value estimation in a high-

dimensional AML real-world dataset, outperforming the standard MICE approach for

most of our target variables while providing observation-level uncertainty metrics. These

findings support our central hypothesis that ensemble strategies yield more reliable

imputation in complex clinical data. In future deployments we hope to add automated

and customized hyperparameter optimization, integrate automatic support for

multinomial and ordinal targets, and further validate its utility in diverse missing data

formats and contexts. Future research would benefit from evaluating this function

among diverse disease areas, across a greater range of variables, its impact on

optimizing risk stratification strategies, and in more extensive simulation and validation

studies that assess uncertainty calibration. Ultimately, by combining improved

performance over traditional methods and flexibility, ensemble learning-derived

imputation can enhance downstream modeling by managing missingness' threat to

validity.

Abbreviations

AML	Acute myeloid leukemia
AUC	Area under the curve
CU	University of Colorado
CYT	Cytogenetics
k-NN	k-Nearest Neighbor
LAB	Laboratory values
LDH	Lactate dehydrogenase
MAR	Missing at random
MAD	Median absolute deviation
MCAR	Missing completely at random
MICE	Multiple imputation by chained equations
ML	Machine learning
MVI	Missing value imputation
NNLS	Non-negative least squares
RMSE	Root mean square error
RWC	Real World Cohort
RWD	Real world data
SL	Super Learner
Ven/Aza	Venetoclax plus azacitidine
$\hat{p}_i$	Predicted probability
τ	Optimal threshold
B_i	Bootstrap samples
$\bar{p}_i$	Mean predicted value

Declarations

Ethics approval and consent to participate: This study was conducted in accordance with the principles of the Declaration of Helsinki. This study was reviewed and approved under the 2018 Requirements of the Federal Policy for the Protection of Human Subjects by the Colorado Multiple Institutional Review Board (COMIRB), located at the University of Colorado Anschutz Medical Campus, Aurora, Colorado, United States. Ethical approval was granted for the study, and a Waiver of Informed Consent and a Health Insurance Portability and Accountability Act (HIPAA) Waiver of Authorization were granted by COMIRB on the basis that all criteria for waiving consent and HIPAA authorization were met. The Flatiron Health data that supported the findings of this study were originated by and are the property of Flatiron Health, Inc."

Consent for publication: Not applicable.

Availability of data and materials: The individual patient-level datasets analyzed during the current study are not publicly available due to data privacy laws but the processed data are available from the corresponding author on reasonable request. The Flatiron Health data that support the findings of this study are available from Flatiron Health Inc., but restrictions apply to the availability of these data, which were used under license for th current study, and so are not publicly available. Flatiron Health data has restriction prohibiting the authors from making the datasets publicly available. Requests for data sharing by license or by permission for the specific purpose of replicating results in this manuscript can be submitted to PublicationsDataAccess@flatiron.com. Lastly, in the supplementary material, the SL-based imputation function is accompanied by an HTML-based illustration that provides

a concise, step-by-step walkthrough that enables users to quickly understand its

purpose, inputs, outputs, and performance metrics, and to apply the function to their

own datasets. This HTML-based illustration serves as a tutorial which includes the full

function code and applies the method to synthetic data. A simple R package to apply

the function is forthcoming.

Competing interests: All authors are affiliated with RefinedScience and receive

compensation as part of employment under RefinedScience. The authors declare no

other conflicts of interest.

Funding: This research received no specific grant from any funding agency in the

public, commercial, or non-profit sectors.

Author's contributions: TZ contributed via conception and design of the work,

analysis of the data, interpretation of the data, creation of the function applied, and

drafting and revising the work. LW contributed via design of the work and acquisition of

the data. JD, JC, KS, FM, and UK contributed via acquisition and management of the

data. JR contributed via acquisition and management of data and internal review of the

manuscript. NI contributed via conception and design of the work, acquisition and

interpretation of the data, and revising the manuscript. All authors read and approved

the final manuscript.

Acknowledgements: We give additional acknowledgement and great gratitude to the

internal reviewers of RefinedScience and external reviewers of Flatiron Health.

References

1. RUBIN DB. Inference and missing data. Biometrika. 1976 Dec 1;63(3):581–92.
doi:10.1093/biomet/63.3.581

2. Schafer JL, Graham JW. Missing data: our view of the state of the art. Psychol
Methods. 2002 Jun;7(2):147–77. PubMed PMID: 12090408.

3. Roderick J.A. Little and Donald B. Rubin (2002) Statistical Analysis with Missing
Data, 2nd ed. John Wiley & Sons | RTI [Internet]. [cited 2025 Jul 3]. Available from:
https://www.rti.org/publication/roderick-j-little-donald-b-rubin-2002-statistical-
analysis-missing-data-2nd-ed-john-wiley-amp-sons-b

4. Petersen I, Welch CA, Nazareth I, Walters K, Marston L, Morris RW, et al. Health
indicator recording in UK primary care electronic health records: key implications for
handling missing data. Clin Epidemiol. 2019;11:157–67. doi:10.2147/CLEP.S191437
PubMed PMID: 30809103; PubMed Central PMCID: PMC6377050.

5. Liu M, Li S, Yuan H, Ong MEH, Ning Y, Xie F, et al. Handling missing values in
healthcare data: A systematic review of deep learning-based imputation techniques.
Artificial Intelligence in Medicine. 2023 Aug 1;142:102587.
doi:10.1016/j.artmed.2023.102587

6. Buuren S van, Groothuis-Oudshoorn K. mice: Multivariate Imputation by Chained
Equations in R. Journal of Statistical Software. 2011 Dec 12;45:1–67.
doi:10.18637/jss.v045.i03

7. Alabadla M, Sidi F, Ishak I, Ibrahim H, Affendey LS, Che Ani Z, et al. Systematic
Review of Using Machine Learning in Imputing Missing Values. IEEE Access.
2022;10:44483–502. doi:10.1109/ACCESS.2022.3160841

8. Stekhoven DJ, Bühlmann P. MissForest--non-parametric missing value imputation
for mixed-type data. Bioinformatics. 2012 Jan 1;28(1):112–8.
doi:10.1093/bioinformatics/btr597 PubMed PMID: 22039212.

9. Ismail AR, Abidin NZ, Maen MK. Systematic Review on Missing Data Imputation
Techniques with Machine Learning Algorithms for Healthcare. Journal of Robotics
and Control (JRC). 2022 Feb 5;3(2):2. doi:10.18196/jrc.v3i2.13133

10. Afkanpour M, Hosseinzadeh E, Tabesh H. Identify the most appropriate imputation
method for handling missing values in clinical structured datasets: a systematic
review. BMC Med Res Methodol. 2024 Aug 28;24(1):188. doi:10.1186/s12874-024-
02310-6

11. Sun Y, Li J, Xu Y, Zhang T, Wang X. Deep learning versus conventional methods for
missing data imputation: A review and comparative study. Expert Systems with
Applications. 2023 Oct 1;227:120201. doi:10.1016/j.eswa.2023.120201

12. Batra S, Khurana R, Khan MZ, Boulila W, Koubaa A, Srivastava P. A Pragmatic
Ensemble Strategy for Missing Values Imputation in Health Records. Entropy. 2022
Apr;24(4):4. doi:10.3390/e24040533

13. "Super Learner In Prediction" by Eric C. Polley and Mark J. van der Laan [Internet].
[cited 2025 Jun 25]. Available from:
https://biostats.bepress.com/ucbbiostat/paper266/

14. Laan MJ van der, Polley EC, Hubbard AE. Super Learner. Statistical Applications in
Genetics and Molecular Biology. 2007 Sep 16;6(1). doi:10.2202/1544-6115.1309

15. Carpenito T, Manjourides J. MISL: Multiple imputation by super learning. Statistical
Methods in Medical Research. 2022 Jun 5. Located at: Sage UK: London, England.
doi:10.1177/09622802221104238

16. Murugesan S, Bhuvaneswaran RS, Nehemiah HK, Sankari SK, Jane YN. Feature
Selection and Classification of Clinical Datasets Using Bioinspired Algorithms and
Super Learner. Computational and Mathematical Methods in Medicine. 2021 May
18. doi:10.1155/2021/6662420

17. Li S, Zhang Y, Fu K, Fang K, Zheng L, Lin Y, et al. Machine learning ensemble
meets clinical practice: developing a real-world risk prediction model for metabolic
syndrome using super learner and scorecard approaches. Journal of Advanced
Research. 2025 Jun 27. doi:10.1016/j.jare.2025.06.072

18. Petersen ML, LeDell E, Schwab J, Sarovar V, Gross R, Reynolds N, et al. Super
Learner Analysis of Electronic Adherence Data Improves Viral Prediction and May
Provide Strategies for Selective HIV RNA Monitoring. J Acquir Immune Defic Syndr.
2015 May 1;69(1):109–18. doi:10.1097/QAI.0000000000000548 PubMed PMID:
25942462; PubMed Central PMCID: PMC4421909.

19. Jin W, Hao W, Shi X, Fritsche LG, Salvatore M, Admon AJ, et al. Using Multi-Modal
Electronic Health Record Data for the Development and Validation of Risk Prediction
Models for Long COVID Using the Super Learner Algorithm. Journal of Clinical
Medicine. 2023 Jan;12(23):7313. doi:10.3390/jcm12237313

20. Zhu X, Zhang P, Jiang H, Kuang J, Wu L. Using the Super Learner algorithm to
predict risk of major adverse cardiovascular events after percutaneous coronary
intervention in patients with myocardial infarction. BMC Med Res Methodol. 2024
Mar 8;24(1):59. doi:10.1186/s12874-024-02179-5

21. Ma X, Long L, Moon S, Adamson BJS, Baxi SS. Comparison of Population
Characteristics in Real-World Clinical Oncology Databases in the US: Flatiron
Health, SEER, and NPCR [Internet]. medRxiv; 2023 [cited 2025 Aug 5]. p.
2020.03.16.20037143. Available from:
https://www.medrxiv.org/content/10.1101/2020.03.16.20037143v3
doi:10.1101/2020.03.16.20037143

22. Birnbaum B, Nussbaum N, Seidl-Rathkopf K, Agrawal M, Estevez M, Estola E, et al.
Model-assisted cohort selection with bias analysis for generating large-scale cohorts
from the EHR for oncology research [Internet]. arXiv; 2020 [cited 2025 Aug 5].
Available from: http://arxiv.org/abs/2001.09765 doi:10.48550/arXiv.2001.09765

23. Islam N, Reuben JS, Dale JL, Zhang J, Coates JW, Sapiah K, et al. A simplified risk
model for pretreatment stratification of newly diagnosed acute myeloid leukemia
patients treated with venetoclax and azacitidine [Internet]. medRxiv; 2024 [cited
2025 Jul 3]. p. 2024.12.02.24318344. Available from:
https://www.medrxiv.org/content/10.1101/2024.12.02.24318344v1
doi:10.1101/2024.12.02.24318344

24. Tierney N, Cook D, McBain M, Fay C, O'Hara-Wild M, Hester J, et al. naniar: Data
Structures, Summaries, and Visualisations for Missing Data [Internet]. 2024 [cited
2025 Jul 30]. Available from: https://cran.r-
project.org/web/packages/naniar/index.html

25. Slovak ML, Kopecky KJ, Cassileth PA, Harrington DH, Theil KS, Mohamed A, et al.
Karyotypic analysis predicts outcome of preremission and postremission therapy in
adult acute myeloid leukemia: a Southwest Oncology Group/Eastern Cooperative
Oncology Group study. Blood. 2000 Dec 15;96(13):4075–83.
doi:10.1182/blood.V96.13.4075

26. Islam N, Reuben JS, Dale J, Coates JW, Sapiah K, Markson FR, et al. Predictive
Models for Long Term Survival of AML Patients Treated with Venetoclax and
Azacitidine or 7+3 Based on Post Treatment Events and Responses: Retrospective
Cohort Study. JMIR Cancer. 2024 Aug 21;10(1):e54740. doi:10.2196/54740

27. Bengtsson H. future: Unified Parallel and Distributed Processing in R for Everyone
[Internet]. 2025 [cited 2025 Jul 29]. Available from: https://cran.r-
project.org/web/packages/future/index.html

28. Islam N, Dale JL, Reuben JS, Sapiah K, Coates JW, Markson FR, et al.
Development of a dynamic counterfactual risk stratification strategy for newly
diagnosed acute myeloid leukemia patients treated with venetoclax and azacitidine
[Internet]. medRxiv; 2025 [cited 2025 Jul 25]. p. 2024.11.25.24317750. Available
from: https://www.medrxiv.org/content/10.1101/2024.11.25.24317750v4
doi:10.1101/2024.11.25.24317750

29. R Development Core Team. R: A Language and Environment for Statistical
Computing [Internet]. Vienna, Austria: R Foundation for Statistical Computing; 2025.
Available from: https://cran.r-project.org/

30. von Elm E, Altman D, Egger M, Pocock S, Gotzsche P, Vandenbroucke J. The
Strengthening the Reporting of Observational Studies in Epidemiology (STROBE)
Statement: guidelines for reporting observational studies.

31. Jerez JM, Molina I, García-Laencina PJ, Alba E, Ribelles N, Martín M, et al. Missing
data imputation using statistical and machine learning methods in a real breast
cancer problem. Artificial Intelligence in Medicine. 2010 Oct 1;50(2):105–15.
doi:10.1016/j.artmed.2010.05.002

32. Zhang Z. Multiple imputation with multivariate imputation by chained equation
(MICE) package. Ann Transl Med. 2016 Jan;4(2):30. doi:10.3978/j.issn.2305-
5839.2015.12.63 PubMed PMID: 26889483; PubMed Central PMCID:
PMC4731595.

33. Hayati Rezvan P, Lee KJ, Simpson JA. The rise of multiple imputation: a review of
the reporting and implementation of the method in medical research. BMC Med Res
Methodol. 2015 Apr 7;15:30. doi:10.1186/s12874-015-0022-1 PubMed PMID:
25880850; PubMed Central PMCID: PMC4396150.

34. Petrazzini BO, Naya H, Lopez-Bello F, Vazquez G, Spangenberg L. Evaluation of
different approaches for missing data imputation on features associated to genomic
data. BioData Mining. 2021 Sep 3;14(1):44. doi:10.1186/s13040-021-00274-7

35. Thomas T, Rajabi E. A systematic review of machine learning-based missing value
imputation techniques. Data Technologies and Applications. 2021 Apr 2;55(4):558–
85. Located at: world. doi:10.1108/DTA-12-2020-0298

36. Mera-Gaona M, Neumann U, Vargas-Canas R, López DM. Evaluating the impact of
multivariate imputation by MICE in feature selection. PLOS ONE. 2021 Jul
28;16(7):e0254720. doi:10.1371/journal.pone.0254720

37. Lin WC, Tsai CF. Missing value imputation: a review and analysis of the literature
(2006–2017). Artif Intell Rev. 2020 Feb 1;53(2):1487–509. doi:10.1007/s10462-019-
09709-4

38. Gelman A, Su YS. arm: Data Analysis Using Regression and Multilevel/Hierarchical
Models [Internet]. 2007 [cited 2025 Jul 29]. p. 1.14-4. Available from:
https://CRAN.R-project.org/package=arm doi:10.32614/CRAN.package.arm

39. Kuhn M. caret: Classification and Regression Training [Internet]. 2007 [cited 2025
Jul 29]. p. 7.0-1. Available from: https://CRAN.R-project.org/package=caret
doi:10.32614/CRAN.package.caret

40. Strobl C, Boulesteix AL, Zeileis A, Hothorn T. Bias in random forest variable
importance measures: Illustrations, sources and a solution. BMC Bioinformatics.
2007 Jan 25;8(1):25. doi:10.1186/1471-2105-8-25

41. R Development Core Team. R: A Language and Environment for Statistical
Computing [Internet]. Vienna, Austria: R Foundation for Statistical Computing; 2010.
Available from: https://cran.r-project.org/

42. Regularization Paths for Generalized Linear Models via Coordinate Descent |
Journal of Statistical Software [Internet]. [cited 2025 Jul 29]. Available from:
https://www.jstatsoft.org/article/view/v033i01

43. Friedman J, Hastie T, Tibshirani R, Narasimhan B, Tay K, Simon N, et al. glmnet:
Lasso and Elastic-Net Regularized Generalized Linear Models [Internet]. 2008 [cited
2025 Jul 29]. p. 4.1-10. Available from: https://CRAN.R-project.org/package=glmnet
doi:10.32614/CRAN.package.glmnet

44. Mouselimis L, Contributor) MP (Github: G. KernelKnn: Kernel k Nearest Neighbors
[Internet]. 2023 [cited 2025 Jul 29]. Available from: https://cran.r-
project.org/web/packages/KernelKnn/index.html

45. Karatzoglou A, Smola A, Hornik K, Zeileis A. kernlab - An S4 Package for Kernel
Methods in R. Journal of Statistical Software. 2004 Nov 2;11:1–20.
doi:10.18637/jss.v011.i09

46. Venables WN, Ripley BD. Modern Applied Statistics with S [Internet]. New York, NY:
Springer; 2002 [cited 2025 Jul 29]. (Chambers J, Eddy W, Härdle W, Sheather S,
Tierney L, editors. Statistics and Computing). Available from:
http://link.springer.com/10.1007/978-0-387-21706-2 doi:10.1007/978-0-387-21706-2

47. Breiman L. Random Forests. Machine Learning. 2001 Oct 1;45(1):5–32.
doi:10.1023/A:1010933404324

48. original) LB (Fortran, original) AC (Fortran, port) AL (R, port) MW (R. randomForest:
Breiman and Cutlers Random Forests for Classification and Regression [Internet].
2024 [cited 2025 Jul 29]. Available from: https://cran.r-
project.org/web/packages/randomForest/index.html

49. Wright MN, Ziegler A. ranger: A Fast Implementation of Random Forests for High
Dimensional Data in C++ and R. Journal of Statistical Software. 2017 Mar 31;77:1–
17. doi:10.18637/jss.v077.i01

50. Therneau T, Atkinson B, port BR (producer of the initial R, maintainer 1999-2017).
rpart: Recursive Partitioning and Regression Trees [Internet]. 2025 [cited 2025 Jul
29]. Available from: https://cran.r-project.org/web/packages/rpart/index.html

51. Enea M, LTD) RM (on behalf of DmwA, LTD) TK (on behalf of DmwA. speedglm:
Fitting Linear and Generalized Linear Models to Large Data Sets [Internet]. 2023
[cited 2025 Jul 29]. Available from: https://cran.r-
project.org/web/packages/speedglm/index.html

52. Ripley B, Venables B, Bates DM, ca 1998) KH (partial port, ca 1998) AG (partial
port, polr) DF (support functions for. MASS: Support Functions and Datasets for
Venables and Ripley's MASS [Internet]. 2025 [cited 2025 Jul 29]. Available from:
https://cran.r-project.org/web/packages/MASS/index.html

53. Chen T, He T, Benesty M, Khotilovich V, Tang Y, Cho H, et al. xgboost: Extreme
Gradient Boosting [Internet]. 2025 [cited 2025 Jul 29]. Available from: https://cran.r-
project.org/web/packages/xgboost/index.html

Additional Files

Additional file 1, png: Figure S1. Molecular Landscape Comparison of CU and RWC. CU and RWC merged cohort's OncoPlot, representing AML phenotypic and genotypic features per-patient. +ve refers to the number of patients with positive features and the % refers to that positive feature proportion. Light grey regions represent missing data. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Additional file 2, docx: Table S1. Default, and used, SL algorithm library with descriptions. All SL learner algorithms used in our default library within the SL-based imputation function. *Abbreviations:* Super Learner (SL).

Additional file 3, png: Figure S2. Merged Cohort Variable Missingness. CU and RWC merged cohort's variable missingness ratios. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Additional file 4, png: Figure S3. Merged Cohort Missingness Heatmap – Cytogenetic Testing. CU and RWC merged cohort's missingness heatmap for all observations and binary cytogenetics variables. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC), Cytogenetics (CYT).

Additional file 5, png: Figure S4. Merged Cohort Missingness Heatmap – Mutations. CU and RWC merged cohort's missingness heatmap for all observations and binary mutation variables. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Additional file 6, png: Figure S5. Merged Cohort Missingness Heatmap – Lab Values. CU and RWC merged cohort's missingness heatmap for all observations and continuous laboratory values variables. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC), Laboratory Values (LAB).

Additional file 7, png: Figure S6. Top 10 Predictors for TP53 Mutation. Top 10 predictors for

the TP53 mutation binary variable from the merged CU and RWC cohorts. *Abbreviations:*

University of Colorado (CU), Real World Cohort (RWC).

Additional file 8, png: Figure S7. Top 10 Predictors for LDH Lab Value. Top 10 predictors for

the LDH continuous variable from the merged CU cohort and RWC. *Abbreviations:* Lactate

Dehydrogenase (LDH), University of Colorado (CU), Real World Cohort (RWC).

Additional file 9, png: Figure S8. Risk stratification-stratified Kaplan Meier OS curves

comparing the SL-based ensemble's imputation of risk stratification variables and the MICE-

based imputation of risk stratification variables. Note, imputations for this additional analysis

were re-run on updated data, reflecting 6 new observations. *Abbreviations:* Overall Survival

(OS), Multiple Imputations by Chained Equations (MICE), Super Learner (SL), Log-Rank test

(LR), Tarone-Ware test (TW), Fleming-Harrington early-weighted test (FH:e), Fleming-

Harrington late-weighted test (FH:l).

Additional file 10, html: HTML-based illustration that contains the core MVI function code in

its most recent version as well as serving as a tutorial of the function's arguments, outputs, and

how to apply it in an example using synthetic data.

Learner	Description
SL.bayesglm	Bayesian generalized linear modeling for estimating linear relationships between predictors and outcomes, incorporating prior distributions to stabilize estimates.[37]
SL.caret.rpart	Recursive partitioning via the *caret* package, building decision trees by recursively splitting data into homogeneous groups for prediction.[38]
SL.cforest	Conditional inference forests from the *party* package, combining multiple conditional inference trees with resampling to reduce variable selection bias.[39]
SL.glm	Standard generalized linear model from base R.[40]
SL.glm.interaction	Generalized linear model including specified interaction terms to capture variable interplay.[40]
SL.glmnet	Penalized regression with elastic net regularization, balancing LASSO and ridge penalties for improved prediction and feature selection in high-dimensional settings.[41,42]
SL.kernelKnn	Kernelized k-nearest neighbors using flexible distance metrics to identify local patterns in predictor space [43].
SL.ksvm	Support vector machines from the *kernlab* package, capable of handling nonlinear classification or regression through hyperplane-based separation.[44]
SL.mean	Simple mean imputation serving as a baseline for comparison with more complex learners.
SL.nnet	Feed-forward neural network modeling complex nonlinear relationships between predictors and outcomes.[45]
SL.randomForest	Classic random forest implementation that builds ensembles of classification or regression trees using random subsets of data and predictors.[46,47]
SL.ranger	High-speed random forest implementation optimized for large, high-dimensional datasets.[48]
SL.rpart	Recursive partitioning and regression trees for interpretable, hierarchical data modeling.
SL.rpartPrune	Modified version of *rpart* that applies pruning to reduce overfitting and improve generalizability.[49]
SL.speedglm	Optimized generalized linear modeling for large datasets, improving computational performance over standard GLMs [50].
SL.step	Stepwise regression for variable selection using both forward and backward selection.[45,51]
SL.step.forward	Stepwise regression using forward selection only [45,51].
SL.stepAIC	Stepwise regression based on Akaike's Information Criterion via the *MASS* package.[45,51]
SL.xgboost	Gradient boosting machine implementation that sequentially builds trees to correct previous errors, often achieving strong predictive performance in tabular data.[52]

Merged Cohort Variable Missingness

Merged Cohort Missingness Heatmap - Cytogenetic Testing

Merged Cohort Missingness Heatmap - Mutations

Data Missing   TRUE   FALSE

Merged Cohort Missingness Heatmap - Lab Values

Top 10 Predictors for TP53 Mutation

Top 10 Predictors for LDH Lab Value