A Comparative Analysis in a Clinical Cohort: Multiple Imputation by Chained Equations and a Novel Super Learner-Based Imputation Approach

Tony Zbysinski[1], PhD (iD) ; Lezhou Wu[1], PhD; Justin Dale[1], BBA; James Coates[1], MS;

Karan Sapiah[1], MS; Jamie Reuben[1], MPH; Frank Markson[1], BA; Ujjwal Kulkarni[1], MS;

Nazmul Islam[1], PhD

[1]RefinedScience, Aurora, Colorado

Corresponding author:

Tony Zbysinski III, PhD

RefinedScience, 2115 N Scranton Street, Suite 2-70

Aurora Colorado, 80045, USA

Phone: +17637428523

Email: tony.zbysinski@refinedscience.com

Acknowledgements: We give additional acknowledgement and great gratitude to the

internal reviewers of RefinedScience and external reviewers of Flatiron Health.

Declaration of conflicting interests: All authors are affiliated with RefinedScience and

receive compensation as part of employment under RefinedScience. The authors

declare no other conflicts of interest.

Funding: This research received no specific grant from any funding agency in the public,

commercial, or non-profit sectors.

Ethical Approval: This retrospective study was approved by The Colorado Multiple Institutional Review Board (COMIRB) and used a limited dataset with a waiver of consent. The Flatiron Health data that supported the findings of this study were originated by and are the property of Flatiron Health, Inc.

Data Availability: The raw, individual patient data are protected and not available due to data privacy laws. The processed data are available at reasonable requests to the corresponding author. The Flatiron Health data that supported the findings of this study originated by and are the property of Flatiron Health, Inc., which has restrictions prohibiting the authors from making the data set publicly available. Requests for data sharing by license or by permission for the specific purpose of replicating results in this manuscript can be submitted to PublicationsDataAccess@flatiron.com. Lastly, upon publication, the SL-based imputation function will be accompanied by an HTML-based illustration that provides a concise, step-by-step walkthrough that enables users to quickly understand its purpose, inputs, outputs, and performance metrics, and to apply the function to their own datasets.

Abstract

Background: Missing data is a challenge in clinical research, especially in real-world data (RWD), where complete case analysis can bias results and reduce power. Ensemble learning approaches like Super Learner (SL) show strong numerical performance for prediction problems, but their use for missing value imputation (MVI) in oncology datasets is unexplored. We sought to develop and evaluate a novel SL-based imputation function that can impute multiple variables and quantify uncertainty.

Methods: We analyzed two independent cohorts of acute myeloid leukemia patients (n=1641). The SL-based MVI function includes data processing, predictor selection, binary and continuous variable pipelines, and performance measurement. Performance was compared to multiple imputation by chained equations (MICE) using balanced accuracy, F_1-score, root mean square error (RMSE), and visualizations.

Results: In a numerical experiment with 9 clinically important features, the proposed MVI function imputed and achieved higher balanced accuracy than MICE for 7/9 variables (mean balanced accuracy 89.04% vs 80.75%) with comparable performance for other variables. The continuous variable SL ensemble showed comparable RMSE (582) relative to MICE (597).

Conclusions: This study demonstrates that the SL-based imputation function improves accuracy over MICE in high-dimensional RWD while providing novel, observation-level uncertainty quantification.

MeSH keywords: Acute Myeloid Leukemia, Data Science, Machine Learning, Uncertainty, Imputation, Missingness

1 Introduction

Data missingness is a common occurrence in clinical research and poses a

persistent threat to the validity of statistical inference and the strength of predictive

models. Missing values can arise for several reasons such as instrument failure, patient

dropout, or recording decisions driven by underlying patient characteristics.[1,2] These

challenges lead to reduced statistical power, biased effect estimates, and compromised

precision, ultimately undermining predictive modeling efforts.[3,4] As real-world data

(RWD) sources grow in volume and complexity, particularly in high-dimensional settings

such as electronic health records or genomic repositories, the challenge of appropriately

handling missingness increases. Traditional approaches like complete-case analysis

become unrealistic in many scenarios and can propagate selection bias.[5]

Early work on missing data classified the mechanisms by which values are

missing. These include missing completely at random (MCAR), missing at random

(MAR), and missing not at random (MNAR). Such mechanisms are one part of

understanding which imputation approach is needed.[3] Classical single and multiple

imputation techniques, such as mean/median/mode substitution or multiple imputation

via chained equations (MICE), provide straightforward and satisfactory solutions under

MCAR and MAR assumptions, but can perform poorly when these assumptions are

violated or when variable interdependencies are complex.[6,7] Machine learning (ML)

methods including k-nearest neighbors (k-NN), random forests, support vector

machines, and others have typically demonstrated improved performance over purely

statistical methods, particularly for moderate missingness and MAR settings.[7–9] Deep

learning approaches, such as generative adversarial imputation networks and

variational autoencoders, offer promise in capturing nonlinear relationships and high-

order interactions,[5,10] but comparative studies against well-established algorithms like

missForest and MICE in RWD scenarios have shown that conventional methods remain

competitive or superior in practice at this time. This is likely due to the volume of tuning

parameters and the dataset size requirements of deep learning approaches.[11]

Despite the broad array of available imputation strategies, no single method

uniformly or consistently outperforms others across mechanisms, domains, and

dimensionalities.[12] In clinical settings, where variable distributions may be skewed and

the mechanisms of missingness are frequently a complex mix of MCAR, MAR, and

MNAR, ensemble learning techniques hold particular promise by combining multiple

base learners to hedge against model-specific weaknesses.[12] The Super Learner (SL)

framework implements a stacking ensemble that uses cross-validation (CV) specific risk

estimates, risk being a term used for brevity when referring to objective functions top

optimally weight ML algorithms (e.g. minimizing mean squared error). In this approach it

combines the strengths of multiple semi-parametric or non-parametric models to make a

balanced single weighted imputation of missing values,[13,14] unlike MICE which is a more

iterative process. It has been applied and tested for missing value imputation (MVI) in

previous literature, showing superior performance in at least synthetic data compared to

more popular methods such as MICE.[15] Outside of MVI, but within the clinical domain,

SL-based approaches have yielded strong results for numerous prediction-related

tasks.[16–20] However, SL's adoption for imputation in clinical RWD has been limited

despite its ability to outperform traditional methods. This advancement is critical given

the potential impact of imputation on downstream tasks, such as treatment effect

estimation, risk stratification, and clinical decision-making.

This study addresses a key gap in application by evaluating the performance of

MVI techniques using a SL-based approach on a high-dimensional dataset. In addition,

we build on this approach by introducing a novel function designed to greatly simplify

the imputation process with SL and provide measures of uncertainty for other modeling

tasks. The evaluation is conducted on clinical data comprising acute myeloid leukemia

(AML) patients treated with venetoclax plus azacitidine (Ven/Aza) or cytarabine plus

anthracycline (7+3). We experiment with varying missingness ratios and mixed or

unknown missingness mechanisms to reflect realistic challenges in clinical data

analysis. By benchmarking our SL-based imputation function against a conventional

statistical technique and selected ML methods, we aim to determine whether a SL-

based approach can deliver more robust and accurate imputations under clinical RWD

conditions and provide uncertainty measures for downstream tasks. Our specific

objectives are threefold: 1. Develop a novel user-friendly SL-based imputation function

capable of iteratively imputing multiple target variables while quantifying uncertainty

measures for other modeling purposes; 2. Apply the SL-based imputation function to

impute missing diagnostic patient AML data and quantify numerical performance of

singular learners of the ensemble; 3. Compare the SL-based imputation function's

predictive performance to state-of-the-art MICE performance. Note the proposed model

is disease-agnostic and thus can be applied beyond AML without loss of generalizability.

While we confine our objectives to imputing baseline features for convenience, the

function can be generalized and extended to imputing values at other clinically relevant

time-points.

Methods

Data Description

This study leveraged data from two cohorts (n=1641) of adult patients (aged ≥ 18

years) with newly diagnosed AML. Briefly, these patients were treated with Ven/Aza or

7+3. The University of Colorado (CU) cohort included 546 patients that began treatment

in a clinical trial between January 2015 and March 2024 in the UCHealth system. Data

is continuously updated over time as follow-up progresses, where follow-up ends at

date of death, loss to follow-up, or until the most recent follow-up update. We censor

patients only to their last known alive date. The real world cohort (RWC) was derived

from the nationwide Flatiron Health electronic health record-derived, de-identified,

longitudinal database consisting of patient-level structured and unstructured data

curated via technology enabled abstraction and was comprised of 1095 patients from 87

unique sites of care.[21,22] Flatiron Health dataset patients had a minimum of two

documented clinical visits between January 2014 and December 2023 and received the

Ven/Aza treatment as frontline therapy. The de-identified data is sourced from

approximately 280 cancer clinics across the United States, including 800 sites of care

primarily within community oncology settings. Inclusion and exclusion criteria were

applied to minimize systematic differences between the cohorts, as discussed by Islam

et al.[23] Specifically, patients were excluded if they had acute promyelocytic leukemia,

biphenotypic leukemia, chronic myeloid leukemia in blast crisis, or central nervous

system involvement at diagnosis. A more thorough description of this data can be found

in previous literature.[23] Supplementary Figure S1 describes via a visual summary the

genetic alteration patterns of both the RWC and the CU cohorts. Figure 1 illustrates the

5 key steps of our novel SL-based imputation framework, providing an overview of the

processes detailed in the following sections on specification and data processing,

imputation pipelines, performance assessment, and our application in high-dimensional

clinical data.

Specification and Data Processing

Step 1 includes all manual data pre-processing for the purpose of having correct

data format and structure for the developed SL-based imputation function. Data pre-

processing included, for our analysis, only variables measured at baseline (e.g.,

cytogenetic testing or laboratory measured values at diagnosis or treatment start date).

The function accepts input data containing continuous and binary variable types;

multinomial and ordinal features need to be transformed into a design matrix with binary

columns before applying the MVI function. In our application, diagnostic clinical

variables were harmonized between cohorts by merging on identified common

Figure 1. SL-based MVI imputation function methods flow diagram. *Abbreviations:* Median Absolute Deviation (MAD), Multiple Imputation by Chained Equations (MICE), Missing Value Imputation (MVI), Super Learner (SL).

variables. All dichotomous variables were made binary following traditional conventions

for reference groups, coding values such as "No" or "Wild Type" as 0. To enhance

imputation performance and reduce noise, variables considered irrelevant to modeling,

including patient identifiers, upper and lower reference ranges for laboratory values,

unknown data flags, and non-binary or non-continuous variables, were excluded during

preprocessing, leaving 124 variables.

Step 2 specifies the SL-based imputation function and its interim preprocessing

steps. This function accepts 4 parameters. The target_vars parameter takes a vector of

binary or continuous variables for imputation. We recommend ordering these variables

from least to most missingness, or from least to most importance, as the function's

iterative imputation scheme can leverage earlier imputations to improve subsequent

estimates. The learners and screeners parameters are user-defined character vectors

listing the base learners and screening wrappers to be incorporated into the SL calls. A

comprehensive list of available wrappers can be retrieved using the listWrappers

function in the SuperLearner package.[13] The final parameter, df_input, specifies the input

dataset, formatted according to the structure described in step 1.

In step 3, interim processing, the SL-based imputation function constructs the SL

library, removes variables produced by earlier imputations that are irrelevant for

subsequent targets, identifies the top predictors for each target variable, handles

missingness in those predictors, and identifies the target variable as binary or

continuous. An embedded utility function generates all possible combinations of user-

specified base learners and screening wrappers. For example, if conditional forest and

neural network learners are selected alongside correlation- and t-test-based screeners,

each learner is paired with each screener to create a SL library of four unique algorithm

inputs. It is important to note that the function has a built-in method of identifying and

ranking top potential predictors based on missingness and correlation, reducing the

demand for screener specification. To enhance interpretability in downstream outputs, a

mapping of learner names is also established. If a user does not specify any base

learning or screening wrappers, a default library of 19 learners is used with no

screeners. These learners are listed with a brief description and reference in

Supplementary Table S1. While users may incorporate most available base learner

wrappers and screeners within the SL framework, doing so may quickly become

computationally infeasible, particularly in high-dimensional settings. Predictor selection

is performed by first excluding variables generated during previous iterations (e.g., row

ID trackers, uncertainty weights, confidence interval outputs) that do not inform

estimation. For the remaining candidate predictors, a predictor score is computed as the

product of (i) the absolute Pearson correlation with the target variable and (ii) the

proportion of observed (non-missing) data, elevating predictors that are both informative

and well-represented in the dataset. By default, the top 10 predictors ranked by this

score are selected, keeping the next steps informed, parsimonious, and reducing

overfitting. The number of predictors to use in modeling is a customizable parameter.

Since the SL framework requires complete predictor data and missingness is prevalent

in RWD, simple internal imputation is applied, median imputation for continuous

variables and mode imputation for binary variables. This simple imputation step is used

solely within the function and is not returned in the final output. Target variables with

>80% missingness are flagged, and then the top predictor's and target variable's data is

subset for subsequent SL-based methods to reduce dimensionality.

SL-based Binary Imputation Pipeline

Step 4a defines the binary target variable pipeline, encompassing several key

processes: (i) class balance checks, (ii) performance benchmarking via MICE, (iii) the

core SL prediction process with CV, (iv) optimal threshold selection for classification, (v)

resampling for accuracy variability, (vi) imputation of missing data, and (vii) generation

of uncertainty weights. A class balance check identifies severely imbalanced binary

variables. If one class comprises more than 92.5% of observations, or a class has equal

to or less than 20 observations, a flag is triggered, and mode imputation is applied

instead of SL-based modeling, as extreme imbalance can cause k-fold cross-validation

to fail. In this case, a simple weight is assigned equal to the observed class proportion

to reflect reduced uncertainty. For performance benchmarking of MICE, 30% of

observed values are randomly masked, and MICE, using 5 imputations, is applied using

a predictor matrix built from the input data. This provides a reference for comparison

against the SL-based approach. The SL process then performs nested modeling and

validation, where each base learner is trained and validated within cross-validation folds

to generate predictions. These predictions are then combined by the meta-learner to

optimize ensemble performance and minimize error.[13] Within this pipeline, each learner

undergoes 10-fold CV to estimate accuracy, and an outer CV loop (via CV.SuperLearner)

evaluates the entire SL estimation process to provide performance estimates. The

model uses the top 10 predictors identified in step 3, with simple internal imputation

applied to handle missingness, and optimizes predictions for the area under the ROC

curve (AUC). We next find the optimal threshold for classifying predicted probabilities by

maximizing AUC when class imbalance is below 90%. In scenarios of 90-92.5% class

imbalance, the F_1-score was prioritized over AUC as it better reflects the trade-off

between precision and recall and provides a more informative measure of performance

for the minority class. Estimated probabilities obtained from the CV process are

resampled 1000 times with replacement. This resampling enables calculation of

confidence intervals for balanced accuracy, quantifying between subject variability in

classification performance by applying the same threshold to each bootstrap replicate.

Additionally, by resampling from the predicted distribution, computational feasibility is

increased while accounting for uncertainty to an extent. The CV.SuperLearner object

cannot directly estimate unseen data, we therefore rerun the SL process using

snowSuperLearner with identical arguments to generate imputations for truly missing

values.

SL-based Binary Imputation Uncertainty

A similar 1000 resampling scheme is applied and the 2.5th and 97.5th percentiles

of these samples form 95% observation-specific uncertainty intervals, reflecting

variability in potential imputed predicted probabilities. The previously determined optimal

threshold is applied to classify the original predicted probability and the lower 2.5th and

upper 97.5th predicted probabilities. Finally, uncertainty weights are assigned to each

imputed observation's predicted probabilities to reflect classification confidence. These

weights are calculated, as seen in Equation 1, by taking the absolute difference

between the predicted probability of each observation, $\hat{p}_i$ and the optimal threshold τ,

scaled by the maximum possible distance to that threshold.

$$\text{weight}_i = |\hat{p}_i - \tau| \, / \, \max(\tau, 1 - \tau) \tag{1}$$

Predicted probabilities closer to the threshold receive lower weights, reflecting higher

uncertainty, while those further away approach a weight of 1, normalizing uncertainty

values between 0 and 1 while observed data is assigned a weight of 1.

SL-based Continuous Imputation Pipeline

202  Step 4b describes the continuous target variable pipeline, which mirrors the

binary pipeline but is adapted for continuous outcomes. After selecting the top 10

predictors and applying simple internal imputations to handle missingness among these

predictors, a MICE-based comparison is conducted with specifications consistent with

Step 4a. The SL CV process is then performed using 10-fold CV, a Gaussian family, and

a non-negative least squares (NNLS) loss function to estimate performance for each

base learner and the ensemble. The final SL ensemble model is subsequently trained

on all observed data for the selected predictors and used to impute missing values in

the target variable, producing direct value imputations rather than probabilities.

SL-based Continuous Imputation Uncertainty

212  Imputation uncertainty for each imputed observation is quantified using a

residual-based bootstrap approach, generating 1000 resampled imputations by adding

resampled residuals to model-predicted values. To account for heteroskedasticity, the

bootstrap resampling process selects the 50 residuals closest to each predicted value

based on Euclidean distance from the observed target values, ensuring that resampled

errors are drawn from observations with similar outcome magnitudes. The 2.5th and

97.5th percentiles of these samples form 95% observation-specific uncertainty intervals,

reflecting variability in potential imputed values. Observation-specific uncertainty

weights for continuous variables are shown in equation 2, calculated as the inverse of 1

plus the median absolute deviation (MAD) of the bootstrap sample distribution per

observation, B_i, normalized by the mean predicted value of the observation-specific

bootstrap distribution $\bar{p}_i$, thereby assigning higher weights to imputed values with lower

relative variability.

225
$$\text{weight}_i = 1 / (1 + (\text{MAD}(B_i) / \bar{p}_i)) \qquad (2)$$

226 These outputs provide both a point estimate and observation-specific uncertainty

227 intervals, enabling other analyses to account for uncertainty and down-weight less

228 certain imputations.

Performance Assessment and Application

Step 5 involves data output, iterative imputation, and comprehensive

performance assessment. The SL-based imputation function produces an interim

dataset in which each target variable is sequentially replaced by its imputed counterpart,

supplemented with observation-specific uncertainty weights. The output additionally

includes observation-specific 95% estimation uncertainty intervals that capture model

uncertainty, enabling downstream analyses to consider a plausible range of imputed

values rather than relying on single-point estimates. This augmented dataset is

iteratively updated as each variable in the input vector is imputed, ultimately yielding a

complete dataset supported with uncertainty-aware outputs. In addition to the final

imputed data, the proposed imputation function returns a suite of diagnostic metrics and

visualizations, providing strong transparency into the imputation process over standard

methods like MICE. These include visualizations of top predictor scores for each target

variable, flags for variables with >80% missingness, benchmark MICE performance

metrics (confusion matrices and F_1-scores for binary variables, RMSE, root mean

square error, for continuous variables), and illustration of average CV risk estimates for

every base learner in the SL ensemble (risk being RMSE for continuous variables, AUC

for binary variable). The function also reports ensemble-level performance measures,

balanced accuracy with bootstrap-based confidence intervals for binary targets, optimal

thresholds for classification, and visualization of average ensemble weights based on

nested CV folds illustrating each learner's contribution to the SL model. Predicted

values or probabilities are visualized along with resampling distributions. Furthermore,

computing time is provided for both the independent MICE run and the final SL

ensemble that is trained for imputation. Collectively, these outputs deliver not only a fully

imputed dataset but also a novel, uncertainty-aware, and performance-benchmarked

framework, offering users enhanced interpretability and awareness in the resulting

imputations compared to conventional MVI approaches.

We summarize general descriptives of our merged 1641 patient cohort via counts

for categorical variables and median and IQR for continuous variables. Additionally we

describe missingness of the entire cohort leveraging the naniar R package.[25]

Missingness descriptives include missingness prevalence and visualizations to aid in

identification of missingness patterns. In our initial testing application of this novel SL-

based imputation function, we selected variables that have been previously identified in

analyses of our data as high priority for upfront risk stratification and clinical relevance.[23]

These binary flag variables include NPM1 mutation, IDH1 mutation, IDH2 mutation,

good risk cytogenetics as based on SWOG,[26] inv(3) abnormality, TP53 mutation, -17

abnormality, t(9;11) abnormality, -5 abnormality, complex cytogenetics, and FLT3-ITD

mutation. Given that these variables do not include a continuous data type, we

additionally selected the laboratory-measured lactate dehydrogenase (LDH) value

variable for continuous variable evaluation due to its prognostic importance.[27] We

ordered all selected variables from least to most missingness and supplied this vector to

the MVI function, reporting summarizations of the previously mentioned performance

metrics. In our application, we used the default 19 learner algorithms library. This

diverse selection of learners ensures that the SL library balances simple benchmarks,

linear and nonlinear models, tree-based approaches, penalized regression, and modern

machine learning methods, enhancing flexibility and robustness in the estimation

procedure and accounting for algorithmic uncertainty. To enable deeper insight into the

SL-based imputation's behavior and output data, we further isolated TP53 mutation and

LDH to conduct a more detailed evaluation of SL predictive performance. This deeper

comparison examined the performance of individual base learners, highlighting one

algorithm that emerged as the top-performing single learner, referred to as the discrete

learner. For SL processes, parallelization was configured using the $parallel$ R package,

and for resampling parallelization was configured using the $future$ R package,[24] both

leveraging maximum cores available. All statistical analyses were performed in R

version 4.4.1.[28]

Results

Descriptive Results

General cohort and target variable descriptive statistics are available in Table 1.

Most of the 1641 patient cohort were male (703, 57.16%), White (1211, 73.8%), not

Hispanic or Latino (1302, 79.34%), deceased at follow-up (1042, 63.5%), on the

Table 1. Merged cohort and target variable descriptive results and missingness.

Variable and Type	Count (%, n=1641)	Missingness Count and Ratio
Categorical		
Sex		0%
Female	703 (42.84)	
Male	938 (57.16)	
Race		201 (12.25)
Asian	17 (1.04)	
Black	76 (4.63)	
Other	136 (8.29)	
White	1211 (73.80)	
Ethnicity		256 (15.60)
Hispanic or Latino	78 (4.75)	
Not Hispanic or Latino	1302 (79.34)	
Not Reported	5 (0.30)	
Secondary AML		0%
No	1076 (65.57)	
Yes	565 (34.43)	
Vital Status		0%
Censored To Last Known Alive Date	599 (36.50)	
Deceased	1042 (63.50)	
Treatment		0%
7+3	187 (11.40)	
Ven/Aza	1454 (88.60)	
Data Source		0%
CU Cohort	546 (33.27)	
Real World Cohort	1095 (66.73)	
Good Risk Cytogenetics	88 (5.36)	3 (0.18)
Complex Cytogenetics	269 (16.39)	38 (2.32)
Inv(3) abnormality	21 (1.28)	362 (22.06)
T(9;11) abnormality	17 (1.04)	362 (22.06)
-5 abnormality	182 (11.09)	367 (22.36)
-17 abnormality	109 (6.64)	368 (22.43)
IDH2 Mutation	182 (11.09)	584 (35.59)
IDH1 Mutation	104 (6.34)	592 (36.08)
NPM1 Mutation	193 (11.76)	617 (37.60)
FLT3-ITD Mutation	123 (7.50)	700 (40.27)
TP53 Mutation	249 (15.17)	744 (45.34)
Continuous	**Median (IQR)**	
Age at Enrollment	74 (67-79)	0%
LDH	285 (190-487)	889 (54.17%)

Abbreviations: Acute Myeloid Leukemia (AML), University of Colorado (CU), Lactate Dehydrogenase (LDH).

Ven/Aza treatment regime (1454, 88.60%), and de novo AML (1076, 65.57%). Median

age at enrollment was 74 (IQR 67-79). The target variables had missingness ratios that

ranged from as low as 0.18% for good risk cytogenetics (3/1641) to high missingness of

54.17% for LDH (889/1641). Supplementary Figure S2 displays missingness ratios

across all variables in the merged dataset, missingness across all variables can be

summarized as highly diverse. Supplementary Table S2 shows all variables categorized

as either binary or numeric and then sorted by missingness thresholds for a more

comprehensive description of missingness. Broadly, most variables were binary and

had 40-80% missingness. Supplementary Figures S3-5 demonstrate missingness

feature categories of cytogenetics, mutations, and lab values, respectively. Taken

together, these missingness figures indicate primarily arbitrary and block patterns of

missingness.

Primary Results

Table 2 details the performance for nearly all binary target variables of interest,

comparing the performance of the SL-based ensemble approach to MICE. Variables

inv(3) and t(9;11) abnormalities are not shown as they had high class imbalance and as

a result were defaulted to the simple imputation pipeline. Performance measures

included balanced accuracy, F_1-score, and computational time. The SL-based ensemble

approach had a greater mean balanced accuracy, 89.04%, than MICE, 80.75% and had

superior balanced accuracy for 7 out of 9 variables, with 2 out of 9 variables having

comparable (<1% difference) balanced accuracy. The mean F_1-score for MICE, 94.34%,

and the SL-based ensemble approach, 96.25%, were more mixed and slightly favoring

the SL-based ensemble approach. Lastly, computational time was on average longer for

Table 2. Performance of all binary target variables of interest compared between MICE
and the SL-based imputation function approach.

Variable	MICE Balanced Accuracy (%)	SL Balanced Accuracy (95% CI[a], %)	MICE F$_1$-score (%)	SL F$_1$-score (%)	MICE Time (seconds)	SL-based Time[b] (seconds)
Good Risk Cytogenetics	92.68	96.93 (94.11-99.15)	98.91	99.61	0.79	137.67
Complex Cytogenetics	95.04	98.88 (98.45-99.26)	98.08	98.86	0.72	203.89
-5 abnormality	63.1	82.69 (79.89-85.36)	90.47	87.82	0.42	190.88
-17 abnormality	58.03	57.58 (54.38-61.16)	92.53	95.98	0.55	116.01
IDH2 Mutation	69.63	94.93 (92.87-96.63)	88.93	97.52	0.51	131.08
IDH1 Mutation	95.99	95.19 (92.05-97.69)	98.57	99.47	0.46	178.63
NPM1 Mutation	86.69	93.65 (91.54-95.71)	95.95	97.22	0.48	123.61
TP53 Mutation	91.78	95.27	94.68	98.02	0.44	127.77
FLT3-ITD Mutation	87.22	95.67 (93.12-97.81)	90.91	91.71	0.53	95.65

[a] 95% confidence intervals represent the SL CV loop's 1000 resamples with classified via the optimal threshold for measures of precision for balanced accuracy.
[b] SL-based time refers to only the SL model trained for prediction and not the CV loop for performance measures.
Abbreviations: Multiple Imputation by Chained Equations (MICE), Super Learner (SL), Cross-Validation (CV).

the SL ensemble trained for imputation, 145 seconds, compared to MICE, 0.5 seconds.

In our specific performance analysis of the SL-based ensemble and MICE approaches

of TP53 mutation and LDH imputation, we found that the SL-based approach was

mostly superior to MICE. For TP53 mutation imputation, MICE had a balanced accuracy

of 91.8%, sensitivity 93.7%, specificity 89.9%, and an F$_1$-score of 94.7% while the SL-

based ensemble approach had respective values of 95.3%, 99.4%, 91.2%, and 98.0%.

Compared to the SL-based ensemble approach, the discrete learner of the ensemble

had comparable performance (balanced accuracy 95.3%; sensitivity 99.4%; specificity

91.2%; F$_1$-score 97.9%) and another select algorithm for comparison, GLM interaction,

had worse performance (balanced accuracy 91.7%; sensitivity 96.6%; specificity 87.8%;

F_1-score 95.8%). Supplementary Figure S6 shows the top 10 predictors of the TP53

mutation variable that were used in the SL-based approach, indicating that several

previous target variables that were imputed supported the imputation of TP53 mutation.

Figure 2 shows the CV-specific base learner risks for TP53 mutation, suggesting that

most base learners performed well (>0.9 AUC) with conditional forest having the

absolute minimum risk observed. Figure 3 demonstrates the subsequent average

assigned weights of the SL-based ensemble's learners where many of the learners can

be perceived to receive comparable weights as the SL technique aims to reduce

overfitting. Lastly, for TP53 mutation, Figure 4 shows the predicted probability and

corresponding resampled distribution of predicted probabilities based on 1000

resamples. With a calculated optimal threshold of 0.38 and the observed predicted

Figure 2. Cross-validated base learner risks for binary TP53 mutation variable prediction, risk measured as AUC. *Note:* multiple points may appear because of multiple default hyperparameter settings. *Abbreviations:* Area Under the Curve (AUC).

Figure 3. Cross-validated SL ensemble weight averages for binary variable TP53 mutation. *Abbreviations:* Super Learner (SL).

Figure 4. SL-based ensemble's predicted probability density distribution for TP53 mutation binary variable data with overlapping 1000 resampled density distribution. *Abbreviations:* Super Learner (SL).

probabilities, we would estimate that most classifications were 0 and were likely

assigned moderate uncertainty weights. This is validated when analyzing the

distribution of the TP53 mutation uncertainty weights (median 0.52, IQR 0.45-0.53).

With respect to LDH, results were more mixed. MICE had a RMSE of 597, higher than

that of the SL-based ensemble's RMSE of 582. Furthermore, the discrete learner of the

ensemble performed best with 557 RMSE, and other algorithms including neural

network and all GLM algorithms, performed far worse with >5000 RMSE.

Supplementary Figure S7 displays the top 10 predictors of the LDH variable that were

used in the SL-based approach. Figure 5 shows the average CV-specific base learner

risks for LDH. The SL-based ensemble's learner's average weights are shown in Figure

6, supporting a narrower range of base learners unequally. Figure 7 displays the SL

Figure 5. Cross-validated base learner average risks for continuous variable LDH, risk measured as RMSE. *Abbreviations:* Root Mean Square Error (RMSE), Lactate Dehydrogenase (LDH).

Figure 6. Cross-validated SL-based ensemble average weights for continuous variable LDH. *Abbreviations:* Super Learner (SL), Lactate Dehydrogenase (LDH).

ensemble's predicted values density distribution for LDH and the corresponding density

distribution of resampled values based on 1000 resamples, suggesting introduced

variation. Subsequent weights indicate moderate to high certainty and relatively small

variability of imputations across resamples compared to the observed data's variation

(median 0.81, IQR 0.80-0.83). Our computing setup with 48 cores and 188 GB of RAM,

with parallelization and a 19-learner library, processed 11 binary targets and a

continuous target in approximately 2.5 hours.

Discussion

356   In this study we evaluated a SL-based ensemble imputation approach for

357   handling missing diagnostic data in a dataset comprised of 1641 newly diagnosed AML

358   patients treated with Ven/Aza or 7+3. Leveraging the SL framework, we demonstrated

359   consistently improved imputation performance over a commonly used statistical

Figure 7. SL-based ensemble's predicted values density distribution for missing LDH continuous variable data, overlayed with the 1000 resampled density distribution. Figure was log transformed after running the function for interpretability. *Abbreviations:* Lactate Dehydrogenase (LDH).

method, MICE, specifically for binary genetic variables, even when they had substantial

missingness. On average, the SL-based ensemble achieved higher balanced accuracy

(89.0% vs 80.8%) and F1 score (96.3% vs 94.3%) compared to MICE across 9 binary

genetic features. In focused evaluations of TP53 mutation and LDH laboratory values,

the SL-based ensemble approach led to superior or comparable performance to

singular algorithms and uncertainty weights. These results underscore the potential of

SL-based methods to enhance data integrity in clinical prediction pipelines, especially in

high-dimensional electronic health record derived datasets where conventional single-

model approaches may struggle. To our knowledge, this study represents one of the

first applications of the SL-based ensemble for missing value imputation in a clinical

oncology context. Furthermore, we demonstrate the method's utility by achieving strong

performance while introducing novel, observation-level uncertainty estimates which

quantify variation, while being delivered through a streamlined, user-friendly function

that automates imputation, performance evaluation, and data output.

Prior studies into missing value imputation in clinical cohorts have repeatedly

shown that standard approaches such as MICE can yield reasonable accuracy when

data are moderately complete and missingness mechanisms approximate MAR, but

their performance often deteriorates in high-dimensional or block-missing contexts.[7,29]

MICE has strong advantages such as being well-documented and easily applied.[30]

These strengths are evident by the notable abundance of MICE's application in health

research literature, with MICE serving as either the primary imputation method or the

benchmark comparison. An earlier 2015 review by Rezvan et al. with narrow search

criteria showed the dominance of MICE in imputation methodology in medical research,

with 53% (20/38) of research articles reporting methods of imputation using MICE.[31]

ML-based methods like random forest and k-NN have improved on MICE's limitations in

several ways such as by capturing nonlinear feature relationships.[5,8] In the systematic

review of 94 ML performance assessing research articles by Alabadla et al. it was found

that across most studies k-NN, random forest, and support vector machine methods

performed best, these results would agree with our rankings of ML algorithms by AUC

and RMSE. This study also noted though the lack of, and need for, computational time

reporting and consistency across performance measures to best evaluate overall

performance.[7] Another study that analyzed high dimensional genetic data compared

ML-based approaches to MICE and simple mean imputation, also finding that k-NN and

random forest typically performed far better than both of these approaches.[32] Such

popularity for k-NN, and other algorithms, is explained by a systematic review of 117

research articles by Thomas and Rajabi. The review clarifies that these algorithm's easy

implementation across knowledge domains make them an attractive option. However,

these authors also note that despite such popularity there continues to be no single

universal solution to the missing data problem.[33] While ML-based methods have grown

immensely in popularity and application frequency since 2015,[7] in part due to

improvements over MICE and simple imputation, as previously mentioned these

methods remain relatively constrained by the reliance on a single learner that may have

varying performance for different missingness scenarios. Ensemble learning

approaches may prove an effective next step to overcome these challenges. While

using a more typical ensemble strategy compared to our SL-based strategy, our results

would concur with those found by Batra et al. who found that a stacked ensemble

strategy proved superior to simple imputation and several singular ML algorithms.[12] In a

different context than imputation, a 2023 review of 45 articles evaluated ensemble

learning approaches in highly researched disease prediction. They concluded that

amongst these studies, those that employed the stacking method of ensemble learning

performed best compared to other ensemble methods. This work gives us greater

confidence in our findings using a SL-based approach.[14] Prior literature using super

learning for missing data imputation is sparse, however, one study showed that multiple

imputation by super learning yielded superior results compared to traditional methods in

a comparative analysis. Albeit, this application was limited by synthetic data, not having

quantified uncertainty, and a process that did not automatically generate performance

measures.[15] Lastly, many imputation strategies do not automatically provide

observation-level uncertainty estimates. Our results extend prior work by demonstrating

that a CV-specific stacking ensemble can more effectively integrate varying base

learners to handle diverse variable missingness contexts, and when incorporated into a

function, can also output measures of uncertainty.

Despite the promising performance of our SL-based approach, our study has

several limitations. First, we employed default SL hyperparameters for all base learners

rather than performing extensive tuning. While this decision simplified the pipeline and

demonstrated robust gains over MICE by default, it may have missed additional

opportunities to further improve performance. Second, the computational burden of

training the CV-specific ensemble represents the greatest practical hurdle to routine

deployment. However, this cost is justified in settings where imputation accuracy and

uncertainty quantification materially impact other modeling tasks in high stakes clinical

applications such as risk stratification for patient-enrichment or treatment maintenance

decisions related to aggressive diseases like AML. Regarding the computational time of

the whole process, it was also longer than MICE but to quantify uncertainty from MICE

using traditional approaches of bootstrapping would likely incur even more

computational costs. Lastly, prior to ensemble fitting we perform simple imputation on

the top 10 predictors for each target, which may propagate initial error and contribute to

cumulative uncertainty. We partially mitigate this through our resampling-based

uncertainty weights, observations with high variance can be down-weighted in

downstream models. However, such bootstrapping-based uncertainty does not capture

within-subject variability and may be susceptible to the amount of missing data and

representation of the true missing data pattern in the bootstrap samples. More rigorous

initial imputation of predictors, such as using MICE,[34] and incorporation of initial subject-

specific uncertainty measures in imputation of target variables would further reduce this

concern. Conversely, our SL-based imputation function offers several key strengths. By

vectorizing imputation across diverse base learners, it provides a nearly fully

automated, scalable framework that consistently outperforms single-method

approaches in our application in high-dimensional clinical data. Additionally, while we

applied the function to AML data for evaluation, there stands no reason it cannot be

applied to other datasets. The model's ability to generate observation-specific

uncertainty weights and uncertainty intervals allow end-users to conduct a variety of

sensitivity analyses using these values across different settings. The flexibility of the SL

framework allows inclusion of new algorithms as they emerge, ensuring that the pipeline

can adapt to evolving patterns of data complexity and missingness. Finally, in line with

identified gaps in performance assessment in the literature[35] and combined with

descriptive statistics of missingness, the SL-based imputation function's performance

output allows a user to well understand key aspects of MVI including computational time

and common performance measures.

In summary, our work demonstrates that a SL-based imputation function can

significantly improve the accuracy and robustness of missing-value estimation in a high-

dimensional AML real-world dataset, outperforming the standard MICE approach for

most of our target variables while providing observation-level uncertainty metrics. These

findings support our central hypothesis that ensemble strategies yield more reliable

imputation in complex clinical data. In future deployments we hope to add automated

and customized hyperparameter optimization, integrate automatic support for

multinomial and ordinal targets, and further validate its utility in diverse missing data

formats and contexts. Future research would benefit from evaluating this function

among diverse disease areas, across a greater range of variables, and its impact on

optimizing risk stratification strategies. Ultimately, by combining improved performance

over traditional methods and flexibility, ensemble learning-derived imputation can

enhance downstream modeling by managing missingness' threat to validity.

Abbreviations

AML	Acute myeloid leukemia
AUC	Area under the curve
CU	University of Colorado
CYT	Cytogenetics
IRB	Institutional review board
k-NN	k-Nearest Neighbor
LAB	Laboratory values
LDH	Lactate dehydrogenase
MAR	Missing at random
MAD	Median absolute deviation
MCAR	Missing completely at random
MICE	Multiple imputation by chained equations
ML	Machine learning
MVI	Missing value imputation
NNLS	Non-negative least squares
RMSE	Root mean square error
RWC	Real world cohort
RWD	Real world data
SL	Super Learner
Ven/Aza	Venetoclax plus azacitidine
$\hat{p}_i$	Predicted probability
τ	Optimal threshold
B_i	Bootstrap samples
$\bar{p}_i$	Mean predicted value

References

1.   RUBIN DB. Inference and missing data. *Biometrika* 1976; 63: 581–592.

2.   Schafer JL, Graham JW. Missing data: our view of the state of the art. *Psychol Methods*
2002; 7: 147–177.

3.   Roderick J.A. Little and Donald B. Rubin (2002) Statistical Analysis with Missing Data,
2nd ed. John Wiley & Sons | RTI, https://www.rti.org/publication/roderick-j-little-donald-b-
rubin-2002-statistical-analysis-missing-data-2nd-ed-john-wiley-amp-sons-b (accessed 3
July 2025).

4.   Petersen I, Welch CA, Nazareth I, et al. Health indicator recording in UK primary care
electronic health records: key implications for handling missing data. *Clin Epidemiol* 2019;
11: 157–167.

5.   Liu M, Li S, Yuan H, et al. Handling missing values in healthcare data: A systematic
review of deep learning-based imputation techniques. *Artificial Intelligence in Medicine*
2023; 142: 102587.

6.   Buuren S van, Groothuis-Oudshoorn K. mice: Multivariate Imputation by Chained
Equations in R. *Journal of Statistical Software* 2011; 45: 1–67.

7.   Alabadla M, Sidi F, Ishak I, et al. Systematic Review of Using Machine Learning in
Imputing Missing Values. *IEEE Access* 2022; 10: 44483–44502.

8.   Stekhoven DJ, Bühlmann P. MissForest--non-parametric missing value imputation for
mixed-type data. *Bioinformatics* 2012; 28: 112–118.

9.   Ismail AR, Abidin NZ, Maen MK. Systematic Review on Missing Data Imputation
Techniques with Machine Learning Algorithms for Healthcare. *Journal of Robotics and*
Control (JRC) 2022; 3: 143–152.

10.   Afkanpour M, Hosseinzadeh E, Tabesh H. Identify the most appropriate imputation method
for handling missing values in clinical structured datasets: a systematic review. *BMC Med*
Res Methodol 2024; 24: 188.

11.   Sun Y, Li J, Xu Y, et al. Deep learning versus conventional methods for missing data
imputation: A review and comparative study. *Expert Systems with Applications* 2023; 227:
120201.

12.   Batra S, Khurana R, Khan MZ, et al. A Pragmatic Ensemble Strategy for Missing Values
Imputation in Health Records. *Entropy* 2022; 24: 533.

13.   'Super Learner In Prediction' by Eric C. Polley and Mark J. van der Laan,
https://biostats.bepress.com/ucbbiostat/paper266/ (accessed 25 June 2025).

14. Laan MJ van der, Polley EC, Hubbard AE. Super Learner. *Statistical Applications in Genetics and Molecular Biology*; 6. Epub ahead of print 16 September 2007. DOI: 10.2202/1544-6115.1309.

15. Carpenito T, Manjourides J. MISL: Multiple imputation by super learning. *Statistical Methods in Medical Research*. Epub ahead of print 5 June 2022. DOI: 10.1177/09622802221104238.

16. Murugesan S, Bhuvaneswaran RS, Nehemiah HK, et al. Feature Selection and Classification of Clinical Datasets Using Bioinspired Algorithms and Super Learner. *Computational and Mathematical Methods in Medicine*. Epub ahead of print 18 May 2021. DOI: 10.1155/2021/6662420.

17. Li S, Zhang Y, Fu K, et al. Machine learning ensemble meets clinical practice: developing a real-world risk prediction model for metabolic syndrome using super learner and scorecard approaches. *Journal of Advanced Research*. Epub ahead of print 27 June 2025. DOI: 10.1016/j.jare.2025.06.072.

18. Petersen ML, LeDell E, Schwab J, et al. Super Learner Analysis of Electronic Adherence Data Improves Viral Prediction and May Provide Strategies for Selective HIV RNA Monitoring. *J Acquir Immune Defic Syndr* 2015; 69: 109–118.

19. Jin W, Hao W, Shi X, et al. Using Multi-Modal Electronic Health Record Data for the Development and Validation of Risk Prediction Models for Long COVID Using the Super Learner Algorithm. *Journal of Clinical Medicine* 2023; 12: 7313.

20. Zhu X, Zhang P, Jiang H, et al. Using the Super Learner algorithm to predict risk of major adverse cardiovascular events after percutaneous coronary intervention in patients with myocardial infarction. *BMC Med Res Methodol* 2024; 24: 59.

21. Ma X, Long L, Moon S, et al. Comparison of Population Characteristics in Real-World Clinical Oncology Databases in the US: Flatiron Health, SEER, and NPCR. 2023; 2020.03.16.20037143.

22. Birnbaum B, Nussbaum N, Seidl-Rathkopf K, et al. Model-assisted cohort selection with bias analysis for generating large-scale cohorts from the EHR for oncology research. Epub ahead of print 13 January 2020. DOI: 10.48550/arXiv.2001.09765.

23. Islam N, Reuben JS, Dale JL, et al. A simplified risk model for pretreatment stratification of newly diagnosed acute myeloid leukemia patients treated with venetoclax and azacitidine. 2024; 2024.12.02.24318344.

24. Bengtsson H. future: Unified Parallel and Distributed Processing in R for Everyone, https://cran.r-project.org/web/packages/future/index.html (2025, accessed 29 July 2025).

25. Tierney N, Cook D, McBain M, et al. naniar: Data Structures, Summaries, and Visualisations for Missing Data, https://cran.r-project.org/web/packages/naniar/index.html (2024, accessed 30 July 2025).

543   26.   Slovak ML, Kopecky KJ, Cassileth PA, et al. Karyotypic analysis predicts outcome of
544   preremission and postremission therapy in adult acute myeloid leukemia: a Southwest
545   Oncology Group/Eastern Cooperative Oncology Group study. *Blood* 2000; 96: 4075–4083.

546   27.   Islam N, Reuben JS, Dale J, et al. Predictive Models for Long Term Survival of AML
547   Patients Treated with Venetoclax and Azacitidine or 7+3 Based on Post Treatment Events
548   and Responses: Retrospective Cohort Study. *JMIR Cancer* 2024; 10: e54740.

549   28.   R Development Core Team. R: A Language and Environment for Statistical Computing,
550   https://cran.r-project.org/ (2025).

551   29.   Jerez JM, Molina I, García-Laencina PJ, et al. Missing data imputation using statistical and
552   machine learning methods in a real breast cancer problem. *Artificial Intelligence in*
553   *Medicine* 2010; 50: 105–115.

554   30.   Zhang Z. Multiple imputation with multivariate imputation by chained equation (MICE)
555   package. *Ann Transl Med* 2016; 4: 30.

556   31.   Hayati Rezvan P, Lee KJ, Simpson JA. The rise of multiple imputation: a review of the
557   reporting and implementation of the method in medical research. *BMC Med Res Methodol*
558   2015; 15: 30.

559   32.   Petrazzini BO, Naya H, Lopez-Bello F, et al. Evaluation of different approaches for missing
560   data imputation on features associated to genomic data. *BioData Mining* 2021; 14: 44.

561   33.   Thomas T, Rajabi E. A systematic review of machine learning-based missing value
562   imputation techniques. *Data Technologies and Applications* 2021; 55: 558–585.

563   34.   Mera-Gaona M, Neumann U, Vargas-Canas R, et al. Evaluating the impact of multivariate
564   imputation by MICE in feature selection. *PLOS ONE* 2021; 16: e0254720.

565   35.   Lin W-C, Tsai C-F. Missing value imputation: a review and analysis of the literature
566   (2006–2017). *Artif Intell Rev* 2020; 53: 1487–1509.

567   36.   Gelman A, Su Y-S. arm: Data Analysis Using Regression and Multilevel/Hierarchical
568   Models. 2007; 1.14-4.

569   37.   Kuhn M. caret: Classification and Regression Training. 2007; 7.0–1.

570   38.   Strobl C, Boulesteix A-L, Zeileis A, et al. Bias in random forest variable importance
571   measures: Illustrations, sources and a solution. *BMC Bioinformatics* 2007; 8: 25.

572   39.   R Development Core Team. R: A Language and Environment for Statistical Computing,
573   https://cran.r-project.org/ (2010).

574   40.   Regularization Paths for Generalized Linear Models via Coordinate Descent | Journal of
575   Statistical Software, https://www.jstatsoft.org/article/view/v033i01 (accessed 29 July 2025).

41. Friedman J, Hastie T, Tibshirani R, et al. glmnet: Lasso and Elastic-Net Regularized
Generalized Linear Models. 2008; 4.1-10.

42. Mouselimis L, Contributor) MP (Github: G. KernelKnn: Kernel k Nearest Neighbors,
https://cran.r-project.org/web/packages/KernelKnn/index.html (2023, accessed 29 July
2025).

43. Karatzoglou A, Smola A, Hornik K, et al. kernlab - An S4 Package for Kernel Methods in
R. *Journal of Statistical Software* 2004; 11: 1–20.

44. Venables WN, Ripley BD. *Modern Applied Statistics with S*. New York, NY: Springer.
Epub ahead of print 2002. DOI: 10.1007/978-0-387-21706-2.

45. Breiman L. Random Forests. *Machine Learning* 2001; 45: 5–32.

46. original) LB (Fortran, original) AC (Fortran, port) AL (R, et al. randomForest: Breiman and
Cutlers Random Forests for Classification and Regression, https://cran.r-
project.org/web/packages/randomForest/index.html (2024, accessed 29 July 2025).

47. Wright MN, Ziegler A. ranger: A Fast Implementation of Random Forests for High
Dimensional Data in C++ and R. *Journal of Statistical Software* 2017; 77: 1–17.

48. Therneau T, Atkinson B, port BR (producer of the initial R, et al. rpart: Recursive
Partitioning and Regression Trees, https://cran.r-project.org/web/packages/rpart/index.html
(2025, accessed 29 July 2025).

49. Enea M, LTD) RM (on behalf of DmwA, LTD) TK (on behalf of DmwA. speedglm: Fitting
Linear and Generalized Linear Models to Large Data Sets, https://cran.r-
project.org/web/packages/speedglm/index.html (2023, accessed 29 July 2025).

50. Ripley B, Venables B, Bates DM, et al. MASS: Support Functions and Datasets for
Venables and Ripley's MASS, https://cran.r-project.org/web/packages/MASS/index.html
(2025, accessed 29 July 2025).

51. Chen T, He T, Benesty M, et al. xgboost: Extreme Gradient Boosting, https://cran.r-
project.org/web/packages/xgboost/index.html (2025, accessed 29 July 2025).

Supplementary Material

606   **Table S1**. Default, and used, SL algorithm library with descriptions.

Learner	Description
SL.bayesglm	Bayesian generalized linear modeling for estimating linear relationships between predictors and outcomes, incorporating prior distributions to stabilize estimates.[36]
SL.caret.rpart	Recursive partitioning via the *caret* package, building decision trees by recursively splitting data into homogeneous groups for prediction.[37]
SL.cforest	Conditional inference forests from the *party* package, combining multiple conditional inference trees with resampling to reduce variable selection bias.[38]
SL.glm	Standard generalized linear model from base R.[39]
SL.glm.interaction	Generalized linear model including specified interaction terms to capture variable interplay.[39]
SL.glmnet	Penalized regression with elastic net regularization, balancing LASSO and ridge penalties for improved prediction and feature selection in high-dimensional settings.[40,41]
SL.kernelKnn	Kernelized k-nearest neighbors using flexible distance metrics to identify local patterns in predictor space [42].
SL.ksvm	Support vector machines from the *kernlab* package, capable of handling nonlinear classification or regression through hyperplane-based separation.[43]
SL.mean	Simple mean imputation serving as a baseline for comparison with more complex learners.
SL.nnet	Feed-forward neural network modeling complex nonlinear relationships between predictors and outcomes.[44]
SL.randomForest	Classic random forest implementation that builds ensembles of classification or regression trees using random subsets of data and predictors.[45,46]
SL.ranger	High-speed random forest implementation optimized for large, high-dimensional datasets.[47]
SL.rpart	Recursive partitioning and regression trees for interpretable, hierarchical data modeling.
SL.rpartPrune	Modified version of *rpart* that applies pruning to reduce overfitting and improve generalizability.[48]
SL.speedglm	Optimized generalized linear modeling for large datasets, improving computational performance over standard GLMs [49].
SL.step	Stepwise regression for variable selection using both forward and backward selection.[44,50]
SL.step.forward	Stepwise regression using forward selection only [44,50].
SL.stepAIC	Stepwise regression based on Akaike's Information Criterion via the *MASS* package.[44,50]
SL.xgboost	Gradient boosting machine implementation that sequentially builds trees to correct previous errors, often achieving strong predictive performance in tabular data.[51]

608 **Table S2.** Merged cohort common variable's missingness ratio categories.

Missingness Ratio Category	Binary Variables	Continuous Variables
0%	20	3
<5%	5	0
5-20%	0	0
20-40%	25	10
40-80%	41	10
>80%	9	1

610 *Note:* Variables with >80% missingness include CD36 flow cytometry, FLT3 other PCR, IDH2 other PCR, FISH DEK rearrangement, IDH1 other PCR, FISH BCRABL rearrangement, peripheral blood blasts, NMP1 PCR, CEBPA PCR, and JAK2 other PCR. *Abbreviations:* University of Colorado (CU), Lactate Dehydrogenase (LDH), Polymerase Chain Reaction (PCR), Fluorescence In Situ Hybridization (FISH).

Figure S1. CU and RWC merged cohort's OncoPlot, representing AML phenotypic and genotypic features per-patient. +ve refers to the number of patients with positive features and the % refers to that positive feature proportion. Light grey regions represent missing data. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Figure S2. CU and RWC merged cohort's variable missingness ratios. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Figure S3. CU and RWC merged cohort's missingness heatmap for all observations and binary cytogenetics variables. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC), Cytogenetics (CYT).

Merged Cohort Missingness Heatmap - Mutations

Data Missing ☐ TRUE ☐ FALSE

Figure S4. CU and RWC merged cohort's missingness heatmap for all observations and binary mutation variables. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Merged Cohort Missingness Heatmap - Lab Values

Figure S5. CU and RWC merged cohort's missingness heatmap for all observations and continuous laboratory values variables. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC), Laboratory Values (LAB).

Figure S6. Top 10 predictors for the TP53 mutation binary variable from the merged CU and RWC cohorts. *Abbreviations:* University of Colorado (CU), Real World Cohort (RWC).

Figure S7. Top 10 predictors for the LDH continuous variable from the merged CU cohort and RWC. *Abbreviations:* Lactate Dehydrogenase (LDH), University of Colorado (CU), Real World Cohort (RWC).

624