Vision-Language Foundation Models Do Not Transfer to Medical Imaging Classification: A Negative Result on Chest X-ray Diagnosis

George Fisher*

December 6, 2025

Abstract

Vision-language models (VLMs) pretrained on web-scale data have achieved remarkable performance across diverse tasks, leading to widespread adoption in industry. A natural question is whether these powerful representations transfer to specialized medical imaging domains, and whether domain-specific medical pretraining improves transfer. We tested these hypotheses using two VLMs on the NIH ChestX-ray14 benchmark: Qwen2.5-VL (pretrained on web data) and BiomedCLIP (pretrained on 15 million PubMed biomedical image-text pairs). Both models dramatically underperformed compared to convolutional neural networks (CNNs) with ImageNet pretraining. The best VLM achieved F1=0.203 versus a CNN baseline of F1=0.811. Domain-specific pretraining provided marginal improvement: BiomedCLIP's frozen encoder achieved F1=0.161 versus Qwen's F1=0.124 (+30%), but this remains clinically inadequate. Fine-tuning both models led to catastrophic overfitting, with sensitivity collapsing from >65% to <15% as the models learned to predict "no disease" for all inputs. These results demonstrate that neither general-purpose nor medical-specific vision-language pretraining produces features suitable for dense multi-label medical imaging classification. For chest X-ray diagnosis, traditional CNNs with ImageNet pretraining remain substantially more effective than VLM-based approaches.

Keywords: vision-language models, transfer learning, medical imaging, chest X-ray, negative result, BiomedCLIP

1 Introduction

Large vision-language models (VLMs) have emerged as powerful foundation models capable of understanding both images and text. Models such as GPT, Claude, and open-source alternatives like Qwen-VL and LLaVA have demonstrated impressive zero-shot and few-shot capabilities across diverse visual understanding tasks. This success has driven rapid adoption: recent reports indicate that open-source Chinese VLMs are increasingly being used as drop-in replacements for proprietary systems in production applications across Silicon Valley startups [1], and in hospital settings [2].

A natural question arises: do these powerful visual representations transfer to specialized domains such as medical imaging? The hypothesis is plausible—VLMs are trained on billions of image-text pairs spanning enormous visual diversity, potentially learning universal visual features. Furthermore, domain-specific VLMs such as BiomedCLIP [3] have been pretrained on millions of biomedical image-text pairs, which might provide better initialization for medical tasks.

However, medical imaging presents unique challenges. Chest X-ray interpretation requires detecting subtle radiographic patterns—small opacities, cardiomegaly, pleural effusions—that differ fundamentally from the objects, scenes, and text that dominate web-scale training data. Furthermore, medical classification is inherently multi-label and class-imbalanced, with most images containing no pathology.

We tested whether vision-language pretraining transfers to medical imaging using two models: Qwen2.5-VL [4, 5], a state-of-the-art open-source VLM pretrained on web data, and BiomedCLIP [3], pretrained on 15 million biomedical image-text pairs from PubMed Central. We evaluated both on the NIH ChestX-ray14 benchmark [6], comparing against CNNs with ImageNet pretraining as described in our previous work [7].

---

*Independent Researcher. Email: george@georgefisher.com

Our results are unambiguous: neither VLM transfers effectively. While BiomedCLIP's domain-specific pretraining provides marginal improvement over Qwen (+30% F1 for frozen encoders), both dramatically underperform the CNN baseline. Fine-tuning leads to catastrophic overfitting regardless of model size or pretraining domain. These findings have practical implications for medical AI practitioners considering foundation models for clinical applications.

2 Methods

2.1 Dataset and Preprocessing

We used the NIH ChestX-ray14 dataset, comprising 112,120 frontal chest radiographs from 30,805 patients, each labeled for the presence or absence of 14 thoracic pathologies. Following established protocols to prevent data leakage, we performed patient-level splits: images from any given patient appeared in only one of training (70%), validation (15%), or test (15%) sets. Images were resized to 224×224 pixels for BiomedCLIP and 128×128 pixels for Qwen, normalized using ImageNet statistics.

2.2 Model Architectures

Qwen2.5-VL: We extracted the vision encoder from Qwen2.5-VL-3B-Instruct, a 3-billion parameter vision-language model. The vision encoder is a Vision Transformer (ViT) with approximately 668 million parameters, pretrained jointly on web image-text pairs using contrastive and generative objectives.

BiomedCLIP: We used BiomedCLIP-PubMedBERT_256-vit_base_patch16_224 [3], which employs a ViT-B/16 vision encoder with 86 million parameters. This model was pretrained on PMC-15M, a dataset of 15 million image-text pairs from 4.4 million PubMed Central scientific articles.

For both models, we attached a classification head consisting of a linear layer mapping the encoder's output embedding to 14 classes with sigmoid activation for multi-label classification.

2.3 Experimental Conditions

We evaluated two configurations for each model:

Frozen encoder: The pretrained ViT weights were frozen, using the model purely as a feature extractor. Only the classification head was trained. This tests whether VLM features are directly useful for medical imaging.

Unfrozen encoder: All parameters were trainable, allowing the vision encoder to adapt to the medical domain. This tests whether fine-tuning can rescue poor initial representations.

2.4 Training Details

Models were trained using binary cross-entropy loss with the AdamW optimizer. For frozen experiments, we used learning rate 10^{-3}; for unfrozen experiments, 10^{-4}. We used batch size 64 and trained with early stopping based on validation F1 score. Training was performed on an AWS g5.2xlarge instance with a single NVIDIA A10G GPU (24GB).

2.5 Baseline

Our baseline is a ConvNeXt-Base model [8] pretrained on ImageNet-1K, fine-tuned on ChestX-ray14 using identical splits and evaluation procedures, achieving F1=0.811 as reported in our previous work [7].

2.6 Evaluation Metrics

We report macro-averaged F1 score (primary metric), ROC-AUC, sensitivity, and specificity across all 14 pathology classes.

3 Results

Table 1 summarizes our findings. Both VLMs dramatically underperformed the CNN baseline across all configurations.

Table 1: Classification performance on ChestX-ray14 validation set

Model	F1	ROC-AUC	Sensitivity	Specificity
CNN Baseline (ConvNeXt)	0.811	0.94	0.76	0.99
Qwen Frozen	0.124	0.67	0.71	0.43
Qwen Unfrozen (best)	0.188	0.68	0.53	0.54
Qwen Unfrozen (final)	0.07	0.52	0.05	0.98
BiomedCLIP Frozen	0.161	0.74	0.66	0.68
BiomedCLIP Unfrozen (best)	0.203	0.69	0.29	0.90
BiomedCLIP Unfrozen (final)	0.08	0.55	0.14	0.97

3.1 Domain-Specific Pretraining Helps Marginally

BiomedCLIP's medical pretraining provided modest improvement over Qwen's web pretraining. With frozen encoders, BiomedCLIP achieved F1=0.161 versus Qwen's F1=0.124 (+30%). ROC-AUC improved from 0.67 to 0.74. However, even BiomedCLIP's best performance (F1=0.203) remains only 25% of the CNN baseline, far below clinical utility.

3.2 Both Models Exhibit Catastrophic Overfitting

Fine-tuning led to catastrophic overfitting for both models (Figures 1 and 2). The pattern is consistent: training loss collapses toward zero while validation loss rises, and sensitivity drops precipitously as specificity approaches 100%. This indicates both models learn the degenerate solution of predicting "no disease" for all inputs.

For Qwen (668M parameters), sensitivity collapsed from 71% to 5% over 16 epochs. For BiomedCLIP (86M parameters), sensitivity dropped from 100% to 14% over 42 epochs. The smaller BiomedCLIP model overfit more slowly but reached the same degenerate endpoint. Neither model size nor domain-specific pretraining prevented this failure mode.

Figure 1: **Training dynamics of fine-tuned Qwen vision encoder.** Left: Training loss decreases while validation loss increases after epoch 3. Center: F1 peaks at 0.188 then declines. Right: Sensitivity collapses from 71% to 5% while specificity rises to 98%.

Figure 2: **Training dynamics of fine-tuned BiomedCLIP vision encoder.** The same overfitting pattern occurs despite different pretraining: training loss collapses to near-zero while validation loss rises, and sensitivity drops from 100% to 14% as the model learns to predict "no disease" for all inputs.

Figure 3: **Training dynamics of frozen BiomedCLIP encoder.** With frozen weights, training is stable: validation loss remains flat, and sensitivity/specificity maintain reasonable balance (66%/68%). However, F1 plateaus at 0.161, far below the CNN baseline.

4 Discussion

Our results demonstrate that vision-language foundation models—whether pretrained on general web data or domain-specific medical images—do not provide transferable representations for dense multi-label medical imaging classification.

4.1 Why VLM Features Don't Transfer

Several factors likely contribute to this failure. First, **pretraining objective mismatch**: Both CLIP-style contrastive learning and VLM generative objectives optimize for image-text alignment, learning to match images with semantic descriptions. Medical imaging classification requires detecting subtle pixel-level patterns—small nodules, faint infiltrates, slight cardiac enlargement—that are rarely described in image captions, whether from the web or PubMed.

Second, **task structure mismatch**: VLM pretraining typically involves single-label or retrieval tasks. ChestX-ray14 is a 14-way multi-label classification problem with severe class imbalance (most images have no findings). The pretrained representations may not support the fine-grained, multi-label discrimination required.

Third, **capacity-data mismatch**: Both encoders (86M and 668M parameters) are overparameterized relative to the training data (78,000 images), enabling memorization rather than generalization. The degenerate "predict negative" solution exploits class imbalance while minimizing loss.

4.2 Domain-Specific Pretraining Is Insufficient

BiomedCLIP's advantage over Qwen (+30% F1 frozen, +8% unfrozen) confirms that pretraining domain matters. However, this improvement is insufficient for clinical use. The PMC-15M dataset contains diverse biomedical images (histopathology, diagrams, photographs) with figure captions optimized for publication rather than diagnostic description. This may not align well with the radiographic pattern recognition required for chest X-ray classification.

4.3 Implications for Practitioners

1. **VLMs are unsuitable** for dense multi-label medical classification, even with domain-specific pretraining.

2. **CNNs remain superior**: ImageNet-pretrained ConvNeXt achieves 4× higher F1 than the best VLM configuration.

3. **Beware overfitting**: Large pretrained encoders memorize medical datasets regardless of their pretraining source.

4. **Pretraining task matters more than domain**: The contrastive/generative objectives may be fundamentally misaligned with classification tasks.

4.4 Limitations

We tested two VLM families; other architectures might perform differently. We used a linear classification head; more complex heads might improve performance. We did not explore extensive hyperparameter tuning or regularization strategies that might mitigate overfitting.

4.5 Conclusion

Vision-language models do not transfer effectively to chest X-ray classification, regardless of whether they are pretrained on web data or biomedical images. The CLIP-style contrastive objective and VLM generative pretraining do not produce features suited for fine-grained, multi-label pathology detection. For medical imaging applications, traditional CNNs with ImageNet pretraining remain substantially more effective. Practitioners should be skeptical of claims that foundation models can readily replace domain-specific solutions in medical AI.

Corresponding Author

George Fisher
Email: GeorgeRFisher@gmail.com

Author Contributions

G.F. conceived the study, designed the experiments, conducted all data analysis, developed the training and evaluation infrastructure, performed the computational experiments, analyzed the results, and wrote the manuscript. All work was conducted independently without collaborators.

Funding

This research received no external funding and was conducted independently using personal resources.

Data Availability

The NIH ChestX-ray14 dataset is publicly available at https://nihcc.app.box.com/v/ChestXray-NIHCC.

Code Availability

Code for reproducing these experiments is available in the AWS S3 bucket `nih-chest-x-rays` in the `qwen` folder (region: us-east-2).

To list contents:

```
aws s3 ls s3://nih-chest-x-rays/qwen/ --no-sign-request
```

To download to a local 'qwen' folder:

```
aws s3 sync s3://nih-chest-x-rays/qwen ./qwen --no-sign-request
```

Competing Interests

The author declares no competing interests.

References

[1] Thorbecke, C. More of Silicon Valley is building on free Chinese AI (2025). URL https://www.nbcnews.com/tech/innovation/silicon-valley-building-free-chinese-ai-rcna242430.

[2] Bressem, K. K., Papaioannou, J.-A., Grundmann, P. *et al.* Benchmark evaluation of DeepSeek large language models in clinical decision-making. *Nature Medicine* (2025).

[3] Zhang, S. *et al.* BiomedCLIP: A multimodal biomedical foundation model pretrained from fifteen million scientific image-text pairs. *arXiv preprint arXiv:2303.00915* (2023). 2303.00915.

[4] Bai, J. *et al.* Qwen-VL: A frontier large vision-language model with versatile abilities. *arXiv preprint arXiv:2308.12966* (2023). 2308.12966.

[5] Wang, P. *et al.* Qwen2.5-VL technical report. *arXiv preprint arXiv:2502.13923* (2025). 2502.13923.

[6] Wang, X. *et al.* ChestX-ray8: Hospital-scale chest X-ray database and benchmarks on weakly-supervised classification and localization of common thorax diseases. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2097–2106 (2017).

[7] Fisher, G. Pretraining Diversity and Clinical Metric Optimization Achieve State-of-the-Art Performance on ChestX-ray14. *medRxiv* (2025).

[8] Liu, Z. *et al.* A ConvNet for the 2020s. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 11976–11986 (2022).