Vision-Language Models vs Autonomous AI Agents for Anterior Capsular Radial Folds: A Diagnostic Study

Ye Zhang†[1,2], MD; Lei Chen†[1,3], BEng; Wenhao Zhao[1,4], BEng; Hui Zhang[2], MD; Chunyan Qiao[2], MD; Zijian Liu[2], MD; Charlotte Hui Chung[1], Medical Student; Marcus Chun Jin Tan[1], MMed; Meng Wang[1,5], PhD; Yih Chung Tham[1,6,7], MD, PhD; Victor Koh[6], MD; Chingyu Cheng[1,5,7], MD, PhD; Dianbo Liu[1,4 #,] PhD

† These two authors contributed equally to this work as first authors.

1. Yong Loo Lin School of Medicine, National University of Singapore, Singapore.

2. Beijing Tongren Eye Center, Beijing Key Laboratory of Ophthalmology and Visual Science, Beijing Tongren Hospital, Capital Medical University, Beijing, China

3. Department of Public Health and AI, National Cancer Center Graduate School of Cancer Science and Policy, Korea

4. Department of Biomedical Engineering and Department of Electrical and Computer Engineering, National University of Singapore, Singapore.

5. Singapore Eye Research Institute, Singapore National Eye Centre, Singapore.

6. Eye Academic Clinical Program, Duke NUS Medical School, Singapore.

7. Ophthalmology & Visual Sciences Academic Clinical Program (EYE ACP), Duke-NUS Medical School, Singapore, Singapore.

Word Count: Abstract: 348 words; Main text: 3030 words.

[#] **Corresponding Author:** Dianbo Liu, Centre for Innovation and Precision Eye Health, Department of Ophthalmology, Yong Loo Lin School of Medicine, National University of Singapore, Singapore.

Email: dianbo@nus.edu.sg

Key Points

Question:

How do generalist vision–language models (VLMs) and autonomous AI agents compare with human graders in detecting brief, low-contrast intraoperative cues in surgical video?

Findings:

In this retrospective, multicenter diagnostic benchmarking study of 537 phacoemulsification video clips, VLMs showed limited discrimination of anterior capsular radial folds, even with few-shot prompting, whereas autonomous AI agents successfully generated supervised classifiers with substantially higher performance, approaching that of junior glaucoma specialists.

Meaning:

For fine-grained intraoperative video interpretation, task-specific classifiers engineered by autonomous agents currently demonstrate greater clinical relevance than generalist VLMs.

Abstract

Importance: Vision–language models (VLMs) enable generalist multimodal reasoning, but their ability to resolve brief, low-contrast cues in surgical video without task-specific training is uncertain. Autonomous artificial intelligence (AI) agents offer an alternative paradigm by autonomously generating supervised classifiers tailored to specific visual tasks.

Objective: To benchmark the performance of VLMs against supervised classifiers engineered by autonomous AI agents for detecting anterior capsular radial folds during continuous curvilinear capsulorhexis (CCC), and to compare both approaches with human graders.

Design, Setting, and Participants: This retrospective diagnostic study utilized a multicenter dataset of 537 CCC videos collected from Beijing Tongren Hospital (China), National University Hospital (Singapore), and the OphNet-APTOS public dataset.

Exposure: Presence or absence of anterior capsular radial folds during CCC, defined based on established expert consensus, was annotated at both clip and frame levels by senior glaucoma surgeons. Two analytic paradigms were evaluated: (1) direct zero-shot and few-shot inference using 11 generalist

and medical-specific VLMs on single frames and frame sequences; and (2) autonomous code generation by 4 AI agents to construct supervised image classifiers from labeled frames. Human comparison included 7 graders with varying levels of ophthalmic experience.

Main Outcomes and Measures: Discrimination of fold-positive versus fold-negative cases was assessed using macro-averaged precision, recall, and F1-score at the clip and frame levels. Secondary outcomes included comparisons with human graders.

Results: Among 537 video clips (7.32 ± 3.35 seconds), 156 (29.1%) were fold-positive. VLM performance was limited; the top-performing model, Qwen2.5-VL, achieved a mean F1-score of 0.519. Few-shot prompting improved GPT-4.1 performance (mean F1-score from 0.177 to 0.480) but remained unstable. In contrast, an agent-engineered classifier achieved an F1-score of 0.869 and an area under the receiver operating characteristic curve of 0.958. In comparison with human graders, the top agent-generated model (F1-score, 0.835) matched junior specialists (mean F1-score, 0.829), whereas fine-tuned VLMs (maximum F1-score, 0.606) underperformed all human graders.

Conclusions and Relevance: Generalist VLMs showed limited capacity to detect subtle intraoperative cues, whereas autonomous AI agents successfully constructed task-specific classifiers with near-clinical-level performance. These findings support agent-driven supervised modeling as a more effective strategy for fine-grained surgical video interpretation.

Introduction

Vision-Language models (VLMs) have demonstrated rapid progress in aligning visual and textual data, driving a shift toward "generalist" AI systems designed to handle diverse tasks using a single, pre-trained backbone. However, these models rely on broad training data that may lack the granular specificity required for high-stakes surgical diagnostics.[1-3] Even when fine-tuned, generalist VLMs remain constrained by their underlying architectures and often struggle to adapt to the unique visual domains of specific medical problems. Consequently, existing benchmarks which predominantly focus on static medical images or curated visual question–answering tasks do not evaluate whether a single generalist model can reliably resolve the subtle, transient, and low-contrast cues that characterize real-world operative video, or if their broad training introduces noise that obscures fine-grained clinical signals. [4-6]

In parallel, autonomous artificial intelligence (AI) agents have emerged as an alternative paradigm that aligns more closely with the principles of precision medicine. Rather than relying on direct inference from a fixed model, these agents act as autonomous engineers, generating executable code to build and train bespoke, task-specific supervised classifiers. By constructing a dedicated solution optimized for the specific constraints of a dataset, autonomous agents potentially offer a more personalized and robust approach to medical image analysis than one-size-fits-all generalist models.[7,8] However, whether this task-specific engineering offers superior diagnostic utility for complex surgical video interpretation remains unverified.

To address this uncertainty, we benchmarked these two contrasting strategies using anterior capsular radial folds at the initiation of continuous curvilinear capsulorhexis (CCC), a critical intraoperative sign suggestive of zonular instability in during cataract surgeries, as a stringent test case for fine-grained visual discrimination.[9,10] Prior work in ophthalmic AI has addressed surgical instrument detection, phase recognition, and risk prediction, but existing benchmarks have not systematically evaluated subtle intraoperative cues or compared VLM reasoning with autonomous code-generation approaches.[11-15] We curated a multicenter dataset of annotated capsulorhexis video clips and compared the diagnostic performance of leading generalist and medical-specific VLMs against task-specific classifiers autonomously engineered by AI agents. Furthermore, we contextualized these findings

against human graders of varying experience to assess whether the personalized adaptation offered by AI agents can bridge the performance gap between multimodal AI and clinical expertise.

Methods

Dataset, Annotation and Task

A multi-source dataset was assembled from three independent cohorts, restricted to the CCC phase. This phase was selected because anterior capsular radial folds typically manifest at CCC initiation, when the capsule is punctured and traction is transmitted through zonular fibers.

Beijing Cohort. A total of 215 phacoemulsification videos were retrospectively collected from Beijing Tongren Hospital under Institutional Review Board (IRB) approval. After excluding clips with inadequate visualization, 201 videos were included. Among these, 94 (46.8%) demonstrated radial folds, while 107 (53.2%) did not. Demographic characteristics are shown in Supplementary A.

Singapore Cohort. Thirty videos were obtained from National University Hospital, Singapore. Following screening for completeness, 27 were included for analysis. Of these, 6 (22.2%) demonstrated radial folds and 21 (77.8%) showed no folds.

OphNet–APTOS Public Dataset. The OphNet–APTOS repository was reviewed to supplement external data.[16] From 496 cataract surgery videos, 308 evaluable CCC clips were selected (one video contained two distinct segments). Expert annotation identified 56 (18.1%) clips with visible radial folds and 253 (81.9%) without.

Final Dataset. The combined dataset comprised 537 clips, with 156 (29.1%) labeled as fold-positive and 381 (70.9%) as fold-negative. All clips were limited to the CCC phase, with durations ranging from 5 to 20 seconds (mean ± standard deviation [SD]: 7.32 ± 3.35 s).

Figure 1. Overview of the study workflow.

(A) Data Collection and Annotation: A multi-center dataset of 537 continuous curvilinear capsulorhexis video clips were curated from three cohorts (Beijing, OphNet-APTOS, and Singapore) and annotated by experienced surgeons at both clip and frame levels. **(B) Prediction Tasks:** The study evaluates two AI paradigms: (1) **Vision-Language Models (VLMs) Inference**, where models perform direct reasoning on single frames (aggregated to clip level) or frame sequences via zero-shot and few-shot; and (2) Automatic AI agents, which autonomously generate, debug, and optimize code to train supervised classifiers using pre-partitioned CSVs. **(C) Evaluation & Analysis:** Comprehensive assessment includes quantitative metrics, qualitative analysis of VLMs' reasoning patterns and agent-generated code quality, and comparison against human experts.

Labeling was performed in two stages. Clip-level labels were assigned by two experienced glaucoma surgeons via consensus based on intraoperative observation (Beijing) or video review (Singapore/OphNet). Clips were classified as fold-positive or fold-negative based on visible radial folds at CCC initiation. Frame-level annotation was performed independently by a single experienced glaucoma surgeon. Videos were sampled at 1–2 fps and each frame underwent a two-step review: (1) identification of active tearing initiation (instrument contact with traction), and (2) assessment of radial fold presence. Frames representing pauses were excluded, resulting in a dataset of discrete tearing images.

Automated detection was formulated as a binary classification task (fold-positive vs. fold-negative). To evaluate diagnostic capabilities, we defined three distinct levels of analysis, ranging from static image recognition to temporal event understanding. Frame-Level Analysis: Evaluates perceptual limits using single static frames, isolating visual feature detection without temporal context. Clip-Level Analysis: Simulates a screening workflow favoring sensitivity. Using an "OR" aggregation rule, a clip is classified as positive if the model detects pathology in any constituent frame. Frame-Sequence Analysis: Assesses contextual reasoning using continuous video clips. The model processes the temporal sequence to distinguish pathological events from motion artifacts.

Two complementary task settings were established to test these levels: VLMs Inference, where models predicted folds in zero-shot or few-shot modes using frames or sequences (Supplementary B); and Agent-generated Supervised Classification, where AI agents were provided only with image paths and labels to generate executable training pipelines. Due to the complexity of temporal architectures, agent-generated models focused on frame-level classification.

VLMs Detection and Evaluation

We evaluated 11 VLMs utilizing their publicly released checkpoints without fine-tuning. These included 2 proprietary models (GPT-4.1, Gemini 2.5 Pro) and 9 open-source general-purpose or

medical-specific models included Qwen2.5-VL (7B)[17] and InternVL-3.5 (8B).[18] Medical-specific models included Lingshu (7B),[19] HuatuoGPT-Vision (7B),[20] MedGemma (4B),[21] HealthGPT,[22] QoQ-Med-VL (7B),[23] LLaVA-Med (v1.5-7B),[24] and the ophthalmology-focused OphthaReason.[25]

Inference was conducted at a uniform sampling rate of 2 frames per second. For single-frame analysis, static images were evaluated using zero-shot text prompts. Three prompt variants were tested (Supplementary C). For models supporting multiple inputs, a few-shot condition was added using three reference images (one normal case, two abnormal cases [mild and severe]) to aid in resolving subtle deformations. Additionally, continuous frame sequences were processed simultaneously to leverage temporal context for holistic prediction (Supplementary D). Performance was assessed using macro-averaged precision, recall, and F1-score across three levels of granularity: frame-level; clip-level; and frame-sequence level.

Automatic AI Agent Detection and Evaluation

Four autonomous AI agents (CodeX, Qoder, AIDE,[26] and GitHub Copilot powered by Claude Sonnet 4.5) with generating executable code for supervised image classification. The dataset was structured to ensure rigorous evaluation: Beijing and OphNet-APTOS cohorts were combined and split into training (60%), validation (20%), and internal test (20%) sets, while the Singapore cohort as an external test set. Guided by a standardized prompt (Supplementary E) and input CSV files, the agents executed an autonomous two-stage workflow. This process progressed from an initial code generation phase to an iterative optimization stage, where agents analyzed execution logs, error reports, and preliminary results to implement targeted refinements, such as modifying loss function weighting or tuning prediction thresholds. The final outputs were evaluated based on classification performance and code quality, utilizing an LLM-as-judge framework to assess modularity, documentation, robustness, engineering best practices, and efficiency (Supplementary F).

Human–AI Frame-Level Comparison

To contextualize AI performance, a single-frame classification benchmark was conducted using 729 frames (224 fold-positive) extracted from 100 expert-validated clips (50 positive, 50 negative). This setting isolated visual pattern recognition to ensure consistency with frame-level AI inference.

Seven human graders participated, stratified by experience: six glaucoma specialists from Beijing Tongren Hospital (two junior, two intermediate, two senior) and one medical student from Singapore. Graders independently classified frames while masked to ground truth, class distribution, and AI predictions. Standard metrics (macro-averaged) were calculated for individual graders and summarized by experience level to provide a comparative baseline.

Results

Performance of Vision-Language Models

Performance was evaluated across frame, clip, and frame-sequence levels using macro-averaged metrics (Supplementary G). At the frame level, GPT-4.1 benefited substantially from few-shot visual context, with F1-scores rising from 0.177 ± 0.035 (zero-shot) to 0.480 ± 0.055 (Figure 2[a]). Gemini 2.5 Pro exhibited moderate zero-shot performance (F1: 0.307 ± 0.134) with high sensitivity to prompt variations. Among open-source models, Qwen2.5-VL achieved the strongest overall results (few-shot F1: 0.519 ± 0.029). Notably, the medical-specific QoQ-Med-VL demonstrated superior stability, achieving a few-shot F1-score of 0.485 ± 0.004 and outperforming general-purpose models like InternVL-3.5 in zero-shot settings. Conversely, the ophthalmology-focused OphthaReason displayed inverse scaling, performing significantly better with text-only instructions (F1: 0.386 ± 0.155) than with visual examples (F1: 0.245 ± 0.172). Other medical models, including Lingshu, MedGemma, and LLaVA-Med, showed limited discriminative capacity, with F1-scores often falling below 0.170. HuatuoGPT-Vision and HealthGPT showed marked variability, ranging from functional performance to near-failure depending on prompt formulation.

Figure 2. Performance of Vision-Language Models in Detecting Anterior Capsular Radial Folds.

Comparison of model performance metrics (Precision, Recall, and F1-score) at the frame level (a) and aggregated clip level (b) via single-frame analysis. Models were evaluated under zero-shot (striped bars) and few-shot (solid bars) inference settings. Data are presented as the mean of 3 prompt variations; error bars indicate the Standard Deviation (SD). In the frame-level analysis, few-shot prompting yielded statistically significant improvements for GPT-4.1 and Qwen2.5-VL compared with zero-shot inference. *P < .05.

Clip-level aggregation amplified these trends (Figure 2[b]). Qwen2.5-VL remained the top performer (few-shot F1: 0.487 ± 0.046). GPT-4.1 improved with few-shot inputs (F1: 0.369 ± 0.118) but exhibited constrained recall in zero-shot modes. QoQ-Med-VL maintained high stability (F1: 0.430 ± 0.006), again surpassing general-purpose models in zero-shot tasks. OphthaReason continued its negative trend with few-shot prompting, while MedGemma and LLaVA-Med produced degenerate predictions with no variance. Frame-sequence analysis yielded similar hierarchies (Supplementary F). Qwen2.5-VL achieved the highest mean F1-score (0.461 ± 0.054) but with significant precision variability. QoQ-Med-VL followed closely (F1: 0.432 ± 0.011) with reduced volatility across prompting strategies. InternVL-3.5 and HuatuoGPT-Vision showed moderate performance but struggled to balance precision and recall, while Lingshu demonstrated limited effectiveness for temporal analysis.

Qualitative analysis of textual rationales and spatial attention provided further insights into

performance variability. Recurrent errors included the misinterpretation of surgical stages, frequently confusing initial punctures with later capsulorhexis phases, and the failure to recognize subtle, transient deformations. Classification was further hindered by temporal confounders, such as specular reflections. Moreover, spatial attention analysis using relative attention normalization,[27] which computes layer-wise attention ratios between task-specific and generic prompts from the final prompt token during the prefill phase, revealed consistently diffuse and poorly localized activation maps (Figure 3). Across these models, attention was predominantly distributed toward surgical instruments, suture lines, and periocular tissue rather than concentrated at the capsular puncture site itself. Even higher-performing models exhibited broad attention across the surgical field, indicating reliance on global contextual cues rather than anatomically focused visual grounding of the subtle capsular deformations critical for accurate classification.

Figure 3. Grad-CAM Visualization of Attention Patterns Across AI Paradigms.

Comparison of visual attention between generalist Vision-Language Models (VLMs; columns 2-5) and supervised classifiers engineered by autonomous AI agents (columns 6-9). For VLMs, heatmaps were generated via relative attention normalization applied to the final prompt token during the prefill phase, averaged across all attention layers. For agent-generated models, heatmaps were generated via Gradient-weighted Class Activation Mapping (Grad-CAM) applied to the final convolutional layer. Rows a-f represent distinct surgical cases containing anterior capsular radial folds; pink arrows in the original frames (column 1) indicate the ground-truth location of the pathology. Warmer colors (red/orange) indicate regions of high model activation.

Performance of AI Agents

Quantitative evaluation of agent-generated frame-level classifiers revealed distinct performance tiers (Figure 4; Supplementary H). GitHub Copilot achieved the highest overall effectiveness with an F1-score of 0.869 and a robust area under the receiver operating characteristic curve (AUROC) of 0.958. Qoder demonstrated the highest discrimination capability (AUROC: 0.960, F1: 0.859), while CodeX delivered comparable strong results (F1: 0.850, AUROC: 0.954). In sharp contrast, AIDE failed to produce a viable classifier, suffering from mode collapse (F1: 0.484, AUROC: 0.500) and an inability to differentiate between fold-positive and fold-negative frames.

Beyond classification metrics, code quality was assessed via a blinded LLM-as-judge protocol (GPT-5). Copilot and CodeX ranked highest (mean scores: 18.2 and 17.6), reflecting consistent engineering practices, effective modular design, and calibrated threshold tuning. Qoder maintained balanced quality (16.6) through optimized loss and scheduler implementations. AIDE scored substantially lower (9.2), as its reliance on an older backbone (GPT-4o) often resulted in incomplete pipelines or single-class predictions.

Grad-CAM visualizations (Figure 3) corroborated these findings[28]. Models generated by the top-performing agents (Copilot, Qoder, and CodeX) exhibited localized attention centered precisely on the capsulorhexis region, aligning with their superior quantitative metrics. Conversely, AIDE-generated models displayed diffuse, scattered attention patterns, failing to converge on anatomically relevant structures.

Figure 4. Comparative Performance and Code Quality of Four Automatic AI Agents.

The bar chart (left) displays classification metrics on the test set, while the radar chart (right) illustrates code quality scores (0–20) assessed by five dimensions.

Human and AI Comparison Results

To contextualize AI performance, frame-level classification was compared against seven human graders of varying experience using a held-out set of 100 clips. Human performance generally correlated with clinical seniority. Senior glaucoma specialists achieved the highest mean F1-score (0.905), characterized by balanced precision and recall. Intermediate specialists exhibited higher variability (mean F1: 0.810), while junior residents (mean F1: 0.829) and the medical student (F1: 0.830) showed consistent, comparable performance.

Benchmarking revealed distinct performance stratification between model types (Table 1). VLMs consistently underperformed all human graders. The best proprietary model, GPT-4.1, achieved an F1-score of 0.587, indicating a substantial gap in domain-specific recognition. Similarly, Qwen2.5-VL remained inferior to novice human graders even after fine-tuning (F1: 0.606), underscoring the limitations of generalist multimodal reasoning for detecting subtle intraoperative cues.

In contrast, agent-generated supervised classifiers approached human-level competence. GitHub Copilot achieved a macro-averaged F1-score of 0.835, matching junior specialists (0.829) and the

medical student (0.830), and exceeding the intermediate group average. CodeX also demonstrated competitive performance (F1: 0.812), comparable to attending physicians. While Qoder trailed slightly (F1: 0.774) due to lower recall, all top-tier agents significantly outperformed VLMs. Although no agent reached the expert ceiling established by senior specialists (mean F1: 0.905), these results demonstrate that autonomously constructed, task-specific classifiers can operate at a clinically meaningful level.

Table 1. Comprehensive Performance Comparison: Humans, AI Agents, and Vision-Language Models. This table presents a direct comparison of the top-performing AI agent and VLMs against human graders on a held-out subset of 100 video clips. All classification metrics are macro-averaged. Data are presented as Mean ± Standard Deviation for each metric and setting.

Evaluation Setting & Category	Model / Grader	Setting / Prompt	Precision	Recall	F1-Score
Human Experts	Senior glaucoma specialists (n=2)	Senior Specialists	0.905	0.907	0.905
	Intermediate glaucoma specialists (n=2)	Intermediate Specialists	0.836	0.832	0.810
	Junior glaucoma specialists (n=2)	Junior Specialists	0.821	0.863	0.829
	Medical Student (n=1)	Novice	0.823	0.873	0.830
AI Agent	GitHub Copilot	Supervised Classifier	0.835	0.837	0.835
	Codex	Supervised Classifier	0.811	0.813	0.812
	Qoder	Supervised Classifier	0.825	0.752	0.774
VLMs	Qwen2.5-VL	Fine-tuned	0.684	0.603	0.606
	GPT-4.1	Few-shot	0.588	0.666	0.587
	Qwen2.5-VL	Few-shot	0.804	0.555	0.568

Discussion

This study evaluated VLMs and autonomous code-generating agents on their ability to resolve brief, low-contrast cues in surgical video, using anterior capsular radial folds during CCC as a constrained test case. Across 537 annotated multicenter video clips, we compared zero-shot and few-shot VLM inference with agent-generated supervised classifiers and contextualized model performance against human graders with varying levels of clinical experience. These findings highlight both the potential and current limitations of general-purpose multimodal AI for fine-grained surgical video interpretation.

Principal Findings

This work introduces a multicenter surgical video dataset focused on phacoemulsification, providing a reproducible framework for evaluating fine-grained intraoperative classification under real-world variability. By integrating data from two Asian surgical centers (Beijing and Singapore) and a publicly available international repository, the dataset captures heterogeneity in surgical technique, imaging conditions, and operative context that is essential for benchmarking algorithmic generalization.

Evaluation of VLMs revealed a landscape characterized by strong prompt sensitivity and architectural dependence. Few-shot prompting partially mitigated performance deficits: for example, increasing GPT-4.1's F1-score from 0.177 to 0.480, but this reliance on visual exemplars underscores the difficulty generalist models face in grounding subtle surgical concepts, such as anterior capsular radial folds, through text alone. Among medical-specific models, performance was highly polarized: QoQ-Med-VL demonstrated stable and competitive discrimination (F1 approximately 0.48), comparable to leading generalist models such as Qwen2.5-VL, whereas other adapters (e.g., MedGemma and Lingshu) exhibited severe mode collapse. These findings indicate that domain pre-training alone does not guarantee fine-grained visual discrimination and may, in some architectures, introduce visual noise rather than clarity.

In contrast, autonomous code-generating agents consistently produced supervised classifiers that approached the performance of junior glaucoma specialists, substantially narrowing,

though not eliminating, the gap to expert observers. Human benchmarking further contextualized these results: VLMs underperformed across all levels of clinical experience, remaining below even junior specialists despite few-shot prompting or fine-tuning, whereas agent-generated classifiers achieved parity with junior specialists and medical trainees, although they did not reach the expert ceiling set by senior consultants.

Analysis of fine-tuning further highlighted the limitations of large multimodal models for this task. Although fine-tuning Qwen2.5-VL improved sensitivity (recall from 0.555 to 0.603), it did so at the expense of specificity (precision from 0.804 to 0.684), yielding an overall F1-score (0.606) well below that of agent-generated convolutional neural networks. Collectively, these findings suggest that for specialized, high-stakes intraoperative visual recognition, task-specific supervised models engineered by autonomous agents currently offer a more viable near-term path to clinical utility than general-purpose multimodal reasoning.

Comparison with Prior Work

Recent ophthalmic AI research has shifted from general performance reporting toward specialized benchmarks that probe clinically meaningful reasoning. This trend is exemplified by text-based resources such as BELO, which evaluate the clinical knowledge and reasoning of LLMs, as well as multimodal benchmarks including EyecareGPT and LMOD that focus on visual question answering.[29,30,31] Datasets such as MM-Retinal-Reason have further attempted to bridge basic pattern recognition with higher-level clinical reasoning, and more recently, EH-Benchmark has extended evaluation to agent-driven workflows and hallucination-related failures.[25,32]

Despite these advances, standardized benchmarks for intraoperative surgical video interpretation remain limited. Prior work has largely focused on static images or outpatient diagnostic scenarios, whereas the present dataset targets dynamic surgical events and a subtle visual cue observable only within a narrow temporal window at capsular puncture. In addition, by benchmarking autonomous code-generating agents alongside VLMs, our study introduces a complementary methodological perspective: assessing whether task-specific supervised

classifiers can be constructed without manual programming, which has received little attention in ophthalmic surgical AI.

Limitations

Several limitations of our study warrant discussion. First, the dataset reflects the relatively low clinical prevalence of zonular instability, resulting in substantial class imbalance, with fold-negative cases constituting about 70% of cohorts. This imbalance likely biases VLMs inference toward the majority class, favoring accuracy over sensitivity and contributing to the high precision but limited recall observed across models. To account for this imbalance and to ensure consistency between AI evaluation and human–AI comparison, we primarily reported macro-averaged precision, recall, and F1-scores, which weight both classes equally and provide a more appropriate assessment under skewed class distributions. Metrics such as sensitivity–specificity pairs or AUROC, while informative, were less suitable for direct comparison with human graders operating on the same imbalanced sample.

Second, the Singapore cohort was small, which limits the precision of external generalization estimates. Third, annotation of anterior capsular radial folds relied on binary labels without quantitative severity grading, and the frame-level annotations were performed by a single expert surgeon. Given the subtle and transient nature of early capsular folds, this approach introduces unavoidable subjectivity and precludes formal assessment of inter-rater reliability. Fourth, the frame sampling rate of 1-2 frames per second, although necessary for computational feasibility, may fail to capture brief visual cues occurring between sampled frames.

Future Directions

Future research may address these limitations through enhanced annotation strategies and methodological refinement. Incorporation of multi-expert annotation would enable formal assessment of inter-rater reliability and support the development of continuous or ordinal severity scales that better capture the spectrum of zonular instability. From a video-analysis

perspective, adaptive keyframe selection strategies that estimate the distribution of visual content could help identify the most informative frames, capturing fleeting pathological manifestations while reducing redundant information.[33]

In addition, comprehensive assessment of intraoperative zonular instability may require integration of multiple correlated signs beyond the capsulorhexis phase, including equator visibility, capsulorhexis flutter, and postoperative decentration. Future work may therefore explore multi-task learning approaches that jointly model these correlated indicators to improve overall diagnostic accuracy.

Conclusion

This benchmark demonstrates that generalist VLMs do not reliably resolve brief, low-contrast cues in surgical video, even with few-shot visual examples, whereas autonomous code-generating agents can construct supervised classifiers with substantially higher discriminative performance, approaching the level of junior glaucoma specialists. These findings reflect a methodological gap rather than a clinical determination and suggest that fine-grained surgical video interpretation currently relies on domain-trained models. The dataset provides a reference point for future work on temporal grounding and surgical video analysis.

ARTICLE INFORMATION

Author Contributions: Y. Zhang and D. Liu had full access to all of the data in the study and take responsibility for the integrity of the data and the accuracy of the data analysis.

Concept and design: Y. Zhang,   M. Tan, M. Wang, Y. Tham , C. Cheng, D. Liu.

Acquisition, analysis, or interpretation of data: Y. Zhang, L. Chen, W. Zhao, H Zhang, Chunyan Qiao, Zijian Liu,   Charlotte Hui Chung.

Drafting of the manuscript: Y. Zhang, L. Chen, M. Tan, M. Wang, Y. Tham , C. Cheng, D. Liu.

Critical review of the manuscript for important intellectual content: Y. Zhang, L. Chen, M. Tan, M. Wang, Y. Tham , C. Cheng, D. Liu.

Statistical analysis: Y. Zhang, L. Chen.

Administrative, technical, or material support: M. Tan, M. Wang, Y. Tham , C. Cheng, D. Liu.

Conflict of Interest Disclosures: None reported.

Data and Sharing Statement

Data Sharing: Deidentified full-length surgical videos supporting the findings of this study will be made publicly available. The released dataset includes complete phacoemulsification videos from the Beijing Tongren Hospital cohort, with **clip-level annotations** indicating major surgical phases (eg, incision, continuous curvilinear capsulorhexis, hydrodissection, phacoemulsification, cortical aspiration, intraocular lens implantation) and multiple intraoperative signs related to zonular instability. These annotations include equator visibility, anterior capsular radial folds at capsulorhexis initiation, capsulorhexis flutter during cortical aspiration, and capsulorhexis deviation after cortical aspiration. The dataset is available at https://huggingface.co/datasets/leonChen/Tongren-Zonular-Video. A data dictionary and detailed annotation descriptions are provided within the repository.

Code: All source code used for model training, evaluation, and analysis is publicly available at https://github.com/cherishleon/ZonularBench.

Timing and Access: The data and code are available at the time of publication and will remain accessible without time restriction.

Conditions of Use: The data may be used for noncommercial research purposes, including method development, benchmarking, and secondary analyses related to surgical video analysis. Users are required to cite the present study and comply with the repository's license terms.

Additional Information: No individual patient identifiers are included in the shared data. Institutional review board approval was obtained at the contributing institutions, and data sharing complies with applicable ethical and privacy regulations.

References

1. Munasinghe S, Gani H, Zhu W, et al. VideoGLaMM: A Large Multimodal Model for Pixel-Level Visual Grounding in Videos. arXiv. Preprint posted online November, 2024. doi:10.48550/arXiv.2411.04923

2. Wu J, Liu W, Liu Y, et al. A Survey on Video Temporal Grounding with Multimodal Large Language Model. arXiv. Preprint posted online August, 2025. doi:10.48550/arXiv.2508.10922

3. Pramanick S, Mavroudi E, Song Y, Chellappa R, Torresani L, Afouras T. Enrich and Detect: Video Temporal Grounding with Multimodal LLMs. arXiv. Preprint posted online October, 2025. doi:10.48550/arXiv.2510.17023

4. Orlando JI, Fu H, Barbosa Breda J, et al. REFUGE Challenge: A unified framework for evaluating automated methods for glaucoma assessment from fundus photographs. Med Image Anal. 2020;59:101570.

5. Liu H, Li L, Wormstone IM, et al. Development and Validation of a Deep Learning System to Detect Glaucomatous Optic Neuropathy Using Fundus Photographs. JAMA Ophthalmol. 2019;137(12):1353-1360.

6. Lau JJ, Gayen S, Ben Abacha A, Demner-Fushman D. A dataset of clinically generated visual

questions and answers about radiology images. Sci Data. 2018;5:180251

7. O'Byrne C, Abbas A, Korot E, Keane PA. Automated Deep Learning in Ophthalmology – AI That Can Build AI. Curr Opin Ophthalmol. 2021;32(5):406-412.

8. Silva PS, Zhang D, Jacoba CMP, et al. Automated Machine Learning for Predicting Diabetic Retinopathy Progression From Ultra-Widefield Retinal Images. JAMA Ophthalmol. 2024;142(3):171-177.

9. Venkateswaran N, Henderson BA. Loose zonules in cataract surgery. Curr Opin Ophthalmol. 2022; 33(1): 53-57.

10. Zhang H, Zhang Y, Zhang S, Cao K, Li D, Liu M, Liang J, Song J, Wang N, Qiao C. Zonulopathy Identified During Cataract Extraction in Patients With Primary Angle Closure Disease. J Glaucoma. 2023; 32(9): 783-791.

11. Ting DSW, Pasquale LR, Peng L, et al. Artificial intelligence and deep learning in ophthalmology. Br J Ophthalmol. 2019;103(2):167-175.

12. Shimizu E, Tanji M, Nakayama S, et al. AI-based diagnosis of nuclear cataract from slit-lamp videos. Sci Rep. 2023;13(1):22046.

13. Savastano MC, Rizzo C, Fossataro C, Bacherini D, Giansanti F, Savastano A, Arcuri G, Rizzo S, Faraldi F. Artificial intelligence in ophthalmology: Progress, challenges, and ethical implications. Prog Retin Eye Res. 2025:107:101374.

14. Müller S, Jain M, Sachdeva B, et al. Artificial Intelligence in Cataract Surgery: A Systematic Review. Transl Vis Sci Technol. 2024;13(4):20.

15. Leiderman YI, Gerber MJ, Hubschman JP, Yi D. Artificial intelligence applications in ophthalmic surgery. Curr Opin Ophthalmol. 2024;35(6):526-532.

16. Hu M, Xia P, Wang L, et al. OphNet: A Large-Scale Video Benchmark for Ophthalmic Surgical Workflow Understanding. In: Computer Vision – ECCV 2024. Vol 15062. Lecture Notes in Computer Science. Springer; 2024. doi:10.1007/978-3-031-73235-5_27

17. Bai S, Chen K, Liu X, et al. Qwen2.5-VL Technical Report. arXiv. Preprint posted online February, 2025. doi:10.48550/arXiv.2502.13923

18. Wang W, Gao Z, Gu L, et al. InternVL3.5: Advancing Open-Source Multimodal Models in Versatility, Reasoning, and Efficiency. arXiv. Preprint posted online August, 2025. doi:10.48550/arXiv.2508.18265

19. Team L, Xu W, Chan HP, et al. Lingshu: A Generalist Foundation Model for Unified Multimodal Medical Understanding and Reasoning. arXiv. Preprint posted online June, 2025. doi:10.48550/arXiv.2506.07044

20. Chen J, Gui C, Ouyang R, et al. HuatuoGPT-Vision, Towards Injecting Medical Visual Knowledge into Multimodal LLMs at Scale. arXiv. Preprint posted online June, 2024. doi:10.48550/arXiv.2406.19280

21. Sellergren A, Kazemzadeh S, Jaroensri T, et al. MedGemma Technical Report. arXiv. Preprint posted online July, 2025. doi:10.48550/arXiv.2507.05201

22. Lin T, Zhang W, Li S, et al. HealthGPT: A Medical Large Vision-Language Model for Unifying Comprehension and Generation via Heterogeneous Knowledge Adaptation. arXiv. Preprint posted online February, 2025. doi:10.48550/arXiv.2502.09838

23. Dai W, Chen P, Ekbote C, Liang PP. QoQ-Med: Building Multimodal Clinical Foundation Models with Domain-Aware GRPO Training. arXiv. Preprint posted online June, 2025. doi:10.48550/arXiv.2506.00711

24. Li C, Wong C, Zhang S, et al. LLaVA-Med: Training a Large Language-and-Vision Assistant for Biomedicine in One Day. arXiv. Preprint posted online June, 2023. doi:10.48550/arXiv.2306.00890

25. Wu R, Yao Y, Ma T, et al. Bridging the Gap in Ophthalmic AI: MM-Retinal-Reason Dataset and OphthaReason Model toward Dynamic Multimodal Reasoning. arXiv. Preprint posted online August, 2025. doi:10.48550/arXiv.2508.16129

26. Jiang Z, Schmidt D, Srikanth D, et al. AIDE: AI-Driven Exploration in the Space of Code. arXiv. Preprint posted online February, 2025. doi:10.48550/arXiv.2502.13138

27. Zhang J, Khayatkhoei M, Chhikara P, Ilievski F. MLLMs Know Where to Look: Training-free Perception of Small Visual Details with Multimodal LLMs. arXiv. Preprint posted online February, 2025. doi: 10.48550/arXiv.2502.17422

28. Selvaraju RR, Cogswell M, Das A, Ramakrishna Vedantam, Parikh D, Batra D. Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization. In: 2017 IEEE International Conference on Computer Vision (ICCV). IEEE; 2017:618-626. doi:10.1109/ICCV.2017.74

29. Srinivasan S, Ai X, Soon W, et al. BEnchmarking LLMs for Ophthalmology (BELO) for Ophthalmological Knowledge and Reasoning. arXiv. Preprint posted online July, 2025. doi:10.48550/arXiv.2507.15717

30. Li S, Lin T, Lin L, et al. EyecareGPT: Boosting Comprehensive Ophthalmology Understanding with Tailored Dataset, Benchmark and Model. arXiv. Preprint posted online April, 2025.

doi:10.48550/arXiv.2504.13650

31. Qin Z, Yin Y, Campbell D, et al. LMOD: A Large Multimodal Ophthalmology Dataset and Benchmark for Large Vision-Language Models. In: Findings of the Association for Computational Linguistics: NAACL 2025. Association for Computational Linguistics; 2025:2501-2522. doi:10.18653/v1/2025.findings-naacl.135

32. Pan X, Bai Y, Zou K, et al. EH-Benchmark: Ophthalmic hallucination benchmark and agent-driven top-down traceable reasoning workflow. Inf Fusion. 2026;126:103631. doi:10.1016/j.inffus.2025.103631

33. Guo W, Chen Z, Wang S, et al. Logic-in-Frames: Dynamic Keyframe Search via Visual Semantic-Logical Verification for Long Video Understanding. arXiv. Preprint posted online March, 2025. doi:10.48550/arXiv.2503.13139

Supplementary Material

A. Demographic and Ocular Characteristics of Patients from Beijing Cohort

Characteristic	Value
Patient Characteristics	**(N = 182)**
Age, median (IQR), y	68.0 (62.0–72.0)
Female sex, No. (%)	134 (73.6)
Medical History, No. (%)	
Hypertension	17 (14.5)
Diabetes	48 (26.4)
Hospital Campus, No. (%)	
West Campus	138 (75.8)
South Campus	44 (24.2)
Affected Eye (s), No. (%)	
Right eye	78 (42.9)
Left eye	85 (46.7)
Both eyes	19 (10.4)
OCULAR CHARACTERISTICS	**(N = 201 Eyes)**
Diagnosis, No. (%)	
Primary angle-closure glaucoma (PACG)	97 (48.3)
Acute primary angle closure (APAC)	48 (23.9)
Primary angle closure suspect (PACS)	32 (15.9)
Primary angle closure (PAC)	24 (11.9)
Surgical Procedure, No. (%)	
Phacoemulsification + GSL	117 (58.2)
Phacoemulsification + GSL + Goniotomy	79 (39.3)
Other combined procedures*	5 (2.5)
Capsular tension ring implantation	38 (18.9)
Biometry and Clinical Measures	
Median (IQR)	
Presenting visual acuity	0.40 (0.22–0.82)
Intraocular pressure (mm Hg)	16.0 (13.0–21.0)

Vertical cup-to-disc ratio	0.6 (0.3–0.8)
Central corneal thickness (μm)	526.0 (498.3–548.0)
Axial length (mm)	22.48 (21.96–22.98)
Mean ± SD	
Anterior chamber depth (mm)	2.20 ± 0.31
Lens thickness (mm)	5.05 ± 0.34

PACS, primary angle closure suspect; PAC, primary angle closure; PACG, Primary angle-closure glaucoma; APAC, Acute primary angle closure; PEI, phacoemulsification and intraocular lens implantation; GSL, goniosynechialysis; IR, Interquartile range; SD, standard deviation.

* Other combined procedures include: Phacoemulsification alone (n=2); Phacoemulsification + GSL + trabeculectomy (n=1); Phacoemulsification + GSL + anterior vitrectomy (n=1); and Phacoemulsification + anterior vitrectomy (n=1).

B. Overview of the VLMs inference pipelines.

Overview of the Vision-Language Models inference pipelines.

The top panel shows the Single-Frame Analysis, where reference images, a query image, and a task definition prompt are processed by the Vision-Language Model to generate a prediction. The bottom

panel shows the Frame-Sequence Analysis, utilizing a sequence of frames to provide temporal context, along with reference images and a specific prompt, leading to a prediction.

C. Prompt for VLMs for Single-Frame Analysis

V1: '''[MEDICAL DOCUMENT - CATARACT SURGERY ANALYSIS]

You are analyzing medical/surgical footage from a cataract extraction procedure (phacoemulsification). This is a routine ophthalmic surgical procedure.

Task: Does this frame show "Anterior capsule puncture with striae/folds"?

Definition: Puncture = Creation of an orifice in the anterior capsule using a needle or forceps. Surgical steps: - Inject viscoelastic - Anterior capsule puncture - Initiate capsulorhexis - Continue capsulorhexis - Complete capsulorhexis

Important: Only count striae if they appear during puncture. Ignore striae in later steps (e.g., capsulorhexis).

Output: YES or NO '''

V2: '''[MEDICAL DOCUMENT - OPHTHALMIC SURGICAL ANALYSIS]

You are reviewing frames from a cataract extraction procedure. This is a standard medical/surgical documentation task.

Question: Does this image show "Anterior capsule puncture with striae"?

Criteria:

- Look for a puncture being made with a needle/forceps.

- If folds radiate from this puncture point, answer YES.

- If no folds, or folds appear later in capsulorhexis, answer NO.

Output: YES or NO. '''

V3: '''[MEDICAL DOCUMENT - OPHTHALMIC SURGICAL ANALYSIS]

You are reviewing frames from a cataract extraction procedure. This is a standard medical/surgical documentation task.

Instruction: Assess whether this frame shows "Anterior capsule puncture with striae".

Checkpoints: Puncture = a needle or forceps is creating the first opening in the anterior capsule. Striae/folds must radiate from this puncture point at that moment. If striae appear only later in capsulorhexis, do not count.

Answer with: YES or NO. '''

D. Prompt for VLMs for Frame-Sequence Analysis

V1: '''Task: Determine whether the video sequence (seq) contains the surgical event "Anterior capsule puncture with striae/folds".

Definition:

- Puncture = the moment when a needle or forceps creates the very first opening in the anterior capsule.

- Striae/folds must appear *during the puncture moment*, radiating outward from the puncture point.

- Ignore striae that occur before puncture or during later steps (e.g., capsulorhexis).

Surgical steps: - Inject viscoelastic - Anterior capsule puncture - Initiate capsulorhexis - Continue capsulorhexis - Complete capsulorhexis

Output: YES or NO.'''

V2: '''Question: During the anterior capsule puncture process shown in this video sequence, do striae/folds appear?

Criteria:

- Locate the moment when the needle/forceps initiates the anterior capsule puncture.

- Answer YES if folds/striae arise from the capsule surface at that moment.

- Answer NO if: puncture happens without folds, or folds occur only before or after the puncture period.

Important:

Evaluate only the puncture phase, not later capsulorhexis.

Output: YES or NO.'''

V3: '''Instruction: Inspect the full video sequence and determine whether striae/folds appear during the anterior capsule puncture.

Checkpoints:

- Identify the puncture moment when the needle or forceps creates the initial opening.

- Confirm whether striae/folds appear at that same time.

- Ignore folds that occur outside the puncture process.

Answer with: YES or NO.'"

E. Prompt for Automatic AI agents

"'*You are an advanced code generation and optimization agent. Your task is to automatically build, train, and evaluate a binary classification model for surgical image classification using PyTorch and CUDA device 0.*

Project structure: The current directory contains three CSV files:

- *train_data.csv — training set*
- *val_data.csv — validation set*
- *test_data.csv — test set*

Each CSV file has two columns:

- *image_path — the file path to each image*
- *abnorm — binary label (0 = normal, 1 = abnormal)*

Your goals: Automatically generate complete runnable code that:

1. *Loads and preprocesses the dataset from the CSVs (train/val/test)*
2. *Uses appropriate image transformations (resize, normalization, augmentation for train)*
3. *Creates PyTorch Dataset and DataLoader classes*
4. *Builds an efficient CNN or pretrained backbone (e.g. ResNet50, EfficientNet, or similar) for binary classification*
5. *Supports GPU acceleration with cuda:0*
6. *Periodically evaluates on the validation set during training and prints accuracy, precision, recall, F1, AUROC*
7. *Saves the best model checkpoint based on validation F1*
8. *After training, runs final evaluation on the test set and prints a classification report*
9. *Include all necessary imports and ensure reproducibility (set seeds)*
10. *Make the code modular and readable, with functions for dataset loading, model definition, training loop, and evaluation*
11. *Automatically optimize model hyperparameters (e.g., learning rate, batch size, number of layers,*

dropout) if possible

12. *At the end, print total training time and final metrics on the test set*

Environment: PyTorch ≥ 2.0, CUDA device 0. Use mixed-precision training if beneficial (torch.amp).

After completing the code, you need to run it, automatically analyze the results, and then optimize the code.'''

F. Prompt for LLM-as-Judge

''' You are an expert code reviewer tasked with evaluating the quality of automatically generated Python code for a deep learning image classification project. Please assess the provided code across five dimensions, assigning a score from 0 to 20 points for each dimension based on the criteria below. Provide a score and brief justification for each dimension.

Evaluation Criteria:

1. Code Organization and Modularity (0-20 points)

- Logical code structure with clear separation of concerns (data loading, model definition, training, evaluation)
- Modular design with reusable functions and classes
- Well-defined abstraction layers
- Avoidance of code duplication

Scoring Guide:

- 18-20: Excellent organization with highly modular, reusable components and clear separation of concerns
- 14-17: Good organization with reasonable modularity, minor improvements possible
- 10-13: Adequate organization but lacks clear modularity or has some structural issues
- 6-9: Poor organization with significant structural problems or code duplication
- 0-5: Minimal organization, monolithic code structure

2. Documentation and Readability (0-20 points)

- Clear and meaningful variable and function naming conventions
- Consistent code style and formatting
- Readable code flow and logic

Scoring Guide:

- 18-20: Excellent readability with intuitive naming and consistent style throughout
- 14-17: Good readability with clear naming, minor inconsistencies
- 10-13: Adequate readability but some confusing names or style inconsistencies
- 6-9: Poor readability with unclear naming or inconsistent formatting
- 0-5: Very poor readability, cryptic naming, or chaotic formatting

3. Error Handling and Robustness (0-20 points)

- Exception handling mechanisms for critical operations (file I/O, model loading, GPU operations)
- Input validation and boundary condition checks
- Graceful handling of missing or corrupted data
- Fault tolerance in data loading and training pipelines

Scoring Guide:

- 18-20: Comprehensive error handling with robust exception management and validation
- 14-17: Good error handling for most critical operations
- 10-13: Basic error handling present but incomplete coverage
- 6-9: Minimal error handling, vulnerable to common failure models
- 0-5: No error handling or verification mechanisms

4. Software Engineering Best Practices (0-20 points)

- Reproducibility through proper random seed configuration
- Standardized data loading workflows
- Configuration management (avoiding hard-coded values, using arguments or config files)
- Comprehensive logging and experiment tracking
- Result visualization capabilities (training curves, confusion matrices, etc.)
- Model checkpoint management with ability to resume training

Scoring Guide:

- 18-20: Exemplary implementation of all best practices
- 14-17: Most best practices implemented, minor gaps
- 10-13: Some best practices present but significant omissions
- 6-9: Few best practices implemented, major gaps
- 0-5: Minimal or no adherence to best practices

5. Code Efficiency (0-20 points)

- Efficient data loading pipelines (multi-worker data loaders, prefetching, caching)

- GPU utilization and parallel processing optimizations
- Memory usage optimization (batch size management, gradient accumulation if needed)
- Implementation of performance-enhancing features (mixed-precision training, efficient transforms)

Scoring Guide:

- 18-20: Highly optimized with multiple efficiency techniques implemented
- 14-17: Well-optimized with most efficiency features present
- 10-13: Adequate efficiency with basic optimizations
- 6-9: Suboptimal efficiency, missing key optimizations
- 0-5: Inefficient implementation with no optimization considerations

G. The specific performance of VLMs at the frame-level, clip-level and frame-sequence across three prompts

Table G-1. Comprehensive Performance Benchmark of Vision-Language Models across Multi-Granularity Analysis Tasks.

This Table provides a general benchmark of VLMs, detailing their performance on the full test set across three tasks: Frame-Level (top 3 models), Clip-Level (top 3 models), and Frame-Sequence analysis (all evaluated models). Data are presented as Mean ± Standard Deviation for each metric and setting. The result is macro-averaged.

1. Frame-Level Analysis	Qwen2.5-VL	Few-shot	0.590 ± 0.090	0.520 ± 0.016	0.519 ± 0.029
	QoQ-Med-VL	Few-shot	0.555 ± 0.129	0.501 ± 0.002	0.485 ± 0.004
	GPT-4.1	Few-shot	0.537 ± 0.009	0.622 ± 0.021	0.480 ± 0.055
2. Clip-Level Analysis	Qwen2.5-VL	Few-shot	0.520 ± 0.106	0.524 ± 0.019	0.487 ± 0.046
	QoQ-Med-VL	Few-shot	0.426 ± 0.079	0.501 ± 0.001	0.430 ± 0.006
	QoQ-Med-VL	Zero-shot	0.526 ± 0.024	0.521 ± 0.015	0.422 ± 0.046
3. Frame-Sequence Analysis	Qwen2.5-VL	Few-shot	0.589 ± 0.256	0.509 ± 0.012	0.461 ± 0.054
	QoQ-Med-VL	Few-shot	0.426 ± 0.097	0.501 ± 0.002	0.432 ± 0.011
	InternVL-3.5	Few-shot	0.425 ± 0.034	0.437 ± 0.025	0.320 ± 0.081

HuatuoGPT-Vision	Few-shot	0.571 ± 0.015	0.519 ± 0.002	0.272 ± 0.013
Lingshu	Few-shot	0.433 ± 0.267	0.506 ± 0.009	0.237 ± 0.050

H. Result for Automatic AI agents

Table 1. Agent performance on the test set.

Agent	Precision	Recall	F1	AUC
Copilot	0.842	**0.903**	**0.870**	0.959
Qoder	**0.851**	0.866	0.859	**0.960**
CodeX	0.840	0.862	0.850	0.954
AIDE	0.470	0.500	0.484	0.500

Table 2. Code quality (LLM-as-judge, 0–20).

Agent	Organization & Modularity	Documentation & Readability	Error Handling & Robustness	SE Best Practices	Code Efficiency
Copilot	**19**	**18**	**17**	**19**	**18**
CodeX	**19**	17	15	18	**19**
Qoder	17	16	15	17	**18**
AIDE	10	12	**5**	8	11