TDA Engine v1.0: A Computational Framework for Detecting Structural Voids in Spatially Censored Epidemiological Data

Grold Otieno Mboya[1,2]

[1]*School of Health Sciences, Department of Epidemiology and Biostatistics, Jaramogi Oginga Odinga University of Science and Technology (JOOUST), Kenya*
[2]*Co-Founder and CTO, NIXQUE LTD, Kenya*
[*]*Correspondence: groldotieno97@gmail.com*

February 15, 2026

Abstract

Background: In public health surveillance, silence—the absence of data—is often more significant than the signal. Traditional epidemiological mapping tools efficiently visualize data density but struggle to mathematically define data absence. Standard approaches conflate stochastic sparsity with systemic suppression and remain vulnerable to edge effects.

Methods: We introduce a topological framework that detects *structural voids*—regions of unexpected data absence *within* clusters. Using Distance-to-Measure (DTM) filtration with adaptive thresholding via the Kneedle algorithm [11], we eliminate arbitrary parameter choices. Parameters are derived geometrically from the DTM distribution itself. We validate against known ground truth through a censoring simulation framework: 80% of points are artificially removed from test regions in public Kenyan health facility data, creating known suppression events. Detection accuracy is quantified using the Jaccard index [12], centroid error, and recovery rate—metrics that measure *spatial fidelity*, not binary detection.

Results: TDA Engine achieves Jaccard = 0.82 (95% CI: 0.74–0.89) on simulated suppression events, significantly outperforming KDE (0.45) and relative risk surfaces (0.38). Centroid error is 342 m (IQR: 187–512 m), indicating high spatial precision. The DTM parameter $m_0 = 0.05$ lies within a topologically stable plateau [0.03, 0.07], demonstrating that results are insensitive to small parameter variations. Permutation tests using void area as the test statistic yield $p = 0.003$ (95% CI: 0.001–0.008) [13], confirming statistical significance beyond complete spatial randomness.

Conclusion: This work provides a mathematically rigorous, topology-based framework for detecting structural voids in censored epidemiological data. By shifting from density-based to geometry-based inference with *quantitative validation metrics*, we enable public health officials to distinguish between natural gaps and potential suppression. We emphasize that structural voids are geometric anomalies *consistent with* suppression, not proof thereof—requiring contextual validation through population density, land use, and facility registry cross-checks.

Keywords: Topological Data Analysis, Spatial Epidemiology, Distance-to-Measure, Structural Voids, Censored Data, Jaccard Index, Permutation Testing, Adaptive Thresholding, Kneedle Algorithm.

Introduction

The primary artifact of a health surveillance system is the map. Whether tracking HIV prevalence in Sub-Saharan Africa or facility distribution in the Nyanza Basin, policymakers rely on spatial data to allocate resources. However, these maps possess a fundamental blindness: they are designed to show presence, not absence. When a region on a map is empty, it presents an interpretative ambiguity. Does the emptiness signify a healthy population requiring no intervention, or a marginalized community with no access to reporting mechanisms?

Classical spatial statistics struggle to resolve this ambiguity. Kernel Density Estimation (KDE) smooths over gaps, treating them as low-probability gradients rather than distinct topological features [1]. Voronoi diagrams partition space based on proximity, often creating unbounded polygons at the periphery—the "edge effect" [2]. Spatial scan statistics (e.g., SaTScan) detect clusters of *excess* cases, not absences [4]. These methods lack a rigorous criterion to distinguish between *stochastic voids* (natural low-density areas) and *structural voids* (systematic reporting failures).

We propose a fundamental shift: from density-based smoothing to **topological inference**. By treating health facilities as a point cloud sampled from an underlying service landscape, we employ Topological Data Analysis (TDA) to recover the geometric signature of data absence. Specifically, we utilize the *Distance-to-Measure* (DTM) function [3], which provides a robust distance metric resilient to the very censorship we seek to detect.

Contributions

This paper makes five methodological contributions:

1. **Adaptive Thresholding:** Elimination of arbitrary constants ($1.5\times$ median, 5 km cutoff) via the Kneedle algorithm [11], deriving thresholds geometrically from the DTM distribution itself.

2. **Quantitative Validation Framework:** A censoring simulation protocol that creates known ground truth voids in real facility data, enabling Jaccard index [12], centroid error, and recovery rate metrics—transforming validation from binary to spatial accuracy assessment.

3. **Topological Stability Analysis:** Demonstration that $m_0 = 0.05$ lies within a stable plateau [0.03, 0.07], proving parameter robustness and rebutting the "arbitrary tuning" critique.

4. **Enhanced Statistical Inference:** Replacement of the unstable maximum DTM statistic with *total void area* as the test statistic, plus confidence intervals on Monte Carlo p-values [13].

5. **Explicit Scope Delineation:** Formal caveats distinguishing geometric anomalies from proven suppression, with required contextual covariates for operational deployment.

We implement these advances in *TDA Engine v1.0*, an open-source R application, and validate them against both synthetic ring clusters and public Kenyan health facility data with simulated suppression events.

Methods

Related Work

Spatial epidemiology has long grappled with missing data, but methods have predominantly focused on imputation or smoothing rather than topological inference. Table 1 summarizes the

limitations of existing approaches.

Table 1: Comparison of existing spatial methods for handling data absence

Method	Internal voids[1]	Censorship[2]	Edge effects[3]	Arbitrary params[4]
Kernel Density Estimation	No	No	Severe	Yes
Voronoi/Thiessen polygons	No	No	Severe	No
SaTScan	No	No	Minimal	Yes
Kriging	No	No	Moderate	Yes
DTM (proposed)	**Yes**	**Yes**	**None**	**No**

[1] Detects voids inside data clusters, not at boundaries
[2] Robust to missing/censored data points
[3] Edge effects at convex hull boundary
[4] Requires manual parameter selection (bandwidth, window size, etc.)

Persistent homology in TDA has been applied to clustering and pattern detection in biomedicine [6, 7], but not specifically to identifying structural voids in censored epidemiological data. Boundary detection methods identify clusters with uncertain edges but lack topological rigor for *internal* absences [9]. Our work bridges this gap by adapting DTM filtration to detect voids *within* data support, not at boundaries.

Coordinate Projection

Geographic coordinates (latitude/longitude) describe angles on an ellipsoid, making Euclidean distance calculations distorted, particularly near the equator. To perform accurate geometric inference, we first project the point cloud $X_{raw} \subset \mathbb{R}^2$ from WGS84 to Universal Transverse Mercator (UTM) Zone 36S (EPSG:32736). This transformation maps the domain to a metric Cartesian plane where $\|x - y\|$ corresponds to true ground meters.

Distance-to-Measure Filtration

Let $X = \{x_1, \ldots, x_n\} \subset \mathbb{R}^d$ be the projected point cloud of n facility locations. The standard distance function $d_X(x) = \min_{y \in X} \|x - y\|$ is sensitive to outliers—precisely the censorship we aim to detect. Instead, we define a probability measure μ based on the empirical distribution of X.

The Distance-to-Measure function $d_{m_0} : \mathbb{R}^d \to \mathbb{R}^+$ depends on a mass parameter $m_0 \in (0, 1)$. For a query point x, let $X_{(1)}, \ldots, X_{(k)}$ be the k nearest neighbors of x in X, where $k = \lceil m_0 \cdot n \rceil$. The DTM is defined as the quadratic mean of these distances:

$$d_{m_0}(x) = \sqrt{\frac{1}{k} \sum_{i=1}^{k} \|x - X_{(i)}\|^2} \tag{1}$$

This formulation ensures $d_{m_0}(x)$ is 1-Lipschitz and robust to up to m_0 fraction of outliers. Intuitively, $d_{m_0}(x)$ represents the radius of the smallest ball capturing m_0 of the data mass. We set $m_0 = 0.05$ (5% of the network), matching the WHO standard of 95% expected reporting completeness. Section 4.2 demonstrates this value lies within a topologically stable plateau.

Adaptive Thresholding via Kneedle Algorithm

Previous implementations relied on arbitrary constants (e.g., $1.5\times$ median DTM). We eliminate this subjectivity by deriving thresholds geometrically from the DTM distribution itself using curvature analysis [11].

Let $D = \{d_1, \ldots, d_m\}$ be the sorted DTM values at grid points. We normalize to $[0, 1]$:

$$x_i = \frac{i-1}{m-1}, \quad y_i = \frac{d_i - \min(D)}{\max(D) - \min(D)} \tag{2}$$

The curvature (second derivative) is approximated by:

$$y_i'' \approx \frac{(y_{i+1} - y_i)/(x_{i+1} - x_i) - (y_i - y_{i-1})/(x_i - x_{i-1})}{(x_{i+1} - x_{i-1})/2} \tag{3}$$

The elbow point is the index of maximum absolute curvature:

$$i^* = \arg\max_i |y_i''| \tag{4}$$

The adaptive threshold is then:

$$T_{\text{adaptive}} = d_{i^*} \tag{5}$$

This threshold corresponds to the quantile where the DTM distance growth rate accelerates most rapidly—a purely geometric, assumption-free criterion. The sensitivity parameter α is derived as:

$$\alpha = 1 - \hat{F}(T_{\text{adaptive}}) \tag{6}$$

where $\hat{F}$ is the empirical CDF of DTM values.
A grid point $g \in G$ is flagged as void if:

$$d_{m_0}(g) > T_{\text{adaptive}} \quad \wedge \quad d_{m_0}(g) \leq Q_{0.75} + 2 \cdot \text{IQR} \tag{7}$$

The upper bound excludes extreme outliers (areas outside data support), ensuring we detect *internal* voids only.

Statistical Significance Testing

We employ a Monte Carlo permutation test under the null hypothesis of Complete Spatial Randomness (CSR). Rather than the unstable maximum DTM statistic, we use **total void area** as our test statistic:

$$T_{\text{area}}(X) = \sum_{g \in G} \mathbb{1}\{d_{m_0}(g) > T_{\text{adaptive}}\} \cdot \text{Area}(g) \tag{8}$$

For $N = 999$ CSR realizations $X^{(i)}$ with the same intensity as observed data, we compute $T_{\text{area}}^{(i)}$. The p-value is:

$$p = \frac{1 + \sum_{i=1}^{N} \mathbb{1}(T_{\text{area}}^{(i)} \geq T_{\text{area}}^{\text{obs}})}{N + 1} \tag{9}$$

We report 95% confidence intervals for p-values using the Wilson score interval for binomial proportions [13]:

$$\hat{p} \pm z_{\alpha/2} \sqrt{\frac{\hat{p}(1 - \hat{p})}{N}} \tag{10}$$

This provides uncertainty quantification for the significance estimate itself.

Structural vs. Stochastic Voids

Not all detected voids represent suppression; some correspond to uninhabited terrain. We classify a void polygon P as **structural** if:

1. **Significant Area:** $\text{Area}(P) > 1.0 \text{ km}^2$ (5th percentile of observed void areas)

2. **Proximity to Service:** $\min_{x \in X} \text{dist}(\text{centroid}(P), x) < 5000 \text{ m}$ (95th percentile of bootstrap null distribution)

These thresholds are *data-driven*, derived from bootstrap resampling of observed void characteristics, not arbitrary constants.

Validation Framework: Censoring Simulation

To quantitatively assess detection accuracy, we require **ground truth**. We construct this by taking complete facility data and simulating realistic suppression events:

$$P(\text{observed} \mid u) = \begin{cases} 0.2 & \text{if } u \in \text{Suppression Zone} \\ 1.0 & \text{otherwise} \end{cases} \tag{11}$$

We remove 80% of points within a randomly selected suppression zone of radius 2.5 km. The removed points constitute the *ground truth* void. This transforms the synthetic data critique into a strength: we now have known validation targets.

Spatial Accuracy Metrics

We quantify detection performance using three complementary metrics [12]:
Jaccard Index (Intersection over Union):

$$J = \frac{|A \cap B|}{|A \cup B|} \in [0, 1] \tag{12}$$

where A is the detected void polygon and B is the ground truth convex hull. $J = 0$ indicates no overlap; $J = 1$ indicates perfect spatial congruence.
Centroid Error:

$$\text{CE} = \|\mathbf{c}_A - \mathbf{c}_B\|_2 \quad (\text{meters}) \tag{13}$$

where $\mathbf{c}_A$ and $\mathbf{c}_B$ are polygon centroids.
Recovery Rate:

$$R = \frac{|A \cap B|}{|B|} \in [0, 1] \tag{14}$$

The proportion of true suppressed area successfully detected.

These metrics provide *quantitative* assessment of spatial accuracy, replacing binary "detected/not detected" comparisons.

Topological Stability Analysis

A common critique of DTM-based methods is sensitivity to the mass parameter m_0. We systematically evaluate stability across $m_0 \in [0.01, 0.15]$:

$$\text{Stability}(m_0) = -\text{SD}\left(\{n_{\text{voids}}(m_{0j})\}_{j=i}^{i+w}\right) \tag{15}$$

A *stable plateau* is defined as a contiguous interval where the number of detected voids varies by $< 20\%$. We demonstrate that $m_0 = 0.05$ lies within such a plateau, proving topological persistence rather than arbitrary tuning.

Implementation: TDA Engine v1.0

The complete methodology is implemented in the *TDA Engine*, an open-source R/Shiny application. Algorithm 1 details the detection pipeline.

Algorithm 1 Structural Void Detection with Adaptive Thresholding

---

1: **Input:** Point cloud X_{raw} (Long/Lat)
2: **Parameters:** $m_0 = 0.05$, Resolution Δ
3: **Optional:** Ground truth G_t for validation
4:
5: $X_{utm} \leftarrow \text{Project}(X_{raw}, \text{EPSG:32736})$
6: $\mathcal{H} \leftarrow \text{ConvexHull}(X_{utm})$
7: $G \leftarrow \text{Grid}(\mathcal{H}, \text{resolution} = \Delta)$
8:
9: **for** each $g \in G$ **do**
10:     $d_{m_0}(g) \leftarrow \sqrt{\frac{1}{k}\sum_{i=1}^{k}\|g - X_{(i)}\|^2}$
11: **end for**
12:
13: $D_{\text{sorted}} \leftarrow \text{sort}(\{d_{m_0}(g)\})$
14: $i^* \leftarrow \text{Kneedle}(D_{\text{sorted}})$ ▷ Adaptive threshold
15: $T \leftarrow D_{\text{sorted}}[i^*]$
16:
17: $V \leftarrow \{g \in G \mid d_{m_0}(g) > T\}$
18: $\text{Polygons} \leftarrow \text{RasterToPolygons}(V)$
19:
20: **for** each $P \in \text{Polygons}$ **do**
21:     **if** $\text{Area}(P) > 1.0\text{km}^2$ **and** $\text{DistToData}(P) < 5\text{km}$ **then**
22:         Classify as **Structural Void**
23:         $\text{Ring} \leftarrow \text{Welzl}(P)$ [10]
24:     **else**
25:         Classify as **Stochastic Void**
26:     **end if**
27: **end for**
28:
29: **if** G_t provided **then**
30:     $J \leftarrow \text{Jaccard}(\text{Polygons}, G_t)$
31:     $\text{CE} \leftarrow \|\mathbf{c}_{\text{detected}} - \mathbf{c}_{\text{truth}}\|_2$
32: **end if**
33:
34: **Output:** Map, metrics, significance test

Results

Validation Against Censoring Simulation

We validated TDA Engine against 100 independent censoring simulations using public Kenyan health facility data (N = 312 facilities in Nyanza region). Each simulation randomly selected a suppression zone (radius 2.5 km) and removed 80% of points within it.

Table 2: Quantitative Validation Results (Mean ± 95% CI)

Metric	TDA Engine	KDE	Relative Risk
Jaccard Index	**0.82 ± 0.07**	0.45 ± 0.11	0.38 ± 0.13
Recovery Rate	**0.79 ± 0.08**	0.41 ± 0.12	0.35 ± 0.14
Centroid Error (m)	**342 ± 89**	1234 ± 312	1567 ± 401
Dice Coefficient	**0.89 ± 0.05**	0.62 ± 0.09	0.55 ± 0.11

TDA Engine achieves significantly higher spatial fidelity than baseline methods. The Jaccard index of 0.82 indicates substantial overlap (82%) between detected and true suppression zones. Centroid error of 342 m (approximately 3.5 grid cells at 1.5 km resolution) demonstrates precise localization.

Topological Stability of m_0

Figure 1 shows the sensitivity analysis across $m_0 \in [0.01, 0.15]$. The number of detected voids remains stable (range: 2–4) across $m_0 \in [0.03, 0.07]$. $m_0 = 0.05$ lies well within this plateau.

Figure 1: m_0 sensitivity analysis showing stable plateau from 0.03 to 0.07. $m_0 = 0.05$ is within the stable region.

This stability proves that our results are not artifacts of parameter tuning but reflect genuine topological features of the data.

Statistical Significance

Permutation testing (N = 999) using total void area as the test statistic yielded:

- Observed void area: 42.7 km²

- Mean void area under CSR: 8.3 km² (SD: 3.1 km²)

- Effect size: 5.1× larger than random expectation

- **p = 0.003 (95% CI: 0.001–0.008)**

The confidence interval on the p-value confirms statistical significance well below conventional thresholds ($\alpha = 0.05$).

Adaptive Thresholding Performance

The Kneedle algorithm successfully identified an elbow point in 94% of validation runs. When an elbow was detected, the automatically selected α (median = 0.08, IQR: 0.06–0.11) produced Jaccard indices statistically indistinguishable from oracle-tuned thresholds (paired t-test: p = 0.23). When no clear elbow was detected (6% of runs), manual $\alpha = 0.10$ was used, with no significant degradation in performance.

Case Study: Nyanza Basin Health Facilities

Applying the validated engine to the complete Nyanza Basin facility dataset (N = 623), we identified:

- **3 Structural Voids** (total area: $42.7\,\mathrm{km}^2$) in peri-urban corridors between Kisumu and Homa Bay. These areas have high population density ($\l>500/\mathrm{km}^2$) but zero facilities within 5 km.
- **5 Stochastic Voids** (total area: $105.3\,\mathrm{km}^2$) corresponding to Lake Victoria and protected forest reserves—areas with near-zero population density.

Table 3: Detected Structural Voids in Nyanza Basin

Void ID	Area (km^2)	Population Density	Nearest Facility	Ring Radius
SV-01	18.4	$847/\mathrm{km}^2$	3.2 km	4.1 km
SV-02	14.2	$623/\mathrm{km}^2$	4.1 km	3.8 km
SV-03	10.1	$512/\mathrm{km}^2$	4.8 km	3.2 km

Statistical validation confirmed these voids were significant under permutation testing (p = 0.003, 95% CI: 0.001–0.008). Each structural void was flagged for field investigation to determine whether the absence represents suppressed reporting, private facilities not in the public registry, or genuine access barriers.

Discussion

Principal Findings

We have demonstrated that topological inference via DTM filtration, enhanced with adaptive thresholding and quantitative validation, can reliably detect structural voids in spatially censored data. The key advances are:

1. **Validation with ground truth:** By simulating realistic suppression events in complete facility data, we established that TDA Engine achieves Jaccard = 0.82—substantially outperforming conventional methods.

2. **Elimination of arbitrary parameters:** The Kneedle algorithm derives thresholds geometrically, removing subjective tuning. This addresses a major criticism of previous DTM implementations.

3. **Proof of topological stability:** $m_0 = 0.05$ lies within a stable plateau [0.03, 0.07], demonstrating that results are not artifacts of parameter choice.

4. **Enhanced statistical rigor:** Using void area as the test statistic with confidence intervals on p-values provides more robust inference than the maximum DTM statistic.

Limitations and Scope Clarification

It is crucial to emphasize what this method does **not** do:

- **TDA Engine does not detect suppression directly.** It detects geometric anomalies—regions of unexpectedly high DTM values within data support. The interpretation of these anomalies as "suppressed reporting" requires three external validations: (1) population density to rule out uninhabited areas, (2) facility registry cross-checks to confirm absence of private facilities, and (3) temporal analysis to distinguish acute suppression from chronic under-service.

- **The method assumes accurate geocoding.** Systematic errors in facility coordinates would propagate through the distance calculations.

- **The 2D Euclidean assumption** may not hold in regions with extreme topography (e.g., mountainous areas where travel distance exceeds Euclidean distance). Future work will integrate cost-distance surfaces based on road networks.

- **The method requires sufficient data density.** With fewer than 30 points, the DTM approximation becomes unstable. For sparse data regimes, we recommend coarsening the resolution or increasing m_0.

Ethical Considerations

This method identifies *candidates* for investigation, not definitive evidence of suppression. Deployment in conflict-affected regions requires:

1. **Community partnership and informed consent:** Affected communities must be consulted before field investigations are launched based on algorithmic flags.

2. **Data sovereignty:** Facility data remains the property of the Ministry of Health. Our analysis is conducted on publicly available, anonymized coordinates.

3. **Uncertainty communication:** All detected voids should be presented with confidence intervals on their boundaries. A polygon is not a precise boundary; it is an estimate.

4. **Dual-use awareness:** While designed for humanitarian applications, the same methodology could theoretically be used to identify populations for surveillance or control. We strongly discourage such applications and have implemented conservative classification thresholds to minimize false positives.

All structural voids detected in this study were verified against satellite imagery to ensure they did not correspond to water bodies, protected areas, or obviously uninhabited terrain.

Future Work

1. **Spatiotemporal extension:** Track void evolution over time to distinguish acute suppression events from chronic under-service.

2. **Network DTM:** Replace Euclidean distance with travel time/cost distance along road networks for more realistic accessibility modeling.

3. **Uncertainty quantification:** Provide confidence bands on void boundaries via bootstrap resampling of the DTM surface.

4. **Automated calibration:** Develop cross-validation framework for simultaneous optimization of m_0 and resolution.

5. **Integration with DHIS2:** Deploy as a real-time surveillance dashboard for Ministries of Health.

6. **Multi-modal data fusion:** Incorporate satellite imagery, population density grids, and conflict event data as covariates in a spatial Cox process model.

Conclusion

This paper presents a rigorously validated, geometrically principled framework for detecting structural voids in spatially censored epidemiological data. By shifting from density-based to topology-based inference, and crucially, by *quantifying* rather than merely asserting detection accuracy, we provide public health officials with a defensible tool for distinguishing natural gaps from potential suppression.

The open-source TDA Engine v1.0 implements these advances in an accessible interface, enabling field deployment and fostering reproducibility. We emphasize that structural voids are geometric anomalies *consistent with* suppression—not proof thereof—and require contextual intelligence for correct interpretation.

In the geometry of silence, not every empty space is a void worth investigating. Our contribution is not to declare which silences matter, but to measure their shape with mathematical precision so that human judgment—epidemiological, ethical, and contextual—can be applied where it is most needed.

Data and Code Availability

The source code for *TDA Engine v1.0* is available at:

- **Development Repository (GitHub):**
  `https://github.com/Grolds-Code/Topological-Inference`

- **Archived Release (Zenodo):**
  `https://doi.org/10.5281/zenodo.18403767`

The Kenyan health facility data used for validation is publicly available from the Kenya Master Health Facility List (`https://kmhfl.health.go.ke`). Our censoring simulation framework, validation scripts, and all analysis code required to reproduce Tables 1–3 and Figure 1 are included in the repository under the `analysis/` directory.

The software is released under the GNU General Public License v3.0 (GPLv3).

Competing Interests

The author declares no competing interests.

Funding

This research received no specific grant from any funding agency.

Acknowledgments

The author thanks the open-source R community for maintaining the essential packages that made this research possible: `TDA`, `sf`, `shiny`, and `leaflet`. Special thanks to the developers of the `TDA` package for implementing the DTM algorithm in an accessible form.

The Kenya Ministry of Health is acknowledged for maintaining the public health facility registry, and the Humanitarian Data Exchange (HDX) for curating and distributing this critical infrastructure dataset.

References

[1] Silverman, B. W. (1986). *Density Estimation for Statistics and Data Analysis*. Chapman and Hall.
DOI: 10.1007/978-1-4899-3324-9

[2] Okabe, A., Boots, B., Sugihara, K., & Chiu, S. N. (2009). *Spatial Tessellations: Concepts and Applications of Voronoi Diagrams* (2nd ed.). John Wiley & Sons.
DOI: 10.1002/9780470317013

[3] Chazal, F., Cohen-Steiner, D., & Mérigot, Q. (2011). Geometric inference for probability measures. *Foundations of Computational Mathematics*, 11(6), 733-751.
DOI: 10.1007/s10208-011-9098-0

[4] Kulldorff, M. (1997). A spatial scan statistic. *Communications in Statistics—Theory and Methods*, 26(6), 1481–1496.
DOI: 10.1080/03610929708831995

[5] Kulldorff, M. (2023). SaTScan™: Software for the spatial, temporal, and space-time scan statistics.
URL: https://www.satscan.org/

[6] Skaf, Y., & Laubenbacher, R. (2022). Topological data analysis in biomedicine: A review. *Journal of Biomedical Informatics*, 130, 104082.
DOI: 10.1016/j.jbi.2022.104082

[7] Lum, P. Y., Singh, G., Lehman, A., Ishkanov, T., Vejdemo-Johansson, M., Alagappan, M., Carlsson, J., & Carlsson, G. (2013). Extracting insights from the shape of complex data using topology. *Scientific Reports*, 3, 1236.
DOI: 10.1038/srep01236

[8] Edelsbrunner, H., & Harer, J. (2010). *Computational Topology: An Introduction*. American Mathematical Society.
DOI: 10.1090/mbk/069

[9] Chen, Y.-C., Genovese, C. R., & Wasserman, L. (2014). Enhanced mode clustering. *Journal of the American Statistical Association*, 111(514), 704–719.
DOI: 10.1080/01621459.2016.1165103
arXiv: 1406.1780

[10] Welzl, E. (1991). Smallest enclosing disks (balls and ellipsoids). In H. Maurer (Ed.), *New Results and New Trends in Computer Science* (pp. 359-370). Springer.
DOI: 10.1007/BFb0038202

[11] Satopää, V., Albrecht, J., Irwin, D., & Raghavan, B. (2011). Finding a "kneedle" in a haystack: Detecting knee points in system behavior. In *2011 31st International Conference on Distributed Computing Systems Workshops* (pp. 166-171). IEEE.
DOI: 10.1109/ICDCSW.2011.20

[12] Jaccard, P. (1901). Étude comparative de la distribution florale dans une portion des Alpes et du Jura. *Bulletin de la Société Vaudoise des Sciences Naturelles*, 37, 547-579.
DOI: 10.5169/seals-266450

[13] Davison, A. C., & Hinkley, D. V. (1997). *Bootstrap Methods and their Application.* Cambridge University Press.
DOI: 10.1017/CBO9780511802843