Stochastic forecasting of COVID-19 daily new cases across countries with a novel hybrid time series model

Arinjita Bhattacharyya¹⁺, Tanujit Chakraborty^{2+*}, Shesh N. Rai^{1,3,4,5,6}

¹ Department of Bioinformatics & Biostatistics, University of Louisville, KY, USA.

² Center for Data Sciences, International Institute of Information Technology, Bangalore, India.

³ Biostatistics & Bioinformatics Facility, JG Brown Cancer Center, University of Louisville, KY, USA.

⁴ The Christina Lee Brown Envirome Institute, University of Louisville, KY, USA.

⁵ University of Louisville Alcohol Research Center, University of Louisville, KY, USA.

⁶ University of Louisville Hepatobiology & Toxicology Center, University of Louisville, KY, USA.

* Corresponding author's contact: tanujit_r@isical.ac.in

+ These authors have contributed equally.

ARTICLE HISTORY

Compiled April 25, 2021

ABSTRACT

An unprecedented outbreak of the novel coronavirus (COVID-19) in the form of peculiar pneumonia has spread globally since its first case in Wuhan province, China, in December 2019. Soon after, the infected cases and mortality increased rapidly. The future of the pandemic's progress was uncertain, and thus, predicting it became crucial for public health researchers. These future predictions help the effective allocation of health care resources, stockpiling, and help in strategic planning for clinicians, government authorities, and public health policymakers after understanding the extent of the effect. The main objective of this paper is to develop a hybrid forecasting model that can generate real-time out-of-sample forecasts of COVID-19 outbreaks for five profoundly affected countries, namely the USA, Brazil, India, UK, and Canada. A novel hybrid approach based on the Theta method and Autoregressive neural network (ARNN) model, named Theta-ARNN (TARNN) model, is developed. Daily new cases of COVID-19 are nonlinear, non-stationary, and volatile; thus a single specific model cannot be ideal for future prediction of the pandemic. However, the newly introduced hybrid forecasting model with an acceptable prediction error rate can help healthcare and government for effective planning and resource allocation. The proposed method outperforms traditional univariate and hybrid forecasting models for the test data sets on an average.

KEYWORDS

COVID-19; Forecasting; Theta model; Autoregressive Neural Networks; Hybrid model; Asymptotic stationarity.

1. Introduction

In December 2019, clusters of pneumonia cases caused by the novel severe acute respiratory syndrome coronavirus 2 (SARS-Cov-2) were identified at Wuhan, Hubei province in China [19,22,54]. Soon after the emergence of the novel beta coronavirus,

World Health Organization (WHO) characterized this contagious disease as a pandemic in March 2020 due to its rapid spread within and outside the highly mobile population of China which got further aggravated by the densely populated location of the sea-food market and time of Chinese new year [47]. It resulted in an exponential increase in the incidence rate (IR) and case-fatality rate (CFR) [37]. As of March 16, 2021, a total of 120,512,041 confirmed global cases and 2,665,742 deaths have been reported worldwide [3].

Researchers have faced significant challenges to forecast real-time COVID-19 cases with traditional mathematical, statistical, and machine learning-based forecasting tools [9,14,29,31,40,56,60]. Studies in March 2020 with simple and efficient forecasting methods such as exponential smoothing model predicted cases ten days ahead, with large confidence intervals, that despite the positive bias, had reasonable forecast error [43]. Previously used linear and exponential model forecasts for better preparation regarding hospital beds, ICU admission estimation, resource allocation, emergency funding, and proposing strong containment measures were conducted [17] that projected ICU admissions in Italy for March 20, 2020. ICU admission and mechanical ventilation for critically ill patients reached their peak shattering the health system of Lombardy, Italy, by end of March 2020 [18]. Health-care workers had to go through the immense mental stress left with a formidable choice of prioritizing young and healthy adults over the elderly for allocation of life support, especially unwanted ignoring of those who are extremely unlikely to survive [13,48]. Real estimates of mortality with 14-day delay demonstrated underestimating the COVID-19 outbreak and indicated a grave future with a global CFR of 5.7% [2]. Some of the countries are eventually in a second wave with cases rising in India, and the UK. The uncertain future has several unanswered questions on the daily trajectory of the pandemic, infection rate, and number of deaths. Thus, real-time forecasting with time series models could respond to these debatable quires to reach a statistically validated conjecture in this current health crisis. Some of the impacting leading-edge research concerning real-time projections of COVID-19 confirmed cases, recovered cases, and mortality using statistical, epidemiological and machine learning models are as follows. Short-term forecasting of cumulative confirmed cases was produced using autoregressive integrated moving average (ARIMA), Cubist regression, Random Forest, Ridge, Support Vector Regression (SVR) and Stacking-Ensemble Learning (SEL) model in [46] whereas Exponential smoothing model produced ten days ahead forecasts of actual cases within 90% CI and forecasts reflect the significant increase in the trend of global cases with growing uncertainty [43]. Forecasting and nowcasting domestic and international COVID-19 cases is also done with epidemiological compartmental models, like Susceptible-Exposed-Infectious-Recovered (SEIR) and SIR models [14,45,56]. Modern machine learning techniques like neural networks and black-box deep learning models were also used for COVID-19 forecasting [50,52]. However, forecasting COVID-19 cases is harder and this is primarily due to the following major factors [28]: (a) Very less amount of data is available; (b) Less understanding of the factors that contribute to it; (c) Model accuracy is constrained by our knowledge of the virus. With an emerging disease such as COVID-19, many biologic features of transmission are hard to measure and remain unknown; (d) Another source of uncertainty, affecting all models, is that we don't know how many people are, or have been, infected; (e) We are certainly missing a substantial number of cases due to virologic testing, so models fitted to confirmed cases are likely to be highly uncertain [21].

Time-series forecasting models take input of historical observations and extrapolate the patterns into the future. The past in no way will continue in the future for this pandemic, so it is challenging to model and produce predictions. There are essentially two general approaches to forecasting a time series: (a) generating forecasts from a single model; and (b) combining forecasts from many models (Hybrid). In classical time series forecasting, the ARIMA model is used predominantly for forecasting linear time series [4], which has a significant strong assumption of linearity in the system and homoscedastic error distribution; typically without sudden jumps and bursts. Individual models such as ARIMA, Wavelet ARIMA (WARIMA)[11], and Theta method [1,26] are inadequate to model such situations. Usage of nonlinear time series techniques in infectious disease modeling has successfully demonstrated the success of Artificial Neural Networks (ANN) and Autoregressive Neural Networks (ARNN) [6,32,34,58]. The idea of hybridizing forecasting models is not a new concept and their empirical applications resulted in superior forecasts to their counterparts. Most recently, some hybrid models combining linear and nonlinear time series models are proposed for COVID-19 [9,16] and performed exceptionally well for predicting these epidemics.

Motivated by this, this study considers the time series data sets of coronavirus confirmed cases that show non-linearity, non-stationary and non-Gaussian patterns, thus making decisions based on a discrete model critical and unreliable. Another difficulty in COVID-19 data from the modeling aspect is the unavailability of sufficient data points, which generates biased predictions and estimates, which can be well maneuvered by neural nets [38]. Most of the relevant studies focused on the outbreak's short-term and long-term forecasts of reported confirmed cases have a broad range of fluctuations, wide confidence intervals, poorly reported data and model specifics, and highly optimistic predictive performance [57]. Hybridization of two or more models is the most common solution [36] for optimizing forecasting performance, and efficiency with unknown complete data characteristics [30]. The importance of hybrid methodology with a fusion of linear and non-linear forecasting models becomes evident in tackling such dynamic/non-linear time series and its inbuilt time-changing variance, complex autocorrelation structure [9,42]. With the growing need for advanced parsimonious hybrid forecasting methods accompanied by precise accuracy and accurate forecasts, the main objectives of this study are:

- (1) To propose a simple and computationally efficient hybrid forecasting model which generates out-of-sample forecasts (two months) for five profoundly affected countries (United States of America (USA), Brazil, India, UK, and Canada) with higher accuracy as compared to state-of-the-art forecasting methods..
- (2) To prove the model's stationarity and ergodicity properties from a statistical point of view.
- (3) To discuss the merits and future challenges that needs attention while working with the proposal for epidemiological forecasting. We also recommend policy-making decisions, resource allocation based on these forecasts.

Therefore, this study proposes a novel hybrid Theta Autoregressive neural network model (TARNN) model combining Theta and ARNN models that can capture complex COVID-19 data structures. The proposed TARNN model has easy interpretability, produces robust predictions, and is adaptable to seasonality. An RShiny application is also built for TARNN can help practitioners reproducing and updating

the forecasts as further data becomes available.

The rest of the paper is organized as follows: Section 2 describes the formulation of the proposed hybrid TARNN model. The ergodicity and stationarity of the proposed hybrid model are discussed in Section 3. In Section 4, we discuss the country-wise COVID-19 confirmed case data sets and experimental results. The discussions about the results and practical implications are given in Section 5.

2. Methodology

We start by discussing the single forecasting models to be used in the hybridization, followed by the detailed formulation of the proposed hybrid Theta-ARNN model.

2.1. Theta Method

The ‘Theta method’ or ‘Theta model’ is a univariate time series forecasting technique that performs particularly well in M3 forecasting competition and of interest to forecasters [1]. The method decomposes the original data into two or more lines, called theta lines, and extrapolates them using forecasting models. Finally, the predictions are combined to obtain the final forecasts. The theta lines can be estimated by simply modifying the ‘curvatures’ of the original time series. This change is obtained from a coefficient, called θ coefficient, which is directly applied to the second differences of the time series:

$$Y_{new}''(\theta) = \theta Y_{data}'', \quad (1)$$

where $Y_{data}'' = Y_t - 2Y_{t-1} + Y_{t-2}$ at time t for $t = 3, 4, \dots, n$ and $\{Y_1, Y_2, \dots, Y_n\}$ denote the observed univariate time series. In practice, the coefficient θ can be considered as a transformation parameter which creates a series of the same mean and slope with that of the original data but having different variances. Now, Eqn. (1) is a second-order difference equation and has solutions of the following form [26]:

$$Y_{new}(\theta) = a_\theta + b_\theta(t - 1) + \theta Y_t, \quad (2)$$

where a_θ and b_θ are constants and $t = 1, 2, \dots, n$. Thus, $Y_{new}(\theta)$ is equivalent to a linear function of Y_t with a linear trend added. The values of a_θ and b_θ are computed by minimizing the sum of squared differences:

$$\sum_{i=1}^t [Y_t - Y_{new}(\theta)]^2 = \sum_{i=1}^t [(1 - \theta)Y_t - a_\theta - b_\theta(t - 1)]^2. \quad (3)$$

Forecasts from the Theta model are obtained by a weighted average of forecasts of $Y_{new}(\theta)$ for different values of θ . Furthermore, the prediction intervals and likelihood-based estimation of the parameters can be obtained based on a state space model which is demonstrated in [26]. The generalized version of the Theta method is suitable for automatic forecasting of time series [51].

2.2. ARNN Model

Artificial Neural Network-based forecasting methods received increasing interest in various applied domains in the late 1990s. A wide variety of neural nets are popularly used for supervised classification, prediction, and nonlinear time series forecasting [59]. The architecture of a simple feedforward neural network can be described as a network of neurons arranged in an input layer, hidden layer, and output layer in a prescribed order. Each layer passes the information to the next layer using weights that are obtained using a learning algorithm [15]. ARNN model is a modification to the simple ANN model especially designed for prediction problems of time series data sets [15]. ARNN model uses a prespecified number of lagged values of the time series as inputs and the number of hidden neurons in its architecture is also fixed [24]. ARNN(p, k) model uses p lagged inputs of the time series data in a one hidden layered feedforward neural network with k hidden units in the hidden layer. Let $\underline{x}$ denotes a p -lagged inputs and f is a neural network of the following architecture:

$$f(\underline{x}) = c_0 + \sum_{j=1}^k w_j \phi(a_j + b'_j \underline{x}); \quad (4)$$

where c_0, a_j, w_j are connecting weights, b_j are p -dimensional weight vector and ϕ is a bounded nonlinear sigmoidal function (e.g., logistic squasher function or tangent hyperbolic activation function). These Weights are trained using a gradient descent backpropagation [49]. Standard ANN faces the dilemma to choose the number of hidden neurons in the hidden layer and the optimal choice is unknown. However, for ARNN model, we adopt the formula $k = [(p + 1)/2]$ for non-seasonal time series data where p is the number of lagged inputs in an autoregressive model [24].

2.3. Proposed TARNN Model

In this section, we describe the proposed hybrid model based on Theta method and ARNN model and we name it TARNN model. The proposed TARNN model is based on an error remodeling approach and there are broadly two types of error calculations popular in the literature which are given below [35].

Definition 2.1. In the additive error model, the forecaster treats the expert's estimate as a variable, $\hat{Y}_t$, and thinks of it as the sum of two terms:

$$\hat{Y}_t = Y_t + e_t,$$

where Y_t is the true value and e_t is the additive error term.

Definition 2.2. In the multiplicative error model, the forecaster treats the expert's estimate $\hat{Y}_t$ as the product of two terms:

$$\hat{Y}_t = Y_t \times e_t,$$

where Y_t is the true value and e_t be the multiplicative error term.

Now, even if the relationship is of product type, in the log-log scale, it becomes additive. Hence, without loss of generality, we may assume the relationship to be

additive and expect the errors (additive) of a forecasting model to be random shocks. However, this is violated when there are complex correlation structures in the time series data and less amount of knowledge is available about the data generating process. A simple example is the daily confirmed cases of the COVID-19 cases for various countries where very little is known about the structural properties of the current pandemic. Thus, we need two-stage modeling approach to formulate this complex time series problem. The proposed TARNN model is a hybrid model based on the additive error re-modeling approach. The hybrid TARNN approach consists of three basic steps:

- In the first step of the TARNN model, the Theta method is applied to the time series data to model the linear components of a given time series data set.
- Theta model generates in-sample forecasts and the error series is calculated.
- In the next phase, the residuals (additive errors) generated by the Theta method are remodeled using a nonlinear ARNN model. Finally, both the forecasts obtained from the Theta and ARNN models are combined together to get the final forecasts for the given time series.

The mathematical formulation of the proposed hybrid TARNN model (Z_t) is as follows:

$$Z_t = L_t + N_t,$$

where L_t is the linear part and N_t is the nonlinear part of the hybrid model. We can estimate both L_t and N_t from the available time series data. Let $\hat{L}_t$ be the forecast value of the Theta model at time t and ϵ_t represent the error residuals at time t , obtained from the Theta model. Then, we write

$$\epsilon_t = Z_t - \hat{L}_t.$$

These left-out residuals are further modeled by ARNN model and can be represented as follows:

$$\epsilon_t = f(\epsilon_{t-1}, \epsilon_{t-2}, \dots, \epsilon_{t-p}) + \varepsilon_t,$$

where f is a nonlinear function and the modeling is done by the ARNN model as defined in Eqn. (4) and ε_t is supposed to be random shocks. Therefore, the combined forecast can be obtained as follows:

$$\hat{Z}_t = \hat{L}_t + \hat{N}_t,$$

where $\hat{N}_t$ is the forecasted value of the ARNN model. An overall flow diagram of the proposed TARNN model is given in Figure 1.

In the proposed TARNN model, ARNN is applied to remodel the left-over autocorrelations in the residuals which Theta model individually could not model. Thus, the proposed TARNN model can be considered as an error re-modeling approach. This is important because due to model mis-specification and disturbances in the pandemic time series, the linear Theta model may fail to generate white noise behavior for the forecast residuals. The TARNN approach eventually can improve the predictions for the epidemiological forecasting problem as shown in Section 4.

Figure 1. The main workflow of the proposed TARNN model.

Remark 1. The idea of additive error modelling is useful for modeling complex time series for which achieving random shocks based on individual forecasting models is difficult. More precisely, the TARNN approach is developed for forecasting the COVID-19 confirmed cases for which the data generating process and the various characteristics of the epidemic are still unknown. The proposed TARNN model only assumes that the linear and nonlinear components of the epidemic time series can be separated individually.

3. Ergodicity and Stationarity of the proposed TARNN model

In this section, we derive the results for the ergodicity and asymptotic stationarity of the proposed TARNN model. The ergodicity and stationarity is of particular importance from a statistician's point of view in time series analysis since for such processes a single realization displays the whole probability of the data generating process. We use several previous results on nonlinear time series and Markov chains to find sufficient conditions for which the overall process is ergodic and stationary [5,7,10,53].

239

To start, we write the underlying stochastic model of the Theta method using the state space approach. We initialize the model by setting $Y_1 = l_1$ and then for $t = 2, 3, \dots$; and drift term b , let

$$Y_t = l_{t-1} + b + \epsilon_t \quad \text{and} \quad l_t = l_{t-1} + b + \alpha \epsilon_t ;$$

240 where $\{\epsilon_t\}$ is assumed to follow Gaussian white noise with mean zero and variance σ^2
 241 and α is the smoothing parameter for the simple exponential smoothing (SES) model.
 242 Now, Y_t follows a state space model which gives forecasts equivalent to SES with drift
 243 [26]. Also, Y_t can be written in the following form:

$$Y_t = Y_{t-1} + b + (\alpha - 1)\epsilon_{t-1} + \epsilon_t. \quad (5)$$

244 The above is an ARIMA(0,1,1) process with drift term [26]. The left-out residuals of
 245 Theta model is further modeled by ARNN process. We consider the ARNN process
 246 generated by the additive noise of the ARIMA(0,1,1) process with drift. Let ϵ_t be the
 247 process defined by the stochastic difference equation of the following form:

$$\epsilon_t = f(\epsilon_{t-1}, \epsilon_{t-2}, \dots, \epsilon_{t-p}, \Theta) + \varepsilon_t, \quad (6)$$

248 where ε_t is an i.i.d. noise process and $f(\cdot, \Theta)$ is a feedforward neural network with
 249 weight (parameter) vector Θ and inputs $\epsilon_{t-1}, \epsilon_{t-2}, \dots, \epsilon_{t-p}$. The definition of f is
 250 given in Eqn. (4).

251 **3.1. Time Series as Markov chains**

252 We start by defining the following notations:

$$\begin{aligned} z_{t-1} &= (\epsilon_{t-1}, \dots, \epsilon_{t-p})' \\ F(z_{t-1}) &= (f(z_{t-1}), \epsilon_{t-1}, \dots, \epsilon_{t-p+1})' \\ e_t &= (\varepsilon_t, 0, \dots, 0)' \end{aligned}$$

253 Then Eqn. (6) can be written as follows [10]:

$$z_t = F(z_{t-1}) + e_t \quad (7)$$

254 with $z_t, e_t \in \mathbb{R}^p$. In this section, we show the (strict) stationarity of the state space
 255 form, as defined in Eqn. (7). The problem of showing $\{z_t\}$ to be stationary is closely
 256 related to the ergodicity of the process [55]. A Markov chain $\{z_t\}$ is called geometrically
 257 ergodic if there exists a probability measure π on the state space $(\mathbb{R}^p, \mathbb{B})$ and a constant
 258 $\rho > 1$ such that

$$\lim_{n \rightarrow \infty} \rho^n \|P^n(z, A) - \pi(A)\| = 0 \quad (8)$$

259 for each $z \in \mathbb{R}^p$, $\mathbb{B}$ is the Borel σ -algebra on $\mathbb{R}^p$ and $\|\cdot\|$ denotes the total variation
 260 norm. If Eqn. (8) holds for $\rho = 1$, then $\{z_t\}$ is called ergodic.

261

The definition for $P^n(z, A)$ can be given as the probability that $\{z_n\}$ moves from z to the set $A \in \mathbb{B}$ in n steps: $P^n(z, A) = P(z_{t+n} \in A | z_t = z)$. Also, expression for $\pi(A)$ is as follows:

$$\pi(A) = \int P^1(z, A) \pi(dz) \text{ for all } A \in \mathbb{B}.$$

Thus, we call π as the stationary measure and the distribution of z_t converges to π if $\{z_t\}$ is ergodic. Then, we say $\{z_t\}$ is asymptotically stationary [33]. To establish the ergodicity of TARNN processes, we need the concept of irreducibility and aperiodicity. A Markov chain $\{z_t\}$ is called irreducible if

$$\sum_{n=1}^{\infty} P^n(z, A) > 0 \text{ for all } z \in \mathbb{R}^p,$$

whenever $\lambda(A) > 0$ and λ denotes the Lebesgue measure on $(\mathbb{R}^p, \mathbb{B})$. Thus, for an irreducible Markov chain, all parts of the state space can be reached by the Markov chain irrespective of the starting point. Now, an irreducible Markov chain is aperiodic if there exists an $A \in \mathbb{B}$ with $\lambda(A) > 0$ and for all $C \in \mathbb{B}$, $C \subseteq A$ with $\lambda(C) > 0$, there exists a positive integer n such that

$$P^n(z, C) > 0 \text{ and } P^{n+1}(z, C) > 0 \text{ for all } z \in \mathbb{R}^p.$$

262 Hence, it is possible that the Markov chain returns to given sets only at specific time
263 points for an aperiodic Markov chain. For most general time series models, irreducibil-
264 ity and aperiodicity cannot be assumed automatically. However, for a TARNN process,
265 these conditions can be checked. In general, it is sufficient to assume the distribution of
266 the noise process to be an absolutely continuous component with respect to Lebesgue
267 measure and the support of the probability density function (PDF) is sufficiently large.

268 3.2. Main Results

269 It is clear from the above discussion that if the Markov chain is geometrically ergodic,
270 then its distribution will converge to π and the corresponding time series will be called
271 asymptotically stationary, see also [53]. Lemma 3.1 states that the state space of the
272 Markov chain cannot be reduced depending on the starting point.

273 **Lemma 3.1.** *Let $\{z_t\}$ is defined by (7), and let $E|\varepsilon_t| < \infty$ and the PDF of ε_t is positive
274 everywhere in $\mathbb{R}$. Then if f is defined by (4), the Markov chain $\{z_t\}$ is φ -irreducible
275 and aperiodic.*

276 **Proof.** Since the support of the PDF of ε_t is the whole real line, that is, the PDF
277 is positive everywhere in $\mathbb{R}$, then we can say that $\{z_t\}$ is φ -irreducible by using [10].
278 In our case, every non-null p -dimensional hypercube can be reached in p steps with
279 positive probability (and hence every non-null Borel set A). A necessary and sufficient
280 condition for $\{z_t\}$ to be aperiodic is to have a set A and positive integer n such that
281 $P^n(z, A) > 0$ and $P^{n+1}(z, A) > 0$ for all $z \in A$ [53]. In this case, this is true for all n
282 due to consideration of the unbounded additive noise. $\square$

283 The theorem below states the necessary conditions for geometric ergodicity of a
284 Markov chain. This can be obtained using the decomposition technique and ergodicity
285 of stochastic difference equations [7,10].

286 **Theorem 3.2.** Suppose $\{z_t\}$ is defined as in (6) and (7), F be a compact set that can
287 be decomposed as $F = F_h + F_d$, and the following conditions hold:

- 288 (i) $F_h(\cdot)$ is continuous and homogeneous and $F_d(\cdot)$ is bounded;
289 (ii) $E|\varepsilon_t| < \infty$ and probability distribution function of ε_t is positive everywhere in $\mathbb{R}$;
290 then $\{z_t\}$ is geometrically ergodic.

291 **Proof.** $\{z_t\}$ satisfies the following equation:

$$z_t = F(z_{t-1}) + e_t; \quad t \geq 1, \text{ and } F: \mathbb{R}^p \rightarrow \mathbb{R}^p. \quad (9)$$

292 Let F_h be continuous and homogeneous, viz., $F_h(cz) = cF_h(z)$ for all $c > 0$, $z_t \in \mathbb{R}^p$,
293 and F_d is bounded. Let the origin, O , be a fixed point of F_h . It is important to note that
294 ε_t satisfies the condition (ii) in Theorem 3.2. We are going to show that the existence
295 of a continuous Lyapunov function, V , in a neighbourhood of the origin which will
296 ensure the geometric ergodicity of (7).

297 To start with we let $W \subseteq \mathbb{R}^p$, the closure of W by $\overline{W}$ and its boundary by $\widehat{W}$. We also
298 let V be defined over the closure of the unit ball. We let $p_0 = \inf_{\|z\|=1} V(z)$, where
299 $\|\cdot\|$ denote the Euclidean norm. Also, let G be the maximal connected component of
300 $\{z: V(z) < \frac{p_0}{2}\}$ that contains the origin. Then we have $F(\overline{G}) \subset G$.

301 Let $g(z) = \inf\{r \geq 0, z \in rG\}$, $z \in \mathbb{R}^p$, where $rG = \{rz, z \in G\}$. Then $g(z)$ is well
302 defined and it can easily be checked that g has the following properties:

- 303 (1) $g(cz) = cg(z)$, for all $c > 0$.
304 (2) There exists $0 < c < \mathbb{C} < \infty$ such that $c\|z\| \leq g(z) \leq \mathbb{C}\|z\|$.
305 (3) $(z/g(z)) \in \widehat{G}$.
306 (4) There exists $\epsilon > 0$, $0 < \theta < 1$ such that for all $z \in \widehat{G}$, $y \in \mathbb{R}^p$, we have
307 $\|y - F(z)\| < \epsilon \Rightarrow y \in G$ and $g(y) < \theta$.

Now, for Eqn. (7), ε_t satisfies $E|\varepsilon_t| < \infty$. Let $A \in \mathbb{B}$ and $z \in \mathbb{R}^p$, we define $P(z, A)$ be the transition probability function as:

$$P(z, A) = \int_{A-F(z)} f(t) \mathbb{P}(dt).$$

Thus, it holds that

$$\begin{aligned}
 & \int g(y)P(z, dy) \\
 &= \int g(F_h(z) + t)f(t)\mathbb{P}(dt) \\
 &= \int_{\|t/g(z)\| < \epsilon} g(z)g\left(F_h\left(\frac{z}{g(z)}\right) + \frac{t}{g(z)}\right)f(t)\mathbb{P}(dt) \\
 & \quad + \int_{\|t/g(z)\| \geq \epsilon} g(z)g\left(F_h\left(\frac{z}{g(z)}\right) + \frac{t}{g(z)}\right)f(t)\mathbb{P}(dt) \\
 &< [\theta g(z)] + [M + g(z)\beta(z)] \text{ for some } M > 0.
 \end{aligned}$$

Here $|\beta(z)| < B < \infty$ for all z and $\beta(z) \rightarrow 0$ as $\|z\| \rightarrow \infty$. We let $h(z) = g(z) + 1$, and r be such that

$$|\beta(z)| < \frac{(1 - \theta)}{4} \quad \text{for } \|z\| > r.$$

308 Then for $r_0 = \max\left(r, \frac{4(C+1)}{(1-\theta)^p}\right)$, there exists B' such that

- 309 (1) $\int f(y)P(z, dy) < B' < \infty$ when $\|z\| \leq r_0$.
 310 (2) $\int f(y)P(z, dy) < \frac{1}{2}(1 + \theta)h(z)$ when $\|z\| > r_0$.

311 Using Theorem 4 of [55], we can conclude that $\{z_t\}$ is geometric ergodic. $\square$

312 The next theorem gives the main result for asymptotic stationary of the TARNN
 313 model.

314 **Theorem 3.3.** *Let $E|\varepsilon_t| < \infty$ and the PDF of ε_t is positive everywhere in $\mathbb{R}$, and $\{\varepsilon_t\}$
 315 and $\{z_t\}$ are defined as in (6) and (7), respectively. Then if f is a nonlinear neural
 316 network as defined in (4), then $\{z_t\}$ is geometrically ergodic and $\{\varepsilon_t\}$ is asymptotically
 317 stationary.*

318 **Proof.** The noise process ε_t satisfies $E|\varepsilon_t| < \infty$ by assumption (e.g., Gaussian noise).
 319 It is also important to note that neural network activation functions, more precisely
 320 logistics or tan-hyperbolic activation functions, are continuous compact functions and
 321 have a bounded range. Thus $\{z_t\}$ satisfies all the criteria to be geometrically ergodic
 322 and using Theorem (3.2), one can write that for the ARNN process with $F_h \equiv 0$ and
 323 $F_d \equiv F$. Thus, the series $\{\varepsilon_t\}$ is asymptotically stationary. $\square$

324 **Remark 2.** Some interpretations and practical implications of the theoretical results
 325 are given below:

- 326 • The geometric rate of convergence in Theorem 3.3 implies that the memory
 327 of TARNN process vanishes exponentially fast. This implies that the simplest
 328 version of the proposed model converges to a Wiener process.
- 329 • This is important for predictions over larger intervals of time, for example, one
 330 might train the network on an available sample and then use the trained network
 331 to generate new data with similar properties like the training sample. The results

for the asymptotic stationarity can guarantee that the proposed hybrid model can not have growing variance over time.

- From practitioners point of view, when the data is generated by the irreducible TARNN process, the estimated weights are not too far from the true weights. Then, one can draw an indirect conclusion on the statistical nature of the observed data based on the estimated weights.

4. Experimental Analysis

Table 1. Training data sets (new daily cases) and corresponding ACF, PACF plots for all the countries considered in this study.

Five time series COVID-19 datasets are considered for assessing various forecasting models (individual and hybrid). The datasets are mostly nonlinear, nonstationary, and

non-Gaussian in nature. We have used root mean square error (RMSE), mean absolute error (MAE), and mean absolute scaled error (MASE) [27] to evaluate the predictive performance of the models used in this study. Since the number of data points in all the datasets is limited, advanced deep learning techniques will overfit the datasets [20].

4.1. Data Description

Data is collected from the “Our World in Data” public repository (Link: <https://ourworldindata.org/coronavirus>) on five countries: USA, Brazil, India, UK, and Canada that have the leading number of confirmed cases of COVID-19. These are univariate time-series from inception-Feb 26, 2021 of confirmed cases that are analyzed for generating future outbreak predictions. We have taken last 60 data points as test points on which the forecasting models are evaluated. A summary of the COVID-19 data sets of confirmed cases and their descriptions are presented in Table 2. A pictorial view of the training data sets along with auto-correlation function (ACF) and partial ACF (PACF) plots are given in Table 1.

Country Name	Start-End Date	No. of Days	Minimum Value	Maximum Value	Train size	Test size
USA	22/01/2020 - 26/02/2021	402	0	251161	342	60
Brazil	26/02/2020 - 26/02/2021	367	0	70574	307	60
India	30/01/2020 - 26/02/2021	394	0	97894	334	60
UK	31/01/2020 - 26/02/2021	393	0	41460	333	60
Canada	26/01/2020 - 26/02/2021	398	0	10100	338	60

Table 2. Description of COVID-19 datasets.

4.2. Performance Evaluation Metrics

The performance of different forecasting models are evaluated based on RMSE, MAE, and MASE metrics for these five time series [24]:

$$RMSE = \sqrt{\frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2}; \quad MAE = \frac{1}{n} \sum_{i=1}^n |y_i - \hat{y}_i|$$

where, y_i is the actual value, $\hat{y}_i$ is the predicted value, and n denotes the number of data points. MASE is computed using ‘mase’ function available under the “Metrics” package in R statistical software. By definition, the lower the value of these performance metrics, the better is the performance of the concerned forecasting model.

4.3. Analysis of Results

A schematic diagram is presented in Figure 2 to give an outline of the models to be used in this section. We start the experimental evaluation for all data sets with the classical ARIMA(p, d, q) using ‘forecast’ [25] statistical package in the R statistical software [44]. The nonlinear and nonseasonal time series of these countries were modelled with traditional and advanced methods such as ARIMA, Theta,

Figure 2. Time series forecasting tools (available and proposed) used in this study.

WARIMA, ETS, TBATS, ARNN, and two popularly used hybrid models, namely hybrid ARIMA-ARNN [8], hybrid ARIMA-WARIMA [9], and the newly introduced hybrid Theta-ARNN (TARNN) models. For the accuracy of prediction, the data was partitioned into training and test sets, where the test set consisted of last 60 data points, and the training set included (inception - 60+1) data points. Table 3 gives the essential details about the functions and packages required for the implementation of standard individual models.

In the proposed TARNN model, linear modelling is conducted with Theta model using ‘thetaf’ function under the “forecast” package in R statistical software. Nonlinear modelling with ARNN approach is carried out with “caret” package using ‘nnetar’ function in R statistical software. Furthermore, Theta residuals are modelled with ARNN(p, k) model having a pre-defined Box-Cox transformation set $\lambda = 0$ to ensure the forecast values to stay positive. The values of p and k are obtained by training the network, which is a data-dependent approach as discussed in Section 2.2. Further, both the linear and nonlinear forecasts are summed up to obtain the final forecasts. Theta model was fitted to five data sets namely USA, Brazil, India, UK, and Canada. Theta model residuals for these five countries were trained using ARNN(15,8), ARNN(21,11), ARNN(25,13), ARNN(24,12), ARNN(12,6), and ARNN(9,5) models with an average of 500 networks for all five data sets, each of which is a 15-8-1, 21-11-1, 25-13-1, 24-12-1, 12-6-1, and 9-5-1 networks with 137, 254, 352, 313, 85, and 56 weights and with 5807711, 309816, 20735, 883.6, 209396, and 59477 estimated σ^2 , respectively. Finally, the predicted results of both Theta and ARNN models are added together to obtain the estimated forecasts of the proposed TARNN model. Rest of the hybrid models were compared in the similar fashion.

We compared our proposed TARNN model with traditional single models (ARIMA, TBATS, Theta, ARNN, WARIMA, ETS) along with hybrid ARIMA-WARIMA model, hybrid ARIMA-ARNN model and the experimental results are

Model	R function	R package	Reference
ARIMA	auto.arima	forecast	[25]
ETS	ets	forecast	[25]
TBATS	tbats	forecast	[25]
Theta	thetaf	forecast	[25]
ARNN	nnetar	forecast	[25]
WARIMA	WaveletFittingarma	WaveletArima	[39]

Table 3. R functions and packages for standard forecasting model implementations.

reported in Table 4. The performance of the proposed hybrid Theta-ARNN (TARNN) model is superior compared to all traditional individual and hybrid models on average. The theoretically proven asymptotic stationarity of the proposed hybrid model also suggests that the model cannot have a growing variance over time. The consistency and adequacy in the experimental results empirically approves the same. Thus, the efficacy of the proposed methodology of the proposed hybrid model is experimentally validated. Nevertheless, no model can have dominant advantage and this is related to no free lunch theorem in statistical learning [20]. Forecast of COVID-19 cases for March 20-29, 2021 are generated using proposed TARNN model and shown in Figure 3.

Methods	USA	UK	India	Canada	Brazil
MASE values					
ARIMA	3.55	5.53	0.67	2.08	1.55
Theta	3.24	5.88	1.89	2.08	1.31
WARIMA	4.97	6.46	5.26	1.8	1.53
ETS	2.47	5.62	1.17	1.65	1.86
TBATS	2.46	5.58	1.44	1.81	4.77
ARNN	3.29	5.67	3.16	2.23	2.83
ARIMA-ARNN	3.59	5.50	0.71	2.06	1.53
ARIMA-WARIMA	3.64	5.69	0.72	2.05	1.58
Proposed TARNN	3.27	5.07	1.60	1.53	1.05
RMSE values					
ARIMA	85378.21	19598.5	5325.44	2879.54	28661.69
Theta	77538.27	21033.15	9159.85	2976.44	22950.91
WARIMA	116791.17	43298.22	25609.64	2764.52	28139.06
ETS	60473.05	20017.92	6527.45	2425.78	33242.02
TBATS	60472.43	19855.08	7262.95	2647.24	86202.46
ARNN	79694.81	16796.84	14859.34	3063.08	48693.24
ARIMA-ARNN	86626.36	19557.8	5323.38	2876.86	27825.87
ARIMA-WARIMA	86938.13	20249.21	5428.55	2845.54	28908.41
Proposed TARNN	78320.37	16559.04	7854.66	2323.95	20423.69
MAE values					
ARIMA	72823.9	17672.58	2833.76	2390.47	24714.92
Theta	66491.15	18797.76	8024.95	2497.19	20853.47
WARIMA	101923.84	36890.4	22279.76	2069.01	24294.93
ETS	50537.67	17953.84	4972.05	1893.77	29506.42
TBATS	50533.39	17839.37	6091.65	2074.26	75834.12
ARNN	67409.69	14941.82	13389.13	2556.93	44939.99
ARIMA-ARNN	73690.5	17585.56	3023.91	2386.66	24259.25
ARIMA-WARIMA	74637.97	18187.05	3056.05	2353.5	25162.57
Proposed TARNN	66939.65	14770.08	5487.11	758.82	16701.18

Table 4. Quantitative measure of performances of forecasting methods on the COVID-19 test data sets for five countries. Best results are made 'bold'. Proposed TARNN beats all the models for three out of five data sets and remain competitive for other two data sets.

Figure 3. Forecast of COVID-19 cases for March, 2021 using proposed TARNN model.

405 5. Discussions and Conclusions

406 In this study, we proposed a novel hybrid Theta-ARNN (TARNN) model using
 407 residual modelling approach that performs considerably well for confirmed cases of
 408 COVID-19 forecasting for the countries that include the ones with the highest number
 409 of cases USA, followed by Brazil, India, UK, and Canada. The proposed TARNN

model filters linearity using the Theta model and can better explain the linear, nonlinear, and nonstationary tendencies present in the selected COVID-19 data sets compared to the traditional single and hybrid models. It also yields better forecast accuracy than various traditional single and hybrid models for three out of five countries. The proposal will be useful in decision and policy making for government officials and policymakers to allocate adequate health care resources for the coming days in responding to the crisis. Time series of epidemics can oscillate heavily due to various epidemiological factors and these fluctuations are challenging to be captured adequately for precise forecasting. This newly developed model can still predict with better accuracy provided the conditions of asymptotic stationarity of the hybrid model are satisfied. This method can be used to update real-time forecasts as more data becomes available. The study covering multiple countries can be utilized without geographical borders and reflects the impact of social distancing, wearing masks, lock down, shutdown, quarantine, and sanitizing proper measures implemented by authorities. Prevalent techniques in literature were unable to completely capture the nonlinear behavior of stochastic time series containing inherent random shock components. This new method have significant theoretical (established ergodicity and stationarity of the proposed TARNN process) as well as practical implications. Authorities and health care can modify their planning in stockpiles and hospital-beds depending on these forecasts of the COVID-19 pandemic.

Many parameters associated with COVID-19 transmission are still poorly understood. The resulting model uncertainty is not always calculated or reported in a standardized way. Once we can incorporate these variables, we can improve our estimates and update the TARNN model accordingly. Since purely statistical approaches do not account for how transmission occurs, they are generally not well suited for long-term predictions about epidemiological dynamics (such as when the peak will occur and whether a resurgence will happen) or for inferences about intervention efficacy. Most forecasting models therefore limit their projections to one week or a few weeks ahead. Moreover, the problem of using confirmed cases to fit models is further complicated by the fact that the fraction of cases that are confirmed is spatially heterogeneous and time-varying. Amid enormous uncertainty about the future of the COVID-19 pandemic, the proposed TARNN model yields quantitative projections that policymakers may need in the short term to allocate resources or plan interventions. To conclude, this model can further be easily extended for similar nonlinear and non-Gaussian forecasting problems arising in other applied domains.

Data and Code

All the results can be effortlessly updated with the help of R-shiny application as new data becomes available. This publicly available repository link <https://github.com/arinjita9/COVID-19-Forecasting-by-TARNN> contains the current data files and R scripts for the TARNN model which ensures the repeatability and reproducibility of the results presented in this study.

Disclosure statement

The authors declare that they have no competing interests.

Funding

The authors had no funding for this work.

References

- [1] V. Assimakopoulos and K. Nikolopoulos, *The theta model: a decomposition approach to forecasting*, International journal of forecasting 16 (2000), pp. 521–530.
- [2] D. Baud, X. Qi, K. Nielsen-Saines, D. Musso, L. Pomar, and G. Favre, *Real estimates of mortality following covid-19 infection*, The Lancet infectious diseases (2020).
- [3] M.N.K. Boulos and E.M. Geraghty, *Geographical tracking and mapping of coronavirus disease covid-19/severe acute respiratory syndrome coronavirus 2 (sars-cov-2) epidemic and associated events around the world: how 21st century gis technologies are supporting the global fight against outbreaks and epidemics* (2020).
- [4] G.E. Box, G.M. Jenkins, G.C. Reinsel, and G.M. Ljung, *Time series analysis: forecasting and control*, John Wiley & Sons, 2015.
- [5] P.J. Brockwell and A. Lindner, *Strictly stationary solutions of autoregressive moving average equations*, Biometrika 97 (2010), pp. 765–772.
- [6] E. Cadenas and W. Rivera, *Wind speed forecasting in three different regions of mexico, using a hybrid arima-ann model*, Renewable Energy 35 (2010), pp. 2732–2738.
- [7] T. Chakraborty, A.K. Chakraborty, M. Biswas, S. Banerjee, and S. Bhattacharya, *Unemployment rate forecasting: A hybrid approach*, Computational Economics 57 (2021), pp. 183–201.
- [8] T. Chakraborty, S. Chattopadhyay, and I. Ghosh, *Forecasting dengue epidemics using a hybrid methodology*, Physica A: Statistical Mechanics and its Applications (2019), p. 121266.
- [9] T. Chakraborty and I. Ghosh, *Real-time forecasts and risk assessment of novel coronavirus (covid-19) cases: A data-driven analysis*, Chaos, Solitons & Fractals (2020), p. 109850.
- [10] K.S. Chan and H. Tong, *On the use of the deterministic lyapunov function for the ergodicity of stochastic difference equations*, Advances in applied probability 17 (1985), pp. 666–678.
- [11] A.J. Conejo, M.A. Plazas, R. Espinola, and A.B. Molina, *Day-ahead electricity price forecasting using the wavelet transform and arima models*, IEEE transactions on power systems 20 (2005), pp. 1035–1042.
- [12] A.M. De Livera, R.J. Hyndman, and R.D. Snyder, *Forecasting time series with complex seasonal patterns using exponential smoothing*, Journal of the American statistical association 106 (2011), pp. 1513–1527.
- [13] E.J. Emanuel, G. Persad, R. Upshur, B. Thome, M. Parker, A. Glickman, C. Zhang, C. Boyle, M. Smith, and J.P. Phillips, *Fair allocation of scarce medical resources in the time of covid-19* (2020).
- [14] D. Fanelli and F. Piazza, *Analysis and forecast of covid-19 spreading in china, italy and france*, Chaos, Solitons & Fractals 134 (2020), p. 109761.
- [15] J. Faraway and C. Chatfield, *Time series forecasting with neural networks: a comparative study using the air line data*, Journal of the Royal Statistical Society: Series C (Applied Statistics) 47 (1998), pp. 231–250.
- [16] I. Ghosh and T. Chakraborty, *An integrated deterministic-stochastic approach for forecasting the long-term trajectories of covid-19*, International Journal of Modeling, Simulation, and Scientific Computing (2021), p. 2141001.
- [17] G. Grasselli, A. Pesenti, and M. Cecconi, *Critical care utilization for the covid-19 outbreak in lombardy, italy: early experience and forecast during an emergency response*, Jama 323 (2020), pp. 1545–1546.
- [18] G. Grasselli, A. Zangrillo, A. Zanella, M. Antonelli, L. Cabrini, A. Castelli, D. Cereda, A.

- Coluccello, G. Foti, R. Fumagalli, *et al.*, *Baseline characteristics and outcomes of 1591 patients infected with sars-cov-2 admitted to icus of the lombardy region, italy*, *Jama* 323 (2020), pp. 1574–1581.
- [19] W.j. Guan, Z.y. Ni, Y. Hu, W.h. Liang, C.q. Ou, J.x. He, L. Liu, H. Shan, C.l. Lei, D.S. Hui, *et al.*, *Clinical characteristics of coronavirus disease 2019 in china*, *New England journal of medicine* 382 (2020), pp. 1708–1720.
- [20] T. Hastie, R. Tibshirani, and J. Friedman, *The elements of statistical learning: data mining, inference, and prediction*, Springer Science & Business Media, 2009.
- [21] I. Holmdahl and C. Buckee, *Wrong but useful—what covid-19 epidemiologic models can and cannot tell us*, *New England Journal of Medicine* (2020).
- [22] C. Huang, Y. Wang, X. Li, L. Ren, J. Zhao, Y. Hu, L. Zhang, G. Fan, J. Xu, X. Gu, *et al.*, *Clinical features of patients infected with 2019 novel coronavirus in wuhan, china*, *The lancet* 395 (2020), pp. 497–506.
- [23] R. Hyndman, A.B. Koehler, J.K. Ord, and R.D. Snyder, *Forecasting with exponential smoothing: the state space approach*, Springer Science & Business Media, 2008.
- [24] R.J. Hyndman and G. Athanasopoulos, *Forecasting: principles and practice*, OTexts, 2018.
- [25] R.J. Hyndman, G. Athanasopoulos, C. Bergmeir, G. Caceres, L. Chhay, M. O’Hara-Wild, F. Petropoulos, S. Razbash, and E. Wang, *Package ‘forecast’*, Online] <https://cran.r-project.org/web/packages/forecast/forecast.pdf> (2020).
- [26] R.J. Hyndman and B. Billah, *Unmasking the theta method*, *International Journal of Forecasting* 19 (2003), pp. 287–290.
- [27] R.J. Hyndman and A.B. Koehler, *Another look at measures of forecast accuracy*, *International journal of forecasting* 22 (2006), pp. 679–688.
- [28] J.P. Ioannidis, S. Cripps, and M.A. Tanner, *Forecasting for covid-19 has failed*, *International journal of forecasting* (2020).
- [29] A.J. Kucharski, T.W. Russell, C. Diamond, Y. Liu, J. Edmunds, S. Funk, R.M. Eggo, F. Sun, M. Jit, J.D. Munday, *et al.*, *Early dynamics of transmission and control of covid-19: a mathematical modelling study*, *The lancet infectious diseases* (2020).
- [30] L.I. Kuncheva, *Combining pattern classifiers: methods and algorithms*, John Wiley & Sons, 2004.
- [31] Q. Li, W. Feng, and Y.H. Quan, *Trend and forecasting of the covid-19 outbreak in china*, *Journal of Infection* 80 (2020), pp. 469–496.
- [32] A. Maleki, S. Nasser, M.S. Aminabad, and M. Hadi, *Comparison of arima and nnar models for forecasting water treatment plant’s influent characteristics*, *KSCE J. CIV. ENG.* 22 (2018), pp. 3233–3245.
- [33] S.P. Meyn and R.L. Tweedie, *Markov chains and stochastic stability*, Springer Science & Business Media, 1993.
- [34] L. Milačić, S. Jović, T. Vujović, and J. Miljković, *Application of artificial neural network with extreme learning machine for economic growth estimation*, *Physica A* 465 (2017), pp. 285–288.
- [35] A. Mosleh and G. Apostolakis, *The assessment of probability distributions from expert opinions with an application to seismic fragility curves*, *Risk analysis* 6 (1986), pp. 447–461.
- [36] M.R. Oliveira and L. Torgo, *Ensembles for time series forecasting*, *J. Mach. Learn. Res.* 39 (2014), pp. 360–370.
- [37] W.H. Organization, *et al.*, *Who director-general’s opening remarks at the media briefing on covid-19-11 march 2020* (2020).
- [38] A. Pasini, *Artificial neural networks for small dataset analysis*, *Journal of thoracic disease* 7 (2015), p. 953.
- [39] R.K. Paul, S. Samanta, M.R.K. Paul, and T. LazyData, *Package ‘waveletarima’*, *Seed* 500 (2017), pp. 1–5.
- [40] M. Perc, N. Gorišek Miksić, M. Slavinec, and A. Stožer, *Forecasting covid-19*, *Frontiers in Physics* 8 (2020), p. 127.
- [41] D.B. Percival and A.T. Walden, *Wavelet methods for time series analysis*, Vol. 4, Cam-

- bridge university press, 2000.
- [42] D.B. Percival and A.T. Walden, *Spectral Analysis for Univariate Time Series*, Vol. 51, Cambridge University Press, 2020.
- [43] F. Petropoulos and S. Makridakis, *Forecasting the novel coronavirus covid-19*, PloS one 15 (2020), p. e0231236.
- [44] R Core Team, *R: A Language and Environment for Statistical Computing*, R Foundation for Statistical Computing, Vienna, Austria (2017). Available at <https://www.R-project.org/>.
- [45] D. Ray, M. Salvatore, R. Bhattacharyya, L. Wang, J. Du, S. Mohammed, S. Purkayastha, A. Halder, A. Rix, D. Barker, *et al.*, *Predictions, role of interventions and effects of a historic national lockdown in india's response to the covid-19 pandemic: data science call to arms*, Harvard data science review 2020 (2020).
- [46] M.H.D.M. Ribeiro, R.G. da Silva, V.C. Mariani, and L. dos Santos Coelho, *Short-term forecasting covid-19 cumulative confirmed cases: Perspectives for brazil*, Chaos, Solitons & Fractals (2020), p. 109853.
- [47] K. Roosa, Y. Lee, R. Luo, A. Kirpich, R. Rothenberg, J. Hyman, P. Yan, and G. Chowell, *Real-time forecasts of the covid-19 epidemic in china from february 5th to february 24th, 2020*, Infectious Disease Modelling 5 (2020), pp. 256–263.
- [48] L. Rosenbaum, *Facing covid-19 in italy—ethics, logistics, and therapeutics on the epidemic's front line*, New England Journal of Medicine 382 (2020), pp. 1873–1875.
- [49] D.E. Rumelhart, G.E. Hinton, and R.J. Williams, *Learning internal representations by error propagation*, Tech. Rep., California Univ San Diego La Jolla Inst for Cognitive Science, 1985.
- [50] F. Rustam, A.A. Reshi, A. Mehmood, S. Ullah, B.W. On, W. Aslam, and G.S. Choi, *Covid-19 future forecasting using supervised machine learning models*, IEEE access 8 (2020), pp. 101489–101499.
- [51] E. Spiliotis, V. Assimakopoulos, and S. Makridakis, *Generalizing the theta method for automatic forecasting*, European Journal of Operational Research 284 (2020), pp. 550–558.
- [52] R. Sujath, J.M. Chatterjee, and A.E. Hassanien, *A machine learning forecasting model for covid-19 pandemic in india*, Stochastic Environmental Research and Risk Assessment (2020), p. 1.
- [53] A. Trapletti, F. Leisch, and K. Hornik, *Stationary and integrated autoregressive neural network processes*, Neural Computation 12 (2000), pp. 2427–2450.
- [54] A. Trilla, G. Trilla, and C. Daer, *The 1918 "spanish flu" in spain*, Clinical infectious diseases 47 (2008), pp. 668–673.
- [55] R. Tweedie, *The existence of moments for stationary markov chains*, Journal of Applied Probability 20 (1983), pp. 191–196.
- [56] J.T. Wu, K. Leung, and G.M. Leung, *Nowcasting and forecasting the potential domestic and international spread of the 2019-ncov outbreak originating in wuhan, china: a modelling study*, The Lancet 395 (2020), pp. 689–697.
- [57] L. Wynants, B. Van Calster, M.M. Bonten, G.S. Collins, T.P. Debray, M. De Vos, M.C. Haller, G. Heinze, K.G. Moons, R.D. Riley, *et al.*, *Prediction models for diagnosis and prognosis of covid-19 infection: systematic review and critical appraisal*, bmj 369 (2020).
- [58] G.P. Zhang, *Time series forecasting using a hybrid arima and neural network model*, Neurocomputing 50 (2003), pp. 159–175.
- [59] G. Zhang, B.E. Patuwo, and M.Y. Hu, *Forecasting with artificial neural networks: The state of the art*, International journal of forecasting 14 (1998), pp. 35–62.
- [60] Z. Zhuang, P. Cao, S. Zhao, Y. Lou, W. Wang, S. Yang, L. Yang, and D. He, *Estimation of local novel coronavirus (covid-19) cases in wuhan, china from off-site reported cases and population flow data from different sources*, medRxiv (2020).