1 Comparison of respiratory protection during exercising tasks between different wearing methods of
2 replaceable particulate respirators and powered air-purifying respirators

3

4 Hiroka Baba, Hajime Ando*, Kazunori Ikegami, Shingo Sekoguchi, Taiki Shirasaka, Akira Ogami

5

6 Department of Work Systems and Health, Institute of Industrial Ecological Sciences, University of

7 Occupational and Environmental Health, Japan

8 1-1, Iseigaoka, Yahata-nishi-ku, Kitakyushu, Fukuoka 807-8555, Japan

9 Tel: +81-93-691-7471, Fax: +81-93-601-2667

10

11 *Corresponding author

12 Hajime Ando, MD, PhD.

13 Department of Work System and Health at the University of Occupational and Environmental Health,

14 Japan 1-1, Iseigaoka, Yahata-nishi-ku, Kitakyushu, Fukuoka 807-8555, Japan

15 Tel: +81-93-691-7471, Fax: +81-93-601-2667

16 E-mail: h-ando@med.uoeh-u.ac.jp

17

18 **Running title:** Replaceable particulate respirators versus powered air-purifying respirators

19

20 **Funding**

21 This study was funded by the Industrial Disease Clinical Research Grants.

22

23 **Abstract**

24 **Background**

25 This study evaluated the differences in respiratory protection between replaceable particulate
26 respirators (RPRs) and powered air-purifying respirators (PAPRs), with different wearing methods,
27 during exercising tasks.

28 **Methods**

29 Ten participants wore either RPR or PAPR according to the recommended method, with a knit cover
30 placed between the facepiece cushion and the face, or with the headband on a helmet. We measured
31 the number of particles inside and outside the respiratory protective equipment (RPE) during
32 exercising tasks for each wearing variation. The exercise state was set to exercise with an ergometer
33 set at 80W load. While exercising tasks, the participants performed five actions adopted from JIS
34 T8150 in 2018 (1. Normal breathing, 2. Deep breathing, 3. Turning head side to side, 4. Moving head
35 up and down, 5. Talking). Each action was performed for 1 min. For measurements of exercise state,
36 after 10 minutes of exercise tasks, we measured while the exercise was continued. The fit factor was
37 calculated by dividing the concentration within the RPE by the concentration outside of it. Data were
38 analyzed after they were log-transformed with a linear mixed model, with fit factor as the dependent

39 variable.

40 Results

41 We compared the results with experimental data of resting state reported in our previous studies. Fit
42 factor of RPRs in the exercise state was significantly lower ($p < 0.001$) than that in the resting state,
43 indicating inadequate respiratory protection. In contrast, the fit factor of PAPRs during exercising
44 tasks was significantly lower ($p < 0.001$) than that at rest; however, respiratory protection was
45 maintained. PAPR did not show a significant decrease ($p = 1.000$) in fit factor owing to the wearing
46 variations during exercising tasks.

47 Conclusions

48 PAPRs were found to be superior to RPRs in terms of respiratory protection. PAPRs are better than
49 RPRs for workers who have to wear RPE inappropriately due to health problems.

50

51 **Key words:** particulate respirator, powered air-purifying respirator, fit factor, respiratory disease

52

53

54 Introduction

55 The number of cases of pneumoconiosis and occupational diseases due to complications of
56 pneumoconiosis in Japan decreased to 164 in 2019; however, new cases are still occurring.¹

57 It is necessary to implement technical and work control measures to reduce the risk of

pneumoconiosis and its complications. If such measures are not sufficient to reduce hazards, it is important to wear respiratory protective equipment (RPE), which helps to reduce workers' exposure to dust and toxic chemicals through inhalation and prevent various occupational diseases. However, previous studies have shown that wearing RPE that do not allow sufficient adhesion between the face and the RPE does not provide adequate respiratory protection.^{2,3} For this reason, the Ministry of Health, Labour and Welfare in Japan has issued guidelines on matters to be considered in the selection and use of RPE.⁴ Previous studies have shown that those working in dusty workplaces in Japan wear RPE in various ways. We found that RPE was worn in several inappropriate ways, such as by wearing a tightening strap over the helmet or by wearing RPE over a towel wrapped around the face in hot workplace environments.⁵ When the respiratory protection capacity of RPE is reduced, inhalation of dust, toxic chemicals, etc. can lead to the development of respiratory diseases such as pneumoconiosis and lung cancer. Prior to this study, we evaluated the difference in protective performance between replaceable particulate respirators (RPRs) and powered air-purifying respirators (PAPRs) by having the participants wear them at rest in various ways in a laboratory. In this previous study, the average leakage rate at rest for RPR ranged from 1.82% to 10.92%, and the average leakage rate at rest for PAPR ranged from 0.18% to 0.42%. Under the rest condition, while there was a decrease in respiratory protection with RPR due to different methods of wear, no significant decrease in respiratory protection was observed with PAPR based on different methods of wear. This indicates that PAPRs can provide sufficient protection for workers who are unable to wear RPRs appropriately

77 due to the work environment.⁶ A previous study that examined the effect of the wearing method on
 78 respiratory protection at rest found that PAPRs maintained high respiratory protection regardless of
 79 the wearing method; therefore, we thought it might be possible to maintain high respiratory protection
 80 regardless of workload. In this previous study, we were unable to verify the effect of workload on
 81 respiratory protection. Therefore, we thought it was important to verify the effect of RPE on
 82 respiratory protection during workload, depending on the method of wearing RPE among workers.
 83 The purpose of this study was to measure the fit factor of RPRs and PAPRs during workload, in a
 84 laboratory, using various wearing methods, and to clarify the differences in respiratory protection and
 85 the wearing methods that maintain adequate respiratory protection.

86

87 **Methods**

88 *Ethical Approval*

89 The Ethics and Informed Consent Procedure for this study was approved by the Ethics Committee of
 90 Medical Research, University of Occupational and Environmental Health, Japan (Receipt No.
 91 H30-58). Informed consent was obtained from all the participants.

92 *Study design and setting*

93 We conducted a crossover comparison study of 10 participants who agreed to participate in the
 94 experiment. Two physical states (resting and exercise state) were used to measure the fit factor of each
 95 combination (hereafter called “wearing variation”) of the RPE type and wearing method.

Fit factor is the numerical result of a quantitative fit test performed on an RPE face piece, which indicates the effectiveness of the seal against the face.

The experiment was conducted from August to September 2018 in an artificial climate chamber at the University of Occupational and Environmental Health, Japan to exclude environmental influences.

The climatic conditions in the artificial climate chamber were set to maintain a room temperature of 20°C and a relative humidity of 50%.

Participants

We recruited participants from the University of Occupational and Environmental Health, Japan. All participants were healthy adults over 20 years old and were non-smokers, to prevent tobacco dust from affecting the leakage rate measurement. Ten participants, eight males (mean age [standard deviation (SD)]: 32.1 [3.98] years) and two females (mean age [SD]: 34.0 [5.0] years), were eligible for this study.

Particulate respirator

The RPR selected for testing was the 1180–05 (Koken Ltd.), and the PAPR was the BL–321S (Koken Ltd). The RPR used was a model that complied with RL2, and the particulate filtering efficiency according to the Japanese standard for dust mask is 95%.⁷

PAPR used was a model that complied with PL1, and the particulate filtering efficiency in the

Japanese standard for PAPRs is 95%.⁸ The PAPR used had the following capacity: motor blower capacity; large airflow volume type (over 138 L/min), leakage rate; B class (less than 5.0%), filtering efficiency; PL1 (over 95.0%). The RPR selected for testing was the 1180-05 (Koken Ltd., Japan) with a filtering efficiency RL2 (over 95.0%). This RPR consisted of a half facepiece and a single filter with a shape similar to that of the BL-321S.

To minimize the influence of individual RPE fitting techniques, the participants used a mirror to standardize the fitting procedure. The tightness of the fastening straps was measured with a measuring instrument using a Sensor Interchangeable Amplifier (force gauge) (eZT, IMADA CO., LTD, Japan). The tightness of the fastening straps was adjusted so that the force with which the fastening straps of the RPE pressurized the head was uniform.

Wearing variations

The method of wearing the RPEs was based on the commonly observed method of wearing them in the workplace⁵ revealed in our previous study. They were as follows: the recommended method (R) in which the headband was placed on the area from the parietal region to the occipital region with nothing between the facepiece cushion and the face; the method in which a knit cover is placed between the facepiece cushion and the face (K); and the method in which the headband was placed over a helmet (H). Figure 1 shows an image of the wearing methods. We represented wearing variation as the combination of “RPR” or “PAPR” and “wearing method.”

For example, a PAPR worn according to the recommended method (R) was represented with PAPR-R.

We conducted an experiment with six wearing variations. Finally, we set RPR-R, RPR-K, RPR-H,

PAPR-R, PAPR-K, and PAPR-H as the six wearing variations.

Measurement procedure

We measured the fit factor of the RPE at two physical states, resting and exercise, for the six different

wearing variations. We reported the experimental data of the resting state in a previous study.⁶ The

exercise state was set to exercise with an ergometer set at an 80 W load. The order of the fit factor

measurements for each wearing variation was assigned using a random number table. Figure 2

illustrates the measurement procedure.

Measurement of fit factor

To measure fit factor, the participants wore the particulate respirator and performed five actions (1.

Normal breathing, 2. Deep breathing, 3. Turning the head side-to-side: 4. Moving head up and down,

and 5. Talking). Each action was performed for 1 min. For measurements of exercise state, after 10

minutes of exercise tasks, we measured fit factor while the exercise loading is continued. The

measurement device measured the concentration of atmospheric dust inside and outside the particulate

respirator.

The fit testing procedure according to the occupational safety and health administration (OSHA)

specifies that seven motions should be performed to measure the fit factor.⁹ However, because the measurement was to be performed while exercising tasks, the five motions of the Japan Industrial Standard (JIS) T8150 in 2018 were adopted for safety reasons.¹⁰ To avoid any influence on the measurements due to the fatigue in the participants, fit factor measurements while exercising tasks were limited to two times per day, with an interval of at least one hour.

Measurement apparatus of fit factor

The leakage rate was measured using an MT-03 device (Sibata Scientific Technology Ltd.), which uses a light scattering system particle counter for the detection part and counts the particles present in the air inside and outside the RPE sucked at 1 l/min. After measuring the air outside the RPE for 17 s, the instrument measured the air inside the RPE for 17 s. The replacement time for the dust remaining in the pipe at the start of the measurement and when switching the measurement path was set to 10 s. The time required for each measurement was approximately 1 min. The particles measured by the device were atmospheric dust with a particle size of at least 0.5 µm. During the measurement, incense sticks were burned to maintain a level of dust in an environment of more than 1000 counts/3 s, which is the recommended value for MT-03. The concentration within the RPE was measured by sampling the air inside the facepiece using a tube joint set fixed to the sampling tube and the RPE. The concentration outside the RPE was measured by sampling the air outside the RPE using a sampling tube fixed with a string hung from the ceiling so that the end of the sampling tube was close to the

RPE.

Calculating the fit factor

According to JIS T8150¹⁰ or fit testing procedure by OSHA,⁹ the fit factor was calculated by dividing the concentration within the particulate respirator (Ni) by the concentration outside it (No):

$$Fit\ factor = \frac{Number\ of\ test\ exercises}{Ni/No_1 + Ni/No_2 + Ni/No_3 + Ni/No_4 + Ni/No_5}$$

The numbers from 1 to 5 represent test exercises 1-5.

OSHA indicated that the test participant should not be permitted to wear a half mask or quarter facepiece respirator unless a minimum fit factor of 100 is obtained.⁹ In this study, we used fit factor $\geq$ 100 as the criterion to ensure that respiratory protection was maintained.

Variables

The outcome variable was fit factor, and the predictor variables were physical state (resting state and exercise state) and wearing variations. We adjusted for sex as a confounding factor.

Statistical methods

Data were analyzed after they were log-transformed with a linear mixed model (LMM), with fit factor as the dependent variable. Among the independent variables, the random factor was the survey participants, and the fixed factors were sex, physical states, wearing variations, and interaction

between physical states and wearing variations. The Bonferroni method was used for multiple comparisons. The estimated marginal means (EMM) by physical states or wearing variations were calculated by adjusting for the dependent variable of LMM. All statistical analyses were performed using the IBM SPSS Statistics 23.0. The significance level was set at $p < 0.05$.

Results

Fit factor according to physical states and wearing variations

Table 1 shows the number of cases with fit factor > 100 and the mean (SD) of fit factor for each physical condition and wearing variation. We could not observe cases of fit factor ≥ 100 when the participants wore the RPE by RPR_K. The number of cases with fit factor ≥ 100 was higher when wearing the PAPR than when wearing the RPR in both the resting state and exercise state. In each of the three methods, when wearing the PAPR in the resting state, the fit factor was ≥ 100 ; however, only one of ten cases had fit factor < 100 when wearing the PAPR in exercise state. The mean values of fit factor were also higher when wearing the PAPR than when wearing the RPR, and they were higher in the resting state than in the exercise state.

Comparisons of the values of fit factor by physical states and wearing variations

Table 2 shows the results of the statistical comparison of the values of fit factor by physical states and wearing variations. We analyzed the interactions between the physical states and wearing variations.

The value of fit factor was significantly lower when the RPE was worn in the exercise state than when it was worn in the resting state. The fit factor was significantly the lowest among all wearing variations when RPE was applied by RPR_K. When fitted by RPR_R and RPR_H, the fit factor was significantly lower than when the PAPR was worn. No significant difference in fit factor values was observed when the PAPR was worn by PAPR_H, PAPR_K, and PAPR_R. There was no significant interaction between physical state and wearing variations.

Discussion

In this study, we measured the fit factor of the RPR and PAPR used in the resting state and exercise state, using three different wearing variations. The fit factor of the RPR and PAPR in the exercise state was significantly lower than that during the resting state. This may be because the adhesion between the face and the RPE tends to decrease due to the exercising tasks. There was no significant interaction between the physical states and the wearing variations. It was suggested that even when workers wear RPE properly, working reduces respiratory protection. Since there is a possibility that working may impair protection, employers should try to reduce the risk by implementing engineering measures.

The fit factor of the PAPR used in the exercise state was greater than 100 in 9 of 10 cases for all wearing variations. There were three cases in which the fit factor of the RPR in the exercise state was greater than 100, using the recommended wearing method. There were no cases in which the fit factor

229 of the RPR was greater than 100 when the knit cover was attached to the RPR. The inside of the

230 PAPR was always under positive pressure, which may maintain respiratory protection even if working

231 impairs the adhesion between the PAPR and the face. It is clear that PAPRs are superior to RPRs in

232 terms of respiratory protection. However, it has been reported that PAPRs are rarely used in the

233 workplace because⁵ they are expensive, they are larger than RPRs, and most workers complained

234 about their heaviness;¹¹ these reasons may have hindered the use of PAPR.

235 The mean fit factor of wearing a knit cover in RPRs was 12.3 in the resting state and 9.3 in the

236 exercise state, which was significantly the lowest among all wearing methods. The fit factor was less

237 than 100 in all participants, and this study also indicated that wearing a knit cover is a wearing method

238 that can easily compromise the adhesion between the face and the RPR.¹² When wearing a knit cover

239 in PAPRs, the fit factor was more than 100 even during exercising tasks, and respiratory protection

240 was maintained. If there is a risk of causing eczema or other skin problems by wearing RPE, workers

241 are allowed to use a knit cover as long as there is good adhesion between the RPE and the face.⁴ Since

242 this study showed that wearing a knit cover impairs adhesion to the RPR, it is recommended that

243 workers with skin disorders who use a knit cover wear a PAPR.

244 There was no significant difference in the fit factor between the recommended method of wearing the

245 RPR and the method of wearing the RPR over the helmet. In this study, we kept the pressure on the

246 tightening cord constant among the participants, but there may be differences among individuals in

247 the workplace. The RPR, PAPR, and helmet we examined were of one model and they were unused.

248 In this case, the RPE headband merely fits well with the helmet, and it is unclear whether the results
249 are similar for the other models. It is also unclear how the degradation of the RPR or helmet affects
250 the fit of the headband and helmet. Further study is required on these points, and we cannot yet
251 recommend wearing RPE over a helmet. However, it has been reported that many workers in the
252 workplace wore RPE over their helmets.⁵ Working in a dusty environment while wearing RPE with a
253 poorly adherent attachment does not sufficiently prevent pneumoconiosis. It is important to provide
254 continuous education and guidance to workers to ensure that they wear RPE with minimal leakage.
255 Recently, the concept of workplace protection factor (WPF) has emerged because of the importance of
256 evaluating the respiratory protection of RPE in the workplace environment. WPF is a measure of the
257 protection provided in the workplace when a properly functioning respirator is correctly fitted and
258 used,¹³ and several studies on WPF have been reported.¹⁴⁻¹⁸ In this study, respiratory protection during
259 exercising tasks was evaluated in an artificial climate chamber, and it is desirable to evaluate the
260 respiratory protection of various methods of wearing RPE in the workplace.
261 This study has some limitations. First, the number of participants was small, and type II errors may be
262 large, so we need to increase the sample size. Second, the RPRs, PAPRs, knit cover, and helmet we
263 used were of only one type, so we thought it was necessary to verify with multiple types of RPE.
264 Moreover, the RPE, knit cover, and helmet used were new. In the workplace, workers use the
265 equipment for many years, so the deterioration of the silicone of the RPE, knit cover, and helmet may
266 affect the fit factor. Third, participants may have worn the RPE more rigorously than the actual

workers. To minimize the effect of the individual's ability to accurately fit the RPE, the participants wore the RPE while looking at a mirror reflection during the survey. If the examiner noticed an abnormality, such as a twisted strap, the participant was asked to remove the RPE and re-attach it. The verification of WPF in actual workers without any advice on how to wear the RPE is a subject for future study.

Conclusion

We evaluated the respiratory protection of RPRs and PAPRs during exercising tasks, using various wearing methods. The fit factor of RPRs in the exercise state was significantly lower than that in the resting state, indicating inadequate respiratory protection. In contrast, the fit factor of PAPRs was significantly lower than that at rest, but respiratory protection was maintained. As in a previous study, PAPRs were found to be superior to RPRs in terms of respiratory protection. Therefore, PAPRs are better than RPRs for workers who have to wear RPE inappropriately due to health problems.

Acknowledgements

We would like to thank Editage (<http://www.editage.com>) for editing and reviewing this manuscript for English language.

Declaration of Conflict interests

286 The authors declare no conflicts of interest.

287

288 **Author Contributions**

289 Conceptualization: Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

290 Data curation: Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

291 Formal analysis: Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

292 Funding acquisition: Akira Ogami

293 Investigation: Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

294 Methodology – Development or design of methodology; creation of models.

295 Project administration: Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

296 Supervision: Akira Ogami

297 Validation: Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

298 Visualization: Hiroka Baba, Taiki Shirasaka, Hajime Ando, Kazunori Ikegami

299 Writing - original draft: Hiroka Baba, Hajime Ando, Kazunori Ikegami

300 Writing - review & editing: Hiroka Baba, Hajime Ando, Kazunori Ikegami, Shingo Sekoguchi, Taiki

301 Shirasaka, Akira Ogami

302

303 **ORCID iDs**

304 Hiroka Baba: <https://orcid.org/0000-0002-2394-2362>

305 Hajime Ando: <https://orcid.org/0000-0001-7717-0030>

306 Kazunori Ikegami: <https://orcid.org/0000-0001-5486-8639>

307 Shingo Sekoguchi: <https://orcid.org/0000-0003-1375-3282>

308 Taiki Shirasaka: <https://orcid.org/0000-0002-1531-3857>

309 Akira Ogami: <https://orcid.org/0000-0002-4940-3818>

310

311 **References**

312 1. Ministry of Health, Labour, and Welfare, Japan. Survey on Occurrence of Work-related Illnesses.

313 (2019) (in Japanese). https://www.mhlw.go.jp/stf/newpage_12883.html. Updated 2021 Accessed

314 August 18, 2021.

315 2. Stobbe TJ, daRoza RA and Watkins MA. Facial hair and respirator fit: a review of the literature.

316 *Am Ind Hyg Assoc J* 1988;49:199–204.

317 3. Floyd EL, Henry JB and Johnson DL. Influence of facial hair length, coarseness, and areal

318 density on seal leakage of a tight-fitting half-face respirator. *J Occup Environ Hyg* 2018;15:334–40.

319 4. Ministry of Health Labour and Welfare, Labour Standards Bureau, Japan. Labor Standards

320 Bureau Notification No. 0207006: Selection and use of respiratory protection equipment (in Japanese),

321 https://www.mhlw.go.jp/web/t_doc?dataId=00tc2747&dataType=1&pageNo=1. Updated 2021

322 Accessed August 18, 2021.

323 5. Shirasaka T, Ando H, Ikegami K, Ogami A. A survey on methods of wearing respiratory

- 324 protective equipment and awareness of respiratory protection among workers engaged in
- 325 dust-generating work. *Environmental and Occupational Health Practice* 2019;1:39–45.
- 326 6. Sekoguchi S, Shirasaka T, Ando H, Ikegami K, Ogami A. Evaluation of the performance of
- 327 replaceable particulate and powered air-purifying respirators considering non-recommended wearing
- 328 methods. *Ind Health* 2020;58:573–80.
- 329 7. Ministry of Health Labour and Welfare, Japan. Standard for Dust Mask (in Japanese).
- 330 <https://www.jniosh.johas.go.jp/icpro/jicosh-old/english/law/DustMask/index.html>. Updated 2009
- 331 Accessed August 18, 2021.
- 332 8. Japan Ministry of Health Labour and Welfare. Standard for Powered Air-Purifying Respirator.
- 333 <https://www.jaish.gr.jp/anzen/hor/hombun/hor1-11/hor1-11-39-1-0.htm>. Updated 2016 Accessed
- 334 August 18, 2021.
- 335 9. Occupational Safety and Health Administration. Appendix A to §1910.134—Fit Testing
- 336 Procedures (Mandatory).
- 337 <https://www.osha.gov/lawsregs/regulations/standardnumber/1910/1910.134AppA>. Updated 2021
- 338 Accessed August18, 2021.
- 339 10. Japanese Industrial Standards. Guidance for selection, use and maintenance of respiratory
- 340 protective devices (JIS T 8150) (in Japanese). <https://kikakurui.com/t8/T8150-2006-01.html>. Updated
- 341 2021 Accessed August 18, 2021.
- 342 11. Kishimoto T. Research on the practicality and diffusion of PAPR, Measurement of leakage rate

343 and questionnaire survey for comparison between ordinary dust mask and Powered Air Purifying
344 Respirator (PAPR) (in Japanese). https://www.mhlw.go.jp/content/30_180302-01.pdf. Updated 2020
345 Accessed August 18, 2021).

346 12. Kikuzi K. A study on facepiece-to-face fitting of dust respirators. *J Science of Labour*
347 1984;60:559–68.

348 13. Janssen L, Zhuang Z and Shaffer R. Criteria for the collection of useful respirator performance
349 data in the workplace. *J Occup Environ Hyg* 2014;11:218–26.

350 14. Myers WR, Zhuang Z and Nelson T. Field performance measurements of half-facepiece
351 respirators--foundry operations. *Am Ind Hyg Assoc J* 1996;57:166–74.

352 15. Myers WR and Zhuang Z. Field performance measurements of half-facepiece respirators: steel
353 mill operations. *Am Ind Hyg Assoc J* 1998;59:789–95.

354 16. Han DH. Correlations between workplace protection factors and fit factors for filtering
355 facepieces in the welding workplace. *Ind Health* 2002;40:328–34.

356 17. Janssen LL, Nelson TJ and Cuta KT. Workplace protection factors for an N95 filtering facepiece
357 respirator. *J Occup Environ Hyg* 2007;4:698-707.

358 18. Chazelet S, Wild P, Silvente E, Eypert-Blaison C. Workplace Respiratory Protection Factors
359 during Asbestos Removal Operations. *Ann Work Expo Health* 2018;62:613–21.

360

361 **Figure 1.** Photographs depicting different wearing methods, using a replaceable particulate respirator

362 as an example. We adapted these photos from the study by Sekoguchi et al.⁶

363

364 **Figure 2.** Outline of the study

365

366

Table 1. Number of cases with fit factor > 100 and the mean (standard deviation) of fit factor for each physical condition and wearing variation.

Wearing variations	Fit Factor (FF)					
	Resting state			Exercise state		
	# of FF ≥	M ^f	SD ^g	# of FF ≥	M	SD
	100			100		
RPR ^a _H ^c	3	118.7	(111.8)	2	68.2	(55.4)
RPR_K ^d	0	12.3	(5.5)	0	9.3	(4.7)
RPR_R ^e	4	145.3	(141.1)	3	84.8	(75.6)
PAPR ^b _H	10	737.2	(408.8)	9	468.7	(284.3)
PAPR_K	10	762.4	(357.0)	9	396.6	(282.0)
PAPR_R	10	786.5	(375.7)	9	444.5	(326.9)

of FF ≥ 100

Abbreviations: ^aRPR, replaceable particulate respirators; ^bPAPR, powered air-purifying respirators;

^cH, the method in which the headband was placed over a helmet; ^dK, the method in which a knit cover

is placed between the face piece cushion and the face; ^eR, the recommended method in which the

headband was placed on the area from the parietal region to the occipital region with nothing between

the facepiece cushion and the face; ^fM, mean; ^gSD, standard deviation

Table 2. Comparison of the values of FF^a among physical states and among wearing variations

Variables		Ln (the values of FF)		
		EMM ⁱ	95% CI ^j	p
PS ^b	Resting	5.13	[4.54-5.71]	<0.001
	Exercising tasks	4.62	[4.04-5.21]	
WV ^c	RPR ^d _H ^f	4.14	[3.53-4.75]	<0.001
	RPR_K ^g	2.29	[1.67-2.90]	
	RPR_R ^h	4.29	[3.68-4.90]	
	PAPR ^e _H	6.20	[5.59-6.81]	
	PAPR_K	6.13	[5.52-6.74]	
	PAPR_R	6.22	[5.61-6.83]	
Interaction between PS and WV				0.795

379 We represented wearing variation as the combination of “RPR” or “PAPR” and “wearing method.”

380 For example, a PAPR worn according to the recommended method (R) was represented with PAPR-R.

381 Post-hoc test: RPR_K<RPR_H/R<PAPR_H/K/R

382 **Abbreviations:** ^aFF, Fit factor; ^bPS, physical states; ^cWV, wearing variations; ^dRPR, replaceable

383 particulate respirators; ^ePAPR, powered air-purifying respirators; ^fH, the method in which the

384 headband was placed over a helmet; ^gK, the method in which a knit cover is placed between the face

385 piece cushion and the face; ^hR, the recommended method in which the headband was placed on the

386 area from the parietal region to the occipital region with nothing between the facepiece cushion and

387 the face; ⁱEMM, estimated marginal mean; ^jCI, confidence interval

388